Efficiently Controlling Multiple Risks with Pareto Testing

Abstract

Machine learning applications frequently come with multiple diverse objectives and constraints that can change over time. Accordingly, trained models can be tuned with sets of hyper-parameters that affect their predictive behavior (e.g., their run-time efficiency versus error rate). As the number of constraints and hyper-parameter dimensions grow, naively selected settings may lead to sub-optimal and/or unreliable results. We develop an efficient method for calibrating models such that their predictions provably satisfy multiple explicit and simultaneous statistical guarantees (e.g., upper-bounded error rates), while also optimizing any number of additional, unconstrained objectives (e.g., total run-time cost). Building on recent results in distribution-free, finite-sample risk control for general losses, we propose Pareto Testing: a two-stage process which combines multi-objective optimization with multiple hypothesis testing. The optimization stage constructs a set of promising combinations on the Pareto frontier. We then apply statistical testing to this frontier only to identify configurations that have (a) high utility with respect to our objectives, and (b) guaranteed risk levels with respect to our constraints, with specifiably high probability. We demonstrate the effectiveness of our approach to reliably accelerate the execution of large-scale Transformer models in natural language processing (NLP) applications. In particular, we show how Pareto Testing can be used to dynamically configure multiple inter-dependent model attributes—including the number of layers computed before exiting, number of attention heads pruned, or number of text tokens considered—to simultaneously control and optimize various accuracy and cost metrics.

1 Introduction

Suppose you want to deploy a modern machine learning model in a real-world environment. As a practitioner, you may frequently have to weigh several performance considerations (Jin & Sendhoff, 2008; Ribeiro et al., 2020; Min et al., 2021). For example, how much computational budget can you spend? What accuracy do you require? How large, if any, of a discrepancy in predictive performance across different groups of end-users can you tolerate? Often models are equipped with hyper-parameter configurations that provide "knobs" for tuning different aspects of their performance, depending on how such questions are answered. As the number of dimensions and objectives grow, however, choosing the right set of parameters to rigorously control model performance on test data in the intended ways can become prone to error.

To address this challenge, the recently proposed *Learn Then Test* (LTT) framework of Angelopoulos et al. (2021) combines any type of parameterizable predictive model with classic statistical hypothesis testing to provide an algorithm for selecting configurations that lead to provable distribution-free, finite-sample risk control of any user-specified objective. Nevertheless, while theoretically general, again, a key pair of practical challenges arises when the space of parameters to explore and constraints to satisfy are large. The first is that evaluating all possible configurations can quickly become intractable, while the second is that the statistical tests relied upon to guarantee risk control can quickly lose power—and fail to identify configurations that are also useful for the task at hand.

In this work, we build upon the results of LTT by introducing *Pareto Testing*, a simple procedure that can provide a computationally and statistically efficient way to identify valid, risk-controlling configurations with (specifiably) high probability, which, critically, are also useful with respect to other objectives of interest. Our method consists of two stages. In the first stage, we solve an unconstrained,

Figure 1: A demonstration of our calibration procedure applied to multi-dimensional adaptive computation in a Transformer model. Here we have the option to drop tokens from the input, make an "early-exit" prediction after processing a subset of the layers, or only compute a subset of the self-attention heads in each layer. Each dimension affects the overall performance in non-trivial and non-independent ways. Our method determines the extent to which we can apply each adaptation such that any user-specified performance constraints are *guaranteed* to be met (e.g., minimal accuracy drop), while *also* optimizing other desirable (but unconstrained) objectives (e.g., inference cost).

multi-objective optimization problem in order to recover an approximate set of Pareto-optimal configurations, i.e., settings for which no other configuration exists that is uniformly better in all respects. Here we can exploit standard multi-objective optimization methods to efficiently explore and filter large parameter spaces to only its most promising configurations. In the second stage, we perform rigorous sequential testing over the recovered set, which we empirically find to yield tight control of our desired risks, while also giving good performance with respect to our free objectives.[1]

We apply our approach to configurable, adaptive computation in natural language processing (NLP) tasks (see Figure 1). In a nutshell, large-scale Transformer models (Vaswani et al., 2017), though accurate for many NLP tasks, can also be incredibly expensive to run (Bapna et al., 2020; Schwartz et al., 2020; Moosavi et al., 2021). Although larger models generally perform better, the same amount of computation is not always required for every application, domain, or example to achieve "satisfactory" performance. As such, many techniques have been proposed for adaptive computation, including attention head pruning, token dropping, or early exiting (Graves, 2016; Xin et al., 2020; Hou et al., 2020; Goyal et al., 2020). Still, the process for determining different thresholds that control the extent to which to apply none, any, or all of these modifications simultaneously without incurring unpredictable degradations in various measures of model performance can be tricky. In this regard, our procedure provides what other general adaptive computation strategies—including those that provide control over *singular* objectives such as consistency as in Schuster et al. (2021; 2022)—do not: a flexible framework for jointly configuring *multiple* model settings subject to *multiple* statistical guarantees on model performance, including bounds on the average reduction in accuracy and worst-case reduction in accuracy while optimizing average inference cost, or vice versa.

Contribution. The core idea and contribution of our work can be summarized quite plainly:

1. Our framework leverages statistical testing techniques via the Learn Then Test framework (Angelopoulos et al., 2021) to identify valid risk-controlling hyper-parameter configurations;
2. To improve efficiency, we introduce Pareto Testing, our main contribution, as a way to efficiently guide the number and order of configurations that we test when searching for valid settings;
3. We demonstrate the scalability and effectiveness of our method in managing trade-offs in multi-dimensional adaptive computation in NLP applications with large-scale Transformer models;
4. On diverse text classification tasks, we empirically achieve tight, simultaneous control of multiple risks while also improving performance on any non-controlled objectives, relative to baselines.

---

[1] If we fail to find any valid configurations (which may not exist) with the right confidence, then we abstain.

2 RELATED WORK

Risk control. Our work adds to a rich history of tools for uncertainty estimation and risk control for machine learning algorithms (Vovk, 2002; Vovk et al., 2015; 2017; Lei et al., 2013; 2018; Gupta et al., 2020; Bates et al., 2021; Barber et al., 2021; Angelopoulos et al., 2021). Here we focus on achieving model-agnostic, distribution-free, and finite-sample performance guarantees—similar to the coverage guarantees given by prediction sets or regression intervals in conformal prediction (Papadopoulos et al., 2002; Vovk et al., 2005; Angelopoulos et al., 2022). As outlined in §1, this paper builds on the groundwork set by Angelopoulos et al. (2021), which provides a general methodology for calibrating any risk function that is controllable via some low-dimensional hyper-parameter configuration. We extend their framework to efficiently handle (relatively) higher-dimensional settings with multiple auxiliary objectives. Our application to confident model acceleration is also closely related to Schuster et al. (2021; 2022), though our method is designed for a much broader setting that involves (i) multiple objectives, and (ii) multiple model pruning dimensions.

Multi-objective optimization. Solving for multiple objectives is a fundamental problem (Deb, 2001; Miettinen, 2012; Bradford et al., 2018). Typically, multi-objective problems are more difficult than single-objective problems, as a single solution does not always exist due to trade-offs. Instead, there is a set of solutions that are all equally "good", which is known as the Pareto frontier (Censor, 1977; Arora, 2004). Our setting falls at the intersection of multi-objective optimization and risk-control, where we want to perform multi-objective optimization subject to statistical bounds on a subset of the objectives. Our two-stage approach is able to directly combine techniques in multi-objective optimization (Knowles, 2006; Lindauer et al., 2022) with those in risk control (Angelopoulos et al., 2021), in order to identify valid, statistically efficient solutions.

Model configuration. We approach our multi-objective optimization problem by uncovering model configurations that deliver on the desired performance guarantees (e.g., maximal error rates), while also providing "best-effort" optimization of the auxiliary objectives (e.g., minimal inference cost) without any re-training. This is adjacent to the field of hyper-parameter tuning and architecture search, which deal with determining appropriate model hyper-parameter values, or even designing higher-level network structures (Elsken et al., 2019). While most approaches focus on finding configurations that maximize predictive performance, some have also considered additional measures such as efficiency (Shah & Ghahramani, 2016; Belakaria et al., 2019; Elsken et al., 2018; Dong et al., 2018; Zhou et al., 2018; Chu et al., 2020), fairness (Schmucker et al., 2020; Candelieri et al., 2022), or robustness (Karl et al., 2022). Our work, however, differs by treating hyper-parameter selection as a multiple-testing problem with rigorous statistical guarantees following Angelopoulos et al. (2021).

Adaptive computation. Our main application is configuring adaptive model computation. Large-scale deep learning models can be accurate, but also computationally intensive to run. Many efforts have focused on improving run-time efficiency, including model distillation (Sanh et al., 2019; Jiao et al., 2020; Sun et al., 2020), dynamic architecture selection (Yu et al., 2019; Cai et al., 2020; Hou et al., 2020), early-exiting (Teerapittayanon et al., 2016; Liu et al., 2020), token pruning (Goyal et al., 2020; Ye et al., 2021; Kim et al., 2021; Modarressi et al., 2022; Guan et al., 2022), and others. This work focuses on configurable, adaptive computation that does not require model re-training. Furthermore, only a few methods have proposed *combining* multiple pruning dimensions, such as depth and width (Hou et al., 2020), token pruning with early-exiting (He et al., 2021), and pruning model units of different granularity (Xia et al., 2022). Our multi-dimensional calibration scheme generalizes these approaches, and allows for flexible tuning in each pruning axis.

3 PROBLEM FORMULATION

Consider an input variable $X \in \mathcal{X}$, and an associated label $Y \in \mathcal{Y}$, drawn from some joint distribution. Assume a predictive model of the form $f \colon \mathcal{X} \times \mathcal{T} \to \mathcal{Y}$, where $\mathcal{T} \triangleq \mathcal{T}_1 \times \ldots \times \mathcal{T}_n$ is the space of n hyper-parameters that configure f. The parameters of the model f are optimized over a training set $\mathcal{D}_{\text{train}}$, while the hyper-parameters $(\tau_1, \ldots, \tau_n)$ then provide n additional degrees of freedom in influencing either (i) how the model is trained over $\mathcal{D}_{\text{train}}$, or (ii) how the model is used. We focus on the latter in this paper. For example, in our adaptive Transformer example, f has $n = 3$ pruning dimensions: the number of attention heads per layer, the truncated length of the input text sequence, and the effective network depth in terms of the selected early-exit layer. In this

scenario, the hyper-parameters (τ_1, τ_2, τ_3) are real-valued thresholds, and determine the extent of sparsification along each axis given some "importance/confidence" score (to be defined).

Next, consider a set of objective functions $\{Q_1, \ldots, Q_{c+1}\}$ of the form $Q_i(\tau_1, \ldots, \tau_n) = \mathbb{E}[q_i(X, Y; \tau_1, \ldots, \tau_n)]$ for some loss q_i. For simplicity, we assume a setting in which the user wishes to arbitrarily bound the first c objective functions (hereby called *risk* functions) by $\{\alpha_1, \ldots, \alpha_c\} \in \mathbb{R}^c$, while minimizing the remaining objective function, Q_{c+1} (we consider multiple free objectives later). We further assume that $(\tau_1, \ldots, \tau_n)$ can be used to either increase or decrease Q_i (not necessarily independently), though we do not assume that a feasible solution always exists.

To estimate suitable values of $(\tau_1, \ldots, \tau_n)$, let $\mathcal{D}_{\text{cal}} = (X_i, Y_i)$, $i = 1, \ldots, m$ be an i.i.d. *calibration* set that we will use to select $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$. As functions of $\mathcal{D}_{\text{cal}}$, $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$ are also random variables, and therefore $Q_i(\hat{\tau}_1, \ldots, \hat{\tau}_n)$ is a *random* conditional expectation (constant given $\mathcal{D}_{\text{cal}}$). Our goal is to select $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$ in such a way that the $\{Q_1, \ldots, Q_c\}$ objectives that we wish to control are appropriately bounded with specifiably high probability—as we now formally define.

Definition 3.1 ((α, δ)-risk controlling configuration)**.** *Let* $\mathcal{D}_{\text{cal}} = \{(X_i, Y_i)\}_{i=1}^m$ *be set of i.i.d. random variables used to estimate a model configuration* $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$. *Let* $\{Q_i(\hat{\tau}_1, \ldots, \hat{\tau}_n)\}_{i=1}^c$ *be a set of risk functions conditioned on the choice of* $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$. *For any set of risk levels* $\{\alpha_i\}_{i=1}^c$ *and tolerance* $\delta \in (0, 1)$, *we say that* $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$ *is a* (α, δ)*-risk controlling configuration, if:*[2]

$$\mathbb{P}\left(Q_i(\hat{\tau}_1, \ldots, \hat{\tau}_n) \leq \alpha_i\right) \geq 1 - \delta, \ \ \forall 1 \leq i \leq c \quad simultaneously, \tag{1}$$

where the probability in Eq. (1) is over the draw of $\mathcal{D}_{\text{cal}}$.

For a given task and risk constraints, many satisfactory configurations may exist. Our key practical goal is to find a (α, δ)-risk controlling configuration that *also* best minimizes the remaining objective(s) Q_{c+1}. As such, we will focus on the expected performance of $Q_{c+1}(\hat{\tau}_1, \ldots, \hat{\tau}_n)$ as a relative measure of effectiveness, when comparing procedures for selecting $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$.[3]

4 BACKGROUND

We begin with a brief review of the Learn then Test (LTT) framework of Angelopoulos et al. (2021), on which our method is based. The core idea of LTT is to split model development into two stages: first a predictive model f is fit to training data using an some learning procedure, and second a low-dimensional hyper-parameter combination $\boldsymbol{\tau} = (\tau_1, \ldots, \tau_n) \in \mathcal{T}$ that controls the way the model makes predictions is selected in a way that provides rigorous risk control via hypothesis testing.

Risk control as a hypothesis test. Consider a single risk Q. A set of possible configurations $\mathcal{T}_g$ is chosen for testing, usually by defining a discrete grid over $\mathcal{T}$. For each configuration $\boldsymbol{\tau} \in \mathcal{T}_g$, LTT tests the null hypothesis $H_{\boldsymbol{\tau}}: Q(\boldsymbol{\tau}) \geq \alpha$, i.e., that the risk is *not* controlled. Rejecting $H_{\boldsymbol{\tau}}$ then implies that $\boldsymbol{\tau}$ *is* risk-controlling. A valid p-value, $p^{\text{cal}}(\boldsymbol{\tau}, \alpha) = p(\hat{Q}^{\text{cal}}(\boldsymbol{\tau}); \alpha, m)$, to use as a basis for accepting or rejecting $H_{\boldsymbol{\tau}}$ can be derived from concentration bounds on the empirical risk, $\hat{Q}^{\text{cal}}(\boldsymbol{\tau})$, computed over i.i.d. calibration data (we use $p(\cdot)$ to denote some p-value calculation—in this work we use Hoeffding-Bentkus p-values throughout, see Angelopoulos et al. (2021)). A subset of valid $\boldsymbol{\tau}$ is then selected out of $\mathcal{T}_g$ by applying a family-wise error rate (FWER) controlling procedure, so that the probability of making one or more false discoveries (i.e., choosing invalid $\boldsymbol{\tau}$) is bounded by $\delta \in (0, 1)$. This can be extended to *multiple* risk control by defining $H_{\boldsymbol{\tau}}: \exists i$ where $Q_i(\boldsymbol{\tau}) \geq \alpha_i$, and a valid combined p-value can be obtained from

$$p^{\text{cal}}(\boldsymbol{\tau}, \boldsymbol{\alpha}) = \max_{1 \leq i \leq c} p(\hat{Q}_i^{\text{cal}}(\boldsymbol{\tau}); \alpha_i, m), \quad \text{with } \boldsymbol{\alpha} = (\alpha_1, \ldots, \alpha_c). \tag{2}$$

Multiple hypothesis testing. A key component of LTT is the choice FWER-controlling procedure. As the number of tested hypotheses $H_{\boldsymbol{\tau}}$ grows (e.g., for combinatorially many $\boldsymbol{\tau}$), the harder it is to reject $H_{\boldsymbol{\tau}}$ while limiting the probability of false discoveries to δ. Different FWER-controlling procedures will have different statistical efficiency/power (i.e., ability to correctly reject $H_{\boldsymbol{\tau}}$ if $H_{\boldsymbol{\tau}}$ is false). Angelopoulos et al. (2021) consider a number of FWER-controlling procedures, namely the Bonferroni correction, Fixed Sequence Testing (FST), and Sequential Graphical Testing (SGT)—see Appendix E for a complete discussion. At a high level, the Bonferroni correction naively assigns an

---

[2]This is a slight abuse of terminology in that, technically, $(\hat{\tau}_1, \ldots, \hat{\tau}_n)$ is not necessarily a configuration that achieves risk control—but rather the *procedure* for selecting it can achieve (α, δ) risk control.

[3]This is analogous to using average set size to compare conformal predictors (Vovk et al., 2005; 2016).

"error budget" $\delta/|\mathcal{T}_g|$ to each possible $\tau \in \mathcal{T}_g$. For large $|\mathcal{T}_g|$, this tolerance is extremely strict, and results in very conservative rejections. FST and SGT attempt to exploit *structure* in $\mathcal{T}$ by ordering and testing them in ways that are more likely to result in valid rejections. Nevertheless, FST and SGT can still be (statistically) inefficient and challenging to apply over large, and possibly unstructured (or with unknown structure) $\mathcal{T}$. This challenge intensifies when combined with the *additional* goal of finding configurations that not only provide multiple risk control, but also optimize Q_{c+1}.

5 PARETO TESTING

We now present our method for selecting effective risk-controlling configurations. Note that a related constrained optimization problem can be defined by:

$$\underset{(\tau_1,\ldots,\tau_n)\in\mathcal{T}}{\arg\min} \quad \hat{Q}_c(\tau_1,\ldots,\tau_n) \quad \text{s.t.} \quad \hat{Q}_i(\tau_1,\ldots,\tau_n) < \alpha_i, \ \forall 1 \leq i \leq c, \tag{3}$$

where $\hat{Q}_i$ denotes the empirical risk over some dataset. Directly solving for Eq. (3) over the calibration data, however, would not necessarily yield a generalizable $(\hat{\tau}_1,\ldots,\hat{\tau}_n)$ with the desired $1-\delta$ probability. In other words, the true expectation $Q_i(\hat{\tau}_1,\ldots,\hat{\tau}_n)$ over test data might exceed α_i, possibly with high probability. In the following, we show how we can combine a variant of the above optimization problem with a FST procedure in order to obtain valid bounds with $1-\delta$ probability.

5.1 CONSTRUCTING THE PARETO FRONTIER

FST considers a sequence of hypothesis tests in some order, and terminates when the first null hypothesis (here, some H_{τ}) fails to be rejected. The efficiency of FST relies heavily on the ordering of hypothesis tests (e.g., those that are more likely to be rejected should be tested earlier). We adopt the strategy of split FST (Angelopoulos et al., 2021) for separating the calibration data into two disjoint subsets $\mathcal{D}_{\text{opt}}$ and $\mathcal{D}_{\text{testing}}$ of sizes m_1 and m_2, respectively. The first split is used for defining an ordered sequence of configurations to test, while the second is used to conduct the hypothesis tests.

We begin with defining a set of tests/configurations to consider. Accounting for $k \geq 1$ free objectives, we solve the following (unconstrained) multi-objective optimization problem over $\mathcal{D}^{\text{opt}}$

$$\underset{(\tau_1,\ldots,\tau_n)\in\mathcal{T}}{\arg\min} \quad \{\hat{Q}_1^{\text{opt}}(\tau_1,\ldots,\tau_n),\ldots,\hat{Q}_{c+k}^{\text{opt}}(\tau_1,\ldots,\tau_n)\}. \tag{4}$$

If the objective functions compete with each other (e.g., performance vs. cost), a uniformly optimal solution may not exist. Instead, a solution is called non-dominated, or Pareto optimal, if there is no other point for which the value of one objective function can be improved without degrading another objective function. The set of Pareto optimal solutions, also known as the Pareto front, is given by:

$$\mathcal{T}_{\text{par}} = \{\tau' \in \mathcal{T} : \ \{\tau'' \in \mathcal{T} : \ \tau'' \succ \tau', \tau' \neq \tau'' \} = \emptyset\}. \tag{5}$$

where $\tau'' \succ \tau'$ denotes dominance in all objectives, i.e. $\hat{Q}_i^{\text{opt}}(\tau'') < \hat{Q}_i^{\text{opt}}(\tau'), \forall 1 \leq i \leq c+k$. The main idea of our method is to perform testing only over the Pareto optimal set. This consists of the most "promising" configurations, and provides the best achievable trade-offs between all objective functions (with respect to $\mathcal{D}_{\text{opt}}$). As mentioned earlier, a major challenge when dealing with a large hyper-parameter space is that testing numerous configurations can quickly lead to a loss in statistical efficiency. We overcome this by focusing only on the "optimal" region of the hyper-parameter space.

5.2 ORDERING THE PARETO FRONTIER

We now define an ordering for the set of tests/configurations on the Pareto frontier along which to conduct FST. We take the simple, but empirically effective, strategy of ordering configurations by their estimated p-values—see Eq. (2)—which we compute over $\mathcal{D}_{\text{opt}}$ (the same data used to define the Pareto frontier, but separate from the testing data to be used for FST). A benefit of converting the constrained dimensions to p-values and taking their maximum allows us to align and compare risks of different distributions (e.g., binary 0/1 error vs. precision/recall rates in $[0,1]$), or that are controlled by different values of alpha (e.g., $\alpha_i \ll \alpha_j$). Intuitively, because we focus on the Pareto optimal set, for each configuration along this ordering there is no other configuration with a lower estimated p-value that is also expected to be dominant on the free objectives $\{Q_{c+1},\ldots,Q_{c+k}\}$. Note that for $c > 1$, we can optionally decide to prune the Pareto frontier by considering only the subset

$$\mathcal{T}'_{\text{par}} = \underset{\tau \in \mathcal{T}_{\text{par}}}{\arg\min} \left\{ p^{\text{opt}}(\tau, \alpha), \hat{Q}_{c+1}^{\text{opt}}(\tau),\ldots,\hat{Q}_{c+k}^{\text{opt}}(\tau) \right\}. \tag{6}$$

Algorithm 1 Pareto Testing

Definitions: f is a configurable model with n thresholds $\boldsymbol{\tau} = (\tau_1, \ldots, \tau_n)$. $\mathcal{D}_{\text{cal}} = \mathcal{D}_{\text{opt}} \cup \mathcal{D}_{\text{testing}}$ is a calibration set of size m, split into optimization and (statistical) testing sets of size m_1 and m_2, respectively. $\{Q_1, \ldots, Q_{c+k}\}$ are objective functions. $\boldsymbol{\alpha} = \{\alpha_1, \ldots, \alpha_c\}$ are user-specified risk bounds for the first c objectives. δ is the tolerance. B is the max size of the Pareto front returned after multi-objective optimization.

1: **function** OPTIMIZATION($\mathcal{D}_{\text{opt}}, \boldsymbol{\alpha}$)
2:      Define the multi-objective problem, $\arg\min_{\boldsymbol{\tau} \in \mathcal{T}} \{\hat{Q}_1^{\text{opt}}(\boldsymbol{\tau}), \ldots, \hat{Q}_{c+k}^{\text{opt}}(\boldsymbol{\tau})\}$.
3:      Apply multi-objective optimization to identify up to B configurations $\boldsymbol{\tau}^1, \ldots, \boldsymbol{\tau}^B$ in the Pareto front.
4:      Compute p-values $p^{\text{opt}}(\boldsymbol{\tau}, \boldsymbol{\alpha}) = \max_{1 \leq i \leq c} p(\hat{Q}_i^{\text{opt}}(\boldsymbol{\tau}); \alpha_i, m_1)$.
5:      Order configurations according to $p^{\text{opt}}(\boldsymbol{\tau}, \boldsymbol{\alpha})$ from low to high $\mathcal{T}_{\text{opt}} = (\boldsymbol{\tau}^{(1)}, \ldots, \boldsymbol{\tau}^{(B)})$.
6:      **return** $\mathcal{T}_{\text{opt}}$

7: **function** CALIBRATION($\mathcal{D}_{\text{testing}}, \mathcal{T}_{\text{opt}}, \boldsymbol{\alpha}, \delta$)
8:      Compute objective: $\hat{Q}_i^{\text{testing}}(\boldsymbol{\tau}) = \frac{1}{m_2} \sum_{(x,y) \in \mathcal{D}_{\text{testing}}} q_i(x, y; \boldsymbol{\tau}), 1 \leq i \leq c$ for all $\boldsymbol{\tau} \in \mathcal{T}_{\text{opt}}$.
9:      Compute p-values: $p^{\text{testing}}(\boldsymbol{\tau}, \boldsymbol{\alpha}) = \max_{1 \leq i \leq c} p(\hat{Q}_i^{\text{testing}}(\boldsymbol{\tau}); \alpha_i, m_2)$.
10:      Apply FST: $\mathcal{T}_r = \{\boldsymbol{\tau}^{(j)} : j < J\}$, $J = \min_j\{j : p^{\text{testing}}(\boldsymbol{\tau}^{(j)}, \boldsymbol{\alpha}) \geq \delta\}$
11:      $\mathcal{T}^* = \arg\min_{\boldsymbol{\tau} \in \mathcal{T}_r} \{\hat{Q}_{c+1}(\boldsymbol{\tau}), \ldots, \hat{Q}_{c+k}(\boldsymbol{\tau})\}$
12:      **return** $\mathcal{T}^*$

In other words, since we only care about the *maximum* p-value over the constrained objectives, we can ignore configurations in $\mathcal{T}_{\text{par}}$ that only differ along constrained dimensions $\{1, \ldots, c\}$ without affecting the free dimensions $\{c+1, \ldots, c+k\}$ or the maximum p-value, $\max_{1 \leq i \leq c} p(\hat{Q}_i^{\text{opt}}(\boldsymbol{\tau}; \alpha_i, m_1)$.

5.3 APPLYING FIXED SEQUENTIAL TESTING ON THE PARETO FRONTIER

After defining and ordering $\mathcal{T}_{\text{par}}$ over $\mathcal{D}_{\text{opt}}$, we then proceed with FST on $\mathcal{D}_{\text{testing}}$ to identify a subset $\mathcal{T}_r \subseteq \mathcal{T}_{\text{par}}$ of configurations for which we can successfully reject $H_{\boldsymbol{\tau}}$ (i.e., that we are confident are valid risk-controlling configurations). The final configuration selection is given by $\mathcal{T}^* = \arg\min_{\boldsymbol{\tau} \in \mathcal{T}_r} \{\hat{Q}_{c+1}^{\text{testing}}(\boldsymbol{\tau}), \ldots, \hat{Q}_{c+k}^{\text{testing}}(\boldsymbol{\tau})\}$, which is a single configuration when $k = 1$, or a set of configurations when $k > 1$ (representing different possible trade-offs for the free objectives).

Our method is summarized in Algorithm 1 and illustrated in Figure 2. We call it *Pareto Testing* for two reasons: (i) the method reduces to applying FST over a path defined by the Pareto front of the multi-objective problem, and (ii) repeated testing for different $\boldsymbol{\alpha}$ limitations yields a *calibrated* Pareto frontier with constraints on specific dimensions in the objective function space. It is straightforward to show that Pareto Testing achieves valid risk control.

Figure 2: Pareto Testing with two objectives. Q_1 is controlled at α while Q_2 is minimized. FST is applied along the sequence of configurations on the Pareto front, ordered from high to low expected risk w.r.t. Q_1.

Proposition 5.1. *Let $\mathcal{D}^{\text{cal}} = \{(X_i, Y_i)\}_{i=1}^{m}$ be a set of i.i.d. random variables split into two disjoint subsets, $\mathcal{D}^{\text{opt}}$ and $\mathcal{D}^{\text{testing}}$. Let $p^{\text{testing}}(\boldsymbol{\tau}, \boldsymbol{\alpha})$ be a valid p-value for a configuration $\boldsymbol{\tau}$, where $\mathbb{P}(p^{\text{testing}}(\boldsymbol{\tau}, \boldsymbol{\alpha}) \leq u) \leq u$ for all $u \in [0, 1]$ over the draw of $\mathcal{D}^{\text{testing}}$. Then all configurations in the output set $\mathcal{T}^*$ of Algorithm 1 are also simultaneously (α, δ)-risk controlling configurations.*

The proof of Proposition 5.1, given in Appendix A, follows from Split FST. Note that the surviving Pareto set $\mathcal{T}^*$ contains configurations that are simultaneously valid. We are therefore free to use any $\boldsymbol{\tau}_i^* \in \mathcal{T}^*$. In fact, any combined configuration in the convex hull of $\mathcal{T}^*$ can be used as follows. Consider a randomized strategy where for each point prediction (X, Y) we sample the configuration $\boldsymbol{\tau}_j^* \in \mathcal{T}^*$ to use with probability Δ_j, where Δ is a point in the $|\mathcal{T}^*|$-d probability simplex. The resulting combination is valid, and allows for different (average) outcomes on the k free objectives.

Corollary 5.2. *Any randomized time-shared use of configurations in $\mathcal{T}^*$ is (α, δ)-risk controlling.*

6 ADAPTIVE MULTI-DIMENSIONAL PRUNING

We now turn to a concrete application of our method, in which we demonstrate its effectiveness for reliably accelerating Transformer models (Vaswani et al., 2017). Here we pair each pruning "dimension" with a score function that estimates the relative importance of each prunable element in that dimension. By thresholding scores, we can obtain different versions of the model with different performance characteristics. We assume a K-layer Transformer model with W attention heads per layer, and $L(X)$ input tokens (see Vaswani et al. (2017) for a complete description of the Transformer model). We then consider the following pruning dimensions (see also Appendix B for details):

1. **Token pruning.** In each layer, we predict for each token, its importance, defined by the norm of the gradient of the predicted label with respect to the token embedding, following Modarressi et al. (2022). We only keep tokens with predicted scores greater than a threshold τ^{tok} (which we calibrate) to obtain a sequence length of size $L_k(X; \tau^{\text{tok}})$ at the k-th layer.
2. **Early exiting.** We attach a softmax classifier head to each layer, and exit whenever the predictive entropy of its output is below a threshold τ^{layer}. The exit layer is denoted as $K_{\text{exit}}(X; \tau^{\text{layer}})$.
3. **Head pruning.** Similar to token pruning, we compute an importance score for each attention head per layer by the gradient of the loss with respect to the head hidden representation over the validation set (from training) following Michel et al. (2019). $W_k(\tau^{\text{head}})$ denotes the number of retained heads in layer k. Note that this is fixed for all inputs, unlike the previous mechanisms.

We also define several practical objective functions that can be either controlled or minimized by our proposed Pareto Testing method. The full model without pruning is denoted as $f(\cdot; \tau_0)$.

Relative computational cost. We define the relative computations cost by computing the ratio between the computational cost of the pruned model and the computational cost of the full model:

$$Q_{\text{cost}}(\tau) = \mathbb{E}\left[\frac{\sum_{k=1}^{K_{\text{exit}}(X;\tau^{\text{layer}})} W_k(\tau^{\text{head}}) \cdot L_k(X; \tau^{\text{tok}})^2}{\sum_{k=1}^{K} W \cdot L(X)^2} \right]. \tag{7}$$

Note that the exact definition may vary according to the specific architecture, hardware, or application. Eq. (7) reflects a simplistic definition that incorporates a quadratic dependency on the sequence length due to the attention mechanism, and a linear dependency on the number of attention heads. We also consider total FLOPs (floating-point operations) per forward pass.

Relative accuracy reduction. Speeding up the run-time of a model can also degrade its accuracy. Define the random variable $D(X, Y; \tau) = \mathbf{1}\{f(X; \tau_0) = Y\} - \mathbf{1}\{f(X; \tau) = Y\}$, which is 0 when both model predictions are the same, 1 when the full model is correct while the pruned model is incorrect, and -1 if the opposite is true. We define the relative accuracy reduction as:

$$Q_{\text{acc}}(\tau) = \mathbb{E}\left[D(X, Y; \tau)\right] = \mathbb{E}\left[\mathbf{1}\{f(X; \tau_0) = Y\}\right] - \mathbb{E}\left[\mathbf{1}\{f(X; \tau) = Y\}\right], \tag{8}$$

i.e, the difference in accuracy between the full and pruned models. In order to exploit p-values derived from confidence bounds that assume the risk is in $[0, 1]$ (Angelopoulos et al., 2021), we define $D(X, Y; \tau)' = [D(X, Y; \tau)]_+$, which differs only for the rare event that the pruned model is correct while the full model is not, and is more restrictive since $\mathbb{E}[D(X, Y; \tau)] \leq \mathbb{E}[D'(X, Y; \tau)]$.

Worst-class relative accuracy reduction. In some cases, we would like to control the worst-class accuracy, or equivalently, that every class accuracy reduction is controlled by the same level:

$$\mathbb{E}\left[D'(X, Y; \tau) \mid Y = y\right] \leq \alpha, \ \forall y \in \mathcal{Y}. \tag{9}$$

which is equivalent to (see Appendix A):

$$Q_{\text{acc-class}}(y; \tau) = \mathbb{E}\left[D'(X, Y; \tau) \cdot \mathbf{1}\{Y = y\} + \alpha \cdot \mathbf{1}\{Y \neq y\}\right] \leq \alpha, \ \forall y \in \mathcal{Y}. \tag{10}$$

Note that this adds an additional $|\mathcal{Y}|$ objectives (that can still be solved efficiently, see Appendix A).

Selective classification abstention rate. Consider a selective classification problem, where the model is allowed to abstain from making a prediction when it is unsure, based on some threshold λ on the model's confidence (we use the probability of the predicted class $\max_y f(X, y; \tau)$). In this case, we re-define the relative accuracy and cost reductions to be conditioned on making a prediction. We also introduce an average coverage (e.g., to make predictions at least 80% of the time):

$$Q_{\text{abstention-rate}}(\tau, \lambda) = \mathbb{E}\left[\mathbf{1}\{\max_y f(X, y; \tau) < \lambda\}\right]. \tag{11}$$

(a) IMDB   (b) AG News   (c) QNLI   (d) QQP

Figure 3: Resuts for two objectives (one controlled, one free). Relative accuracy reduction is controlled by $\alpha \in \{0.025, 0.5, \ldots, 0.2\}$, $\delta = 0.1$ while computational cost is minimized. The top plots show accuracy difference while the bottom shows relative cost (computed over 100 random trials).

7   EXPERIMENTS

Experimental setup. we test our method over five text classification tasks of varied difficulty levels: **IMDB** (Maas et al., 2011), **AG News** (Zhang et al., 2015), **QNLI** (Rajpurkar et al., 2016), **QQP**, **MNLI** (Williams et al., 2018). We use a BERT-base model (Devlin et al., 2018) with $K = 12$ layers and $W = 12$ heads per layer, and attach a prediction head and a token importance predictor per layer.

Baselines and Evaluation. We present both risk controlling and non-controlling baselines. Non-risk-controlling baselines: (1) α-**constrained**, the solution to the constrained optimization problem in Eq. (3); (2) (α, δ)-**constrained**, the same as before, but with constraints defined over p-values, which is equivalent to testing without FWER control. Risk-controlling baselines: (3) **3D SGT**, SGT defined over a 3D graph, see Algorithm F.2; (4) **Split FST**, the split method proposed in Angelopoulos et al. (2021), where a set of hypotheses is ordered by estimated increasing p-value. For fairness, each baseline (including our method) operates over the same predefined grid of configurations. We use 6480 configurations in total (18 head, 20 token, and 18 early-exit thresholds). Note that the recovered Pareto front in this case is restricted to points in this grid. We also show the results obtained while using a multi-objective optimizer for determining the Pareto front to demonstrate the actual *computationally* efficient implementation of our method (rather than brute-force exploration of the grid). We repeat each experiment over different splits of testing and calibration data (50-100 runs in total), and report the average over all splits for the configurations selected by each method.

Two objectives (one controlled, one free). We start with a two-objective scenario, where we wish to control the accuracy reduction (Eq. (8)), while minimizing the cost (Eq. (7)). The average accuracy reduction and relative cost are presented in Figs. 3 for the risk controlling baselines. We observe that the proposed method obtains the lowest cost among the risk controlling baselines for all α values and across all tasks. In particular, it can be seen that Split FST obtains slightly looser control of relative accuracy reduction, but higher relative computational costs compared to Pareto Testing. Ordering by p-values alone does not take into account scenarios where several configurations have similar accuracy, but vary in costs, while the proposed method optimizes the selection and ordering of configurations in both dimensions. We also see that 3D-SGT performs well for low α values, but often becomes worse as α increases. A possible factor is that as α increases, 3D testing is allowed to explore more of the 3D graph, but does so inefficiently—leading to overall lower rejection rates. Figure 4 shows the difference between the risk controlling and the non-risk-controlling baselines in terms of satisfying Definition 3.1. In non-risk controlling baselines (left), the risk exceeds α more frequently than the allowed tolerance level $\delta = 0.1$. In unsurprising contrast, we see that all the risk controlling baselines (right) are always below the tolerance level.

Three objectives (two controlled, one free). We study a scenario with three objectives on MNLI, where we control both the average accuracy (Eq. (8)) and the worst-class accuracy (Eq. (10)) while minimizing cost (Eq. (7)). We vary the values of α_1 for average accuracy and set $\alpha_2 = 0.15$ for worst accuracy. Figure 5 reports the results of the three objective functions. It can be seen that when

Figure 4: Two-objectives, QQP (100 splits). Acc. reduction is controlled, cost is minimized. Left: histogram of acc. reduction, $\alpha = 0.05$; middle: violin plots of acc. reduction; right: risk violations.

Figure 5: Three-objectives, MNLI (100 random splits): average accuracy is controlled by $\alpha_1 \in \{0.025, 0.5, \ldots, 0.2\}$, worst accuracy is controlled by $\alpha_2 = 0.15$, $\delta = 0.1$, and cost is minimized.

α_1 is small, testing is dominated by average accuracy (worst accuracy is not tight), and as α_1 increases, worst accuracy becomes dominant and average accuracy becomes loosely controlled. Here too we see that Pareto Testing obtains improved cost reduction with respect to the other baselines.

Results with an off-the-shelf optimizer. On the first scenario with accuracy control and cost minimization, in Figure D.1 we show a comparison between the proposed method with grid (blue) and multi-objective optimizer (red to yellow) with different number of function evaluations. For multi-objective optimizer, we used an implementation (Lindauer et al., 2022) of ParEGO optimization algorithm (Knowles, 2006; Cristescu & Knowles, 2015). We observe that even with a small number of evaluations (e.g. 50), we obtain reasonable results, which further improve as the number of evaluations increases. The grid option is performing better for certain α values, but it requires significantly more function evaluations. A more in depth analysis of how the multi-objective optimization method and the number of evaluations allowed influence testing efficiency is left for future work.

Additional results. We briefly highlight a number of results contained in Appendix D. On the same accuracy control setting, we report FLOPs saved, as an alternative measure for cost improvement. In addition, we show flipped results for controlling cost while minimizing the relative loss in accuracy. We also explore three objective settings with one controlled objective and two free objectives. Specifically, we control the selective accuracy loss (Eq. (21)), while minimizing the selective cost (Eq. (20)), and maximizing the selective coverage (Eq. (11)). Figure D.2 reports the cost and abstention rate for chosen configurations by either the proposed method and Split FST. It can be seen that Pareto Testing selects a richer set of configurations that conveys better cost-coverage trade-offs.

8 CONCLUSION

Deployment of machine learning models in the real world can frequently demand precise guarantees that certain constraints will be satisfied, together with good empirical performance on other objectives of interest. In this work, we presented *Pareto Testing*, a two-stage procedure for multiple risk control combined with multi-objective optimization. In the first stage, Pareto Testing relaxes all constraints, and converts the problem to a standard multi-objective optimization format that can be efficiently solved with off-the-shelf optimizers to yield a Pareto frontier of hyper-parameter configurations affecting model performance. In the second stage, this Pareto frontier is filtered via multiple hypothesis testing to identify only the configurations that simultaneously satisfy the desired risk constraints with (specifiably) high probability—while also being effective solutions for the free objectives. Bridging theory and practice, we demonstrated the effectiveness of the our method for computationally efficient adaptive computation on several text classification tasks under various conditions.

REFERENCES

Anastasios N Angelopoulos, Stephen Bates, Emmanuel J Candès, Michael I Jordan, and Lihua Lei. Learn then test: Calibrating predictive algorithms to achieve risk control. *arXiv preprint arXiv:2110.01052*, 2021.

Anastasios N Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, and Tal Schuster. Conformal risk control. *arXiv preprint arXiv:2208.02814*, 2022.

Jasbir Arora. *Introduction to optimum design*. Elsevier, 2004.

Ankur Bapna, Naveen Arivazhagan, and Orhan Firat. Controlling computation versus quality for neural sequence models. 2020. doi: 10.48550/ARXIV.2002.07106. URL https://arxiv.org/abs/2002.07106.

Rina Foygel Barber, Emmanuel J Candes, Aaditya Ramdas, and Ryan J Tibshirani. Predictive inference with the jackknife+. *The Annals of Statistics*, 49(1):486–507, 2021.

Stephen Bates, Anastasios Angelopoulos, Lihua Lei, Jitendra Malik, and Michael Jordan. Distribution-free, risk-controlling prediction sets. *Journal of the ACM (JACM)*, 68(6):1–34, 2021.

Syrine Belakaria, Aryan Deshwal, and Janardhan Rao Doppa. Max-value entropy search for multi-objective bayesian optimization. *Advances in Neural Information Processing Systems*, 32, 2019.

Carlo Bonferroni. Teoria statistica delle classi e calcolo delle probabilita. *Pubblicazioni del R Istituto Superiore di Scienze Economiche e Commericiali di Firenze*, 8:3–62, 1936.

Eric Bradford, Artur M Schweidtmann, and Alexei Lapkin. Efficient multiobjective optimization employing gaussian processes, spectral sampling and a genetic algorithm. *Journal of global optimization*, 71(2):407–438, 2018.

Frank Bretz, Willi Maurer, Werner Brannath, and Martin Posch. A graphical approach to sequentially rejective multiple test procedures. *Statistics in medicine*, 28(4):586–604, 2009.

Han Cai, Chuang Gan, Tianzhe Wang, Zhekai Zhang, and Song Han. Once for all: Train one network and specialize it for efficient deployment. In *International Conference on Learning Representations*, 2020.

Antonio Candelieri, Andrea Ponti, and Francesco Archetti. Fair and green hyperparameter optimization via multi-objective and multiple information source bayesian optimization. *arXiv preprint arXiv:2205.08835*, 2022.

Yair Censor. Pareto optimality in multiobjective problems. *Applied Mathematics and Optimization*, 4(1):41–59, 1977.

Xiangxiang Chu, Bo Zhang, and Ruijun Xu. Multi-objective reinforced evolution in mobile neural architecture search. In *European Conference on Computer Vision*, pp. 99–113. Springer, 2020.

Cristina Cristescu and Joshua Knowles. Surrogate-based multiobjective optimization: Parego update and test. In *Workshop on Computational Intelligence (UKCI)*, volume 770, 2015.

Kalyanmoy Deb. *Multi-Objective Optimization using Evolutionary Algorithms*. John Wiley & Sons, 2001.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Jin-Dong Dong, An-Chieh Cheng, Da-Cheng Juan, Wei Wei, and Min Sun. Dpp-net: Device-aware progressive search for pareto-optimal neural architectures. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 517–531, 2018.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Efficient multi-objective neural architecture search via lamarckian evolution. *arXiv preprint arXiv:1804.09081*, 2018.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *The Journal of Machine Learning Research*, 20(1):1997–2017, 2019.

Saurabh Goyal, Anamitra Roy Choudhury, Saurabh Raje, Venkatesan Chakaravarthy, Yogish Sabharwal, and Ashish Verma. Power-bert: Accelerating bert inference via progressive word-vector elimination. In *International Conference on Machine Learning*, pp. 3690–3699. PMLR, 2020.

Alex Graves. Adaptive computation time for recurrent neural networks. 2016.

Yue Guan, Zhengyi Li, Jingwen Leng, Zhouhan Lin, and Minyi Guo. Transkimmer: Transformer learns to layer-wise skim. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7275–7286, 2022.

Chirag Gupta, Aleksandr Podkopaev, and Aaditya Ramdas. Distribution-free binary classification: prediction sets, confidence intervals and calibration. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Xuanli He, Iman Keivanloo, Yi Xu, Xiang He, Belinda Zeng, Santosh Rajagopalan, and Trishul Chilimbi. Magic pyramid: Accelerating inference with early exiting and token pruning. *arXiv preprint arXiv:2111.00230*, 2021.

Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian journal of statistics*, pp. 65–70, 1979.

Lu Hou, Zhiqi Huang, Lifeng Shang, Xin Jiang, Xiao Chen, and Qun Liu. Dynabert: Dynamic bert with adaptive width and depth. *Advances in Neural Information Processing Systems*, 33: 9782–9793, 2020.

Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. Tinybert: Distilling bert for natural language understanding. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 4163–4174, 2020.

Yaochu Jin and Bernhard Sendhoff. Pareto-based multiobjective machine learning: An overview and case studies. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 38(3):397–415, 2008.

Florian Karl, Tobias Pielok, Julia Moosbauer, Florian Pfisterer, Stefan Coors, Martin Binder, Lennart Schneider, Janek Thomas, Jakob Richter, Michel Lang, et al. Multi-objective hyperparameter optimization–an overview. *arXiv preprint arXiv:2206.07438*, 2022.

Sehoon Kim, Sheng Shen, David Thorsley, Amir Gholami, Woosuk Kwon, Joseph Hassoun, and Kurt Keutzer. Learned token pruning for transformers. *arXiv preprint arXiv:2107.00910*, 2021.

Joshua Knowles. Parego: A hybrid algorithm with on-line landscape approximation for expensive multiobjective optimization problems. *IEEE Transactions on Evolutionary Computation*, 10(1): 50–66, 2006.

Jing Lei, James Robins, and Larry Wasserman. Distribution-free prediction sets. *Journal of the American Statistical Association*, 108(501):278–287, 2013.

Jing Lei, Max G'Sell, Alessandro Rinaldo, Ryan J Tibshirani, and Larry Wasserman. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113 (523):1094–1111, 2018.

Marius Lindauer, Katharina Eggensperger, Matthias Feurer, André Biedenkapp, Difan Deng, Carolin Benjamins, Tim Ruhkopf, René Sass, and Frank Hutter. Smac3: A versatile bayesian optimization package for hyperparameter optimization. *J. Mach. Learn. Res.*, 23:54–1, 2022.

Weijie Liu, Peng Zhou, Zhe Zhao, Zhiruo Wang, Haotang Deng, and Qi Ju. Fastbert: a self-distilling bert with adaptive inference time. *arXiv preprint arXiv:2004.02178*, 2020.

Andrew Maas, Raymond E Daly, Peter T Pham, Dan Huang, Andrew Y Ng, and Christopher Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th annual meeting of the association for computational linguistics: Human language technologies*, pp. 142–150, 2011.

Paul Michel, Omer Levy, and Graham Neubig. Are sixteen heads really better than one? *Advances in neural information processing systems*, 32, 2019.

Kaisa Miettinen. *Nonlinear multiobjective optimization*, volume 12. Springer Science & Business Media, 2012.

Sewon Min, Jordan Boyd-Graber, Chris Alberti, Danqi Chen, Eunsol Choi, Michael Collins, Kelvin Guu, Hannaneh Hajishirzi, Kenton Lee, Jennimaria Palomaki, Colin Raffel, Adam Roberts, Tom Kwiatkowski, Patrick Lewis, Yuxiang Wu, Heinrich Küttler, Linqing Liu, Pasquale Minervini, Pontus Stenetorp, Sebastian Riedel, Sohee Yang, Minjoon Seo, Gautier Izacard, Fabio Petroni, Lucas Hosseini, Nicola De Cao, Edouard Grave, Ikuya Yamada, Sonse Shimaoka, Masatoshi Suzuki, Shumpei Miyawaki, Shun Sato, Ryo Takahashi, Jun Suzuki, Martin Fajcik, Martin Docekal, Karel Ondrej, Pavel Smrz, Hao Cheng, Yelong Shen, Xiaodong Liu, Pengcheng He, Weizhu Chen, Jianfeng Gao, Barlas Oguz, Xilun Chen, Vladimir Karpukhin, Stan Peshterliev, Dmytro Okhonko, Michael Schlichtkrull, Sonal Gupta, Yashar Mehdad, and Wen-tau Yih. Neurips 2020 efficientqa competition: Systems, analyses and lessons learned. In *Proceedings of the NeurIPS 2020 Competition and Demonstration Track*, 2021.

Ali Modarressi, Hosein Mohebbi, and Mohammad Taher Pilehvar. Adapler: Speeding up inference by adaptive length reduction. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1–15, 2022.

Nafise Sadat Moosavi, Iryna Gurevych, Angela Fan, Thomas Wolf, Yufang Hou, Ana Marasović, and Sujith Ravi (eds.). *Proceedings of the Second Workshop on Simple and Efficient Natural Language Processing*, 2021.

Harris Papadopoulos, Kostas Proedrou, Volodya Vovk, and Alex Gammerman. Inductive confidence machines for regression. In *European Conference on Machine Learning*, pp. 345–356. Springer, 2002.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. *arXiv preprint arXiv:1606.05250*, 2016.

Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2020.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. *arXiv preprint arXiv:1911.08731*, 2019.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Robin Schmucker, Michele Donini, Valerio Perrone, Muhammad Bilal Zafar, and Cédric Archambeau. Multi-objective multi-fidelity hyperparameter optimization with application to fairness. In *NeurIPS Workshop on Meta-Learning*, volume 2, 2020.

Tal Schuster, Adam Fisch, Tommi Jaakkola, and Regina Barzilay. Consistent accelerated inference via confident adaptive transformers. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 4962–4979, 2021.

Tal Schuster, Adam Fisch, Jai Gupta, Mostafa Dehghani, Dara Bahri, Vinh Q Tran, Yi Tay, and Donald Metzler. Confident adaptive language modeling. *arXiv preprint arXiv:2207.07061*, 2022.

Roy Schwartz, Jesse Dodge, Noah A. Smith, and Oren Etzioni. Green ai. *Communications of the ACM*, 63(12), 2020.

Amar Shah and Zoubin Ghahramani. Pareto frontier learning with expensive correlated objectives. In *International conference on machine learning*, pp. 1919–1927. PMLR, 2016.

Zhiqing Sun, Hongkun Yu, Xiaodan Song, Renjie Liu, Yiming Yang, and Denny Zhou. Mobilebert: a compact task-agnostic bert for resource-limited devices. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 2158–2170, 2020.

Surat Teerapittayanon, Bradley McDanel, and Hsiang-Tsung Kung. Branchynet: Fast inference via early exiting from deep neural networks. In *2016 23rd International Conference on Pattern Recognition (ICPR)*, pp. 2464–2469. IEEE, 2016.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Vladimir Vovk. On-line confidence machines are well-calibrated. In *The 43rd Annual IEEE Symposium on Foundations of Computer Science.*, 2002.

Vladimir Vovk, Alexander Gammerman, and Glenn Shafer. *Algorithmic learning in a random world*. Springer Science & Business Media, 2005.

Vladimir Vovk, Ivan Petej, and Valentina Fedorova. Large-scale probabilistic predictors with and without guarantees of validity. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2015.

Vladimir Vovk, Valentina Fedorova, Ilia Nouretdinov, and Alexander Gammerman. Criteria of efficiency for conformal prediction. In *International Symposium on Conformal and Probabilistic Prediction with Applications - Volume 9653*, 2016.

Vladimir Vovk, Jieli Shen, Valery Manokhin, and Min-ge Xie. Nonparametric predictive distributions based on conformal prediction. In *Proceedings of the Sixth Workshop on Conformal and Probabilistic Prediction and Applications*, 2017.

Adina Williams, Nikita Nangia, and Samuel R Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In *2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL HLT 2018*, pp. 1112–1122. Association for Computational Linguistics (ACL), 2018.

Maciej Wołczyk, Bartosz Wójcik, Klaudia Bałazy, Igor T Podolak, Jacek Tabor, Marek Śmieja, and Tomasz Trzcinski. Zero time waste: Recycling predictions in early exit neural networks. *Advances in Neural Information Processing Systems*, 34:2516–2528, 2021.

Mengzhou Xia, Zexuan Zhong, and Danqi Chen. Structured pruning learns compact and accurate models. *arXiv preprint arXiv:2204.00408*, 2022.

Ji Xin, Raphael Tang, Jaejun Lee, Yaoliang Yu, and Jimmy Lin. DeeBERT: Dynamic early exiting for accelerating BERT inference. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2020.

Deming Ye, Yankai Lin, Yufei Huang, and Maosong Sun. Tr-bert: Dynamic token reduction for accelerating bert inference. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 5798–5809, 2021.

Jiahui Yu, Linjie Yang, Ning Xu, Jianchao Yang, and Thomas Huang. Slimmable neural networks. In *International Conference on Learning Representations*, 2019.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. *Advances in neural information processing systems*, 28, 2015.

Yanqi Zhou, Siavash Ebrahimi, Sercan Ö Arık, Haonan Yu, Hairong Liu, and Greg Diamos. Resource-efficient neural architect. *arXiv preprint arXiv:1806.07912*, 2018.

A MATHEMATICAL DETAILS

We present the proofs for our theoretical claims.

A.1 MAX P-VALUE FOR MULTIPLE RISKS

First we re-state and re-prove that taking the maximum p-value is also a valid p-value.

Lemma A.1. *Let $p_i(\boldsymbol{\tau}, \boldsymbol{\alpha})$ be a p-value for $H_{\boldsymbol{\tau},i}$, for each $i \in \{1, \ldots, c\}$. Define $p(\boldsymbol{\tau}, \boldsymbol{\alpha}) := \max_{1 \le i \le c} p_i(\boldsymbol{\tau}, \alpha_i)$. Then, for all $\boldsymbol{\tau}$ such that $H_{\boldsymbol{\tau}}$ holds, we have:*

$$\mathbb{P}\left(p(\boldsymbol{\tau}, \boldsymbol{\alpha}) \le u\right) \le u \tag{12}$$

Proof. Let $\mathcal{I} \subseteq \{1, \ldots, c\}$ be the set of all true null hypothesis at $\boldsymbol{\tau}$. We have:

$$\begin{aligned}
\mathbb{P}\left(p(\boldsymbol{\tau}, \boldsymbol{\alpha}) \le u\right) &\le \mathbb{P}\left(\max_{i \in \mathcal{I}} p_i(\boldsymbol{\tau}, \boldsymbol{\alpha}) \le u\right) \\
&= \mathbb{P}\left(\bigcap_{i \in \mathcal{I}} p_i(\boldsymbol{\tau}, \alpha_i) \le u\right) \le \max_{i \in \mathcal{I}} \mathbb{P}\left(p(\boldsymbol{\tau}, \alpha_i) \le u\right).
\end{aligned} \tag{13}$$

Since for each $i \in \mathcal{I}$, $\mathbb{P}\left(p_i(\boldsymbol{\tau}, \alpha_i) \le u\right) \le u$, we have $\max_{i \in \mathcal{I}} \mathbb{P}\left(p(\boldsymbol{\tau}, \alpha_i) \le u\right) \le u$, which implies $\mathbb{P}\left(p(\boldsymbol{\tau}, \boldsymbol{\alpha}) \le u\right) \le u$. $\qquad\square$

A.2 PROOF OF PROPOSITION 5.1

This is direct result of Split FST (Angelopoulos et al., 2021), which we prove here for completeness.

Proof. Since $\mathcal{D}^{\mathrm{opt}}$ and $\mathcal{D}^{\mathrm{testing}}$ are disjoint, i.i.d., $\mathcal{D}^{\mathrm{testing}}$ is also i.i.d. w.r.t the returned Pareto frontier over $\mathcal{D}^{\mathrm{opt}}$. Lemma A.1 then gives that $p^{\mathrm{testing}}(\boldsymbol{\tau}, \boldsymbol{\alpha})$ are super-uniform under $H_{\boldsymbol{\tau}}$.

We now prove simultaneous (α, δ)-control over $\mathcal{T}^*$. Let $H_{\boldsymbol{\tau}^*}$ be the first true null hypothesis in the sequence. Given that $p(\boldsymbol{\tau}^*, \boldsymbol{\alpha})$ is a super uniform p-value under $H_{\boldsymbol{\tau}^*}$, the probability of making a false discovery at $\boldsymbol{\tau}^*$ is bounded by δ. However, if $H_{\boldsymbol{\tau}^*}$ fails to be rejected (no false discovery), then all other $H_{\boldsymbol{\tau}}$ that follow in the sequence also fail to be rejected (regardless of if $H_{\boldsymbol{\tau}}$ is true or not). So the probability of making any false discoveries is also bounded by δ.

This implies that the probability that all configurations in $\mathcal{T}^*$ are risk controlling is at least $1 - \delta$, which also implies that any configuration in $\mathcal{T}^*$ is (α, δ)-risk controlling. $\qquad\square$

A.3 PROOF OF PROPOSITION 5.2

Proof. We restate our randomized time-sharing strategy: for each point prediction (X, Y) we independently sample the configuration $\boldsymbol{\tau}_j^* \in \mathcal{T}^*$ to use with probability Δ_j, where Δ is a point in the $|\mathcal{T}^*|$-d probability simplex. We then have that

$$\mathbb{P}(Q_i(\boldsymbol{\tau}^{\mathrm{share}}) \le \alpha_i) = \sum_{j=1}^{|\mathcal{T}^*|} \Delta_j \mathbb{P}(Q_i(\boldsymbol{\tau}_j^*) \le \alpha_i), \tag{14}$$

as Δ_j is independent of $Q_i(\boldsymbol{\tau}_j^*)$. Each $\boldsymbol{\tau}_j^* \in \mathcal{T}^*$ is (α, δ)-risk controlling. Therefore $\forall \boldsymbol{\tau}_j^* \in \mathcal{T}^*$, $\mathbb{P}\left(Q_i(\boldsymbol{\tau}_j^*) > \alpha_i\right) \le \delta$ simultaneously. We can therefore bound

$$\mathbb{P}(Q_i(\boldsymbol{\tau}^{\mathrm{share}}) \le \alpha_i) = \sum_{j=1}^{|\mathcal{T}^*|} \Delta_j \mathbb{P}(Q_i(\boldsymbol{\tau}_j^*) \le \alpha_i) \ge (1 - \delta) \sum_{j=1}^{|\mathcal{T}^*|} \Delta_j = 1 - \delta. \tag{15}$$

This holds simultaneously for all $Q_i(\boldsymbol{\tau}^{\mathrm{share}})$, $i \in \{1, \ldots, c\}$. Thus $\boldsymbol{\tau}^{\mathrm{share}}$ is also (α, δ)-risk controlling for any Δ. $\qquad\square$

A.4 EQUIVALENCE OF EQS. (9) AND (10)

For $P(Y = y) > 0$, the conditional probability $f_{X|Y}(X|Y = y)$ is equal to $\frac{f_{XY}(X, Y = y)}{P(Y=y)} = \frac{f_{XY}(X, Y=y)}{\mathbb{E}[\mathbf{1}\{Y=y\}]}$, and 0 elsewhere. Eq. (9) can then be written as:

$$\mathbb{E}\left[D'(X, Y; \tau)|Y = y\right] = \frac{\mathbb{E}\left[D'(X, Y; \tau) \cdot \mathbf{1}\{Y = y\}\right]}{\mathbb{E}\left[\mathbf{1}\{Y = y\}\right]} \le \alpha \tag{16}$$

Multiplying both sides by $\mathbb{E}\left[\mathbf{1}\{Y = y\}\right]$, we get:

$$\mathbb{E}\left[D'(X, Y; \tau) \cdot \mathbf{1}\{Y = y\}\right] \leq \alpha \cdot \mathbb{E}\left[\mathbf{1}\{Y = y\}\right] = \alpha \cdot (1 - \mathbb{E}\left[\mathbf{1}\{Y \neq y\}\right]) \tag{17}$$

Then, Eq. 10 immediately follows:

$$\mathbb{E}\left[D'(X, Y; \tau) \cdot \mathbf{1}\{Y = y\} + \alpha \cdot \mathbf{1}\{Y \neq y\}\right] \leq \alpha, \ \ \forall y \in \mathcal{Y} \tag{18}$$

Note that the per-class risks are of the same type and bounded by the same α. Since the p-value is monotonic with respect to the empirical risk, we have:

$$p(\boldsymbol{\tau}, \alpha) = \max_{y \in \mathcal{Y}} p\left(\hat{Q}_{\text{acc-class}}(y, \boldsymbol{\tau}); \alpha, m\right) = p\left(\max_{y \in \mathcal{Y}} \hat{Q}_{\text{acc-class}}(y, \boldsymbol{\tau}); \alpha, m\right). \tag{19}$$

Therefore, instead of $|\mathcal{Y}|$ objective functions, one per each class, we can define a single equivalent empirical objective $\hat{Q}_{\text{acc-worst}}(\boldsymbol{\tau}) = \max_{y \in \mathcal{Y}} \hat{Q}_{\text{acc-class}}(y, \boldsymbol{\tau})$.

A.5 SELECTIVE CLASSIFICATION

Similarly to above derivation for per-class accuracy, for selective classification we define the selective cost (given selection):

$$Q_{\text{select-cost}}(\boldsymbol{\tau}), \lambda) = \mathbb{E}\left[q_{\text{cost}}(X; \boldsymbol{\tau}) \cdot \mathbf{1}\left\{\max_y f(X, y; \boldsymbol{\tau}) \geq \lambda\right\} + \alpha \cdot \mathbf{1}\left\{\max_y f(X, y; \boldsymbol{\tau}) < \lambda\right\}\right] \tag{20}$$

and the same for selective accuracy reduction:

$$Q_{\text{select-acc}}(\boldsymbol{\tau}), \lambda) = \mathbb{E}\left[q_{\text{acc}}(X; \boldsymbol{\tau}) \cdot \mathbf{1}\left\{\max_y f(X, y; \boldsymbol{\tau}) \geq \lambda\right\} + \alpha \cdot \mathbf{1}\left\{\max_y f(X, y; \boldsymbol{\tau}) < \lambda\right\}\right] \tag{21}$$

B MULTI-DIMENSIONAL PRUNING

First, we describe the core model units and introduce some essential notation, while keeping the exact model implementation as general as possible. Second, we describe each of the pruning dimensions, its associated importance score, and the thresholding mechanism.

B.1 TRANSFORMER MODEL

Consider a Trasformer model (Vaswani et al., 2017; Devlin et al., 2018) with K layers. The input to the model is given as a sequence of L (for notational simplicity we omit here the dependency of the length on x) tokens $x = (x_1, \ldots, x_L)$, which are first mapped to learneable word embeddings $e = (e_1, \ldots, e_L)$. Tokens are then passed through the model's layers, with $h_k = (h_{k,1}, \ldots, h_{k,L})$ denoting the k-th layer hidden representation. Each layer consists of a multi-head attention, with W heads producing the combined output $a_k = \sum_{w=1}^{W} \text{Attn}_{k,w}(h_{k-1})$, which is followed by a feed-forward network to provide the next layer hidden representation. The last layer is attached to a classification head with $|\mathcal{Y}|$ outputs, where $f(x)_y$ denotes the output of class y. The model is optimized by minimizing a loss function $\mathcal{L}$ computed empirically over the training set.

B.2 TOKEN PRUNING

It is of often the case that the input consists of a large amount of tokens that have a negligible contribution for the prediction task. The idea in token pruning is to identify unimportant tokens and discard them at some point in the model.

To identify the contribution of each token, we attach to each layer a token importance predictor $s_k^{\text{tok}} : \mathcal{X} \to \mathbb{R}$ based on the token hidden representation $h_{k,l}$. Following (Modarressi et al., 2022), we use as importance scores gradient attributions, computed by:

$$r_l = \left\| \frac{\partial f(x)_y}{\partial e_l} \cdot e_l \right\|_2 \tag{22}$$

The token importance predictors in each layer are optimized with a cross-entropy loss, where the labels are the scores, normalised to sum to one. In the k-th layer, tokens with $s_k^{\text{tok}}(x_l) < \tau^{\text{tok}}$ are pruned and are not transferred to next layer. The number of tokens remaining after pruning is given by $L_k(x; \tau^{\text{tok}}) = \sum_{l=1}^{L} \bigcap_{k'=1}^{k} \mathbf{1}\left\{s_{k'}^{\text{tok}}(x_l) > \tau^{\text{tok}}\right\}$.

Table C.1: Datasets Details

Dataset	$\|\mathcal{Y}\|$	Task	Train	Val.	Test	Cal. (out of Test)	Full model Acc.
IMDB	2	Sentiment analysis on movie reviews	20K	5K	10K	5K	94
AG News	4	News topic classification	115K	5K	7.6K	5K	93
QNLI	2	Question-answer pair classification	~ 10K	5K	~ 5.5K	3.4K	92
QQP	2	Question pair semantic equivalence	~ 360K	5K	10K	5K	91
MNLI	3	Ntural language inference	~ 250K	~ 150K	30K	10K	86

B.3 EARLY EXITING

Early-exiting is based on the idea that examples vary in their difficulty level, hence, require different amount of computation to reach to a good prediction. While for simple examples a decision can be made early on, difficult examples may require going through the full model. We attach a prediction head $f_k : \mathcal{X} \to \mathcal{Y}$ to each layer, trained to predict the labels via the same loss function as the original model. Following (Liu et al., 2020), we define the importance score based on the prediction head entropy:

$$s_k^{\text{layer}}(x) = \sum_{y \in |\mathcal{Y}|} p_k(y|x) \log p_k(y|x) \tag{23}$$

where $p_k(y|x)$ are the per-class probabilities provided by the k-th prediction head. Based on this score, examples with $s_k^{\text{layer}}(x) < \tau^{\text{layer}}$ exit in the k-th layer. The exit layer of x is given by $K_{\text{exit}}(x; \tau^{\text{layer}}) = \arg\min_k \left\{ k \in \{1, \dots, K\} \middle| s_k^{\text{layer}}(x) < \tau^{\text{layer}} \right\}$.

B.4 HEAD PRUNING

It was shown (Michel et al., 2019), that significant fraction of attention heads can be removed with a little impact on the performance. Each attention head (w, k), $1 \le k \le K, 1 \le w \le W$ is assigned a score $s_k^{\text{head}}(w)$ according to:

$$s_k^{\text{head}}(w) = \left| \text{Attn}_{k,w}(h_{k-1})^T \frac{\partial \mathcal{L}}{\partial \text{Attn}_{k,w}(h_{k-1})} \right|. \tag{24}$$

The scores in each layer are normalized to sum to one. Attention heads with $s_k^{\text{head}}(w) < \tau^{\text{head}}$ are pruned. The number of heads left after pruning is given by $W_k(\tau^{\text{head}}) = \sum_{w=1}^{W} \mathbf{1} \left\{ s_k^{\text{head}}(w) > \tau^{\text{head}} \right\}$. Note that this is a fixed pruning, unlike the previous pruning dimensions that vary according to the input x.

C IMPLEMENTATION AND DATASET DETAILS

Datasets. Splitting specifications and full model performance on each task are contained in Table C.1. Note that for IMDB, QQP and MNLI we used a subset of the original dev/test set in order to expedite evaluation. For MNLI we used the split of (Sagawa et al., 2019).

Prediction Heads. Each prediction head is a 2-layer feed-forward neural network with 32 dimensional hidden states, and ReLU activation. The input is the hidden representation of the `[CLS]` token concatenated with the hidden representation of all previous layers, as was proposed in (Wołczyk et al., 2021).

Token importance predictors. Each token importance predictor is a 2-layer feed-forward neural network with 32 dimensional hidden states, and ReLU activation. The input is the hidden representation of each token in the current layer and all previous layers, following (Wołczyk et al., 2021).

Training. The core model is first finetuned on each task. We compute the attention head importance scores based on validation data. We freeze the backbone model and train the early-exit classifiers and the token importance predictors on the training data.

Figure D.1: Results of Pareto Testing over AG News with multi-objective optimizer for different number of evaluations, and with a grid of thresholds. Results are averaged over 50 random splits. Accuracy reduction is controlled and cost is minimized.

Figure D.2: Three-objectives, AG News - one controlled, two free: accuracy reduction is controlled by $\alpha = 0.05, \delta = 0.1$, cost and abstention rate are minimized. coloring is according to accuracy reduction.

D ADDITIONAL BASELINES AND RESULTS

Our method is based on LTT framework (Angelopoulos et al., 2021), which is summarized in Algorithm F.1. We compare our methods to two baselines from (Angelopoulos et al., 2021): 3D-SGT summarised in Algorithm F.2, which is a 3D extension to the 2D Hamming SGT, and Split-FST described in Appendix E. Note that we consider a broader setting in which, besides multiple risk control we wish to optimize additional free objective functions.

Moreover, we develop two additional baselines and present their results herein:

Low-Risk Path - similar to Split-FST (and Pareto Testing), this is a dual-stage method, assuming that the calibration data is split into two subsets. In the first stage, we find a solution to the constrained optimization problem, defined in Eq. (3). Then a low risk path is defined from full model to the solution. The path is defined over the grid of hyper-parameter combinations, where in each step in the path we pick a neighbouring hyper-parameter combination (increasing one dimension of previous step), where neighbour with lowest risk is chosen. The method is summarized in Algorithm F.3. Note that the method assumes that the objective functions are monotonic with respect to each of the hyper-parameters.

Constrained-Path Testing - This can be considered a variant of the proposed method. When interested in a single configuration selection for specific α and δ, a cheaper (but not equivalent) approach would be to solve *multiple* constrained problems:

$$\underset{(\tau_1,\ldots,\tau_n)\in\mathcal{T}}{\arg\min} \quad \left\{ \hat{Q}_{c+1}(\tau_1,\ldots,\tau_n),\ldots,\hat{Q}_{c+k}(\tau_1,\ldots,\tau_n) \right\}$$

$$\text{s.t.} \quad \hat{Q}_i(\tau_1,\ldots,\tau_n) < \alpha_i - \epsilon, \ \ \forall 1 \leq i \leq c \tag{25}$$

for a sequence of ϵ values in $[0,\ldots,\min_i \alpha_i]$. Then, an ordered set of hypotheses to test is defined by the solutions to Eq. (26) with *decreasing* values of ϵ. Note that both the constrained and the full multi-objective variants are equivalent for the case of a single control constraint. However, when there are multiple constraints our method operates on a larger set of hyper-parameter combinations,

Figure D.3: Shows cost and accuracy trade-offs over test data provided by a grid of 6480 configurations (18 head, 20 token and 18 early-exit thresholds).

consisting of solutions to:

$$\underset{(\tau_1,\ldots,\tau_n)\in\mathcal{T}}{\arg\min}\quad\left\{\hat{Q}_{c+1}(\tau_1,\ldots,\tau_n),\ldots,\hat{Q}_{c+k}(\tau_1,\ldots,\tau_n)\right\}$$

$$\text{s.t.}\quad\hat{Q}_i(\tau_1,\ldots,\tau_n)<\alpha_i-\epsilon_i,\ \ \forall 1\le i\le c \tag{26}$$

with ϵ_i values in $[0,\ldots,\alpha_i]$, namely, solving the constrained problem for all possible combinations of $(\epsilon_1,\ldots,\epsilon_c)$. We show in the results bellow that due to this difference, Constrained Path-Testing is inferior when constraints operate on risks with different decay patterns (such as coverage and accuracy).

Pruning model. Figure D.3 shows the accuracy and the relative cost of the proposed adaptive pruning model f for various threshold combinations, computed over test data. We see that the fusion of all pruning dimensions yields a wide variety of configurations with a clear trade-offs between accuracy and cost. In addition, the Pareto front consists of different threshold combinations, indicating that the optimal threshold value in each dimension is not fixed and varies with the desired cost/accuracy level.

Two objectives - accuracy controlled, cost minimized (additional results). Results for additional baselines are shown in Fig. D.4, including the two non-controlling baselines: α-constrained and (α,δ)-constrained, and our derived Low-Risk Path baseline. We see that, in many cases, Low-Risk Path obtains similar cost reduction compared to our proposed method, however, it is inferior for certain tasks and α values. As expected, both non-risk controlling baselines obtain lower costs compared to our method. This of course comes with a price of suffering from risk violations that exceeds $\delta=0.1$, as can be seen in the bottom line bar plots. However, we see that the there is not a large difference between the cost reductions obtained by our method and the non-controlling baselines. This indicates that our method, though providing risk control guarantees, as opposed to the non-controlling baselines, is not overly conservative, and effectively optimizes the free objective function, leading to significant cost reduction.

(a) IMDB   (b) AG News   (c) QNLI   (d) QQP

Figure D.4: Additional results for two-objectives - accuracy reduction is controlled by $\alpha \in \{0.025, 0.5, \ldots, 0.2\}$, $\delta = 0.1$, cost is minimized. Top row: accuracy reduction; middle row: relative cost; last row: rate of risk-violations. Results are averaged over 100 random splits to calibration and test.

Table D.1: Two-objective scenario: relative cost is controlled by $\alpha \in \{0.1, 0.2, 0.3\}$, $\delta = 0.1$, accuracy reduction is minimized. Shows accuracy reduction. Results are averaged over 100 trials with random splits to calibration and test.

Method	$\alpha = 0.1$				$\alpha = 0.2$				$\alpha = 0.3$			
	Ag News	IMDB	QNLI	QQP	Ag News	IMDB	QNLI	QQP	Ag News	IMDB	QNLI	QQP
3D-SGT	0.05	0.04	0.14	0.09	0.03	0.02	0.09	0.06	0.02	0.00	0.05	0.03
Split FST	0.05	0.04	0.15	0.10	0.02	0.02	0.09	0.06	0.00	0.00	0.06	0.03
Low-Risk Path	0.26	0.10	0.22	0.25	0.17	0.05	0.26	0.11	0.02	0.01	0.12	0.05
Pareto Testing	0.05	0.04	0.13	0.09	0.02	0.02	0.08	0.06	0.02	0.00	0.05	0.03

Two objectives - cost controlled, relative accuracy loss minimized. We evaluated the opposite scenario where the relative cost is controlled, while accuracy reduction is minimized. Note that for 3D-SGT and Low-Risk Path we start testing from the empty model (lowest cost risk) towards the full model. The accuracy reductions of all methods are summarized in Table D.1. We observe that as opposed to accuracy reduction, here the results of all methods are similar (except for Low-Risk Path).

Two objectives - accuracy controlled, FLOPs minimized. We experimented with a different cost measure in terms of FLOPs speed-up, which can be considered as a more practical measure, tailored to the specific architecture being used. Results are summarized in Table D.2. We see that the proposed method almost always obtains the best speed-ups, which is inline with our other results.

Three objectives - accuracy/worst accuracy controlled, cost minimized. Results for additional baselines are shown in Fig. D.5. Here too, our method performs the best. In this scenario, Constrained-Path Testing obtains similar results while Low-Risk Path is significantly worse.

Three objectives - accuracy and abstention rate controlled, cost minimized. We use the same setup of selective classification described in §7. Note that combining λ with the other three pruning dimensions, we obtain a four dimensional hyper-parameter space, where there is a complex interplay between the hyper-parameters and the risk functions. As λ increases we expect to get better

Table D.2: FLOPs Speed-Up. Accuracy Reduction is controlled by level α, while Flops Speed-Up is maximized. Results are averaged over 10 random splits to calibration and test.

Method	$\alpha = 0.025$				$\alpha = 0.05$				$\alpha = 0.1$			
	Ag News	IMDB	QNLI	QQP	Ag News	IMDB	QNLI	QQP	Ag News	IMDB	QNLI	QQP
3D-SGT	×2.34	×1.71	×1.38	×**1.89**	×2.89	×4.45	×1.59	×2.16	×3.12	×4.45	×1.99	×2.71
Split FST	×2.11	×1.69	×1.35	×1.66	×2.38	×1.99	×1.50	×2.15	×2.80	×4.18	×1.89	×2.69
Low-Risk Path	×2.38	×3.86	×1.37	×1.85	×2.95	×4.2	×1.56	×2.16	×3.65	×4.20	×1.94	×2.73
Pareto Testing	×**2.42**	×**4.82**	×**1.37**	×1.86	×**3.00**	×**4.82**	×**1.59**	×**2.18**	×**3.65**	×**4.82**	×**2.02**	×**2.86**

(a) Accuracy Difference	(b) Worst Accuracy Difference	(c) Relative Cost

Figure D.5: Three-objective scenario, MNLI - two controlled, one free: average accuracy is controlled by $\alpha_1 \in \{0.025, 0.5, \ldots, 0.2\}$, worst accuracy is controlled by $\alpha_2 = 0.15$, $\delta = 0.1$, cost is minimized without control. Results are averaged over 100 random splits to calibration and test.

accuracy-cost trade-offs since we remove difficult examples. In addition, abstention rate is monotonic with respect to λ but is also influenced by the pruning dimension in an uncharacterized manner. We control both accuracy reduction and abstention rate, while minimizing cost. Recall that in this scenario the risk functions are not necessarily monotonic with respect to the hyper-parameters, thus Low-Risk Path is not relevant. Since here we have a 4D hyper-parameter space, 3D SGT cannot be applied. Results are summarized in Fig. D.6. Here too, Pareto Testing performs the best, with similar results to Split-FST, and worst results to Constrained-Path Testing.

E FWER CONTROL

Let $\mathcal{T}_g$ denote a set of possible configurations to test, and $\mathcal{T}_r \subseteq \mathcal{T}_g$ denote the set of rejected hypotheses. When performing multiple hypothesis testing (MHT), a FWER-controlling procedure accounts for controlling the probability of making one or more false discoveries, i.e. falsely rejecting at least one true null hypothesis:

$$\mathbb{P}\left(|\mathcal{T}_r \cap \mathcal{T}_0| \geq 1\right) \leq \delta \tag{27}$$

where $\mathcal{T}_0 \subseteq \mathcal{T}_g$ is the set of configurations for which the null hypothesis is true.

We briefly describe several possible procedures, some of which exploit a-priori known structure in the hypotheses set.

Bonferroni Correction. This is the simplest procedure for counteracting the multiple testing problem, while being also the most conservative. The set of rejected hypotheses retrieved by the Bonferroni correction (Bonferroni, 1936), is given by:

$$\mathcal{H}_{BF} = \left\{ H_\tau : p^{\text{cal}}(\boldsymbol{\tau}, \boldsymbol{\alpha}) < \delta / |\mathcal{T}_g| \right\} \tag{28}$$

Fixed Sequence Testing. Multiplicity correction can be avoided when relying on a *pre-defined* ordering of the hypotheses. In FST, the hypotheses are sequentially tested with the same error budget, until failing to reject for the first time. Denoting by $H_{\tau^{(1)}}, \ldots, H_{\tau^{(T)}}$ the ordered set of hypotheses, FST yields the following set of rejected hypotheses (Holm, 1979):

$$\mathcal{H}_{FST} = \{H_{(j)} : j < J\}, \ \ J = \min_j \{j : p_{(j)} \geq \delta\} \tag{29}$$

(a) Accuracy Difference   (b) Abstention Rate   (c) Relative Cost

Figure D.6: Three-objective scenario - two controlled, one free: average accuracy is controlled by $\alpha_1 \in \{0.025, 0.5, \ldots, 0.2\}$, abstention rate is controlled by $\alpha_2 = 0.1$, $\delta = 0.1$, cost is minimized without control. Results are averaged over 100 random splits to calibration and test.

This procedure is advantageous in the case that there is a natural ordering of the hypotheses from the most likely to be rejected to the least likely one. For example, it can be applied in our problem when $n = 1$ and the hypotheses are ordered by threshold values from low to high.

Sequential Graphical Testing SGT (Bretz et al., 2009) can be viewed as an extension to FST, where the relation between the hypotheses is richer than just a sequential path, and is therefore parameterized by a directed graph G. The graph's nodes are null hypotheses, and the edges connecting between them specify the way the error budget propagates from one node to the other. Each node is allocated an initial error budget. Each time an hypothesis is rejected, the procedure reallocates the error budget from node i to the rest of the nodes according to the edge's weights, and the graph is modified. Several possible graph structures were proposed in (Angelopoulos et al., 2021) for the case of a two-dimensional grid of hypothesis. A 'Hamming graph' in which the all initial error budget is allocated to the bottom-right node, and error budget is propagated outward. Another option is 'Fallback', where the error budget is split between each possibility in the first dimension. An FST is performed for a fixed value on the first dimension, and progressing in the other dimension.

Split Fixed Sequence Testing. Proposed in (Angelopoulos et al., 2021), Split-FST can be utilized when there is no clear structural relationship between the hypotheses for defining a graph for SGT. The core idea is to split the calibration data in two subsets, where the first split is used to learn the graph, while the other is used for testing. Specifically, they propose to define a sequence of p-values β ranging from 0 to 1. Then, for each β, find the hypothesis where the p-values of all risks (computed over the first split) are the closest (in vector infinity norm) to β. Based on this ordering, FST can be then performed over the second split.

F ALGORITHMS

Algorithm F.1 Learn then Test

Definitions: f is a configurable model with n hyper-parameters $\boldsymbol{\tau} = (\tau_1, \ldots, \tau_n)$, Q is a risk function, α is a user-control bound and δ is the tolerance level. $\mathcal{T}_g$ is a set of hyper-parameters.

1: **function** CALIBRATION($\mathcal{D}_{\text{cal}}, \mathcal{T}_g, \alpha, \delta$)
2:     **for** $\tau \in \mathcal{T}_g$ **do**
3:         Associate the null hypothesis:

$$H_\tau : Q(\tau) \geq \alpha \tag{30}$$

4:         Compute the *empirical* risks over $\mathcal{D}_{\text{cal}}$:

$$\hat{Q}^{\text{cal}}(\tau) = \frac{1}{m} \sum_{(x,y) \in \mathcal{D}_{\text{cal}}} q(x, y; \tau) \tag{31}$$

5:         Compute Hoeffding p-value (or Hoeffding-Bentkus p-value):

$$p^{\text{cal}}(\tau, \alpha) = p\left(\hat{Q}^{\text{cal}}(\tau); \alpha, m\right) = e^{-2m\left(\alpha - \hat{Q}^{\text{cal}}(\tau)\right)_+^2} \tag{32}$$

6:         Recover a subset of thresholds $\mathcal{T}^* \subseteq \mathcal{T}_g$ for which the null hypothesis is rejected, by applying a FWER controlling procedure.
7:     **return** $\mathcal{T}^*$

Algorithm F.2 3D Graph Testing

Definitions: configurable model f adapted by n thresholds $\boldsymbol{\tau} = (\tau_1, \ldots, \tau_n)$, calibration data $\mathcal{D}_{\text{cal}}$ of size m, objective functions $Q_1, \ldots, Q_c$, user-specified control limits $\boldsymbol{\alpha} = (\alpha_1, \ldots, \alpha_c)$ and tolerance level δ, a grid of $I \times J \times K$ thresholds $\mathcal{T}_g = \{\tau_1^1, \ldots, \tau_1^I\} \times \{\tau_2^1, \ldots, \tau_2^J\} \times \{\tau_3^1, \ldots, \tau_3^K\}$, $\tau^{i,j,k} = (\tau_1^i, \tau_2^j, \tau_3^k)$, $\mathbf{A}$ an $I \times J \times K$ matrix with initial error budget for each configuration, satisfying $\sum_{i,j,k} A_{i,j,k} = \delta$.

1: **function** CALIBRATE($\mathcal{D}_{\text{cal}}, \boldsymbol{\alpha}, \mathbf{A}$)

2:     **for** $\boldsymbol{\tau} \in \mathcal{T}_g$ **do**

3:         For $\boldsymbol{\tau} \in \mathcal{T}_g$ compute $\hat{Q}_i^{\text{cal}}(\boldsymbol{\tau}) = \frac{1}{m} \sum_{(x,y) \in \mathcal{D}_{\text{cal}}} q_i(x, y; \boldsymbol{\tau})$.

4:         For $\boldsymbol{\tau} \in \mathcal{T}_g$ compute, compute p-values $p^{\text{cal}}(\boldsymbol{\tau}, \boldsymbol{\alpha}) = \max_{1 \leq i \leq c} p\left(\hat{Q}_i^{\text{cal}}(\boldsymbol{\tau}); \alpha_i, m\right)$.

5:     $W \leftarrow$ CREATEGRAPH ().

6:     $\mathcal{T}^* \leftarrow$ SGT $\left(W, p^{\text{cal}}(\boldsymbol{\tau}, \boldsymbol{\alpha})\right)$.

7:     $\boldsymbol{\tau}^* = \arg\min_{\boldsymbol{\tau} \in \mathcal{T}^*} \hat{Q}_c^{\text{testing}}(\boldsymbol{\tau})$

8:     **return** $\boldsymbol{\tau}^*$

9: **function** SGT($W, p^{\text{cal}}(\boldsymbol{\tau}, \boldsymbol{\alpha})$)

10:     $\mathcal{I} = \{1, \ldots, I\} \times \{1, \ldots, J\} \times \{1, \ldots, K\}$

11:     $\mathcal{T}^* \leftarrow \{\}$

12:     $i^*, j^*, k^* = \arg\min_{(i,j,k) \in O} p^{\text{cal}}(\boldsymbol{\tau}^{i,j,k}, \boldsymbol{\alpha})/A_{i,j,k}$

13:     **while** $|\mathcal{I}| \geq 1$ **do**

14:         **if** $p^{\text{cal}}(\boldsymbol{\tau}^{i,j,k}, \boldsymbol{\alpha}) < A_{i^*,j^*,k^*}$ **then**

15:             $\mathcal{T}^* \leftarrow \mathcal{T}^* \cup \boldsymbol{\tau}^{i^*,j^*,k^*}$

16:             $\mathcal{I} \leftarrow \mathcal{I}/(i^*, j^*, k^*)$

17:             $A_{i,j,k} \leftarrow A_{i,j,k} + A_{i*,j*,k*} W_{i*,j*,k* \rightarrow i,j,k}, \forall (i, j, k) \in O$

18:             $i^*, j^*, k^* = \arg\min_{(i,j,k) \in \mathcal{I}} p^{\text{cal}}(\boldsymbol{\tau}^{i,j,k}, \boldsymbol{\alpha})/A_{i,j,k}$

Algorithm F.3 Shortest-Path Testing

Definitions: configurable model f adapted by n thresholds $\boldsymbol{\tau} = (\tau_1, \ldots, \tau_n)$, calibration data $\mathcal{D}_{\text{cal}}$ of size m, objective functions $Q_1, \ldots, Q_c$, user-specified control limits $\boldsymbol{\alpha} = (\alpha_1, \ldots, \alpha_c)$ and tolerance level δ, m_1 size for first split, $m_2 = m - m_1$ size of second split, Δ_j is the resolution in the j-th dimension, $\Delta = (\Delta_1, \ldots, \Delta_n)$, $\boldsymbol{\tau}_{\text{min}}$ consists of the minimum values of all thresholds, $\boldsymbol{\tau}_{\text{max}}$ consists of the minimum values of all thresholds.

1: **Splitting:** Randomly split $\mathcal{D}_{\text{cal}}$ into $\mathcal{D}_{\text{opt}}$ and $\mathcal{D}_{\text{testing}}$ of sizes m_1 and m_2, respectively.

2: **function** OPTIMIZATION($\mathcal{D}_{\text{opt}}, \boldsymbol{\alpha}$)

3:     Define the constrained problem $\arg\min_{\boldsymbol{\tau} \in \mathcal{T}} \hat{Q}_c^{\text{opt}}(\boldsymbol{\tau})$, s.t. $\hat{Q}_i^{\text{opt}}(\boldsymbol{\tau}) < \alpha_i, \forall 1 \leq i \leq c - 1$.

4:     Apply constrained optimization to find optimal configuration $\boldsymbol{\tau}_{\text{opt}}$.

5:     $\mathcal{T}_{\text{opt}} \leftarrow$ CREATEPATH $(\boldsymbol{\tau}_{\text{min}}, \boldsymbol{\tau}_{\text{opt}}, \Delta) \cup$ CREATEPATH $(\boldsymbol{\tau}_{\text{opt}}, \boldsymbol{\tau}_{\text{max}}, \Delta)$.

6:     **return** $\mathcal{T}_{\text{opt}}$

7: **function** CREATEPATH($\boldsymbol{\tau}^{\text{start}}, \boldsymbol{\tau}^{\text{end}}, \Delta$)

8:     $\boldsymbol{\tau}^{(0)} \leftarrow \boldsymbol{\tau}_{\text{start}}$

9:     $i \leftarrow 1$

10:     **while** $\boldsymbol{\tau}^{(i)} \neq \boldsymbol{\tau}^{\text{end}}$ **do**

11:         $p_{\text{min}} \leftarrow \infty$

12:         **for** $j \in \{1, \ldots, n\}$ **do**

13:             $\tilde{\tau}_j^{(i)} \leftarrow \tau_j^{(i)} + \Delta_j$

14:             **if** $\tilde{\tau}_j^{(i)} > \tau_j^{\text{end}}$ **then**

15:                 **Continue**

16:             **else**

17:                 $\boldsymbol{\tau}^{\text{next}} \leftarrow \left(\tau_1^{(i)}, \ldots, \tilde{\tau}_j^{(i)}, \ldots, \tau_n^{(i)}\right)$

18:                 **if** $p^{\text{opt}}(\boldsymbol{\tau}^{\text{next}}, \boldsymbol{\alpha}) < p_{\text{min}}$ **then**

19:                     $\boldsymbol{\tau}^{(i)} \leftarrow \boldsymbol{\tau}^{\text{next}}$

20:                     $p_{\text{min}} \leftarrow p^{\text{opt}}(\boldsymbol{\tau}^{\text{next}}, \boldsymbol{\alpha})$

21:         $i \leftarrow i + 1$
        return $\left(\boldsymbol{\tau}^{(0)}, \ldots, \boldsymbol{\tau}^{(i)}\right)$

22: **function** CALIBRATION($\mathcal{D}_{\text{testing}}, \mathcal{T}_{\text{opt}}, \boldsymbol{\alpha}, \delta$)   ▷ Same as in Algorithm 1