RAISIN: RESIDUAL ALGORITHMS FOR VERSATILE OFFLINE REINFORCEMENT LEARNING

ABSTRACT

The residual gradient algorithm (RG), gradient descent of the Mean Squared Bellman Error, brings robust convergence guarantees to bootstrapped value estimation. Meanwhile, the far more common semi-gradient algorithm (SG) suffers from well-known instabilities and divergence. Unfortunately, RG often converges slowly in practice. Baird (1995) proposed residual algorithms (RA), weighted averaging of RG and SG, to combine RG's robust convergence and SG's speed. RA works moderately well in the online setting. We find, however, that RA works disproportionately well in the offline setting. Concretely, we find that merely adding a variable residual component to SAC increases its score on D4RL gym tasks by a median factor of 54. We further show that using the minimum of ten critics lets our algorithm match SAC-N's state-of-the-art returns using $50\times$ less compute and no additional hyperparameters. In contrast, TD3+BC with the same minimum-of-ten-critics trick does not match SAC-N's returns on a handful of environments.

1 INTRODUCTION

Strong data scaling has given us baffling success in supervised learning. Offline reinforcement learning (offline RL) holds promise for RL to scale with that same success, among other benefits. Despite all the compelling motivations of offline RL (Levine et al., 2020), we still lack a simple, versatile, and computationally efficient solution. By versatile, we mean algorithms that attain high returns when trained on any of a diverse range of datasets, such as data collected by greatly differing policies.

Arguably the simplest and most versatile approach thus far is SAC-N (An et al., 2021), which uses the minimum of N critics instead of SAC's usual two critics. SAC-N achieves state-of-the-art scores but, unfortunately, requires up to 500 critics for sufficient pessimism on benchmark problems. Hu et al. (2022) illustrates that stronger pessimism, specifically a smaller discount factor, enables SAC-N to solve harder tasks (Rajeswaran et al., 2017). A smaller discount factor is simple and computationally efficient pessimism but not versatile — it increases bias (Zhang et al., 2020).

In this paper, we identify residual algorithms (RA) (Baird, 1995) as a simple, versatile, and computationally efficient source of pessimism for SAC-N. As we explained, RA saw moderate success in its goal of fusing RG's convergence with SG's speed. Recently, Zhang et al. (2019) found similar success when extending RA to deep learning. But we find RA truly excels in the *offline* setting. Prior works in both the online and offline settings (Geist et al., 2016; Fujimoto et al., 2022; Saleh, 2019) show that, while RG performs well with data near the optimal policy, RG consistently fails when the data is far from the optimal policy. One potential explanation for this is RG's tendency to maintain its initial value predictions combined with the common scenario of Q initialized around zero and positive rewards (Wang & Ueda, 2021). Our key insight is that RA allows for the adjustable exploitation of RG's natural pessimism. In other words, a weighted RG component may serve as a superior alternative to the widespread use of a weighted behavior cloning component for offline RL (Fujimoto & Gu, 2021; Buckman et al., 2020).

We propose Raisin, roughly **RA** for **S**AC-**N**, giving D4RL (Fu et al., 2020) gym scores matching SAC-N — the state-of-the-art — with one-fiftieth of the critics. EDAC (An et al., 2021) matches those scores as well but requires both five times more compute than Raisin and adjustment of two

hyperparameters per dataset. Raisin keeps the number of critics small and fixed and solely requires adjusting one hyperparameter for pessimism (the residual weight).

Raisin easily runs at the same speed with one critic as it does with its standard ten critics (on one GPU) thanks to embarrassing parallelization, similar to SAC-N (An et al., 2021). We plan to release a clean and efficient implementation of Raisin (and SAC-N) upon acceptance of this manuscript.

Meanwhile, TD3+BC (Fujimoto & Gu, 2021) equipped with the same minimum-of-N-critics tool (TD3+BC-N) does not appear versatile. It still does not match the scores of SAC-N on a few datasets (especially the random datasets) despite extra pessimism tuning. Outside of fundamental offline RL research, such simple combinations of behavior cloning and reinforcement learning are debatably the most common approach in the literature (Humphreys et al., 2022; Baker et al., 2022; Nakano et al., 2021).

IQL is computationally efficient and potentially versatile but needs more testing on suboptimal data (e.g., the random datasets of D4RL gym tasks). Maybe even more importantly, IQL is not simple. For example, IQL uses a learning rate decay for its actor, rescales its rewards by 1000, clips advantages to 100, and adds a third learning rate. Each one of these components may be overfitting. Conversely, Raisin makes a single change to SAC-N, and SAC-N itself makes one change to SAC (Haarnoja et al., 2018), an extensively well-tested algorithm.

Upside-down reinforcement learning (UDRL) (Schmidhuber, 2019; Kumar et al., 2019) has shown some potential in recent work (Chen et al., 2021a; Lee et al., 2022), but scores poorly on suboptimal data. Not to mention that it wastes capacity learning poor behaviors (Emmons et al., 2021) and that it kicks the maximization can down the road — UDRL requires a desired-return hyperparameter, a goal specification, or a complicated equivalent.

2 PRELIMINARIES

We consider the standard offline RL setting of a fixed dataset $\mathcal{D}$ of transitions (s, a, r, s'), where s is a state, a is an action taken in that state, r is the reward received for that action, and s' is the new state. We denote our policy $\pi_\phi(\cdot|s)$, whose goal is to learn actions that maximize the discounted sum of rewards $\sum_t \gamma^t r$, where γ is the discount factor. $Q_\theta(s, a)$ is our state-action value function, whose goal is to estimate the future discounted sum of rewards given a state-action pair.

For a comprehensive overview of residual algorithms (RA), see Zhang et al. (2019). We will give a brief primer here in the context of SAC. Ignoring discounting for simplicity, SAC's loss is:

$$L(\theta_i, \mathcal{D}) := \mathop{\mathrm{E}}_{(s,a,r,s')\sim\mathcal{D}} \left[\left(Q_{\theta_i}(s, a) - \min_{j=1,2} \bar{y}(j, r, s') \right)^2 \right],$$

where θ_i refers to the parameters θ of the ith of two Q networks; and $\bar{y}$, the next-state target before minimization, is:

$$\bar{y}(j, r, s') := r + \left(\bar{Q}_{\theta_j}(s', \tilde{a}') - \alpha \log \pi_\phi(\tilde{a}'|s') \right), \quad \tilde{a}' \sim \pi_\phi(\cdot|s').$$

$\bar{Q}$ denotes the target network (Mnih et al., 2015), and α is SAC's entropy coefficient.

This critic loss derives from the Mean Squared Bellman Error (MSBE), a natural error function for bootstrapped value estimation. But SAC's critic does not quite optimize the MSBE, partly because SAC, like all common value-based RL algorithms using gradient descent, ignores the gradient contribution from the next-state term. In other words, gradient descent of SAC's critic loss treats the value of the next state (plus the reward) as a fixed target towards which the current state's value is stepped. This is known as the semi-gradient (SG) algorithm. In contrast, performing true gradient descent of the MSBE is called the residual gradient (RG) algorithm. As a true gradient algorithm, RG brings robust convergence guarantees. But, thus far, RG has empirically obtained poor returns and at slow speeds. It also suffers from a few theoretical concerns (Baird, 1995; Sutton & Barto, 2018). SG typically obtains higher returns (when it converges) despite its lesser convergence guarantees and instabilities. For this reason, SG is used in practice.

In hopes of the best of both worlds, Baird (1995) proposed RA, weighted averaging of RG and SG. Zhang et al. (2019) extended RA to DDPG, introducing bidirectional target networks as an intuitive analog to the target networks commonly used for SG: since RG uses the current state and next state symmetrically for the gradient, symmetry of the current state and next state for RG's target network likely makes sense as well. Zhang et al. (2019)'s critic loss for residual DDPG with bidirectional target networks is:

$$ L(\theta, \mathcal{D}) := \mathop{\mathrm{E}}_{(s,a,r,s') \sim \mathcal{D}} \left[\left(Q_\theta(s,a) - \bar{y}(r,s') \right)^2 + \eta \left(\bar{Q}_\theta(s,a) - y(r,s') \right)^2 \right], $$

where $\eta \in [0,1]$ controls the weight for backwards bootstrapping; and y, unlike $\bar{y}$, uses the main Q network instead of $\bar{Q}$. Both y and $\bar{y}$ otherwise follow DDPG (Lillicrap et al., 2015).

3 RAISIN

SAC-N's impressive versatility comes at the cost of massive ensembles in some environments. And as discussed in the introduction, it appears likely that even more pessimism may give SAC-N yet more versatility.

Aiming to solve both challenges, we introduce Raisin, RA adapted to SAC-N. We incorporate Zhang et al. (2019)'s bidirectional target networks, taking the minimum of N critics in the target network terms, creating the critic loss (for the i-th of the N critics):

$$ L(\theta_i, \mathcal{D}) := \mathop{\mathrm{E}}_{(s,a,r,s') \sim \mathcal{D}} \left[\left(Q_{\theta_i}(s,a) - \min_j \bar{y}(j,r,s') \right)^2 + \eta \left(\min_j \bar{Q}_{\theta_j}(s,a) - y(i,r,s') \right)^2 \right], $$

where $j \in 1, \ldots, N$; $\eta \in [0,1]$ again controls the weight for backwards bootstrapping; and again y, unlike $\bar{y}$, uses the main Q networks instead of the target networks $\bar{Q}$:

$$ y(i,r,s') := r + \left(Q_{\theta_i}(s', \tilde{a}') - \alpha \log \pi_\phi(\tilde{a}'|s') \right), \quad \tilde{a}' \sim \pi_\phi(\cdot|s'). $$

In limited testing of alternative placements of the minimum operations, Raisin performed best. Likewise, in limited testing of unidirectional target networks, Raisin performed best.

We have not yet considered whether $\tilde{a}'$ ought to be sampled twice, independently for y and $\bar{y}$ (or independently for each critic, for that matter). In our experiments, we only sample it once, which empirically works well.

Raisin's policy update otherwise follows SAC (and SAC-N), maximizing only the minimum critic estimate in the policy loss. Cheng et al. (2022) observed that, with their method, such an SAC-style policy loss resulted in a limit cycle between their critics. We did not thoroughly investigate the potential for this issue in Raisin or SAC-N, but we did test TD3-style policy optimization (maximizing a fixed, arbitrary critic in the policy loss rather than the minimum critic) as they use, finding it not to help. We additionally tested maximizing the median, the maximum, the total average, and order statistics of the critic estimates in the policy loss, in various combinations with similar approaches to the critic loss. None worked significantly better than Raisin. This aligns with Bai et al. (2022)'s comparable conclusions regarding their policy loss. From the other direction, we ran preliminary tests of TD3+BC with an SAC-style policy loss (maximizing the minimum critic) that did not appear to improve TD3+BC.

With a fixed $\eta = 0$, and our default 10 critics, Raisin would be exactly SAC-10 (SAC-N with $N = 10$). When $\eta = 0$ and $N = 2$, Raisin equates to SAC. This contrasts with TD3+BC, where no pessimism setting α recovers the base algorithm, TD3. This aspect of TD3+BC might explain its poor scores on some datasets requiring optimism, like halfcheetah (Wu et al., 2021) and the more difficult random datasets.

Table 1: Score on D4RL v2 environments, mean over four seeds. For readability, scores are rounded to whole numbers, and standard deviations to two digits. Scores $\geq 90\%$ of the best score are highlighted . BC scores are taken from the SAC-N paper. IQL scores were taken from its paper. SAC-N and SAC-10 scores were taken from the SAC-N paper where applicable. SAC-N uses up to $N = 500$ critics. We use 10.

Task Name	BC	IQL	SAC-10 ($N=10$)	TD3+BC-10 ($N=10$)	SAC-N ($N \leq 500$)	Raisin ($N=10$)
halfcheetah-random	2 ± 0.0	14	28 ± 0.9	30 ± 2.1	28 ± 0.9	28 ± 0.9
hopper-random	4 ± 0.6	8	9 ± 0.7	17 ± 11	31 ± 0.0	31 ± 0.1
walker2d-random	1 ± 0.1	8	7 ± 12	4 ± 1.0	22 ± 0.0	18 ± 9.2
halfcheetah-medium	43 ± 0.6	47	68 ± 1.2	49 ± 2.8	68 ± 1.2	68 ± 1.2
hopper-medium	54 ± 3.8	66	4 ± 1.0	87 ± 10	100 ± 0.3	73 ± 21
walker2d-medium	71 ± 11	78	95 ± 1.4	83 ± 6.7	88 ± 0.2	95 ± 1.4
halfcheetah-medium-replay	38 ± 2.1	44	64 ± 0.8	44 ± 1.4	64 ± 0.8	64 ± 0.8
hopper-medium-replay	17 ± 4.8	95	102 ± 0.3	98 ± 12	102 ± 0.5	102 ± 0.3
walker2d-medium-replay	20 ± 9.8	74	83 ± 1.1	76 ± 18	79 ± 0.7	83 ± 1.1
halfcheetah-medium-expert	44 ± 1.6	87	107 ± 2.0	91 ± 3.7	107 ± 2.0	107 ± 2.0
hopper-medium-expert	54 ± 4.7	92	6 ± 8.0	113 ± 0.2	110 ± 0.3	111 ± 0.6
walker2d-medium-expert	90 ± 13	110	88 ± 58	110 ± 2.0	117 ± 0.4	103 ± 9.1
halfcheetah-expert	92 ± 1.5	94	105 ± 2.6	91 ± 0.8	105 ± 2.6	105 ± 2.6
hopper-expert	108 ± 9.7	110	1 ± 0.0	112 ± 0.2	110 ± 0.3	110 ± 0.4
walker2d-expert	109 ± 0.2	108	3 ± 2.8	110 ± 0.3	107 ± 2.4	109 ± 0.3

With a fixed $\eta = 1$, Raisin could roughly be interpreted as RG-SAC-N. We found RG-SAC-N underperforms on certain datasets, such as halfcheetah-random. This supports the conclusion of some works we discuss in section 5, namely that RG may perform poorly when the data is far from the optimal policy. This lower performance persisted even when tuning γ (Schoknecht & Merke, 2003), using larger or smaller value nets (Nakkiran et al., 2019), or leveraging various ensemble aggregation approaches to imparting optimism.

We give the complete algorithm pseudocode in Algorithm 1.

4 EXPERIMENTS

In all of our experiments with Raisin, we do not attempt to tune any hyperparameters other than pessimism. We use the default hyperparameters of SAC-N, which uses the default hyperparameters of SAC aside from increasing the number of layers (for both the actor and critic) from 2 to 3, following e.g., CQL.

Like SAC-N and ATAC (Cheng et al., 2022), we find that tuning the pessimism (in our case η) per dataset is crucial for performance, so we study that setting, tuning for both Raisin and the new baseline we introduce below. SAC-N's experiments were tuned the same way.

4.1 RAISIN-10 VS. TD3+BC-10

Fixing $N = 10$, and giving TD3+BC the minimum-of-N-critics trick as well, we find that Raisin outscores TD3+BC-10 even when we tune each method's respective pessimism on each of the datasets. We show this in Table 1.

An et al. (2021) echoes this finding, where CQL does not match SAC-N's performance even when CQL is given the N critics trick, and the pessimism (N) is tuned per dataset. Evidently, the N critics trick is no silver bullet for all offline RL algorithms — RA-SAC with bidirectional target networks appears to be the best base algorithm.

Table 2: $N = 2$ scores. SAC scores from An et al. (2021). TD3+BC scores (for v2 environments) are taken from the TD3+BC appendix. Unlike our main experiments with TD3+BC-10 above, this experiment is an unfair comparison in Raisin-2's favor in that TD3+BC scores here use only 1M gradient steps and a single pessimism setting. But the TD3+BC paper's (Fujimoto & Gu, 2021) Figures 4 and 6 might imply neither difference would help TD3+BC as much as one might think.

Task Name	TD3+BC	Raisin-2	SAC
halfcheetah-random	11 ± 1.1	30 ± 1.4	30 ± 1.4
hopper-random	9 ± 0.6	31 ± 0.2	10 ± 1.5
walker2d-random	2 ± 1.7	7 ± 7.8	1 ± 0.8
halfcheetah-medium	48 ± 0.3	63 ± 0.4	55 ± 28
hopper-medium	59 ± 4.2	71 ± 29	1 ± 0.0
walker2d-medium	84 ± 2.1	89 ± 1.0	0 ± 0.2
halfcheetah-medium-replay	45 ± 0.5	54 ± 2.0	1 ± 1.0
hopper-medium-replay	61 ± 19	102 ± 1.2	7 ± 0.5
walker2d-medium-replay	82 ± 5.5	90 ± 5.9	0 ± 0.3
halfcheetah-medium-expert	91 ± 4.3	50 ± 38	28 ± 19
hopper-medium-expert	98 ± 9.4	80 ± 57	1 ± 0.0
walker2d-medium-expert	110 ± 0.5	115 ± 1.1	2 ± 3.9
halfcheetah-expert	97 ± 1.1	43 ± 24	-1 ± 1.8
hopper-expert	108 ± 7.0	31 ± 45	1 ± 0.0
walker2d-expert	110 ± 0.3	45 ± 50	1 ± 0.3

As An et al. (2021) found with SAC-N, we find Raisin requires longer to converge on certain environments, so, like them, we run our experiments (Raisin and TD3+BC-10) for 3M gradient steps.

We give the pessimism settings for each method in Appendix A.

4.2 ENSEMBLE ABLATION: RAISIN-2 ($N = 2$)

We find Raisin with $N = 2$, which we call Raisin-2 (approximately SAC with residual algorithms and bidirectional target networks), surprisingly improves SAC's D4RL gym scores by a median factor of 54. We show those scores in Table 2. Raisin-2 gives a competitive offline RL algorithm on its own, with negligible additional computation — but Raisin shines best with scaling (as shown in Table 1).

While we again use 3M gradient steps for this experiment, Raisin-2 looks like it would benefit from more gradient steps. We include learning curves in Appendices C and D.

4.3 WHY ARE RAS ROBUSTLY PESSIMISTIC HERE? ($N = 1$)

To our knowledge, we are the first to show that RA can induce robust pessimism, in the sense that RA can empirically turn an online algorithm into a strong offline algorithm. In these two experiments, we test two hypotheses for this robust pessimism.

Is it the second minimum? We first test the hypothesis that RAs are robustly pessimistic here primarily due to the second minimum operation we introduced, on the current state in the backwards bootstrapping term: $\min_j \bar{Q}_{\theta_j}(s, a)$. To do so, we run Raisin with $N = 1$, effectively removing both our new minimum operation and SAC-N's original minimum operation. Even with $N = 1$, increasing the backwards bootstrapping weight η drastically increases scores, as we show in the left plot of Figure 1.

Figure 1: **Left**: Raisin-1 ($N = 1$) scores on hopper-expert with 1M gradient steps, varying η, the residual weight. $\eta = 100\%$'s massive improvement over $\eta = 0\%$ suggests our second minimum operation is not the only driver of Raisin's pessimism. **Right**: Average Q targets for Raisin-1 on hopper-expert, showing that higher η avoids unreasonably large Q values. The convergence of $\eta = 0\%$ might also imply that instability alone does not account for the failure of SG.

Figure 1 (right) additionally shows that larger η values decrease the Q targets. Notably, even $\eta = 0\%$ does converge (albeit to massive values) despite poor scores, suggesting RAs indeed play an important role beyond improved convergence.

These results rule out the second minimum operation as being Raisin's primary source of increased pessimism.

Is it value function initialization? Wang & Ueda (2021) argue that RG (recall that RG is equivalent to RA with $\eta = 100\%$) has a tendency to maintain the average prediction. They point out that, in the tabular case, the changes in RG's value prediction at the current state and next state nearly cancel out (dependent on the discount factor) when viewing the value predictions aggregated over all states and actions. They further argue that when Q^* lies above Q's initialization (as it does in our experiments), RG's performance hinges on the exploration strategy chosen. This relates to the earlier observations that residual algorithms can be slow (Baird, 1995).

Accordingly, we test the effects of varying the value initialization. With $N = 1$, increasing the value initialization indeed quickly gives worse scores, shown in the left of Figure 2. And the average Q targets indeed remain nearly constant over gradient steps with larger initializations, shown in the right of Figure 2.

Thus, at first sight, negative rewards, along with a standard near-zero initialization (Andrychowicz et al., 2020), might pose an issue for Raisin. However, returning to our standard $N = 10$, Raisin performs far more robustly, as we show in the left of Figure 3.

Consequently, one might expect the corresponding Q targets to look like the $N = 1$ case but to just decrease faster towards Q^*. Instead, we see more and more of a peculiar rebound effect from excessive optimism towards excessive pessimism as we *increase* Q's initialization, all despite the decent returns. We show this in the right of Figure 3.

Granted, both SAC-N and Raisin sometimes exhibit similar behavior of high scores with excessively low Q targets even without modifying Q's initialization. For example, we reliably see this with the standard SAC-500 to solve hopper-expert.

In any case, we ran limited tests at large value initializations with re-tuning of η, further improving performance. Moreover, removing the need to tune η may be within close reach through recent work related to RG, some of which we discuss in the following section. Not to mention, a larger N nearly eliminated the issue already, and there are clear routes for additional improvements to Raisin's computational efficiency, such as DroQ (Hiraoka et al., 2021) and BatchEnsemble (Wen et al., 2020).

Figure 2: **Left**: Raisin-1 scores on hopper-expert, varying the value initialization. Scores deteriorate quickly as the initialization increases. For reference, Raisin-10, TD3+BC-10, and SAC-N all achieve average returns of roughly 3,500 on hopper-expert (normalized scores of 110). $N = 1$ is not robust to large initializations. **Right**: Raisin-1's average Q targets on hopper-expert when varying the initialization of Q. The slow rates of change align with Wang & Ueda (2021)'s speculation that their argument extends to the function approximation case.

Figure 3: **Left**: Raisin-10 scores on hopper-expert, varying the value initialization. **Right**: Raisin-10's average Q targets on hopper-expert when varying the initialization of Q. Note the strange overshooting effect at higher value initializations, even though such agents often achieve high scores. We do sometimes observe this even with the standard initialization of 0, for example, SAC-N on hopper-expert with 500 critics, as suggested by An et al. (2021).

5 RELATED WORK

5.1 ONLINE RESIDUAL APPROACHES

Bi-Res-DDPG (Zhang et al., 2019) reviews RG, SG, RA, and their respective fixed points. They introduce bidirectional target networks for residual algorithms in the context of DDPG. Bi-Res-DDPG shows up to a $3\times$ improvement in AUC (area under the curve of returns) over DDPG on the DeepMind Control Suite (Tassa et al., 2018). Whereas we identify RA as a natural fit for offline RL, propose what can be seen as Bi-Res-SAC, and show a median $50\times$ improvement in final scores over SAC. We further show that the minimum-of-N-critics trick synergizes with our algorithm particularly well, which lets us match SAC-N with a tiny fraction of the ensemble size and outscore TD3+BC given the same N critics trick. Lastly, we also delve into the sources of our robust pessimism.

C-DQN (Wang & Ueda, 2021) minimizes the maximum of RG's loss and SG's loss. Similar to RA, they claim this captures the best of both worlds, convergence and efficiency. They do not compare against RA, and they study only the online setting. A C-DQN-like approach might offer a way to avoid the need to tune η or some equivalent. They additionally analyze potential failure modes of RG, as we discussed earlier.

5.2 OFFLINE RESIDUAL APPROACHES

ATAC (Cheng et al., 2022) introduces an adversarially trained algorithm with strong theoretical backing. They also incorporate RA as a fixed, equal weighting of RG and SG, using it for stability on top of their offline RL method. In contrast, we use a variable RA in order to control pessimism, showing among other things that RA integrated into SAC dramatically improves its returns in offline RL when η is set appropriately.

DBRM (Saleh, 2019) finds that RG fails at simple offline RL benchmarks when given the trajectories of a Q-learning agent trained online. This holds even with a fully deterministic environment (i.e., no double sampling bias, explained below), and despite the fact that Q-learning (a new agent trained offline on the same dataset) performs fairly well. They propose and test higher norms of the Bellman error in order to penalize larger residuals more, which requires more optimization steps but gets slightly better performance. It does not match SG's performance. This experimental setting is similar to D4RL's -medium-replay and -full-replay datasets, where we find intermediate values of η to significantly outperform $\eta \in \{0, 1\}$.

Xiao et al. (2021) analyzes the fixed points of RG and SG in the overparameterized linear setting, finding they converge to different fixed points, potentially calling for increased caution around the common discussion point that overparameterized neural networks are capable of minimizing the MSBE perfectly by minimizing its projection (Fujimoto et al., 2022), the Mean Squared Projected Bellman Error (MSPBE). They further introduce two regularizers for SG and RG, again in the hopes of obtaining the best of both worlds. This is another potential avenue for replacing the need to tune η for Raisin, or for upgrading/removing Raisin's SG component (which, as with the most commonly used RL algorithms, may cause divergence).

5.3 DOUBLE SAMPLING BIAS

In stochastic environments, the algorithm we have presented looks more like the naive residual gradient (naive RG) algorithm (Sutton & Barto, 2018) than the true RG. Naive RG arises when applying RG without a second, independent sample for all stochastic transitions. Naive RG, a biased estimate of true RG, no longer minimizes the MSBE. As such, naive RG can lead to poor solutions in certain stochastic environments.

Our understanding is that MuJoCo (Todorov et al., 2012) (at least in the context of the v2 environments of gym (Brockman et al., 2016), which we use in this paper) is stochastic (OpenAI, 2022; DeepMind, 2022). Although Fujimoto et al. (2022) claims otherwise, perhaps because they assume the stochasticity is minor enough to ignore. That being said, we follow Zhang et al. (2019) in ignoring this stochasticity, which empirically is not a blocker for strong performance. Granted, this suggests properly handling the double sampling bias could lead to yet stronger performance for Raisin. Many

prior works, such as K-loss (Feng et al., 2019) and SBEED (Dai et al., 2017), have already tackled this issue.

5.4 MISCELLANEOUS RELATED WORK

Estimation Bias and The Update-to-Data Ratio. Offline RL and SAC-N, in particular, have clear ties to the literature on estimation bias in bootstrapped value learning, such as the many works making use of ensembles in ways similar to the minimum-of-N-critics trick, and/or high update-to-data (UTD) ratios (of which offline RL is the extreme point). This includes methods such as Maxmin Q-Learning (Lan et al., 2020), REDQ (Chen et al., 2021b), TQC (Kuznetsov et al., 2020), and more recently DroQ (Hiraoka et al., 2021), which have led to impressive results in real-world reinforcement learning (Smith et al., 2022).

Theoretically Sound Algorithms. Works such as TDC (Sutton et al., 2009), SBEED (Dai et al., 2017), and QRC (Patterson et al., 2021) use gradient corrections to build convergent online RL algorithms. Gradient correction algorithms can be seen as approximations to gradient descent of the MSBE (Patterson et al., 2021), which Raisin approximates as well (in a much different manner). We believe our empirical results may help further develop such sound algorithms, especially in the offline setting. Additionally, the adaptivity of these algorithms might point to a similar adaptive approach that obviates Raisin's need to tune η.

Recent Criticism of The Bellman Error. Fujimoto et al. (2022) uses both theory and experiments to point out drawbacks of the Bellman error, primarily its deficiencies concerning the value error. However, they conclude that the Bellman error can be a usable objective for on-policy evaluation. Geist et al. (2016) proposes a method for minimizing the Bellman residual through policy search (tangentially circumventing double sampling bias in the process) to more fairly compare the minimization of the Bellman residual versus direct maximization of the estimated value. They theoretically and empirically analyze the two approaches, similarly finding that their minimization of the Bellman residual performs poorly when the optimal policy is far from the data.

Pessimism. Buckman et al. (2020) argues that offline RL algorithms that induce pessimism by penalizing deviations from the policy that collected the data may be strictly worse than uncertainty-based approaches. This would further support the notion that Raisin and Raisin-like approaches are a more promising tack than TD3+BC and TD3+BC-like approaches.

6 CONCLUSION

Prior offline RL algorithms are either not versatile, not simple, or computationally inefficient. Raisin works on datasets collected by diverse behavior policies, consists of two simple changes to SAC, and requires only two percent of the compute of SAC-N despite state-of-the-art scores.

Important future work includes investigating automatic alternatives to tuning η, evaluating on more challenging benchmarks, and integrating a sound alternative to SG (though nearly all other RL algorithms used in practice are also based on SG).

Another promising direction involves removing the target networks altogether, instead relying on the stability of RG, thus reducing bias and potentially increasing convergence speed (Liang et al., 2022). In Zhang et al. (2019)'s experiments, RA-DDPG, when excluding target networks, performed best with a larger RG weight than RA-DDPG's optimal RG weight when including target networks. This lends some support to the possibility that in the offline setting, for which RG seems to be a natural fit, removing target networks may be the better choice.

Regarding sound alternatives to SG, perhaps the first step ought to be confirming which if either aspect of RG is most important for Raisin: the learning dynamics of RG versus its fixed point (Xiao et al., 2021). One good way to examine that might be to start from a value net trained with SG and then switch to RG, and vice versa. Such investigations may prove particularly useful if Raisin does not scale better than existing approaches (Lee et al., 2022).

REFERENCES

Gaon An, Seungyong Moon, Jang-Hyun Kim, and Hyun Oh Song. Uncertainty-Based Offline Reinforcement Learning with Diversified Q-Ensemble. *arXiv*, October 2021. doi: 10.48550/arXiv. 2110.01548.

Marcin Andrychowicz, Anton Raichuk, Piotr Stańczyk, Manu Orsini, Sertan Girgin, Raphael Marinier, Léonard Hussenot, Matthieu Geist, Olivier Pietquin, Marcin Michalski, Sylvain Gelly, and Olivier Bachem. What Matters In On-Policy Reinforcement Learning? A Large-Scale Empirical Study. *arXiv*, June 2020. doi: 10.48550/arXiv.2006.05990.

Chenjia Bai, Lingxiao Wang, Zhuoran Yang, Zhihong Deng, Animesh Garg, Peng Liu, and Zhaoran Wang. Pessimistic Bootstrapping for Uncertainty-Driven Offline Reinforcement Learning. *arXiv*, February 2022. doi: 10.48550/arXiv.2202.11566.

L. Baird. Residual Algorithms: Reinforcement Learning with Function Approximation. 1995. URL https://www.semanticscholar.org/paper/Residual-Algorithms.

Bowen Baker, Ilge Akkaya, Peter Zhokhov, Joost Huizinga, Jie Tang, Adrien Ecoffet, Brandon Houghton, Raul Sampedro, and Jeff Clune. Video PreTraining (VPT): Learning to Act by Watching Unlabeled Online Videos. *arXiv*, June 2022. doi: 10.48550/arXiv.2206.11795.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Jacob Buckman, Carles Gelada, and Marc G. Bellemare. The Importance of Pessimism in Fixed-Dataset Policy Optimization. *arXiv*, September 2020. doi: 10.48550/arXiv.2009.06799.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision Transformer: Reinforcement Learning via Sequence Modeling. *arXiv*, June 2021a. doi: 10.48550/arXiv.2106.01345.

Xinyue Chen, Che Wang, Zijian Zhou, and Keith Ross. Randomized Ensembled Double Q-Learning: Learning Fast Without a Model. *arXiv*, January 2021b. doi: 10.48550/arXiv.2101.05982.

Ching-An Cheng, Tengyang Xie, Nan Jiang, and Alekh Agarwal. Adversarially Trained Actor Critic for Offline Reinforcement Learning. *arXiv*, February 2022. doi: 10.48550/arXiv.2202.02446.

Bo Dai, Albert Shaw, Lihong Li, Lin Xiao, Niao He, Zhen Liu, Jianshu Chen, and Le Song. SBEED: Convergent Reinforcement Learning with Nonlinear Function Approximation. *arXiv*, December 2017. doi: 10.48550/arXiv.1712.10285.

DeepMind. dm_control, September 2022. URL https://github.com/deepmind/dm_control/issues/64.

Scott Emmons, Benjamin Eysenbach, Ilya Kostrikov, and Sergey Levine. RvS: What is Essential for Offline RL via Supervised Learning? *arXiv*, December 2021. doi: 10.48550/arXiv.2112.10751.

Yihao Feng, Lihong Li, and Qiang Liu. A Kernel Loss for Solving the Bellman Equation. *arXiv*, May 2019. doi: 10.48550/arXiv.1905.10506.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: Datasets for Deep Data-Driven Reinforcement Learning. *arXiv*, April 2020. doi: 10.48550/arXiv.2004.07219.

Scott Fujimoto and Shixiang Shane Gu. A Minimalist Approach to Offline Reinforcement Learning. *arXiv*, June 2021. doi: 10.48550/arXiv.2106.06860.

Scott Fujimoto, David Meger, Doina Precup, Ofir Nachum, and Shixiang Shane Gu. Why Should I Trust You, Bellman? The Bellman Error is a Poor Replacement for Value Error. *arXiv*, January 2022. doi: 10.48550/arXiv.2201.12417.

Matthieu Geist, Bilal Piot, and Olivier Pietquin. Is the Bellman residual a bad proxy? *arXiv*, June 2016. doi: 10.48550/arXiv.1606.07636.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft Actor-Critic: Off-Policy Maximum Entropy Deep Reinforcement Learning with a Stochastic Actor. *arXiv*, January 2018. doi: 10.48550/arXiv.1801.01290.

Takuya Hiraoka, Takahisa Imagawa, Taisei Hashimoto, Takashi Onishi, and Yoshimasa Tsuruoka. Dropout Q-Functions for Doubly Efficient Reinforcement Learning. *arXiv*, October 2021. doi: 10.48550/arXiv.2110.02034.

Hao Hu, Yiqin Yang, Qianchuan Zhao, and Chongjie Zhang. On the Role of Discount Factor in Offline Reinforcement Learning. *arXiv*, June 2022. doi: 10.48550/arXiv.2206.03383.

Peter C. Humphreys, David Raposo, Toby Pohlen, Gregory Thornton, Rachita Chhaparia, Alistair Muldal, Josh Abramson, Petko Georgiev, Alex Goldin, Adam Santoro, and Timothy Lillicrap. A data-driven approach for learning to control computers. *arXiv*, February 2022. doi: 10.48550/arXiv.2202.08137.

Aviral Kumar, Xue Bin Peng, and Sergey Levine. Reward-Conditioned Policies. *arXiv*, December 2019. doi: 10.48550/arXiv.1912.13465.

Arsenii Kuznetsov, Pavel Shvechikov, Alexander Grishin, and Dmitry Vetrov. Controlling Overestimation Bias with Truncated Mixture of Continuous Distributional Quantile Critics. *arXiv*, May 2020. doi: 10.48550/arXiv.2005.04269.

Qingfeng Lan, Yangchen Pan, Alona Fyshe, and Martha White. Maxmin Q-learning: Controlling the Estimation Bias of Q-learning. *arXiv*, February 2020. doi: 10.48550/arXiv.2002.06487.

Kuang-Huei Lee, Ofir Nachum, Mengjiao Yang, Lisa Lee, Daniel Freeman, Winnie Xu, Sergio Guadarrama, Ian Fischer, Eric Jang, Henryk Michalewski, and Igor Mordatch. Multi-Game Decision Transformers. *arXiv*, May 2022. doi: 10.48550/arXiv.2205.15241.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline Reinforcement Learning: Tutorial, Review, and Perspectives on Open Problems. *arXiv*, May 2020. doi: 10.48550/arXiv.2005.01643.

Litian Liang, Yaosheng Xu, Stephen McAleer, Dailin Hu, Alexander Ihler, Pieter Abbeel, and Roy Fox. Reducing Variance in Temporal-Difference Value Estimation via Ensemble of Deep Networks. *arXiv*, September 2022. doi: 10.48550/arXiv.2209.07670.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv*, September 2015. doi: 10.48550/arXiv.1509.02971.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen, Charlie Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.

Reiichiro Nakano, Jacob Hilton, Suchir Balaji, Jeff Wu, Long Ouyang, Christina Kim, Christopher Hesse, Shantanu Jain, Vineet Kosaraju, William Saunders, Xu Jiang, Karl Cobbe, Tyna Eloundou, Gretchen Krueger, Kevin Button, Matthew Knight, Benjamin Chess, and John Schulman. WebGPT: Browser-assisted question-answering with human feedback. *arXiv*, December 2021. doi: 10.48550/arXiv.2112.09332.

Preetum Nakkiran, Gal Kaplun, Yamini Bansal, Tristan Yang, Boaz Barak, and Ilya Sutskever. Deep Double Descent: Where Bigger Models and More Data Hurt. *arXiv*, December 2019. doi: 10.48550/arXiv.1912.02292.

OpenAI. gym, September 2022. URL `https://github.com/openai/gym/issues/1193`.

Andrew Patterson, Adam White, and Martha White. A Generalized Projected Bellman Error for Off-policy Value Estimation in Reinforcement Learning. *arXiv*, April 2021. doi: 10.48550/arXiv.2104.13844.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. *arXiv*, September 2017. doi: 10.48550/arXiv.1709.10087.

Ehsan Saleh. Deterministic Bellman Residual Minimization, 2019. URL https://www.semanticscholar.org/paper/Deterministic-Bellman-Residual-Minimization-Saleh/a47e9b858af68ded7c31432a9da04b3f4e666b1d.

Juergen Schmidhuber. Reinforcement Learning Upside Down: Don't Predict Rewards – Just Map Them to Actions. *arXiv*, December 2019. doi: 10.48550/arXiv.1912.02875.

Ralf Schoknecht and Artur Merke. Td (0) converges provably faster than the residual gradient algorithm. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pp. 680–687, 2003.

Laura Smith, Ilya Kostrikov, and S. Levine. A Walk in the Park: Learning to Walk in 20 Minutes With Model-Free Reinforcement Learning. *undefined*, 2022. URL https://www.semanticscholar.org/paper/A-Walk-in-the-Park%3A-Learning-to-Walk-in-20-Minutes-Smith-Kostrikov/b4888a20a9910e292448a51bf4248cc5b60e2af3.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Richard S Sutton, Hamid Reza Maei, Doina Precup, Shalabh Bhatnagar, David Silver, Csaba Szepesvári, and Eric Wiewiora. Fast gradient-descent methods for temporal-difference learning with linear function approximation. In *Proceedings of the 26th annual international conference on machine learning*, pp. 993–1000, 2009.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, Timothy Lillicrap, and Martin Riedmiller. DeepMind Control Suite. *arXiv*, January 2018. doi: 10.48550/arXiv.1801.00690.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ international conference on intelligent robots and systems*, pp. 5026–5033. IEEE, 2012.

Zhikang T. Wang and Masahito Ueda. Convergent and Efficient Deep Q Network Algorithm. *arXiv*, June 2021. doi: 10.48550/arXiv.2106.15419.

Yeming Wen, Dustin Tran, and Jimmy Ba. BatchEnsemble: An Alternative Approach to Efficient Ensemble and Lifelong Learning. *arXiv*, February 2020. doi: 10.48550/arXiv.2002.06715.

Yanqiu Wu, Xinyue Chen, Che Wang, Yiming Zhang, Zijian Zhou, and Keith W. Ross. Aggressive Q-Learning with Ensembles: Achieving Both High Sample Efficiency and High Asymptotic Performance. *arXiv*, November 2021. doi: 10.48550/arXiv.2111.09159.

Chenjun Xiao, Bo Dai, Jincheng Mei, Oscar A Ramirez, Ramki Gummadi, Chris Harris, and Dale Schuurmans. Understanding and leveraging overparameterization in recursive value estimation. In *International Conference on Learning Representations*, 2021.

Shangtong Zhang, Wendelin Boehmer, and Shimon Whiteson. Deep Residual Reinforcement Learning. *arXiv*, May 2019. doi: 10.48550/arXiv.1905.01072.

Shangtong Zhang, Romain Laroche, Harm van Seijen, Shimon Whiteson, and Remi Tachet des Combes. A Deeper Look at Discounting Mismatch in Actor-Critic Algorithms. *arXiv*, October 2020. doi: 10.48550/arXiv.2010.01069.

A PESSIMISM SETTINGS

Table 3: TD3+BC-10's α multiplies Q in its policy loss (higher is more optimistic). Raisin's η multiplies its backwards bootstrapping term (lower is more optimistic).

Task Name	TD3+BC-10: α	Raisin: η ($N = 10$)	Raisin-2: η ($N = 2$)
halfcheetah-random	150	0%	0%
hopper-random	20	10%	40%
walker2d-random	0.5	1%	20%
halfcheetah-medium	4	0%	20%
hopper-medium	10	10%	60%
walker2d-medium	10	0%	20%
halfcheetah-medium-replay	2	0%	20%
hopper-medium-replay	50	0%	20%
walker2d-medium-replay	8	0%	40%
halfcheetah-medium-expert	2	0%	0%
hopper-medium-expert	2	20%	40%
walker2d-medium-expert	4	30%	20%
halfcheetah-expert	0.5	0%	40%
hopper-expert	2	20%	80%
walker2d-expert	1	5%	60%

B ALGORITHM PSEUDOCODE

Algorithm 1 Raisin. Differences from SAC highlighted .

1: **repeat**
2:     Sample a batch $B = \{(s, a, r, s')\}$ from the offline dataset $\mathcal{D}$
3:     Compute the shared, pre-minimization, current-state targets $\bar{Q}_{\theta_j}(s, a)$ for $j \in 1, \ldots, N$.
4:     Compute the shared, pre-minimization, next-state targets for $j \in 1, \ldots, N$:

$$\bar{y}(j, r, s') := r + \left(\bar{Q}_{\theta_j}(s', \tilde{a}') - \alpha \log \pi_\phi(\tilde{a}'|s') \right), \quad \tilde{a}' \sim \pi_\phi(\cdot|s')$$

5:     Update each critic Q_{θ_i} descending its gradient:

$$\nabla_{\theta_i} \frac{1}{|B|} \sum_{(s,a,r,s') \in B} \left[\left(Q_{\theta_i}(s, a) - \min_{j \in 1, \ldots, N} \bar{y}(j, r, s') \right)^2 + \eta \left(\min_{j \in 1, \ldots, N} \bar{Q}_{\theta_j}(s, a) - y(i, r, s') \right)^2 \right]$$

where the next-state prediction is :

$$y(i, r, s') := r + \left(Q_{\theta_i}(s', \tilde{a}') - \alpha \log \pi_\phi(\tilde{a}'|s') \right), \quad \tilde{a}' \sim \pi_\phi(\cdot|s')$$

6:     Update the policy π_ϕ ascending its gradient:

$$\nabla_\phi \frac{1}{|B|} \sum_{s \in B} \left(\min_{j=1, \ldots, N} Q_{\phi_j}(s, \tilde{a}_\phi(s)) - \alpha \log \pi_\phi(\tilde{a}_\phi(s) \mid s) \right),$$

where $\tilde{a}_\phi(s)$ is a sample from $\pi_\phi(\cdot \mid s)$ which is differentiable w.r.t. ϕ via the reparameterization trick.
7:     Update target networks with $\phi_i' \leftarrow \rho\phi_i' + (1 - \rho)\phi_i$

C RAISIN ($N = 10$) LEARNING CURVES

Like An et al. (2021), we see strange, highly non-monotonic learning over gradient steps on some datasets. This occurs in the most consistent manner on the hopper datasets, particularly hopper-random. We speculate this might be related to epoch-wise double descent (Nakkiran et al., 2019), but it's unclear. We omit a few curves where Raisin's optimal setting recovers SAC-N ($\eta = 0$), since we only re-ran enough of those experiments to verify we still saw the same behavior. (Our code is built on their SAC-N code.)

D   RAISIN-2 ($N = 2$) LEARNING CURVES

With smaller N, the first peak is less sharp. For a similar depiction of this phenomenon as N varies more, see An et al. (2021)'s Figure 1.