Unifying Pixel-Labeling Vision Tasks by Sequence Modeling

Abstract

Developing a single neural network that can perform a wide range of tasks is an active area of research in computer vision. However, unifying models for pixel-labeling tasks presents significant challenges due to the diverse forms of outputs and the reliance on task-specific structures. In this paper, we propose UniTask, a model that unifies pixel-labeling tasks by modeling them with discrete vocabulary codes. UniTask consists of two main components: a Sequence Learner that produces a unified expression and a Dense Decoder that constructs latent codes for dense prediction outputs. This combination enables UniTask to model the complex task space using unified discrete representations while maintaining high-quality output for pixel-labeling tasks. We evaluate UniTask on three pixel-labeling tasks: semantic segmentation, surface normal estimation, and monocular depth estimation. The experimental results show that UniTask is a promising approach for unifying pixel-labeling tasks and is competitive with established task-specific models. Code will be available.

1 Introduction

Researchers have been working on developing general models that use a single neural network to perform multiple tasks. A key aspect of achieving this goal is to build unified representations for multiple modalities and tasks. The rise of autoregressive sequence models parameterized by Transformers (Vaswani et al., 2017) has led to the use of discrete vocabulary codes as a popular method for achieving unification. Compared to continuous and high-dimensional representations, discrete representations have more potential to fit different modalities and tasks. Language can be represented as a sequence of symbols, which are inherently discrete. Similarly, visual tasks such as keypoints detection and object detection produce discrete sets of keypoints or bounding boxes.

Recent models (Jaegle et al., 2021b;a; Wang et al., 2022; Alayrac et al., 2022) have made various attempts in this regard. For instance, Pix2Seq (Chen et al., 2021) quantizes the coordinates of bounding boxes and class labels of object detection into discrete tokens. Pix2Seq v2 (Chen et al., 2022) further expresses the discrete forms of more tasks like instance segmentation and keypoint estimation. Unified-IO (Lu et al., 2022) targets a wider set of vision and language tasks and homogenizes them into a sequence of discrete tokens.

However, for dense prediction tasks which produce pixel-level predictions of images, unifying them still poses great challenges. Labels for these tasks have diverse forms and may be continuous values. Simply quantizing these outputs into discrete variables can lead to a loss of accuracy. Moreover, unlike most tasks that only require a global representation, pixel-labeling tasks focus on local semantic details, necessitating pixel-level outputs that are dependent on feature resolution. However, due to the quadratic increase in sequence length, the traditional model is difficult to scale.

To address these problems, in this paper, we propose UniTask, a novel unified approach for modeling dense prediction tasks using latent discrete tokens. Our model is depicted in Figure 1 and we contribute in three ways:

Figure 1: Overview of the UniTask framework.

- Sequence Learner and Dense Decoder work jointly to achieve discrete representation modeling for dense prediction tasks. Sequence Learner is efficient at predicting discrete vocabulary tokens while Dense Decoder is capable of generating task-specific outputs.

- Our compression and restoration modules enable efficient modeling of feature representations using a small number of latent codes. By restoring in the channel, spatial, and semantic dimensions, we are able to efficiently reconstruct features from discrete codes with minimal information loss. This allows us to model complex pixel-labeling tasks while maintaining high-quality output.

- As a unified approach, UniTask is well suited to multiple tasks, including semantic segmentation, surface normal estimation, and monocular depth estimation. It achieves competitive results with well-established task-specific models.

2 Related Work

2.1 Pixel-labeling Vision Tasks

Pixel-labeling, also called dense prediction, refers to tasks that produce pixel-level outputs for images. These tasks perform pixel-level classification or regression based on the feature map (Wang et al., 2021b). Examples of dense prediction tasks include semantic segmentation (Lin et al., 2014), surface normal estimation (Silberman et al., 2012), and monocular depth estimation (Eigen et al., 2014). Semantic segmentation predicts the semantic class of each pixel, surface normal estimation predicts the surface orientation of each pixel, and monocular depth estimation predicts the distance of each pixel from the camera.

Semantic segmentation is the task of assigning a semantic category to each pixel of an image. The fully convolution network (FCN) (Long et al., 2015) has been the fundamental work in the field of semantic segmentation. Follow up methods use atrous convolution (Chen et al., 2017a;b), pyramid pooling module (Zhao et al., 2017) or CRF/MRF (Liu et al., 2015; Liang-Chieh et al., 2015; Zheng et al., 2015) to help refine the coarse predictions by FCN. Recently, motivated by the success of Transformer architecture (Vaswani et al., 2017), SETR (Zheng et al., 2021), MaX-DeepLab (Wang et al., 2021a), MaskFormer (Cheng et al., 2021) and SegFormer (Xie et al., 2021) have proved the effectiveness of Transformer-based architectures for semantic segmentation.

Surface normal estimation is to extract 3D geometry and surface orientation from a single image. Traditional approaches design networks with high capacity to learn both global and local cues. For example, Deep3D (Wang et al., 2015) proposes a two-stream CNN to fuse coarse scene structure and fine details. SkipNet (Bansal et al., 2016) introduces a skip-network approach to recover fine object details. PAP (Zhang et al., 2019) proposes pattern-affinitive propagation to utilize the matched non-local affinity information. TiltedSN (Do et al., 2020) introduces a spatial rectifier to transform the surface normal distribution and

handle tilted images. Moreover, GeoNet (Qi et al., 2018) enforces depth-normal consistency and incorporates geometric relation based on two-stream CNNs. EAU (Bae et al., 2021) introduces a new parameterization for the surface normal probability distribution to address the aleatoric uncertainty.

Monocular depth estimation requires estimating depth from a single RGB image. Methods based on deep convolutional neural networks have been proposed to achieve good accuracy, including the usage of radar modalities (Lo & Vandewalle, 2021), adopting multi-scale network architecture Laina et al. (2016); Hu et al. (2019); Xu et al. (2021), using geometric constraints (Yin et al., 2021) or guiding by local planar (Lee et al., 2019). Recently, AdaBins (Bhat et al., 2021) leverages a Transformer-based architecture block to perform global processing of the scene's information. Depthformer (Agarwal & Arora, 2022) introduces an encoder-decoder Transformer network to predict multiscale feature maps.

However, each task requires a unique network design, resulting in significant differences among networks for different tasks. In this paper, we aim to unify the networks and expressions of various dense prediction tasks.

2.2 Vision Model Unification

Recently, there has been a significant amount of research in the field of computer vision focused on developing models that can perform a wide range of tasks without the need for task-specific architectures. These unified models are able to achieve good results on a variety of tasks and have attracted significant attention from researchers.

Examples of these unified models include Perceiver (Jaegle et al., 2021b) and Perceiver IO (Jaegle et al., 2021a), which propose general architectures that can handle data from arbitrary settings. OFA (Wang et al., 2022) designs a unified sequence-to-sequence framework for a diverse set of multimodal and uni-modal understanding and generation tasks. Pix2Seq (Chen et al., 2021) proposes a generic framework for object detection using sequences of discrete tokens, and Pix2Seq v2 (Chen et al., 2022) extends this approach to tasks such as segmentation, keypoint estimation, and image captioning. Flamingo (Alayrac et al., 2022) introduces a universal structure that produces natural language outputs for a variety of cross-modal tasks, demonstrating the effectiveness of using a unified architecture for multi-task and multimodal tasks in vision and language.

However, these models typically perform tasks that inherently generate discrete outputs or natural language, while our proposed approach, UniTask, focuses on dense prediction tasks that produce pixel-level predictions. Concurrent to our work, UViM (Kolesnikov et al., 2022) proposes a discrete guiding code for unifying a set of vision tasks like panoptic segmentation, depth prediction, and colorization, and Unified-IO (Lu et al., 2022) homogenizes different forms of input and output for a wide set of tasks into a sequence of discrete vocabulary tokens. These works leverage VQ-GAN (Esser et al., 2021) to encode pixel-level labels as discrete tokens. However, this approach is limited by the structure and conversion precision of VQ-GAN. In this paper, we propose an alternative approach that models discrete representation in the intermediate feature space, allowing us to benefit from arbitrary well-established structures. We also incorporate modules for compressing the sequence to improve the unified efficiency of our approach.

3 UniTask

In this section, we introduce UniTask: a unified approach to model dense prediction tasks by discrete latent variables. It consists of three main parts: (i) a Sequence Learner to generate a unified expression of the input data in an autoregressive manner; (ii) a novel Dense Decoder to construct discrete codes for various dense prediction tasks; (iii) the unified training objective and the approach to obtain task-specific predictions.

3.1 Sequence Generation

The goal of Sequence Learner is to perform various tasks with discrete tokens drawn from a unified and finite vocabulary. As language is inherently discrete, inputs and outputs across a wide number of NLP tasks are represented as a sequence of symbols. Similarly, vision tasks like keypoints detection and object detection

can be represented by a set of discrete points. To benefit from this homogeneous property, we construct Sequence Learner by the language modeling approach to generate discrete tokens for dense prediction tasks.

Sequence Learner is modeled by an encoder-decoder architecture. The decoder is responsible for autoregressive generation while the encoder extracts image representation. The decoder predicts one token at a time, conditioned on the image representation and the preceding sequence. Both modules are composed of stacked Transformer layers (Vaswani et al., 2017), which consist of self-attention, feed-forward neural network, layer norm and residual learning. Specially, a cross-attention module is additionally included in each layer of the decoder to perform a correlation learning between tokens and images.

3.2 Discrete Construction of Dense Predictions in Latent Feature Space

Different from most vision tasks, the dense prediction task which produces diverse forms of pixel-level predictions poses great challenges for unification. For example, the output of semantic segmentation is the predicted category for each pixel while the output of surface normal estimation is the three values for x/y/z orientations. Simply quantizing these outputs into discrete variables will inevitably lead to decline of accuracy and loss of local semantic details. Experimental results of this scheme can be also found in Section 4.2.

Meanwhile, since the autoregressive decoder predicts code by code, the length of predicted sequence will significantly influence the computational costs. For example, considering a 6-layer autoregressive Transformer, predicting a map with 80×80 codes needs to go through 38,400 layers. Due to the quadratically increasing cost in sequence length, the traditional model is hard to be scaled to higher resolutions.

Therefore, to address these problems, we propose Dense Decoder with compression and restoration modules to achieve efficient and high-quality transformation of discrete codes. The model is a combination of two mappings: from the image input to discrete tokens $f : \mathcal{X} \to \mathcal{V}$ and from tokens to restored output $g : \mathcal{V} \to \mathcal{Y}_i$. In general, $\mathcal{X}$, $\mathcal{V}$, $\mathcal{Y}$ represent the image space, discrete space, and output space respectively. The index i represents different forms of outputs in dense prediction tasks. Unlike simple quantization at the output level, we focus on the intermediate feature space in order to confront the accuracy decline under the discretization. Accordingly, the goal of Dense Decoder is to take $\mathbf{x} \in \mathcal{X}$ as the input, model the discrete representation $\mathbf{v} \in \mathcal{V}$, and finally be able to construct the output $\mathbf{y} \in \mathcal{Y}$.

As discussed above, the quantization in $\mathcal{V}$ should be a collection of finite and discrete representations. We raise the idea from vector quantization (VQ), where the representations can be drawn from a learned codebook. To be specific, the vocabulary $\mathcal{V} \in \mathbb{R}^{k \times d}$ is a set of k vectors $v \in \mathcal{V}$ with d dimensions. Note that $\mathcal{V} = \{v_i\}_{i=1}^k$, $v_i \in \mathbb{R}^d$. Then Dense Decoder will learn how to choose codes from the vocabulary to perform a task with pixel-level labels.

The first mapping f consists of a Vision Transformer (Dosovitskiy et al., 2020) backbone, a compression module, and a tokenizer. Given an input image $\mathbf{x} \in \mathbb{R}^{H \times W \times 3}$, the vision transformer first projects the input into vectors and extracts the feature $\mathbf{z} \in \mathbb{R}^{h \times w \times c}$, where $(H/h, W/w)$ is the projected patch size and c is the channel dimension. Then the following compression module reduces the size of the feature map to (h', w') by learnable down-sampling layers. In practice, the total number of features is compressed to a quarter of the original map, indicating that the predictions of corresponding discrete tokens are able to reduce the computational cost to 1/4.

Finally, the tokenizer projects the compressed features into code space $\mathbf{z}' \in \mathbb{R}^{h' \times w' \times d}$ (where the channel dimension d is typically much smaller than c) and obtain the discrete tokens by mapping onto the nearest neighbor in the codebook $\mathcal{V}$:

$$\mathbf{e}_i = v_j, \text{ where } j = \text{argmin}_j \|\mathbf{z}'_i - v_j\|_2. \tag{1}$$

$\mathbf{e} = f(\mathbf{x})$ is exactly the discrete representation we want. It is chosen from the finite discrete space, that is, $j \in \{1, 2, ..., k\}$. On the one hand, it is correspondingly generated from each image input. And on the other hand, it is capable to predict the task-specific output for dense prediction tasks.

Then this transformation from the discrete codes to the task-specific output space is achieved by the second mapping g. The most challenging goal of g is to use compressed tokens to accomplish dense predictions with

high quality. Accordingly, besides task output heads, a restoration module is proposed to combine into this second mapping. The module can be summarized into three parts, channel restoration, spatial restoration, and semantic restoration.

Firstly, the channel restoration is performed by the efficient vision Transformer. It projects the channel dimension of discrete tokens d to that of the latent feature space c. Then, a learnable up-sampling approach as spatial restoration is engaged to construct the original spatial size of feature map. On this basis, the semantic restoration consisting of stacked Transformer layers will be used to obtain $\tilde{\mathbf{z}} \in \mathbb{R}^{h \times w \times c}$, making up for the inconsistency of semantics after the first two restoration. Finally, with this continuous high-dimensional feature, we can use an arbitrary existing task head to acquire the prediction $\mathbf{y}$ for the desired task. The total process of second mapping can be expressed by $\mathbf{y} = g(\mathbf{e})$.

Figure 2: The structure of Dense Decoder. It consists of two mappings. The output of the first mapping and the input of the second mapping are discrete code representations, which are shown in the upper right of the figure. The first mapping consists of a backbone, a compression module, and a tokenizer, while the second mapping consists of three restoration modules and task heads.

3.3 Training Objectives

To obtain a well-trained Dense Decoder, the objectives can be divided into two parts. On the one hand, the learning of discrete code representations is shared by all tasks. And on the other hand, the restoration and prediction of outputs are specific for each task.

When constructing discrete representations, the key is to minimize the conversion loss when mapping the compressed features onto the codebook. Thus a commitment loss is adopted. The objective can be written as:

$$\mathcal{L}_f = \|\mathrm{sg}[\mathbf{z}'] - \mathbf{e}\|_2^2 + \|\mathbf{z}' - \mathrm{sg}[\mathbf{e}]\|_2^2, \tag{2}$$

where $sg[\cdot]$ denotes the stop-gradient operation. The first term optimizes the codebook, moving the embedding vectors toward the output features in code space. Meanwhile, the second term updates the Transformer backbone, compression module, and the projection layer in the first mapping of Dense Decoder, constraining the output to a limited set of discrete space.

Next, the training of Dense Decoder also requires the help of task-specific objectives. They are used to optimize the second mapping which needs to be able to effectively restore the task output and meanwhile help construct the code space to support the task. We employ task-specific models to generate the training labels for the restored features output by restoration modules in the second mapping. Given a well-trained task model T, it generally consists of two parts, a feature extraction backbone T_1 and a task output head T_2. The objective is to minimize the difference between task features $T_1(\mathbf{x})$ and the restored features from discrete codes:

$$\mathcal{L}_t = \|T_1(\mathbf{x}), \hat{\mathbf{z}}\|_2. \tag{3}$$

Here we use the mean squared error to supervise this restoration. Then when the features restored by the Dense Decoder are consistent with the features extracted by T_1, we can directly use T_2 as the task output head in Dense Decoder to obtain the final task predictions.

For Sequence Learner, the goal is to predict the distribution of possible indices for the next code $p(e_i|\mathbf{x}, e_{<i})$ based on the image representation and previous codes $e_{<i}$. Thus the training objective of Sequence Learner is shared among all tasks, which is to maximize the log-likelihood of the predicted representations:

$$\mathcal{L}_e = \sum_i \hat{e}_i \log p(e_i|\mathbf{x}, e_{<i}). \tag{4}$$

$\mathbf{x}$ is the input image and $\hat{e}$ is the one-hot label generated by the code prediction of well-trained Dense Decoder. When the code predicted by Sequence Learner is consistent with that of the first mapping in Dense Decoder, we can then leverage the second mapping to perform the prediction of task output.

Therefore, at the inference stage, generating the dense prediction by a given image therefore involves two modules: Sequence Learner to obtain discrete tokens, and the second mapping in Dense Decoder to predict the task output. The sequence is generated code by code while each is sampling the largest likelihood predicted by Sequence Learner, *i.e.*, $p(e_i|\mathbf{x}, e_{<i})$. Then once the sequence with a certain length is generated, it can be fed into Dense Decoder for restoration and prediction of task-specific outputs.

4 Experiments

We apply UniTask to three pixel-level labeling vision tasks: semantic segmentation, surface normal estimation and monocular depth estimation. We describe the unified settings and select task-specific output head for each task below. Quantitative results are presented in Table 1,2,3 respectively and qualitative results are shown in Figure 4.

4.1 Implementation Details

Sequence Learner Any backbone architecture can be compatible with the encoder. In experiments, we adopt Swin-B (Liu et al., 2021) as the encoder and add a simple feature pyramid module with 3×3 convolution layers to extract multi-scale features. We then construct a 6-layer Transformer (Vaswani et al., 2017) as decoder to predict code in autoregressive way.

Dense Decoder For backbone model, we select Swin-B as well and also use a feature pyramid module to obtain multi-scale features. Then we use a combination of a 3×3 convolution layer with 2 strides and a hyperbolic tangent function to construct the compression module. For all the projection layers, we directly use a 1×1 convolution layer.

In the second mapping, the channel restoration is composed of two 3×3 convolution layers with a tangent function in the middle and a subsequent 3-layer Transformer with 768 hidden size. Then a transposed convolution is adopted as the dimension restoration. Finally, another 3-layer Transformer is employed as the semantic restoration.

4.2 Baseline

We design a baseline model for clearer comparison, which structure is shown in Figure 3. Rather than looking for a latent variable feature space for unification, the baseline model directly quantizes the output space into a finite sequence of discrete codes. For fair comparison, we limit the length of codes for the baseline same as the codes used in UniTask. We first down-sample the ground-truth map and then convert it to discrete codes as new labels.

Notably, the baseline model fails to perform both surface normal and depth estimation tasks, as its result is shown in Table 2 and Table 3. The poor performances are due to the high requirements of details and resolutions on these two tasks. The results demonstrate that the outputs for some pixel-labeling tasks are

Figure 3: The structure of baseline model.

difficult to directly express only by 1/256 discrete codes. UniTask provides an appealing solution with high accuracy based on the same amount of codes.

4.3 Semantic Segmentation

Semantic segmentation requires assigning each pixel of an image a semantic category. Each value of the output is a class index representing the predicted category in that pixel. We follow MaskFormer (Cheng et al., 2021) to construct the task-specific output head. The tokenizer has 1024 dictionary vectors where each has a length of 16.

We train on ADE20k (Zhou et al., 2017) dataset, which is a popular scene parsing benchmark containing dense labels of 150 categories. It includes 20K images in the training set, and 2K images in the validation set. For evaluation, we follow MaskFormer to use the standard metric mIoU (mean Intersection-over-Union) (Everingham et al., 2015). The training crop size is 640×640, while Sequence Learner will predict a length of 20×20 codes to perform the segmentation task. For the baseline, we use the index of the class label which is in discrete form and has a fixed mapping.

Table 1 shows that UniTask achieves 48.5 mIoU on semantic segmentation. It significantly outperforms the baseline and Unified-IO with the same backbone. And compared to the task-specific model, UniTask is only 4.2 points lower than MaskFormer. We analyze that the accuracy gap with the task-specific model comes from the loss of details where we only use very few tokens to express the full image. Nevertheless, Figure 4 demonstrates that our model is capable of producing a segmentation map of similar quality to that of the task-specific model.

4.4 Surface Normal Estimation

Surface normal estimation predicts three values of x/y/z orientations for each pixel. We adopt the decoder of EAU model (Bae et al., 2021) as the task output head. We combine the Swin-B model and the decoder, and then retrain it to obtain the ready task head. The tokenizer has 1024 dictionary vectors where each has a length of 64. For the baseline, since the ground-truth map of x/y/z orientations are normalized and each orientation value is in the range of $[0, 1]$, we divide the value of x and y axes into 32 bins respectively and obtain the value of z axis by the normalization formula. Therefore, the total number of codes required for the surface normal label is 1024.

We evaluate UniTask on NYUv2 (Silberman et al., 2012), which consists of 464 indoor scenes with RGB-D video sequences. As the official training set only contains 795 images, recent methods leverage on additional images to reconstruct the training set (Bansal et al., 2016; Qi et al., 2018; 2020). To ensure a fair comparison, we follow the same training and dataset settings as EAU (Bae et al., 2021). The training crop size is 480×640 and Sequence Learner will predict a length of 30×40 codes.

Table 2 compares the accuracy of UniTask and other related works. Compared to task-specific approaches, our method is only 1.7 rmse higher than EAU. Meanwhile, it outperforms other task-specific models, demonstrating the effectiveness of the proposed unified architecture.

4.5 Monocular Depth Estimation

Monocular Depth Estimation requires estimating the depth map where each value is an arbitrary positive number. We follow AdaBins (Bhat et al., 2021) to construct the task output head. The tokenizer has 1024 dictionary vectors where each has a length of 64. For the baseline, we divide the ground-truth depth map into 256 bins. Each code represents a specific bin that can be transferred to a depth value.

We train on NYU Depth v2 (Silberman et al., 2012), which provides images and depth maps for different indoor scenes. 24,231 image-depth pairs are divided for the training set and the rest 654 pairs are for the test set. The training crop size is 480×640, and the corresponding predicted sequence has a length of 30×40.

Table 3 shows that UniTask achieves 0.414 rmse on depth estimation, outperforming UViM and Unified-IO by significant margins. It is only 0.05 worse than the task-specific model AdaBins and is competitive with other state-of-the-art, demonstrating UniTask contributes an effective unified way for pixel-labeling tasks.

Method	Backbone	Crop Size	mIoU (s.s.) ↑	mIoU (m.s.) ↑
DeepLabV3+	ResNet-101	512×512	45.5	46.4
MaskFormer	ResNet-101	512×512	46.0	48.1
SETR	ViT-L	512×512	-	50.3
Swin-UperNet	Swin-B	640×640	-	51.6
MaskFormer (Cheng et al., 2021)	Swin-B	640×640	52.7	53.9
Dense Decoder (Ours)	Swin-B	640×640	50.5	52.0
Baseline	Swin-B	640×640	41.4	-
Unified-IO[†]	Swin-B	640×640	43.2	-
UniTask (Ours)	Swin-B	640×640	48.7	50.5

Table 1: Comparison of the proposed method and related works for semantic segmentation on ADE20k. The upper part of the table shows task-specific approaches, while the lower part shows unified models which represent the task by unified discrete codes. [†] denotes our reproduction of the method by replacing the backbone to Swin-B for a fair comparison. We report both single-scale (s.s.) and multi-scale (m.s.) for evaluation. Our method outperforms unified models and is competitive with recent task-specific approaches.

Method	mean ↓	median ↓	rmse ↓	11.25° ↑	22.5° ↑	30° ↑
SkipNet (Bansal et al., 2016)	19.8	12.0	28.2	47.9	77.0	77.8
SURGE	20.6	12.2	-	47.3	68.9	76.6
GeoNet (Qi et al., 2018)	19.0	11.8	26.9	48.4	71.5	79.5
PAP (Zhang et al., 2019)	18.6	11.7	25.5	48.8	72.2	79.8
GeoNet++ (Qi et al., 2020)	18.5	11.2	26.7	50.2	73.2	80.7
EAU (Bae et al., 2021)	14.9	7.5	23.5	62.2	79.3	85.2
Dense Decoder (Ours)	16.7	9.4	24.7	55.8	75.7	82.8
Baseline	48.3	47.1	54.5	6.6	19.9	29.4
UniTask (Ours)	17.1	9.8	25.2	54.6	75.0	82.2

Table 2: Accuracy of surface normal estimation on NYUv2. The upper part of the table shows task-specific approaches, while the lower part shows unified models which represent the task by unified discrete codes. The baseline model has poor performance due to the high requirements of details and the constraint of 1/256 codes. Our method achieves state-of-the-art performances under the same setting.

Method	Backbone	$\delta_1 \uparrow$	$\delta_2 \uparrow$	$\delta_3 \uparrow$	REL $\downarrow$	RMS $\downarrow$
RSIDE (Hu et al., 2019)	SENet-154	0.866	0.975	0.993	0.115	0.530
SARBN (Chen et al., 2019)	SENet	0.878	0.977	0.994	0.111	0.514
EGC (Yin et al., 2019)	ResNeXt-101	0.875	0.976	0.994	0.108	0.416
BTS (Lee et al., 2019)	DenseNet-161	0.885	0.978	0.994	0.110	0.392
AdaBins	EfficientNet-B5	0.903	0.984	0.997	0.103	0.364
Dense Decoder (Ours)	Swin-B	0.888	0.985	0.997	0.116	0.386
Baseline	Swin-B	0.365	0.627	0.798	0.374	1.163
Unified-IO	T5-B	-	-	-	-	0.469
UViM	ViT-L	-	-	-	-	0.467
UniTask (Ours)	Swin-B	0.864	0.979	0.995	0.126	0.414

Table 3: Comparison of the proposed method and related works for depth estimation on NYYU-Depth-v2 dataset. The upper part of the table shows task-specific approaches, while the lower part shows unified models which represent the task by unified discrete codes. The baseline model fails again due to the high requirements of details and the constraint of 1/256 codes. Under the same length of codes, our method outperforms Unified-IO and UViM and is competitive with recent task-specific approaches.

5 Key Issues and Discussion

5.1 Influence of Code Length and Codebook Size

We study how the length of discrete code and size of the codebook affect the performance. We vary the two dimensions of vocabulary: the number of vectors k and the dimension d. Nine models are trained with different settings: a cross-product of $k \in \{16, 64, 256\}$ and $d \in \{256, 1024, 4096\}$, to show a clear comparison. Table 4 reports the comparison results of Dense Decoder on semantic segmentation while Table 5 reports the results of UniTask.

		Codebook Size		
		256	1024	4096
Code Length	16	49.1	50.5	51.3
	64	48.3	49.2	49.4
	256	47.1	48.4	48.0

		Codebook Size		
		256	1024	4096
Code Length	16	48.5	48.7	48.5
	64	45.2	47.1	46.7
	256	44.8	46.1	46.5

Table 4: Performances of Dense Decoder under different settings of codebook size and code length on ADE20k (measured as single-scale mIoU).

Table 5: Performances of Sequence Learner under different settings of codebook size and code length on ADE20k (measured as single-scale mIoU).

The experiments are held on ADE20k for semantic segmentation. For Dense Decoder, when the code length is relatively small, *i.e.*, 16 and 64, the accuracy of the model benefits from the increase of codebook size. However, when the code length reaches 256, the use of the tokenizer in Dense Decoder will be saturated quickly, resulting in a decrease of accuracy after 1024 codes. Meanwhile, when the codebook size is fixed, the results show that the accuracy of Dense Decoder benefits from a shorter code length.

For Sequence Learner, it is rather unclear how the accuracy is affected by size of codebook and the length of codes. In general, when the codebook size is fixed, the model is still benefiting from a shorter code length. However, for different code lengths, all optimal sizes of codebooks in Dense Decoder have changed.

| Input Image | Ground Truth | Task-Specific Model | Dense Decoder | UniTask |

Figure 4: Visualizations of our model on three pixel-labeling tasks: semantic segmentation (1st row), monocular depth estimation (2nd row) and surface normal estimation (3rd row). The columns represent the visualization results predicted by different models. Dense Decoder quantizing by discrete codes is able to generate near perfect results. And the UniTask predicting in autoregressive way also achieves very high quality, demonstrating its effectiveness.

We analyze that longer codes and larger codebook will have potentially negative effect on autoregressive-predicted models.

5.2 Utilization rate of Codebook

Next, we further investigate the codebook utilization rate under the variation of code length and codebook size to to explore potential reasons for the performance fluctuations. For the Dense Decoder, we count how many codes in the vocabulary have been used at least once during the inference stage. Intuitively, a short length of code will have limited ability to express semantic information and thus require more vocabulary to achieve the task. Figure 5 reports the utilization rates under the same cross-product of nine settings in Section 5.1.

As expected, with the same size of the codebook, the utilization rate of shorter codes in the codebook is higher than that of longer codes. Meanwhile, for codebooks with the same code length, the number of used codes will increase accordingly with the expansion of the vocabulary size. For example, for a codebook with a code length of 16, when the optional vocabulary is only 256, the number of used codes is 252. However, when the optional vocabulary is increased to 1024, the number of used codes will be increased to 990. This shows that the increase in the optional vocabulary will encourage the model to spread the task semantics to more codes and avoid overloading a few codes. However, for a codebook with

Figure 5: The utilization rate of the codebook in Dense Decoder. The experiments are held on ADE20k for the semantic segmentation task under different settings. The utilization rates are measured on validation set.

a relatively low utilization rate, such as a codebook with a code length of 256 and a size of 1024, increasing its vocabulary size hardly improves the total usage. At this time, a large number of unused codes in the codebook are redundant.

5.3 Computational Cost Evaluation

We evaluate the memory usage, model size, and inference time of four models, including baseline, Unified-IO reproduced by Swin-B, Dense Decoder, and the final UniTask. The result is shown in Table 6. We also take the original Unified-IO with T5-B backbone for comparison. We compute the floating point operations (FLOPs) and report fps (images/s) on the input with 640×640 crop size. The experiments are held on Tesla V100 32G. Since Dense Decoder predicts the whole image in only one forward pass rather than in an autoregressive way, its flops and fps are significantly better than other methods. It is worth noting that despite adopting a task-specific decoder and leveraging on restoration modules in Dense Decoder, UniTask still achieves lower memory usage and similar fps compared to reproduced Unified-IO under the same backbone. It thus shows that the proposed components are not only efficient but also lightweight.

Method	Backbone	flops (G)	params (M)	fps (images/s)
Baseline	Swin-B	1152.07	94.7	0.69
Unified-IO	T5-B	-	241.0	-
Unified-IO[†]	Swin-B	1366.5	135.4	0.28
Dense Decoder*	Swin-B	183.3	126.3	10.48
UniTask	Swin-B	1195.5	137.8	0.28

Table 6: Computational cost evaluation. [†] denotes our reproduction of the method with Swin-B backbone. * denotes that the method does not predict in autoregressive way. Despite adopting a task-specific decoder and leveraging on restoration modules in Dense Decoder, UniTask still achieves lower memory usage and similar fps compared to reproduced Unified-IO under the same backbone.

6 Conclusion

In this paper, we introduce UniTask, a unified approach that achieves state-of-the-art performance in dense prediction tasks. The key idea behind UniTask is to unify the representations of various tasks using discrete codes. It consists of two components: Sequence Learner, which learns to generate predictions in an autoregressive manner, and Dense Decoder, which models diverse inputs and outputs using discrete codes with task semantics. We demonstrate that our model performs effectively on semantic segmentation, surface normal estimation, and monocular depth estimation tasks. In the future, we plan to extend UniTask to support additional tasks and modalities.

References

Ashutosh Agarwal and Chetan Arora. Depthformer: Multiscale vision transformer for monocular depth estimation with local global information fusion. *arXiv preprint arXiv:2207.04535*, 2022.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *arXiv e-prints*, pp. arXiv–2204, 2022.

Gwangbin Bae, Ignas Budvytis, and Roberto Cipolla. Estimating and exploiting the aleatoric uncertainty in surface normal estimation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 13137–13146, 2021.

Aayush Bansal, Bryan Russell, and Abhinav Gupta. Marr revisited: 2d-3d alignment via surface normal prediction. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5965–5974, 2016.

Shariq Farooq Bhat, Ibraheem Alhashim, and Peter Wonka. Adabins: Depth estimation using adaptive bins. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4009–4018, 2021.

Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *IEEE transactions on pattern analysis and machine intelligence*, 40(4):834–848, 2017a.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv preprint arXiv:1706.05587*, 2017b.

Ting Chen, Saurabh Saxena, Lala Li, David J Fleet, and Geoffrey Hinton. Pix2seq: A language modeling framework for object detection. *arXiv preprint arXiv:2109.10852*, 2021.

Ting Chen, Saurabh Saxena, Lala Li, Tsung-Yi Lin, David J Fleet, and Geoffrey Hinton. A unified sequence interface for vision tasks. *arXiv preprint arXiv:2206.07669*, 2022.

Xiaotian Chen, Xuejin Chen, and Zheng-Jun Zha. Structure-aware residual pyramid network for monocular depth estimation. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence*, pp. 694–700, 2019.

Bowen Cheng, Alex Schwing, and Alexander Kirillov. Per-pixel classification is not all you need for semantic segmentation. *Advances in Neural Information Processing Systems*, 34:17864–17875, 2021.

Tien Do, Khiem Vuong, Stergios I Roumeliotis, and Hyun Soo Park. Surface normal estimation of tilted images via spatial rectifier. In *European Conference on Computer Vision*, pp. 265–280. Springer, 2020.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

David Eigen, Christian Puhrsch, and Rob Fergus. Depth map prediction from a single image using a multi-scale deep network. *Advances in neural information processing systems*, 27, 2014.

Patrick Esser, Robin Rombach, and Bjorn Ommer. Taming transformers for high-resolution image synthesis. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 12873–12883, 2021.

Mark Everingham, SM Eslami, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes challenge: A retrospective. *International journal of computer vision*, 111 (1):98–136, 2015.

Junjie Hu, Mete Ozay, Yan Zhang, and Takayuki Okatani. Revisiting single image depth estimation: Toward higher resolution maps with accurate object boundaries. In *2019 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 1043–1051. IEEE, 2019.

Andrew Jaegle, Sebastian Borgeaud, Jean-Baptiste Alayrac, Carl Doersch, Catalin Ionescu, David Ding, Skanda Koppula, Daniel Zoran, Andrew Brock, Evan Shelhamer, et al. Perceiver io: A general architecture for structured inputs & outputs. In *International Conference on Learning Representations*, 2021a.

Andrew Jaegle, Felix Gimeno, Andy Brock, Oriol Vinyals, Andrew Zisserman, and Joao Carreira. Perceiver: General perception with iterative attention. In *International conference on machine learning*, pp. 4651–4664. PMLR, 2021b.

Alexander Kolesnikov, André Susano Pinto, Lucas Beyer, Xiaohua Zhai, Jeremiah Harmsen, and Neil Houlsby. Uvim: A unified modeling approach for vision with learned guiding codes. *arXiv preprint arXiv:2205.10337*, 2022.

Iro Laina, Christian Rupprecht, Vasileios Belagiannis, Federico Tombari, and Nassir Navab. Deeper depth prediction with fully convolutional residual networks. In *2016 Fourth international conference on 3D vision (3DV)*, pp. 239–248. IEEE, 2016.

Jin Han Lee, Myung-Kyu Han, Dong Wook Ko, and Il Hong Suh. From big to small: Multi-scale local planar guidance for monocular depth estimation. *arXiv e-prints*, pp. arXiv–1907, 2019.

Chen Liang-Chieh, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan Yuille. Semantic image segmentation with deep convolutional nets and fully connected crfs. In *International Conference on Learning Representations*, 2015.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10012–10022, 2021.

Ziwei Liu, Xiaoxiao Li, Ping Luo, Chen-Change Loy, and Xiaoou Tang. Semantic image segmentation via deep parsing network. In *Proceedings of the IEEE international conference on computer vision*, pp. 1377–1385, 2015.

Chen-Chou Lo and Patrick Vandewalle. Depth estimation from monocular images and sparse radar using deep ordinal regression network. In *2021 IEEE International Conference on Image Processing (ICIP)*, pp. 3343–3347. IEEE, 2021.

Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3431–3440, 2015.

Jiasen Lu, Christopher Clark, Rowan Zellers, Roozbeh Mottaghi, and Aniruddha Kembhavi. Unified-io: A unified model for vision, language, and multi-modal tasks. *arXiv preprint arXiv:2206.08916*, 2022.

Xiaojuan Qi, Renjie Liao, Zhengzhe Liu, Raquel Urtasun, and Jiaya Jia. Geonet: Geometric neural network for joint depth and surface normal estimation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 283–291, 2018.

Xiaojuan Qi, Zhengzhe Liu, Renjie Liao, Philip HS Torr, Raquel Urtasun, and Jiaya Jia. Geonet++: Iterative geometric neural network with edge-aware refinement for joint depth and surface normal estimation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

Nathan Silberman, Derek Hoiem, Pushmeet Kohli, and Rob Fergus. Indoor segmentation and support inference from rgbd images. In *European conference on computer vision*, pp. 746–760. Springer, 2012.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Huiyu Wang, Yukun Zhu, Hartwig Adam, Alan Yuille, and Liang-Chieh Chen. Max-deeplab: End-to-end panoptic segmentation with mask transformers. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 5463–5474, 2021a.

Peng Wang, An Yang, Rui Men, Junyang Lin, Shuai Bai, Zhikang Li, Jianxin Ma, Chang Zhou, Jingren Zhou, and Hongxia Yang. Ofa: Unifying architectures, tasks, and modalities through a simple sequence-to-sequence learning framework. In *International Conference on Machine Learning*, pp. 23318–23340. PMLR, 2022.

Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 568–578, 2021b.

Xiaolong Wang, David Fouhey, and Abhinav Gupta. Designing deep networks for surface normal estimation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 539–547, 2015.

Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M Alvarez, and Ping Luo. Segformer: Simple and efficient design for semantic segmentation with transformers. *Advances in Neural Information Processing Systems*, 34:12077–12090, 2021.

Xianfa Xu, Zhe Chen, and Fuliang Yin. Multi-scale spatial attention-guided monocular depth estimation with semantic enhancement. *IEEE Transactions on Image Processing*, 30:8811–8822, 2021.

Wei Yin, Yifan Liu, Chunhua Shen, and Youliang Yan. Enforcing geometric constraints of virtual normal for depth prediction. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5684–5693, 2019.

Wei Yin, Yifan Liu, and Chunhua Shen. Virtual normal: Enforcing geometric constraints for accurate and robust depth prediction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Zhenyu Zhang, Zhen Cui, Chunyan Xu, Yan Yan, Nicu Sebe, and Jian Yang. Pattern-affinitive propagation across depth, surface normal and semantic segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4106–4115, 2019.

Hengshuang Zhao, Jianping Shi, Xiaojuan Qi, Xiaogang Wang, and Jiaya Jia. Pyramid scene parsing network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2881–2890, 2017.

Shuai Zheng, Sadeep Jayasumana, Bernardino Romera-Paredes, Vibhav Vineet, Zhizhong Su, Dalong Du, Chang Huang, and Philip HS Torr. Conditional random fields as recurrent neural networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 1529–1537, 2015.

Sixiao Zheng, Jiachen Lu, Hengshuang Zhao, Xiatian Zhu, Zekun Luo, Yabiao Wang, Yanwei Fu, Jianfeng Feng, Tao Xiang, Philip HS Torr, et al. Rethinking semantic segmentation from a sequence-to-sequence perspective with transformers. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 6881–6890, 2021.

Bolei Zhou, Hang Zhao, Xavier Puig, Sanja Fidler, Adela Barriuso, and Antonio Torralba. Scene parsing through ade20k dataset. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 633–641, 2017.

A Appendix

We provide detailed settings of training hyperparameters of three pixel-labeling tasks: semantic segementation (Table 7), surface normal estimation (Table 8) and monocular depth estimation (Table 9).

A.1 Hyperparameters for Semantic Segmentation Training

Hyperparameters	Values
Autoregressive Layers	6
Restored Channel	256
Hidden Size	512
FFN Hidden Size	2048
Attention Heads	8
Dropout	0.1
Pre-Norm	✓
Patch Size	16×16
Codebook Size	1024×16
Input Size	640×640
Batch size	16
Adam	✓
Peak Learning Rate	0.00006
Minimal Learning Rate	1e-6
Warmup Epochs	1500
Gradient clipping	$\times$
Weight decay	0.01
Random Flip	✓
Random Crop	✓

Table 7: Hyperparameters for Semantic Segmentation on ADE20k.

Hyperparameters	Values
Autoregressive Layers	6
Restored Channel	256
Hidden Size	512
FFN Hidden Size	2048
Attention Heads	8
Dropout	0.1
Pre-Norm	✓
Patch Size	8×8
Codebook Size	1024×64
Input Size	480×640
Batch size	16
Adam	✓
Learning Rate	0.00036
Gradient clipping	0.1
Weight decay	0.01
Random Flip	✓
Color Augmentation	✓
Random Crop	✓

Table 8: Hyperparameters for Surface Normal Estimation on NYUv2.

Hyperparameters	Values
Autoregressive Layers	6
Restored Channel	256
Hidden Size	512
FFN Hidden Size	2048
Attention Heads	8
Dropout	0.1
Pre-Norm	✓
Patch Size	8×8
Codebook Size	1024×64
Input Size	480×640
Batch size	16
Adam	✓
Learning Rate	0.0006
Gradient clipping	$\times$
Weight decay	0.01
Random Flip	✓
Random Rotation	✓
Random Crop	✓

Table 9: Hyperparameters for Monucular Depth Estimation on NYU Depth v2.