Anonymized Histograms
in Intermediate Privacy Models

Abstract

We study the problem of privately computing the *anonymized histogram* (a.k.a. *unattributed histogram*), which is defined as the histogram without item labels. Previous works have provided algorithms with ℓ_1 and ℓ_2^2-errors of $O_\varepsilon(\sqrt{n})$ in the central model of differential privacy (DP).

In this work, we provide an algorithm with a nearly matching error guarantee of $\tilde{O}_\varepsilon(\sqrt{n})$ in the shuffle DP and pan-private models. Our algorithm is very simple: it just post-processes the discrete Laplace-noised histogram! Using this algorithm as a subroutine, we show applications in privately estimating symmetric properties of distributions such as entropy.

1 Introduction

Computing histograms is among the most well-studied tasks in data analytics and machine learning. Suppose that there is a domain $[D] := \{1, \ldots, D\}$, where the ith user's input is $z_i \in [D]$. The histogram of the users' inputs $\{z_1, \ldots, z_n\}$ is defined as $\mathbf{h} := (h_1, \ldots, h_D)$ where $h_j := |\{i \in [n] \mid z_i = j\}|$, i.e., the number of users who contribute item $j \in [D]$. For many tasks, however, the different items themselves are not important and it instead suffices to consider the *anonymized histogram* (a.k.a. *unattributed histogram*) corresponding to $\mathbf{h}$, which is defined as $\mathbf{n_h} := (n^{(1)}, \ldots, n^{(D)})$ where $n^{(\ell)}$ denotes the ℓth largest element among the h_j's. Whenever $\mathbf{h}$ is clear from context, we will skip the subscript and denote the anonymized histogram as simply $\mathbf{n}$.

Anonymized histograms have several applications including estimating symmetric properties of discrete distributions [10, 2, 15, 30], privately releasing the degree-distributions in social networks [33, 32, 38], and anonymizing password frequency lists [12, 13]. For more details, we refer the reader to [41] and the references therein.

In this work, we study private anonymized histograms. The notion of privacy we study is differential privacy (DP) [23, 22] which has emerged as a very popular notion of private data analysis leading to numerous practical deployments [26, 40, 29, 7, 20, 1, 35, 39].

Multiple works have studied the problem of computing private anonymized histogram, with the focus so far being on the central model of DP.[1] Moreover, two measures of error have been studied: ℓ_1-error[2] and ℓ_2^2-error[3]. For the ℓ_2^2-error, Hay et al. [33] give an ε-DP algorithm with a bound of

---

[1]Recall that in the central model of DP, a trusted curator has access to the raw inputs of the users, and is supposed to output a DP estimate of the desired function, in this case, the anonymized histogram.

[2]Defined as $\|\mathbf{n} - \hat{\mathbf{n}}\|_1 = \sum_{r \in [D]} |n^{(j)} - \hat{n}^{(j)}|$ where $\hat{\mathbf{n}}$ denotes the output anonymized histogram.

[3]Defined as $\|\mathbf{n} - \hat{\mathbf{n}}\|_2^2 = \sum_{r \in [D]} (n^{(j)} - \hat{n}^{(j)})^2$.

$\tilde{O}(\sqrt{n}/\varepsilon^2)$ on the expected error[4]. As for the ℓ_1-error, Blocki et al. [12] observed that the exponential mechanism yields an expected ℓ_1-error of $O(\sqrt{n}/\varepsilon)$ since there are at most $\exp(O(\sqrt{n}))$ anonymized histograms in total [31]; recently, this bound was improved to $O(\sqrt{n \log(1/\varepsilon)}/\varepsilon)$ by Suresh [41]. On the lower bound front, Alda and Simon [5] proved a lower bound of $\Omega(\sqrt{n}/\varepsilon)$ for the expected ℓ_1-error; recently, this was improved to $\Omega(\sqrt{n \log(1/\varepsilon)/\varepsilon})$ by Manurangsi [36], matching the aforementioned upper bound of [41] to within a constant factor. The latter lower bound also applies to (ε, δ)-DP algorithms for any sufficiently small δ (depending only on ε).

The anonymized histogram problem generalizes the COUNT-DISTINCT problem, which asks for the number of items j such that $h_j > 0$. COUNT-DISTINCT can be easily solved in the central DP model by applying the discrete Laplace mechanism. In the (non-interactive) local DP setting, Chen et al. [16] proved a lower bound of $\Omega_\varepsilon(n)$, which means that one cannot asymptotically beat the trivial algorithm that always outputs zero. The strong lower bounds on the error incurred by protocols in the local setting generally motivate the study of intermediate models of privacy including the pan-private [24] and shuffle DP [11, 25, 17] models. In these models, it turns out that COUNT-DISTINCT can be solved to within $\tilde{O}_\varepsilon(\sqrt{n})$-error, and lower bounds of $\Omega_\varepsilon(\sqrt{n})$ are known [37, 8].

In this work, we show that, surprisingly, the anonymized histogram problem (which seems much harder than COUNT-DISTINCT) can in fact be solved with essentially the same asymptotic error of $O_\varepsilon(\sqrt{n})$ as COUNT-DISTINCT, in both the pan-private and shuffle DP models. On the other hand, the aforementioned lower bound from [16] for COUNT-DISTINCT also implies $\Omega_\varepsilon(n)$ lower bound for the expected ℓ_1-error of anonymized histogram in the more challenging local DP model. In other words, in the typical case where ε is an absolute constant, it is impossible to achieve any asymptotic advantage over the trivial algorithm that always outputs the all-zeros histogram.

1.1 Our Results

A prominent approach for computing private histograms in the central DP model is to add discrete[5] Laplace noise to each histogram entry. We show that there is a post-processing algorithm that takes such a noised histogram and produces an accurate estimate of the anonymized histogram:

Theorem 1 (Informal version of Theorem 9). *There is an algorithm that takes in a noisy histogram, where an independent discrete Laplace noise of parameter $1/\varepsilon$ is added to each entry, and outputs an approximate anonymized histogram such that the expected ℓ_1 and ℓ_2^2-errors are[6] $\tilde{O}_\varepsilon(\sqrt{n + D})$.*

Note that there is a dependency of $\sqrt{D}$ in the error bound in Theorem 1. When the domain size is large, this can dominate the $\sqrt{n}$ term. Fortunately, we show that this can be overcome by first randomly hashing into B buckets before computing the histogram. By picking B to be $O(n)$, we show that one can achieve an error that is $\tilde{O}_\varepsilon(\sqrt{n})$ *without* any dependency on D:

Theorem 2 (Informal version of Corollary 13). *There is an algorithm that takes in a noisy hashed histogram, where an independent discrete Laplace noise of parameter $1/\varepsilon$ is added to each bucket after hashing, and outputs an approximate anonymized histogram such that the expected ℓ_1 and ℓ_2^2-errors are $\tilde{O}_\varepsilon(\sqrt{n})$.*

Random hashing and computing discrete Laplace-noised histograms can be implemented in the pan-private[7] and shuffle DP settings [28, 9], where in the latter case we have to concede $\delta > 0$ in the privacy parameter. Thus, the theorem above yields:

Corollary 3. *For any $\varepsilon > 0, \delta \in (0, 1]$, there is an ε-DP algorithm for anonymized histogram in the pan-private model and an (ε, δ)-DP algorithm in the shuffle DP model, with expected ℓ_1 and ℓ_2^2-errors of $\tilde{O}_\varepsilon(\sqrt{n})$.*

---

[4]In fact, Hay et al. [33] proved a slightly stronger expected error bound of $O(d \log^3 n/\varepsilon^2)$ where d denote the number of unique values appearing in $\mathbf{n}$. Since there are at most $\sqrt{n}$ different values in the worst case, this guarantee yields $O(\sqrt{n} \log^3 n/\varepsilon^2)$ bound for any instance.

[5]Our results can be adapted to continuous Laplace noise [23] with only a constant factor overhead in the error. We use discrete noise since it can be applied in the shuffle DP model (which is discrete in nature).

[6]$\tilde{O}(f)$ denotes $O(f \log^c f)$ for some constant $c > 0$ and $O_\varepsilon(f)$ denotes $O(g(\varepsilon)f)$ for some function $g(\cdot)$.

[7]This is done by starting with D i.i.d. discrete Laplace r.v.'s and incrementing each entry for the next item.

As an immediate application of the above, we get algorithms for estimating symmetric properties of distributions; a distribution property is said to be symmetric if it remains unchanged under relabeling of the domain symbols. For any (non-private) symmetric estimator with low sensitivity, we get a private estimator in the pan-private and shuffle DP models.

Theorem 4 (Informal version of Theorem 17). *For all $\varepsilon > 0, \delta \in (0, 1]$, and distributions $\mathcal{D}$, for any symmetric distribution property f, and any symmetric estimator $\hat{f}$, there exists an ε-DP mechanism $\mathcal{M}$ in the pan-private model and an (ε, δ)-DP mechanism $\mathcal{M}$ in the shuffle DP model, such that $\mathcal{M}$ outputs an α-approximation to $f(\mathcal{D})$ with high probability, and the sample complexity of the mechanism is given as $C_{\hat{f}}(f, \alpha) + D_{\hat{f}}(\alpha, \varepsilon)$, where the first term is the non-private sample complexity of $\hat{f}$ and the second term depends on the sensitivity of $\hat{f}$.*

In particular, in Section 5, we apply the above result to estimate the Shannon entropy of discrete distributions, which to the best of our knowledge, is the first such sample complexity bound in the pan-private and shuffle DP models.

1.2 Overview of Techniques

We now describe the high-level ideas of our algorithms and proofs. For ease of exposition, will be intentionally informal; all details are formalized in later sections. To describe our algorithm, we need definitions of prevalence and cumulative prevalence.

Definition 5 (Prevalence and Cumulative Prevalence). The *prevalence* of a histogram $\mathbf{h}$ is defined as $\boldsymbol{\varphi}^{\mathbf{h}} := (\varphi_0^{\mathbf{h}}, \ldots, \varphi_n^{\mathbf{h}})$ where $\varphi_r^{\mathbf{h}} := |\{j \in [D] : h_j = r\}|$ is the number of entries with value r. The *cumulative prevalence* of a histogram $\mathbf{h}$ is defined as $\boldsymbol{\varphi}_{\geq}^{\mathbf{h}} := (\varphi_{\geq 1}^{\mathbf{h}}, \ldots, \varphi_{\geq n}^{\mathbf{h}})$ where $\varphi_{\geq r}^{\mathbf{h}} := |\{j \in [D] : h_j \geq r\}|$ is the number of entries with value at least r.

Prevalence and cumulative prevalence can be similarly defined for an anonymized histogram $\mathbf{n}$; note that $\boldsymbol{\varphi}^{\mathbf{h}} = \boldsymbol{\varphi}^{\mathbf{n_h}}$ and $\boldsymbol{\varphi}_{\geq}^{\mathbf{h}} = \boldsymbol{\varphi}_{\geq}^{\mathbf{n_h}}$. An important property of cumulative prevalence is that the ℓ_1-distance is preserved.

Observation 6. For all anonymized histograms $\mathbf{n}, \hat{\mathbf{n}}$, it holds that $\|\boldsymbol{\varphi}_{\geq}^{\mathbf{n}} - \boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}}\|_1 = \|\mathbf{n} - \hat{\mathbf{n}}\|_1$.

We stress that, while cumulative prevalence has been used before in DP algorithms for computing anonymized histograms [41, 36], these algorithms require access to the true anonymized histogram first and therefore will only work in the central DP model.

Algorithm for ℓ_1-error. For each $j \in [D]$, using the discrete Laplace-noised count, we produce an unbiased estimate for whether $h_j \geq r$ for each $r \in [n]$. Adding these up over all $j \in [D]$ gives an unbiased estimate for $\varphi_{\geq r}^{\mathbf{h}}$. We then "project" the estimated $\boldsymbol{\varphi}_{\geq}$ back so that it corresponds to a valid anonymized histogram. It can be seen that this last step can only double the error at most.

While the algorithm described above is simple, it is unclear why it incurs an error of $\tilde{O}_{\varepsilon}(\sqrt{n + D})$. The analysis turns out to be subtle and delicate. The key is that the unbiased estimator we use has variance that decreases exponentially with $|h_j - r|$. (In other words, the uncertainty is only when h_j is close to r.) Roughly speaking, this means that the total error is dominated by the error in the case where $h_j = r$. Suppose for simplicity that we only focus on this case, since there are $\varphi_r^{\mathbf{h}}$ entries satisfying the condition, the expected ℓ_1-error for $\boldsymbol{\varphi}_{\geq r}$ will be $\tilde{O}_{\varepsilon}(\sqrt{\varphi_r^{\mathbf{h}}})$. Thus, in total, the ℓ_1-error of the estimated cumulative prevalence is dominated by $\tilde{O}_{\varepsilon}(\sum_{r \in [n]} \sqrt{\varphi_r^{\mathbf{h}}})$. We can now apply the Cauchy–Schwarz inequality to yield $\sum_{r \in [n]} \sqrt{\varphi_r^{\mathbf{h}}} \leq \sqrt{\sum_{r \in [n]} 1/r} \sqrt{\sum_{r \in [n]} r \cdot \varphi_r^{\mathbf{h}}} = \Theta(\sqrt{n \log n})$, where the last equality follows from the fact that $\sum_{r \in [n]} r \cdot \varphi_r^{\mathbf{h}}$ is simply the total counts in the histogram. See Section 3 for details.

Handling Large Domain Sizes. When $D \gg n$, we randomly hash into $B = \tilde{O}(n)$ buckets and compute the noisy "reduced" histogram on these B buckets. We can use our approach above to compute the anonymized histogram on these B buckets with ℓ_1-error at most $\tilde{O}_{\varepsilon}(\sqrt{n})$. While this is a reasonable approach, it does not yet give a good estimate for the original anonymized histogram: the reason is that there could be as many as $\tilde{\Omega}(n)$ collisions due to hashing. To handle this, we define a function that "inverts" the reduced anonymized histogram to the original anonymized histogram.

We then show that (i) this inverse has "sensitivity" $O(1)$ and (ii) the reduced histogram is concentrated around its mean with an ℓ_1-deviation of $\tilde{O}(\sqrt{n})$. Combining these two allows us to conclude that the inverse of the noisy anonymized histogram has expected ℓ_1-error of $\tilde{O}_\varepsilon(\sqrt{n})$ as desired. See Section 4 for details.

Algorithm for ℓ_2^2-error. Adapting the algorithm for ℓ_2^2-error proceeds as follows: recall (e.g., by Hölder's inequality) that $\|\mathbf{n} - \hat{\mathbf{n}}\|_2^2 \leq \|\mathbf{n} - \hat{\mathbf{n}}\|_1 \cdot \|\mathbf{n} - \hat{\mathbf{n}}\|_\infty$. Notice also that the concentration of the noise implies that each discrete Laplace-noised count is within $O(\log D/\varepsilon)$ of the true value. Due to this, we may only change the last (i.e., "projection") step with an extra constraint that each entry of the output estimated anonymized histogram is within $O(\log D/\varepsilon)$ of the corresponding entry of the noisy histogram. This way we have ensured that $\|\mathbf{n} - \hat{\mathbf{n}}\|_\infty \leq O(\log D/\varepsilon)$. Combining this with our earlier bound on the expected ℓ_1-error then immediately yields the desired bound on the ℓ_2^2-error. See Appendix B for details.

Privately Computing Symmetric Properties of Distributions. A large body of work starting with [2] have shown that plug-in estimators using the so-called profile maximum likelihood (PML) distribution achieve nearly optimal sample complexity for many symmetric distribution properties. At the core of these works is an important fact that many symmetric distribution properties have estimators (based on the anonymized histogram) with low sensitivity. Our algorithms then apply these estimators on our private anonymized histogram. The sensitivity of the estimator, together with the ℓ_1-error bound we have shown for our anonymized histogram, immediately yield bounds on the errors of the estimators. See Section 5 for details.

1.3 Other Related Work

The original paper on the pan-private model [24] also studies the problem of estimating $\varphi_r^{\mathbf{n}}$. However, their focus is on algorithms with small space complexity, and, if one were to sum up their error bounds for all r directly, it would yield a trivial bound for the error on the anonymized histogram.

Several recent works have studied the testing/estimation/learning of symmetric and other properties of distributions under privacy constraints mostly in the central DP model [3, 4, 6, 14, 19, 34] and some in the local DP model [21]. In particular, Acharya et al. [3] study privately computing symmetric distribution properties in the central model. Indeed, they also exploit the fact that the estimators have low sensitivity. However, in the central DP case, low sensitivity allows one to get a private estimate by adding Laplace noise directly to the non-private estimate, whereas we need to compute the estimator from our approximate anonymized histogram.

2 Differential Privacy

In this section, we review the basics of differential privacy (DP) and the shuffle DP and the pan-private models. Let $[n]$ denote the set $\{1, \ldots, n\}$ and let $\mathbf{1}[\cdot]$ denote the binary indicator function.

Two datasets $S = \{z_1, \ldots, z_n\}$ and $S' = \{z_1', \ldots, z_n'\}$ are said to be *neighboring*, denoted $S \sim S'$, if there is an index $i \in [n]$ such that $z_j = z_j'$ if and only if $j \in [n] \setminus \{i\}$. We recall the following definition [23, 22]:

Definition 7 (Differential Privacy (DP)). Let $\varepsilon > 0$ and $\delta \in [0, 1]$. A randomized algorithm $\mathcal{M} : \mathcal{Z}^n \to \mathcal{R}$ is (ε, δ)-*differentially private* ((ε, δ)-*DP*) if, for all $S \sim S'$ and all (measurable) outcomes $E \subseteq \mathcal{R}$, we have that $\Pr[\mathcal{M}(S) \in E] \leq e^\varepsilon \cdot \Pr[\mathcal{M}(S') \in E] + \delta$.

We denote $(\varepsilon, 0)$-DP as ε-DP or *pure*-DP. The case when $\delta > 0$ is referred to as *approximate*-DP.

In the *central DP* model, all the inputs are stored and processed by an analyzer and the privacy is enforced only on the output of the analyzer.

Shuffle DP [11, 25, 17]. In the *shuffle DP* model, there are three algorithms, namely, a local randomizer $\mathcal{R}$, a shuffler $\mathcal{S}$, and an analyzer $\mathcal{A}$. Let $S = \{z_1, \ldots, z_n\}$ be the input dataset. The randomizer $\mathcal{R}$ takes a $z \in S$ and outputs a set of messages. The shuffler $\mathcal{S}$ takes the multiset of messages obtained from $\mathcal{R}$ applied to each $z \in S$ and permutes them randomly. The analyzer $\mathcal{A}$ takes this permuted multiset and computes the final output. The privacy in the shuffle model is enforced on the output of the shuffler $\mathcal{S}$, when a single input is changed.

Pan-privacy [24]. In the pan-private model, there is an algorithm that takes in a data stream of unbounded length consisting of elements in the domain. It is required that the internal state of the algorithm after any number steps satisfies ε-DP over the data stream prefix until that step.

Histograms in Central DP. For a distribution D, let $x \sim D$ denote that the random variable x is chosen from D. For $p \in (0, 1)$, the *discrete Laplace distribution* (aka symmetric geometric distribution), denoted by $\mathrm{DLap}(p)$, is the distribution supported on $\mathbb{Z}$ whose probability mass at $i \in \mathbb{Z}$ is $\frac{1-p}{1+p} \cdot p^{|i|}$.

We use the following well-known fact about central DP and histograms.

Fact 8. *The algorithm that adds $\mathrm{DLap}(e^{-\varepsilon/2})$ noise to each entry of a histogram is ε-DP in the central model.*

We refer to the output of this algorithm as the *discrete Laplace-noised* histogram.

For a histogram $\mathbf{h}$, we use $\mathbf{n_h}$ to denote the anonymized histogram corresponding to $\mathbf{h}$, often dropping the subscript whenever $\mathbf{h}$ is clear from context.

3 Post-Processing Noised Histogram

In this section we describe our main algorithm, which obtains an anonymized histogram by suitably post-processing a noised histogram. We first define the following function $f : \mathbb{Z} \to \mathbb{R}$, which is used in our post-processing method described in Algorithm 1.

$$f(m) = \begin{cases} 1 & \text{if } m > 0, \\ 1 + \frac{p}{(1-p)^2} & \text{if } m = 0, \\ -\frac{p}{(1-p)^2} & \text{if } m = -1, \\ 0 & \text{if } m < -1. \end{cases} \tag{1}$$

Algorithm 1 Anonymized Histogram Estimator w.r.t. ℓ_1 loss.

Input: Discrete Laplace-noised histogram $\mathbf{h}'$, i.e., $h'_j \sim h_j + \mathrm{DLap}(p)$

for $r \in [n]$ **do**
    $\hat{\varphi}_{\geq r} \leftarrow \sum_{j \in [D]} f(h'_j - r)$, where f is defined in (1)
return $\hat{\mathbf{n}}$ that minimizes $\|\boldsymbol{\varphi}^{\hat{\mathbf{n}}}_{\geq} - \hat{\boldsymbol{\varphi}}_{\geq}\|_1$

We now state the main guarantee of the post-processing method.

Theorem 9. *For all histograms $\mathbf{h}$, the estimate $\hat{\mathbf{n}}$ returned by Algorithm 1 satisfies*

$$\mathbb{E}[\|\hat{\mathbf{n}} - \mathbf{n}\|_1] \leq O\left(\sqrt{C_p(n + D) \log n}\right),$$

where $C_p := \frac{p^2}{(1-p)^5} + \frac{p}{1-p}$.

From Fact 8, for ε-DP, we may set $p = e^{-\varepsilon/2}$. Theorem 9 then gives a bound of $O(\sqrt{(n + D) \log n}/\varepsilon^{2.5})$.

The crucial result needed in our analysis is the guarantee of the individual estimator f. We show that $f(h'_j - r)$ is an unbiased estimator of $\mathbf{1}[h_j \geq r]$ and furthermore its variance decreases (exponentially) as $|h_j - r|$ increases.

Lemma 10. *For all $h, r \in \mathbb{N} \cup \{0\}$, if $h' \sim h + \mathrm{DLap}(p)$, then it holds that*

$$\mathbb{E}[f(h' - r)] = \mathbf{1}[h \geq r], \quad and \tag{2}$$

$$\mathrm{Var}[f(h' - r)] \leq 4p^{|h-r|+1}\left(\frac{p}{(1-p)^3} + (1-p)\right). \tag{3}$$

Proof. Let $\tau := h - r, \tau' := h' - r$ and $x := p/(1 - p)^2$. Consider $g : \mathbb{Z} \to \mathbb{R}$ defined by $g(m) := f(m) - 1/2$. Notice that (2) is equivalent to $\mathbb{E}[g(\tau')] = \mathbf{1}[\tau \geq 0] - 1/2$. Due to symmetry, it suffices to consider the case where $\tau \geq 0$. In this case, we have

$$\mathbb{E}[g(\tau')] = \mathbb{E}_{Z \sim \mathrm{DLap}(p)}[g(\tau + Z)] = \Pr[Z > -\tau] \cdot (1/2) + \Pr[Z \leq -\tau] \cdot \mathbb{E}[g(\tau + Z) \mid Z \leq -\tau].$$

The last term can be expanded as follows:

$$\begin{aligned}
&\mathbb{E}[g(\tau + Z) \mid Z \leq -\tau] \\
&= (1/2 + x) \cdot \Pr[Z = -\tau \mid Z \leq -\tau] - (1/2 + x) \cdot \Pr[Z = -\tau - 1 \mid Z \leq -\tau] \\
&\quad - (1/2) \cdot \Pr[Z < -\tau - 1 \mid Z \leq -\tau] \\
&= (1/2 + x) \cdot (1 - p) - (1/2 + x) \cdot p(1 - p) - (1/2) \cdot p^2 = 1/2.
\end{aligned}$$

Combining the two equations above, we arrive at $\mathbb{E}[g(\tau')] = \Pr[Z > -\tau] \cdot (1/2) + \Pr[Z \leq -\tau] \cdot (1/2) = 1/2$, thereby proving (2).

To prove (3), notice again that $\mathrm{Var}[f(\tau')] = \mathrm{Var}[g(\tau')]$. Again, due to symmetry, we may only consider the case $\tau \geq 0$. Here, we have

$$\begin{aligned}
\mathrm{Var}[g(\tau')] &= \mathbb{E}_{Z \sim \mathrm{DLap}(p)}[(g(\tau + Z) - 1/2)^2] \\
&= \Pr[Z \leq -\tau] \cdot \mathbb{E}[(g(\tau + Z) - 1/2)^2 \mid Z \leq -\tau] \\
&\leq p^\tau \cdot \mathbb{E}[(g(\tau + Z) - 1/2)^2 \mid Z \leq -\tau]
\end{aligned}$$

Similar to before, we can expand the last term as

$$\begin{aligned}
&\mathbb{E}[(g(\tau + Z) - 1/2)^2 \mid Z \leq -\tau] \\
&= x^2 \cdot \Pr[Z = -\tau \mid Z \leq -\tau] + (1 + x)^2 \cdot \Pr[Z = -\tau - 1 \mid Z \leq -\tau] \\
&\quad + 1 \cdot \Pr[Z < -\tau - 1 \mid Z \leq -\tau] \\
&= x^2 \cdot (1 - p) + (1 + x)^2 \cdot p(1 - p) + p^2 \\
&\leq p^2/(1 - p)^3 + 2(1 + x^2) \cdot p(1 - p) + p^2 \\
&\leq 4p^2/(1 - p)^3 + 2p(1 - p).
\end{aligned}$$

Plugging this into the above, we get $\mathrm{Var}[g(\tau')] \leq 4p^{\tau+1}(p/(1 - p)^3 + (1 - p))$ as desired. $\qquad\square$

The following is an immediate consequence of Lemma 10, by summing over all $j \in [D]$.

Observation 11. For all $r \in [n]$, and $\kappa := 4p\left(\frac{p}{(1-p)^3} + (1 - p)\right)$ it holds that

$$\mathbb{E}[\hat{\varphi}_{\geq r}] = \varphi_{\geq r}^{\mathbf{n}} \quad \text{and} \quad \mathrm{Var}[\hat{\varphi}_{\geq r}] \leq \sum_{\ell=0}^{n} \kappa \cdot p^{|\ell - r|} \cdot \varphi_\ell^{\mathbf{n}}.$$

Proof of Theorem 9. The error is bounded as

$$\begin{aligned}
\|\hat{\mathbf{n}} - \mathbf{n}\|_1 &= \|\varphi_{\geq}^{\hat{\mathbf{n}}} - \varphi_{\geq}^{\mathbf{n}}\|_1 \leq \|\varphi_{\geq}^{\hat{\mathbf{n}}} - \hat{\varphi}_{\geq}\|_1 + \|\hat{\varphi}_{\geq} - \varphi_{\geq}^{\mathbf{n}}\|_1 \leq 2 \cdot \|\varphi_{\geq}^{\hat{\mathbf{n}}} - \hat{\varphi}_{\geq}\|_1 \\
\implies \|\hat{\mathbf{n}} - \mathbf{n}\|_1 &\leq 2 \cdot \sum_{r \in [n]} |\varphi_{\geq r}^{\hat{\mathbf{n}}} - \hat{\varphi}_{\geq r}|
\end{aligned} \tag{4}$$

where we use that $\|\varphi_{\geq}^{\hat{\mathbf{n}}} - \hat{\varphi}_{\geq}\|_1 \leq \|\hat{\varphi}_{\geq} - \varphi_{\geq}^{\mathbf{n}}\|_1$ by choice of $\hat{\mathbf{n}}$. From Observation 11, we have

$$\mathbb{E}\left[|\varphi_{\geq r}^{\hat{\mathbf{n}}} - \hat{\varphi}_{\geq r}|\right] \leq \sqrt{\mathrm{Var}[\hat{\varphi}_{\geq r}]} \leq \sqrt{\kappa} \cdot \sqrt{\sum_{\ell=0}^{n} p^{|\ell - r|} \cdot \varphi_\ell^{\mathbf{n}}}.$$

Combining this with (4), we have

$$\begin{aligned}
\mathbb{E}[\|\hat{\mathbf{n}} - \mathbf{n}\|_1] &\leq 2 \cdot \sum_{r \in [n]} \mathbb{E}\left[|\varphi_{\geq r}^{\hat{\mathbf{n}}} - \hat{\varphi}_{\geq r}|\right] \\
&\leq 2\sqrt{\kappa} \cdot \left(\sum_{r \in [n]} \sqrt{\sum_{\ell=0}^{n} p^{|\ell - r|} \cdot \varphi_\ell^{\mathbf{n}}}\right) \\
&\leq 2\sqrt{\kappa} \cdot \sqrt{\sum_{r \in [n]} \frac{1}{r}} \cdot \sqrt{\sum_{r \in [n]} r \cdot \left(\sum_{\ell=0}^{n} p^{|\ell - r|} \cdot \varphi_\ell^{\mathbf{n}}\right)} \quad \text{(Cauchy–Schwarz)} \\
&\leq 2\sqrt{\kappa} \cdot O(\sqrt{\log n}) \cdot \sqrt{\sum_{\ell=0}^{n} \varphi_\ell^{\mathbf{n}} \cdot \left(\sum_{r \in [n]} r \cdot p^{|\ell - r|}\right)}
\end{aligned}$$

$$
\begin{aligned}
&\leq\ 2\sqrt{\kappa}\cdot O(\sqrt{\log n})\cdot\sqrt{\textstyle\sum_{\ell=0}^{n}\varphi_\ell^{\mathbf{n}}\cdot 2(\ell+1)\cdot(\sum_{t=0}^{\infty}(t+1)\cdot p^t)}\\
&=\ 2\sqrt{\kappa}\cdot O(\sqrt{\log n})\cdot\sqrt{\textstyle\sum_{\ell=0}^{n}\varphi_\ell^{\mathbf{n}}\cdot 2(\ell+1)\cdot(1/(1-p)^2)}\\
&=\ 2\sqrt{\kappa/(1-p)^2}\cdot O(\sqrt{\log n})\cdot\sqrt{(\textstyle\sum_{\ell=0}^{n}\ell\cdot\varphi_\ell^{\mathbf{n}})+(\sum_{\ell=0}^{n}\varphi_\ell^{\mathbf{n}})}\\
&=\ 2\sqrt{\kappa/(1-p)^2}\cdot O(\sqrt{\log n})\cdot\sqrt{n+D}. \qquad\qquad\qquad\qquad\qquad \square
\end{aligned}
$$

4 Reducing Domain Size via Hashing

In this section we propose an algorithm to handle the case where $D \gg n$. The approach in this case is to hash the domain into something smaller. Let $B \in \mathbb{N}$ be the number of hash values. The distribution of the anonymized histogram produced after random hashing into B buckets is equivalent to the following process:

▶ Let $\mathbf{n} = (n^{(1)}, \dots, n^{(D)})$ be the starting anonymized histogram.

▶ Pick a random hash function $H : [D] \to [B]$.

▶ Let $\mathbf{h}^{\mathrm{red}} := (h_1^{\mathrm{red}}, \dots, h_B^{\mathrm{red}})$ denote the reduced histogram given by $h_i^{\mathrm{red}} = \sum_{j \in H^{-1}(i)} n^{(j)}$.

▶ Let $\mathbf{n}^{\mathrm{red}}$ denote the corresponding anonymized histogram.

Let Γ^B be the mapping from $\mathbf{n}$ to $\mathbb{E}[\varphi_\geq^{\mathbf{n}^{\mathrm{red}}}]$ where $\mathbf{n}^{\mathrm{red}}$ is generated as above, and the expectation is over the choice of random hash functions H. With this notation, we present Algorithm 2.

Algorithm 2 Anonymized Histogram Estimator w.r.t. ℓ_1 loss, for large domains.

> **Input:** Discrete Laplace-noised histogram $\tilde{\mathbf{h}}^{\mathrm{red}}$, i.e., $\tilde{h}_j^{\mathrm{red}} \sim h_j^{\mathrm{red}} + \mathrm{DLap}(p)$
>
> Compute an estimate $\hat{\mathbf{n}}^{\mathrm{red}}$ of $\mathbf{n}^{\mathrm{red}}$ using Algorithm 1
> **return** $\hat{\mathbf{n}}$ that minimizes $\|\Gamma^B(\hat{\mathbf{n}}) - \varphi_\geq^{\hat{\mathbf{n}}^{\mathrm{red}}}\|_1$, subject to $\|\hat{\mathbf{n}}\|_1 = n$

The main result of this section is the following:

Theorem 12. *For all $B > 5n$ and histograms $\mathbf{h}$, the estimate $\hat{\mathbf{n}}$ returned by Algorithm 2 satisfies*

$$
\begin{aligned}
\mathbb{E}[\|\hat{\mathbf{n}} - \mathbf{n}\|_1] &\leq\ O(\mathbb{E}[\|\hat{\mathbf{n}}^{\mathrm{red}} - \mathbf{n}^{\mathrm{red}}\|_1] + \sqrt{n^2/B}\cdot\log n)\\
&\leq\ O\left(\sqrt{C_p(n+B)\log n} + \sqrt{n^2/B}\log n\right).\qquad \textit{(using Theorem 9)}
\end{aligned}
$$

By setting $B = n\sqrt{\log n}$, we get the following corollary.[8]

Corollary 13. *For all $\varepsilon > 0$, Algorithm 2 for $p = e^{-\varepsilon/2}$ and $B = n\sqrt{\log n}$ is an ε-DP algorithm, and achieves an expected ℓ_1-error of $E(n, \varepsilon) = O(\sqrt{n}(\log n)^{3/4}/\varepsilon^{2.5})$.*

We describe the main steps in the proof of Theorem 12.

Lipschitzness of Inverse of Γ^B. We start by showing that the "inverse" of Γ^B is $O(1)$-Lipschitz:

Lemma 14 (Proof in Appendix A.1). *For $B > 5n$ and all anonymized histograms $\mathbf{n}, \mathbf{n}'$ with $\|\mathbf{n}\|_1 = \|\mathbf{n}'\|_1 = n$,*

$$
\|\Gamma^B(\mathbf{n}) - \Gamma^B(\mathbf{n}')\|_1 \geq \|\mathbf{n} - \mathbf{n}'\|_1/5.
$$

Concentration of $\mathbf{n}^{\mathrm{red}}$. We now bound the expected ℓ_1-distance between $\varphi_\geq^{\hat{\mathbf{n}}^{\mathrm{red}}}$ and its expectation $\Gamma^B(\mathbf{n})$.

Lemma 15. *Assume that $B \geq 2n$. Then, $\mathbb{E}[\|\varphi_\geq^{\hat{\mathbf{n}}^{\mathrm{red}}} - \Gamma^B(\mathbf{n})\|_1] \leq O(\sqrt{n^2/B}\cdot\log n)$.*

---

[8]By choosing $B = n\sqrt{\varepsilon^{2.5}\log n}$, the bound in Corollary 13 could be improved to $O(\sqrt{n}((\log n)^{3/4}/\varepsilon^{1.25} + (\log n)^{1/2}/\varepsilon^{2.5}))$; we state the simpler bound for brevity.

 Proof. We have

$$
\begin{aligned}
\mathbb{E}[\|\boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}^{\mathrm{red}}} - \Gamma^B(\mathbf{n})\|_1] &= \sum_{r \in [n]} \mathbb{E}[|\varphi_{\geq r}^{\hat{\mathbf{n}}^{\mathrm{red}}} - \Gamma^B(\mathbf{n})_r|] \\
&= \sum_{r \in [n]} \mathbb{E}[|\varphi_{\geq r}^{\hat{\mathbf{n}}^{\mathrm{red}}} - \mathbb{E}[\varphi_{\geq r}^{\hat{\mathbf{n}}^{\mathrm{red}}}]|] \\
&\leq \sum_{r \in [n]} \sqrt{\mathrm{Var}[\varphi_{\geq r}^{\hat{\mathbf{n}}^{\mathrm{red}}}]}. \qquad\qquad (5)
\end{aligned}
$$

We next use the following bound on the variance.

Lemma 16 (Proof in Appendix A.2)**.** *For all* $r \in [n]$, $\mathrm{Var}[\varphi_{\geq r}^{\hat{\mathbf{n}}^{\mathrm{red}}}] \leq \frac{16n}{B} \cdot \left(\frac{n}{r^2} + \sum_{t \in [r-1]} \frac{t \cdot \varphi_t^{\mathbf{n}}}{r(r-t)} \right).$

Plugging Lemma 16 into (5), we have

$$
\begin{aligned}
\mathbb{E}[\|\boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}^{\mathrm{red}}} - \Gamma^B(\mathbf{n})\|_1] &\leq O\left(\sqrt{n/B}\right) \cdot \sum_{r \in [n]} \sqrt{\frac{n}{r^2} + \sum_{t \in [r-1]} \frac{t \cdot \varphi_t^{\mathbf{n}}}{r(r-t)}} \\
\text{(Cauchy–Schwarz)} \quad &\leq O\left(\sqrt{n/B}\right) \cdot \sqrt{\sum_{r \in [n]} \frac{1}{r}} \sqrt{\sum_{r \in [n]} r \cdot \left(\frac{n}{r^2} + \sum_{t \in [r-1]} \frac{t \cdot \varphi_t^{\mathbf{n}}}{r(r-t)} \right)} \\
&= O\left(\sqrt{n \log(n)/B}\right) \sqrt{\sum_{r \in [n]} \left(\frac{n}{r} + \sum_{t \in [r-1]} \frac{t \cdot \varphi_t^{\mathbf{n}}}{r-t} \right)} \\
&= O\left(\sqrt{n \log(n)/B}\right) \sqrt{O(n \log n) + \sum_{t \in [n-1]} \sum_{\ell \in [n-t]} \frac{t \cdot \varphi_t^{\mathbf{n}}}{\ell}} \\
&\leq O\left(\sqrt{n \log(n)/B}\right) \sqrt{O(n \log n) + O(\log n) \cdot \sum_{t \in [n-1]} t \cdot \varphi_t^{\mathbf{n}}} \\
&= O\left(\sqrt{n \log(n)/B}\right) \sqrt{O(n \log n)} \\
&= O(\sqrt{n^2/B} \cdot \log n). \qquad\qquad \square
\end{aligned}
$$

Putting things together. With all the components ready, we can now prove Theorem 12.

Proof of Theorem 12. By Lemma 14, we have

$$
\begin{aligned}
\mathbb{E}[\|\mathbf{n} - \hat{\mathbf{n}}\|_1] &\leq 5 \cdot \mathbb{E}[\|\Gamma^B(\mathbf{n}) - \Gamma^B(\hat{\mathbf{n}})\|_1] \\
&\leq 5 \cdot \left(\mathbb{E}[\|\Gamma^B(\mathbf{n}) - \boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}^{\mathrm{red}}}\|_1 + \|\boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}^{\mathrm{red}}} - \Gamma^B(\hat{\mathbf{n}})\|_1] \right) \\
&\leq 10 \cdot \left(\mathbb{E}[\|\Gamma^B(\mathbf{n}) - \boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}^{\mathrm{red}}}\|_1] \right) \qquad\qquad \text{(By definition of } \hat{\mathbf{n}}) \\
&\leq 10 \cdot \left(\mathbb{E}[\|\boldsymbol{\varphi}_{\geq}^{\mathbf{n}^{\mathrm{red}}} - \boldsymbol{\varphi}_{\geq}^{\hat{\mathbf{n}}^{\mathrm{red}}}\|_1 + \|\Gamma^B(\mathbf{n}) - \boldsymbol{\varphi}_{\geq}^{\mathbf{n}^{\mathrm{red}}}\|_1] \right) \\
&= O(\|\mathbf{n}^{\mathrm{red}} - \hat{\mathbf{n}}^{\mathrm{red}}\|_1) + O(\|\Gamma^B(\mathbf{n}) - \boldsymbol{\varphi}_{\geq}^{\mathbf{n}^{\mathrm{red}}}\|_1) \\
&\leq O(\|\mathbf{n}^{\mathrm{red}} - \hat{\mathbf{n}}^{\mathrm{red}}\|_1 + \sqrt{n^2/B} \cdot \log n) \qquad \text{(From Lemma 15).} \qquad \square
\end{aligned}
$$

5 Estimating Symmetric Properties of Discrete Distributions

In this section we show how to use Theorem 12 for the task of estimating symmetric properties of discrete distributions over $[k]$. Here, a distribution property is *symmetric* if it remains unchanged under relabeling of the domain symbols. For example, a notable such property is the Shannon entropy of a distribution $\mathcal{D}$ defined as $H(\mathcal{D}) := \sum_x \mathcal{D}(x) \log \frac{1}{\mathcal{D}(x)}$, a central object in information theory, machine learning, and statistics. If the support is unbounded, estimating $H(\mathcal{D})$ is impossible with any finite number of samples. Our goal is to estimate the entropy of a distribution $\mathcal{D} \in \Delta_k$ up to an additive $\pm\alpha$ error, where Δ_k denotes the set of all distributions over $[k]$.

One of the key ideas in the literature (e.g., [3]) is to design *low sensitivity* estimators $\hat{f} : \mathcal{X}^n \to \mathbb{R}$ for the desired symmetric distribution property $f : \Delta_k \to \mathbb{R}$. The (non-private) *sample complexity* of a property $f : \Delta_k \to \mathbb{R}$, denoted by $C_{\hat{f}}(f, \alpha)$, is the smallest number of samples n needed to

estimate $f(\mathcal{D})$ upto accuracy α with probability at least $2/3$, that is, $\Pr[|\hat{f}(S) - f(\mathcal{D})| > \alpha] < 1/3$.[9]
The *sensitivity* of an estimator $\hat{f}$ is $\Delta_{n,\hat{f}}$, which is the smallest value for which it holds for adjacent datasets $S \sim S'$ each with n elements, that $|\hat{f}(S) - \hat{f}(S')| \le \Delta_{n,\hat{f}}$. Let $D_{\hat{f}}(\alpha, \varepsilon) := \min\{n : \Delta_{n,\hat{f}} \le 0.1\alpha/E(n,\varepsilon)\}$, for $E(n,\varepsilon)$ defined in Corollary 13.

We will only consider *symmetric* estimators $\hat{f}$, for which we will abuse notation to use $\hat{f}(\mathbf{n})$ to denote $\hat{f}(S)$ for any dataset S that corresponds to the anonymized histogram $\mathbf{n}$.

Theorem 17. *For all $\varepsilon > 0, \delta \in (0,1]$, for any symmetric distribution property f, and any symmetric estimator $\hat{f}$, there exists an ε-DP mechanism in the pan-private model and (ε,δ)-DP mechanism in the shuffle DP model, such that* $\Pr_{S \sim \mathcal{D}^n}[|\mathcal{M}(S) - f(\mathcal{D})| > \alpha] < 0.44$ *with sample complexity*

$$O\left(C_{\hat{f}}\left(f, \frac{\alpha}{2}\right) + D_{\hat{f}}\left(\frac{\alpha}{2}, \varepsilon\right)\right).$$

Proof. Let $\mathbf{n}$ denote the anonymized histogram corresponding to the sampled dataset S. The mechanism $\mathcal{M}$ simply outputs $\hat{f}(\hat{\mathbf{n}})$ for $\hat{\mathbf{n}}$ returned by Algorithm 2. Clearly the mechanism $\mathcal{M}$ is DP due to the post-processing property.

We have that for a suitable $n = O\left(C_{\hat{f}}\left(f, \frac{\alpha}{2}\right) + D_{\hat{f}}\left(\frac{\alpha}{2}, \varepsilon\right)\right)$, it holds that

$$\Pr\left[\left|\hat{f}(\mathbf{n}) - f(\mathcal{D})\right| > \frac{\alpha}{2}\right] \le 1/3 \quad\text{and}\quad \Pr\left[\left|\hat{f}(\hat{\mathbf{n}}) - \hat{f}(\mathbf{n})\right| > \frac{\alpha}{2}\right] \le 0.1,$$

where, the first inequality holds by definition of $C(f, \alpha/2)$, and the second inequality holds because $|\hat{f}(\hat{\mathbf{n}}) - \hat{f}(\mathbf{n})| \le \Delta_{n,\hat{f}} \cdot \|\hat{\mathbf{n}} - \mathbf{n}\|_1$ and by the guarantee of Theorem 12 and Markov's inequality $\Pr[\|\hat{\mathbf{n}} - \mathbf{n}\|_1 > 10E(n,\varepsilon)] \le 0.1$. By a union bound, we have $\Pr[|\hat{f}(\hat{\mathbf{n}}) - \hat{f}(\mathbf{n})| > \alpha] \le 0.44$. $\quad\square$

We get the following sample complexity bounds for private estimation of Shannon entropy in the pan-private and shuffle DP models, as an immediate application of Theorem 17.

Corollary 18 (Proof in Appendix C). *For all $\varepsilon > 0, \delta \in (0,1]$, there exists an ε-DP mechanism in the pan-private model and (ε,δ)-DP mechanism in the shuffle DP model, that can estimate the entropy of $\mathcal{D} \in \Delta_k$ up to an additive error of $\pm\alpha$ with a sample complexity of*

$$\min_{\lambda \in (0,1)} \left\{ O\left(\frac{k}{\alpha} + \frac{\log^2 k}{\alpha^2} + \frac{\log^4(1/(\alpha^2 \varepsilon^5))}{\alpha^2 \varepsilon^5}\right), \quad O\left(\frac{k}{\lambda^2 \alpha \log k} + \frac{\log^2 k}{\alpha^2} + \left(\frac{\log^2(1/(\alpha^2 \varepsilon^5))}{\alpha^2 \varepsilon^5}\right)^{1+2\lambda}\right) \right\}.$$

These bounds have the same dependence on k as in the work of Acharya et al. [3]. The dependence on α and ε is slightly worse due to a higher cost of sensitivity in our setting, and the worse dependence on ε in our guarantees in Corollary 13. The detailed proof is presented in Appendix C.

6 Conclusions and Future Directions

In this paper we give simple algorithms for privately computing anonymized histograms. Our algorithms can be implemented in the shuffle and pan-private models.

There are several immediate open questions: our upper bounds have a dependency of $O(1/\varepsilon^{2.5})$ in the ℓ_1-error case and $O(1/\varepsilon^{3.5})$ in the ℓ_2^2-error case; it is unclear if these are tight. Similarly, there is a lower order multiplicative term of $O(\log n)$ and $O(\log^2 n)$ in our ℓ_1 and ℓ_2^2-error bounds respectively. Closing these gaps would be an interesting next step; these would also lead to improvements to the sample complexity bounds on private estimation of symmetric distribution properties, such as the Shannon entropy (Corollary 18).

Note also that our shuffle DP algorithm has $\delta > 0$, i.e., approximate-DP. This may not be necessary: there are a couple of recent algorithms for computing histogram with shuffle DP with $\delta = 0$ [27, 18]. Our post-processing approach does not immediately apply to these algorithms because the noise to each count is not a discrete Laplace noise (and in fact is not even an independent additive noise). Adapting our approach to their setting is another interesting research direction.

---

[9]The choice of $1/3$ is arbitrary; using the "median trick", we can boost the success probability to $1 - \beta$ with an additional multiplicative $\log(1/\beta)$ more samples.

References

[1] J. M. Abowd. The US Census Bureau adopts differential privacy. In *KDD*, pages 2867–2867, 2018.

[2] J. Acharya, H. Das, A. Orlitsky, and A. T. Suresh. A unified maximum likelihood approach for estimating symmetric properties of discrete distributions. In *ICML*, pages 11–21, 2017.

[3] J. Acharya, G. Kamath, Z. Sun, and H. Zhang. INSPECTRE: privately estimating the unseen. *J. Priv. Confidentiality*, 10(2), 2020.

[4] J. Acharya, Z. Sun, and H. Zhang. Differentially private testing of identity and closeness of discrete distributions. In *NeurIPS*, pages 6879–6891, 2018.

[5] F. Aldà and H. U. Simon. A lower bound on the release of differentially private integer partitions. *IPL*, 129:1–4, 2018.

[6] M. Aliakbarpour, I. Diakonikolas, and R. Rubinfeld. Differentially private identity and equivalence testing of discrete distributions. In *ICML*, pages 169–178, 2018.

[7] Apple Differential Privacy Team. Learning with privacy at scale. *Apple Machine Learning Journal*, 2017.

[8] V. Balcer, A. Cheu, M. Joseph, and J. Mao. Connecting robust shuffle privacy and pan-privacy. In *SODA*, pages 2384–2403, 2021.

[9] B. Balle, J. Bell, A. Gascón, and K. Nissim. Private summation in the multi-message shuffle model. In *CCS*, pages 657–676, 2020.

[10] T. Batu, L. Fortnow, R. Rubinfeld, W. D. Smith, and P. White. Testing that distributions are close. In *FOCS*, pages 259–269, 2000.

[11] A. Bittau, Ú. Erlingsson, P. Maniatis, I. Mironov, A. Raghunathan, D. Lie, M. Rudominer, U. Kode, J. Tinnés, and B. Seefeld. Prochlo: Strong privacy for analytics in the crowd. In *SOSP*, pages 441–459, 2017.

[12] J. Blocki, A. Datta, and J. Bonneau. Differentially private password frequency lists. In *NDSS*, 2016.

[13] J. Bonneau. The science of guessing: analyzing an anonymized corpus of 70 million passwords. In *S & P*, pages 538–552, 2012.

[14] B. Cai, C. Daskalakis, and G. Kamath. Priv'it: Private and sample efficient identity testing. In *ICML*, pages 635–644, 2017.

[15] M. Charikar, K. Shiragur, and A. Sidford. Efficient profile maximum likelihood for universal symmetric property estimation. In *STOC*, pages 780–791, 2019.

[16] L. Chen, B. Ghazi, R. Kumar, and P. Manurangsi. On distributed differential privacy and counting distinct elements. In *ITCS*, pages 56:1–56:18, 2021.

[17] A. Cheu, A. D. Smith, J. R. Ullman, D. Zeber, and M. Zhilyaev. Distributed differential privacy via shuffling. In *EUROCRYPT*, pages 375–403, 2019.

[18] A. Cheu and C. Yan. Pure differential privacy from secure intermediaries. *CoRR*, abs/2112.10032, 2021.

[19] I. Diakonikolas, M. Hardt, and L. Schmidt. Differentially private learning of structured discrete distributions. In *NIPS*, pages 2566–2574, 2015.

[20] B. Ding, J. Kulkarni, and S. Yekhanin. Collecting telemetry data privately. In *NeurIPS*, pages 3571–3580, 2017.

[21] J. C. Duchi, M. I. Jordan, and M. J. Wainwright. Minimax optimal procedures for locally private estimation. *JASA*, 2017.

[22] C. Dwork, K. Kenthapadi, F. McSherry, I. Mironov, and M. Naor. Our data, ourselves: Privacy via distributed noise generation. In *EUROCRYPT*, pages 486–503, 2006.

[23] C. Dwork, F. McSherry, K. Nissim, and A. D. Smith. Calibrating noise to sensitivity in private data analysis. In *TCC*, pages 265–284, 2006.

[24] C. Dwork, M. Naor, T. Pitassi, G. N. Rothblum, and S. Yekhanin. Pan-private streaming algorithms. In *ICS*, pages 66–80, 2010.

[25] Ú. Erlingsson, V. Feldman, I. Mironov, A. Raghunathan, K. Talwar, and A. Thakurta. Amplification by shuffling: From local to central differential privacy via anonymity. In *SODA*, pages 2468–2479, 2019.

[26] Ú. Erlingsson, V. Pihur, and A. Korolova. RAPPOR: Randomized aggregatable privacy-preserving ordinal response. In *CCS*, pages 1054–1067, 2014.

[27] B. Ghazi, N. Golowich, R. Kumar, P. Manurangsi, R. Pagh, and A. Velingker. Pure differentially private summation from anonymous messages. In *ITC*, pages 15:1–15:23, 2020.

[28] B. Ghazi, R. Kumar, P. Manurangsi, and R. Pagh. Private counting from anonymous messages: Near-optimal accuracy with vanishing communication overhead. In *ICML*, pages 3505–3514, 2020.

[29] A. Greenberg. Apple's "differential privacy" is about collecting your data – but not your data. *Wired, June*, 13, 2016.

[30] Y. Hao and A. Orlitsky. The broad optimality of profile maximum likelihood. In *NeurIPS*, pages 10989–11001, 2019.

[31] G. H. Hardy and S. Ramanujan. Asymptotic Formulaæ in Combinatory Analysis. *Proc. London Math. Soc.*, s2-17(1):75–115, 01 1918.

[32] M. Hay, C. Li, G. Miklau, and D. D. Jensen. Accurate estimation of the degree distribution of private networks. In *ICDM*, pages 169–178, 2009.

[33] M. Hay, V. Rastogi, G. Miklau, and D. Suciu. Boosting the accuracy of differentially private histograms through consistency. *VLDB*, 3(1):1021–1032, 2010.

[34] V. Karwa and S. Vadhan. Finite sample differentially private confidence intervals. In *ITCS*, 2018.

[35] K. Kenthapadi and T. T. L. Tran. Pripearl: A framework for privacy-preserving analytics and reporting at linkedin. In *CIKM*, pages 2183–2191, 2018.

[36] P. Manurangsi. Tight bounds for differentially private anonymized histograms. In *SOSA*, pages 203–213, 2022.

[37] D. J. Mir, S. Muthukrishnan, A. Nikolov, and R. N. Wright. Pan-private algorithms via statistics on sketches. In *PODS*, pages 37–48, 2011.

[38] S. Raskhodnikova and A. Smith. Efficient lipschitz extensions for high-dimensional graph statistics and node private degree distributions. *FOCS*, 2016.

[39] R. Rogers, S. Subramaniam, S. Peng, D. Durfee, S. Lee, S. K. Kancha, S. Sahay, and P. Ahammad. Linkedin's audience engagements API: A privacy preserving data analytics system at scale. *J. Priv. Confiden.*, 11(3), 2021.

[40] S. Shankland. How Google tricks itself to protect Chrome user privacy. *CNET, October*, 2014.

[41] A. T. Suresh. Differentially private anonymized histograms. In *NeurIPS*, pages 7969–7979, 2019.