Relation-Constrained Decoding for Text Generation

Abstract

The dominant paradigm for neural text generation nowadays is seq2seq learning with large-scale pretrained language models. However, it is usually difficult to manually constrain the generation process of these models. Prior studies have introduced *Lexically Constrained Decoding (LCD)* to ensure the presence of pre-specified words or phrases in the output. However, simply applying lexical constraints has no guarantee of the grammatical or semantic relations between words. Thus, more elaborate constraints are needed. To this end, we first propose a new constrained decoding scenario named *Relation-Constrained Decoding (RCD)*, which requires the model's output to contain several given word pairs with respect to the given relations between them. For this scenario, we present a novel plug-and-play decoding algorithm named **RE**lation-guided probability **S**urgery and b**E**am **AL**location (RESEAL), which can handle different categories of relations, e.g., syntactical relations or factual relations. Moreover, RESEAL can adaptively "reseal" the relations to form a high-quality sentence, which can be applied to the inference stage of any autoregressive text generation model. To evaluate our method, we first construct an RCD benchmark based on dependency relations from treebanks with annotated dependencies. Experimental results demonstrate that our approach can achieve better preservation of the input dependency relations compared to previous methods. To further illustrate the effectiveness of RESEAL, we apply our method to three downstream tasks: sentence summarization, data-to-text generation, and fact-based text editing. We observe an improvement in generation quality[1].

1   Introduction

Incorporating complex manual constraints into neural text generation is a challenging research topic. One of the most important manual constraints is the *relation constraint*, i.e. to guarantee that two pre-specified words must appear in the generated text and keep the given relation between them. Such relation constraints have various applications. For instance, data-to-text generation [9, 17] and fact-based text editing [14] aim to ensure the presence of given facts (entities and relations between them) in the output. Moreover, in sentence summarization task [31], there are some key semantic relations that must be preserved to ensure the fluency and factual constituency of the summaries.

The most prominent paradigm for text generation is seq2seq learning by finetuning the large-scale pretrained models [18, 29] and obtaining the outputs by beam search in an autoregressive manner. However, this paradigm often fails to satisfy the complex constraints because the objective of beam search process is the log-likelihood of candidate sentences, not the number of constraints they have met. In other words, there is no explicit mechanism to enforce these constraints. To tackle this problem, previous works [12, 13, 26] propose *Lexically Constrained Decoding (LCD)* to specify some keywords that should be contained in the output. However, simply utilizing these lexical constraints

---

[1]We will release the source code upon acceptance.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: The framework of our proposed RESEAL. During decoding, RESEAL will relatively maintain or reduce the probability of those candidate words that meet the relation constraints in an adaptive way. The relation identifier aims to identify the existence of each relation. Note that "amod" denotes adjectival modifier and "nsubj" denotes nominal subject.

still struggles to ensure the word relation constraints. Therefore, we need to explore another form of constrained decoding to handle the relations between words.

In this paper, we propose a new constrained decoding scenario named *Relation-Constrained Decoding (RCD)*. Specifically, we adopt the triplets (*head, relation, tail*) as the *relation constraints*. At the decoding stage, we aim to force the model output to include these relation constraints. The right side of Figure 1 shows two instances for RCD with different relation types. In an evident way, satisfying relation constraints requires satisfying corresponding lexical constraints. A straightforward solution to this problem is to generate a set of candidate sentences using any LCD algorithm to ensure the keyword preservation, and then rerank them by the number of relation constraints they have met. However, this approach requires to first generate a number of whole sentences, which is inefficient and inflexible. To this end, we propose RESEAL (**RE**lation-guided probability **S**urgery and b**E**am **AL**location), a relation-guided decoding algorithm for RCD that can dynamically adjust the choice of words during decoding. As illustrated in Figure 1, RESEAL modifies the standard beam search process and incorporates an external relation identifier to help the model to identify the presence of relation constraints. Based on the relation identifier, RESEAL dynamically adjusts the probability of the candidate constrained words in the generation process. Thereafter, we further extend the dynamic beam allocation (DBA) algorithm [26] to satisfy the relation constraints.

Among all categories of word relations, the dependency relation is most basic, standard and representative which has various public available datasets for evaluation. Therefore, in this paper, we mainly focus on the dependency relation scenario of RCD. To illustrate the effectiveness of our proposed RESEAL, we construct a benchmark from publicly available treebanks [34] that contain sentences and their dependency trees annotated by human. We randomly sample a subset of dependency triplets as the input constraints and regard the original sentences as reference outputs. We call this task "Dependency Placement". Experiment results show that our method outperforms baselines and LCD methods on dependency coverage (the ratio of satisfied relation constraints for dependency). After that, to showcase the applicability of this work, we further explore some potential applications of RCD. We conduct extensive experiments on three downstream tasks: sentence summarization (with dependency relations), fact-based text editing (with relations between two entities in the knowledge graph), and data-to-text generation (with relations extracted from knowledge bases). Across different tasks, we observe a consistent improvement over the strong baselines.

To sum up, the contributions of our work are three-fold: (i) We propose Relation-Constrained Decoding (RCD), a scenario for constrained text generation, and construct its benchmarks. To the best of our knowledge, we are the first to study this problem. (ii) We design RESEAL, a decoding algorithm that can generate high-quality sentences that meet relation constraints. (iii) The experimental results on the RCD task and downstream tasks including sentence summarization, fact-based text editing and data-to-text generation show the effectiveness of RESEAL.

2 Problem Formulation

In this section, we first formulate the Relation-Constrained Decoding (RCD) problem. For the text generation tasks, given an input sequence $X = (x_1, x_2, ..., x_N)$, where N is the input sequence length, $x_i \in \mathcal{V}_\mathcal{S}$ and $\mathcal{V}_\mathcal{S}$ is the source vocabulary, the model generates a sequence $Y = (y_1, y_2, ..., y_M)$, where M is the output sequence length, $y_i \in \mathcal{V}_\mathcal{T}$ and $\mathcal{V}_\mathcal{T}$ is the target vocabulary. The conditional probability of Y given X and model parameter θ can be calculated as follows:

$$p(Y|X;\theta) = \prod_{t=1}^{M} p(y_t|y_{<t}, X; \theta). \tag{1}$$

Eq. 1 usually acts as an objective for beam search. In this paper, we denote each relation constraint as a triplet (h, r, τ), where h is the *head*, τ is the *tail*, and r is the relation between them. Given an unordered relation constraints set $C = \{(h_l, r_l, \tau_l)\}_{l=1}^{L}$, where L is the number of constraints and $h_l, \tau_l \in \mathcal{V}_\mathcal{T}$, we aim to make the output Y satisfy the constraints in C as much as possible. For the model's output Y, we denote $C'(Y) = \{(h'_l, r'_l, \tau'_l)\}_{l=1}^{M}$ be the relation triplets of Y, and then we propose to jointly optimize Eq. 1 and $|C \cap C'(Y)|$ as a novel objective for RCD.

3 Methodology

RESEAL aims to enforce the relation constraints during standard beam search. Algorithm 1 gives an overview of RESEAL. To start the decoding, the decoder input is initialized with a single $\langle \texttt{BOS} \rangle$ token. At each time step t, the model maintains the k-best candidate sentences, where k is the beam size. The decoder produces the distribution $p_{\text{vocab}}(w|y_{<t}, X; \theta)$ for each token w in the target vocabulary $\mathcal{V}_\mathcal{T}$ (line 3). Each candidate has different p_{vocab} respectively to produce $k|\mathcal{V}_\mathcal{T}|$ candidates, then we can select top k candidates from them by the cumulative log probability (line 5). The decoding ends when candidates contain k finished sentences.(line 6-7). Different from standard beam search, RESEAL follows a two-step approach as follows:

Algorithm 1 RESEAL (overview)

Input: Max sequence length N, beam size k, relation constraints C, relation identifier R, enc_inputs.
Output: Output sequence.
1: Initialize k candidates and dec_inputs
2: **for** time step t **in** $[1, N]$ **do**
3:    $p_{\text{vocab}} \leftarrow \text{MODEL}(\text{enc\_inputs}, \text{dec\_inputs})$
4:    $\tilde{p} \leftarrow \text{PROB\_SURGERY}(p_{\text{vocab}}, \text{candidates}, C, R)$
5:    candidates $\leftarrow \text{RG\_TOPK}(\tilde{p}, \text{candidates}, C)$
6:    **if** have finished k sentences **then**
7:       **break**
8: **return** candidate with highest score

Step 1: Probability Surgery (line 4) RESEAL operates the produced probability distributions according to the result of a *relation identifier*, which serves as an explicit signal to guarantee the presence of relation constraints.

Step 2: Relation-Guided Top-K (line 5) To satisfy lexical constraints, we replace the standard Top-K operation by the one used in DBA [26]. Furthermore, to satisfy relation constraints, RESEAL dynamically allocates beam by the results of *relation identifier* instead of the number of satisfied constraints used in DBA.

If removing line 4 and replacing line 5 with a normal Top-K, RESEAL is equivalent to the beam search. We will describe the aforementioned two steps in detail in the rest of this section.

3.1 Probability Surgery

Algorithm 2 (line 1-7) shows the process of probability surgery. At time step t during decoding, the model predicts the next token probability $p_{\text{vocab}}(w|y_{<t}, X; \theta)$. In the scenario of RCD, when predicting next token w, we need to consider whether w is a head or tail in a relation constraint, which can be modeled with $p_{\text{rel}}(w|y_{<t}, C)$, the probability that w satisfies the relation constraints. The core idea of our proposed probability surgery is to combine p_{vocab} and p_{rel} together to produce an augmented distribution $\tilde{p}$, and then use $\tilde{p}$ instead of p_{vocab} to choose the words.

We first give a formal definition of $p_{\text{rel}}(w|y_{<t}, C)$. The p_{rel} depends on two factors: (1) the transition probability $p_{\text{trans}}(y_j, y_i)$, the probability that y_j is the head of y_i, (2) the relation type probability $p_{\text{type}}(y_j, r, y_i)$, the probability that the relation between y_i and y_j falls in type r. Both p_{trans} and p_{type} can be obtained during decoding by a *relation identifier*. For dependency relations, the relation

Algorithm 2 Probability Surgery and RG-Top-K

1: **function** PROB_SURGERY(p_{vocab}, candidates, C, R)
2:     **for all** candidate **in** candidates **do**
3:         **for all** unmet lexical constraints w of candidate **do**
4:             sent $\leftarrow$ candidate.sentence (i.e., $y_{<t}$) $+ w$
5:             Get $p_{\text{trans}}, p_{\text{type}}$ by R and sent, and then calculate $p_{\text{rel}}(w|y_{<t}, C)$ by Eq. 3
6:         Calculate and normalize $\tilde{p}$ by $\widetilde{p}(w|y_{<t}, X, C; \theta) \propto g(p_{\text{rel}}(w|y_{<t}, C)) \cdot p_{\text{vocab}}(w|y_{<t}, X; \theta)$
        return $\tilde{p}$ of every candidate
7: **function** RG_TOPK($\tilde{p}$, candidates, C)
8:     candidates $\leftarrow$ Generate_candidates_by_DBA($\tilde{p}$, candidates)
9:     relation_counts $\leftarrow$ [0 for i in $[0, |C|]$], bank $\leftarrow$ [[] for i in $[0, |C|]$], pruned_candidates $\leftarrow$ []
10:     **for all** candidate **in** candidates **do**
11:         relation_counts[n_i] += 1, where n_i is the number of correct relation constraints
12:         bank[n_i].add(candidate)
13:     bank_sizes $\leftarrow$ Beam_Allocate_by_DBA(relation_counts)
14:     **for** j **in** $[0, |C|]$ **do**
15:         pruned_candidates += bank[j][:bank_sizes[j]]
    return pruned_candidates

---

identifier can be a left-to-right dependency parser [7] to better fit the left-to-right manner of autoregressive decoding. For relations between entities, the relation identifier can be any relation extraction model. The function of relation identifier is to predict the head of y_i, which produces a series of $p_{\text{trans}}(y_j, y_i)$. Additionally, the relation identifier also predict the relation types, which produces a series of $p_{\text{type}}(y_j, r, y_i)$. Note that if y_j is not the head of y_i, $p_{\text{type}}(y_j, r, y_i) = 0$ for all types r.

Given the incomplete output sequence $y_{<t} = (y_1, y_2, ..., y_{t-1})$ at time step t and the next token w, we choose the relation constraints related to w in C. Let $C_{\text{head}}(w, t), C_{\text{tail}}(w, t)$ denote the subset of relation constraints C at time step t where the w serves as the head or the tail, respectively:

$$C_{\text{head}}(w, t) = \{(w, r, y)|(w, r, y) \in C \land y \in y_{<t}\}, \ \forall w \in \mathcal{V}_{\mathcal{T}}.$$
$$C_{\text{tail}}(w, t) = \{(y, r, w)|(y, r, w) \in C \land y \in y_{<t}\}, \ \forall w \in \mathcal{V}_{\mathcal{T}}. \tag{2}$$

We can calculate $p_{\text{rel}}(w|y_{<t}, C)$ as follows[2]:

$$p_{\text{rel}}(w|y_{<t}, C) = \frac{1}{Z_{w,t}} \left\{ \sum_{\substack{(w,r,y) \in \\ C_{\text{head}}(w,t)}} [p_{\text{trans}}(w, y) + p_{\text{type}}(w, r, y)] + \sum_{\substack{(y,r,w) \in \\ C_{\text{tail}}(w,t)}} [p_{\text{trans}}(y, w) + p_{\text{type}}(y, r, w)] \right\}, \tag{3}$$

where $Z_{w,t} = 2[|C_{\text{head}}(w,t)| + |C_{\text{tail}}(w,t)|]$ is a normalizing factor. Consequently, the augmented distribution can be calculated as follows:

$$\widetilde{p}(w|y_{<t}, X, C; \theta) \propto g(p_{\text{rel}}(w|y_{<t}, C)) \cdot p_{\text{vocab}}(w|y_{<t}, X; \theta), \tag{4}$$

where $g : [0, 1] \to (0, 1]$ is a gate function to transform p_{rel} to a weight of p_{vocab}. We aim to increase the weight when the p_{rel} increases, so g cannot be a monotonically decreasing function. Moreover, the output of this function should not be exactly zero, because assigning zero probability will make the log-likelihood of the whole sentence be negative infinite. Based on these requirements, inspired by Schick et al. [32], we adopt this parameterized form of g in this paper:

$$g(p_{\text{rel}}) = \begin{cases} e^{-\lambda(1-p_{\text{rel}})} & \text{if } p_{\text{rel}} < \rho \\ 1 & \text{otherwise} \end{cases} \tag{5}$$

where λ, ρ are the hyperparameters and $\lambda > 0, \rho \in (0, 1]$. λ controls the decay of output value. ρ is a threshold for the probability. We fix $\rho = 0.5$ in this paper. If the p_{rel} of a word w is greater than or equal to this pre-specified threshold ρ, it is confident enough to consider w satisfies the relation constraints. Thus we set $g(p_{\text{rel}}) = 1$ for this situation to preserve the p_{vocab} of w. On the contrary, when p_{rel} is close to 0, $g(p_{\text{rel}})$ will be close to a relatively small value $e^{-\lambda}$, which indicates that the model will be less likely to choose the words violating relation constraints.

---

[2]Note that $p_{\text{rel}}(w|y_{<t}, C) = 0$ if $C_{\text{head}}(w, t) = C_{\text{tail}}(w, t) = \emptyset$. Apart from that, we use additive form of p_{rel} instead of a multiplicative manner, we further discuss this in Appendix A.

3.2 Relation-Guided Top-K

To ensure the presence of lexical constraints, we adopt the Top-K operation in DBA [26]. DBA firstly generates a set of candidates and then selects k of them through beam allocation. The candidate set generated by DBA (line 8) is the union of three sets: (1) the normal Top-K tokens, (2) all unsatisfied lexical constraints, and (3) the single-best token for each hypothesis in the beam. After that, DBA groups together the candidates with the same number of satisfied lexical constraints into some *banks* and selects a different number of candidates from different banks. The candidates with fewer lexical constraints will have more chances to be selected. However, the original DBA is not aware of the relations between words. Since we have already processed the candidate sentences by relation identifier in probability surgery, we can now use the processed result to guide the bank allocation. As illustrated in Algorithm 2, we propose to use the number of correct relation constraints of i-th candidates (line 10-12) to divide the banks, rather than the number of satisfied lexical constraints used by DBA. This modification can jointly consider both lexical and relation constraints, because one relation constraint is equivalent to two lexical constraints and their relation.

4 Experiments on Dependency Placement

There are many kinds of word relations in natural language, so it is necessary to showcase the performance of our proposed RESEAL on different relations. Since syntactic dependency structures serve as the principle of how words are combined to form sentences, dependency relations can be the most basic and important for text generation. Thus, in this section, we mainly focus on the dependency relation scenario of RCD, and evaluate RESEAL on the **Dependency Placement** task. Besides, we will conduct extensive experiments on three downstream tasks in Section 5.

4.1 Task and Dataset

We first define **Dependency Placement** task: given the constraints C of dependency relations, output a fluent sentence Y which appropriately places these constraints. The model input X is optional, which can be a single $\langle \text{BOS} \rangle$ token, or a sequential transformation of C to provide necessary information. We then construct the dataset for dependency placement task from the English-EWT [34] corpus[3], which contains 16,621 sentences with dependency annotations and standard train/dev/test set split. For each sentence with m words, we randomly sample n dependency triplets $\{(h_i, r_i, \tau_i)\}_{i=1}^{n}$ as the given constrains C, where $n < m$. The original sentences serve as references. We refer to this dataset as English-EWT-Dep. More details about English-EWT-Dep can be found in Appendix B.

4.2 Evaluation Metrics

In this section, we discuss the appropriate metrics for the dependency placement task to evaluate an RCD algorithm (including but not limited to our proposed RESEAL). Simply using the automatic evaluation to compare the system outputs with the references is not suitable, because there are too many sentences that can be the correct answer given several dependencies. We mainly focus on whether the relation constraints are satisfied when examining an RCD algorithm. To this end, the output sentences should be processed again by an accurate external parser[4]. This parser should preferably be different from the one used in an RCD algorithm, which can better examine the generalization ability across the parsers. In this paper, we use two widely-used dependency parsers provided by `Stanza` [27] and `spaCy`[5] for evaluation. Let $C^{(i)}$ denote the relation constraints of i-th output $Y^{(i)}$ in test set. Let $C'(Y^{(i)})$ denote the dependency relation triplets obtained by the external parser. Let $W^{(i)}$ and $W'(Y^{(i)})$ denote the sets if we omit the dependency relation r of $C^{(i)}$ and $C'(Y^{(i)})$. Similar to the unlabeled/labeled attachment score (UAS/LAS) used in dependency parsing, we can define the unlabeled/labeled coverage (UC/LC) as follows:

$$\text{UC} = \frac{\sum_i |W^{(i)} \cap W'(Y^{(i)})|}{\sum_i |W^{(i)}|}, \quad \text{LC} = \frac{\sum_i |C^{(i)} \cap C'(Y^{(i)})|}{\sum_i |C^{(i)}|}. \tag{6}$$

---

[3]`https://universaldependencies.org/`

[4]Another choice is to process the outputs by human, which is too expensive.

[5]`https://explosion.ai/blog/ud-benchmarks-v3-2#project`

Table 1: Evaluation result for dependency placement task. "Reference" denotes evaluating the ground truth sentences, which can be viewed as an approximated upper bound of this task. Despite that the BLEU score is not so accurate to evaluate this task, we still provide it for reference only.

Method	Stanza		spaCy		BLEU↑	PPL↓	Word%↑
	UC↑	LC↑	UC↑	LC↑			
Base [18]	80.52	69.69	81.04	71.02	11.92	865.40	97.11
Rerank ($k = 20$)	84.32	74.86	84.04	74.93	11.66	346.44	**99.88**
CGMH [23]	39.46	25.70	37.50	24.69	1.47	2341.83	96.20
X-MCMC [10]	51.78	37.36	52.30	37.99	4.62	513.18	99.86
X-MCMC-C [10]	58.17	44.90	58.90	46.23	6.39	557.58	**99.88**
DBA [26]	79.54	67.39	79.78	68.47	11.47	318.67	99.82
DDBA [22]	79.22	68.72	79.96	70.11	12.22	796.76	97.01
NEUROLOGIC [21]	82.47	71.72	83.03	72.87	12.23	436.27	98.93
RESEAL	**86.45**	**79.26**	**86.73**	**80.66**	**12.62**	**260.80**	99.60
Reference	86.80	81.49	90.50	86.49	100.00	527.35	100.00

Moreover, we also report the BLEU [25] metric, the GPT-2 [28] perplexity (PPL) and word coverage (the proportion of lexical constraints that are satisfied).

4.3 Baselines

Since there are no existing work about dependency placement, we design some straightforward baselines to compare with our method:

- **Base**: Use BART$_{large}$ [18] as the backbone, and then funetine it English-EWT-Dep. The input is the concatenation of the triplets of C separated by special token #. For example, if $C = \{(h_1, r_1, \tau_1), (h_2, r_2, \tau_2)\}$, the input sequence $X = h_1 \# r_1 \# \tau_1, h_2 \# r_2 \# \tau_2$. The target output is the reference. During decoding, we use standard beam search with beam size $k = 20$.

- **CGMH** [23]: Use MCMC sampling to generate a sentence by modifying it. We use BERT$_{large}$ [4] as its replacement probability, and GPT-2$_{large}$ [28] as its language model.

- **X-MCMC** [10]: Improve CGMH by using XLNet [41]. **X-MCMC-C** adds a classifier to instruct the X-MCMC models where and how to modify the candidate sentences.

- **DBA** [26]: Use DBA algorithm to decode on **Base** model. Beam size k is set to 20.

- **DDBA** [22]: A denoised variant of DBA by filtering noisy constraints.

- **NEUROLOGIC** [21]: A LCD algorithm which support complex lexical constraints in Conjunctive Normal Form (CNF).

- **Rerank**: Preserve all k sentences generated by **DBA**, and select the sentence that satisfies the most relation constraints using left-to-right parser [7].

We report the results when applying RESEAL to the **Base**. More details can be found in Appendix C.1.

4.4 Discussion

Results Table 1 shows the results for dependency placement. We find that the sampling-based method [10, 23] can achieve better word coverage, but the low UC/LC scores demonstrate that they fail to enforce the relation constraints. RESEAL achieves best UC/LC among all the methods with significant decline of the PPL and competitive word coverage. Specifically, RESEAL gains an improvement of 1.15 on BLEU and $11.87\%/12.19\%$ (Stanza/spaCy) on LC compared to DBA. These results illustrate the weakness of existing LCD algorithms to correctly place the multiple relation constraints. In addition, though Rerank requires to generate many completed sentences, and thus is much more inefficient than RESEAL, our proposed RESEAL still outperforms Rerank on almost all the metrics. An intrinsic reason for this may be that RESEAL can dynamically adjust the word selection according to the parsing result during decoding, but Rerank can not make a choice until finishing all the sentences.

Table 2: Result of ablation study for dependency placement task. We remove a single component from the full algorithm to study the individual effect. "w/o prob" denotes without probability surgery, "w/o RG-Top-K" denotes using the way of original DBA to allocate beam. "word+rel" denotes using the number of satisfied lexical and (dependency) relation constraints to allocate beam.

Method	Stanza		spaCy		BLEU↑	PPL↓	Word%↑
	UC↑	LC↑	UC↑	LC↑			
RESEAL	**86.45**	**79.26**	**86.73**	**80.66**	**12.62**	260.80	99.60
w/o prob	81.70	70.91	82.12	72.21	11.83	**256.88**	**99.80**
w/o RG-Top-K	82.12	74.27	83.03	75.49	11.89	361.96	99.76
word+rel	82.40	74.51	83.34	75.42	11.08	452.50	99.72

Figure 2: The result when altering the value of λ and beam size k.

Ablation Study   Table 2 shows the results of ablation study. We observe a decrease of 0.79 on BLEU and 8.35%/8.45% (Stanza/spaCy) on LC by removing probability surgery. We also observe a decrease of 0.73 on BLEU and 4.99%/5.17% (Stanza/spaCy) on LC by removing RG-Top-K. Probability surgery enables the tokens with correct dependencies to enter the candidate set. RG-Top-K dynamically allocates the beam according to the parsing result to satisfy more relation constraints. These two components are both crucial. Furthermore, we find that adopting another beam allocation strategy ("word+rel" in Table 2) also hurt the performance.

Impact of Hyperparameters   For the dependency placement task, the performance would benefit from a larger beam size, which is consistent with the observations of Post and Vilar [26]. The left of Figure 2 shows the labeled coverage (LC) as a function of beam size by different methods on the test set. We observe that RESEAL can achieve better LC scores with smaller beam sizes when compared with **Rerank**. Apart from that, the decay factor λ introduced in Section 3.1 is another important hyperparameter of RESEAL. We investigate its influence on the model performance. Figure 2 shows the results when varying λ from 0 to 10 based on the validation set. If we set λ as a relatively large value (> 4), the performance of RESEAL tends to be stable. Specifically, $\lambda = 0$ is equivalent to removing probability surgery (from Eq. 5), which will result in worse performance.

More Discussions   In Appendix D.1, we discuss the impact of the dependency parser. In Appendix D.2, we discuss the time complexity of RESEAL. In Appendix D.3, we show some generated texts for dependency placement task.

5 Experiments on Downstream Tasks

To further explore the effectiveness of our proposed RESEAL, we conduct experiments on the three downstream tasks: sentence summarization, fact-based text editing, and data-to-text generation.

5.1 Sentence Summarization

Dataset   We conduct experiments on English Gigaword dataset [31], which contains about 3.8M training sentence pairs. We use the validation and test set provided by Zhou et al. [43] with 8,000 and

Table 3: Evaluation results for sentence summarization experiments.

Methods	Gigaword			DUC2004			MSR-ATC		
	RG-1	RG-2	RG-L	RG-1	RG-2	RG-L	RG-1	RG-2	RG-L
SEASS [43]	46.86	24.58	43.53	29.21	9.56	25.51	25.75	10.63	22.90
Keyword [19]	47.14	25.06	44.39	-	-	-	-	-	-
SemSum [15]	-	-	-	31.00	11.11	26.94	33.82	17.08	30.62
BART [18]	50.14	27.37	46.69	31.38	11.43	27.51	40.39	22.09	35.32
BART+RESEAL	**50.73**	**27.84**	**47.18**	**32.67**	**11.63**	**28.38**	**43.77**	**25.28**	**37.78**
BART+RESEAL (gold)	53.74	31.00	48.99	35.53	12.41	28.68	69.42	41.76	51.71

2,000 sentence pairs, respectively. Following previous work, we also evaluate our model on the test set of DUC2004 [24] (with 500 input sentences) and MSR-ATC [37] (with 785 input sentences).

Dependency Prediction To apply RESEAL to sentence summarization, we first need to obtain reasonable dependency triples to construct relation constraints. In this paper, we train a vanilla BERT-base-uncased [4] model to predict which dependencies should be present in the target output. Firstly, we parse the sentences in the dataset by the left-to-right parser [7]. Then we use the intersection of dependencies of source and target sentences as the ground truth to train the dependency predictor. For each triplet (h, r, τ), we concatenate the contextual embedding of h, τ and label embedding of r to perform binary classification. More details can be found in Appendix C.2.

Results Following previous work [15, 43], we report ROUGE F1 [20] on Gigaword and MSR-ATC, and ROUGE recall on DUC2004. Table 3 show the results. BART consistently outperforms the previous models without pretraining across different datasets. Over the strong BART baseline, RESEAL can achieve better ROUGE scores on all datasets with predicted relation constraints. We also investigate the upper bound of BART+RESEAL by using the gold relation constraints, which shows that there is room for improvement with more accurate dependency predictors.

5.2 Fact-Based Text Editing

Dataset Fact-based Text Editing is a novel task proposed by Iso et al. [14]. Given some triplets (facts) from knowledge graphs and a draft text, this task aims to revise the draft text to contain these facts. We adopt the WebEdit dataset provided by Iso et al. [14], which contains 181K/23K/29K instances as train/valid/test set. Note that this dataset can be viewed as a natural scenario for RCD because both the relation constraints (facts) and model input (draft text) are provided. More importantly, based on the results of error analysis, the models trained on this dataset still suffer from missing facts and incorrect relations (see "Qualitative evaluation" section in [14]). RESEAL may alleviate these problems by explicitly enforcing facts and relations.

Models and Results For the relation identifier, we train a simple BiLSTM [11] encoder with biaffine attention [6] on the training set of WebEdit (See Appendix C.3.1 for more details). We use EncDecEditor and FactEditor reported by Iso et al. [14] as our baseline models. EncDecEditor is an encoder-decoder model based on LSTM, with two separate encoders for facts and drafts and a decoder for generating revised texts. FactEditor shares the same encoders with EncDecEditor but has a novel decoder that doesn't follow the conventional autoregressive decoding manner. Thus we can only apply RESEAL to the EncDecEditor. For a fair comparison, we do not use pretrained models and keep the same architecture setting as EncDecEditor. However, the source code and the training details of EncDecEditor are unreleased, thus we reimplement EncDecEditor using our own training configuration (See Appendix C.3.2). We denote this model as Seq2Seq. Table 4 shows the experiment results of WebEdit. Following Iso et al. [14], we report the BLEU and SARI [40] score (the average F1-score for keep, add and delete operations). Owing to the difference of training settings, Seq2seq can achieve significant improvement on BLEU (+7.28) and SARI (+1.54) compared to FactEditor. Based on this result, we further adopt RESEAL on Seq2Seq and then observe a substantial improvement on BLEU (+1.16) and SARI (+4.59). The above results demonstrate that RESEAL can achieve better facts and relations preservation over the strong Seq2Seq baseline.

Table 4: Evaluation result of WebEdit dataset. "K", "A", "D" denote the metrics of "KEEP", "ADD", "DELETE", respectively.

Methods	BLEU	SARI	K	A	D
EncDecEditor [14]	71.03	69.59	89.49	43.82	75.48
FactEditor [14]	75.68	72.20	91.84	47.69	**77.07**
Seq2Seq	82.96	73.74	93.62	64.56	63.05
Seq2Seq+RESEAL	**84.12**	**78.33**	**96.07**	**69.63**	69.29

Table 5: Evaluation result for WebNLG test set.

Methods	BLEU
T5-small [29]	56.34
T5-small + RESEAL	**56.87**
T5-base [29]	59.17
T5-base + RESEAL	**59.59**

5.3 Data-to-Text Generation

Dataset Data-to-text generation is another direct application for RESEAL. In this paper, we adopt WebNLG dataset [9] which provides facts as inputs and sentences containing these facts as outputs. We use the data provided by Ribeiro et al. [30] which contains 18,102/872/1,862 instances as train/valid/test set. Each test instance has 1-3 references.

Models and Results For WebNLG dataset, the setting of the relation identifier is the same as that for WebEdit. Table 5 shows the experiment results of WebNLG dataset. We adopt our RESEAL on T5 [29] and report the BLEU score for evaluation. We observe an improvement of 0.53 BLEU on T5-small and 0.42 BLEU on T5-base. The detailed experimental settings can be found in Appendix C.4.

6 Related Work

Lexically Constrained Decoding (LCD) Prior explorations for LCD can be summarized into four categories. The first line of studies has proposed some model-agnostic methods which only modify the decoding process. They are independent from the training. Hokamp and Liu [12] propose the grid beam search (GBS) algorithm, a modification to beam search to impose the lexical constraints. Post and Vilar [26] propose the dynamic beam allocation (DBA) algorithm with less time complexity. Vectorized DBA [13] and Denoised DBA [22] are two different DBA variants. The second line of studies requires some modifications to the training process. Augmenting the training data with the lexical constraints is a general approach [3, 5, 35]. Another branch of previous works focuses on adding additional structure to the model [36, 38, 39]. The fourth line of studies applies Markov Chain Monte Carlo (MCMC) to constrained text generation in a refinement manner [10, 23, 33]. Different from these methods, we do not only focus on the isolated lexical constraints. We propose to adopt relation constraints to consider the relationship between words.

Dependency-Guided Generation Dependency is a natural way to represent the syntactic or semantic relations between words, so it can be used to guide the text generation. There are few works exploring this. Filippova and Strube [8] propose to compress the dependency graph to guide the sentence fusion. Akoury et al. [1] propose to predict a chunked syntactic parse tree and then generate tokens conditioned on the parse. Jin et al. [15] encode the dependency relations by a graph encoder to improve sentence summarization. Casas et al. [2] propose a language model where the generation is driven by the expansion over the dependency parse tree. Yang and Wan [42] propose a dependency modeling objective to incorporate dependency knowledge. However, one drawback of these methods is the limitation of interpretability and controllability since they only use the dependency as a latent variable during training, and cannot explicitly control the generation at the inference stage.

7 Conclusion

In this paper, we explore the Relation-Constrained Decoding (RCD), a new decoding scenario with a more complex definition of constraints. We propose RESEAL, a novel algorithm for RCD, which can be applied to the decoder of different models to preserve specific relation constraints. We examine two different experiment settings of RCD: dependency placement and downstream tasks. For dependency placement, we construct the benchmark for dependency placement, and the experiment results show the strength of RESEAL for satisfying relation constraints. Furthermore, we apply RESEAL to three downstream tasks as extended experiments for practical applications. Extensive experiments demonstrate the effectiveness and universality of our method.

References

[1] Nader Akoury, Kalpesh Krishna, and Mohit Iyyer. Syntactically supervised transformers for faster neural machine translation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 1269–1281, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1122. URL https://aclanthology.org/P19-1122.

[2] Noe Casas, José A. R. Fonollosa, and Marta R. Costa-jussà. Syntax-driven iterative expansion language models for controllable text generation. In *Proceedings of the Fourth Workshop on Structured Prediction for NLP*, pages 1–10, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.spnlp-1.1. URL https://aclanthology.org/2020.spnlp-1.1.

[3] Guanhua Chen, Yun Chen, Yong Wang, and Victor O. K. Li. Lexical-constraint-aware neural machine translation via data augmentation. In Christian Bessiere, editor, *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI 2020*, pages 3587–3593. ijcai.org, 2020. doi: 10.24963/ijcai.2020/496. URL https://doi.org/10.24963/ijcai.2020/496.

[4] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://aclanthology.org/N19-1423.

[5] Georgiana Dinu, Prashant Mathur, Marcello Federico, and Yaser Al-Onaizan. Training neural machine translation to apply terminology constraints. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3063–3068, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1294. URL https://aclanthology.org/P19-1294.

[6] Timothy Dozat and Christopher D Manning. Deep biaffine attention for neural dependency parsing. *arXiv preprint arXiv:1611.01734*, 2016.

[7] Daniel Fernández-González and Carlos Gómez-Rodríguez. Left-to-right dependency parsing with pointer networks. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 710–716, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1076. URL https://aclanthology.org/N19-1076.

[8] Katja Filippova and Michael Strube. Sentence fusion via dependency graph compression. In *Proceedings of the 2008 Conference on Empirical Methods in Natural Language Processing*, pages 177–185, Honolulu, Hawaii, 2008. Association for Computational Linguistics. URL https://aclanthology.org/D08-1019.

[9] Claire Gardent, Anastasia Shimorina, Shashi Narayan, and Laura Perez-Beltrachini. Creating training corpora for nlg micro-planning. In *55th annual meeting of the Association for Computational Linguistics (ACL)*, 2017.

[10] Xingwei He and Victor OK Li. Show me how to revise: Improving lexically constrained sentence generation with xlnet. In *Proceedings of AAAI*, pages 12989–12997, 2021.

[11] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

[12] Chris Hokamp and Qun Liu. Lexically constrained decoding for sequence generation using grid beam search. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1535–1546, Vancouver, Canada, 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1141. URL https://aclanthology.org/P17-1141.

[13] J. Edward Hu, Huda Khayrallah, Ryan Culkin, Patrick Xia, Tongfei Chen, Matt Post, and Benjamin Van Durme. Improved lexically constrained decoding for translation and monolingual rewriting. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 839–850, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1090. URL `https://aclanthology.org/N19-1090`.

[14] Hayate Iso, Chao Qiao, and Hang Li. Fact-based Text Editing. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 171–182, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.17. URL `https://aclanthology.org/2020.acl-main.17`.

[15] Hanqi Jin, Tianming Wang, and Xiaojun Wan. Semsum: Semantic dependency guided neural abstractive summarization. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 8026–8033. AAAI Press, 2020. URL `https://aaai.org/ojs/index.php/AAAI/article/view/6312`.

[16] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL `http://arxiv.org/abs/1412.6980`.

[17] Rémi Lebret, David Grangier, and Michael Auli. Neural text generation from structured data with application to the biography domain. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 1203–1213, Austin, Texas, 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1128. URL `https://aclanthology.org/D16-1128`.

[18] Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7871–7880, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.703. URL `https://aclanthology.org/2020.acl-main.703`.

[19] Haoran Li, Junnan Zhu, Jiajun Zhang, Chengqing Zong, and Xiaodong He. Keywords-guided abstractive sentence summarization. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 8196–8203. AAAI Press, 2020. URL `https://aaai.org/ojs/index.php/AAAI/article/view/6333`.

[20] Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain, 2004. Association for Computational Linguistics. URL `https://aclanthology.org/W04-1013`.

[21] Ximing Lu, Peter West, Rowan Zellers, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. NeuroLogic decoding: (un)supervised neural text generation with predicate logic constraints. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4288–4299, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.339. URL `https://aclanthology.org/2021.naacl-main.339`.

[22] Yuning Mao, Wenchang Ma, Deren Lei, Jiawei Han, and Xiang Ren. Extract, denoise and enforce: Evaluating and improving concept preservation for text-to-text generation. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 5063–5074, Online and Punta Cana, Dominican Republic, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.413. URL `https://aclanthology.org/2021.emnlp-main.413`.

[23] Ning Miao, Hao Zhou, Lili Mou, Rui Yan, and Lei Li. CGMH: constrained sentence generation by metropolis-hastings sampling. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pages 6834–6842. AAAI Press, 2019. doi: 10.1609/aaai.v33i01.33016834. URL `https://doi.org/10.1609/aaai.v33i01.33016834`.

[24] Paul Over, Hoa Dang, and Donna Harman. Duc in context. *Information Processing & Management*, 2007.

[25] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318, Philadelphia, Pennsylvania, USA, 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL `https://aclanthology.org/P02-1040`.

[26] Matt Post and David Vilar. Fast lexically constrained decoding with dynamic beam allocation for neural machine translation. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1314–1324, New Orleans, Louisiana, 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1119. URL `https://aclanthology.org/N18-1119`.

[27] Peng Qi, Yuhao Zhang, Yuhui Zhang, Jason Bolton, and Christopher D. Manning. Stanza: A python natural language processing toolkit for many human languages. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pages 101–108, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-demos.14. URL `https://aclanthology.org/2020.acl-demos.14`.

[28] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 2019.

[29] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21:1–67, 2020.

[30] Leonardo F. R. Ribeiro, Martin Schmitt, Hinrich Schütze, and Iryna Gurevych. Investigating pretrained language models for graph-to-text generation. In *Proceedings of the 3rd Workshop on Natural Language Processing for Conversational AI*, pages 211–227, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.nlp4convai-1.20. URL `https://aclanthology.org/2021.nlp4convai-1.20`.

[31] Alexander M. Rush, Sumit Chopra, and Jason Weston. A neural attention model for abstractive sentence summarization. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 379–389, Lisbon, Portugal, 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1044. URL `https://aclanthology.org/D15-1044`.

[32] Timo Schick, Sahana Udupa, and Hinrich Schütze. Self-diagnosis and self-debiasing: A proposal for reducing corpus-based bias in NLP. *Transactions of the Association for Computational Linguistics*, 9:1408–1424, 2021. doi: 10.1162/tacl_a_00434. URL `https://aclanthology.org/2021.tacl-1.84`.

[33] Lei Sha. Gradient-guided unsupervised lexically constrained text generation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 8692–8703, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.701. URL `https://aclanthology.org/2020.emnlp-main.701`.

[34] Natalia Silveira, Timothy Dozat, Marie-Catherine de Marneffe, Samuel Bowman, Miriam Connor, John Bauer, and Chris Manning. A gold standard dependency corpus for English. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation*

(*LREC'14*), pages 2897–2904, Reykjavik, Iceland, 2014. European Language Resources Association (ELRA). URL `http://www.lrec-conf.org/proceedings/lrec2014/pdf/1089_Paper.pdf`.

[35] Kai Song, Yue Zhang, Heng Yu, Weihua Luo, Kun Wang, and Min Zhang. Code-switching for enhancing NMT with pre-specified translation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 449–459, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1044. URL `https://aclanthology.org/N19-1044`.

[36] Kai Song, Kun Wang, Heng Yu, Yue Zhang, Zhongqiang Huang, Weihua Luo, Xiangyu Duan, and Min Zhang. Alignment-enhanced transformer for constraining NMT with pre-specified translations. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 8886–8893. AAAI Press, 2020. URL `https://aaai.org/ojs/index.php/AAAI/article/view/6418`.

[37] Kristina Toutanova, Chris Brockett, Ke M. Tran, and Saleema Amershi. A dataset and evaluation metrics for abstractive compression of sentences and short paragraphs. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 340–350, Austin, Texas, 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1033. URL `https://aclanthology.org/D16-1033`.

[38] Yufei Wang, Ian Wood, Stephen Wan, Mark Dras, and Mark Johnson. Mention flags (MF): Constraining transformer-based text generators. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 103–113, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.9. URL `https://aclanthology.org/2021.acl-long.9`.

[39] Yufei Wang, Can Xu, Huang Hu, Chongyang Tao, Stephen Wan, Mark Dras, Mark Johnson, and Daxin Jiang. Neural rule-execution tracking machine for transformer-based text generation. *Advances in Neural Information Processing Systems*, 34, 2021.

[40] Wei Xu, Courtney Napoles, Ellie Pavlick, Quanze Chen, and Chris Callison-Burch. Optimizing statistical machine translation for text simplification. *Transactions of the Association for Computational Linguistics*, 4:401–415, 2016. doi: 10.1162/tacl_a_00107. URL `https://aclanthology.org/Q16-1029`.

[41] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime G. Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. Xlnet: Generalized autoregressive pretraining for language understanding. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 5754–5764, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/dc6a7e655d7e5840e66733e9ee67cc69-Abstract.html`.

[42] Zhixian Yang and Xiaojun Wan. Dependency-based mixture language models. *arXiv preprint arXiv:2203.10256*, 2022.

[43] Qingyu Zhou, Nan Yang, Furu Wei, and Ming Zhou. Selective encoding for abstractive sentence summarization. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1095–1104, Vancouver, Canada, 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1101. URL `https://aclanthology.org/P17-1101`.

A More Explanations About RESEAL

Both $C_{\text{head}}(w, t)$ and $C_{\text{tail}}(w, t)$ can be empty set as C can be arbitrary. Noted that in this part we simply sum over all p_{trans} and p_{type} to produce p_{rel}, which is different from the method we use when combining p_{vocab} and p_{rel}. The reason why we use this form is that if substituting Eq. 5 and 3 into Eq. 4, we can derive a decomposed form:

$$
g(p_{\text{rel}}(w|y_{<t}, C)) = \left\{ \prod_{\substack{(w,y,r)\in \\ C_{\text{head}}(w,t)}} [g(p_{\text{trans}}(w,y)) \cdot g(p_{\text{type}}(w,y,r))] \cdot \right.
$$
$$
\left. \prod_{\substack{(y,w,r)\in \\ C_{\text{tail}}(w,t)}} [g(p_{\text{trans}}(y,w)) \cdot g(p_{\text{type}}(y,w,r))] \right\}^{Z_{w,t}} . \tag{7}
$$

Eq. 7 indicates that we assign high probability to w at time step t if and only if all the relation constraints in $C_{\text{head}}(w, t) \cup C_{\text{tail}}(w, t)$ are satisfied. Any violation of the constraints will result in a small value of $g(p_{\text{rel}}(w|y_{<t}, C))$ and reduce the augmented probability $\tilde{p}$ of w according to Ed. 4.

B Dataset Construction for English-EWT-Dep

In this section, we give more details about the data construction process of English-EWT-Dep introduced in Section 4.1. We only consider the dependency relations whose modifier is an *adjective, noun, or verb* and randomly sample parts of them (at a ratio of 40%). The sentences which are shorter than 4 words are omitted. Some sentences containing personal information (e.g. phone number or address) are also discarded. The statistics of the English-EWT-Dep dataset is as follows:

Table 6: Statistics of the English-EWT-Dep dataset.

	train	dev	test
Sentence	10119	1454	1407
Avg word count	19.39	15.98	16.19
Avg number of dependencies	2.43	2.04	2.04
Max number of dependencies	18	13	11

C Implementation Details

We provided the implementation details for the four tasks included in this work: dependency placement, sentence summarization, fact-based text editing and data-to-text generation. Note that in this paper, we conduct all the experiments on a NVIDIA A40 GPU with 40 GB memory.

C.1 Dependency Placement

For the **Base** model of dependency placement task, we use BART$_{\text{large}}$ [18] as our pretrained model. We use label smoothing of 0.1 and optimize the model by Adam [16]. The learning rate is 2e-5 with a warmup rate of 0.1. The weight decay is 0.1. We train the **Base** model for 10 epochs with a batch size of 32.

C.2 Sentence Summarization

For the sentence summarization task, we also use BART$_{\text{large}}$ [18] as our pretrained model. The hyperparameter setting is similar to the dependency placement except that we only train for 5 epochs with a batch size of 100. The ROUGE evaluation option for GigaWord and MSR-ATC is -m -n 2 -w 1.2. The ROUGE evaluation option for DUC2004 is -m -b 75 -n 2 -w 1.2.

For the dependency predictor used in this task, we adopt a BERT-base-uncased [4] model. Since the dependency is a word-level relation and BERT uses sub-word tokenization, we use the mean vector of the start and the end token as the representation $f(w)$ of a word w:

$$f(w) = \frac{1}{2}[\text{BERT}(\text{start token of } w) + \text{BERT}(\text{end token of } w)]. \tag{8}$$

We use an additional embedding layer with the dimension of 200 to represent the dependency label r. Let $f_L(r)$ denotes the representation of r, the feature of (h, r, w) is defined as the concatenation of $f(h)$, $f(w)$ and $f_L(r)$.

We optimize the dependency prediction model by Adam [16]. The learning rate is 2e-5 with a warmup rate of 0.1. The weight decay is 0.1. We train this model for 10 epochs with a batch size of 200. After training, for each sentence in test set, we select the dependency relation constraints with predicted probability larger than a threshold $\rho = 0.6$.

It's worth noting that our reported performance of sentence summarization can be further improved by training a more accurate dependency predictor, or using a single keyword extractor and preserving the corresponding dependencies of predicted keywords. We leave more in-depth explorations as future work.

C.3 Fact-Based Text Editing

Different from sentence summarization task, fact-based text editing does not require to predict the relation constraints, because the relation triplets have been provided in the dataset. Therefore, to adopt RESEAL, we only need to train the relation identifier and the LSTM [11] seq2seq model.

C.3.1 Relation Identifier for Fact-Based Text Editing

The structure of relation identifier for fact-based text editing is borrowed from the biaffine dependency parser [6]. We use a single layer LSTM with single direction. We use two separate MLPs with one hidden layer to extract the features of heads and tails, respectively. Finally, we use a biaffine attention module to classify the relation types. Moreover, following the setting of Iso et al. [14], we use a simple embedding lookup table to embedding the input words. The detailed hyperparameter setting is shown as follows:

Embedding size	300
LSTM hidden size	300
MLP hidden size	512
MLP output size	300
Number of relation categories	229
Maximum source length	128
Learning rate	1e-3
Dropout	0.5
Batch size	300
Total epochs	10

The training data for the relation identifier can be heuristically constructed from WebEdit dataset in a distant supervision manner, which is also the mainstream scheme for dataset construction of relation extraction models. We consider the target texts (revised text) in WebEdit as the inputs, and then use the given facts to match the words in revised texts. We omit the instances where the head word and the tail word are not in the same sentence, because in this situation it is difficult to determine whether these two words have given relations. Furthermore, we construct many negative samples from the positive samples by randomly deleting the words between the head words and the tail words. The relations between the head words and the tail words in negative samples are annotated as "no relation". We add these negative samples into training set and test set to improve the robustness of our relation identifier.

With the above mentioned model and augmented training data, we obtain a robust relation identifier for WebEdit, which can achieve about 93 F1 score in the test set.

C.3.2 Training Configuration

We reimplement the EncDecEditor [14] and denote it as Seq2Seq. The original paper only report the architecture of FactEditor [14]. Therefore, we have to make our Seq2Seq model have the same size as the FactEditor. The detailed hyperparameter setting is shown as follows:

Embedding size	300
Table Encoder hidden size	300
Text Encoder hidden size	300
Decoder hidden size	600
Maximum source length	128
Learning rate	1e-3
Teacher forcing ratio	0.5
Dropout	0.5
Batch size	200
Total epochs	30

Note that we use the same vocabulary as the corresponding relation identifier. Similar to EncDecEditor and FactEditor, our Seq2Seq model also employs attention and copy mechanism.

C.4 Data-to-Text Generation

In this part, we describe more details about the experiments of data-to-text generation task.

C.4.1 Entity and Relation Prediction

The settings of data-to-text generation is similar with that of fact-based text editing. The major difference is that the triplets given in WebNLG dataset cannot directly serve as relation constraints. The entities given in the source inputs may not has the same form in the references. Therefore, similar to the dependency prediction in sentence summarization task, we need to predict whether an entity should appear in its output.

In this paper, we directly use the encoder of T5 [29] to predict how to preserve the entities. Specifically, for all the triplets (h, w, τ), we transform them into a sequential form. Then we perform the sequence labeling task to predict which entities should be preserved in the output. This prediction task can be optimized jointly with the standard seq2seq learning. It must be pointed out that according to our experiment result, this prediction task itself does not influence the performance of data-to-text generation, so adding this task is not the reason for our performance gains. We can obtain the entities and their corresponding relations and set them as relation constraints during the inference stage by adopting RESEAL, which achieves better relation preservation and enhance the performance.

C.4.2 Relation Identifier for Data-to-Text Generation

The relation identifier on WebNLG dataset shares the same architecture with the one used in fact-based text editing. The only difference is the vocabulary. Due to the fact that we use T5 as our backbone for WebNLG, we adopt the tokenizer used in T5 to make the tokenizer consistent. The vocabulary size is 32,128.

C.4.3 Training Configuration

For the training settings for the WebNLG dataset, we train the T5-small and T5-base with a learning rate of 5e-5 and a batch size of 20 for 30 epochs. We optimize the model by Adam [16]. No weight decay and label smoothing are applied. The maximum length for both source and target are 384.

D More Discussions about Dependency Placement

D.1 Impact of the Dependency Parser

In this work, there are two types of dependency parser. The left-to-right parser [7] is used for the decoding. Stanza [27] and spaCy are used for the evaluation of algorithm.

For the parser which is used for the decoding, the result will benefit from a more accurate parser. For the parser which is used for the evaluation, a more accurate one would increase the absolute values of UC and LC. For more precise evaluation, you can use multiple such parsers to produce an average result.

D.2 Time Complexity Analysis

Similar to most of decoding-only LCD algorithms, RESEAL is usually slower than the standard beam search, but the overall runtime is within an acceptable range. The bottleneck of decoding speed is the times of decoder forward propagation. For a sentence of length N, beam search and DBA take N times forward. Our method should be slower due to the relation identifier. There are at most $2|C|$ candidate sentences to be parsed at time step t. Therefore, it will at most take $N(1 + 2|C|)$ times of forward for RESEAL, which still has $O(N)$ time complexity. A faster implementation of RESEAL is to save the outputs and hidden states obtained by the relation identifier at time step t, and reuse them at next time step $t + 1$. This implementation is left for the future work.

D.3 Case Study

Table 7 shows the sentences generated by all listed methods for dependency placement task. **Base** may omit some lexical constraints. **DBA** and **Rerank** satisfy all the lexical constraints, but they cannot correctly handle the relations between them. **Rerank** may generate sentences with repetitions (e.g. the word "charge"). RESEAL can produce sentences that are close to the grammatical structure of the references. Furthermore, table 8 shows more examples for the dependency placement task.

Table 7: Examples with RESEAL and other baselines. The dependency relation constraints are (*thought*, ccomp, *'s*) and (*'s*, nsubj, *charges*).

Method	Generated Sentences
Base	I **thought** the **charges** would be \$ 5,000, but they were \$ 10,000.
DBA	I **thought** the **charges** would be \$ 10,000, but it**'s** \$ 20,000.
Rerank	I **thought** they were going to charge me, but there**'s** no **charges**.
RESEAL	I **thought** there**'s** some **charges**, but I was wrong.
Ref.	I always **thought** there**'s** no custom **charges** for gifts.

E Impact Statement

Our work has a developed generic decoding method for relation-constrained decoding. Therefore, despite the contributes to better text generation, our proposed methods may be used to generate more human-like fake text. However, the impacts are more apparent when considering deployed applications, while our proposed methods as the methodologies can not have any direct negative societal impacts.

Table 8: More examples.

Method	Generated Sentences	Predicted/Gold Dependencies
Base	How do you make a luster product ?	None
DBA	How do you make a luster product ?	['everything', 'needs', 'acl:relcl']
Rerank	How do you make a luster product ?	['everything', 'needs', 'acl:relcl']
RESEAL	How do you make luster out of a luster product ?	['have', 'supermarket', 'nsubj'], ['everything', 'needs', 'acl:relcl']
Ref	The service was friendly and fast , but this just doesn't make up for the lack-luster product .	['have', 'supermarket', 'nsubj'], ['everything', 'needs', 'acl:relcl']
Base	If you 've never tried a brick , try the burger .	['try', 'burger', 'obl']
DBA	I 'm going to try the burger and the brick .	['try', 'burger', 'obl']
Rerank	If you 're looking for a good burger , try the brick .	['try', 'burger', 'obl']
RESEAL	I would not try this brick for a burger .	['try', 'brick', 'obj',], ['try', 'burger', 'obl']
Ref	Along with the great burger try a brick of onion rings if you are with someone .	['try', 'brick', 'obj',], ['try', 'burger', 'obl']
Base	I 'll come back to work when I call .	None
DBA	I 'll come back to work when I call .	None
Rerank	I 'll come back to work when I call .	None
RESEAL	I 'll come back on a call when I 'm back at work .	['come', 'call', 'obl'], ['back', 'work', 'obl']
Ref	Ps I may have to come back to work for a 615 call	['come', 'call', 'obl'], ['back', 'work', 'obl']
Base	At the time , there were no clients in the facility and the staff rushed out of the building as soon as there was a problem .	['clients', 'facility', 'nmod']
DBA	The clients of this facility were rushed out of the building by the time I got there and there was no one there to help me .	['clients', 'facility', 'nmod'], ['rushed', 'time', 'obl'], ['rushed', 'was', 'advcl']
Rerank	The clients of this facility were rushed out of the building by the time I got there and there was no one there to help me .	['clients', 'facility', 'nmod'], ['rushed', 'time', 'obl'], ['rushed', 'was', 'advcl']
RESEAL	When there was clients in facility , they rushed out of the building at the same time as the clients were leaving .	['was', 'clients', 'nsubj',], ['rushed', 'time', 'obl',], ['rushed', 'was', 'advcl'], ['clients', 'facility', 'nmod']
Ref	Overpriced and the doctor acted arrogant and rushed at a time when there was very few clients in the facility .	['was', 'clients', 'nsubj',], ['rushed', 'time', 'obl',], ['rushed', 'was', 'advcl'], ['clients', 'facility', 'nmod']