QuickMerge++: Token Merging with Autoregressive Prior

Dong Liu [1]   **Yanxuan Yu** [2]

Abstract

As generative models scale to larger inputs across language, vision, and video domains, the cost of token-level computation has become a key bottleneck. While prior work suggests that only a subset of tokens significantly influence downstream predictions, most token selection methods are static, modality-specific, or incompatible with autoregressive generation. In this paper, we propose QuickMerge, a lightweight token merging framework designed for efficient next-token prediction.

QuickMerge dynamically selects a reduced number of tokens based on attention norm magnitude, guided by an entropy-based budget estimator. To preserve autoregressive compatibility, we introduce a lightweight transformer prior trained over the merged token sequence. By combining semantic salience estimation, flexible token budgets, and AR alignment, QuickMerge enables accurate generation with fewer tokens.

We evaluate QuickMerge across multi-modality domains, demonstrating consistent improvements in compute-accuracy tradeoffs. Specifically, QuickMerge reduces token counts sustantially while matching as well as exceeding the performance of learned tokenizers and fixed-patch baselines. Our code implementation can be found at https://github.com/NoakLiu/QuickMerge

1. Introduction

Large-scale generative models have achieved remarkable success across language, vision, and multimodal domains. However, their inference and training cost grows linearly with the number of input tokens, creating a fundamental bottleneck when processing long-context sequences or high-resolution inputs. This challenge is particularly acute in autoregressive (AR) generation, where every input token participates in recurrent attention and prediction.

Recent efforts have shown that not all tokens contribute equally to model performance (Ryoo et al., 2021; Kim et al., 2024). A small subset of salient tokens typically dominates the output prediction, suggesting the possibility of selective computation. Yet, most existing token pruning or merging strategies rely on static heuristics, pre-defined token layouts, or non-autoregressive assumptions. These approaches either degrade generation quality or fail to integrate with decoder-only AR models.

To address this, we propose **QuickMerge++**, a lightweight and autoregressive-compatible framework for inference-time token reduction. Our method introduces three key innovations: (1) an entropy-aware mechanism to estimate local input complexity and determine dynamic token budgets; (2) a saliency-guided token merging strategy based on mass-weighted averaging of semantically redundant tokens; and (3) a compact autoregressive prior trained over the merged token sequences to ensure compatibility with downstream generation.

QuickMerge++ is modality-agnostic and plug-and-play: it operates on frozen encoder outputs and applies to text, image, and video inputs alike. Unlike fixed-length quantization or manual patching, it enables adaptive compression conditioned on semantic density. Empirical results across multiple benchmarks demonstrate that QuickMerge++ achieves up to 3× token reduction with minimal or no drop in generation quality.

Our contributions are summarized as follows:

- We identify the mismatch between token-level redundancy and autoregressive decoding, motivating a saliency-aware merging strategy.

- We propose QuickMerge++, a general-purpose framework that combines entropy-based budgeting, norm-weighted merging, and AR-compatible modeling.

- We validate our approach across modalities, showing consistent improvements in efficiency–accuracy trade-offs on long-context generation tasks.

[1]Yale University [2]Columbia University. Correspondence to: Dong Liu <dong.liu.dl2367@yale.edu>.

Proceedings of the 42nd International Conference on Machine Learning, Vancouver, Canada. PMLR 267, 2025. Copyright 2025 by the author(s).

2. Related Work

2.1. Tokenization for Vision, Language, and Video

Tokenization forms the foundation for modern generative models across modalities. In vision, ViT (Dosovitskiy et al., 2020) and VideoMAE (Tong et al., 2022) adopt patch-based tokenization, splitting inputs into fixed-size grids. While simple and effective, these approaches produce a rigid number of tokens regardless of content complexity.

Quantization-based methods like VQ-VAE (Van Den Oord et al., 2017) and its extensions introduce discrete latent representations by learning a codebook. However, they suffer from fixed vocabulary size, mode collapse, and are difficult to align with autoregressive generation.

In language modeling, token-free methods such as ByT5 (Xue et al., 2022) and Charformer (Tay et al., 2021) eliminate subword tokenization altogether, directly modeling raw byte or character sequences. Besides, there are also contemporary toolbox such as LLMEasyQuant (Liu et al., 2024a) and TensorRT (Davoodi et al., 2019) for easy-to-use quantization on languange models. While conceptually elegant, these approaches often require deeper models or extensive training to match subword-level performance.

2.2. Dynamic and Learned Token Selection

Dynamic tokenization aims to adaptively select salient inputs based on task or context. TokenLearner (Ryoo et al., 2021) introduces learned soft-attention pooling to produce a compact set of tokens for vision tasks. Despite its flexibility, it lacks autoregressive alignment and enforces a fixed output size.

LARP (Wang et al., 2024) addresses autoregressive generation by introducing a learned prior over discrete tokens for video. It aligns tokenization with AR objectives but is specific to video and assumes an encoder-decoder structure.

QuickMerge draws inspiration from these efforts but differs in three key ways: it supports variable token budgets, operates at inference time with no retraining, and integrates seamlessly with any backbone.

2.3. Efficient Learning and System Optimization

In parallel with tokenization and compression research, recent advances in efficient learning systems highlight orthogonal strategies for accelerating inference and improving scalability.

HADES (Yang et al., 2024) introduces hardware-accelerated speculative decoding tailored for large language models, enabling low-latency generation via speculative sampling and early validation. Similarly, system-level studies such as (Jin & Yang, 2025; Ji & Luo, 2025) explore elastic scaling and self-healing inference pipelines in cloud-based environments, crucial for production-scale deployment of autoregressive models.

From the learning algorithm side, MT2ST (Liu & Yu, 2024) and model fusion frameworks (Liu et al., 2025) aim to unify task-agnostic and task-specific capabilities under minimal retraining. These directions are complementary to Quick-Merge, which focuses on inference-time adaptation without altering model weights.

Federated and collaborative learning efforts such as AppFL (Li et al., 2024) and privacy-preserving cloud systems (Luo & Ji, 2025) push the boundary of distributed and privacy-aware inference. Their compression-aware infrastructure can benefit from adaptive token reduction modules like QuickMerge to reduce bandwidth and latency.

More broadly, recent works on data augmentation (Yang et al., 2025; Liu & Jiang, 2024), model compression (Liu, 2024), and retrieval acceleration (Liu et al., 2024b) all signal the growing importance of plug-and-play modules that integrate with large models without retraining.

QuickMerge situates itself within this efficient learning paradigm by offering a unified, lightweight, and modality-agnostic token reducer that complements both architectural and system-level optimizations.

2.4. Token Merging and Compression

Recent studies have explored reducing token count via pruning and merging. DynamicViT (Rao et al., 2021) prunes low-importance tokens progressively throughout layers. TokenFusion (Kim et al., 2024) merges nearby visual tokens with similar content to accelerate ViT models.

However, these methods typically require training-time modifications or degrade performance in generation settings. In contrast, QuickMerge provides a plug-and-play module that performs token merging based on entropy and norm-based scores, and maintains compatibility with autoregressive decoding through a lightweight transformer prior.

Our method can be interpreted as a synthesis of token compression, semantic selection, and autoregressive alignment, suitable for text, image, and video modalities under a unified framework.

3. Methodology

We propose **QuickMerge++**, an token compression framework for generative model acceleration, building on three major innovations: (1) multi-scale entropy-aware token saliency estimation, (2) structure-preserving saliency-guided token fusion with differentiable selection, and (3) autoregressive prior alignment with bidirectional predictive

consistency.

3.1. Problem Setup

Given input embeddings $X \in \mathbb{R}^{B \times N \times D}$ from a frozen encoder, the goal is to obtain a compressed sequence $\tilde{X}_i \in \mathbb{R}^{K_i \times D}$ with $K_i \ll N$, where:

$$\tilde{X}_i = g(X_i), \quad \text{s.t. } K_i \leq K_{\max}$$

The compression must preserve semantic fidelity and remain compatible with autoregressive generation.

3.2. Step 1: Multi-Scale Entropy-Aware Saliency

To capture rich token importance, we compute both local and global attention sharpness. Let $A^{(l)}$ be the attention matrix at layer l:

$$A^{(l)} = \text{softmax}\left(\frac{X^{(l)}(X^{(l)})^\top}{\sqrt{D}}\right), \tag{1}$$

$$H_i^{(l)} = -\sum_{j=1}^{N} A_{ij}^{(l)} \log A_{ij}^{(l)} \tag{2}$$

We then aggregate attention entropy across L layers:

$$s_i = \frac{1}{L} \sum_{l=1}^{L} \text{norm}(H_i^{(l)})$$

where $\text{norm}(\cdot)$ denotes min-max normalization. This multi-scale entropy serves as the saliency signal.

3.3. Step 2: Differentiable Saliency-Guided Merging

To improve merge quality and trainability, we use Gumbel-softmax to softly select salient tokens:

$$\pi_i = \frac{\exp((s_i + g_i)/\tau)}{\sum_j \exp((s_j + g_j)/\tau)} \tag{3}$$

$$M_i \sim \text{Gumbel-Softmax}(\pi_i) \tag{4}$$

We define the foreground mass:

$$\tilde{m}_i = M_i \cdot s_i + (1 - M_i) \cdot \epsilon, \quad \text{for small } \epsilon > 0$$

Then, each token is assigned to a group $\mathcal{G}_i$ via structural clustering (e.g., KNN or hierarchical merging using cosine similarity). Merging proceeds as:

$$x_i' = \sum_{j \in \mathcal{G}_i} \frac{\tilde{m}_j x_j}{\sum_{j' \in \mathcal{G}_i} \tilde{m}_{j'}}, \quad \tilde{x}_i = x_i'$$

3.4. Step 3: Bidirectional AR Prior Training

We learn a bidirectional AR prior $(f_\rightarrow, f_\leftarrow)$ to align compressed token trajectories:

$$\mathcal{L}_{\text{forward}} = \sum_{t=1}^{K-1} \|f_\rightarrow(\tilde{x}_{\leq t}) - \tilde{x}_{t+1}\|^2 \tag{5}$$

$$\mathcal{L}_{\text{backward}} = \sum_{t=2}^{K} \|f_\leftarrow(\tilde{x}_{\geq t}) - \tilde{x}_{t-1}\|^2 \tag{6}$$

Total loss:

$$\mathcal{L}_{\text{AR}} = \mathcal{L}_{\text{forward}} + \mathcal{L}_{\text{backward}}$$

3.5. Step 4: Compression-Aware Fidelity Constraint

To ensure reconstruction fidelity, we impose a norm-aware constraint:

$$\gamma = \frac{\sum_{i \in \text{TopK}(\|x_i\|)} \|x_i\|}{\sum_{i=1}^{N} \|x_i\|}, \quad \|X - \tilde{X}_{\text{pad}}\|_F^2 \leq (1-\gamma)^2 \|X\|_F^2$$

3.6. Inference Pipeline

Algorithm 1 QuickMerge++ Inference with Saliency Merging and AR Prior

---

Require: Token embeddings $X \in \mathbb{R}^{N \times D}$, AR prior f_θ, temperature τ, max token count $K_{\max}$

1: # Compute multi-scale entropy-based saliency
2: **for** each attention layer l **do**
3: $\quad A^{(l)} \leftarrow \text{softmax}(X^{(l)}(X^{(l)})^\top/\sqrt{D})$
4: $\quad H_i^{(l)} \leftarrow -\sum_j A_{ij}^{(l)} \log A_{ij}^{(l)} \quad \forall i$
5: **end for**
6: $s_i \leftarrow \frac{1}{L} \sum_l \text{Normalize}(H_i^{(l)}) \quad \forall i$
7: # Saliency normalization and Gumbel-softmax sampling
8: $g_i \sim \text{Gumbel}(0, 1)$
9: $\pi_i \leftarrow \text{softmax}\left(\frac{s_i + g_i}{\tau}\right)$
10: $M_i \leftarrow \text{GumbelSoftmaxSample}(\pi_i)$
11: # Token mass for merge weighting
12: $\tilde{m}_i \leftarrow M_i \cdot s_i + (1 - M_i) \cdot \epsilon$
13: # Structure-aware clustering for token grouping
14: $\{\mathcal{G}_1, \ldots, \mathcal{G}_K\} \leftarrow \text{Cluster}(X, \tilde{m}, K = K_{\max})$
15: # Saliency-weighted token merging
16: **for** each group $\mathcal{G}_i$ **do**
17: $\quad \tilde{x}_i \leftarrow \sum_{j \in \mathcal{G}_i} \frac{\tilde{m}_j x_j}{\sum_{j' \in \mathcal{G}_i} \tilde{m}_{j'}}$
18: **end for**
19: $\tilde{X} \leftarrow \{\tilde{x}_1, \ldots, \tilde{x}_K\}$
20: # Autoregressive prior rollout over compressed tokens
21: **for** $t = 1$ **to** $K-1$ **do**
22: $\quad \hat{x}_{t+1} \leftarrow f_\theta(\tilde{x}_1, \ldots, \tilde{x}_t)$
23: **end for**
24: **return** Compressed AR-compatible token sequence $\tilde{X}$

---

4. Experiments

We conduct extensive experiments to evaluate **Quick-Merge++** across *text*, *image*, and *video* modalities. Our experiments are designed to answer the following:

Q1. Can QuickMerge++ reduce token count while preserving generation quality?

Q2. What is the contribution of each component: entropy-based budgeting, saliency-guided merging, and autoregressive (AR) prior?

Q3. How efficient is QuickMerge++ in terms of runtime, memory, and compression trade-offs?

4.1. Setup and Metrics

Datasets. We evaluate across modalities: WikiText-103 (Merity et al., 2016), ImageNet-1K (Deng et al., 2009), and UCF101 (Soomro et al., 2012), and extend to long-context tasks: BookSum (Kryściński et al., 2021), Ego4D-NLQ (Grauman et al., 2022).

Metrics. We use task-specific quality metrics: PPL (text), accuracy (image), FVD (video), ROUGE / mAP (long-context). Efficiency is assessed via compression rate (K/N), decoding latency, and KV memory cost.

Model. A 6-layer Transformer decoder (hidden size 512) is trained with fixed pretrained encoders (BERT, ViT, Video-MAE). QuickMerge++ dynamically selects tokens with entropy threshold $\alpha = 0.45$ and norm masking. Results are averaged over 3 seeds.

4.2. Overall Performance (Q1)

Table 1. QuickMerge++ improves performance while compressing input tokens. Values are mean ± std over 3 runs.

Method	PPL ↓	Acc ↑	FVD ↓	CompRate ↑
Fixed Patches	21.4	76.2	108.4	1.00×
VQ-VAE	19.8	74.9	97.2	1.31 × ±0.02
Token-Free	17.9	76.3	89.7	2.08 × ±0.05
TokenLearner	18.6	77.0	94.1	1.83 × ±0.04
QuickMerge++	**17.1**	**78.1**	**85.6**	**2.37 × ±0.06**

QuickMerge++ consistently achieves stronger results with fewer tokens. On average, it yields $2.37\times$ compression with up to 4.3% relative improvement in accuracy or quality, confirming Q1. The token budget adapts to sequence complexity—e.g., longer sequences yield higher savings (Table 3).

4.3. Component Analysis (Q2)

We ablate each component in QuickMerge++:

Table 2. Component-wise ablation (averaged across all tasks).

Variant	PPL ↓	Acc ↑	FVD ↓
Full Model	**17.1**	**78.1**	**85.6**
– Entropy Budgeting	18.4	76.5	91.0
– AR Prior	17.9	76.9	88.3
– Norm Masking	18.7	75.2	93.5

Each module is necessary: removing entropy control increases overcompression variance; removing the AR prior impairs temporal alignment; removing norm masking merges semantically irrelevant tokens. This supports Q2.

4.4. Efficiency and Scaling (Q3)

We benchmark runtime and memory usage in autoregressive generation. Experiments are run on an NVIDIA A100 (batch size 32):

Table 3. Efficiency metrics of QuickMerge++.

Metric	Baseline	QuickMerge++	Rel. Change
Latency (ms)	6.3	4.1	−34.9%
KV Memory (MB)	1120	412	−63.2%
Tokens (mean)	128	54	−57.8%

QuickMerge++ significantly reduces decoding latency and memory load with only minor preprocessing overhead ($+1.6$ ms). These results confirm Q3.

4.5. Extended Benchmarks

Long-Context. On BookSum (text summarization) and Ego4D-NLQ (video QA), QuickMerge++ reduces token count by 2.4–$2.7\times$ while improving ROUGE-L and mAP:

Table 4. QuickMerge++ results on long-context benchmarks. It improves quality metrics while significantly reducing token count.

Task	Metric	Baseline	QuickMerge++	Improve
	Quality (↑)			
BookSum	ROUGE-L	36.2	**37.1**	+0.9
Ego4D-NLQ	mAP@0.5	38.6	**40.3**	+1.7
	Token Count (↓)			
BookSum	Tokens	4096	**1682 ± 33**	−58.9%
Ego4D-NLQ	Tokens	2048	**821 ± 25**	−59.9%

Cross-Task Transfer. We evaluate QuickMerge++ (no retraining) on MSCOCO, Something-Something-v2, TVQA,

and QASPER. Compression rates fluctuate based on input entropy:

Table 5. Generalization across unseen tasks.

Task	Metric ↑	QMerge++ / Baseline	Compression
MSCOCO	BLEU-4	36.0 / 35.7	2.21 ± 0.07
SSv2	Accuracy	53.8 / 53.1	2.06 ± 0.05
TVQA	QA Acc	71.5 / 71.2	1.92 ± 0.06
QASPER	F1	76.4 / 75.9	2.35 ± 0.04

Compression adapts to complexity without hurting performance—validating QuickMerge++ as a plug-in token reducer.

4.6. Conclusion

QuickMerge++ provides a general, adaptive, and efficient token merging strategy across domains. By leveraging entropy-guided budgeting, norm-based saliency, and autoregressive priors, it reduces token count by $2.0\text{--}2.5\times$ while preserving or improving task performance and reducing compute cost. All three research questions (Q1–Q3) are affirmatively answered.

5. Conclusion

We present **QuickMerge++**, a lightweight and modality-agnostic framework for token reduction in generative modeling. By integrating entropy-aware token budgeting, saliency-guided merging, and autoregressive prior alignment, QuickMerge++ provides a principled solution to the growing inefficiency of dense token sequences. Extensive experiments across text, image, and video domains demonstrate that QuickMerge++ achieves significant token compression while maintaining or improving generation quality. Furthermore, it generalizes effectively across tasks and domains without retraining. These results suggest that adaptive token merging—grounded in semantic salience and generative compatibility—can serve as a key building block in the next generation of efficient autoregressive systems.

In future work, we plan to integrate QuickMerge++ with streaming decoders, long-context memory modules, and multi-agent generative systems to further expand its scalability and applicability.

References

Davoodi, P., Gwon, C., Lai, G., and Morris, T. Tensorrt inference with tensorflow. In *GPU Technology Conference*, 2019.

Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., and Fei-Fei, L. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Grauman, K., Westbury, A., Byrne, E., Chavis, Z., Furnari, A., Girdhar, R., Hamburger, J., Jiang, H., Liu, M., Liu, X., et al. Ego4d: Around the world in 3,000 hours of egocentric video. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 18995–19012, 2022.

Ji, C. and Luo, H. Cloud-based ai systems: Leveraging large language models for intelligent fault detection and autonomous self-healing. *arXiv preprint arXiv:2505.11743*, 2025.

Jin, Y. and Yang, Z. Scalability optimization in cloud-based ai inference services: Strategies for real-time load balancing and automated scaling. *arXiv preprint arXiv:2504.15296*, 2025.

Kim, M., Gao, S., Hsu, Y.-C., Shen, Y., and Jin, H. Token fusion: Bridging the gap between token pruning and token merging. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1383–1392, 2024.

Kryściński, W., Rajani, N., Agarwal, D., Xiong, C., and Radev, D. Booksum: A collection of datasets for long-form narrative summarization. *arXiv preprint arXiv:2105.08209*, 2021.

Li, Z., He, S., Yang, Z., Ryu, M., Kim, K., and Madduri, R. Advances in appfl: A comprehensive and extensible federated learning framework. *arXiv preprint arXiv:2409.11585*, 2024.

Liu, D. Contemporary model compression on large language models inference. *arXiv preprint arXiv:2409.01990*, 2024.

Liu, D. and Jiang, M. Distance recomputator and topology reconstructor for graph neural networks. *arXiv preprint arXiv:2406.17281*, 2024.

Liu, D. and Yu, Y. Mt2st: Adaptive multi-task to single-task learning. *arXiv preprint arXiv:2406.18038*, 2024.

Liu, D., Jiang, M., and Pister, K. Llmeasyquant–an easy to use toolkit for llm quantization. *arXiv preprint arXiv:2406.19657*, 2024a.

Liu, D., Waleffe, R., Jiang, M., and Venkataraman, S. Graph-snapshot: Graph machine learning acceleration with fast storage and retrieval. *arXiv preprint arXiv:2406.17918*, 2024b.

Liu, Z., Yang, Z., Lin, X., Qiu, R., Wei, T., Zhu, Y., Hamann, H., He, J., and Tong, H. Breaking silos: Adaptive model fusion unlocks better time series forecasting. *arXiv preprint arXiv:2505.18442*, 2025.

Luo, H. and Ji, C. Cross-cloud data privacy protection: Optimizing collaborative mechanisms of ai systems by integrating federated learning and llms. *arXiv preprint arXiv:2505.13292*, 2025.

Merity, S., Xiong, C., Bradbury, J., and Socher, R. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Rao, Y., Zhao, W., Liu, B., Lu, J., Zhou, J., and Hsieh, C.-J. Dynamicvit: Efficient vision transformers with dynamic token sparsification. *Advances in neural information processing systems*, 34:13937–13949, 2021.

Ryoo, M. S., Piergiovanni, A., Arnab, A., Dehghani, M., and Angelova, A. Tokenlearner: What can 8 learned tokens do for images and videos? *arXiv preprint arXiv:2106.11297*, 2021.

Soomro, K., Zamir, A. R., and Shah, M. Ucf101: A dataset of 101 human actions classes from videos in the wild. *arXiv preprint arXiv:1212.0402*, 2012.

Tay, Y., Tran, V. Q., Ruder, S., Gupta, J., Chung, H. W., Bahri, D., Qin, Z., Baumgartner, S., Yu, C., and Metzler, D. Charformer: Fast character transformers via gradient-based subword tokenization. *arXiv preprint arXiv:2106.12672*, 2021.

Tong, Z., Song, Y., Wang, J., and Wang, L. Videomae: Masked autoencoders are data-efficient learners for self-supervised video pre-training. *Advances in neural information processing systems*, 35:10078–10093, 2022.

Van Den Oord, A., Vinyals, O., et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

Wang, H., Suri, S., Ren, Y., Chen, H., and Shrivastava, A. Larp: Tokenizing videos with a learned autoregressive generative prior. *arXiv preprint arXiv:2410.21264*, 2024.

Xue, L., Barua, A., Constant, N., Al-Rfou, R., Narang, S., Kale, M., Roberts, A., and Raffel, C. Byt5: Towards a token-free future with pre-trained byte-to-byte models. *Transactions of the Association for Computational Linguistics*, 10:291–306, 2022.

Yang, Q., Ji, C., Luo, H., Li, P., and Ding, Z. Data augmentation through random style replacement. *arXiv preprint arXiv:2504.10563*, 2025.

Yang, Z., Jin, Y., and Xu, X. Hades: Hardware accelerated decoding for efficient speculation in large language models. *arXiv preprint arXiv:2412.19925*, 2024.