Reliable Active Learning via Influence Functions

Abstract

Due to the high cost and time-consuming nature of collecting labeled data, having insufficient labeled data is a common challenge that can negatively impact the performance of deep learning models when applied to real-world applications. Active learning (AL) aims to reduce the cost and time required for obtaining labeled data by selecting valuable samples during model training. However, recent works have pointed out the performance unreliability of existing AL algorithms for deep learning (DL) architectures under different scenarios, which manifests as their performance being comparable (or worse) to that of basic random selection. This behavior compromises the applicability of these approaches. We address this problem by proposing a theoretically motivated AL framework for DL architectures. We demonstrate that the most valuable samples for the model are those that, unsurprisingly, improve its performance on the entire dataset, most of which is unlabeled, and present a framework to efficiently estimate such performance (or loss) via influence functions, pseudo labels and diversity selection. Experimental results show that the proposed *reliable active learning via influence functions* (RALIF) can consistently outperform the random selection baseline as well as other existing and state-of-the art active learning approaches.

1 Introduction

In the last decade, deep learning (DL) models have achieved record-breaking performance on datasets with millions or even billions of samples (Chen et al., 2022; 2023; Jain et al., 2022). However, their broad practical applicability in scenarios where data is scarce has been limited mainly due to the lack of sufficient (and high-quality) labeled data for training. This is often due to the high cost or time-consuming nature of manual labeling (or sample annotation) often requiring subject-matter expertise. Aiming to address this gap in the field, active learning (AL), which has been historically applied to traditional machine learning approaches, emerged as a means to improve the applicability of deep learning models in such scenarios. The main objective of AL is to design strategies to selectively annotate (label) small subsets of a large (unlabeled) dataset so that model performance can be maximized while controlling the cost associated with annotations (Settles, 2009; Sener & Savarese, 2017). It is worth noting that there are also situations where both data (*e.g.*, images) and labels are scarce, however, such scenario is outside of the scope of this work.

Early AL algorithms (Lewis & Gale, 1994; Dagan & Engelson, 1995; McCallum et al., 1998; Tong & Koller, 2001) were originally developed for traditional machine learning models, such as logistic regression (Kleinbaum et al., 2002), support vector machines (SVMs) (Hearst et al., 1998), or naive Bayes classifiers (Rish et al., 2001). Unfortunately, applying these algorithms directly to deep neural networks is challenging because they rely on unique characteristics of traditional machine learning models (*e.g.*, the convexity of their learning objective), and the widely known, but incompatible, need for large datasets when training DL models. As an example of the former, Tong & Koller (2001) leveraged the *version space duality* in SVMs consisting in that each training sample corresponds to a hyperplane in the version (solution) space of SVMs (Vapnik, 1999; Herbrich et al., 2001), and aimed to select and label samples that have the most significant impact on shrinking such solution space, which is a sensible approach considering that SVMs are known to have a *unique* optimum classification hyperplane. Unfortunately, there is no theoretical basis or direct evidence to support the assumption that each sample in a deep neural network corresponds to a hyperplane in their solution space. In fact, neural networks have in general non-convex optimization objectives known for not yielding a unique global optimum, and instead being overwhelmed by local optima.

Figure 1: The basic reliable active learning via influence functions (RALIF) framework. Starting with a small labeled dataset and a much larger unlabeled dataset, at each selection cycle, we first train the target DL model with the labeled dataset and generate pseudo labels for the entire unlabeled dataset using the trained target DL model. We then use the selection mechanism based on influence functions to rank the most likely useful samples from the unlabeled dataset, query the oracle to obtain the true labels for the top K ranked samples, and update the labeled and unlabeled datasets accordingly. This process is repeated for a fixed number of cycles or until the labeling budget has been spent or performance target has been achieved.

In contrast, numerous DL-based AL algorithms have been proposed specifically for deep learning models (Gal et al., 2017; Beluch et al., 2018; Sinha et al., 2019; Yoo & Kweon, 2019; Wang et al., 2022). While DL-based AL algorithms have demonstrated strong performance in some scenarios, recent work by Ash et al. (2019); Munjal et al. (2022); Wang et al. (2022) revealed the performance unreliability of many DL-based AL methods across different scenarios. Specifically and quite often, existing DL-based AL algorithms (Wang & Shang, 2014; Sener & Savarese, 2017; Gal et al., 2017; Sinha et al., 2019) fail to consistently outperform the most basic (no skill) random AL selection mechanism, which assumes that all (unlabeled) samples are equally likely to improve the performance of the model if labeled and added to the training set. This unreliability undermines their applicability and adoption, particularly in situations when labeling costs are high.

Motivated by such findings, we propose a more reliable AL algorithm for DL architectures we call *reliable active learning via influence functions* (RALIF), which benefits from a theoretically grounded selection mechanism that increases the likelihood of selecting samples that will yield performance improvements when labeled and included in dataset used for model training. The RALIF framework illustrated in Figure 1 introduces a new objective for AL that leverages the concept of *influence function* (Hampel, 1974) to make the sample selection process more efficient. Specifically, Koh & Liang (2017) showed that influence functions can approximate the changes in model parameters caused by incorporating new samples into the training dataset, but without the need for explicitly retraining the deep neural network. This enables RALIF, in principle, to efficiently quantify the generalization ability of a model by estimating the influence of new samples on the complete-dataset performance, thus enabling informed decisions during the AL sample selection process. Our contribution consists on leveraging pseudo labels to repurpose these influence functions for the AL case where labels are not available for most of the dataset. Experimental results on three datasets (CIFAR10, FICAR100 and iNaturalist) demonstrate that RALIF achieves consistent and superior performance compared to random selection (as a no-skill baseline), as well as existing AL approaches across various practical scenarios, thus providing strong empirical evidence of the reliability and effectiveness of RALIF.

The rest of this paper is organized as follows, in Section 2 we discuss the related work in the context of the RALIF framework. In Section 3, we provide a detailed description of the notation used in this paper and define the standard setting for a (sequential) AL algorithms. In Section 4, we introduce the proposed AL objective and describe the strategies we employ to implement RALIF with deep learning neural networks. Subsequently, in Section 5, we present the results of our experiments, which highlight the performance reliability of the proposed AL framework across different scenarios, and conclude in Section 6 with a discussion and directions for future work.

2 Related Work

AL for traditional machine learning models Among the early AL algorithms, *uncertainty* sampling stands out as one of the most commonly used. This strategy aims to selecting samples for which predictions with the model trained on the current labeled dataset exhibit the highest uncertainty. The rationale behind this approach is that selecting samples with uncertain predictions is believed to provide additional information to the model that can likely improve its performance relative to the current version of the trained model. For example, Lewis & Gale (1994) introduced a probabilistic binary classifier that utilized a bag-of-words representation for text data and proposed selecting samples with posterior predictive probabilities close to the decision boundary. In another example involving multi-class text classification tasks, Settles & Craven (2008) suggested selecting samples for which the entropy of the predicted outputs of a conditional random field (Lafferty et al., 2001) is high, as a proxy for uncertainty.

Another popular early introduced AL strategy is *query-by-committee* (Seung et al., 1992). This approach consists of constructing a committee of models trained on a labeled dataset. The selection process typically involves choosing samples that elicit the most diverse or heterogeneous predictions among the committee members. Importantly, constructing the committee is a key aspect of this approach. For instance, McCallum et al. (1998) constructed the committee by training a naive Bayes classifier with a labeled text dataset and sampled multiple naive Bayes classifier instances from the posterior distribution of the trained parameters. Alternatively, Dagan & Engelson (1995) trained a hidden Markov model (HMM) (Rabiner, 1989) with a labeled text dataset and constructed the committee by sampling a collection of HMMs based on the posterior distribution of the trained HMM parameters. Moreover, there are several other early AL strategies, such as *Variance Reduction* (Cohn et al., 1996) or *Fisher Information Ratio* (Zhang & Oles, 2000), which aim to minimize the expected generalization error of the model by selecting unlabeled samples that minimize the variance or the Fisher information ratio estimated for the model including such samples. See Settles (2009) for a comprehensive overview of these methods.

AL for deep neural networks Over the past few years, an abundance of DL-based AL algorithms have been proposed, most of which can be categorized into three main strategies, namely, *i*) based on uncertainty (Wang & Shang, 2014; Beluch et al., 2018), *ii*) based on diversity (Sener & Savarese, 2017; Geifman & El-Yaniv, 2017), and *iii*) hybrid approaches (Lughofer, 2012; Ash et al., 2019; Wu et al., 2021).

Uncertainty-based AL algorithms for DL architectures built upon the ideas of the early uncertainty sampling strategies for AL (Hwa, 2004; Settles & Craven, 2008), where uncertainty is typically estimated by calculating the entropy of the model predictions for each unlabeled sample (Wang & Shang, 2014). In addition to directly using the model's predictions to estimate uncertainty, several other methods have been proposed to estimate the uncertainty of deep neural networks for unlabeled samples. One of such methods, proposed by Gal & Ghahramani (2016), involved applying dropout (Srivastava et al., 2014) before each layer of the neural network. By sampling from the dropout masks, multiple predictions could be obtained for each unlabeled sample. These predictions were then averaged to obtain the final prediction for the sample, and the entropy of the *expected* prediction could be calculated as a measure of uncertainty. Another approach, presented by Beluch et al. (2018), followed a similar framework to Gal & Ghahramani (2016), but used a different method to obtain multiple predictions for unlabeled samples. Instead of using dropout, Beluch et al. (2018) trained multiple models with identical architecture but different random initialization seeds using the same labeled dataset. By obtaining predictions from these independently trained models, multiple predictions for unlabeled samples could be obtained, which could then be used to estimate uncertainty. Note that this approach is more computationally expensive than simply using dropout like in Gal & Ghahramani (2016).

In diversity-based AL algorithms, samples that are representative of the entire dataset distribution are preferred. For instance, in Sener & Savarese (2017), features extracted from the model trained on the labeled dataset were used as representations for the unlabeled samples. Then, their goal was to select a subset (batch) of samples that minimized the maximum distance of any arbitrary sample from the dataset to its nearest selected sample. Similarly, Geifman & El-Yaniv (2017) also used features extracted from the model trained on the labeled dataset as representations for the unlabeled samples. They focused on selecting samples that were farthest away from the labeled dataset. By selecting samples that were farthest from the

labeled dataset, they aimed to capture the most diverse and informative samples that are distinct from those already labeled.

Hybrid strategies typically combine uncertainty and diversity approaches to select samples that are both uncertain and highly representative of the entire unlabeled dataset. For instance, Lughofer (2012) proposed a two-stage hybrid active learning algorithm. In the first stage, they employed the evolving vector quantization approach (Lughofer, 2008) to cluster the data. In the second stage, they selected samples that were either close to the cluster centers (highly representative) or near the boundaries of clusters (highly uncertain). In Ash et al. (2019), a similar approach to the diversity strategy presented in Sener & Savarese (2017) was employed, but with a consideration of the trade-off between uncertainty and diversity. Pseudo labels were generated for the unlabeled samples using the model trained on the labeled dataset, and the gradients of the loss function with respect to the model parameters were computed. The gradients of the unlabeled samples were then used as representations for a clustering algorithm. The first cluster center was selected as the unlabeled sample with the largest norm of gradients (uncertainty), and subsequent centers were selected based on their distance to the nearest center (diversity). Another study by Wu et al. (2021) introduced a hybrid active learning approach using two deep neural networks. One network was trained to estimate the diversity of the unlabeled samples, while the other network estimated the loss for each unlabeled sample. Samples with high diversity (representativeness) and high loss (uncertainty) were then selected for labeling.

There are also AL algorithms specifically designed based on the understanding or techniques specific to deep neural networks. For example, Sinha et al. (2019) leveraged adversarial training to select unlabeled samples that were most dissimilar from labeled samples. Yoo & Kweon (2019) posited that samples with the largest loss indicated the largest informativeness, thus they trained a module to estimate loss for unlabeled samples, then selected samples with the largest predicted loss. More recently, Wang et al. (2022) proved that samples that mostly change the DNN weights were most useful, and accordingly, they selected samples that generated the largest approximate gradients.

Reliability in active learning   While most AL algorithms for traditional machine learning models with convex objectives enjoy theoretical guarantees for their performance (Tong & Koller, 2001; Brinker, 2003; He et al., 2004), this is in general not the case for DL-based AL algorithms. For instance, uncertainty- and DL-based AL algorithms (Wang & Shang, 2014; Gal et al., 2017) have been shown to perform comparably to basic random selection in several scenarios (Sener & Savarese, 2017), whereas the performance of Wang & Shang (2014) was even slightly worse than random selection in the early stages of the AL selection process (Ash et al., 2019). Studies by Yoo & Kweon (2019) and Wang et al. (2022) revealed that DL-based AL algorithms with theoretical support, such as Sener & Savarese (2017) and Gal et al. (2017), also failed to consistently outperform random selection. Further, experiments conducted by Munjal et al. (2022) demonstrated that many DL-based AL algorithms, including Wang & Shang (2014); Sener & Savarese (2017); Gal et al. (2017); Sinha et al. (2019), exhibited inconsistent performance when compared to random selection under the same experimental conditions. In their experiments, the conditions referred to applying these algorithms on the same datasets, using the same classification model, and employing the same sample selection size at each active learning selection cycle; all of this to make comparisons easier and fairer.

This reported inconsistency in performance undermines the applicability and adoption of AL algorithms in real-world scenarios. Therefore, we are motivated to propose a DL-based AL algorithm that is not only theoretically grounded, but also demonstrates reliable performance across various AL selection scenarios, *e.g.*, different datasets, model architectures and selected sample size (batch size) in each AL selection cycle.

3   Problem Definition (Active Learning)

We consider a hypothetical multi-class classification dataset $D = \{(x_i, y_i)\}_{i=1}^{n}$, where n is the total number of samples, $x_i \in \mathcal{X}$ represents an input sample (*e.g.*, images in our experiments), and $y_i \in \mathcal{Y} = \{1, ...K\}$ represents its corresponding class label, which is not available for the majority of the dataset D. In active learning, we begin with a small labeled subset $L_0 = \{(x_i, y_i)\}_{i=1}^{m_0}$ containing $m_0 \ll n$ labeled samples. The remaining samples, which are unlabeled, are denoted as the set $U_0 = \{x_j\}_{j=m_0+1}^{n}$. Importantly, in active learning (AL), we do not have access to the true labels of the samples in U_0, denoted as $U_0^Y = \{y_j | x_j \sim$

$U_0\}_{j=m_0+1}^n$. Let M denote a classification learner, *e.g.*, a deep neural network, and let M_{L_0} denote the learner M trained with labeled dataset L_0. Further, $l(\cdot, \cdot; M) : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}$ denotes the loss function used during the training process, *e.g.*, the standard cross-entropy loss for classification tasks.

In each AL selection cycle c (full model training iteration), a sequential AL algorithm selects a single sample $x_s \sim U_{c-1}$ from the unlabeled set U_{c-1} at cycle $c-1$, and queries its true label y_s with an oracle function[1], resulting in a new labeled dataset $L_c = L_{c-1} \cup (x_s, y_s)$. The most basic (*no skill*) strategy for AL is random selection, where a sample x_s is randomly chosen from U_{c-1} and its true label is queried; this is denoted as the *Random* strategy. Arguably the most common baseline strategy is the *Uncertainty* strategy, which selects the sample x_s from U_{c-1} with the largest predictive uncertainty under the current model $M_{L_{c-1}}$. Such uncertainty is quantified in terms of the entropy (Shannon, 1948). A more detailed information about these two strategies can be found in Section 5.

4 Reliable Sample Selection for Active Learning

We propose a selection strategy that aims to pick samples from the unlabeled set U_{c-1}, denoted as $x_s \sim U_{c-1}$, such that the loss of M_{L_c} on the entire set D is minimized. This objective reflects the goal of improving the generalization performance of M_{L_c} on the entire dataset D, which in turn is a proxy for its generalization ability. Formally then, the objective of the sequential AL algorithm in each cycle c can be formulated as

$$\underset{x_s \sim U_{c-1}}{\arg\min} \; \mathbb{E}_{(x_i, y_i) \sim D}[l(x_i, y_i; M_{L_c})] = \frac{1}{n} \sum_{i=1}^n l(x_i, y_i; M_{L_c}). \tag{1}$$

There are two key barriers preventing us from using (1) directly, namely, *i*) at cycle c we do not have access to the label for x_s to be able to obtain M_{L_c} via labeled set $L_c = L_{c-1} \cup (x_s, y_s)$, and *ii*) we do not have access to most of the labels in D, but only to those in L_{c-1}.

Below, we describe how we propose approximating (1) to use it as a means to select samples that are likely to improve the generalization performance of the model M_{L_c} on D. Specifically, we will introduce a variant objective based on (1) as a modification to the original AL objective, which underscores the issue concerning lacking most of the labels in D. Then, we will propose strategies to address the practical implementation challenges that arise when applying such an objective variant in practice. More precisely, we will address the challenges associated with lacking labels for most samples and the expensive selection process resulting due to the time-consuming nature of DL model training. Finally, we motivate the need for selecting multiple samples (a batch) in each cycle in the context of deep learning. Taken together, the objective, implementation strategies and batch selection constitute the proposed RALIF which is conceptually summarized in Figure 1.

4.1 AL Objective Revisited

We can readily derive the following upper bound for (1):

$$
\begin{aligned}
\mathbb{E}_{(x_i, y_i) \sim D}[l(x_i, y_i; M_{L_c})] &= \frac{1}{n} \sum_{i=m_c+1}^n l(x_i, y_i; M_{L_c}) + \frac{1}{n} \sum_{i=1}^{m_c} l(x_i, y_i; M_{L_c}) \\
&\leq \frac{1}{n-m_c} \sum_{i=m_c+1}^n l(x_i, y_i; M_{L_c}) + \frac{1}{m_c} \sum_{i=1}^{m_c} l(x_i, y_i; M_{L_c}) \\
&= \underbrace{\mathbb{E}_{(x_i \sim U_c, y_i \sim U_c^Y)}[l(x_i, y_i; M_{L_c})]}_{\text{Unlabeled subset loss}} + \underbrace{\mathbb{E}_{(x_i, y_i) \sim L_c}[l(x_i, y_i; M_{L_c})]}_{\text{Training loss}},
\end{aligned}
\tag{2}
$$

in which we made explicit that the labels for U_c denoted as U_c^Y are not available in practice. From (2) we see that for the purpose of selecting $x_s \sim U_{c-1}$ via $\mathbb{E}_{(x_i, y_i) \sim D}[l(x_i, y_i; M_{L_c})]$, the training loss becomes irrelevant (a constant), so it can be safely ignored. Therefore, we can use the following objective in place of (1):

$$\underset{x_s \sim U_{c-1}}{\arg\min} \; \mathbb{E}_{(x_i \sim U_c, y_i \sim U_c^Y)}[l(x_i, y_i; M_{L_c})], \tag{3}$$

---

[1]In practice, this is replaced by a human or expert observing the sample and producing the label of interest.

however, akin to that in (1), the label y_s and label set U_c^Y are not available. In order to tackle this problem, below we present Theorem 1 that bridges the gap between a practical but estimated loss and the inaccessible but actual loss.

Theorem 1. *Given the true data joint distribution $p_X p_{Y|X}$, where $\mathcal{X}$ is the input space and $\mathcal{Y}$ is the label space, and an estimated data joint distribution $p_X \tilde{p}_{Y|X}$ (assuming we can access the input distribution p_X but not the true label conditional $p_{Y|X}$), any positive and bounded loss function $l(\cdot, \cdot; M) : \mathcal{X} \times \mathcal{Y} \mapsto [0, L]$ for model M must satisfy*

$$\mathbb{E}_{(x,y) \sim p_X p_{Y|X}} l(x, y; M) \leq \mathbb{E}_{(x,\tilde{y}) \sim p_X \tilde{p}_{Y|X}} l(x, \tilde{y}; M) + 2L \cdot \delta_{TV}(p_X p_{Y|X}, p_X \tilde{p}_{Y|X}), \tag{4}$$

where $\delta_{TV}(\cdot, \cdot)$ denotes the total variation difference between two distributions.

The detailed proof for Theorem 1 can be found in Appendix A.1. Conceptually, Theorem 1 shows that the difference between the estimated and true loss in (4), obtained via $\tilde{p}_{Y|X}$ and $p_{Y|X}$, respectively, is bounded by two terms: *i)* the magnitude, L, of the loss function, and *ii)* the difference between the real and estimated joint distributions via $\delta_{TV}(p_X p_{Y|X}, p_X \tilde{p}_{Y|X})$. In most cases, for instance when using the standard cross-entropy loss for classification, the total variation is bounded by some power r of the norm of the parameters $\|W\|_2^r$, where W denotes all the parameters of the model, which itself is bounded via the use of a regularization term during the training process (Figueiredo, 2001; Figueiredo & Jain, 2001; Figueiredo, 2003). We provide a detailed proof for the cross-entropy loss in Appendix A.1.

With regard to the second term involving $\delta_{TV}(\cdot, \cdot)$, we propose to generate pseudo labels from $M_{L_{c-1}}$ as a means to intrinsically and effectively sample from the estimated label conditional distribution $\tilde{p}_{Y|X}$ implied by $M_{L_{c-1}}$. Conveniently, for the purpose of sample selection, the second term in (4) becomes approximately a constant by assuming that $\delta_{TV}(p_{X \cup x_s} \tilde{p}_{Y|X \cup x_s}, p_{X \cup x_{s'}} \tilde{p}_{Y|X \cup x_{s'}}) \to 0$, where $X \cup x_s$ and $X \cup x_{s'}$ for $x_s \neq x_{s'}$ are used (in a slight abuse of notation) to denote the estimated conditionals with $L_c = L_{c-1} \cup (x_s, y_s)$ and $L_c = L_{c-1} \cup (x_{s'}, y_{s'})$, respectively, which is reasonable as long as m_{c-1} is not too small. Consequently, combining (4) with (3) results in

$$\underset{x_s \sim U_{c-1}}{\arg\min} \; \mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X=x_i})}[l(x_i, \tilde{y}_i; M_{L_c})]. \tag{5}$$

Unlike (3), we can readily evaluate the loss $l(x_i, y_i; M_{L_c})$ on U_c for every sample in U_{c-1}. Below, we will describe how to implement (5) provided that M_{L_c} is not available when selecting $x_s \sim U_{c-1}$.

4.2 Estimating Loss without Retraining

Though the AL selection objective introduced in (5) is theoretically justified, its practical application to deep neural network architectures raises two key issues that need to be addressed. The first issue has to do with *efficiency* in that implementing equation (5) necessitates training M_{L_c} for each data candidate $(x_s \sim U_{c-1}, y_s \sim U_{c-1}^Y)$, resulting in the training of $n - m_{c-1}$ distinct models. Unfortunately, the time-consuming nature of training deep neural networks makes this process highly impractical or even prohibitive in some cases. The second problem associated with *labeling* is that obtaining M_{L_c} for each candidate data requires access to the true label $y_s \sim U_{c-1}^Y$, which is unavailable during AL selection cycles. To address these two issues, we propose the following strategies.

To tackle the efficiency problem due to the need of explicitly training $n - m_{c-1}$ models in each AL selection cycle, we leverage *influence functions* (IL) (Hampel, 1974). Following Koh & Liang (2017), given a trained model $M_{L_{c-1}}$, whose parameters are denoted as $\theta_{M_{L_{c-1}}}$, and a new sample $(x_s \sim U_{c-1}, y_s \sim U_{c-1}^Y)$, the influence of adding (x_s, y_s) into the training dataset L_{c-1} that produced $\theta_{M_{L_{c-1}}}$ can be expressed as:

$$IL(x_s, \theta_{M_{L_{c-1}}}) = -H_{M_{L_{c-1}}}^{-1} \nabla l(x_s, y_s; M_{L_{c-1}}), \tag{6}$$

where $H_{M_{L_{c-1}}} \overset{\text{def}}{=} \frac{1}{m_{c-1}} \sum_{i=1}^{m_{c-1}} \nabla^2 l(x_i, y_i; M_{L_{c-1}})$ is the Hessian of model $M_{L_{c-1}}$. Utilizing (6), Koh & Liang (2017) proved that the parameters $\theta_{M_{L_{c-1} \cup (x_s, y_s)}}$ of $M_{L_{c-1} \cup (x_s, y_s)}$ *i.e.*, M_{L_c} in (5), can be estimated as $\theta_{M_{L_c}} = \theta_{M_{L_{c-1}}} + IL(x_s, \theta_{M_{L_{c-1}}})$. Conveniently, this allows us to efficiently obtain M_{L_c} in (5) without the

need to explicitly train M_{L_c} with $L_{c-1} \cup (x_s, y_s)$ for each data candidate $(x_s \sim U_{c-1}, y_s \sim U_{c-1}^Y)$. Additional details about the theory and efficient implementation of IL can be found in Koh & Liang (2017).

To address the labeling problem associated with lacking access to $y_s \sim U_{c-1}^Y$, we consider three approaches. The first one, which we refer to as *single-IL*, uses pseudo labels generated by $M_{L_{c-1}}$, *i.e.*, by simply replacing y_s with the (most likely) pseudo label $\hat{y}_s = \arg\max\ M_{L_{c-1}}(x_s)$. This can be formulated as

$$\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})] \approx \mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_{c-1}} \cup (x_s, \hat{y}_s))]. \tag{7}$$

Though conceptually simple, this method may introduce severe approximation bias if $y_s \neq \hat{y}_s$. Alternatively, to obtain a relaxed approximation of $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, y_i; M_{L_c})]$ for each x_s, we account for all class labels for each x_s, rather than relying solely on the single most probable (maximum likelihood) class $\hat{y}_s$ in (7). One straightforward approach is to weight all possible classes for x_s using the probabilistic predictions from $M_{L_{c-1}}(x_s)$. We refer to this approach as *expectation-IL* and formulate it as

$$\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})] \approx \sum_{k=1}^{K} p_k(x_s) \cdot \mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_{c-1} \cup (x_s, \tilde{y}_s^k)})], \tag{8}$$

where $\tilde{y}_s^k$ denotes setting the label for x_s as class k, $p_k(x_s)$ is the predicted probability (weight) that x_s is of class k, which is obtained from $M_{L_{c-1}}$, and K is the number of classes. Note that this is conceptually equivalent to considering all possible outcomes for x_s, but weighting them according to how likely they are under the current version of the model, *i.e.*, $M_{L_{c-1}}$.

In practice, we found that (8) has the potentially significant problem that for unlikely classes, $p_k(x_s)$ is likely to be nonzero, thus introducing estimation noise. Moreover, we are mostly interested in classes for which $p_k(x_s)$ is large or at least comparable to $\max\ M_{L_{c-1}}(x_s)$. With this in mind, we propose an alternative solution we call *truncated-IL*, which involves considering several high-probability class labels for each x_s instead of all classes. More formally we write

$$\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})] \approx \sum_{k=1}^{K} \pi(p_k(x_s)) \cdot p_k(x_s) \cdot \mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_{c-1} \cup (x_s, \tilde{y}_s^k)})], \tag{9}$$

from which we see that compared with (8), (9) has a indicator function $\pi(\cdot)$ defined as

$$\pi(p_k(x_s)) = \begin{cases} 1 & \text{if } p_k(x_s) > \tau \\ 0 & \text{otherwise} \end{cases}, \tag{10}$$

where τ is a threshold value set to filter out highly unlikely class assignments for x_s. For all experiments, we set $\tau = \frac{4}{K}$, which we found empirically gives the best overall performance. Nevertheless and for illustration, we provide a comparison of the results obtained by using different values of τ in one specific active learning scenario in Appendix A.3.

Having addressed the challenges involved in implementing (5) that are associated with efficiency and labeling, we have developed a single-sample sequential DL-based AL algorithm. Conceptually, we will rank all unlabeled samples based on their ability to minimize the model loss on the current unlabeled dataset using *single-IL* in (7), *expectation-IL* in (8) or *truncated-IL* in (9), and then select the top-ranked sample at each AL selection cycle, however, as discussed below, this approach may not be practical for DL models.

4.3 Batch Selection AL for DL

In the previous subsection we introduced a practical single-sample sequential deep learning active learning algorithm. However, when dealing with deep neural networks, adding only one sample at the time to the training dataset is not likely to meaningfully affect performance between AL cycles[2], but will definitely

---

[2]In fact, it may be detrimental in some cases due to the use of stochastic gradient learning approaches.

Algorithm 1 RALIF: Reliable active learning via influence functions with *truncated-IL* selection.

Input: L_0: Initial labeled dataset, U_0: initial unlabeled dataset, M: model, C: AL cycles, B: query set, P: candidate set, $\phi_{M_{L_{c-1}}}(\cdot)$: convolutional encoder, and τ: truncation hyperparameter.

 1: **for** $c = 1, \ldots, C$ **do**
 2:     Train model $M_{L_{c-1}}$ with labels set L_{c-1}
 3:     $|P| = 0.1|U_{c-1}|$
 4:     $\forall x_i \sim U_c$ generate pseudo-labels $\tilde{y}_i = \arg\max M_{L_{c-1}}(x_i)$
 5:     **for** $x_s \in U_{c-1}$ **do**
 6:         Generate probabilistic predictions $\{p_k(x_s)\}_{k=1}^K$ from $M_{L_{c-1}}(x_s)$
 7:         Calculate $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})]$ via (9)
 8:     **end for**
 9:     Select top-$|P|$ samples $\{x_i\}_{|P|}$ with minimum $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})]$
10:     Run *k-MEANS++* on $\{\phi_{M_{L_{c-1}}}(x_i)\}_{|P|}$ to select $|B|$ diverse samples
11:     $L_c = L_{c-1} \cup \{(x_s, y_s)\}_{s \in B}$
12: **end for**
Return: Final labeled dataset L_C (of size $L_0 + C|B|$)

---

increase computational requirements to a point that in some scenarios it may render AL prohibitive. Therefore, we opt for batch selection in each AL cycle, which is a common practice in active learning selection mechanisms for deep neural networks (Kirsch et al., 2019; Sener & Savarese, 2017; Wang et al., 2022).

From (5) we can conceptualize that given a sample x_s that minimizes the loss, there are likely other samples in U_{c-1} that being very similar to x_s also have comparably small losses. However, by virtue of being similar they are also likely to be redundant in their ability to improve model M. Though such redundancy is not likely to negatively impact performance, it certainly affects efficiency, by requiring unnecessary labeling efforts. This phenomenon of batch AL approaches has been described before (Beluch et al., 2018; Ash et al., 2019; Wang et al., 2022), and several approaches have been proposed to mitigate this problem. For example, Beluch et al. (2018) suggested selecting samples from a subset of the unlabeled dataset rather than considering the entire dataset to avoid including highly similar samples in a selected batch.

To alleviate such issue, we propose a two-step approach. First, we utilize *single-IL* in (7), *expectation-IL* in (8) or *truncated-IL* in (9) to select a pool of candidate samples with the smallest expected losses on the unlabeled dataset. In practice, we set the size of the candidate pool P to be 10% of the size of the unlabeled set, *i.e.*, $P = 0.1 \times |U_c|$. Second, to ensure the diversity of the final selected samples, we cluster the P candidates into B clusters, where B refers to the budget size for each AL selection cycle, and then select from P the centroids of these clusters as the samples selected for labeling. In order to ensure that selected samples are representative of the entire pool of candidates, we use the features extracted from the convolutional encoder as the representation space for clustering. Specifically, we use the *k-MEANS++* (Arthur & Vassilvitskii, 2007) algorithm, a variant of the popular K-means (MacQueen, 1967) algorithm. This particular clustering algorithm was chosen because work by Arthur & Vassilvitskii (2007); Ash et al. (2019) demonstrated that *k-MEANS++* has a fast convergence speed while generating relatively diverse clustering centroids, which encourages the diversity of the set of selected samples.

In practice, one cycle of the RALIF framework consists on selecting a diverse set of samples with the smallest loss on the unlabeled data given in (7), (8) or (9), while using pseudo labels from the current trained model as a proxy for the true, but the unavailable, labels. The complete process for *truncated-IL* in (9) is summarized in Algorithm 1. Further, we provide a more complete algorithm in Appendix A.2, which includes all selection approaches, *i.e.*, *single-IL* in (7), *expectation-IL* in (8), and *truncated-IL* in (9).

5   Experiments

Our experiments aim to demonstrate the reliability of RALIF on various selection scenarios. Below, we first introduce the baseline algorithms with which we compare. Then, we describe the different AL selection

scenarios that we consider in our experiments, along with the model training details. Finally, we will present the results of our experiments, highlighting the performance of the proposed RALIF framework.

Baselines   We consider the following baselines in our experiments: *i*) Random: selecting a random batch of unlabeled samples at each selection cycle, which serves as the naive, *no skill*, baseline for active learning; *ii*) Uncertainty: we leverage the most commonly used uncertainty-based selection method introduced in Beluch et al. (2018), which involves selecting unlabeled samples with the highest entropy based on the classification probabilities produced by the model trained with the labeled dataset; *iii*) CoreSet (Sener & Savarese, 2017): utilizing the model trained with the labeled dataset to extract features for all unlabeled samples, then applying the *K-Center-Greedy* (Wolf, 2011) algorithm on such feature space to select a diverse batch of unlabeled samples; *iv*) BADGE (Ash et al., 2019): selecting unlabeled samples by applying the *K-MEANS++* algorithm on the gradient norms calculated for all unlabeled samples based on the pseudo labels predicted by the model trained with the labeled data; and *v*) GradNorm (Wang et al., 2022): selecting unlabeled samples with the largest gradient norms by using their entropy as loss for backpropagation. Note that this is the same entropy used in Uncertainty.

The five baselines we consider in our experiments cover the most common types of active learning algorithms, namely, Random selection (as a naive baseline for AL), uncertainty-based selection (Uncertainty), diversity-based selection (Coreset), hybrid strategies (BADGE, which combines uncertainty and diversity), and DL-specific selection (GradNorm). In comparison to these baselines, RALIF can be considered a hybrid DL-specific AL algorithm as it combines the DL-specific selection (utilizing influence functions), but encouraging the selection of a set of diverse samples that are likely to minimize the loss incurred by the model on the unlabeled dataset. By comparing RALIF with these baselines, we will also demonstrate how it fares with the state-of-the-art methods, *i.e.*, Ash et al. (2019); Wang et al. (2022).

AL Scenarios   To simulate various selection scenarios, we consider three main determinants in the active learning selection process, namely, dataset, model architecture, and budget size at each selection cycle. In our experiments, we use three datasets: Cifar10 (Krizhevsky et al., 2009), Cifar100 (Krizhevsky et al., 2009), and iNaturalist (14 super classes) (Van Horn et al., 2018), representing simple, medium complexity, and imbalanced datasets, respectively. In terms of model architectures, we consider three options: ResNet18 from scratch denoted as ResNet18 (scratch), ResNet18 with pretrained weights from ImageNet (Deng et al., 2009) denoted, and a simple linear classifier (a fully connected layer) with a fixed but powerful encoder (Clip-Vit-patch16) denoted as CLIP. We use the standard ResNet18 (He et al., 2016) architecture for the pretrained ResNet18, the standard Clip-Vit-patch16 (Radford et al., 2021) for CLIP, and a customized version of ResNet18 for ResNet18 (scratch)[3], where the kernel size of the first convolution layer is modified from 7 to 3 and the max pooling layer is removed. Moreover, we also consider two different budget sizes: 1000 or 2000 samples at each selection cycle.

Training Details   We set different initial labeled dataset sizes for each selection scenario based on model capacity and the complexity of the dataset. For the CLIP model, which has shown excellent performance with a smaller training dataset size compared to other models, we set the initial labeled dataset size to 100 samples. This choice is made to ensure that the initial accuracy is not excessively high, allowing us to observe the effectiveness of the AL algorithms. For all other models, we set the initial labeled dataset size to 1000 samples for Cifar10 and 6000 samples for Cifar100 and iNaturalist. This decision takes into account the higher complexity of the iNaturalist and Cifar100 datasets relative to Cifar10. We trained our models using stochastic gradient descent (Sutskever et al., 2013) with a weight decay of 10^{-4} and a momentum of 0.9. The initial learning rate, learning rate scheduler, and training epochs were set based on the model capacity. For pretrained ResNet18 and CLIP, we employed CosineAnnealingLR (Loshchilov & Hutter, 2016) as the learning rate scheduler and set the initial learning rate to 0.01. The pretrained ResNet18 and CLIP models were trained for 200 and 100 epochs, respectively, the latter accounting for the excellent performance of the CLIP model. For ResNet18 (scratch), following the suggestions in He et al. (2016), we set the initial learning rate to 0.1 and decrease it by a factor of 10 at the 160-th epoch, for a total of 200 training epochs. In our experiments, we consider basic data augmentations, including random horizontal flip, random crop,

---

[3]Source code available at https://github.com/kuangliu/pytorch-cifar.

Table 1: Ablation study results. We present the mean and standard deviation of the performance metrics for all algorithms (different selection strategies and diversity selection) over three trials. Best results are highlighted in green.

Candidate Selection	Diversity k-MEANS++	Cycle First (1^{st})	Last (9^{th})	AUCA Ratio
Random		85.31 ± 0.29	92.29 ± 0.09	1.000 ± 0.000
single-IL		85.60 ± 0.60	93.86 ± 0.04	1.014 ± 0.000
expectation-IL		85.62 ± 0.38	93.00 ± 0.09	1.004 ± 0.001
truncated-IL		86.15 ± 0.20	94.10 ± 0.09	1.017 ± 0.002
single-IL	✓	86.23 ± 0.49	94.05 ± 0.04	1.017 ± 0.001
expectation-IL	✓	85.66 ± 0.18	92.92 ± 0.16	1.006 ± 0.001
truncated-IL	✓	86.92 ± 0.15	94.35 ± 0.05	1.020 ± 0.002

and normalization. For the input images, if the model is ResNet18 (scratch), we resize the inputs to 32×32, otherwise, we resize the inputs to 224×224. This choice is based on the different architectures of the models and their specific requirements for input sizes. For each selection scenario, we run each algorithm three times over 9 AL selection cycles and report the mean and standard deviation of the results as the final performance of the algorithms. Source code is available at `https://github.com/anonymous/Active-Learning.git`[4].

Evaluation Metrics   In our experiments, we use classification accuracy, denoted as ACC, as the primary evaluation metric for comparing the performance of the AL algorithms. Specifically, we train a model with the labeled dataset selected by each AL algorithm at each selection cycle and evaluate the classification accuracy of the model on the corresponding test dataset. To provide a more comprehensive metric of the performance of each AL algorithm over the entire selection process (9 selection cycles), we introduce a summary performance metric we call AUCA Ratio representing the ratio between the area under the classification accuracy curve over all selection cycles for a model and the random selection approach. The AUCA Ratio is calculated using the trapezoidal rule (Yeh et al., 2002). Note that an AUCA Ratio larger than 1 indicates that the corresponding AL algorithm achieves a consistent improvement over the random selection baseline throughout the entire selection process.

5.1   Ablation Study

The proposed RALIF consists of mainly two components. We first utilize results from Theorem 1 and the influence function formulation in (6) via (5) to select the most likely informative and useful sample candidates for labeling. We then use the *k-MEANS++* algorithm on the features of the selected pool of candidates to down-select a batch encouraging sample diversity. We consider three options for the first component of RALIF: *single-IL* in (7), *truncated-IL* in (9), and *truncated-IL* in (8). For the second component, we can choose (or not) to favor diversity by applying the *k-MEANS++*. If we choose not to apply *k-MEANS++*, we simply select a batch of the top-ranked B samples obtained using the ranked loss from the first component.

To investigate the contribution of different choices, we conduct an ablation study on a general selection scenario: using the Cifar10 dataset, the pretrained ResNet18 model architecture, and a budget size of 1000. We compare performance metrics, ACC and AUCA Ratio, after the first and last selection cycles, first and ninth, respectively. Table 1 underscores that each component of our algorithm contributes to the selection process by prioritizing more useful samples compared to the random selection baseline. From Table 1, we also observe that, compared with *single-IL* and *truncated-IL*, *expectation-IL* is less successful at selecting useful samples. This is likely to be caused by samples with small but nonzero probabilities assigned during predictions that negatively bias their influence estimation, thus undermining the selection process. Complementary, the results suggest that applying the *k-MEANS++* algorithm in general improves the performance of the the AL algorithm by alleviating information redundancy during the selection process.

---

[4]This is a placeholder link. Code has been submitted as Supplementary Material.

Table 2: Comparison with baselines in different scenarios. B: budget size at each selection cycle. Note that for RALIF we use *truncated-IL* for candidate selection and *K-MEANS++* for diversity down-selection. We present the mean and standard deviation of the results for all algorithms over three trials. The best and worse than *Random* results are highlighted in green and red, respectively.

| | Setting | | | Cycles | | |
Datasets	B	models	Methods	First(1^{st})	Last (9^{th})	AUCA Ratio
Cifar10	1000	*ResNet18 (scratch)*	Random	61.33 ± 1.20	87.04 ± 0.11	1.000 ± 0.000
			Uncertainty	60.27 ± 3.06	90.39 ± 0.08	1.025 ± 0.008
			Coreset	54.07 ± 2.68	84.80 ± 0.68	0.948 ± 0.006
			BADGE	60.21 ± 0.88	89.79 ± 0.12	1.024 ± 0.006
			Grad-Norm	57.90 ± 3.78	90.08 ± 0.25	1.027 ± 0.002
			RALIF	62.05 ± 0.75	90.53 ± 0.13	1.041 ± 0.003
Cifar10	1000	*ResNet18*	Random	85.31 ± 0.29	92.29 ± 0.09	1.000 ± 0.000
			Uncertainty	85.55 ± 0.28	94.29 ± 0.24	1.016 ± 0.003
			Coreset	85.59 ± 0.11	93.04 ± 0.12	1.008 ± 0.002
			BADGE	86.66 ± 0.16	94.32 ± 0.06	1.019 ± 0.001
			Grad-Norm	86.60 ± 0.07	94.19 ± 0.07	1.019 ± 0.003
			RALIF	86.92 ± 0.15	94.35 ± 0.05	1.021 ± 0.002
Cifar10	2000	*ResNet18*	Random	87.56 ± 0.25	94.06 ± 0.04	1.000 ± 0.000
			Uncertainty	88.64 ± 0.29	95.57 ± 0.03	1.019 ± 0.001
			Coreset	87.58 ± 0.17	94.68 ± 0.20	1.007 ± 0.001
			BADGE	88.88 ± 0.19	95.69 ± 0.16	1.018 ± 0.001
			Grad-Norm	88.46 ± 0.11	95.70 ± 0.03	1.018 ± 0.001
			RALIF	88.96 ± 0.05	95.72 ± 0.07	1.020 ± 0.001
Cifar100	1000	*ResNet18*	Random	64.50 ± 0.55	71.64 ± 0.13	1.000 ± 0.000
			Uncertainty	64.81 ± 0.13	72.41 ± 0.25	1.011 ± 0.003
			Coreset	64.86 ± 0.10	71.67 ± 0.37	1.003 ± 0.001
			BADGE	65.26 ± 0.16	73.21 ± 0.19	1.013 ± 0.001
			Grad-Norm	65.27 ± 0.34	73.11 ± 0.31	1.010 ± 0.003
			RALIF	65.17 ± 0.08	73.26 ± 0.08	1.015 ± 0.002
iNaturalist	1000	*ResNet18*	Random	85.17 ± 0.07	87.10 ± 0.07	1.000 ± 0.000
			Uncertainty	85.14 ± 0.08	87.45 ± 0.08	1.002 ± 0.000
			Coreset	85.43 ± 0.03	87.45 ± 0.07	1.003 ± 0.000
			BADGE	85.53 ± 0.14	88.40 ± 0.01	1.010 ± 0.001
			Grad-Norm	85.56 ± 0.05	88.47 ± 0.08	1.010 ± 0.001
			RALIF	85.66 ± 0.05	88.63 ± 0.12	1.012 ± 0.001
iNaturalist	100	*CLIP*	Random	90.85 ± 0.90	93.98 ± 0.18	1.000 ± 0.000
			Uncertainty	89.13 ± 1.00	93.72 ± 0.20	0.994 ± 0.007
			Coreset	89.64 ± 0.90	93.44 ± 0.18	0.990 ± 0.004
			BADGE	92.66 ± 0.32	95.17 ± 0.08	1.015 ± 0.004
			Grad-Norm	92.71 ± 0.38	95.05 ± 0.02	1.015 ± 0.004
			RALIF	92.82 ± 0.26	95.17 ± 0.01	1.015 ± 0.002
	Average		Random	79.12 ± 11.67	87.69 ± 7.74	1.000 ± 0.000
			Uncertainty	78.92 ± 11.83	88.97 ± 7.89	1.011 ± 0.011
			Coreset	77.86 ± 13.50	87.51 ± 7.92	0.993 ± 0.021
			BADGE	79.87 ± 12.41	89.43 ± 7.75	1.016 ± 0.005
			Grad-Norm	79.42 ± 13.07	89.43 ± 7.76	1.016 ± 0.006
			RALIF	80.26 ± 12.02	89.61 ± 7.74	1.020 ± 0.010

Overall, the combination of *truncated-IL* and *k-MEANS++* achieved the best performance, so we will use this combination, simply referred to as *truncated-IL* for further comparisons with all AL baselines.

5.2 Performance Comparison with Baselines

We conduct a comprehensive comparison of our proposed *truncated-IL* algorithm (with diversity selection) with other baselines in six simulated benchmark scenarios with different datasets (Cifar10, Cifar100 and iNaturalist), batch size (100, 1000 and 2000) and DL model (pretrained RestNet18, ResNet18 from scratch and pretrained CLIP). Table 2 provides a summary of the results, focusing on ACC and AUCA Ratio comparisons for the first and last AL selection cycles. For more detailed ACC comparisons across all selection cycles and boxplots summarizing the AUCA Ratio for different trials see Appendix A.4. In summary, the results presented in Table 2 clearly demonstrate that RALIF with *truncated-IL* selection consistently achieved the best performance across all scenarios, highlighting its reliability and effectiveness.

More specifically, among all the baselines considered, BADGE fared as the second-best approach in three scenarios, followed by Grad-Norm in two scenarios, and Uncertainty in one scenario. However, it is important to note that all baselines performed worse than the Random baseline in at least one selection cycle (highlighted in red in Table 2). In contrast, RALIF with *truncated-IL* selection always outperformed Random. For instance, when considering the Cifar10 dataset with a budget size of 1000 and the ResNet18 (scratch) model, all baselines performed worse than Random in the first selection cycle. Notably, the Coreset algorithm exhibited worse performance than the Random baseline in two scenarios, while Uncertainty performed worse than Random in one scenario. As a summary of the experiments across different settings, we also present average metrics, from which we can see the consistency of RALIF relative to the competing approaches. These results highlight the reliability of RALIF compared to baselines including state-of-the art methods.

5.3 Qualitative results

To gain further insights into the samples selected by different AL approaches, we present visualizations of selected samples using UMAP embeddings for the iNaturalist dataset with AL approaches with a budget of 100 and a fixed CLIP encoder. Figure 2 shows UMAP visualizations of unlabeled and selected samples (in red) for Uncertainty, BADGE, and RALIF. We chose Uncertainty and BADGE for visualization because the former is the most commonly used AL algorithm, and the latter is the second-best AL algorithm among the baselines based on the experimental results in Table 2. In the figure, each point represents a sample, different colors indicate true classes (first two rows) or entropy (third row). Note that true labels are not available to the AL methods.

From Figure 2, several observations can be made. First, compared to the other two AL algorithms, the samples selected by Uncertainty appear to cluster in a smaller area consistent with high uncertainty (entropy), and with most of them closely packed together. This suggests that the Uncertainty algorithm tends to select similar samples in each iteration, leading to redundancy in the selected data and potentially undermining its performance, thus underscoring the benefits of diversity sampling. However, results for Coreset in Table 2 indicate that solely relying diversity during active learning selection cycles can lead to worse performance. Alternatively, BADGE combines uncertainty and diversity in its strategy. Examining Figure 2, we observe that the samples selected by BADGE are more diverse compared to those selected by Uncertainty. This indicates that BADGE effectively avoids selecting samples that are clustered together and rather focuses on selecting more diverse samples. From Figure 2, we also see that RALIF, similar to BADGE, successfully avoids selecting samples that cluster together and selects more diverse samples than Uncertainty. Notably, RALIF seems to select samples more sparsely distributed relative to BADGE, underscoring the effectiveness of the *truncated-IL* selection approach, by minding that both BADGE and RALIF use the same diversity strategy. Further, comparing sample selections for the first and last cycle, we see that Uncertainty naturally favors tightly packed samples with high entropy, BADGE consistently selects sparsely distributed samples, whereas RALIF initially favors more tightly packed samples and then (as the model improves) starts favoring more diverse samples, thus differentiating itself from both Uncertainty and BADGE.

6 Conclusion

In this paper, we proposed a new AL framework for DL architectures called RALIF, which is motivated by theoretical observations on the complete-data loss of a classification model. We established that samples

Figure 2: UMAP embeddings for the first and last selection cycles of different active learning approaches with a fixed CLIP encoder on the iNaturalist data. The first and second rows correspond to the first and last selection cycle, respectively, and with colors indicating true classes for each data point. The bottom row corresponds to the last cycle with colors denoting the normalized entropy for each data point. From left to right, the visualizations are for Uncertainty, BADGE, and RALIF. Red dots highlight samples selected for labeling by each approach.

minimizing the model loss on the unlabeled dataset with generated pseudo labels bound from above the loss on the entire dataset with true labels. To address the challenges associated with evaluating the impact of candidate samples on the loss of the model on the unlabeled dataset, we introduce three efficient selection strategies, namely, *single-IL*, *expectation-IL* and *truncated-IL*. These strategies allow the quantification of the contribution of candidate samples to the loss on the entire dataset without the need for explicit model retraining. Further, we incorporated a diversity prioritization based on *K-MEANS++* similar to BADGE (Ash et al., 2019), to improve the diversity of selected samples when performing batch selection.

We evaluated the reliability and effectiveness of RALIF through comprehensive experiments across various scenarios. The experimental results clearly demonstrated that RALIF consistently outperformed the random baseline and other DL-based AL algorithms in terms of classification performance. Moreover, we provided qualitative results that highlighted RALIF's ability to trade-off high-uncertainty and diversity during the active selection process.

One limitation of RALIF is that the quality of the pseudo labels generated from the model M can affect its performance. There are two main reasons for this behavior. First, RALIF utilizes the model and its predictions as an approximation to the conditional distribution $\tilde{p}_{Y|X}$ in Theorem A.1. If the quality of the model and thus its pseudo labels is poor, the total variation difference $\delta_{TV}(\cdot, \cdot)$ between the estimated label conditional distribution $\tilde{p}_{Y|X}$ and the true label conditional distribution $p_{Y|X}$ will be large. This can

result in a loose bound in Theorem A.1, rendering it less effective for AL. Second, RALIF uses pseudo labels to approximate the influence function in (7). If the quality of the pseudo labels is low, the approximated influence loss for each candidate will be inaccurate. This can affect the selection process and potentially lead to suboptimal results. However, it is important to note that this limitation is not exclusive to RALIF but also applies to other AL baselines since they also dependent on the quality and performance of the model at each selection cycle. For example, when considering Cifar10 with a budget size of 1000 and the ResNet18 model trained from scratch, the results in Table 2 demonstrate that all other AL baselines perform worse than the Random baseline in the first cycle, when the initial model has poor performance. Another limitation of RALIF is that it is currently designed specifically for classification tasks, thus it may not be directly applicable to other types of tasks, such as object detection or natural language processing problems. Consequently, further research and adaptation would be needed to extend RALIF to such tasks.

In future work, we plan to extend RALIF to real-world datasets that exhibit specific label structures, such as datasets with hierarchically organized labels. These datasets pose unique challenges for AL algorithms, as the label hierarchy introduces additional dependencies and relationships among the samples. Moreover, it will be interesting to explore how RALIF can be used to address related tasks such as few-shot learning and test-time domain generalization.

References

David Arthur and Sergei Vassilvitskii. K-means++ the advantages of careful seeding. In *Proceedings of the eighteenth annual ACM-SIAM symposium on Discrete algorithms*, pp. 1027–1035, 2007.

Jordan T Ash, Chicheng Zhang, Akshay Krishnamurthy, John Langford, and Alekh Agarwal. Deep batch active learning by diverse, uncertain gradient lower bounds. *arXiv preprint arXiv:1906.03671*, 2019.

William H Beluch, Tim Genewein, Andreas Nürnberger, and Jan M Köhler. The power of ensembles for active learning in image classification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 9368–9377, 2018.

Klaus Brinker. Incorporating diversity in active learning with support vector machines. In *Proceedings of the 20th international conference on machine learning (ICML-03)*, pp. 59–66, 2003.

Xi Chen, Xiao Wang, Soravit Changpinyo, AJ Piergiovanni, Piotr Padlewski, Daniel Salz, Sebastian Goodman, Adam Grycner, Basil Mustafa, Lucas Beyer, et al. Pali: A jointly-scaled multilingual language-image model. *arXiv preprint arXiv:2209.06794*, 2022.

Xiangning Chen, Chen Liang, Da Huang, Esteban Real, Kaiyuan Wang, Yao Liu, Hieu Pham, Xuanyi Dong, Thang Luong, Cho-Jui Hsieh, et al. Symbolic discovery of optimization algorithms. *arXiv preprint arXiv:2302.06675*, 2023.

David A Cohn, Zoubin Ghahramani, and Michael I Jordan. Active learning with statistical models. *Journal of artificial intelligence research*, 4:129–145, 1996.

Ido Dagan and Sean P Engelson. Committee-based sampling for training probabilistic classifiers. In *Machine Learning Proceedings 1995*, pp. 150–157. Elsevier, 1995.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Mário Figueiredo. Adaptive sparseness using jeffreys prior. *Advances in neural information processing systems*, 14, 2001.

Mário AT Figueiredo. Adaptive sparseness for supervised learning. *IEEE transactions on pattern analysis and machine intelligence*, 25(9):1150–1159, 2003.

Mário AT Figueiredo and Anil K Jain. Bayesian learning of sparse classifiers. In *Proceedings of the 2001 IEEE Computer Society Conference on Computer Vision and Pattern Recognition. CVPR 2001*, volume 1, pp. I–I. IEEE, 2001.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059. PMLR, 2016.

Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep bayesian active learning with image data. In *International conference on machine learning*, pp. 1183–1192. PMLR, 2017.

Yonatan Geifman and Ran El-Yaniv. Deep active learning over the long tail. *arXiv preprint arXiv:1711.00941*, 2017.

Frank R Hampel. The influence curve and its role in robust estimation. *Journal of the american statistical association*, 69(346):383–393, 1974.

Jingrui He, Hanghang Tong, Mingjing Li, Hong-Jiang Zhang, and Changshui Zhang. Mean version space: a new active learning method for content-based image retrieval. In *Proceedings of the 6th ACM SIGMM international workshop on Multimedia information retrieval*, pp. 15–22, 2004.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Marti A. Hearst, Susan T Dumais, Edgar Osuna, John Platt, and Bernhard Scholkopf. Support vector machines. *IEEE Intelligent Systems and their applications*, 13(4):18–28, 1998.

Ralf Herbrich, Thore Graepel, and Colin Campbell. Bayes point machines. *Journal of Machine Learning Research*, 1(Aug):245–279, 2001.

Rebecca Hwa. Sample selection for statistical parsing. *Computational linguistics*, 30(3):253–276, 2004.

Jitesh Jain, Jiachen Li, MangTik Chiu, Ali Hassani, Nikita Orlov, and Humphrey Shi. Oneformer: One transformer to rule universal image segmentation. *arXiv preprint arXiv:2211.06220*, 2022.

Andreas Kirsch, Joost Van Amersfoort, and Yarin Gal. Batchbald: Efficient and diverse batch acquisition for deep bayesian active learning. *Advances in neural information processing systems*, 32, 2019.

David G Kleinbaum, K Dietz, M Gail, Mitchel Klein, and Mitchell Klein. *Logistic regression*. Springer, 2002.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International conference on machine learning*, pp. 1885–1894. PMLR, 2017.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

John Lafferty, Andrew McCallum, and Fernando CN Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. 2001.

David D Lewis and William A Gale. A sequential algorithm for training text classifiers. In *SIGIR'94*, pp. 3–12. Springer, 1994.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

Edwin Lughofer. Extensions of vector quantization for incremental clustering. *Pattern recognition*, 41(3): 995–1011, 2008.

Edwin Lughofer. Hybrid active learning for reducing the annotation effort of operators in classification systems. *Pattern Recognition*, 45(2):884–896, 2012.

J MacQueen. Classification and analysis of multivariate observations. In *5th Berkeley Symp. Math. Statist. Probability*, pp. 281–297. University of California Los Angeles LA USA, 1967.

Andrew McCallum, Kamal Nigam, et al. Employing em and pool-based active learning for text classification. In *ICML*, volume 98, pp. 350–358. Citeseer, 1998.

Prateek Munjal, Nasir Hayat, Munawar Hayat, Jamshid Sourati, and Shadab Khan. Towards robust and reproducible active learning using neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 223–232, 2022.

Lawrence R Rabiner. A tutorial on hidden markov models and selected applications in speech recognition. *Proceedings of the IEEE*, 77(2):257–286, 1989.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PMLR, 2021.

Irina Rish et al. An empirical study of the naive bayes classifier. In *IJCAI 2001 workshop on empirical methods in artificial intelligence*, volume 3, pp. 41–46, 2001.

Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. *arXiv preprint arXiv:1708.00489*, 2017.

Burr Settles. Active learning literature survey. 2009.

Burr Settles and Mark Craven. An analysis of active learning strategies for sequence labeling tasks. In *proceedings of the 2008 conference on empirical methods in natural language processing*, pp. 1070–1079, 2008.

H Sebastian Seung, Manfred Opper, and Haim Sompolinsky. Query by committee. In *Proceedings of the fifth annual workshop on Computational learning theory*, pp. 287–294, 1992.

Claude E Shannon. A mathematical theory of communication. *The Bell system technical journal*, 27(3): 379–423, 1948.

Samarth Sinha, Sayna Ebrahimi, and Trevor Darrell. Variational adversarial active learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5972–5981, 2019.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1): 1929–1958, 2014.

Ilya Sutskever, James Martens, George Dahl, and Geoffrey Hinton. On the importance of initialization and momentum in deep learning. In *International conference on machine learning*, pp. 1139–1147. PMLR, 2013.

Simon Tong and Daphne Koller. Support vector machine active learning with applications to text classification. *Journal of machine learning research*, 2(Nov):45–66, 2001.

Grant Van Horn, Oisin Mac Aodha, Yang Song, Yin Cui, Chen Sun, Alex Shepard, Hartwig Adam, Pietro Perona, and Serge Belongie. The inaturalist species classification and detection dataset. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Vladimir Vapnik. *The nature of statistical learning theory*. Springer science & business media, 1999.

Dan Wang and Yi Shang. A new active labeling method for deep learning. In *2014 International joint conference on neural networks (IJCNN)*, pp. 112–119. IEEE, 2014.

Tianyang Wang, Xingjian Li, Pengkun Yang, Guosheng Hu, Xiangrui Zeng, Siyu Huang, Cheng-Zhong Xu, and Min Xu. Boosting active learning via improving test performance. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 8566–8574, 2022.

Gert W Wolf. Facility location: concepts, models, algorithms and case studies. series: Contributions to management science: edited by zanjirani farahani, reza and hekmatfar, masoud, heidelberg, germany, physica-verlag, 2009, 549 pp.,€ 171.15, \$219.00,£ 144.00, isbn 978-3-7908-2150-5 (hardprint), 978-3-7908-2151-2 (electronic), 2011.

Xing Wu, Cheng Chen, Mingyu Zhong, and Jianjia Wang. Hal: Hybrid active learning for efficient labeling in medical domain. *Neurocomputing*, 456:563–572, 2021.

Shi-Tao Yeh et al. Using trapezoidal rule for the area under a curve calculation. *Proceedings of the 27th Annual SAS® User Group International (SUGI'02)*, pp. 1–5, 2002.

Donggeun Yoo and In So Kweon. Learning loss for active learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 93–102, 2019.

Tong Zhang and F Oles. The value of unlabeled data for classification problems. In *Proceedings of the Seventeenth International Conference on Machine Learning,(Langley, P., ed.)*, volume 20, pp. 0. Citeseer, 2000.

A Appendix

A.1 Proof and explanation of Theorem 1

Proof. Let $p_{X,Y} = p_X p_{Y|X}, \tilde{p}_{X,Y} = p_X \tilde{p}_{Y|X}$,

$$
\begin{aligned}
\left| \mathbb{E}_{(x,y) \sim p_X p_{Y|X}} l(x,y) - \mathbb{E}_{(x,\tilde{y}) \sim p_X \tilde{p}_{Y|X}} l(x,\tilde{y}) \right| &= \left| \int_{X \times Y} (p_{X,Y}(x,y) - \tilde{p}_{X,Y}(x,y)) \, l(x,y) dxdy \right| \\
&\leq \int_{X \times Y} |p_{X,Y}(x,y) - \tilde{p}_{X,Y}(x,y)| \cdot |l(x,y)| \, dxdy \\
&\leq L \cdot \int_{X \times Y} |p_{X,Y}(x,y) - \tilde{p}_{X,Y}(x,y)| \, dxdy \\
&= 2L \cdot \delta_{TV}(p_X p_{Y|X}, p_X \tilde{p}_{Y|X}).
\end{aligned}
\tag{11}
$$

$\square$

In practice, the upper bound L of the loss functions can usually be established given that the network inputs are usually bounded and the network weights are regularized during training. An example is the cross-entropy loss function used for classification. Denote the (before softmax activation) network output as $\mathbf{x} \in \mathbb{R}^K$ with elements x_k, *i.e.*, $\mathbf{x} = (x_k)_{1 \leq k \leq K}$ and the ground truth label vector as $\mathbf{y} \in [0,1]^K$ with elements y_k, *i.e.* $\mathbf{y} = (y_k)_{1 \leq k \leq K}$, and $\sum_{k=1}^{K} y_k = 1$. The cross-entropy loss is defined as:

$$
\mathcal{L}_{CE}(\mathbf{x}, \mathbf{y}) = -\sum_{k=1}^{K} y_k \log p_k,
\tag{12}
$$

where p_k is the post-softmax prediction score for class k, *i.e.*,

$$
p_k = \frac{\exp(x_k)}{\sum_{j=1}^{K} \exp(x_j)}.
\tag{13}
$$

We can show that

$$
\begin{aligned}
\frac{\mathcal{L}_{CE}(\mathbf{x}, \mathbf{y})}{\|\mathbf{x}\|_2} &= \frac{1}{\|\mathbf{x}\|_2} - \sum_{k=1}^{K} y_k \log \frac{\exp(x_k)}{\sum_{j=1}^{K} \exp(x_j)} \\
&= \frac{1}{\|\mathbf{x}\|_2} \sum_{k=1}^{K} y_k \log \frac{\sum_{j=1}^{K} \exp(x_j)}{\exp(x_k)} \\
&\leq \frac{1}{\|\mathbf{x}\|_2} \sum_{i=1}^{K} y_k \log \frac{K \cdot \exp\left(\max_{1 \leq j \leq K} x_j\right)}{\exp(x_k)} \\
&\leq \frac{1}{\|\mathbf{x}\|_2} \sum_{i=1}^{K} y_k \log \frac{K \cdot \exp\left(\max_{1 \leq j \leq K} x_j\right)}{\exp\left(-\max_{1 \leq j \leq K} x_j\right)} \\
&= \frac{1}{\|\mathbf{x}\|_2} \left(\log K + \log \frac{\exp\left(\max_{1 \leq j \leq K} x_j\right)}{\exp\left(-\max_{1 \leq j \leq K} x_j\right)}\right) \\
&= \frac{1}{\|\mathbf{x}\|_2} \left(\log K + 2 \max_{1 \leq j \leq K} x_j\right) \\
&\leq \frac{\log K}{\|\mathbf{x}\|_2} + 2,
\end{aligned}
\tag{14}
$$

from which we can see that the magnitude of $\mathcal{L}_{CE}$ is bounded by a constant multiple of the 2-norm of $\mathbf{x}$. When $\|\mathbf{x}\|_2 \to +\infty$, although the exact form of how the norm of $\mathbf{x}$ is bounded by the model weights depend on many network details, *e.g.*, network architecture, activation functions.

A.2 Complete RALIF Algorithm

The complete Algorithm 2 including all three selecting approaches, *i.e.*, *single-IL* in (7), *expectation-IL* in (8) and *truncated-IL* in (9).

A.3 Different thresholds

To investigate the impact of different values of τ on the performance of RALIF, we conducted experiments on a specific selection scenario. The experiments were performed using the Cifar10 dataset, a pretrained ResNet18 model architecture, and a budget size of 1000. We varied the value of τ across five different values: $\frac{0}{K} = 0$, $\frac{2}{K} = 0.2$, $\frac{4}{K} = 0.4$, $\frac{6}{K} = 0.6$, and $\frac{8}{K} = 0.8$. We then compared the resulting ACC and AUCA Ratio at the first and last selection cycle. The results are summarized in Table 3. It is interesting to note that regardless of the specific value of τ, RALIF consistently outperforms the random baseline. Further, based on the results shown in Table 3, we can observe that $\tau = \frac{4}{K}$ yields the best performance among the tested values.

A.4 Detail results comparison

For a more detailed comparison between the baselines and RALIF, we present the ACC across all AL selection cycles and AUCA Ratio boxplots for all baselines and RALIF under all six AL scenarios in Figure 2.

Algorithm 2 Ralif Framework including all selecting approaches.

Input: L_0: Initial labeled dataset, U_0: initial unlabeled dataset, M: model, C: AL cycles, B: query set, P: candidate set, $\phi_{M_{L_{c-1}}}(\cdot)$: convolutional encoder, and τ: truncation hyperparameter.

1: **for** $c = 1, \ldots, C$ **do**
2:     Train model $M_{L_{c-1}}$ with labels set L_{c-1}
3:     $|P| = 0.1|U_{c-1}|$
4:     $\forall x_i \sim U_c$ generate pseudo-labels $\tilde{y}_i = \arg\max M_{L_{c-1}}(x_i)$
5:     **if** *single-IL* **then**
6:         **for** $x_s \in U_{c-1}$ **do**
7:             Generate pseudo-label $\tilde{y}_s = \arg\max M_{L_{c-1}}(x_s)$
8:             Calculate $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})]$ via (7)
9:         **end for**
10:     **end if**
11:     **if** *expectation-IL* **then**
12:         **for** $x_s \in U_{c-1}$ **do**
13:             Generate probabilistic predictions $\{p_k(x_s)\}_{k=1}^K$ from $M_{L_{c-1}}(x_s)$
14:             Calculate $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})]$ via (8)
15:         **end for**
16:     **end if**
17:     **if** *truncated-IL* **then**
18:         **for** $x_s \in U_{c-1}$ **do**
19:             Generate probabilistic predictions $\{p_k(x_s)\}_{k=1}^K$ from $M_{L_{c-1}}(x_s)$
20:             Calculate $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})]$ via (9)
21:         **end for**
22:     **end if**
23:     Select top-$|P|$ samples $\{x_i\}_{|P|}$ with minimum $\mathbb{E}_{(x_i \sim U_c, \tilde{y}_i \sim \tilde{p}_{Y|X})}[l(x_i, \tilde{y}_i; M_{L_c})]$
24:     Run *k-MEANS++* on $\{\phi_{M_{L_{c-1}}}(x_i)\}_{|P|}$ to select $|B|$ diverse samples
25:     $L_c = L_{c-1} \cup \{(x_s, y_s)\}_{s \in B}$
26: **end for**
Return: Final labeled dataset L_C (of size $L_0 + C|B|$)

Table 3: Comparison with different thresholds for indicator function $\pi(\cdot)$ in (9). We present the mean and standard deviation of the results for all algorithms over three trials. In the first row, we provide the results of the random baseline, which serves as a reference point for comparisons. The best results are highlighted in green.

| τ | Cycle | | AUCA Ratio |
	First (1^{st})	Last (9^{th})	
Random	85.31 ± 0.29	92.29 ± 0.09	1.000 ± 0.000
0.0	85.66 ± 0.18	92.92 ± 0.16	1.007 ± 0.001
0.2	86.60 ± 0.10	94.24 ± 0.04	1.019 ± 0.002
0.4	86.92 ± 0.15	94.35 ± 0.05	1.021 ± 0.002
0.6	86.59 ± 0.16	94.18 ± 0.03	1.019 ± 0.002
0.8	86.63 ± 0.26	94.03 ± 0.05	1.018 ± 0.002

Figure 2: Detailed AL results. Each row corresponds to an AL scenario, following the same order as in Table 2. The title for each row provides a detailed description of the AL scenario, including the Dataset, B (budget size at each selection cycle), and the model used. Standard deviations are omitted in the ACC plots for clarity, and AUCA Ratio boxplots summarize results over the three trials.