Federated Learning under Distributed Concept Drift

Abstract

Federated Learning (FL) under distributed concept drift is a largely unexplored area. Although concept drift is itself a well-studied phenomenon, it poses particular challenges for FL, because drifts arise staggered in time and space (across clients). Our work is the first to explicitly study data heterogeneity in both dimensions. We first demonstrate that prior solutions to drift adaptation, with their single global model, are ill-suited to staggered drifts, necessitating multiple-model solutions. We identify the problem of drift adaptation as a time-varying clustering problem, and we propose two new clustering algorithms for reacting to drifts based on local drift detection and hierarchical clustering. Empirical evaluation shows that our solutions achieve significantly higher accuracy than existing baselines, and are comparable to an idealized algorithm with oracle knowledge of the ground-truth clustering of clients to concepts at each time step.

1 Introduction

Federated learning (FL) [22, 28] is a popular machine learning (ML) paradigm that enables collaborative training without sharing raw training data. FL is crucial in the era of pervasive computing, where massive IoT and mobile phones continuously generate relevant ML data that cannot be easily shared due to privacy and communication constraints. Existing FL solutions generally assume the training data comes from a *stable* underlying distribution, and the training data in the past is sufficiently similar to the test data in the future. This assumption is often violated in the real world, where the underlying data distribution is non-stationary and constantly evolves. For instance, user sentiment and preference change drastically due to external environments such as the pandemic and macroeconomics [13, 21]. Data collected by cameras are also subject to various data changes such as unexpected weather and novel objects, which can lead to significant ML model performance losses [2, 35].

This *concept drift* problem [39] in streaming data has been studied extensively in a centralized learning environment [12, 36]. These centralized solutions, however, cannot address the fundamental challenges of concept drifts in FL where data is heterogeneous over *time* and across different *clients*. When different clients experience the drift *at different times*, no single global model can perform well for all clients. Similarly, when *multiple concepts exist simultaneously*, no centralized training decision works well for all clients. Several recent works have recognized the problem of FL under drift [8, 9, 16, 26], but only under restrictive settings in Figure 1, and proposed solutions that adapt learning rates or add regularization terms. Although these solutions perform better than drift-oblivious algorithms such as FedAvg [28], the solutions still use a single global model for all clients, and hence fail to address the fundamental challenge of heterogeneity over time and across clients.

Our work is the first to acknowledge and explicitly study the more general settings arising in distributed drifts. Consider the distributed drift pattern depicted in Figure 2. This is representative of an emerging trend (e.g., a breaking news event) that effects different clients at different times (e.g., due to their lag in learning of the news). For example, consider a next word prediction app in the period when "war" emerges as the popular next word after "Ukraine" or "slap" emerges after "Will

Submitted to the Workshop on Distribution Shifts, 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: Simplistic drifts studied in prior work. (left) Simultaneous timing. (right) One majority concept.

Figure 2: Distributed drift pattern (2 concepts).

Figure 3: Distributed drift pattern (4 concepts).

Smith". Even for this simple case of a single staggered transition between two concepts, prior work results in significant accuracy loss. In particular, their use of a single global model (and at best a single global drift detection test) results in poor accuracy during the transition period (time steps 4–8, see Figure 4(left) in §4). We also consider more challenging cases, as depicted in Figure 3, where multiple concepts emerge at the same time and concept drifts may be recurring (a.k.a. periodic).

We present the first FL solution that employs multiple models to address FL under distributed concept drift. Our solution aims to create one model for each new concept so that all clients under the same concept can train that model collaboratively, similar to what is done for *personalized* or *clustered* FL [10, 14, 15, 27, 32]. We introduce two new algorithms for client clustering to addresses the challenges of distributed concept drift. Our first algorithm, FedDrift-Eager, is a specialized algorithm that creates models based on drift detection. FedDrift-Eager is effective if new concepts are introduced one at a time. Our second algorithm, FedDrift, is a general algorithm that isolates drifted clients and conservatively merges clients via hierarchical clustering, so that FedDrift can effectively handle general cases where an unknown number of new concepts emerge simultaneously.

We empirically evaluate our solution using four popular concept drift datasets, and we compare our solution against state-of-the-art centralized concept drift solutions (KUE [6] and DriftSurf [36]) and a recent FL solution that adapts to concept drifts (Adaptive-FedAvg [7]). Our results show that (i) FedDrift-Eager and FedDrift consistently achieve much higher and more stable model accuracy than existing baselines (average accuracy 93% vs. 88% for the best baseline, across six dataset/drift combinations); (ii) FedDrift performs much better than FedDrift-Eager when multiple new concepts are introduced at the same time; and (iii) our solution achieves a similar model accuracy as Oracle (94% accuracy), an idealized algorithm that knows the timing and distribution of concept drifts.

2 Problem Setup

We consider a FL setting with P clients, assumed to be stateful and participating at each round, and a central server that coordinates training across the clients. Training data are decentralized and arriving over time. The data $S_c^{(t)}$ at each client $c = 1, 2, \ldots, P$ and each time $t = 1, 2, \ldots$ are sampled from a distribution (concept) $\mathcal{P}_c^{(t)}(x, y)$. We consider that data may be non-IID in two dimensions, varying across clients and time. We say that there is a concept drift at time t and at client c if $\mathcal{P}_c^{(t)} \neq \mathcal{P}_c^{(t-1)}$.

The multiple-model FL problem is to learn a set of global models, and a time-varying clustering of clients. For notation, we denote the global models as h_m for $m \in [M]$, where M is the number of models at a given time (and can vary over time). We denote the cluster identities by one-hot vectors $w_c^{(t)}$, where $w_{c,m}^{(t)} = 1$ when the client c at time t uses model h_m for inference; we denote $h_{w_c^{(t)}}$ to represent the unique model h_m where $w_{c,m}^{(t)} = 1$. The objective is to minimize over all time t,

$$\sum_{c=1}^{P} \mathbb{E}_{(x,y) \sim \mathcal{P}_c^{(t)}} [\ell(h_{w_c^{(t)}}(x), y)]. \tag{1}$$

In presenting our multiple-model solution, we assume that there is one concept and one model at time 1, and show in §3 how to learn the cluster identities $w_c^{(\tau)}$ for each time $\tau > 1$ as new data arrive. Given the cluster identities, learning the set of global models from the clients' data is by continuously retraining via FedAvg [28] within each cluster, which is described precisely in Appendix B.

3 Clustering Algorithms

In §3.1 we handle the case where only one new concept emerges at a time. Then in §3.2 we give an algorithm that handles the general case where multiple new concepts may emerge simultaneously.

3.1 Special Case: One New Concept at a Time

When a new concept emerges, the clients that observe the drift should be split off to a new cluster to start training a new model. In Algorithm 1 (FedDrift-Eager), we apply a drift detection test locally at each client, and create a new cluster for all clients that detect a new concept.

There are many drift detection tests in the literature [1, 11, 17, 20, 29, 31, 36]. The particular test is not our focus and for simplicity we consider a test of the form $\ell_{c,m}^{(\tau)} > \ell_{c,m}^{(\tau-1)} + \delta$ where the loss degrades by a set threshold δ. However, the desired condition for creating a *new model* should check only for drifts that correspond to a concept *previously unobserved* and *ill-suited* for all existing models. Hence, in Algorithm 1, the drift detection test compares against the *best performing* model.

Algorithm 1 FedDrift-Eager at time τ

$\ell_{c,m}^{(\tau)} \leftarrow$ loss of model h_m on client data $S_c^{(\tau)}$
$w_{c,m}^{(\tau)} \leftarrow \mathbf{1}\{m = \arg\min_{m'} \ell_{c,m'}^{(\tau)}\}$
if $\min_m \ell_{c,m}^{(\tau)} > \min_m \ell_{c,m}^{(\tau-1)} + \delta$ at any client c
then // *create one model for all drifted clients*
  $M \leftarrow M + 1$
  Initialize a new global model h_M
  $w_{c,*}^{(\tau)} \leftarrow \mathbf{0}; w_{c,M}^{(\tau)} \leftarrow 1$

Algorithm 1 groups all drifting clients in one cluster. However, under the drift in Figure 3 in which concepts B and C emerge simultaneously, this sub-optimally trains a single model for both concepts.

3.2 General Case

When drifts to new concepts are detected at multiple clients, in general we do not know whether the drifts all correspond to one or multiple concepts (or even zero in the event of false positives in detection). We designed Algorithm 2 (FedDrift) for clustering in the face of this uncertainty. For each client that detects drift to a new concept, Algorithm 2 conservatively isolates the clients to individual clusters, and then merges clusters corresponding to the same concept slowly and safely over time by iteratively applying classical hierarchical agglomerative clustering [33].

Hierarchical clustering is generally specified by a distance function and a stopping criterion. The distance between clusters $D(i, j)$ based on the loss degradation of model h_i over a subsample of the data associated with the cluster for model h_j (and vice versa for symmetry). This distance corresponds to the magnitude of drift between the concepts for each cluster, analogous to the drift detection condition for splitting clusters. Hence, we naturally re-use the drift detection threshold δ to represent the tolerance level up to which clusters can be merged, avoiding the addition of another hyperparameter.

Algorithm 2 FedDrift at time τ

$\ell_{c,m}^{(\tau)} \leftarrow$ loss of model h_m on client data $S_c^{(\tau)}$
for each client $c = 1, 2, \ldots, P$ in parallel **do**
  if $\min_m \ell_{c,m}^{(\tau)} > \min_m \ell_{c,m}^{(\tau-1)} + \delta$ **then**
    Initialize a local model at client c to be added to the set of global models at $\tau + 1$, and assign client c to its own cluster
  else
    $w_{c,m}^{(\tau)} \leftarrow \mathbf{1}\{m = \arg\min_{m'} \ell_{c,m'}^{(\tau)}\}$
for each i, j from $1, 2, \ldots, M$ in parallel **do**
  $L_{ij} \leftarrow$ loss of model h_i on subsample of $\cup_{c,t:w_{c,j}^{(t)}=1} S_c^{(t)}$
Cluster distances $D(i, j) \leftarrow \max(L_{ij} - L_{ii}, L_{ji} - L_{jj}, 0)$
while $\min_{i \neq j} D(i, j) < \delta$ **do**
  MERGE(i, j, D) // *subroutine described in Appendix C*

One subtlety to Algorithm 2 is that the hierarchical clustering is iteratively run at every time step, because the cluster distances vary with time. A simpler alternative would be to only try merging newly created clusters of local models after one time step of training. However, at that one time step, even models corresponding to the same concept may fail to merge given the limited sample size and limited number of training iterations. In other words, while the models are still warming-up, they may still be separated by a distance exceeding δ, but as the models converge over time, the distance may drop below δ, which iterative merging accounts for. A more complete description of Algorithm 2 is described in Appendix C.

Table 1: Average accuracy (%) across all clients and time (over 5 trials, intervals represent 1 std dev)

	SINE-2	CIRCLE-2	SEA-2	MNIST-2	SEA-4	MNIST-4
Oblivious	50.44 ± 1.52	88.36 ± 0.27	86.37 ± 0.34	87.25 ± 0.14	85.38 ± 0.28	82.97 ± 0.04
DriftSurf	83.90 ± 1.01	92.54 ± 0.67	87.27 ± 0.34	91.71 ± 1.60	85.48 ± 0.28	82.99 ± 0.05
KUE	87.05 ± 0.12	93.83 ± 0.04	87.62 ± 0.42	89.74 ± 0.07	85.53 ± 0.12	79.78 ± 0.16
AUE	86.06 ± 0.60	92.74 ± 0.51	87.46 ± 0.12	92.19 ± 0.07	85.55 ± 0.08	81.29 ± 0.19
Window	86.42 ± 0.74	93.67 ± 0.15	88.08 ± 0.10	92.15 ± 0.34	85.76 ± 0.16	81.16 ± 0.46
Adaptive-FedAvg	78.02 ± 10.73	86.26 ± 0.00	86.69 ± 0.39	92.16 ± 0.04	85.32 ± 0.25	81.62 ± 0.07
FedDrift-Eager	98.46 ± 0.03	97.86 ± 0.20	88.35 ± 0.37	**95.99 ± 0.06**	88.08 ± 0.24	89.21 ± 2.02
FedDrift	**98.48 ± 0.01**	**97.88 ± 0.17**	**88.65 ± 0.43**	95.93 ± 0.01	**88.41 ± 0.29**	**94.09 ± 0.08**
Oracle	98.46 ± 0.01	97.57 ± 0.59	88.53 ± 0.23	96.00 ± 0.02	88.75 ± 0.20	94.60 ± 0.04

4 Experimental Results

We empirically demonstrate that FedDrift-Eager and FedDrift are more effective than prior centralized drift adaptation and achieve high accuracy comparable to an oracle algorithm in the presence of distributed drifts. Our evaluation is on the synthetic drifts in Figures 2 and 3, which (i) occur across clients with staggered timing, (ii) correspond to different concept changes across different clients, and (iii) involve recurring concepts (e.g., the sequence A–B–C–D–A). The 2-concept and 4-concept drift patterns are generated for the datasets SINE [30], CIRCLE [30], SEA [3], and MNIST [23], described in Appendix D. We also evaluate on the real-world FMoW-WILDS dataset [21] in Appendix E.

We compare against the following baselines. First, the Oblivious algorithm learns a single model with FedAvg. Second, we consider drift adaptation algorithms applied at the server on top of FedAvg: the drift detection method DriftSurf [36], two ensemble methods KUE [6] and AUE [5], and a Window method that forgets data older than one time step. Third, Adaptive-FedAvg [7] is an FL algorithm that learns a single model and adapts to drifts by centrally tuning the learning rate based on the variability across updates. Fourth, Oracle has oracle access to the ground-truth clustering at training time. Appendix E reports additional less competitive baselines for clustered FL [15, 32].

In Table 1, we report the average test accuracy across clients and time. Across the 2-concept drift datasets, we observe that the multiple-model algorithms FedDrift-Eager and FedDrift outperform prior centralized solutions. In Figure 4(left), the accuracy is broken down per time step on CIRCLE-2, where we observe that centralized algorithms particularly suffer during the transition period—when both concepts simultaneously exist, there is no single model that is an accurate fit at all clients. Even the ensemble algorithms KUE and AUE have poor performance because each model is updated by each client, and there is no available model trained solely over data from the second concept. On the other hand, the clustering of FedDrift-Eager and FedDrift learn models specialized for the second concept immediately after it emerges, achieving performance matching Oracle.

For the 4-concept drift, the accuracy per time step on MNIST-4 is shown in Figure 4(right). We refer to the clustering learned by FedDrift in Figure 5, in which each cell indicates the model ID, and the background color indicates the ground-truth concept. We observe that at time 3, a local model is created for 5 of the 6 drifted clients, and by time 5, under iterative hierarchical clustering, a distinct model is learned for each concept with no excess models. The accuracy of FedDrift is close to Oracle throughout, with a gap at time 3 when each local model is created. Meanwhile, for FedDrift-Eager, just one model is initially created for both the yellow and green concepts, and its accuracy takes longer to recover. The performance of the centralized baselines never recover.

To conclude, our evaluation under distributed drifts demonstrates that FedDrift-Eager and FedDrift achieve accuracy significantly higher than existing baselines and comparable to an oracle algorithm.

Figure 4: Accuracy over time (averaged over clients).

Figure 5: FedDrift on MNIST-4.

References

[1] Manuel Baena-García, José del Campo-Ávila, Raúl Fidalgo, Albert Bifet, R Gavaldà, and R Morales-Bueno. Early drift detection method. In *StreamKDD*, pages 77–86, 2006.

[2] Romil Bhardwaj, Zhengxu Xia, Ganesh Ananthanarayanan, Junchen Jiang, Nikolaos Karianakis, Yuanchao Shu, Kevin Hsieh, Victor Bahl, and Ion Stoica. Ekya: Continuous learning of video analytics models on edge compute servers. *CoRR*, abs/2012.10557, 2020.

[3] Albert Bifet, Geoff Holmes, Richard Kirkby, and Bernhard Pfahringer. MOA: Massive online analysis. *JMLR*, 11:1601–1604, 2010.

[4] Christopher Briggs, Zhong Fan, and Peter Andras. Federated learning with hierarchical clustering of local updates to improve training on non-iid data. In *International Joint Conference on Neural Networks (IJCNN)*, 2020.

[5] Dariusz Brzezinski and Jerzy Stefanowski. Reacting to different types of concept drift: The accuracy updated ensemble algorithm. *IEEE Trans. Neural Netw. Learn. Syst*, 25(1):81–94, 2013.

[6] Alberto Cano and Bartosz Krawczyk. Kappa updated ensemble for drifting data stream mining. *Machine Learning*, 109(1):175–218, 2020.

[7] Giuseppe Canonaco, Alex Bergamasco, Alessio Mongelluzzo, and Manuel Roveri. Adaptive federated learning in presence of concept drift. In *International Joint Conference on Neural Networks*, pages 1–7, 2021.

[8] Fernando E Casado, Dylan Lema, Marcos F Criado, Roberto Iglesias, Carlos V Regueiro, and Senén Barro. Concept drift detection and adaptation for federated and continual learning. *Multimedia Tools and Applications*, pages 1–23, 2021.

[9] Yujing Chen, Zheng Chai, Yue Cheng, and Huzefa Rangwala. Asynchronous federated learning for sensor data with concept drift. In *IEEE International Conference on Big Data*, pages 4822–4831, 2021.

[10] Moming Duan, Duo Liu, Xinyuan Ji, Yu Wu, Liang Liang, Xianzhang Chen, Yujuan Tan, and Ao Ren. Flexible clustered federated learning for client-level data distribution shift. *IEEE Transactions on Parallel and Distributed Systems*, 2021.

[11] Joao Gama, Pedro Medas, Gladys Castillo, and Pedro Rodrigues. Learning with drift detection. In *Advances in Artificial Intelligence-SBIA*, pages 286–295, 2004.

[12] João Gama, Indre Zliobaite, Albert Bifet, Mykola Pechenizkiy, and Abdelhamid Bouchachia. A survey on concept drift adaptation. *ACM Comput. Surv.*, 46(4), 2014.

[13] Abhinav Garg, Naman Shukla, Lavanya Marla, and Sriram Somanchi. Distribution shift in airline customer behavior during COVID-19. *CoRR*, abs/2111.14938, 2021.

[14] Avishek Ghosh, Justin Hong, Dong Yin, and Kannan Ramchandran. Robust federated learning in a heterogeneous environment. *arXiv preprint arXiv:1906.06629*, 2019.

[15] Avishek Ghosh, Jichan Chung, Dong Yin, and Kannan Ramchandran. An efficient framework for clustered federated learning. In *NeurIPS*, pages 19586–19597, 2020.

[16] Yongxin Guo, Tao Lin, and Xiaoying Tang. Towards federated learning on time-evolving heterogeneous data. *arXiv preprint arXiv:2112.13246*, 2021.

[17] Maayan Harel, Koby Crammer, Ran El-Yaniv, and Shie Mannor. Concept drift detection through resampling. In *ICML*, pages 1009–1017, 2014.

[18] Chaoyang He, Songze Li, Jinhyun So, Mi Zhang, Hongyi Wang, Xiaoyang Wang, Praneeth Vepakomma, Abhishek Singh, Hang Qiu, Li Shen, Peilin Zhao, Yan Kang, Yang Liu, Ramesh Raskar, Qiang Yang, Murali Annavaram, and Salman Avestimehr. Fedml: A research library and benchmark for federated machine learning. *arXiv preprint arXiv:2007.13518*, 2020.

[19] Peter Kairouz, H Brendan McMahan, et al. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning*, 14(1–2):1–210, 2021.

[20] Ioannis Katakis, Grigorios Tsoumakas, and Ioannis Vlahavas. Tracking recurring contexts using ensemble classifiers: an application to email filtering. *Knowledge and Information Systems*, 22 (3):371–391, 2010.

[21] Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, Tony Lee, Etienne David, Ian Stavness, Wei Guo, Berton Earnshaw, Imran Haque, Sara M. Beery, Jure Leskovec, Anshul Kundaje, Emma Pierson, Sergey Levine, Chelsea Finn, and Percy Liang. WILDS: A benchmark of in-the-wild distribution shifts. In *ICML*, 2021.

[22] Jakub Konečný, H. Brendan McMahan, Felix X. Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *CoRR*, abs/1610.05492, 2016.

[23] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[24] Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. *Proceedings of Machine Learning and Systems*, 2:429–450, 2020.

[25] Jie Lu, Anjin Liu, Fan Dong, Feng Gu, Joao Gama, and Guangquan Zhang. Learning under concept drift: A review. *IEEE Transactions on Knowledge and Data Engineering*, 31(12): 2346–2363, 2018.

[26] Dimitrios Michael Manias, Ibrahim Shaer, Li Yang, and Abdallah Shami. Concept drift detection in federated networked systems. *arXiv preprint arXiv:2109.06088*, 2021.

[27] Yishay Mansour, Mehryar Mohri, Jae Ro, and Ananda Theertha Suresh. Three approaches for personalization with applications to federated learning. *arXiv preprint arXiv:2002.10619*, 2020.

[28] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Proceedings of the International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2017.

[29] Ali Pesaranghader and Herna L Viktor. Fast hoeffding drift detection method for evolving data streams. In *ECML PKDD*, pages 96–111, 2016.

[30] Ali Pesaranghader, Herna L Viktor, and Eric Paquet. A framework for classification in data streams using multi-strategy learning. In *ICDS*, pages 341–355, 2016.

[31] Ali Pesaranghader, Herna L Viktor, and Eric Paquet. McDiarmid drift detection methods for evolving data streams. In *International Joint Conference on Neural Networks (IJCNN)*, 2018.

[32] Felix Sattler, Klaus-Robert Müller, and Wojciech Samek. Clustered federated learning: Model-agnostic distributed multitask optimization under privacy constraints. *IEEE transactions on neural networks and learning systems*, 32(8):3710–3722, 2020.

[33] Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

[34] Hidetoshi Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of statistical planning and inference*, 90(2), 2000.

[35] Abhijit Suprem, Joy Arulraj, Calton Pu, and Joao Ferreira. ODIN: Automated drift detection and recovery in video analytics. *Proceedings of the VLDB Endowment*, 13(11), 2020.

[36] Ashraf Tahmasbi, Ellango Jothimurugesan, Srikanta Tirthapura, and Phillip B. Gibbons. Drift-Surf: Stable-state / reactive-state learning under concept drift. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2021.

[37] Alexey Tsymbal. The problem of concept drift: definitions and related work. *Computer Science Department, Trinity College Dublin*, 106(2), 2004.

[38] Jianyu Wang and Gauri Joshi. Cooperative sgd: A unified framework for the design and analysis of local-update sgd algorithms. *Journal of Machine Learning Research*, 22(213):1–50, 2021.

[39] Gerhard Widmer and Miroslav Kubat. Learning in the presence of concept drift and hidden contexts. *Machine learning*, 23(1), 1996.

A   Related Work

Concept drift refers to a change over time in the joint distribution $\mathcal{P}(x, y)$. By decomposing the joint distribution $\mathcal{P}(x, y) = \mathcal{P}(x)\mathcal{P}(y|x)$, we distinguish between drifts where only $\mathcal{P}(x)$ changes versus drifts where the feature-to-label mapping $\mathcal{P}(y|x)$ changes. Under the former case (which goes by the names virtual drift [37], covariate drift [34], and feature-distribution skew [19]) a single model can perform well despite change (although achieving fast convergence in an FL setting still requires a specialized strategy; e.g., FedProx [24]). But under the latter case where the feature-to-label mapping changes (real drift or concept drift [37]), lower loss can often be obtained by using specialized models for different concepts.

Concept drift has been studied extensively in the centralized setting for decades. We refer the reader to the surveys by Gama et al. [12] and Lu et al. [25]. As discussed in §1, directly applying centralized adaptation to a single global model in FL is not well-suited for distributed concept drifts with heterogeneous data across time and clients. Furthermore, centralized ensemble methods that use multiple models for adapting to drift also suffer, because the models in an ensemble are distinguished solely over time, and do not account for heterogeneity across clients—in response to a localized data drift, any newly created global model is trained over a mixture of concepts. We demonstrate this in our experimental evaluation, where we compare against state-of-the-art algorithms such as DriftSurf [36] and KUE [6].

Drift in FL, on the other hand, has so far seen only preliminary study. One line of work considers the setting where there is one concept in the system to be learned (either like the example in Figure 1(right) when a minority of clients drift, or when clients observe the main concept under random noise), and seek to speed up the convergence of a model for that one concept by suppressing clients with heterogeneous data via regularization [9, 16] or drift detection [26]. When it comes to adapting to a new concept over time, we are only aware of two works, and both only consider drifts with uniform timing like the example in Figure 1(left). First, Casado et al. [8] consider only the *virtual drift* setting (where the labeling $\mathcal{P}(y|x)$ is fixed and only $\mathcal{P}(x)$ changes) and uses drift detection to partition data from distinct concepts, in order to train a single model accurately in the course of revisiting each partition (i.e., rehearsal). Second, Canonaco et al. [7] propose Adaptive-FedAvg, in which the server tunes the learning rate used by all clients as a function of the variability across updates, with the goal of reacting fast when drift occurs while also achieving stable performance in the absence of drift. In our experimental evaluation, we compare against Adaptive-FedAvg.

Our solution to drift in FL relies on learning multiple models, which has been studied in prior work on *personalized FL* and *clustered FL*. Clients with similar data can be grouped into clusters, where each cluster of clients is associated with a global model that they collaboratively train [4, 10, 14, 15, 27, 32]. As we extend the problem of data heterogeneity in FL with an additional dimension of time, we train multiple models with the algorithm in Appendix B, which is heavily inspired by the prior clustering algorithms IFCA [15] and HypCluster[27]. This serves as the starting point of our solution, where our main contribution is the creation of new clusters as new concepts arrive over time. Finally, our solution in §3 to handle an unknown number of concepts relies on hierarchical clustering, which has been studied in FL (in the static case) previously by Briggs et al. [4]. In the prior work, the clustering is based on clients' local updates, and it is unclear how to set the distance threshold at which to stop merging. In contrast, an advantage of our approach is that the stopping criterion is identical to the drift detection threshold, which has an intuitive interpretation of performance loss.

B   Multiple-Model Training in FL

Distributed concept drift often means that multiple concepts are present simultaneously, necessitating the need for multiple-model training. In §3, we presented algorithms to learn a time-varying clustering of clients, where each cluster is associated with a global model. In this section, we show how train models for each cluster in Algorithm 3.

We define a time step as the granularity at which new data may arrive at a client. A time step may consist of multiple communication rounds. The set of data arriving at client c and time t is denoted by $S_c^{(t)}$. The global models being trained are denoted by h_m for $m \in [M]$, where M is the total number of models at a given time. Each model is trained by a cluster of clients, where the clustering may vary over time as concept drifts occur. The cluster identity of client c at time t is denoted by the

one-hot vector $w_c^{(t)}$, where $w_{c,m}^{(t)} = 1$ when assigned to the cluster associated with model h_m and 0 otherwise. The cluster identities $w_{c,m}^{(t)}$ indicate whether the data $S_c^{(t)}$ that arrived at client c at time t are sampled when computing a local update to the global model h_m. Further, the cluster identity of a client at a given time indicates which model is used for inference.

Within each time, the training of the global models in Algorithm 3 is equivalent to Federated Averaging [28], since the aggregation weight of each client within each cluster is fixed at time τ. So the convergence of Algorithm 3 can be guaranteed by directly using previous analyses for Federated Averaging, such as [24, 38]. The difference here is that the objective function that clients are minimizing at time τ is replaced by the following:

$$\tilde{F}_m^{(\tau)}(h_m) = \sum_{c=1}^{P} \tilde{w}_{c,m}^{\tau} F_c^{(\tau)}(h_m) \tag{2}$$

where $F_c^{(\tau)}$ denotes the local objective function on client c, and the normalized weight is defined as $\tilde{w}_{c,m}^{\tau} = \sum_{t=1}^{\tau} w_{c,m}^{(t)} N_c^{(t)} / \sum_{c=1}^{P} \sum_{t=1}^{\tau} w_{c,m}^{(t)} N_c^{(t)}$.

In the ideal case where each cluster maps to one concept in the system, each h_m is specialized for each concept that is sampled from a unique data distribution ($\mathcal{P}(x, y)$), and these h_m form a strong solution to our overall objective in §2. This ideal solution is the Oracle algorithm in our evaluation in §4, and we empirically demonstrate in §4 that our proposed solutions achieve comparable accuracy.

Algorithm 3 Multiple-model training at time τ

Input: Cluster identities $w_{c,m}^{(t)}$
  for each round $i = 1, 2, \ldots, R$ **do**
    for each client $c = 1, 2, \ldots, P$
    and each model $m = 1, 2, \ldots, M$ in parallel **do**
      $h_{c,m} \leftarrow \text{LOCALUPDATE}(c, h_m, \{w_{c,m}^{(t)}\}_{t=1}^{\tau})$
    for each model $m = 1, 2, \ldots, M$ **do**
      $h_m \leftarrow \dfrac{\sum_{c=1}^{P} h_{c,m} \sum_{t=1}^{\tau} w_{c,m}^{(t)} N_c^{(t)}}{\sum_{c=1}^{P} \sum_{t=1}^{\tau} w_{c,m}^{(t)} N_c^{(t)}}$

  $\text{LOCALUPDATE}(c, h_m, \{w_{c,m}^{(t)}\}_{t=1}^{\tau})$:
  for each local step $j = 1, 2, \ldots, K$ **do**
    $b \leftarrow$ random minibatch of size B from
      $\cup_{t:w_{c,m}^{(t)}=1} S_c^{(t)}$
    $h_m \leftarrow h_m - \eta \nabla \ell(h_m; b)$
  return h_m

τ	current time (prior time indexed by t)
P	# clients (indexed by c)
M	# global models (indexed by m)
R	# communication rounds (indexed by i)
K	# local steps per model per round (by j)
$S_c^{(t)}$	new data arriving at client c at time t
$N_c^{(t)}$	$= \lvert S_c^{(t)} \rvert$
B	minibatch size
η	step size
h_m	global model m
$h_{c,m}$	local update of h_m by client c
$w_{c,m}^{(t)}$	is $S_c^{(t)}$ used to update h_m?

Algorithm 4 Clustering to the lowest loss

$\ell_{c,m}^{(\tau)} \leftarrow$ loss of h_m on client data $S_c^{(\tau)}$
$w_{c,m}^{(\tau)} \leftarrow \mathbf{1}\{m = \arg\min_{m'} \ell_{c,m'}^{(\tau)}\}$
Run Algorithm 3

Note that, as stated, each client c in Algorithm 3 retains its complete history of both the cluster indicators $w_{c,m}^{(t)}$ and the local data arrivals $S_c^{(t)}$. To reduce this overhead, each client could instead maintain just a sliding window of the most recent time steps, as long as the window suffices for the minibatch sampling in LOCALUPDATE.

Finally, Algorithm 4 depicts a clustering in the absence of a mechanism for spawning new clusters, and is closely related to prior static clustering algorithms [15, 27]. In Appendix E, we present experimental results for Algorithm 4 on each dataset.

C   Detailed Description of FedDrift

In this section, we give a more complete presentation of Algorithm 2 first described in §3.2

First, we contend the fundamental challenge of clustering is reacting to new concepts when they emerge. Hypothetically, consider a warm-start setting in which there is a global model already initialized for each concept up to some moderate accuracy. In order to determine the cluster identities for each new time step τ, each client can first test the global models from the previous time step over its newly arrived data; we denote the loss of model h_m over the client data $S_c^{(\tau)}$ as $\ell_{c,m}^{(\tau)}$. Then,

it suffices to use the rule $w_{c,m}^{(\tau)} \leftarrow \mathbf{1}\{m = \arg\min_{m'} \ell_{c,m'}^{(\tau)}\}$, where each client identifies with the model with the best loss. This warm-start setting encompasses time steps involving drifts that occur between concepts known to the system; e.g., the later stages of a staggered drift from concept A to concept B after some clients have already observed concept B (Figure 2).

When new concepts are detected across clients, in general we do not know how many new clusters to create. Algorithm 2 addresses the uncertainty by leveraging hierarchical clustering. The generic hierarchical clustering procedure is specified by a distance function over the set of elements to be clustered and a stopping criterion, and at each step until the stopping criterion is met, merges the two closest clusters, where the distance between clusters of multiple elements is commonly defined to be the maximum distance between their constituents (known as a max-linkage clustering). Algorithm 2 merges clusters as shown in Algorithm 5, combining two clusters i and j by averaging their models with weight proportional to the size of each model's training dataset (over all clients) and unifying the cluster identities.

Algorithm 5 MERGE(i, j, D)

Add a new model $h_k \leftarrow \dfrac{h_i \sum_{c,t} w_{c,i}^{(t)} N_c^{(t)} + h_j \sum_{c,t} w_{c,j}^{(t)} N_c^{(t)}}{\sum_{c,t} w_{c,i}^{(t)} N_c^{(t)} + \sum_{c,t} w_{c,j}^{(t)} N_c^{(t)}}$

$w_{c,k}^{(t)} \leftarrow w_{c,i}^{(t)} + w_{c,j}^{(t)}$ for all c, t

$D(k,l) = \max(D(i,l), D(j,l))$ for all l

Delete models h_i, h_j

To specify a distance function for hierarchical clustering, Algorithm 2 first aggregates at the server the loss estimates L_{ij} of the model h_i evaluated over a subsample of the data associated with the cluster for model h_j. [1] Then the distances between each cluster are initialized as $D(i,j) \leftarrow \max(L_{ij} - L_{ii}, L_{ji} - L_{jj}, 0)$.[2] The first term $L_{ij} - L_{ii}$ measures the loss degradation of model h_i when evaluated over the data associated with h_j, relative to the loss over its own data. We informally interpret this difference as the magnitude of drift between the concept associated with h_i to the concept associated with h_j, analogous to the drift detection condition (although not identical due to the bias of L_{ii} measuring a model's accuracy over its own training data). The term $D(i,j)$ is defined to be symmetric by also accounting for the magnitude of the drift $L_{ji} - L_{jj}$ in the reverse direction from concept j to concept i.

In addition to defining the cluster distances $D(i,j)$, employing hierarchical clustering also requires setting a stopping criterion. Typically, that corresponds to specifying either the desired number of clusters (which in our case is unknown), or an upper limit on the distance between clusters to stop merging. By our identification of the cluster distance as a magnitude of drift, we re-use the drift detection threshold δ to also represent the tolerance level up to which clusters can be merged in Algorithm 2, which avoids introducing another hyperparameter.

In Algorithm 2, both creating new clusters and merging existing clusters are based on the observed difference of the models' accuracy across two samples of data. For the clustering to accurately distinguish concepts, we assume that relevant changes in the concepts are manifested in the degradation of a model's predictive accuracy, and that the local sample size is sufficient for statistical significance—the same assumptions necessary for prior drift detection tests [17, 29, 31, 36].

The hierarchical clustering strategy of Algorithm 2 allows it to adaptively determine the appropriate number of clusters even when an unknown number of new concepts emerge at a time, but it also incurs additional computational resources relative to Algorithm 1. Algorithm 2 creates more global models M, adding to the communication cost of sending $O(MP)$ models. Additionally, the hierarchical clustering adds an $O(M^2 \log M)$ time complexity at the server at every time step (using a heap data structure for finding the minimum pairwise distance). In Appendix E, we discuss how we might restrict Algorithm 2 to create fewer overall models for higher efficiency.

---

[1]More precisely, at client c, the data clustered to h_j are sampled proportionate to the size of the local dataset relative to the global dataset for h_j, $\sum_t w_{c,j}^{(t)} N_c^{(t)} / \sum_{c'} \sum_t w_{c',j}^{(t)} N_{c'}^{(t)}$.

[2]We note that $D(i,j)$ is not necessarily a true distance function as there is no guarantee that it satisfies the triangle inequality.

421 Similar to Algorithm 3, each client c could maintain $w_{c,m}^{(t)}$ and $S_c^{(t)}$ for just a sliding window of the
422 most recent time steps, as long as the window suffices for Algorithm 2's subsampling step.

D Datasets and Experimental Parameters

424 We consider concept drift with respect to the following datasets previously used in the concept drift
425 and personalized FL literature [4, 5, 7, 26, 36]: SINE and CIRCLE [30] which each have 2 defined
426 concepts, and SEA [3] and MNIST [23], which have up to 4 concepts. In SINE, the first concept is a
427 decision boundary of the sine curve $x_2 < \sin(x_1)$ for data points sampled from the unit square, and
428 the second concept reverses the direction (swapping the labels). In CIRCLE, the two concepts are
429 each decision boundaries of two different circles in the unit square, representing a smaller concept
430 change than SINE. The first circle is centered at (0.2, 0.5) with radius 0.15 and the second circle is
431 centered at (0.6, 0.5) with radius 0.25. In SEA, each concept corresponds to a shifted hyperplane.
432 Each point in SEA has three attributees in [0, 10], where the label is determined by $x_1 + x_2 \leq \theta_j$
433 where j corresponds to 4 concepts, $\theta_A = 9, \theta_B = 8, \theta_C = 7, \theta_D = 9.5$. (The third attribute x_3 is
434 not correlated with the label.) In SEA, at every concept there is noise in the observed labels, where
435 the label is swapped with 10% chance for each data point independently. In MNIST, concept A
436 corresponds to the original labeling of the hand-drawn digits, and under each other concept, the labels
437 of two of the digits are swapped (B swaps digits 1 and 2, C swaps digits 3 and 4, and D swaps digits
438 5 and 6).

439 Experiments are run using the using the FedML framework [18]. For each dataset in our experiments,
440 the training data are distributed across 10 clients and arrive over 10 time steps. The partition of the
441 data at each client and time is a constant 500 number of samples from the concept corresponding
442 to the concept drift patterns in Figures 2 and 3 in §1. SINE and CIRCLE each have two defined
443 concepts, and we generate partitions of the data under the 2-concept staggered drift of Figure 2, while
444 SEA and MNIST have more defined concepts, and we generate partitions under both the 2-concept
445 and 4-concept drift patterns of Figures 2 and 3.

446 In our experimental results, after training at each time τ we report the test accuracy over the data
447 at $\tau + 1$. For clarification, in reporting the accuracy at the last time step 10, we test over an 11th
448 sample of data at each client that is from the same concept observed during training at time 10. We
449 report the accuracy averaged across all clients and all time steps (omitting the time of except for the
450 times of drifts. We omit the times of drift because there is no chance for a client to adapt to the drift
451 yet, and all algorithms suffer from the inevitable performance loss. By omitting the time of drift,
452 we eliminate the noise from beneficial clustering mistakes if by chance a client was clustered to the
453 model appropriate for the test data after the drift. For completeness, the results averaging over all
454 time steps including drifts are in Appendix E.

455 Across all algorithms we evaluate, the algorithms that learn a single model use FedAvg for training,
456 and the clustering algorithms that learn multiple models use Algorithm 3 in Appendix B for training
457 (which reduces to FedAvg when there is one cluster). The training parameters used in our experiments
458 are shown in Table 2. The models trained under each algorithm are fully connected neural networks
459 with a single hidden layer of size $2d$ where d is the number of features.

Table 2: Training parameters

Parameter	Description	Experimental setting
P	# clients	10
R	# communication rounds	100
K	# local steps per model per round	50
$N_c^{(t)}$	number of new data arrivals at client c at time t	500
B	minibatch size	50
η	step size	varies

460 Regarding the learning rate selection, first we discuss all algorithms excluding Adaptive-FedAvg.
461 We searched for learning rates of the form 10^{-a} for $a = 1, 2, 3, 4$, for each dataset, and found that
462 $\eta = 10^{-2}$ was the best for SINE-2, CIRCLE-2, SEA-2, and SEA-4, and that $\eta = 10^{-3}$ was best for

MNIST-2 and MNIST-4. (This held for both of the two extremes among our baselines, Oblivious and Oracle, and we apply the same learning rate across all the algorithms.) Also note that for computing the Local Update at each client, we use the implementation of Adam in PyTorch with the options weight decay $= 10^{-3}$ and amsgrad = True. We treat Adaptive-FedAvg separately, because it uses SGD with its own internal learning rate scheduler as its mechanism to react to drifts. We found that the initial learning rate of 10^{-2} was the best for each dataset with the exception of SINE-2, instead using 10^{-1}. (This higher learning rate explains the high standard deviation in the reported accuracy of Adaptive-FedAvg on SINE-2.)

Next, we report the selection of the drift detection threshold δ in the algorithms DriftSurf, FedDrift-Eager, and FedDrift. While the optimal δ is expected to vary across datasets, even for a fixed dataset, different algorithms can peak in performance at varying δ. The performance of each of these three algorithms for each dataset across δ in the range $0.02, 0.04, \ldots, 0.20$ is shown in Figure 6. To not bias towards any one algorithm, the experimental results are reported for each algorithm and dataset using its best δ. However, using a fixed $\delta = 0.04$ for FedDrift-Eager and FedDrift makes at most a 1 pp difference in the results reported in Table 1 (on one trial).

For all other hyperparameters of the algorithms we evaluate, we follow the parameter choices stated in the original papers, with the following exceptions: for DriftSurf, we use $r = 3$ (which performed better than their suggested $r = 4$) and for AUE, we use $K = 5$ as the total ensemble size (compared to the $K = 10$ in their paper they consider over a significantly longer time horizon.)

Finally, regarding the model training in Algorithm 3 at time τ, we apply one optimization for efficiency to only train models that are currently clustered to. (Although note that any such models are still retained by FedDrift-Eager and FedDrift in order to react to recurring drifts even if they are not actively being trained.)

E   Additional Experimental Results

We present additional experimental results on more baseline algorithms and on variants of our algorithms restricted to limited memory or communication.

Additional Baseline Algorithms.   The additional algorithms presented in this appendix are:

- **Four traditional drift adaptation algorithms.** AUE-PC is a variation of the ensemble method AUE with the ensemble weights set *per-client*. Window-2 is a window method like Window, except that it forgets data older than two time steps instead of one. Weighted-Linear and Weighted-Exp also forget older data like window methods, but do so more gradually by down-weighting older data with either linear or exponential decay.

- **The FL clustering algorithm** CFL [32]. In extending the original static algorithm to our time-varying setting, we also consider a variant CFL-W, in which during training, each client samples only from the window of the newest data arriving at each time.

- **Three variations of the** IFCA **clustering algorithm [15]** that we considered for extending the original algorithm to the time-varying setting. First, IFCA(T) is exactly Algorithm 4 in Appendix B, which defines cluster identities for each client and each time, in order to associate the data within a client that are heterogeneous over time across multiple clusters. IFCA(T) chooses the cluster identity once per *time step* (where time steps consist of multiple communication rounds)—this differs from the original algorithm described by Ghosh et al. [15], which recomputes the cluster identity once per *round*. Second, IFCA does the per-round clustering; more precisely, for each time step τ, the cluster identity $w_{c,m}^{(\tau)}$ is recomputed at every round under the same equation used at the beginning of the time step in Algorithm 4. Third, IFCA-W is a variant of IFCA that trains only over the most recent data arrivals at each time, and the cluster identities of data from previous time steps are forgotten. In general, the IFCA-based algorithms require the number of clusters as input, which we provide as oracle knowledge—either 2 or 4 depending on the total number of concepts over time in each dataset. This gives IFCA-based algorithms an advantage over all other algorithms we evaluate, which do not know the number of clusters a priori. For the initialization of all three variations, at time 1 and round 1, all clients are assigned to a single cluster, matching the assumption we made for FedDrift and FedDrift-Eager in §3.

Figure 6: Average accuracy of each drift detection-based algorithm under varying thresholds δ.

- **A more communication-efficient variant of** FedDrift**.** FedDrift-C is the algorithm referred to in the last paragraph of §4 that is restricted to introducing one new global model per time step. More details on this algorithm are described later in this section.

- **Sliding window variants of** FedDrift-Eager **and** FedDrift**.** FedDrift-Eager-W and FedDrift-W are restricted to using only the most recent time step of data $S_c^{(t)}$ and cluster identities $w_{c,m}^{(t)}$.

- **A baseline sliding window variant** Oracle-W, which has oracle access to the ground-truth clustering but only uses the most recent time step of data in training.

In general, we use the -W suffix in the name of an algorithm to indicate a limited memory of a window of one time step. This memory restriction reduces the number of samples used for training at a time and might reduce the accuracy achievable under ground-truth clustering (Oracle-W vs. Oracle). Yet, the window is not strictly a drawback: (i) forgetting the older data builds in a passive adaptation to drift and (ii) in our setting it also guarantees that each client's training data at a step are all drawn from the same distribution—this is why we also investigate -W variants when extending the prior static clustering algorithms CFL and IFCA to our setting when data arrive over time.

Table 3: Average test accuracy (%) across clients and time, omitting drifts (5 trials)

	SINE-2	CIRCLE-2	SEA-2	MNIST-2	SEA-4	MNIST-4
Oblivious	50.44 ± 1.52	88.36 ± 0.27	86.37 ± 0.34	87.25 ± 0.14	85.38 ± 0.28	82.97 ± 0.04
DriftSurf	83.90 ± 1.01	92.54 ± 0.67	87.27 ± 0.34	91.71 ± 1.60	85.48 ± 0.28	82.99 ± 0.05
KUE	87.05 ± 0.12	93.83 ± 0.04	87.62 ± 0.42	89.74 ± 0.07	85.53 ± 0.12	79.78 ± 0.16
AUE	86.06 ± 0.60	92.74 ± 0.51	87.46 ± 0.12	92.19 ± 0.07	85.55 ± 0.08	81.29 ± 0.19
AUE-PC	87.67 ± 1.70	93.05 ± 0.19	87.61 ± 0.08	92.22 ± 0.09	85.60 ± 0.05	81.43 ± 0.22
Window	86.42 ± 0.74	93.67 ± 0.15	88.08 ± 0.10	92.15 ± 0.34	85.76 ± 0.16	81.16 ± 0.46
Window-2	85.21 ± 1.67	93.03 ± 0.46	87.71 ± 0.33	92.54 ± 0.37	85.67 ± 0.16	82.16 ± 0.32
Weighted-Linear	72.78 ± 1.23	89.91 ± 0.65	87.00 ± 0.01	89.70 ± 0.12	85.49 ± 0.17	82.79 ± 0.05
Weighted-Exp	82.77 ± 0.64	92.69 ± 0.25	87.59 ± 0.15	92.19 ± 0.17	85.59 ± 0.09	82.55 ± 0.06
CFL	60.27 ± 4.82	88.39 ± 0.40	86.36 ± 0.28	86.97 ± 0.40	85.33 ± 0.26	81.95 ± 0.55
CFL-W	95.15 ± 0.32	95.62 ± 1.14	87.66 ± 0.36	90.53 ± 0.81	85.67 ± 0.21	79.99 ± 0.58
IFCA(T)	98.45 ± 0.03	91.72 ± 5.19	86.46 ± 0.23	87.33 ± 0.15	85.44 ± 0.14	82.90 ± 0.05
IFCA	98.46 ± 0.02	92.20 ± 5.32	86.45 ± 0.25	87.55 ± 0.25	85.35 ± 0.09	82.89 ± 0.04
IFCA-W	98.49 ± 0.13	94.31 ± 1.62	88.04 ± 0.17	91.76 ± 0.50	86.17 ± 1.00	81.27 ± 0.43
Adaptive-FedAvg	78.02 ± 10.73	86.26 ± 0.00	86.69 ± 0.39	92.16 ± 0.04	85.32 ± 0.25	81.62 ± 0.07
FedDrift-Eager	98.46 ± 0.03	97.86 ± 0.20	88.35 ± 0.37	$\mathbf{95.99 \pm 0.06}$	88.08 ± 0.24	89.21 ± 2.02
FedDrift	98.48 ± 0.01	$\mathbf{97.88 \pm 0.17}$	$\mathbf{88.65 \pm 0.43}$	95.93 ± 0.01	$\mathbf{88.41 \pm 0.29}$	$\mathbf{94.09 \pm 0.08}$
FedDrift-C	98.51 ± 0.11	97.42 ± 0.57	88.30 ± 0.53	95.85 ± 0.05	87.46 ± 0.42	93.22 ± 0.44
FedDrift-Eager-W	98.51 ± 0.12	97.34 ± 0.76	88.43 ± 0.23	94.05 ± 0.02	87.90 ± 0.25	89.31 ± 0.38
FedDrift-W	$\mathbf{98.58 \pm 0.17}$	97.68 ± 0.09	88.43 ± 0.22	93.95 ± 0.02	88.17 ± 0.39	91.47 ± 0.07
Oracle	98.46 ± 0.01	97.57 ± 0.59	88.53 ± 0.23	96.00 ± 0.02	88.75 ± 0.20	94.60 ± 0.04
Oracle-W	98.47 ± 0.03	97.84 ± 0.11	88.70 ± 0.17	94.04 ± 0.02	88.74 ± 0.13	91.89 ± 0.05

Test Accuracy Results. Table 3 (extending Table 1 in §4) shows the test accuracy of all algorithms, averaged across all clients and time steps, but omitting the times of drifts. As noted in §4, we omit the times of drift when all algorithms suffer from the performance loss. For completeness, the test accuracy averaged over all time steps including drifts is shown in Table 4. In this latter table, note that Oracle and Oracle-W suffer a performance loss too at the time of drift. Under the test-then-train evaluation, Oracle has access to the concept ID of the data at training time but not at test time, where at each client, the model used for inference corresponds to the observed concept in the most recently arrived training data. (Aside: in either table, there are some instances where the accuracy of FedDrift-Eager and FedDrift are seemingly higher than Oracle but within the standard deviation, which we attribute to randomness in the training.)

Based on these tables, we make the following observations on the additional algorithms. The AUE-PC variant of AUE extends the model weights in the ensemble method to be individualized per-client, based on the performance of each model over each client's local data (as opposed to weights chosen based on the aggregate performance at the server). This additional flexibility leads to only a marginal accuracy improvement over AUE across all datasets. While it is generally valuable for clients at different stages of a staggered drift to use different models for inference, the more fundamental obstacle is that each global model trained by AUE-PC is updated by all clients. In the course of the 2-concept staggered drift, all of the models in the ensemble are trained either over a mixture of data from both concepts or solely from the first concept, and there is no accurate model available that is a good fit for the second concept.

The Window-2 algorithm and the weighted sampling algorithms Weighted-Linear and Weighted-Exp are techniques for forgetting older data, but less abruptly compared to Window-1, and in general they all perform similarly. On the sharp drift of SINE-2, the fastest forgetting algorithm Window performs the best of these. On the other hand, on the 4-concept drift of MNIST-4 in which the time axis does not well separate different concepts, the slowest forgetting algorithm Weighted-Linear performs best. Meanwhile, the performance of all four algorithms are close on the SEA datasets, which have greater overlap between the concepts.

The clustering algorithms CFL and CFL-W start with each client in one cluster, and recursively split clusters over rounds and over time based on the intra-cluster similarity of their local updates. We observe that the CFL-W variant is the better-performing of the two on each dataset except MNIST-4

Table 4: Average test accuracy (%) across clients and time, including drifts (5 trials)

	SINE-2	CIRCLE-2	SEA-2	MNIST-2	SEA-4	MNIST-4
Oblivious	45.77 ± 1.52	87.12 ± 0.26	86.12 ± 0.35	86.28 ± 0.12	85.11 ± 0.24	81.60 ± 0.03
DriftSurf	79.19 ± 0.88	91.16 ± 0.68	87.00 ± 0.35	90.55 ± 1.68	85.13 ± 0.19	81.62 ± 0.04
KUE	87.05 ± 0.12	93.83 ± 0.04	87.62 ± 0.42	89.74 ± 0.07	85.53 ± 0.12	79.78 ± 0.16
AUE	81.28 ± 0.81	91.50 ± 0.46	87.21 ± 0.11	91.07 ± 0.07	85.15 ± 0.07	79.65 ± 0.25
AUE-PC	82.18 ± 2.01	91.75 ± 0.17	87.34 ± 0.08	91.07 ± 0.09	85.16 ± 0.04	79.70 ± 0.24
Window	81.92 ± 0.88	92.40 ± 0.11	87.86 ± 0.08	91.35 ± 0.43	85.33 ± 0.10	78.88 ± 0.62
Window-2	80.35 ± 2.02	91.73 ± 0.49	87.45 ± 0.34	91.47 ± 0.47	85.24 ± 0.15	80.06 ± 0.61
Weighted-Linear	67.20 ± 1.43	88.67 ± 0.64	86.77 ± 0.02	88.56 ± 0.12	85.16 ± 0.11	81.38 ± 0.04
Weighted-Exp	76.80 ± 0.88	91.30 ± 0.26	87.34 ± 0.16	91.05 ± 0.18	85.19 ± 0.06	80.96 ± 0.07
CFL	54.41 ± 4.33	87.08 ± 0.31	86.10 ± 0.30	86.00 ± 0.38	85.00 ± 0.25	80.45 ± 0.64
CFL-W	86.83 ± 0.55	93.72 ± 0.93	87.36 ± 0.42	89.47 ± 0.74	85.25 ± 0.17	77.35 ± 0.81
IFCA(T)	88.77 ± 0.02	90.06 ± 4.62	86.22 ± 0.22	86.36 ± 0.14	85.12 ± 0.09	81.53 ± 0.05
IFCA	88.78 ± 0.02	90.49 ± 4.73	86.21 ± 0.28	86.56 ± 0.21	85.06 ± 0.04	81.51 ± 0.03
IFCA-W	88.80 ± 0.12	92.84 ± 1.19	87.84 ± 0.14	90.81 ± 0.67	85.52 ± 0.50	79.17 ± 0.39
Adaptive-FedAvg	73.82 ± 10.75	85.60 ± 0.00	86.55 ± 0.35	91.31 ± 0.05	85.01 ± 0.21	79.45 ± 0.06
FedDrift-Eager	88.76 ± 0.01	95.51 ± 0.18	87.86 ± 0.33	**94.09 ± 0.05**	86.64 ± 0.18	83.58 ± 0.79
FedDrift	88.77 ± 0.02	**95.54 ± 0.15**	**88.13 ± 0.39**	94.03 ± 0.02	**86.68 ± 0.20**	**85.72 ± 0.07**
FedDrift-C	88.82 ± 0.09	95.12 ± 0.50	87.78 ± 0.44	93.97 ± 0.05	86.21 ± 0.40	85.62 ± 0.47
FedDrift-Eager-W	88.82 ± 0.12	95.05 ± 0.67	87.87 ± 0.23	92.04 ± 0.03	86.44 ± 0.20	82.15 ± 0.32
FedDrift-W	**88.88 ± 0.15**	95.35 ± 0.08	87.95 ± 0.15	91.93 ± 0.03	86.46 ± 0.31	83.29 ± 0.06
Oracle	88.77 ± 0.01	95.25 ± 0.52	87.99 ± 0.20	94.11 ± 0.02	86.89 ± 0.17	86.10 ± 0.03
Oracle-W	88.77 ± 0.03	95.51 ± 0.10	88.15 ± 0.14	92.03 ± 0.01	86.83 ± 0.06	83.58 ± 0.03

Figure 7: The clustering learned by CFL-W on SINE-2. The number at each client and time indicates the model ID and the background color indicates the ground-truth concept.

(which is also the only dataset where Oblivious outperforms Window), and is a consequence of the passive drift adaptation of its sliding window which forgets older data. The performance of CFL-W is relatively high on SINE-2 and CIRCLE-2. As an example, the clustering learned on SINE-2 is shown in Figure 7. We observe that, for the first 6 time steps, it correctly distinguishes the two concepts by using distinct models. The disadvantage of the clustering of CFL-W is that it creates excess models for the same concept and does not take full advantage of collaborative training. At time 5, it is limited to splitting its cluster for model 0 when the green concept occurs, but cannot merge the drifted clients to the existing cluster created for the green concept at the previous time step.

For IFCA, IFCA-W, and IFCA(T), the clustering is pre-initialized with a random model for each concept that can occur over time for each dataset. In general, we observe that this is not a reliable method for reacting to drift. All the IFCA variants perform well under the sharp label-swap drift of SINE-2. When the new concept occurs, the drifted clients cluster to the second model, and the learned clustering matches the ground-truth. On CIRCLE-2, we found that IFCA and IFCA(T) learned

Table 5: Average accuracy (%), omitting drifts

	MNIST-R
Oblivious	85.12 ± 1.37
FedDrift-Eager	89.85 ± 1.49
FedDrift	94.06 ± 0.38
Oracle	95.03 ± 0.15

Table 6: Average accuracy (%), including drifts

	MNIST-R
Oblivious	83.92 ± 1.23
FedDrift-Eager	85.26 ± 0.81
FedDrift	86.77 ± 0.76
Oracle	87.32 ± 0.86

the correct clustering in 2 out of 5 trials, and otherwise used only a single model in the other 3 trials. IFCA-W learned the correct clustering in 1 out of 5 trials. (Note the high standard deviation in Table 3.) On the remaining datasets, none of the three algorithms ever used more than a single model (with one exception—on SEA-4, in 1 out of 5 trials, IFCA-W used a distinct model for the yellow concept). For these remaining datasets, we observe that IFCA and IFCA(T) degrade to the Oblivious algorithm, and that IFCA-W degrades to the Window algorithm. The authors of the original paper on IFCA note that the accuracy of the clustering is sensitive to the initialization of the models, and propose random restarts to address this issue, but restarts do not translate well to the time-varying setting we study. In our work, FedDrift-Eager and FedDrift address the initialization problem by using drift detection to deal with new concepts as they occur and to cultivate new clusters.

We consider a more communication-efficient variant of FedDrift that we call FedDrift-C. As noted in §3, one of the drawbacks of FedDrift is that it can create more models compared to FedDrift-Eager, adding to the communication cost. The goal is to only use a number of global models close or equal to the number of distinct concepts, and while FedDrift can hierarchically merge created models of the same concept, FedDrift can observe temporary spikes in the number of global models. To mitigate this cost, we consider the variant FedDrift-C, which differs from FedDrift in that, at each time after drift occurs, only one random client that drifted contributes its local model as a global model. In the case that multiple new concepts occur at a time, only one of the new concepts will be learned immediately, but clients that are still at an unlearned concept can detect drift again at the following time step, and get another chance to contribute its local model. Meanwhile, while a concept goes unlearned globally, the drifted clients do not contribute to any of the global models. We observe that the accuracy of the FedDrift-C variant is only marginally sub-optimal relative to FedDrift on MNIST-4, and is superior to FedDrift-Eager.

For FedDrift-Eager-W and FedDrift-W, restricting to a window has minimal impact on the accuracy for the SEA dataset. There is a significant loss of accuracy for the MNIST dataset relative to the non-windowed versions, but note that the same significant loss occurs when going from Oracle to Oracle-W, so this loss is a result of windowing, not specific to our algorithm. Indeed, the accuracy of FedDrift-W is quite close to Oracle-W.

Random Drift Patterns. Throughout this paper, we have considered the 4-concept drift pattern in Figure 3 in §2 as a specific concrete example in order to depict the challenges in distributed concept drift, motivate the design of FedDrift, and discuss the experimental performance by comparing the learned clustering matrix to the ground-truth. To demonstrate the performance of our algorithms more generally, we consider a family of datasets MNIST-R with random concept changes. Using the same four concepts as in MNIST-4, MNIST-R is generated with all clients at the first concept to start, and then each client independently randomly observes one of the four concepts every two time steps (as opposed to every time step which is not possible to adapt to). We evaluate both FedDrift-Eager and FedDrift, compared to the single-model baseline Oblivious and the ideal multiple-model baseline Oracle. Across 5 random seeds, the average accuracy is shown in Table 5 (and in Table 6 for all time including drifts). We observe that the performance of FedDrift is close to that of Oracle. Meanwhile, the performance of FedDrift-Eager is behind, given that it is likely to have multiple new concepts occurring simultaneously in MNIST-R.

Impact of False Positives. To demonstrate the application of the hierarchical clustering in FedDrift, in §4 we discussed the example of the learned clustering for MNIST-4 in Figure 5. Here in Figure 8 we present another example on SINE-2 at a small $\delta = 0.01$ (corresponding to more aggressive detection) to demonstrate an example of how hierarchical clustering can be beneficial even in the case of a 2-concept drift in mitigating false positives. At time 3, in both FedDrift-Eager and FedDrift, there

Figure 8: The clustering learned on SINE-2 when $\delta = 0.01$. Each cell indicates the model ID at each client and time step, and the background color indicates the ground-truth concept.

are three false positives, where in FedDrift-Eager, the new model 1 is retained but its underlying data forgotten, while in FedDrift, although initially 3 redundant models are created, they are all merged back with model 0 within 2 time steps, averaging their parameters and reincorporating their clustered data. Time step 4 also shows a convincing advantage for hierarchical clustering when 2 false positives and 2 true positives occur together. In FedDrift-Eager, one new model is created for all the clients, but this new model is "poisoned" by contributions from the blue concept and does not work well at time 5, resulting in another drift detection to create model 3 (and forgetting about the data associated with model 2). FedDrift, on the other hand, creates models solely trained over either the blue and green concepts, and eventually merges all models of an identical concept, recovering all of the data. While the false positive mitigation demonstrated in this example is not a significant contributor to the observed higher accuracy of FedDrift in our evaluation because we use higher δ values as noted in Appendix D, it is relevant when there is greater uncertainty in selecting the threshold hyperparameter.

Real-World Drift in FMoW-WILDS. In order to evaluate our proposed solution on a more realistic dataset, we also conducted an evaluation using FMoW-WILDS [21], where the task is to identify 1 out of 62 building types (e.g., shopping mall, apartment building) from a satellite image. The satellite images are collected over time, and contains changes in the data distribution both over time and between regions as infrastructure changes due to economic and environmental factors. The curators of the dataset particularly noted a loss in a model's predictive accuracy over time in rapidly developing areas of Africa. The images in the dataset are annotated with the year taken (between 2002-2017) and the region (one of Asia, Europe, Africa, Americas, and Oceania). To translate it into our experimental setup, we identify each region as one client, and each 4-year period as one time step, subsampling up to 500 images per client per time step from the original dataset. Regarding the parameter settings, the optimal initial learning rate was 10^{-4}, except for Adaptive-FedAvg which was 10^{-2}. The optimal settings of the thresholds δ were 0.08 for DriftSurf and FedDrift-Eager and 0.16 for FedDrift.

In Table 7, we report the average test accuracy across all clients and time. The Oracle algorithm is omitted because the ground-truth is unknown. Note that all the reported accuracies are low because, for training efficiency, the model used in all algorithms is a simple neural network with a single hidden layer, but the relative differences between the algorithms is relevant. We observe that the accuracy of both FedDrift-Eager and FedDrift are higher than the other baselines. Specifically, we observe that the clustering learned by FedDrift-Eager over time split the Africa region into its own cluster, and that in addition, FedDrift learned another cluster unifying both the Americas and Oceania. In future work, we will perform a more comprehensive evaluation over this dataset using larger neural networks.

Table 7: Average accuracy (%)

	FMoW-WILDS
Oblivious	9.24 ± 0.12
DriftSurf	9.41 ± 0.17
KUE	9.86 ± 0.23
AUE	9.44 ± 0.17
Window	9.59 ± 0.14
Adaptive-FedAvg	9.39 ± 0.16
FedDrift-Eager	10.24 ± 0.37
FedDrift	$\mathbf{12.46 \pm 0.31}$

(a) SINE-2   (b) SEA-2

(c) MNIST-2   (d) SEA-4

Figure 9: Test accuracy at each time on SINE-2, SEA-2, MNIST-2, and SEA-4. Vertical lines represent standard deviations.

Test Accuracy Over Time. Finally, in Figure 9, we include the plots of the accuracy over time that were omitted from the body of the paper for space, supplementing Figure 4 in §4. (Note the varying scales of the y-axes.) Similarly to Figure 4, here we observe the same general trends: (i) all of the centralized drift adaptation algorithms suffer in performance, particularly during the transition period when no one model works well across all clients; (ii) for the 4-concept drift on SEA-4, centralized baselines never recover in performance when multiple concepts are present; and (iii) FedDrift-Eager lags behind FedDrift on SEA-4 because it creates only one model after the drifts at time 3 corresponding to two concepts, but eventually recovers.