Order-Asymmetry in Diffusion Language Models: Discrete Curl and Conditional Compatibility

Abstract

Diffusion language models decode tokens in flexible orders, but their denoisers provide only local conditionals for partially observed contexts, which need not be compatible with a single joint distribution over an unresolved block. As a result, different commitment orders can induce different order-specific pseudo-joints. We call this model-side failure conditional incompatibility, distinct from data-side dependence. For any two unresolved positions, we define curl as the log-ratio between the pseudo-joints induced by reversing the commitment order; it vanishes exactly when the two orders agree. We then prove that the order-dependent part of sequential decoding error is a data-weighted curl path integral, separate from conditional total correlation and marginal model error. Empirically, pairwise Fisher–Rao curl energy distinguishes list-operation regimes, recovers Sudoku 4×4 constraint structure, and identifies a left-to-right preferred direction on GSM8K for both LLaDA-8B-Instruct and Dream-7B. These results show that order sensitivity reflects a measurable compatibility property of learned local conditionals, not only confidence or data dependence.

1 Introduction

Autoregressive language models factorize text generation into a strict left-to-right product of conditional probabilities. This factorization gives clear probabilistic semantics, but it also imposes an inherent serial bottleneck: the ith token cannot be generated before the preceding $i-1$ tokens have been determined. Diffusion language models (DLMs) relax this constraint by recovering tokens through iterative denoising from highly corrupted text states. Since denoising need not follow a fixed absolute position order, DLMs support arbitrary-order, block-wise, and fully parallel generation (Austin et al., 2021; Sahoo et al., 2024; Lou et al., 2024; Nie et al., 2025; Ye et al., 2025). This flexibility raises a compatibility question: when unresolved tokens are committed in different orders, do these orders induce the same distribution over the block? A DLM denoiser provides local conditionals under partially observed contexts rather than a guaranteed joint distribution. Thus, different commitment orders can induce different order-specific pseudo-joints, making order sensitivity a possible consequence of model-side conditional incompatibility.

Recent theoretical analyses characterize related but distinct aspects of DLM decoding. Parallel decoding and inference schedules have been connected to conditional total correlation and related dependence measures under oracle or optimal-schedule settings (Kang et al., 2026; Chen et al., 2025), while fixed sequential rollout explains how local model error accumulates along one chosen order (Zhang et al., 2026). Practical decoders often lie between these settings: they choose which tokens can be safely committed together using confidence, stability, or learned dependency signals (Wu et al., 2025; Kim et al., 2025; Ringel et al., 2026). What remains less understood is how the decoding distribution changes across different sequential orders within the same block. We study this missing axis through conditional compatibility, connecting DLM decoding to conditionally specified distributions and scan-order effects in incompatible conditional families (Arnold and Press, 1989; Arnold et al., 2001; Kuo and Wang, 2019).

We formalize this order asymmetry with a discrete curl: the log-ratio between the pseudo-joints induced by the local orders $i \to j$ and $j \to i$. We also use Fisher–Rao curl energy as a symmetric magnitude of local incompatibility on the probability simplex. Theoretically, we prove that the order-dependent component of sequential decod-

ing error is governed by a data-weighted curl path integral, separating it from data-side conditional total correlation and marginal model error. Empirically, Fisher–Rao curl energy distinguishes Copy, Sort, and Shuffle on ParallelBench list-operation tasks (Kang et al., 2026), recovers Sudoku 4×4 constraint geometry, and exposes model-induced row–column asymmetry. On GSM8K, the relative curl path integral identifies a local left-to-right preference for both LLaDA-8B-Instruct and Dream-7B, aligning with previously observed left-to-right decoding advantages (Israel et al., 2026) while revealing their local pseudo-joint geometry.

Contributions.

- **Compatibility view.** We formulate DLM block decoding as an order-specific pseudo-joint construction induced by local conditionals, and identify conditional incompatibility as a model-side source of order sensitivity.

- **Curl decomposition.** We define discrete curl as the log-ratio between pseudo-joints induced by reversing a pairwise commitment order, and prove that the order-dependent component of sequential decoding error is exactly a data-weighted curl path integral, separated from conditional total correlation and marginal model error.

- **DLM diagnostics.** We use directed curl and Fisher–Rao curl energy as inference-time diagnostics, showing that learned DLM conditionals exhibit structured incompatibility across list operations, Sudoku constraints, and left-to-right preferences on GSM8K.

2 Related Work

Discrete diffusion language models generate text by iteratively denoising corrupted or masked token states rather than following a fixed left-to-right factorization. Foundational and representative models include D3PMs (Austin et al., 2021), masked discrete diffusion in MDLM (Sahoo et al., 2024) and MD4 (Shi et al., 2024), score-entropy discrete diffusion in SEDD (Lou et al., 2024), and recent large-scale DLMs such as LLaDA (Nie et al., 2025) and Dream (Ye et al., 2025). Alongside model development, recent theoretical analyses have examined the statistical limits of DLM decoding. ParallelBench (Kang et al., 2026) shows that one-shot parallel decoding error is lower-bounded by data

conditional total correlation under oracle model assumptions, and constructs task suites where this bound is tight. Chen et al. (2025) characterize optimal unmasking schedules using total correlation and dual total correlation. Zhang et al. (2026) decompose forward KL of sequential rollout under model error and distinguish forward from reverse KL via incoherence analysis. Other recent work studies confidence-based adaptive decoding (Cai and Li, 2026), and distribution-agnostic schedules that adapt to unknown dependence structure (Zhao and Cai, 2026). These analyses explain parallel-commitment cost, schedule design, and error accumulation along a chosen rollout. Our work instead studies variation across sequential commitment orders within the same block.

Practical DLM decoders use token- or pair-level proxies to decide which positions can be safely committed together. Fast-dLLM (Wu et al., 2025) uses confidence thresholds; KLASS (Kim et al., 2025) uses token-level KL stability; DEMASK (Ringel et al., 2026) attaches a learned pairwise dependency predictor; PUNT (Azangulov et al., 2025) performs binary conditional-independence tests through anchor-and-test procedures; and CoDD (Li et al., 2026) replaces the factorized output with a tractable probabilistic inference layer. These methods motivate the need to understand dependence and compatibility inside decoding blocks.

A classical background line studies conditionally specified distributions, Markov random fields, Gibbs-style constructions, and dependency networks (Besag, 1974; Geman and Geman, 1984; Arnold and Press, 1989; Arnold et al., 2001; Heckerman et al., 2000; Hobert and Casella, 1998). Kuo and Wang (2019) show that incompatible conditional families can produce scan-order-dependent stationary distributions in Gibbs samplers. Our setting is a neural, time-dependent analogue in DLM decoding: learned local conditionals induce order-specific pseudo-joints, and curl serves as a local witness of their incompatibility. Related consistency testing for language models appears in Wagner et al. (2024).

3 DLMs as Local Conditional Specifications

3.1 Local Conditionals Rather Than a Joint

Consider a token sequence $x = (x_1, \ldots, x_L) \in \mathcal{V}^L$ of length L, where each x_i belongs to a vocabulary $\mathcal{V}$. In masked or discrete diffusion language

modeling, the forward process gradually corrupts the original sequence through masks, noisy tokens, or other discrete corruptions, while the reverse process reconstructs text through iterative denoising. Let z_t denote the partially observed state at time step t, and let M_t denote the set of positions that remain masked or corrupted. A typical denoising predictor is written as (Austin et al., 2021; Sahoo et al., 2024; Lou et al., 2024; Nie et al., 2025; Ye et al., 2025)

$$p_\theta(x_i \mid z_t, t), \qquad i \in M_t.$$

For our analysis, we freeze the observed part of z_t and focus on the unresolved coordinates. Let $x = (x_1, \ldots, x_m) \in \mathcal{V}^m$ denote an assignment on those active coordinates, with already observed tokens absorbed into the conditioning context. For any current visible or committed position set A, the denoiser therefore induces a family of partial-context local conditionals

$$q_{\theta,t}(x_i \mid x_A), \qquad i \notin A,$$

where x_A contains the tokens currently visible to the denoiser. A DLM denoiser returns local conditionals under partially observed contexts. These conditionals specify one-step token predictions, but they do not automatically define a jointly normalized distribution over the unresolved block. Compatibility with a single conditional joint is therefore a structural property to be tested, not a consequence of the denoising interface.

3.2 Order-Specific Pseudo-Joints

Fix an observed context index set S and a block $B \subseteq [L] \setminus S$ of unresolved positions. For any permutation $\pi = (\pi_1, \ldots, \pi_{|B|})$ of B, the denoiser induces the order-specific pseudo-joint

$$Q_{\theta,t}^\pi(x_B \mid x_S) = \prod_{m=1}^{|B|} q_{\theta,t}(x_{\pi_m} \mid x_S, x_{\pi_{<m}}).$$

Different orders induce different pseudo-joints unless the partial-context local conditionals are compatible. If there exists a conditional joint $P_{\theta,t}(x_B \mid x_S)$ such that for every prefix set $A \subseteq B$ and every $i \in B \setminus A$,

$$q_{\theta,t}(x_i \mid x_S, x_A) = P_{\theta,t}(x_i \mid x_S, x_A),$$

then every order-specific pseudo-joint satisfies

$$Q_{\theta,t}^\pi(x_B \mid x_S) = P_{\theta,t}(x_B \mid x_S)$$

by the chain rule. In flexible neural denoisers trained through local denoising losses, however, compatibility is a property to be checked rather than an interface guarantee. Block decoding therefore depends not only on which positions are chosen, but also on whether the order-specific pseudo-joints induced by those positions agree.

4 Curl and Order Incompatibility

4.1 Local Curl as a Pseudo-Joint Log-Ratio

Fix a partial context x_S, two unresolved positions $i, j \notin S$, and candidate tokens $a, b \in \mathcal{V}$. Define the two local order-induced pseudo-joints

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = q_{\theta,t}(a \mid x_S)\, q_{\theta,t}(b \mid x_S, x_i{=}a),$$
$$Q_{\theta,t}^{j \to i}(a, b \mid x_S) = q_{\theta,t}(b \mid x_S)\, q_{\theta,t}(a \mid x_S, x_j{=}b).$$

Define the discrete curl, abbreviated as curl,

$$\mathcal{C}_{ij}^{a,b}(x_S, t) =$$
$$\log q_{\theta,t}(x_i = a \mid x_S) + \log q_{\theta,t}(x_j = b \mid x_S, x_i = a)$$
$$- \log q_{\theta,t}(x_j = b \mid x_S) - \log q_{\theta,t}(x_i = a \mid x_S, x_j = b).$$

Theorem 1 (Local curl equals a pseudo-joint log-ratio)**.** *For every x_S, t, i, j, a, b,*

$$\mathcal{C}_{ij}^{a,b}(x_S, t) = \log \frac{Q_{\theta,t}^{i \to j}(a, b \mid x_S)}{Q_{\theta,t}^{j \to i}(a, b \mid x_S)}.$$

Consequently,

$$\mathcal{C}_{ij}^{a,b}(x_S, t) = 0 \quad \forall a, b$$

holds if and only if

$$Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S) = Q_{\theta,t}^{j \to i}(\cdot, \cdot \mid x_S)$$

as distributions. Moreover,

$$\mathbb{E}_{(a,b) \sim Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S)}\big[\mathcal{C}_{ij}^{a,b}(x_S, t)\big] =$$
$$\mathrm{KL}\big(Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S) \,\|\, Q_{\theta,t}^{j \to i}(\cdot, \cdot \mid x_S)\big).$$

This identity follows by expanding the two sequential pseudo-joints. Although algebraically simple, it is operational: it turns order incompatibility into a directly measurable local quantity using only model conditionals.

Directed curl therefore serves two roles at once. Pointwise, it is the signed local preference for the order $i \to j$ over $j \to i$ on the candidate pair (a, b). In expectation under $Q_{\theta,t}^{i \to j}$, it becomes the directed pseudo-joint KL and hence the local penalty for reversing that order.

4.2 Curl Is Not Data Dependence

Any joint distribution is order-compatible by the chain rule:

$$p_{\text{data}}(a, b \mid x_S) = p_{\text{data}}(a \mid x_S)\, p_{\text{data}}(b \mid x_S, a)$$
$$= p_{\text{data}}(b \mid x_S)\, p_{\text{data}}(a \mid x_S, b).$$

Hence if $q_{\theta,t}$ coincides with p_{data} on all relevant partial contexts, $Q_{\theta,t}^{i \to j} = Q_{\theta,t}^{j \to i} = p_{\text{data}}$ and curl vanishes identically. Curl is therefore a strict model-side quantity, computed entirely from $q_{\theta,t}$ and never sourced from the data: nonzero curl certifies that the learned conditional family does not lift to any single joint over the block.

This distinguishes curl from conditional total correlation. For a fixed context x_S,

$$\text{TC}(X_B \mid x_S) := \text{KL}\left(p(x_B \mid x_S) \,\middle\|\, \prod_{i \in B} p(x_i \mid x_S) \right).$$

TC and curl live on different layers: TC measures dependence within a compatible system (the data joint), while curl measures whether the learned conditional family forms a compatible system at all. TC can be large with zero curl; curl can be nonzero with $\text{TC} = 0$.

Separation between dependence and incompatibility.

Proposition 1 (Separation of total correlation and curl). *Data conditional total correlation and curl measure distinct axes. There exist compatible denoisers with $\text{TC}(X_B \mid x_S) > 0$ and zero curl, and there exist incompatible denoisers with $\text{TC}(X_B \mid x_S) = 0$ and nonzero curl.*

Constructive witnesses for both directions are given in Appendix D.1. They show that total correlation belongs to the data conditional, while curl belongs to the learned local conditional specification. The former controls parallel-commitment cost; the latter controls order asymmetry among sequential commitments.

The same curl also admits a discrete exterior-derivative interpretation on the partial-context lattice, which yields the adjacent-swap identity used in the next section.

4.3 From Directed Curl to a Symmetric Magnitude

Directed curl $C_{ij}^{a,b}$ is signed and depends on the chosen local order. For a diagnostic we additionally want an order-agnostic magnitude that vanishes exactly when the two pseudo-joints coincide.

Since $Q_{\theta,t}^{i \to j}$ and $Q_{\theta,t}^{j \to i}$ are points in the probability simplex, we measure their discrepancy with the squared Fisher–Rao distance,

$$\Omega_{ij}^{\text{FR}}(x_S, t) = d_{\text{FR}}^2\left(Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S), Q_{\theta,t}^{j \to i}(\cdot, \cdot \mid x_S) \right).$$

This is the standard information-geometric metric on the simplex. Its bounded form is the squared Hellinger distance H^2 used in our experiments.

5 Curl and Sequential Order Asymmetry

Prior work shows that under Bayes-optimal conditionals, one-shot parallel decoding error is governed by conditional total correlation (Kang et al., 2026; Chen et al., 2025). Our question is different: for the same block, how much does sequential decoding change when the commitment order changes? The answer is that order sensitivity enters only through curl.

Theorem 2 (Sequential decoding error decomposition). *Let*

$$p(x_B \mid x_S) = p_{\text{data}}(x_B \mid x_S).$$

For any block B, observed context x_S, and order π of B,

$$\text{KL}\left(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\pi}(x_B \mid x_S) \right) = \text{TC}(X_B \mid x_S)$$
$$+ \sum_{i \in B} \text{KL}\left(p(x_i \mid x_S) \,\|\, q_{\theta,t}(x_i \mid x_S) \right) - \mathcal{I}_{\theta,t}^{\pi}(x_S),$$

where

$$\mathcal{I}_{\theta,t}^{\pi}(x_S) := \sum_{m=1}^{|B|} \mathbb{E}_p\left[\log \frac{q_{\theta,t}(x_{\pi_m} \mid x_S, x_{\pi_{<m}})}{q_{\theta,t}(x_{\pi_m} \mid x_S)} \right]$$

is the model-perceived intra-block information along order π, evaluated under the data distribution.

This decomposition is the theoretical separation underlying our framework: parallel dependence, marginal model error, and order asymmetry are distinct components. Conditional total correlation captures the first, marginal KL terms capture the second, and only $\mathcal{I}_{\theta,t}^{\pi}$ changes with the commitment order. Curl then gives the local form of this order-dependent variation.

The summand

$$\log q_{\theta,t}(x_{\pi_m} \mid x_S, x_{\pi_{<m}}) - \log q_{\theta,t}(x_{\pi_m} \mid x_S)$$

is the log-ratio of model conditionals at π_m with and without the earlier commitments along π, and

$\mathcal{I}_{\theta,t}^{\pi}$ is the expectation of their sum under p. If $q_{\theta,t}$ agrees with p_{data} on every partial context, the chain rule gives

$$\mathcal{I}_{\theta,t}^{\pi}(x_S) = \text{TC}(X_B \mid x_S)$$

for all π, and Theorem 2 reduces to

$$\text{KL}\big(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\pi}(x_B \mid x_S)\big) = 0.$$

Compatibility thus implies vanishing sequential decoding error along every order. Outside this regime, $\mathcal{I}_{\theta,t}^{\pi}$ differs from TC and depends on π, and the change in $\text{KL}\big(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\pi}(x_B \mid x_S)\big)$ between two orders equals

$$\mathcal{I}_{\theta,t}^{\pi'}(x_S) - \mathcal{I}_{\theta,t}^{\pi}(x_S).$$

Corollary 2.1 (Order asymmetry as a curl path integral). *Let p abbreviate $p(x_B \mid x_S)$. For any two orders π, π' of B,*

$$\text{KL}\big(p \,\|\, Q_{\theta,t}^{\pi}\big) - \text{KL}\big(p \,\|\, Q_{\theta,t}^{\pi'}\big) = -\mathbb{E}_p\left[\sum_{r \in \Gamma} \mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r}, t)\right],$$

where Γ is any adjacent-swap path from π to π'.

The two-position adjacent swap is the elementary building block for comparing arbitrary block orders. In this sense, the pairwise curl is an elementary local quantity, but the order asymmetry of an arbitrary multi-token block is obtained by accumulating these local curl terms along any adjacent-swap path between the two decoding orders.

The corollary makes the structural separation explicit. Conditional total correlation explains the cost of parallel commitment. The difference between two sequential orders is governed entirely by the curl path integral, i.e., by local incompatibility accumulated along the chosen swap path. The same identity also yields Pinsker-type bounds on bounded sample-level order statistics.

6 Experiments

We empirically probe the local conditionals of a pretrained instruction-tuned DLM, asking whether Fisher–Rao curl energy reveals structured incompatibility that varies with task and constraint geometry. We report two statistics: the squared Hellinger form

$$H^2(P, Q) = 1 - \sum_{a,b} \sqrt{P_{ab} Q_{ab}},$$

a bounded reparameterization of Fisher–Rao curl energy that vanishes if and only if the two pseudo-joints coincide, and

$$\text{KL}\big(Q_{\theta,t}^{i \to j} \,\|\, Q_{\theta,t}^{j \to i}\big) = \mathbb{E}_{Q_{\theta,t}^{i \to j}}\left[\mathcal{C}_{ij}^{a,b}(x_S, t)\right].$$

Both pseudo-joints are estimated on a shared top-k support obtained from a base forward pass and renormalized; the conditional terms $q_{\theta,t}(x_j \mid x_S, x_i = a)$ come from intervened forward passes that are cached per candidate token. Full estimator details, top-k stability checks, and the cross-state null baseline are in Appendix B. All scores are computed from model conditionals at inference time.

6.1 Experimental Setup

We use `LLaDA-8B-Instruct` (Nie et al., 2025) in `bfloat16` with seed 42 and maximum sequence length 512. Active sets and masked-pair samples are restricted to the assistant response region; both pseudo-joints are evaluated on a shared per-position top-16 support from a base forward pass, held fixed across conditional intervention passes (Appendix B). All bootstrap 95% CIs use 1000 resamples.

6.2 Incompatibility Across Dependence Regimes

We probe three list-operation tasks from Parallel-Bench (Kang et al., 2026)—Copy, Shuffle, and Sort. Copy and Sort are deterministic permutations of the input: given X, the output Y is uniquely determined, so the conditional total correlation $TC(Y \mid X) = 0$. Shuffle is a random permutation with $TC(Y \mid X) > 0$: under one-step parallel decoding from Kang et al. (2026), Shuffle accuracy converges to zero as the list length n grows, whereas Copy/Sort accuracy remains bounded away from zero.

For each task we draw 200 contexts at mask ratio 0.3 and sample up to 20 masked-position pairs per context from the assistant response.

Table 1 reveals two complementary findings.

(i) Copy validates the vanishing condition. Copy has H^2 near the numerical floor, suggesting that the model's local conditionals compose almost consistently for a position-wise mapping. Shuffle has the largest incompatibility, consistent with the fact that partial contexts make order-conditioned predictions less stable when the target distribution itself is dependent.

Figure 1: Pair-level incompatibility across Copy, Shuffle, and Sort. (**Left, Middle**) Mean H^2 and $\mathbb{E}_{Q_{\theta,t}^{i\to j}}[\mathcal{C}_{ij}^{a,b}]$ with 95% bootstrap CI. (**Right**) Per-pair scatter; the two statistics co-vary as predicted by Proposition 3.

Task	$TC(Y \mid X)$	Pairs	Mean H^2	$\mathbb{E}_{Q_{\theta,t}^{i\to j}}\left[\mathcal{C}_{ij}^{a,b}(x_S,t)\right]$
Copy	0	565	9.3×10^{-6}	4.4×10^{-5}
Sort	0	546	7.5×10^{-5}	2.5×10^{-4}
Shuffle	>0	583	1.4×10^{-3}	6.3×10^{-3}

Table 1: Pair-level incompatibility on three list-operation tasks under LLaDA-8B-Instruct. Mean H^2 and $\mathbb{E}_{Q_{\theta,t}^{i\to j}}[\mathcal{C}_{ij}^{a,b}]$ are our measurements.

(ii) FR exposes incompatibility that TC does not predict. Sort and Copy share the same data-side $TC(Y \mid X) = 0$—both are deterministic permutations of the input—yet FR on Sort is 7.5×10^{-5}, roughly $8\times$ that of Copy and well above the numerical floor. The Sort–Copy gap cannot originate from data-side dependence, since by construction there is none. It must reflect a model-side property: the learned local conditionals on Sort exhibit residual order-dependence that disappears on Copy, despite both tasks being equally tractable for a Bayes-optimal denoiser.

This experiment supports the central distinction developed in the theory. Conditional total correlation describes dependence in the data distribution, while curl energy measures whether the trained denoiser's local conditionals agree across order-induced pseudo-joints. The Copy–Sort gap shows that even within the same deterministic data regime, the learned conditional specification can exhibit different levels of order incompatibility.

6.3 Constraint Structure on Sudoku 4 × 4

We next ask a sharper question: does the geometric profile of incompatibility within a single task reflect that task's known dependence structure? We use the Sudoku 4×4 puzzles from ParallelBench,

in which cells must take distinct values within each row, column, and 2×2 box. We evaluate 100 puzzles, providing 8 ground-truth cells and masking the remaining 8; for each puzzle we compute H^2 for every pair among the masked cells and classify each pair into one of six mutually exclusive geometric classes.

Geometric class	n_{pairs}	Mean H^2	[95% CI]
Independent	1505	0.0071	[0.0064, 0.0078]
Column only	379	0.0078	[0.0068, 0.0087]
Box only	189	0.0099	[0.0081, 0.0115]
Column + box	175	0.0130	[0.0105, 0.0157]
Row only	354	0.0210	[0.0183, 0.0237]
Row + box	198	0.0448	[0.0349, 0.0555]

Table 2: Mean H^2 by exclusive geometric class on Sudoku 4×4 under LLaDA-8B-Instruct. "Box only" denotes pairs in the same 2×2 box that share neither row nor column.

Three features emerge from Table 2 and Figure 2.

(i) The constraint graph is recovered. One-sided Mann–Whitney tests reject equality with the independent baseline at $p < 10^{-3}$ for all three constraint classes.

(ii) Row dominates column. Same-row pairs exhibit $\sim 2.7\times$ the incompatibility of same-column pairs (0.021 vs. 0.008), and column-only is only marginally above independent. Since Sudoku constraints are formally symmetric between rows and columns, this asymmetry must originate in the model rather than the task—most plausibly in the row-major serialization that places same-row cells token-adjacent while separating same-column cells by four tokens.

(iii) Box is a real increment on row. Box-only

Figure 2: Pair-level incompatibility recovers Sudoku constraint structure with a row–column asymmetry. (**Left**) Mean H^2 between anchor cell $(0, 0)$ and the remaining 15 cells. (**Right**) Mean H^2 by exclusive geometric class with 95% bootstrap CI; dashed line marks the independent baseline.

pairs are significant but small (0.010); adding the box constraint to a same-row pair raises H^2 from 0.021 to 0.045 (one-sided Mann–Whitney $p = 2.4 \times 10^{-3}$), so box dependence is learned as a genuine increment.

Crucially, if Fisher–Rao energy merely tracked marginal uncertainty, the three constraint types would yield comparable signal, since they impose symmetric informational restrictions. The asymmetric pattern instead reflects how the model has internalized the constraint structure.

6.4 LTR is Preferred in Pseudo-Joint Geometry

The preceding sections establish FR as a structured, model-side diagnostic. We now ask whether the curl geometry FR captures corresponds to directional preferences in DLM decoding. We address this on two models with different training pipelines: LLaDA-8B-Instruct (Nie et al., 2025) (trained from scratch with a masked diffusion objective) and Dream-7B (Ye et al., 2025) (initialized from the autoregressive Qwen2.5-7B and adapted via diffusion fine-tuning).

Israel et al. (2026) report that on GSM8K, forced left-to-right (LTR) decoding outperforms the default decoding strategies of both LLaDA and Dream. Motivated by this phenomenon, we study whether it is reflected in the local pseudo-joint geometry of DLMs. We replicate this setup and measure each model's geometric preference.

Setup. We run both models on the GSM8K (Cobbe et al., 2021) test set with generation length and diffusion steps set to 256,

Permutation	Kendall to LTR	Mean $\tilde{I}^\pi$	95% CI
123 (LTR)	0	**0.046**	[**0.033**, **0.059**]
132	1	−0.001	[−0.014, 0.013]
213	1	0.011	[−0.002, 0.024]
231	2	−0.008	[−0.020, 0.005]
312	2	−0.025	[−0.038, −0.012]
321 (RTL)	3	−0.023	[−0.036, −0.011]

Table 3: Relative curl path integral $\tilde{I}^\pi$ on LLaDA-8B-Instruct across clean GSM8K mid-decoding blocks. "Kendall to LTR" is the Kendall tau distance to $(1, 2, 3)$. 95% CIs are bootstrap over blocks.

using each model's default decoder (confidence-based for LLaDA, entropy-based for Dream) to generate mid-trajectory states.

We sample size-3 blocks from the mid-trajectory states and enumerate all 6 permutations per block. For each block, we fix the assignment $\hat{x}_B$ to the base-forward argmax tokens at the queried state and evaluate all six permutations on this shared assignment. By Corollary 2.1, the difference $\log Q^\pi_{\theta,t}(\hat{x}_B \mid x_S) - \log Q^{\pi'}_{\theta,t}(\hat{x}_B \mid x_S)$ between any two permutations equals the curl path integral along any adjacent-swap path between them. We define the relative curl path integral as

$$\tilde{I}^\pi = \log Q^\pi_{\theta,t}(\hat{x}_B \mid x_S) - \frac{1}{6} \sum_{\pi'} \log Q^{\pi'}_{\theta,t}(\hat{x}_B \mid x_S), \tag{1}$$

and report the mean and 95% bootstrap CI for each permutation. Blocks whose fixed assignment $\hat{x}_B$ contains special, mask, pad, or non-visible tokens are excluded, as the pseudo-joint is not well-defined for such assignments.

Permutation	Kendall to LTR	Mean $\tilde{I}^\pi$	95% CI
123 (LTR)	0	**0.643**	[**0.485**, **0.813**]
132	1	0.219	[0.060, 0.364]
213	1	−0.146	[−0.291, 0.004]
231	2	−0.181	[−0.347, −0.038]
312	2	0.044	[−0.121, 0.214]
321 (RTL)	3	**−0.578**	[**−0.732**, **−0.408**]

Table 4: Relative curl path integral $\tilde{I}^\pi$ on Dream-7B across clean GSM8K mid-decoding blocks sampled from Dream's default entropy-based trajectory.

LLaDA: LTR is significantly positive; RTL is significantly negative. Table 3 reveals a symmetric directional structure: LTR is the unique permutation with significantly positive mean, the two permutations farthest from LTR (including RTL) are significantly negative, and the intermediate permutations cross zero. $\tilde{I}^\pi$ decreases monotonically with Kendall distance from LTR (Spearman $\rho = -0.88$), and the paired LTR-vs-RTL difference is 0.069 nats ($p < 10^{-7}$).

LLaDA: the preference concentrates in order-sensitive regions. The aggregate effect appears systematically at the block level. LTR is the locally best permutation in 26% of blocks, above the uniform baseline of 17%. When blocks are stratified by order spread $\max_\pi \log Q^\pi - \min_\pi \log Q^\pi$, the mean LTR preference rises monotonically with spread: the bias is weak when the six order-induced pseudo-joints nearly agree, and strongest precisely when the local conditional system is most order-sensitive.

Dream: same direction, substantially larger magnitude. Table 4 replicates the LLaDA finding on Dream: LTR is significantly positive, RTL is significantly negative, and $\tilde{I}^\pi$ decreases monotonically with Kendall distance (Spearman $\rho = -0.85$). The magnitude, however, is roughly an order higher: the paired LTR-vs-RTL difference is 1.22 nats ($p < 10^{-13}$), approximately $18\times$ the value on LLaDA. LTR is also the locally best permutation in 27% of blocks. The directional preference therefore persists across two DLMs with substantially different training pipelines, and is far stronger on the AR-initialized Dream.

Quantitative link to the APD phenomenon. Israel et al. (2026) reports that forcing LTR improves GSM8K accuracy for both LLaDA and Dream, with a larger gain on LLaDA. Our local measurements show the complementary pattern: Dream has a stronger per-block LTR pseudo-joint preference. These observations are consistent because the gain from forced LTR also depends on how well the default decoder aligns with the model's local preference. If the default decoder already follows that preference, forcing LTR yields a smaller additional gain; if it deviates from it, the gain can be larger. Thus, curl captures a local directional bias that trajectory-level accuracy gaps alone do not identify.

Why does Dream prefer LTR more? The cross-model comparison sharpens the mechanism question. The substantially larger bias on Dream is consistent with an additional source of asymmetry: AR initialization. Dream inherits Qwen2.5's autoregressive weights (Qwen et al., 2024), which encode strict left-to-right factorization; diffusion fine-tuning does not fully erase this directional structure, and the pseudo-joint geometry preserves a stronger LTR preference than in the from-scratch trained LLaDA. While we do not isolate this mechanism rigorously, the comparison provides empirical evidence that training-side initialization, beyond training-side data, contributes to DLM directional bias.

7 Conclusion

DLM denoisers provide local conditionals that need not be compatible with a single global joint. This makes block decoding order-specific: each sequential commitment order induces its own pseudo-joint. Curl explains the signed order asymmetry between such pseudo-joints, and Fisher–Rao curl energy diagnoses the magnitude of the local incompatibility. Theorem 2 places this in a structural picture: sequential block decoding error decomposes into conditional total correlation, marginal model error, and a single order-dependent functional, and curl gives the local form of that functional.

The experiments use Fisher–Rao curl energy as a diagnostic and show that this axis is distinct from parallel-dependence. Order sensitivity in DLMs is therefore not only a matter of token confidence or data dependence; it is also a measurable compatibility failure of the learned local conditionals.

Limitations

Our framework isolates conditional compatibility of local denoising conditionals at a fixed partially observed state. This focus separates order asymmetry induced by local pseudo-joint composition

from other trajectory-level factors such as schedule design, sampling temperature, and accumulated token errors, which can interact with the same compatibility structure during full decoding.

The empirical estimator compares order-induced pseudo-joints on restricted shared supports. This makes the comparison stable and tractable, while the scores diagnose high-probability local geometry and do not exhaustively measure the full vocabulary.

We use curl and Fisher–Rao energy as diagnostic quantities rather than a complete online scheduler. Turning these signals into a low-cost decoding policy is a natural direction for future work.

References

Barry C Arnold, Enrique Castillo, and Jose Maria Sarabia. 2001. Conditionally specified distributions: an introduction (with comments and a rejoinder by the authors). *Statistical Science*, 16(3):249–274.

Barry C Arnold and S James Press. 1989. Compatible conditional distributions. *Journal of the American Statistical Association*, 84(405):152–156.

Jacob Austin, Daniel D. Johnson, Jonathan Ho, Daniel Tarlow, and Rianne van den Berg. 2021. Structured denoising diffusion models in discrete state-spaces. In *Advances in Neural Information Processing Systems*.

I. Azangulov, T. Pandeva, N. Prasad, J. Zazo, and S. Karmalkar. 2025. Parallel sampling from masked diffusion models via conditional independence testing. Preprint, arXiv:2510.21961.

Julian Besag. 1974. Spatial interaction and the statistical analysis of lattice systems. *Journal of the Royal Statistical Society. Series B (Methodological)*, 36(2):192–236.

C. Cai and G. Li. 2026. Confidence-based decoding is provably efficient for diffusion language models. Preprint, arXiv:2603.22248.

S. Chen, K. Cong, and J. Li. 2025. Optimal inference schedules for masked diffusion models. Preprint, arXiv:2511.04647.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Stuart Geman and Donald Geman. 1984. Stochastic relaxation, gibbs distributions, and the bayesian restoration of images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 6(6):721–741.

David Heckerman, David Maxwell Chickering, Christopher Meek, Robert Rounthwaite, and Carl Kadie. 2000. Dependency networks for inference, collaborative filtering, and data visualization. *Journal of Machine Learning Research*, 1:49–75.

James P. Hobert and George Casella. 1998. Functional compatibility, markov chains, and gibbs sampling with improper posteriors. *Journal of Computational and Graphical Statistics*, 7(1):42–60.

Daniel Israel, Guy Van den Broeck, and Aditya Grover. 2026. Accelerating diffusion llms via adaptive parallel decoding. *Advances in neural information processing systems*, 38:52870–52888.

W. Kang, K. Galim, S. Oh, M. Lee, Y. Zeng, S. Zhang, C. Hooper, Y. Hu, H. I. Koo, N. I. Cho, and 1 others. 2026. Parallelbench: Understanding the tradeoffs of parallel decoding in diffusion llms. In *International Conference on Learning Representations*. ArXiv:2510.04767.

Seo Hyun Kim, Sunwoo Hong, Hojung Jung, Youngrok Park, and Se-Young Yun. 2025. KLASS: KL-guided fast inference in masked diffusion models. In *Advances in Neural Information Processing Systems*.

K.-L. Kuo and Y. J. Wang. 2019. Pseudo-gibbs sampler for discrete conditional distributions. *Annals of the Institute of Statistical Mathematics*, 71(1):93–105.

I. Li, Z. Shao, B. Wang, R. Yu, G. Van den Broeck, and A. Liu. 2026. Breaking the factorization barrier in diffusion language models. Preprint, arXiv:2603.00045.

Aaron Lou, Chenlin Meng, and Stefano Ermon. 2024. Discrete diffusion modeling by estimating the ratios of the data distribution. In *Proceedings of the 41st International Conference on Machine Learning*.

Shen Nie, Fengqi Zhu, Zebin You, Xiaolu Zhang, Jingyang Ou, Jun Hu, Jun Zhou, Yankai Lin, Ji-Rong Wen, and Chongxuan Li. 2025. Large language diffusion models. In *Advances in Neural Information Processing Systems*.

Denis Paperno, Germán Kruszewski, Angeliki Lazaridou, Ngoc-Quan Pham, Raffaella Bernardi, Sandro Pezzelle, Marco Baroni, Gemma Boleda, and Raquel Fernández. 2016. The lambada dataset: Word prediction requiring a broad discourse context. In *Proceedings of the 54th annual meeting of the association for computational linguistics (volume 1: Long papers)*, pages 1525–1534.

Qwen, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, and 24 others. 2024. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

L. Ringel, A. Ali, and Y. Romano. 2026. Dependency-guided parallel decoding in discrete diffusion language models. Preprint, arXiv:2604.02560.

Subham S Sahoo, Marianne Arriola, Yair Schiff, Aaron Gokaslan, Edgar Marroquin, Justin T Chiu, Alexander Rush, and Volodymyr Kuleshov. 2024. Simple and effective masked diffusion language models. *Advances in Neural Information Processing Systems*, 37:130136–130184.

Jiaxin Shi, Kehang Han, Zhe Wang, Arnaud Doucet, and Michalis Titsias. 2024. Simplified and generalized masked diffusion for discrete data. *Advances in neural information processing systems*, 37:103131–103167.

Eitan Wagner, Yuli Slavutsky, and Omri Abend. 2024. CONTESTS: a framework for consistency testing of span probabilities in language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 15469–15484, Miami, Florida, USA. Association for Computational Linguistics.

Chengyue Wu, Hao Zhang, Shuchen Xue, Zhijian Liu, Shizhe Diao, Ligeng Zhu, Ping Luo, Song Han, and Enze Xie. 2025. Fast-dllm: Training-free acceleration of diffusion llm by enabling kv cache and parallel decoding. *arXiv preprint arXiv:2505.22618*.

Jiacheng Ye, Zhihui Xie, Lin Zheng, Jiahui Gao, Zirui Wu, Xin Jiang, Zhenguo Li, and Lingpeng Kong. 2025. Dream 7b: Diffusion large language models. *arXiv preprint arXiv:2508.15487*.

S. Zhang, L. Yu, R. Brekelmans, L. Tang, S. Asif, and G. Ver Steeg. 2026. Generation order and parallel decoding in masked diffusion models: An information-theoretic perspective. Preprint, arXiv:2602.00286.

Y. Zhao and C. Cai. 2026. Adaptation to intrinsic dependence in diffusion language models. Preprint, arXiv:2602.20126.

A Additional Experimental Details

A.1 Reverse-Time Trajectory of Incompatibility

We vary $t \in \{0.1, 0.3, 0.5, 0.7, 0.9\}$ (the mask ratio at the queried state) and ask how incompatibility evolves along the denoising trajectory. For each t we sample 30 contexts from each of Waiting Line, Sudoku 4×4, and LAMBADA, and report per-context mean pairwise H^2 with 95% bootstrap CIs.

Figure 3: Reverse-time trajectory of pairwise incompatibility on three domains. The three domains exhibit qualitatively distinct trajectory shapes.

The three trajectories differ qualitatively, not merely in magnitude (Figure 3). **LAMBADA** is high and smoothly monotone: $H^2 = 0.012$ already at $t = 0.1$ (when only a single token is unresolved) and rises near-linearly to 0.107 at $t = 0.9$. **Sudoku** starts low (0.005), rises gradually, and saturates near 0.017. **Waiting Line** is nearly at the numerical floor for $t \leq 0.3$ ($H^2 \sim 10^{-6}$, the level of Copy in Section 6.2) and then jumps by three orders of magnitude to 0.010 at $t = 0.5$, reaching 0.052 at $t = 0.9$.

Each shape suggests a distinct mechanism. LAMBADA's persistent high incompatibility reflects natural-language under-determination: even with most positions resolved, neighboring positions admit incompatible completions. Sudoku's early-onset saturation is consistent with constraint propagation—any two unresolved cells must satisfy row/column/box constraints regardless of how many cells remain—bounded by the puzzle's finite solution space. Waiting Line's phase-transition profile suggests sufficiency of context: with most output tokens visible, list operations are unambiguous; once the visible context drops below roughly

half, model conditionals degenerate into mutually inconsistent guesses. The implication is that mask ratio alone is not the controlling variable; the trajectory shape diagnoses *why* a task induces order sensitivity.

A.2 Waiting Line Trajectory: Per-Task Breakdown

Section A.1 aggregates Waiting Line across Copy, Shuffle, and Sort. Figure 4 reports the trajectory for each subtask separately. Copy remains at the numerical floor across all t, consistent with its position-wise determinism. Shuffle and Sort exhibit the same phase-transition profile as the aggregated curve, jumping by three to four orders of magnitude as t crosses approximately 0.5. The aggregated Waiting Line shape in Section A.1 is therefore driven by Shuffle and Sort rather than by Copy.

Figure 4: Per-task reverse-time trajectory within Waiting Line, on a log scale. Copy remains at the numerical floor; Shuffle and Sort show a sharp phase transition near $t = 0.5$.

B Estimator Details

This appendix collects the implementation details of the Fisher–Rao curl estimator and the robustness checks summarized in Section 6.2. The robustness checks in Sections B.4 and B.5 use an earlier diagnostic run on `LLaDA-8B-Base` with WikiText-103, GSM8K, and ParallelBench; the main-text experiments use `LLaDA-8B-Instruct` with the prompt templates of ParallelBench.

B.1 Fisher–Rao Curl Energy

Given a partially committed context x_S at reverse-time state z_t and two unresolved positions $i, j \notin S$, the pairwise Fisher–Rao curl energy is

$$\Omega_{ij}^{\mathrm{FR}}(x_S, t) = d_{\mathrm{FR}}^2\Big(Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S), Q_{\theta,t}^{j \to i}(\cdot, \cdot \mid x_S)\Big),$$

where on the discrete probability simplex

$$d_{\mathrm{FR}}(P, R) = 2 \arccos\left(\sum_{a,b} \sqrt{P_{ab} R_{ab}} \right).$$

By metric definiteness of d_{FR} and Theorem 1,

$$\Omega_{ij}^{\mathrm{FR}}(x_S, t) = 0 \iff \mathcal{C}_{ij}^{a,b}(x_S, t) = 0 \quad \forall a, b.$$

The symmetric score $\Omega_{ij}^{\mathrm{FR}}$ measures the magnitude of local order incompatibility, while the signed pointwise curl $\mathcal{C}_{ij}^{a,b}$ records which local order contributes positively or negatively to a path comparison. The squared Hellinger form H^2 reported in the main text is the bounded reparameterization of d_{FR}^2. Proposition 3 further shows

$$\Omega_{ij}^{\mathrm{FR}} = 2\mathbb{E}_{Q_{\theta,t}^{i \to j}}\left[\mathcal{C}_{ij}^{a,b} \right] + O_m(\|\delta\|^3),$$

so the symmetric and directed scores agree to leading order.

B.2 Top-k Shared-Support Estimation

Computing the full pseudo-joints over $\mathcal{V} \times \mathcal{V}$ is unnecessary for a diagnostic probe. We first run a base forward pass to obtain $q_{\theta,t}(x_i \mid x_S)$ for the active unresolved positions and retain the top-k candidate set $\mathcal{K}_i$ at each position. For a pair (i, j), both pseudo-joints are restricted to the shared support

$$\mathcal{S}_{ij} = \mathcal{K}_i \times \mathcal{K}_j$$

and renormalized before computing $\Omega_{ij}^{\mathrm{FR}}$, the directed KL, or expected curl. Shared-support renormalization prevents the diagnostic from being dominated by incomparable tails and makes scores comparable across positions and reverse-time steps.

B.3 Batched Intervention Cache and Cost

The conditional terms $q_{\theta,t}(x_j \mid x_S, x_i = a)$ and $q_{\theta,t}(x_i \mid x_S, x_j = b)$ are obtained through interventions on the current context. For each active position i and candidate token $a \in \mathcal{K}_i$, we run the model on the intervened context $x_S \cup \{x_i = a\}$ and cache the target distributions at the other active positions. This cache supplies all entries needed to assemble both pseudo-joints for any candidate pair within the active set.

The active set can be restricted by uncertainty, mask geometry, or the experimental block under study. If m active positions are retained and each has k candidates, the diagnostic requires $O(mk)$ intervened forward contexts and yields $O(m^2 k^2)$ cached pseudo-joint entries. All experiments use $k = 16$.

B.4 Top-k Stability

The shared-support top-k approximation gives stable rankings between $k = 8$ and $k = 16$. Table 5 reports high Pearson correlations and stronger Spearman correlations. The diagnostic is therefore reliable as a risk-ranking score across candidate pairs.

Dataset	Pearson	Spearman
WikiText	0.9335	0.9958
GSM8K	0.9985	0.9963
ParallelBench	0.999979	0.998486

Table 5: Top-k stability between $k = 8$ and $k = 16$. Spearman correlation is emphasized because the diagnostic is used as a risk-ranking score.

B.5 Cross-State Null Baseline

To verify that the estimated H^2 scores capture coherent within-state structure rather than estimator artifacts, we construct a matched cross-state null baseline. For each real pair, we replace one side with a donor from a different sample, matched by mask ratio, top-k, and distance bucket. This keeps the estimator configuration fixed while breaking the shared masked-state context. Across WikiText, GSM8K, and ParallelBench, cross-state null distances are consistently larger than real within-state distances (Figure 5), confirming that the within-state signal is not an artifact of support truncation or the estimator floor.

Figure 5: Cross-state null baseline. Real within-state distances are consistently smaller than matched cross-state null distances across WikiText, GSM8K, and ParallelBench, indicating that the reported scores reflect coherent masked-state structure rather than estimator artifacts.

C Order-Sensitivity Prediction on LAMBADA

Sections 6.2–6.3 establish that H^2 tracks the dependence structure of a task, and Section 6.4 shows it correlates with directional decoding preference. We now ask a sharper, sample-level question: does pseudo-joint curl predict whether an individual sample's output actually changes with

decoding order? We test this on LAMBADA (Paperno et al., 2016), where natural-language underdetermination makes order sensitivity an observable phenomenon at the level of individual passages.

LAMBADA is particularly suited to this probe because its targets are designed to require broad discourse context: humans can often infer the last word from the full passage, but not from the immediately preceding sentence alone. This makes the final block locally underdetermined while still globally constrained. Such a regime is ideal for testing our diagnostic, because different sequential orders can reveal different partial contexts and thereby induce different pseudo-joint completions.

Setup. We evaluate the full LAMBADA test set using `LLaDA-8B-Instruct` (Nie et al., 2025). For each passage we select the final four non-special tokens as a target block ($B = 4$), holding the preceding context fixed. To avoid conflating token-level difficulty with order sensitivity—LAMBADA targets are deliberately rare and often outside the model's high-probability region—we replace the gold target with the model's own LTR-decoded output: starting from a fully-masked block, we run forced greedy decoding under the left-to-right ordering $(0, 1, 2, 3)$ to obtain a reference sequence $\mathbf{x}_B = (x_0, x_1, x_2, x_3)$, and all subsequent quantities are computed against this $\mathbf{x}_B$.

We enumerate the $4! = 24$ block permutations. For each permutation π the pseudo-joint log-probability of the reference is

$$\log Q_\theta^\pi(\mathbf{x}_B) = \sum_{m=1}^{4} \log q_\theta(x_{\pi_m} \mid \mathbf{x}_{S_m}),$$
$$S_m = \{\pi_1, \ldots, \pi_{m-1}\},$$

and we define $\pi^+ = \arg\max_\pi \log Q_\theta^\pi(\mathbf{x}_B)$ and $\pi^- = \arg\min_\pi \log Q_\theta^\pi(\mathbf{x}_B)$ as the permutations the model most and least prefers for this sequence.

Order-sensitivity targets. We measure per-sample order sensitivity by two complementary statistics.

Token disagreement Δ_{tok}. Let $\mathbf{y}^+$ and $\mathbf{y}^-$ be the forced greedy outputs under π^+ and π^-. Then

$$\Delta_{\text{tok}} = \frac{1}{4} \sum_{k=0}^{3} \mathbf{1}[y_k^+ \neq y_k^-] \in \{0, 0.25, 0.5, 0.75, 1\}.$$

82.8% of samples have $\Delta_{\text{tok}} > 0$, so ordering choice changes the output for the great majority of LAMBADA passages.

NLL gap under preferred ordering Δ_{NLL}. We score both outputs against π^+:

$$\Delta_{\text{NLL}} = \log Q_\theta^{\pi^+}(\mathbf{y}^+) - \log Q_\theta^{\pi^+}(\mathbf{y}^-) \geq 0.$$

This continuous target captures the magnitude—not merely the existence—of the ordering effect.

Predictors. All predictors are computed from the all-mask marginals $p_i = q_\theta(x_i \mid \mathbf{x}_{S=\emptyset})$ and are therefore independent of $\mathbf{x}_B$. This is a strict predictive setup: the predictor has no access to the reference sequence used to define the targets. We compare four position-averaged predictors:

(i) Peak confidence.
$\bar{p}^{\max} = \frac{1}{4} \sum_i \max_v p_i(v)$.
(ii) Marginal entropy.
$\bar{H} = -\frac{1}{4} \sum_i \sum_v p_i(v) \log p_i(v)$.
(iii) Pairwise marginal KL.

$$\text{KL}_{\text{stab}} = \frac{1}{B(B-1)} \sum_{i \neq j} \text{KL}\big(q_\theta(x_i \mid \emptyset) \,\big\|\, q_\theta(x_i \mid x_j)\big),$$

measuring how much position-i's marginal shifts when position j is conditioned.

(iv) Block-averaged curl $\bar{H}_B^2$. For each pair (i, j), define pseudo-joints over a shared top-k ($k = 16$) support,

$$Q^{i \to j}(a, b) \propto p_i(a)\, q_\theta(x_j = b \mid x_i = a),$$
$$Q^{j \to i}(a, b) \propto p_j(b)\, q_\theta(x_i = a \mid x_j = b),$$

and average squared Hellinger over the $\binom{4}{2} = 6$ pairs:

$$\bar{H}_B^2 = \frac{1}{6} \sum_{(i,j)} H^2(Q^{i \to j}, Q^{j \to i}).$$

This is the block-level aggregation of the H^2 score from Section 6.2.

The first three predictors quantify marginal uncertainty; only $\bar{H}_B^2$ measures pseudo-joint asymmetry, which Theorem 1 identifies as the direct source of order-induced log-probability change.

Results. Table 6 reports Spearman rank correlations and AUC for identifying the top-20% most order-sensitive samples (all $p < 10^{-3}$); Figure 6 visualizes the comparison.

$\bar{H}_B^2$ leads on both targets, with the largest margin on Δ_{NLL}: $\rho = 0.438$ versus the next-best KL_{stab} at 0.198, and AUC 0.706 versus 0.620. To isolate $\bar{H}_B^2$'s unique contribution, we fit a rank regression using all three uncertainty baselines and measure the incremental R^2 from adding $\bar{H}_B^2$ (Table 7). The gain on Δ_{NLL} is +0.148, raising R^2 from 0.049 to 0.196—a $4\times$ increase.

Figure 6: Spearman ρ for each predictor on Δ_{tok} and Δ_{NLL}. $\bar{H}_B^2$ leads on both; the advantage is largest on Δ_{NLL}, where baselines plateau below $\rho = 0.20$.

Figure 7: **Left:** distribution of Δ_{tok} (82.8% nonzero). **Center:** distribution of Δ_{NLL} among nonzero samples (right-skewed, mean = 2.52). **Right:** mean Δ_{NLL} by $\bar{H}_B^2$ quartile, showing a monotone increase from 1.0 (Q1) to 4.0 (Q4).

Table 6: Order-sensitivity prediction on LAMBADA ($N = 5{,}153$, all $p < 10^{-3}$).

| Predictor | Spearman ρ | | AUC (top-20%) | |
	Δ_{tok}	Δ_{NLL}	Δ_{tok}	Δ_{NLL}
$\bar{p}^{\max}$	-0.418	-0.148	0.695	0.563
$\bar{H}$	$+0.355$	$+0.152$	0.654	0.573
KL_{stab}	$+0.455$	$+0.198$	0.728	0.620
$\bar{H}_B^2$	$\mathbf{+0.507}$	$\mathbf{+0.438}$	$\mathbf{0.700}$	$\mathbf{0.706}$

Table 7: Incremental rank-R^2 from adding $\bar{H}_B^2$ to the three uncertainty baselines.

Target	Baselines R^2	$+ \bar{H}_B^2 R^2$	Gain
Δ_{tok}	0.260	0.337	$+0.077$
Δ_{NLL}	0.049	0.196	$+0.148$

Discussion. Marginal uncertainty predictors ($\bar{p}^{\max}$, $\bar{H}$) saturate at $|\rho| \le 0.15$ on Δ_{NLL}, and KL_{stab} reaches only $\rho = 0.198$. $\bar{H}_B^2$, which measures pseudo-joint asymmetry rather than marginal spread, more than doubles this. This is the predicted dissociation: positional difficulty and pairwise marginal shift are properties of individual conditionals and cannot detect the non-commutativity in how those conditionals compose, which Theorem 1 identifies as the direct source of order-induced log-probability change. The contrast between $\rho = 0.198$ (KL_{stab}) and $\rho = 0.438$ ($\bar{H}_B^2$) on Δ_{NLL} is the empirical signature of this theoretical distinction.

D Proofs and Technical Details

D.1 Constructive Separation Examples

This subsection gives the constructive witnesses for Proposition 1.

Dependent data with zero curl. Let $X_i, X_j \in \{0, 1\}$ and suppose

$$p_{\text{data}}(0, 0 \mid x_S) = p_{\text{data}}(1, 1 \mid x_S) = 1/2.$$

Then $\text{TC}(X_i, X_j \mid x_S) > 0$. If the denoiser is Bayes-optimal on all relevant partial contexts, both local orders recover the same data joint by the chain rule:

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = p_{\text{data}}(a, b \mid x_S) = Q_{\theta,t}^{j \to i}(a, b \mid x_S).$$

Hence $\mathcal{C}_{ij}^{a,b}(x_S, t) = 0$ for all a, b despite positive conditional total correlation.

Independent data with nonzero curl. Let X_i and X_j be independent fair bits under $p_{\text{data}}(\cdot, \cdot \mid x_S)$, so $\text{TC}(X_i, X_j \mid x_S) = 0$. Now consider a learned denoiser whose local predictions satisfy

$$q_{\theta,t}(x_i = 1 \mid x_S) = 1/2, \qquad q_{\theta,t}(x_j = 1 \mid x_S) = 1/2,$$

$$q_{\theta,t}(x_j = 1 \mid x_S, x_i = 1) = 0.9, \qquad q_{\theta,t}(x_i = 1 \mid x_S, x_j = 1) = 1/2.$$

Then for $a = b = 1$,

$$\mathcal{C}_{ij}^{1,1}(x_S, t) = \log \frac{(1/2)(0.9)}{(1/2)(1/2)} = \log 1.8 \neq 0.$$

Thus curl can be nonzero even when the data conditional total correlation is zero.

D.2 Proof of Theorem 1

Proof. By definition,

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = q_{\theta,t}(a \mid x_S) \, q_{\theta,t}(b \mid x_S, x_i{=}a)$$

and

$$Q_{\theta,t}^{j \to i}(a, b \mid x_S) = q_{\theta,t}(b \mid x_S) \, q_{\theta,t}(a \mid x_S, x_j{=}b).$$

Taking the logarithm of the ratio gives

$$\log \frac{Q_{\theta,t}^{i \to j}(a, b \mid x_S)}{Q_{\theta,t}^{j \to i}(a, b \mid x_S)} = \log q_{\theta,t}(a \mid x_S) + \log q_{\theta,t}(b \mid x_S, x_i{=}a) - \log q_{\theta,t}(b \mid x_S) - \log q_{\theta,t}(a \mid x_S, x_j{=}b),$$

which is exactly $\mathcal{C}_{ij}^{a,b}(x_S, t)$.

If $\mathcal{C}_{ij}^{a,b}(x_S, t) = 0$ for all a, b, then the displayed ratio equals 1 for all a, b, so

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = Q_{\theta,t}^{j \to i}(a, b \mid x_S)$$

pointwise and hence the two distributions are equal. The converse is immediate from the same identity.

For the expectation claim,

$$\mathbb{E}_{(a,b) \sim Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S)} \left[\mathcal{C}_{ij}^{a,b}(x_S, t) \right]$$

$$= \sum_{a,b} Q_{\theta,t}^{i \to j}(a, b \mid x_S) \log \frac{Q_{\theta,t}^{i \to j}(a, b \mid x_S)}{Q_{\theta,t}^{j \to i}(a, b \mid x_S)}$$

$$= \text{KL}\big(Q_{\theta,t}^{i \to j}(\cdot, \cdot \mid x_S) \,\|\, Q_{\theta,t}^{j \to i}(\cdot, \cdot \mid x_S)\big),$$

which is the definition of KL divergence. $\qquad\square$

D.3 Discrete Exterior Derivative and Swap-Path Identities

Write $C_{ij}^{a,b}(x_S, t) \equiv \mathcal{C}_{ij}^{a,b}(x_S, t)$ for notational compactness. Define on the partial-context lattice the discrete 1-form

$$\omega_i^a(x_S, t) := \log q_{\theta,t}(x_i = a \mid x_S),$$

where (i, a, x_S) ranges over a position not in S, a candidate token, and a partial context. Its discrete exterior derivative on elementary squares is

$$(d\omega)_{ij}^{a,b}(x_S, t) := \omega_i^a(x_S, t) + \omega_j^b(x_S, x_i{=}a, t) - \omega_j^b(x_S, t) - \omega_i^a(x_S, x_j{=}b, t).$$

Theorem 3. *For every x_S, t, i, j, a, b,*

$$C_{ij}^{a,b}(x_S, t) = (d\omega)_{ij}^{a,b}(x_S, t).$$

Theorem 3 follows by direct algebraic expansion: the definition of $(d\omega)_{ij}^{a,b}$ matches the definition of $C_{ij}^{a,b}$ term by term.

Corollary 3.1 (Path independence). *For any two adjacent-swap paths Γ_1, Γ_2 from permutation π to permutation π', the sums*

$$\sum_{r\in\Gamma_1} C_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r^{(1)}}, t) = \sum_{r\in\Gamma_2} C_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r^{(2)}}, t) = \log \frac{Q_{\theta,t}^\pi(x_B \mid x_S)}{Q_{\theta,t}^{\pi'}(x_B \mid x_S)}$$

coincide.

Proof. Theorem 3 writes each adjacent-swap contribution as a finite difference of log-conditionals. Summing those differences along any adjacent-swap path telescopes to the endpoint pseudo-joint log-ratio $\log Q_{\theta,t}^\pi - \log Q_{\theta,t}^{\pi'}$. $\qquad\square$

Corollary 3.2 (Path-specific adjacent-swap decomposition). *Let π and π' be two permutations of B, and fix an adjacent-swap path*

$$\Gamma : \qquad \rho^{(0)} = \pi \to \rho^{(1)} \to \cdots \to \rho^{(R)} = \pi'.$$

Suppose the rth step swaps adjacent positions k_r and $k_r + 1$ in the current ordering $\rho^{(r-1)}$. Write

$$i_r = \rho_{k_r}^{(r-1)}, \qquad j_r = \rho_{k_r+1}^{(r-1)},$$

and let

$$S_r = S \cup \{\rho_1^{(r-1)}, \ldots, \rho_{k_r-1}^{(r-1)}\}$$

be the prefix index set before the swapped adjacent pair. Then for every assignment x_B,

$$\log \frac{Q_{\theta,t}^\pi(x_B \mid x_S)}{Q_{\theta,t}^{\pi'}(x_B \mid x_S)} = \sum_{r=1}^R \mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r}, t).$$

Proof. For each step r, let

$$A_r = (\rho_1^{(r-1)}, \ldots, \rho_{k_r-1}^{(r-1)}) \qquad \text{and} \qquad D_r = (\rho_{k_r+2}^{(r-1)}, \ldots, \rho_{|B|}^{(r-1)}),$$

so that

$$\rho^{(r-1)} = (A_r, i_r, j_r, D_r) \qquad \text{and} \qquad \rho^{(r)} = (A_r, j_r, i_r, D_r).$$

Also write $C_r = S \cup A_r$, which is exactly the prefix index set S_r in the statement. Expanding the sequential products along the two adjacent orders gives

$$Q_{\theta,t}^{\rho^{(r-1)}}(x_B \mid x_S) = Q_{A_r}(x_{A_r} \mid x_S)\, q_{\theta,t}(x_{i_r} \mid x_{C_r}) \cdot q_{\theta,t}(x_{j_r} \mid x_{C_r}, x_{i_r}) \cdot Q_{D_r}(x_{D_r} \mid x_{C_r}, x_{i_r}, x_{j_r}),$$

and

$$Q_{\theta,t}^{\rho^{(r)}}(x_B \mid x_S) = Q_{A_r}(x_{A_r} \mid x_S)\, q_{\theta,t}(x_{j_r} \mid x_{C_r}) \cdot q_{\theta,t}(x_{i_r} \mid x_{C_r}, x_{j_r}) \cdot Q_{D_r}(x_{D_r} \mid x_{C_r}, x_{i_r}, x_{j_r}).$$

The prefix factor Q_{A_r} is identical in both expressions, and the suffix factor Q_{D_r} is also identical because after the adjacent swap both i_r and j_r have entered the conditioning context. Therefore,

$$\log \frac{Q_{\theta,t}^{\rho^{(r-1)}}(x_B \mid x_S)}{Q_{\theta,t}^{\rho^{(r)}}(x_B \mid x_S)} = \log q_{\theta,t}(x_{i_r} \mid x_{C_r}) + \log q_{\theta,t}(x_{j_r} \mid x_{C_r}, x_{i_r}) - \log q_{\theta,t}(x_{j_r} \mid x_{C_r}) - \log q_{\theta,t}(x_{i_r} \mid x_{C_r}, x_{j_r})$$

$$= \mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{C_r}, t).$$

Summing these consecutive log-ratios along the path Γ telescopes:

$$\log \frac{Q_{\theta,t}^{\pi}(x_B \mid x_S)}{Q_{\theta,t}^{\pi'}(x_B \mid x_S)} = \sum_{r=1}^{R} \log \frac{Q_{\theta,t}^{\rho^{(r-1)}}(x_B \mid x_S)}{Q_{\theta,t}^{\rho^{(r)}}(x_B \mid x_S)}$$

$$= \sum_{r=1}^{R} \mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r}, t),$$

which is the claimed decomposition. $\square$

D.4 Bayes-Optimal Compatibility and Conditional Total Correlation

Bayes-optimal compatibility implies zero curl. Suppose the denoiser satisfies

$$q_{\theta,t}(x_i \mid x_S) = p_{\mathrm{data}}(x_i \mid x_S)$$

for every visible context x_S and unresolved coordinate i. Then for every x_S, t, i, j, a, b,

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = p_{\mathrm{data}}(a, b \mid x_S) = Q_{\theta,t}^{j \to i}(a, b \mid x_S),$$

and therefore $\mathcal{C}_{ij}^{a,b}(x_S, t) = 0$.

Proof. Fix x_S, t, i, j, a, and b. By the Bayes-optimal assumption,

$$q_{\theta,t}(a \mid x_S) = p_{\mathrm{data}}(a \mid x_S)$$

and, because x_S together with $x_i = a$ is also a visible context for coordinate j,

$$q_{\theta,t}(b \mid x_S, x_i{=}a) = p_{\mathrm{data}}(b \mid x_S, x_i{=}a).$$

Therefore,

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = q_{\theta,t}(a \mid x_S) q_{\theta,t}(b \mid x_S, x_i{=}a)$$

$$= p_{\mathrm{data}}(a \mid x_S) p_{\mathrm{data}}(b \mid x_S, x_i{=}a)$$

$$= p_{\mathrm{data}}(a, b \mid x_S),$$

where the last step is the chain rule. The same argument with i and j swapped gives

$$Q_{\theta,t}^{j \to i}(a, b \mid x_S) = q_{\theta,t}(b \mid x_S) q_{\theta,t}(a \mid x_S, x_j{=}b)$$

$$= p_{\mathrm{data}}(b \mid x_S) p_{\mathrm{data}}(a \mid x_S, x_j{=}b)$$

$$= p_{\mathrm{data}}(a, b \mid x_S).$$

Hence

$$Q_{\theta,t}^{i \to j}(a, b \mid x_S) = p_{\mathrm{data}}(a, b \mid x_S) = Q_{\theta,t}^{j \to i}(a, b \mid x_S).$$

Applying Theorem 1 then gives $\mathcal{C}_{ij}^{a,b}(x_S, t) = 0$. $\square$

Parallel decoding and conditional total correlation. For completeness, define the one-shot independent parallel approximation

$$Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S) = \prod_{i \in B} q_{\theta,t}(x_i \mid x_S).$$

If $q_{\theta,t} = p_{\mathrm{data}}$, then

$$\mathrm{KL}\Big(p(x_B \mid x_S) \,\Big\|\, Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S)\Big) = \mathrm{TC}(X_B \mid x_S),$$

which is exactly the conditional-total-correlation identity established by Kang et al. (2026); Chen et al. (2025).

D.5 Proof of Theorem 2

Direct algebraic decomposition. Starting from the parallel decoding error

$$\mathrm{KL}\big(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S)\big) = \mathbb{E}_p\!\left[\log \frac{p(x_B \mid x_S)}{\prod_{i \in B} q_{\theta,t}(x_i \mid x_S)}\right],$$

insert $\log \prod_{i \in B} p(x_i \mid x_S)$ to split into

$$\mathbb{E}_p\!\left[\log \frac{p(x_B \mid x_S)}{\prod_{i \in B} p(x_i \mid x_S)}\right] + \mathbb{E}_p\!\left[\log \frac{\prod_{i \in B} p(x_i \mid x_S)}{\prod_{i \in B} q_{\theta,t}(x_i \mid x_S)}\right].$$

The first term is $\mathrm{TC}(X_B \mid x_S)$; the second is $\sum_{i \in B} \mathrm{KL}\big(p(x_i \mid x_S) \,\|\, q_{\theta,t}(x_i \mid x_S)\big)$. This proves

$$\mathrm{KL}\big(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S)\big) = \mathrm{TC}(X_B \mid x_S) + \sum_{i \in B} \mathrm{KL}\big(p(x_i \mid x_S) \,\|\, q_{\theta,t}(x_i \mid x_S)\big).$$

For sequential order π, decompose

$$\mathrm{KL}\big(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\pi}(x_B \mid x_S)\big) = \mathrm{KL}\big(p(x_B \mid x_S) \,\|\, Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S)\big) + \mathbb{E}_p\big[\log Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S) - \log Q_{\theta,t}^{\pi}(x_B \mid x_S)\big].$$

Expand the second term:

$$\log Q_{\theta,t}^{\mathrm{par}}(x_B \mid x_S) - \log Q_{\theta,t}^{\pi}(x_B \mid x_S) = \sum_{m=1}^{|B|} \log q_{\theta,t}(x_{\pi_m} \mid x_S) - \sum_{m=1}^{|B|} \log q_{\theta,t}(x_{\pi_m} \mid x_S, x_{\pi_{<m}}) = -\mathcal{I}_{\theta,t}^{\pi}(x_S).$$

Combining gives Theorem 2.

Corollary 2.1 follows by taking the difference for two orders π, π', noting that the total-correlation and marginal-estimation terms cancel, and applying Corollary 3.2 to

$$\mathcal{I}_{\theta,t}^{\pi} - \mathcal{I}_{\theta,t}^{\pi'} = \mathbb{E}_p\big[\log Q_{\theta,t}^{\pi} - \log Q_{\theta,t}^{\pi'}\big].$$

D.6 Cumulative Cross-Entropy Decomposition

For completeness, we record the rollout-weighted KL decomposition used in the proof of Theorem 2.

Lemma 1. *For any order π,*

$$\mathbb{E}_p\big[-\log Q_{\theta,t}^{\pi}(X_B \mid X_S)\big] = H_p(X_B \mid X_S) + \mathrm{KL}\big(p(X_B \mid X_S) \,\|\, Q_{\theta,t}^{\pi}(X_B \mid X_S)\big).$$

Moreover,

$$\mathrm{KL}\big(p(X_B \mid X_S) \,\|\, Q_{\theta,t}^{\pi}(X_B \mid X_S)\big)$$
$$= \sum_{m=1}^{|B|} \mathbb{E}_p\Big[\mathrm{KL}\big(p(X_{\pi_m} \mid X_S, X_{\pi_{<m}}) \,\|\, q_{\theta,t}(X_{\pi_m} \mid X_S, X_{\pi_{<m}})\big)\Big].$$

Proof. For the first identity,

$$\mathrm{KL}\big(p(X_B \mid X_S) \,\|\, Q_{\theta,t}^\pi(X_B \mid X_S)\big)$$
$$= \mathbb{E}_p\big[\log p(X_B \mid X_S) - \log Q_{\theta,t}^\pi(X_B \mid X_S)\big].$$

Rearranging gives

$$\mathbb{E}_p\big[-\log Q_{\theta,t}^\pi(X_B \mid X_S)\big] = -\mathbb{E}_p\big[\log p(X_B \mid X_S)\big] + \mathrm{KL}\big(p(X_B \mid X_S) \,\|\, Q_{\theta,t}^\pi(X_B \mid X_S)\big)$$
$$= H_p(X_B \mid X_S) + \mathrm{KL}\big(p(X_B \mid X_S) \,\|\, Q_{\theta,t}^\pi(X_B \mid X_S)\big),$$

which is the first claim.

For the second claim, apply the chain rule to both the target conditional and the pseudo-joint in the same order π:

$$p(X_B \mid X_S) = \prod_{m=1}^{|B|} p(X_{\pi_m} \mid X_S, X_{\pi_{<m}})$$

and

$$Q_{\theta,t}^\pi(X_B \mid X_S) = \prod_{m=1}^{|B|} q_{\theta,t}(X_{\pi_m} \mid X_S, X_{\pi_{<m}}).$$

Therefore,

$$\mathrm{KL}\big(p(X_B \mid X_S) \,\|\, Q_{\theta,t}^\pi(X_B \mid X_S)\big)$$
$$= \mathbb{E}_p\left[\sum_{m=1}^{|B|} \log \frac{p(X_{\pi_m} \mid X_S, X_{\pi_{<m}})}{q_{\theta,t}(X_{\pi_m} \mid X_S, X_{\pi_{<m}})}\right]$$
$$= \sum_{m=1}^{|B|} \mathbb{E}_p\left[\log \frac{p(X_{\pi_m} \mid X_S, X_{\pi_{<m}})}{q_{\theta,t}(X_{\pi_m} \mid X_S, X_{\pi_{<m}})}\right].$$

Now condition on $(X_S, X_{\pi_{<m}})$ and apply the definition of KL divergence inside each term:

$$\mathbb{E}_p\left[\log \frac{p(X_{\pi_m} \mid X_S, X_{\pi_{<m}})}{q_{\theta,t}(X_{\pi_m} \mid X_S, X_{\pi_{<m}})}\right]$$
$$= \mathbb{E}_p\Big[\mathrm{KL}\big(p(X_{\pi_m} \mid X_S, X_{\pi_{<m}}) \,\|\, q_{\theta,t}(X_{\pi_m} \mid X_S, X_{\pi_{<m}})\big)\Big].$$

Summing over m yields the claimed decomposition. $\square$

D.7 Pinsker-Type Bound on Bounded Order Statistics

Theorem 4. *For any bounded function $f : \mathcal{V}^{|B|} \to \mathbb{R}$ and any pair of orders π, π' of B,*

$$\big|\mathbb{E}_{Q_{\theta,t}^\pi}[f] - \mathbb{E}_{Q_{\theta,t}^{\pi'}}[f]\big| \le \|f\|_\infty \sqrt{2\mathrm{KL}\big(Q_{\theta,t}^\pi \,\|\, Q_{\theta,t}^{\pi'}\big)}.$$

By Corollary 3.2,

$$\mathrm{KL}\big(Q_{\theta,t}^\pi \,\|\, Q_{\theta,t}^{\pi'}\big) = \sum_r \mathbb{E}_{Q_{\theta,t}^\pi}\big[\mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r}, t)\big].$$

Hence

$$\big|\mathbb{E}_{Q_{\theta,t}^\pi}[f] - \mathbb{E}_{Q_{\theta,t}^{\pi'}}[f]\big| \le \|f\|_\infty \sqrt{2\sum_r \mathbb{E}_{Q_{\theta,t}^\pi}\big[\mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r}, t)\big]}.$$

Proof. Apply Pinsker's inequality to $Q_{\theta,t}^\pi$ and $Q_{\theta,t}^{\pi'}$:

$$\big|\mathbb{E}_{Q_{\theta,t}^\pi}[f] - \mathbb{E}_{Q_{\theta,t}^{\pi'}}[f]\big| \le \|f\|_\infty \sqrt{2\mathrm{KL}\big(Q_{\theta,t}^\pi \,\|\, Q_{\theta,t}^{\pi'}\big)}.$$

By Theorem 1 and Corollary 3.2,

$$\mathrm{KL}\big(Q_{\theta,t}^{\pi} \,\|\, Q_{\theta,t}^{\pi'}\big) = \mathbb{E}_{Q_{\theta,t}^{\pi}}\left[\log \frac{Q_{\theta,t}^{\pi}}{Q_{\theta,t}^{\pi'}}\right] = \sum_r \mathbb{E}_{Q_{\theta,t}^{\pi}}\big[\mathcal{C}_{i_r j_r}^{x_{i_r}, x_{j_r}}(x_{S_r}, t)\big].$$

Substituting gives the claim. $\qquad\square$

D.8 Fisher–Rao Energy Details

Proposition 2. *For every x_S, t, i, j,*

$$\Omega_{ij}^{\mathrm{FR}}(x_S, t) = 0 \iff Q_{\theta,t}^{i\to j} = Q_{\theta,t}^{j\to i} \iff \mathcal{C}_{ij}^{a,b}(x_S, t) = 0 \quad \forall a, b.$$

Proof. By definition,

$$\Omega_{ij}^{\mathrm{FR}}(x_S, t) = d_{\mathrm{FR}}^2\Big(Q_{\theta,t}^{i\to j}(\cdot, \cdot \mid x_S), Q_{\theta,t}^{j\to i}(\cdot, \cdot \mid x_S)\Big).$$

Since d_{FR} is a metric on the discrete probability simplex, $\Omega_{ij}^{\mathrm{FR}}(x_S, t) = 0$ holds exactly when

$$Q_{\theta,t}^{i\to j}(\cdot, \cdot \mid x_S) = Q_{\theta,t}^{j\to i}(\cdot, \cdot \mid x_S).$$

Theorem 1 gives the second equivalence: equality of the two local pseudo-joints is equivalent to $\mathcal{C}_{ij}^{a,b}(x_S, t) = 0$ for every a, b. $\qquad\square$

Proposition 3. *Fix a shared support $\mathcal{S} \subseteq \mathcal{V} \times \mathcal{V}$. Let*

$$P = Q_{\theta,t}^{i\to j}, \qquad R = Q_{\theta,t}^{j\to i} = P + \delta,$$

where the sums below are over $\mathcal{S}$, $\sum_{(a,b)\in\mathcal{S}} \delta_{ab} = 0$, $P_{ab} \geq m > 0$, and $R_{ab} > 0$ on $\mathcal{S}$. For top-k use, both pseudo-joints are first restricted to a shared support and renormalized on that support. Then

$$d_{\mathrm{FR}}^2(P, P + \delta) = \sum_{a,b} \frac{\delta_{ab}^2}{P_{ab}} + O_m(\|\delta\|^3),$$

and

$$\mathrm{KL}(P\|P + \delta) = \frac{1}{2} \sum_{a,b} \frac{\delta_{ab}^2}{P_{ab}} + O_m(\|\delta\|^3).$$

Consequently,

$$\Omega_{ij}^{\mathrm{FR}} = 2\mathrm{KL}\big(Q_{\theta,t}^{i\to j} \,\|\, Q_{\theta,t}^{j\to i}\big) + O_m(\|\delta\|^3) = 2\mathbb{E}_{Q_{\theta,t}^{i\to j}}\big[\mathcal{C}_{ij}^{a,b}\big] + O_m(\|\delta\|^3).$$

Proof sketch. Write

$$\rho(P, P + \delta) := \sum_{a,b} \sqrt{P_{ab}(P_{ab} + \delta_{ab})}.$$

Using

$$\sqrt{P_{ab}(P_{ab} + \delta_{ab})} = P_{ab}\sqrt{1 + \delta_{ab}/P_{ab}} = P_{ab} + \tfrac{1}{2}\delta_{ab} - \tfrac{1}{8}\frac{\delta_{ab}^2}{P_{ab}} + O_m(\|\delta\|^3),$$

and summing over (a, b) gives

$$\rho(P, P + \delta) = 1 - \tfrac{1}{8} \sum_{a,b} \frac{\delta_{ab}^2}{P_{ab}} + O_m(\|\delta\|^3),$$

because $\sum_{a,b} P_{ab} = 1$ and $\sum_{a,b} \delta_{ab} = 0$. For small u, the expansion

$$4\arccos^2(1 - u) = 8u + O(u^2)$$

then yields

$$d_{\mathrm{FR}}^2(P, P + \delta) = \sum_{a,b} \frac{\delta_{ab}^2}{P_{ab}} + O_m(\|\delta\|^3).$$

For the KL term,

$$\mathrm{KL}(P\|P + \delta) = -\sum_{a,b} P_{ab} \log\left(1 + \frac{\delta_{ab}}{P_{ab}}\right) = \frac{1}{2}\sum_{a,b} \frac{\delta_{ab}^2}{P_{ab}} + O_m(\|\delta\|^3),$$

using the Taylor series of $\log(1 + x)$ and $\sum_{a,b} \delta_{ab} = 0$. Substituting $P = Q_{\theta,t}^{i \to j}$ and $P + \delta = Q_{\theta,t}^{j \to i}$ gives

$$\Omega_{ij}^{\mathrm{FR}} = 2\mathrm{KL}\left(Q_{\theta,t}^{i \to j} \,\|\, Q_{\theta,t}^{j \to i}\right) + O_m(\|\delta\|^3).$$

Finally, Theorem 1 implies

$$\mathrm{KL}\left(Q_{\theta,t}^{i \to j} \,\|\, Q_{\theta,t}^{j \to i}\right) = \mathbb{E}_{Q_{\theta,t}^{i \to j}}\left[\mathcal{C}_{ij}^{a,b}\right],$$

which gives the last identity. $\qquad\square$