# Localized Graph Contrastive Learning

## Abstract

Contrastive learning methods based on InfoNCE loss are popular in node representation learning tasks on graph-structured data. However, its reliance on data augmentation and its quadratic computational complexity might lead to inconsistency and inefficiency problems. To mitigate these limitations, in this paper, we introduce a simple yet effective contrastive model named Localized Graph Contrastive Learning (Local-GCL in short). Local-GCL consists of two key designs: 1) We fabricate the positive examples for each node directly using its first-order neighbors, which frees our method from the reliance on carefully-designed graph augmentations; 2) To improve the efficiency of contrastive learning on graphs, we devise a kernelized contrastive loss, which could be approximately computed in linear time and space complexity with respect to the graph size. We provide theoretical analysis to justify the effectiveness and rationality of the proposed methods. Experiments on various datasets with different scales and properties demonstrate that in spite of its simplicity, Local-GCL achieves quite competitive performance in self-supervised node representation learning tasks on graphs with various scales and properties.

## 1 Introduction

Self-supervised learning has achieved remarkable success in learning informative representations without using costly handcrafted labels (van den Oord et al., 2018; Devlin et al., 2019; Banville et al., 2021; He et al., 2020; Chen et al., 2020; Grill et al., 2020; Zhang et al., 2021; Gao et al., 2021). Among current self-supervised learning paradigms, InfoNCE loss (van den Oord et al., 2018) based multi-view contrastive methods (He et al., 2020; Chen et al., 2020; Gao et al., 2021) are recognized as the most widely adopted ones, due to their solid theoretical foundations and strong empirical results. Generally, contrastive learning aims at maximizing the agreement between the latent representations of two views (e.g. through data augmentation) from the same input, which essentially maximizes the mutual information between the two representations (Poole et al., 2019). Inheriting the spirits of contrastive learning on vision tasks, similar methods have been developed to deal with graphs and bring up promising results on common node-level classification benchmarks (Velickovic et al., 2019; Hassani & Ahmadi, 2020; Zhu et al., 2020b; 2021).

The challenge, however, is that prevailing contrastive learning methods rely on predefined augmentation techniques for generating positive pairs as informative training supervision. Unlike grid-structured data (e.g., images or sequences), it is non-trivial to define well-posed augmentation approaches for graph-structured data Zhu et al. (2021); Zhang et al. (2021). The common practice adopted by current methods resorts to random perturbation on input node features and graph structures (You et al., 2020), which might unexpectedly violate the underlying data generation and change the semantic information (Lee et al., 2021). Such an issue plays as a bottleneck limiting the practical efficacy of contrastive methods on graphs. Apart from this, the InfoNCE loss function computes all-pair distance for in-batch nodes as negative pairs for contrasting signals (Zhu et al., 2020b; 2021), which induces quadratic memory and time complexity with respect to the batch size. Given that the model is preferred to be trained in a full-graph manner (i.e., batch size = graph size) since the graph structure information might be partially lost through mini-batch partition, such a nature heavily constrains contrastive methods for scaling to large graphs.

Some recent works seek negative-sample-free methods to resolve the scalability issue by harnessing asymmetric structures (Thakoor et al., 2021) or feature-level decorrelation objectives (Zhang et al., 2021). However, these methods either lack enough theoretical justification (Thakoor et al., 2021) or

necessitate strong assumptions on the data distributions (Zhang et al., 2021). Moreover, they still require data augmentations to generate two views of the input graph, albeit non-contrastive and free from negative sampling. Some other works construct positive examples using the target's $k$-nearest-neighbors (kNN) in the latent space (Dwibedi et al., 2021; Koohpayegani et al., 2021; Lee et al., 2021). Nonetheless, the computation of nearest neighbors could be cumbersome, time-consuming, and therefore hard to scale..

**Presented Work.** To cope with the dilemmas above, in this paper we introduce **Local**ized **G**raph **C**ontrastive **L**earning (LOCAL-GCL in abbreviation), a light and **augmentation-free** contrastive model for self-supervised node-level representation learning on graphs. LOCAL-GCL benefits from two key designs. **First**, it does not rely on data augmentation to construct positive pairs. Instead, inspired by the graph homophiliy theory (McPherson et al., 2001), it directly treats the first-order neighboring nodes as the positive examples of the target node. This not only increases the number of positive examples for each node but also helps our model get rid of complicated data augmentations. Besides, the computation of positive pairs can be performed in linear time and space complexity w.r.t the graph size, bringing no additional cost for the model. **Second**, to deal with the quadratic complexity curse of contrastive loss (i.e., InfoNCE loss (van den Oord et al., 2018)), we propose a surrogate loss function in place of the negative loss term in the vanilla InfoNCE loss, which could be efficiently and accurately approximated within linear time and space complexity (Rahimi et al., 2007; Liu et al., 2020; Yu et al., 2016). Such a design greatly improves the efficiency of our model.

We evaluate the proposed methods on seven public node classification benchmarks with various scales. The empirical results demonstrate that though not using any graph augmentations, our method achieves state-of-the-art performance on six of seven datasets. On the challenging `Ogbn-Arxiv` dataset, our method can also give a competitive performance with a much training speed compared with other scalable models. Experiments on three heterophily graphs demonstrate that besides homophily graphs, LOCAL-GCL can also perform well on graphs with low homophily ratios.

**We summarize the highlights of this paper as follows:**

**1)** We introduce LOCAL-GCL, a simple model for contrastive learning on graphs, where the positive example is fabricated using the first-order neighborhood of each node. This successfully frees node-level contrastive learning methods from unjustified graph augmentations.

**2)** To overcome the quadratic complexity curse of contrastive learning, we propose a kernelized contrastive loss computation that can precisely approximate the original loss function within linear complexity w.r.t. graph size. This significantly reduces the training time and memory cost of contrastive learning on large graphs.

**3)** Experimental results show that without data augmentation and other cumbersome designs LOCAL-GCL achieves quite competitive results on a variety of graphs of different scales and properties. Furthermore, LOCAL-GCL demonstrates a better balance of model performance and efficiency than other self-supervised methods.

## 2 BACKGROUND AND RELATED WORKS

### 2.1 CONTRASTIVE REPRESENTATION LEARNING

Inspired by the great success of contrastive methods in learning image representations (van den Oord et al., 2018; Hjelm et al., 2019; Tian et al., 2020; He et al., 2020; Chen et al., 2020), recent endeavors develop similar strategies for node-level tasks in graph domain (Velickovic et al., 2019; Hassani & Ahmadi, 2020; Zhu et al., 2020b; 2021). Among graph contrastive learning methods, the most popular methods should be those based on the InfoNCE loss (van den Oord et al., 2018) due to their simple concepts and better empirical performance. InfoNCE-based graph contrastive learning methods, including GRACE (Zhu et al., 2020b) and GCA (Zhu et al., 2021) aim to maximize the similarity of positive node-node (or graph-graph) pairs (e.g., two views generated via data augmentation) and minimize the similarity of negative ones (e.g., other nodes/graphs within the current batch). However, they require well-designated data augmentations that could positively inform downstream tasks (Tsai et al., 2021). The quadratic complexity also limits their applications to larger batch sizes/datasets.

## 2.2 Augmentation-Free Self-supervised Learning on Graphs

Besides graph contrastive learning (Zhu et al., 2020b; 2021) and the similar two-branched models (Thakoor et al., 2021; Zhang et al., 2021) that use graph augmentations to create positive pairs, there is another line of work exploring the rich structure information in the graph to create self-supervised signals. Graph AutoEncoders (Kipf & Welling, 2016), for example, learn node embeddings unsupervisedly through reconstructing the adjacency matrix, while GMI (Peng et al., 2020) maximizes the mutual information of both features and edges between inputs and outputs. Inspired by the success of contrastive learning, some recent work explores constructing positive pairs using reliable graph information instead of data augmentations. For example, SUGRL (Mo et al., 2022) employs two encoder models: one is a GCN, and the another is an MLP, to generate two sets of node embedding from different sources. Then for each node, the positive pair can be constructed using its GCN output and MLP output. AFGRL (Lee et al., 2021) and AF-GCL (Wang et al., 2022) treat nodes in the target node's multi-hop neighborhood as candidate positive examples and use well-designed similarity measures to select the most similar nodes as positive examples. LOCAL-GCL, by contrast, treats all neighbors equally without discrimination. This not only simplifies the model design but also offers a theoretical guarantee for the effectiveness of the proposed model. Empirical results also demonstrate that our method can achieve better performance than them.

## 2.3 Random Fourier Features

Random Fourier Features (RFF or Random Features in short) (Rahimi et al., 2007; Liu et al., 2020) is an effective technique for enhancing the scalability of kernel methods such as SVM, ridge regression (Avron et al., 2017) and independence test (Zhang et al., 2018; Li et al., 2021). Also, recently, RFF has been adopted to develop linear Transformers by approximating the softmax attention (Choromanski et al., 2020; Peng et al., 2021). Given $d$-dimensional vectors $\boldsymbol{x}$ and $\boldsymbol{y}$ and a shift-invariant kernel $\kappa(\cdot)$, RFF constructs an explicit mapping $\phi \colon \mathbb{R}^d \to \mathbb{R}^D$, such that $\kappa(\boldsymbol{x}, \boldsymbol{y}) \approx \phi(\boldsymbol{x})^\top \phi(\boldsymbol{y})$, which reduces the quadratic computation cost of the kernel matrix to a linear one w.r.t data size. Generally, given a positive definite shift-invariant kernel $\kappa(\boldsymbol{x}, \boldsymbol{y}) = f(\boldsymbol{x} - \boldsymbol{y})$, the Fourier transform $p$ of kernel $\kappa$ is $p(\boldsymbol{\omega}) = \frac{1}{2\pi} \int e^{-j\boldsymbol{\omega}'\Delta} k(\Delta) \mathrm{d}\Delta$, where $\Delta = \boldsymbol{x} - \boldsymbol{y}$. Then we could draw $D$ i.i.d. samples $\boldsymbol{\omega}_1, \cdots, \boldsymbol{\omega}_D \in \mathbb{R}^d$ from $p$, and $\phi(\boldsymbol{x})$ is given by:

$$\phi(\boldsymbol{x}) = \frac{\left[\cos(\boldsymbol{\omega}_1^\top \boldsymbol{x}), \cdots, \cos(\boldsymbol{\omega}_D^\top \boldsymbol{x}), \sin(\boldsymbol{\omega}_1^\top \boldsymbol{x}), \cdots, \sin(\boldsymbol{\omega}_D^\top \boldsymbol{x})\right]^\top}{\sqrt{D}}. \tag{1}$$

Let $\boldsymbol{W} = [\boldsymbol{\omega}_1, \cdots, \boldsymbol{\omega}_D] \in \mathbb{R}^{d \times D}$ be a linear transformation matrix, one may realize that the computation of Eq. 1 entails computing $\boldsymbol{W}^\top \boldsymbol{x}$. Specifically, when $\kappa(\cdot)$ is a standard Gaussian kernel (a.k.a., RBF kernel), each entry of $\boldsymbol{W}$ can be directly sampled from a standard Gaussian distribution. The improved variants of RFF mainly concentrate on different ways to build the transformation matrix $\boldsymbol{W}$, so as to further reduce the computational cost (Le et al., 2013) or lower the approximation variance (Yu et al., 2016).

## 3 Contrastive Learning on Graphs with InfoNCE Loss

The InfoNCE (van den Oord et al., 2018) loss has been employed in various areas and has shown great power in learning informative representations in a self-supervised manner. Given the embedding of a target data point $\boldsymbol{z}_i$, together with one positive embedding $\boldsymbol{z}_i^+$ and a set of negative embeddings $\{\boldsymbol{z}_j^-\}_{j=1}^M$, the InfoNCE loss aims at discriminating the positive pair $(\boldsymbol{z}_i, \boldsymbol{z}_i^+)$ from the negative pairs $\{(\boldsymbol{z}_i, \boldsymbol{z}_j^-)\}_{j=1}^M$ via the following contrastive objective function:

$$\mathcal{L}_{\mathrm{InfoNCE}}(i) = -\log \frac{\exp(f(\boldsymbol{z}_i, \boldsymbol{z}_i^+)/\tau)}{\sum\limits_{j=1}^M \exp(f(\boldsymbol{z}_i^+, \boldsymbol{z}_j^-)/\tau)}, \tag{2}$$

where $f(\cdot, \cdot)$ is a similarity measure, usually implemented as the simple dot product $f(\boldsymbol{x}, \boldsymbol{y}) = \boldsymbol{x}^\top \boldsymbol{y}$ (He et al., 2020; Chen et al., 2020), and $\tau$ is the temperature hyperparameter. Note that $\boldsymbol{z}_i, \boldsymbol{z}_i^+$ and $\boldsymbol{z}_i^-$ are all $\ell_2$ normalized to have a **unit norm**, i.e., $\|\boldsymbol{z}_i\|_2^2 = 1$. As demonstrated in Eq. 2, the

InfoNCE loss is composed of two terms: 1) the numerator term on the positive pair that maximizes the similarity between positive pairs (positive term); 2) the denominator term on the negative pairs that encourages the embeddings of negative pairs to be distinguished (negative term). Like the study of contrastive learning on vision and language, recent node-level contrastive learning research mainly focuses on how to construct/select more informative positive and negative examples.

The most popular method for constructing **positive examples** on graphs is through data augmentation. For example, MVGRL (Hassani & Ahmadi, 2020) uses graph diffusion to generate a fixed, augmented view of the studied graph. GCC (Qiu et al., 2020) resorts to random walk to sample subgraphs of the anchored node as positive examples. GRACE (Zhu et al., 2020b) and GCA (Zhu et al., 2021) employ random graph augmentation–*feature masking* and *edge removing* to generate two views of the input graph before every training step. However, recent studies have shown that existing graph augmentations might unexpectedly change or lose the semantic information (Lee et al., 2021; Wang et al., 2022) of the target node, hurting the learned representation. This motivates us to investigate the possibility of constructing positive examples without using random, ambiguous graph augmentations.

Compared with the construction of positive examples, **negative examples** are much easier to select. A common adopted and effective practice is to use all other nodes in the graph as negative examples (Zhu et al., 2020b; 2021; Zhang et al., 2021). However, the computation of the negative term of InfoNCE has $\mathcal{O}(|\mathcal{V}|^2 d)$ time complexity and $\mathcal{O}(|\mathcal{V}|^2)$ memory complexity, where $|\mathcal{V}|$ is the number of nodes and $d$ is the embedding dimension. Note that the real-world graphs are usually very large, Eq. 2 can hardly be used in a full-graph training manner. One plausible remedy is to use down-sampling to zoom in on a fraction of negative samples for once feedforward computation. However, theoretical analysis demonstrates InfoNCE loss benefits from a large number of negative examples (Poole et al., 2019), and empirical observations show that reducing the number of negative examples leads to worse performance on downstream tasks (Thakoor et al., 2021) (also see our experiments in Sec. 5.4). As a result, it would be promising to devise an efficient and scalable computation method for the contrastive loss above, without reducing the number of negative examples.

In the next section, we propose Localized Graph Contrastive Learning with Kernel Approximation (LOCAL-GCL in short) to mitigate the above issues. LOCAL-GCL distinguishes itself from previous contrastive methods in the following two aspects: 1) instead of constructing positive examples for target nodes using data augmentations or other techniques, we directly treat all the first-order neighbors of each target node as its positive examples; 2) we introduce a Gaussian kernelized surrogate loss function, which could be accurately and efficiently approximated with linear time and memory complexity in place of the vanilla InfoNCE loss.

## 4 METHODOLOGY

### 4.1 ANCHORING NODE CONTRASTIVE LEARNING ON TOPOLOGY

Contrastive learning is firstly investigated in unsupervised visual representation learning where the data points are i.i.d. sampled from the data distribution, and the ground-truth labels are unknown during training. As a result, we have to employ well-defined augmentations to create two views of the same image that are likely to share the same ground-truth label. Different from images or texts where each input data is often assumed i.i.d. generated from a certain distribution and there is no explicit prior knowledge about the relationship among different instances, in the graph domain, nodes within the same graph are highly inter-dependent given the input graph structure. That is, the graph structure could provide additional information that reflects the affinity of node pairs. Furthermore, in network (graph) science, it is widely acknowledged that many real-world graphs (such as social networks (Wu et al., 2019; McPherson et al., 2001) and citation networks (Ciotti et al., 2016)) conform with the homophily phenomenon that similar nodes may be more likely to attach than dissimilar ones (Zhu et al., 2003; McPherson et al., 2001). Such a phenomenon also inspires the core principle followed by the designs of modern graph neural networks, i.e., connected nodes should have similar embeddings in the latent space (Zhu et al., 2020a). This motivates us to directly treats all the first-order neighboring nodes of the target node as positive examples. Formally, the loss for the positive pairs of node $i$ can be written as

$$\mathcal{L}_{\text{pos}}(i) = -\log \sum_{j \in \mathcal{N}(i)} \exp(\boldsymbol{z}_i^\top \boldsymbol{z}_j / \tau) / |\mathcal{N}(i)|. \quad (3)$$

For the negative term, we can directly use all nodes in the graph as negative examples. Then the loss for the negative pairs of node $i$ can be formulated as:

$$\mathcal{L}_{\text{neg}}(i) = \log \sum_{k \in \mathcal{V}} \exp(\boldsymbol{z}_i^\top \boldsymbol{z}_k / \tau). \tag{4}$$

The overall loss function is simply the sum of $\mathcal{L}_{\text{pos}}$ and $\mathcal{L}_{\text{neg}}$, then averaged over all nodes:

$$\mathcal{L}_{\text{Local}-\text{GCL}} = -\frac{1}{|\mathcal{V}|} \sum_{i=1}^{N} \log \frac{\sum\limits_{j \in \mathcal{N}(i)} \exp(\boldsymbol{z}_i^\top \boldsymbol{z}_j / \tau) / |\mathcal{N}(i)|}{\sum\limits_{k \in \mathcal{V}} \exp(\boldsymbol{z}_i^\top \boldsymbol{z}_k / \tau)}. \tag{5}$$

Then we'd like to provide a theoretical analysis of the effectiveness of constructing positive examples directly with the first-order neighbors. First, let's introduce some notations that will be used in the following analysis. We denote a graph by $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ is the node st and $\mathcal{E}$ is the edge set. The adjacency matrix and degree matrix are denoted by $\boldsymbol{A}$ and $\boldsymbol{D}$, respectively. Let $\tilde{\boldsymbol{A}} = \boldsymbol{D}^{-1/2} \boldsymbol{A} \boldsymbol{D}^{-1/2}$ be the symmetric normalized adjacency matrix, and $\boldsymbol{L} = \boldsymbol{I} - \tilde{\boldsymbol{A}}$ be the symmetric normalized graph Laplacian matrix. Denote the eigenvalues $\boldsymbol{L}$ in a descending order by $\{\lambda_i\}_{i=1}^{|\mathcal{V}|}$. Finally we denote the node embedding matrix $\boldsymbol{Z} = \{\boldsymbol{z}_i\}_{i=1}^{|\mathcal{V}|} \in \mathbb{R}^{|\mathcal{V}| \times d}$ and the one-hot label matrix by $\boldsymbol{Y} = \{\boldsymbol{y}_i\}_{i=1}^{|\mathcal{V}|} \in \mathbb{R}^{|\mathcal{V}| \times c}$. Without loss of generality we assume $d \le |\mathcal{V}|$.

We then give a formal definition of graph homophily ratio $\phi$:

**Definition 1.** *(Graph Homophily Ratio) For a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ with adjacency matrix $\boldsymbol{A}$, its homophily ratio $\phi$ is defined as the probability that two connected nodes share the same label:*

$$\phi = \frac{\sum_{i,j \in \mathcal{V}} A_{ij} \cdot \mathbb{1}[\boldsymbol{y}_i = \boldsymbol{y}_j]}{\sum_{i,j \in \mathcal{V}} A_{ij}} = \frac{\sum_{i,j \in \mathcal{V}} A_{ij} \cdot \mathbb{1}[\boldsymbol{y}_i = \boldsymbol{y}_j]}{|\mathcal{E}|} \tag{6}$$

We then introduce the following theorem which guarantees the linear classification error of the embeddings learned from LOCAL-GCL:

**Theorem 1.** *Let $\boldsymbol{Z}^*$ be the global minimizer of Eq. 5, then for any labeling function $\hat{y} : \mathbb{V} \to \mathbb{R}^c$ with graph homophily $\phi$, there exists a linear classifier $\boldsymbol{B}^* \in \mathbb{R}^{k \times c}$ with norm $\|\boldsymbol{B}^*\|_F \le 1/(1 - \lambda_d)$ such that*

$$\mathbb{E}_{i \in \mathcal{V}} \left[ \|\hat{y}(i) - \boldsymbol{B}^{*\top} \boldsymbol{z}_i^*\|_2^2 \right] \le \frac{1 - \phi}{\lambda_{d+1}} \tag{7}$$

See proof in Appendix A.1. Theorem 1 demonstrates that the linear classification accuracy of the learned embeddings through LOCAL-GCL is bounded by the homophily ratio $\phi$ and the $d+1$ smallest eigenvalue $\lambda_{d+1}$. Specifically, the larger the homophily ratio, the smaller the prediction error. Besides, Eq. 7 indicates that a larger embedding dimension can lead to better classification accuracy, which is also validated empirically in Sec. 5.

## 4.2 FAST AND EFFICIENT APPROXIMATION FOR THE NEGATIVE LOSS

We next probe into how to reduce the computation complexity of the negative loss term $\mathcal{L}_{\text{neg}} = \sum_{i \in \mathcal{V}} \mathcal{L}_{\text{neg}}(i)$, for which the $|\mathcal{V}|^2$ pair-wise similarities can be efficiently and precisely approximated with efficient computation methods for kernel functions (Rahimi et al., 2007; Liu et al., 2020).

We notice that the pair-wise similarity (in dot-product format) in Eq. 4 is essentially a Gaussian kernel function, i.e.,

$$\exp(\boldsymbol{z}_i^\top \boldsymbol{z}_j / \tau) = \exp(\frac{2 - \|\boldsymbol{z}_i - \boldsymbol{z}_j\|_2^2}{2\tau}) = e * \exp(\frac{-\|\boldsymbol{z}_i - \boldsymbol{z}_j\|}{2\tau}) = e \cdot \kappa^G(\boldsymbol{z}_i, \boldsymbol{z}_k; \sqrt{\tau}), \quad (8)$$

where $\kappa^G(\boldsymbol{z}_i, \boldsymbol{z}_k; \sqrt{\tau})$ is the Gaussian kernel function with bandwidth $\sqrt{\tau}$. This motives us to seek for a projection function $\phi(\boldsymbol{x})(\mathbb{R}^d \to \mathbb{R}^D)$ such that $\kappa^G(\boldsymbol{x}, \boldsymbol{y}; \sqrt{\tau}) \approx \phi(\boldsymbol{x})^\top \phi(\boldsymbol{y})$. Then we are able to use a surrogate negative loss function as a remedy of the previous one:

$$\mathcal{L}_{neg} \triangleq \frac{1}{|\mathcal{V}|} \sum_{i \in \mathcal{V}} \left( \log \sum_{j \in \mathcal{V}} \phi(\boldsymbol{h}_i)^\top \phi(\boldsymbol{h}_j) \right) = \frac{1}{|\mathcal{V}|} \sum_{i \in \mathcal{V}} \left( \log \left( \phi(\boldsymbol{h}_i)^\top \sum_{j \in \mathcal{V}} \phi(\boldsymbol{h}_j) \right) \right). \tag{9}$$

Once we obtain all the projected vectors $\{\phi(\boldsymbol{h}_i)\}_{i=1}^{|\mathcal{V}|}$, the summation term $\sum_{j\in\mathcal{V}}\phi(\boldsymbol{h}_j)$ in Eq. 9 could be calculated within $\mathcal{O}(|\mathcal{V}|D)$ in advance (where $D$ is the dimension of projected vectors). In addition to the $\mathcal{O}(|\mathcal{V}|D)$ cost for computing the loss, the overall computational cost will be $\mathcal{O}(|\mathcal{V}|D + |\mathcal{V}|D) = \mathcal{O}(VD)$, which is linear to the number of nodes. Then we discuss how to formulate the projection function $\phi(\cdot)$ below.

**Linear-Order Projection** The theory of Random Fourier Features (Rahimi et al., 2007) introduced in Sec. 2.3 demonstrates that a Gaussian kernel function $\kappa^G(\boldsymbol{x}, \boldsymbol{y}; \sqrt{\tau})$ could be unbiasedly estimated with $\phi(\boldsymbol{x})^\top\phi(\boldsymbol{y})$, and the projection function $\phi(\boldsymbol{x})$ is defined as follows:

$$\phi(\boldsymbol{x}) = \frac{[\cos(\boldsymbol{W}^\top\boldsymbol{x}), \sin(\boldsymbol{W}^\top\boldsymbol{x})]}{\sqrt{D}} = \frac{\left[\cos(\boldsymbol{\omega}_1^\top\boldsymbol{x}), \cdots, \cos(\boldsymbol{\omega}_D^\top\boldsymbol{x}), \sin(\boldsymbol{\omega}_1^\top\boldsymbol{x}), \cdots, \sin(\boldsymbol{\omega}_D^\top\boldsymbol{x})\right]^\top}{\sqrt{D}}.$$
(10)

where $\boldsymbol{W} = [\boldsymbol{\omega}_1^\top, \cdots, \boldsymbol{\omega}_D^\top]$, and each $\boldsymbol{\omega}_i$ is sampled from the Gaussian distribution $p(\boldsymbol{\omega}) = \mathcal{N}(\boldsymbol{0}, \tau\boldsymbol{I})$. $D$ is the number of total samples. Usually, the larger the sampling number $D$ is, the more accurate the approximation will be:

**Theorem 2.** *Let $\{\boldsymbol{\omega}_i\}_{i=1}^D$ be i.i.d samples from Gaussian distribution $\mathcal{N}(\boldsymbol{0}, \tau\boldsymbol{I})$, and $\phi(\boldsymbol{x})$ is given by Eq. 10, then with probability at least $1-\varepsilon$, the approximation error $\Delta = |\phi(\boldsymbol{h}_i)^\top\phi(\boldsymbol{h}_j) - \kappa^G(\boldsymbol{h}_i, \boldsymbol{h}_j)|$ will be bounded by $\mathcal{O}\left(\frac{1-\exp(-4/\tau)}{\sqrt{2D\varepsilon}}\right)$.*

Theorem 2 suggests that the Gaussian kernel function could be accurately approximated with Random Fourier Features as long as we sample enough number of linear transformation vectors $\boldsymbol{\omega}$ (i.e., $D$ should be large enough). Note that the computation of linear projection $\boldsymbol{W}\boldsymbol{h}_i$ ($i = 1 \in \mathcal{V}$) requires additional $\mathcal{O}(|\mathcal{V}|dD)$ time. A large number of the projection dimension $D$ makes the computation of Eq. 9 still expensive for high-dimensional data.

**Log-Order Projection** To handle the above issues, we resort to Structured Orthogonal Random Features (SORF) (Yu et al., 2016), another Random Feature technique that imposes structural and orthogonality on the linear transformation matrix $\boldsymbol{W}$. Different from the vanilla RFF which directly samples linear transformation vectors $\boldsymbol{\omega}$ form normal distribution to construct the transformation matrix $\boldsymbol{W}_{\mathrm{rff}} = [\boldsymbol{\omega}_1^\top, \cdots, \boldsymbol{\omega}_D^\top] \in \mathbb{R}^{d\times D}$, SORF assumes $D = d$ and constructs a structured orthogonal transformation matrix through the continued product of a series of structured matrixes:

$$\boldsymbol{W}_{\mathrm{sorf}} = \frac{\sqrt{d}}{\sigma}\boldsymbol{H}\boldsymbol{D}_1\boldsymbol{H}\boldsymbol{D}_2\boldsymbol{H}\boldsymbol{D}_3,$$
(11)

where $\boldsymbol{D}_i \in \mathbb{R}^{d\times d}, i = 1, 2, 3$, are diagonal "sign-flipping" matrices, with each diagonal entry sampled from the Rademacher distribution, and $\boldsymbol{H} \in \mathbb{R}^{d\times d}$ is the normalized Walsh-Hadamard matrix. By this definition, the projected dimension is restricted to $d$, but could be extended to any dimension by concatenating multiple independently generated features or simply using a proportion of them. The stand-out merit of SORF is that it can be computed in $\mathcal{O}(|\mathcal{V}|D\log d)$ time using fast Hadamard transformation (Fino & Algazi, 1976), and hardly requires extra memory cost using in-place operations (Yu et al., 2016). This further reduces its complexity and endows our method with desirable scalability to not only larger dataset sizes but also larger embedding dimensions. If not specified, in the following section, the term LOCAL-GCL denotes our method equipped with SORF to approximate the negative loss.

## 5 EXPERIMENTS

In this section, we conduct experiments to evaluate the proposed method by answering the following questions:

- **RQ1**: How does LOCAL-GCL perform compared with other self-supervised learning methods on graphs with different properties?
- **RQ2**: How do the specific designs of LOCAL-GCL, such as the embedding dimension and projection dimension, affect its performance?

- **RQ3**: What's the empirical memory and time consumption of LOCAL-GCL compared with prior works? Is LOCAL-GCL able to scale to real-world large-scale graphs with satisfying performance?

## 5.1 EXPERIMENTAL SETUPS

**Datasets.** We evaluate LOCAL-GCL on various datasets with different scales and properties. Following prior works (Zhu et al., 2020b; Zhang et al., 2021) on self-supervised node representation learning, we adopt the 7 common small-scale benchmarking graphs: Cora, Citeseer, Pubmed, Amazon-Computer, Amazon-Photo, Coauthor-CS, and Coauthor-Physics. To evaluate the performance and scalability of LOCAL-GCL on larger graphs, we also adopt Ogbn-Arxiv, on which a lot of methods fail to scale due to memory issues. Furthermore, we adopt three widely used heterophily graphs, Chameleon, Squirrel, and Actor to evaluate the generalization ability of LOCAL-GCL on graphs where the graph homophily assumption does not hold. The detailed introduction and statistics of these datasets are presented in Appendix C.1

**Baselines.** We consider representative prior self-supervised models for comparison. We classify previous methods into two types: 1) **Augmentation-based**, which uses data augmentations to generate positive or negative pairs. 2) **Augmentation-free**, which uses other information rather than any form of data augmentation to create self-supervised signals. For augmentation-based baselines, we consider DGI (Velickovic et al., 2019), MVGRL (Hassani & Ahmadi, 2020), GRACE (Zhu et al., 2020b), GCA Zhu et al. (2021), BGRL (Thakoor et al., 2021) and CCA-SSG (Zhang et al., 2021). For augmentation-free baselines, we consider GMI (Peng et al., 2020), SUGRL (Mo et al., 2022), AFGRL (Lee et al., 2021), AF-GCL (Wang et al., 2022).

**Evaluation Protocols.** We follow the linear evaluation scheme in previous works (Velickovic et al., 2019; Hassani & Ahmadi, 2020; Zhu et al., 2021; Zhang et al., 2021): For each dataset, i) we first train the model on all the nodes in a graph without supervision, by optimizing the objective in Eq. 5; ii) after the training ends, we freeze the parameters of the encoder and obtain all the nodes' embeddings, which are subsequently fed into a linear classifier (i.e., a logistic regression model) to generate a predicted label for each node. In the second stage, only nodes in the training set are used for training the classifier, and we report the classification accuracy on testing nodes.

**Implementation Details.** The model is implemented with PyTorch and DGL (Wang et al., 2019). All experiments are conducted on an NVIDIA V100 GPU with 16 GB memory unless specified. We adopt structure-net[1] to do fast Walsh-Hadamard transformation, which enables much faster forward and backward computation with CUDA accelerations. We use the Adam optimizer (Kingma & Ba, 2015) for both self-supervised pretraining training and linear evaluation using logistic regression. Following previous works (Zhu et al., 2021; Zhang et al., 2021; Thakoor et al., 2021; Wang et al., 2022), we the random 1:1:8 split for Amazon-Computer, Amazon-Photo, Coauthor-CS and Amazon-Computer, and use the public recommended split for the remaining datasets. For each experiment, we report the average test accuracy with the standard deviation over 20 random initialization. If not specified, we use a two-layer GCN model the encoder to generate node embeddings. More detailed hyperparameter settings for each dataset can be found in Appendix C.2

## 5.2 NUMERICAL RESULTS

**Results on common graphs.** We first report the results of node classification tasks on small-scale citation networks and social networks in Table 1. We see that although not relying on data augmentations or other complicated operations to create self-supervised signal, LOCAL-GCL performs competitively with our self-supervised baselines, achieving state-of-the-art performance in 6 out of 7 datasets. It is worth noting that the competitive InfoNCE-loss based contrastive methods GRACE and GCA suffer from OOM on Coauthor-Physics datasets due to the $\mathcal{O}(|\mathcal{V}|^2 d)$ space complexity, while LOCAL-GCL can avoid such an issue thanks to the linear approximation of the negative loss.

**Results on Ogbn-Arxiv.** Then, we evaluate the effectiveness and scalability of LOCAL-GCL on large-scale graphs taking Ogbn-Arxiv as an example. Following the practice in Thakoor et al.

---

[1]https://github.com/HazyResearch/structured-nets

Table 1: Comparison of self-supervised methods on benchmarking graphs. We group each method according to whether it relies on graph augmentation.

| | Methods | Cora | Citeseer | Pubmed | Computer | Photo | CS | Physics |
|---|---|---|---|---|---|---|---|---|
| Aug-based | DGI | 82.3±0.6 | 71.8±0.7 | 76.8±0.6 | 83.95±0.47 | 91.61±0.22 | 92.15±0.63 | 94.51±0.52 |
| | MVGRL | 83.5±0.4 | 73.3±0.5 | 80.1±0.7 | 87.52±0.11 | 91.74±0.07 | 92.11±0.12 | 95.33±0.03 |
| | GRACE | 81.9±0.4 | 71.2±0.5 | 80.6±0.4 | 86.25±0.25 | 92.15±0.24 | 92.93±0.01 | OOM* |
| | GCA | 82.3±0.4 | 72.1±0.4 | 80.7±0.5 | 87.85±0.31 | 92.49±0.09 | 93.10±0.01 | OOM |
| | BGRL | 82.7±0.6 | 71.1±0.8 | 79.6±0.5 | 89.69±0.37 | 93.07±0.28 | 92.59±0.17 | 95.48±0.08 |
| | CCA-SSG | 84.2±0.4 | 73.1±0.3 | 81.6±0.4 | 88.74±0.28 | 93.14±0.14 | 93.31±0.22 | 95.38±0.06 |
| Aug-free | GMI | 82.4±0.6 | 71.7±0.2 | 79.3±1.0 | 84.22±0.52 | 90.73±0.24 | OOM | OOM |
| | SUGRL | 83.4±0.5 | 73.0±0.4 | 81.9±0.3 | 88.93±0.21 | 93.07±0.15 | 92.83±0.23 | 95.38±0.11 |
| | AFGRL | 81.3±0.2 | 68.7±0.3 | 80.6±0.4 | **89.88±0.33** | 93.22±0.28 | 93.27±0.17 | OOM |
| | AF-GCL | 83.2±0.2 | 72.0±0.4 | 79.1±0.8 | 89.68±0.19 | 92.49±0.31 | 91.92±0.10 | 95.12±0.15 |
| | Local-GCL | **84.5±0.4** | **73.6±0.4** | **82.1±0.5** | 88.81±0.37 | **93.25±0.40** | **94.90±0.19** | **96.33±0.13** |

* OOM indicates out-of-memory on an NVIDIA-V100 GPU of 16G memory.

Table 2: Performance on Ogbn-Arxiv dataset. As recommended, we report both the validation accuracy and test accuracy.

| Methods | Validation | Test |
|---|---|---|
| DGI | 71.21±0.23 | 70.32±0.25 |
| GMI | OOM | OOM |
| MVGRL | OOM | OOM |
| GRACE | OOM | OOM |
| GCA | OOM | OOM |
| BGRL | **72.71±0.22** | **71.54±0.17** |
| CCA-SSG | 72.31±0.18 | 71.21±0.20 |
| AFGRL | OOM | OOM |
| Local-GCL | 72.29±0.25 | 71.34±0.25 |

Table 3: Performance on Heterophily graphs. Results of baseline methods are taken from Wang et al. (2022)

| Methods | Chameleon | Squirrel | Actor |
|---|---|---|---|
| DGI | 60.27±0.70 | 42.22±0.63 | 28.30±0.76 |
| GMI | 52.81±0.63 | 35.25±1.21 | 27.28±0.87 |
| MVGRL | 53.81±1.09 | 38.75±1.32 | 32.09±1.07 |
| GRACE | 61.24±0.53 | 41.09±0.85 | 28.27±0.43 |
| GCA | 60.94±0.81 | 41.53±1.09 | 28.89±0.50 |
| BGRL | 64.86±0.63 | 46.24±0.70 | 28.80±0.54 |
| AF-GCL | 65.28±0.53 | 52.10±0.67 | 28.94±0.69 |
| Local-GCL | **68.74±0.49** | **52.94±0.88** | **33.91±0.57** |

(2021), we expand the encoder to a 3-layer GCN model. We report the validation and test accuracy of baseline models and ours in Table 2. As demonstrated, many baseline methods cannot run in a full graph manner (on a GPU with 16GB memory). Compared with other scalable methods, Local-GCL can give a competitive performance on Ogbn-Arxiv.

**Results on Heterophily graphs.** Finally, we investigate the performance on non-homophily graphs, a much more challenging task as directly using first-order neighbors as positive examples without discriminating might be harmful to non-homophily graphs. The results on the three heterophily graphs are presented in Table 3. Counterintuitively, Local-GCL achieves amazing performance, outperforming all the baseline methods. We hypothesize that this is probably due to the following reason: Even though connected nodes may not share the same label, as long as the neighborhood distributions for different classes are different, Local-GCL is able to recognize the neighborhood patterns of different classes and make the node embeddings for different classes distinguishable. This is also justified in one recent work showing that a GCN model can still perform well on heterophily graphs (Ma et al., 2022).

## 5.3 Ablations

As demonstrated in Theorem 1 and Sec. 4.2, the embedding dimension $d$ and projection dimension $D$ should be two critical hyperparameters affecting the model's performance. In this section, we test Local-GCL' sensitivities with respect to them in Fig. 1. The observations are two-fold: 1) Similar to other self-supervised learning models (Hassani & Ahmadi, 2020; Zhu et al., 2021; Zhang et al., 2021; Lee et al., 2021), Local-GCL that benefit from a large embedding dimension (e.g., 512), Local-GCL's performance also grows as we increase the embedding dimension $d$. However, the optimal embedding dimension for Local-GCL is even larger, e.g., 2048 on Cora and Citeseer (note that other methods do not benefit from such a large embedding dimension). This could be

Figure 1: Sensitivity analysis of embedding dimension $d$ and projection dimension $D$.

Figure 2: Test accuracy and training time comparison of LOCAL-GCL, BGRL, CCA-SSG and GRACE with subsampling.

justified by our analysis in Theorem 1, which demonstrates that with a larger embedding dimension, the bound of the prediction error will become lower (because the target eigenvalue $\lambda_{d+1}$ becomes larger). 2) Increasing the projection dimension can lead to better but minimal improvement. This indicates that in practice, LOCAL-GCL can perform quite well without using a huge projection $D$.

## 5.4 SCALABILITY COMPARISON

To evaluate the scalability of LOCAL-GCL on real-world datasets, we compare the total training time and test accuracy with state-of-the-art scalable methods BGRL (Thakoor et al., 2021) and CCA-SSG (Zhang et al., 2021) on Ogbn-Arxiv dataset. To further justify the necessity of adopting a large number of negative examples, we additionally adopt GRACE (Zhu et al., 2020b), a powerful non-scalable contrastive model. We use sub-sampling strategy to randomly sample a fixed number of negative examples every epoch so that the GRACE model could be fit into a GPU with 16G memory. In Fig. 2 we plot the model's performance and the corresponding training time of different methods. We can see that compared with scalable methods CCA-SSG and BGRL, LOCAL-GCL can achieve comparable performance but with the least training time. We can also observe that although reducing the number of negative examples ($k$ in Fig. 2) can enable the model to be trained much faster, the performance drop is significant, which cannot make up for the efficiency benefit. Furthermore, if we continue to use an even larger number of negative examples, GRACE will soon run out of memory. This result demonstrates that LOCAL-GCL can better balance the training efficiency and model performance.

## 6 CONCLUSIONS

In this paper, we have presented LOCAL-GCL, a simple, light-weighted yet effective contrastive model for self-supervised node representation learning. LOCAL-GCL incorporates two orthogonal techniques to address two key issues in contrastive learning on graph data: reliance on data augmentation and scalability, respectively. The former involves a new definition of positive examples such that the model is free from data augmentation whose design could be more difficult than its counterparts in vision and text, and calls for careful customization for different graph data and tasks. The latter devises an approximated contrastive loss, which reduces the quadratic complexity of traditional contrastive learning to linearity in terms of the graph size. Extensive experimental results on seven public graph benchmarks show its efficiency and efficacy.

# REFERENCES

Haim Avron, Michael Kapralov, Cameron Musco, Christopher Musco, Ameya Velingker, and Amir Zandieh. Random fourier features for kernel ridge regression: Approximation bounds and statistical guarantees. In *ICML*, pp. 253–262, 2017.

Randall Balestriero and Yann LeCun. Contrastive and non-contrastive self-supervised learning recover global and local spectral embedding methods. *arXiv preprint arXiv:2205.11508*, 2022.

Hubert Banville, Omar Chehab, Aapo Hyvärinen, Denis-Alexander Engemann, and Alexandre Gramfort. Uncovering the structure of clinical eeg signals with self-supervised learning. *Journal of Neural Engineering*, 18(4):046020, 2021.

Ting Chen, Simon Kornblith ands Mohammad Norouzi, and Geoffrey E. Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, pp. 1597–1607, 2020.

Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. In *ICLR*, 2020.

Valerio Ciotti, Moreno Bonaventura, Vincenzo Nicosia, Pietro Panzarasa, and Vito Latora. Homophily and missing links in citation networks. *EPJ Data Sci.*, 5(1):7, 2016.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In *NAACL*, pp. 4171–4186, 2019.

Debidatta Dwibedi, Yusuf Aytar, Jonathan Tompson, Pierre Sermanet, and Andrew Zisserman. With a little help from my friends: Nearest-neighbor contrastive learning of visual representations. *arXiv preprint arXiv:2104.14548*, 2021.

Bernard J. Fino and V. Ralph Algazi. Unified matrix treatment of the fast walsh-hadamard transform. *IEEE Transactions on Computers*, 25(11):1142–1146, 1976.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*, 2021.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Ávila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent - A new approach to self-supervised learning. In *NeurIPS*, 2020.

Jeff Z HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable guarantees for self-supervised deep learning with spectral contrastive loss. *NeurIPS*, 34:5000–5011, 2021.

Kaveh Hassani and Amir Hosein Khas Ahmadi. Contrastive multi-view representation learning on graphs. In *ICML*, 2020.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross B. Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, pp. 9726–9735, 2020.

R. Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Philip Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *ICLR*, 2019.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. In *NeurIPS*, 2020.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

Thomas N. Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016.

Soroush Abbasi Koohpayegani, Ajinkya Tejankar, and Hamed Pirsiavash. Mean shift for self-supervised learning. In *ICCV*, pp. 10326–10335, 2021.

Quoc Le, Tamás Sarlós, Alex Smola, et al. Fastfood-approximating kernel expansions in loglinear time. In *ICML*, pp. 244–252, 2013.

Namkyeong Lee, Junseok Lee, and Chanyoung Park. Augmentation-free self-supervised learning on graphs. *arXiv preprint arXiv:2112.02472*, 2021.

Yazhe Li, Roman Pogodin, Danica J. Sutherland, and Arthur Gretton. Self-supervised learning with kernel dependence maximization. *arXiv preprint arXiv:2106.08320*, 2021.

Fanghui Liu, Xiaolin Huang, Yudong Chen, and Johan AK Suykens. Random features for kernel approximation: A survey on algorithms, theory, and beyond. *arXiv preprint arXiv:2004.11154*, 2020.

Yao Ma, Xiaorui Liu, Neil Shah, and Jiliang Tang. Is homophily a necessity for graph neural networks? In *ICLR*, 2022.

Julian J. McAuley, Christopher Targett, Qinfeng Shi, and Anton van den Hengel. Image-based recommendations on styles and substitutes. In *SIGIR*, pp. 43–52, 2015.

Miller McPherson, Lynn Smith-Lovin, and James M Cook. Birds of a feather: Homophily in social networks. *Annual review of sociology*, 27(1):415–444, 2001.

Yujie Mo, Liang Peng, Jie Xu, Xiaoshuang Shi, and Xiaofeng Zhu. Simple unsupervised graph representation learning. In *AAAI*, pp. 7797–7805, 2022.

Galileo Namata, Ben London, Lise Getoor, Bert Huang, and UMD EDU. Query-driven active surveying for collective classification. In *10th International Workshop on Mining and Learning with Graphs*, volume 8, 2012.

Hongbin Pei, Bingzhe Wei, Kevin Chen-Chuan Chang, Yu Lei, and Bo Yang. Geom-gcn: Geometric graph convolutional networks. In *ICLR*, 2020.

Hao Peng, Nikolaos Pappas, Dani Yogatama, Roy Schwartz, Noah A Smith, and Lingpeng Kong. Random feature attention. In *ICLR*, 2021.

Zhen Peng, Wenbing Huang, Minnan Luo, Qinghua Zheng, Yu Rong, Tingyang Xu, and Junzhou Huang. Graph representation learning via graphical mutual information maximization. In *WWW*, pp. 259–270, 2020.

Ben Poole, Sherjil Ozair, Aaron Van Den Oord, Alex Alemi, and George Tucker. On variational bounds of mutual information. In *ICML*, pp. 5171–5180, 2019.

Jiezhong Qiu, Qibin Chen, Yuxiao Dong, Jing Zhang, Hongxia Yang, Ming Ding, Kuansan Wang, and Jie Tang. GCC: graph contrastive coding for graph neural network pre-training. In *KDD*, pp. 1150–1160, 2020.

Ali Rahimi, Benjamin Recht, et al. Random features for large-scale kernel machines. In *NIPS*, pp. 1177–1884, 2007.

Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI magazine*, 29(3):93–93, 2008.

Arnab Sinha, Zhihong Shen, Yang Song, Hao Ma, Darrin Eide, Bo-June Paul Hsu, and Kuansan Wang. An overview of microsoft academic service (MAS) and applications. In *WWW*, pp. 243–246, 2015.

Shantanu Thakoor, Corentin Tallec, Mohammad Gheshlaghi Azar, Rémi Munos, Petar Velickovic, and Michal Valko. Bootstrapped representation learning on graphs. *arXiv preprint arXiv:2102.06514*, 2021.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. In *ECCV*, pp. 776–794, 2020.

Yao-Hung Hubert Tsai, Yue Wu, Ruslan Salakhutdinov, and Louis-Philippe Morency. Self-supervised learning from a multi-view perspective. In *ICLR*, 2021.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Petar Velickovic, William Fedus, William L. Hamilton, Pietro Liò, Yoshua Bengio, and R. Devon Hjelm. Deep graph infomax. In *ICLR*, 2019.

Haonan Wang, Jieyu Zhang, Qi Zhu, and Wei Huang. Augmentation-free graph contrastive learning with performance guarantee. *arXiv Preprint arXiv:2204.04874*, abs/2204.04874, 2022.

Minjie Wang, Lingfan Yu, Da Zheng, Quan Gan, Yu Gai, Zihao Ye, Mufei Li, Jinjing Zhou, Qi Huang, Chao Ma, Ziyue Huang, Qipeng Guo, Hao Zhang, Haibin Lin, Junbo Zhao, Jinyang Li, Alexander J. Smola, and Zheng Zhang. Deep graph library: Towards efficient and scalable deep learning on graphs. *arXiv*, 1909.01315, 2019.

Qitian Wu, Hengrui Zhang, Xiaofeng Gao, Peng He, Paul Weng, Han Gao, and Guihai Chen. Dual graph attention networks for deep latent representation of multifaceted social effects in recommender systems. In *WWW*, pp. 2091–2102. ACM, 2019.

Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. Graph contrastive learning with augmentations. In *NeurIPS*, 2020.

Felix Xinnan X Yu, Ananda Theertha Suresh, Krzysztof M Choromanski, Daniel N Holtmann-Rice, and Sanjiv Kumar. Orthogonal random features. In *NIPS*, pp. 1975–1983, 2016.

Hengrui Zhang, Qitian Wu, Junchi Yan, David Wipf, and Philip S Yu. From canonical correlation analysis to self-supervised graph neural networks. In *NeurIPS*, 2021.

Qinyi Zhang, Sarah Filippi, Arthur Gretton, and Dino Sejdinovic. Large-scale kernel methods for independence testing. *Statistics and Computing*, 28(1):113–130, 2018.

Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. In *NeurIPS*, 2020a.

Xiaojin Zhu, Zoubin Ghahramani, and John D. Lafferty. Semi-supervised learning using gaussian fields and harmonic functions. In *ICML*, pp. 912–919, 2003.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Deep graph contrastive representation learning. *arXiv preprint arXiv:2006.04131*, 2020b.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Graph contrastive learning with adaptive augmentation. In *WWW*, 2021.

# A  PROOFS

## A.1  PROOF FOR THEOREM 1

*Proof.* To prove Theorem 1, we first introduce a lemma that shows the optimal representations learned from InfoNCE-like loss function (e.g., Eq. 5) derived from Balestriero & LeCun (2022):

**Lemma 1.** *Denote the eigendecomposition of the graph adjacency matrix by $\tilde{A} = U\Lambda U^\top$, where $U$ and $\Sigma$ are the eigenvectors and eigenvalues of $A$ respectively. Assume node embeddings are free vectors, then a global minimizer of the loss function in Eq. 5 is given by:*

$$Z^* = (U\Lambda^{1/2})_{:,1:d}, \tag{12}$$

*up to permutations of the eigenvector associated to the same eigenvalue.*

Besides, HaoChen et al. (2021) has presented the following theoretical guarantee for the model learned with the matrix factorization loss:

**Lemma 2.** *For a graph $\mathcal{G}$ with symmetric normalized graph adjacency matrix and Laplacian matrix $\tilde{A}$ and $\tilde{L}$, let $f^*_{mf} \in \arg\min_{f_{mf}:\mathcal{V}\to\mathbb{R}^K}$ be a minimizer of the matrix factorization loss: $\mathcal{L}_{\mathrm{mf}}(F) = \|(I - \tilde{L} - FF^\top)\|^2_F$, where $F$ is the embedding matrix. Then, for any labeling function $\hat{y} : \mathcal{X} \to [r]$, there exists a linear classifier $B^* \in \mathbb{R}^{K\times c}$ with norm $\|B^*\|_F \leq 1/(1 - \lambda_{K+1})$ such that:*

$$\mathbb{E}_{v\in\mathcal{V}}\left[\|\,\vec{y}(v) - B^*f^*(v)\|^2_2\right] \leq \frac{1-\phi}{\lambda_{K+1}}, \tag{13}$$

*where $\phi$ is the graph homophily ratio defined in Eq. 6.*

Then we just need to connect our objective function with the matrix factorization loss. Note that according to Lemma 1, the optimal node embeddings with our objective function is given by $(U\Lambda^{1/2})_{:,1:d}$, which is exactly a global minimizer the matrix factorization loss:

$$\mathcal{L}_{mf}(Z^*) = \|I - \tilde{L} - Z^*Z^{*\top}\|^2_F = \|\tilde{A} - \hat{\tilde{A}}\|^2_F, \tag{14}$$

where $\hat{\tilde{A}}$ is the recovered symmetric normalized graph adjacency matrix with the top-$d$ largest eigenvalues and the corresponding eigenvectors of $\tilde{A}$. So $Z^*$ is a global minimizer of $\mathcal{L}_{mf}$ given the embedding dimension $d$. Then we complete the proof.

$\square$

## A.2  PROOF FOR THEOREM 2

*Proof.* To prove Theorem 2, we first introduce the following lemma given by Lemma 1 in (Yu et al., 2016).

**Lemma 3.** *The Random Fourier Estimation $K_{RFF}(x, y)$ is an unbiased estimator of the Gaussian kernel, i.e., $\mathbb{E}_\omega(\phi(x)^\top\phi(y)) = e^{-\|x-y\|^2_2/2\tau}$. Let $z = \|x - y\|_2/\sqrt{\tau}$, then the variance of $K_{RFF}(x, y)$ is $\mathbb{V}_\omega(\phi(x)^\top\phi(y)) = (1 - e^{-z^2})^2/2D$.*

The lemma shows that the Random Fourier Features can achieve an unbiased approximation for the Gaussian kernel with a quantified variance.

Back to our main theorem, we can derive the following probability using the Chebyshev's inequality:

$$\mathbb{P}(\Delta < \frac{1 - \exp(-4/\tau)}{\sqrt{2D\varepsilon}}) \geq 1 - \frac{\mathbb{V}_\omega(\phi(h_i)^\top\phi(h_j)) * 2D\varepsilon}{(1 - \exp(-4/\tau))^2} \tag{15}$$

where $\Delta = |\phi(h_i)^\top\phi(h_j) - \kappa^G(h_i, h_j)|$ denotes the deviation of the kernel approximation. Using the result in Lemma 3, we can further obtain that the RHS of Eq. 15 is

$$1 - \frac{(1 - e^{-z^2})^2 * \varepsilon}{(1 - \exp(-4/\tau))^2} \tag{16}$$

As both $\boldsymbol{h}_i$ and $\boldsymbol{h}_j$ are $\ell_2$-normalized, we have $z^2 = \|\boldsymbol{h}_i - \boldsymbol{h}_j\|_2^2 / \tau \leq 4/\tau$, so we can conclude the stated result:

$$\mathbb{P}(\Delta < \frac{1 - \exp(-4/\tau)}{\sqrt{2D\varepsilon}}) \geq 1 - \frac{(1 - e^{-z^2})^2 * \varepsilon}{(1 - \exp(-4/\tau))^2} \geq 1 - \varepsilon \qquad (17)$$

$\square$

## B  ADVANTAGES OF LOCAL-GCL OVER PRIOR METHODS

We provide a systematic comparison for the proposed LOCAL-GCL with previous typical methods self-supervised node representation learning, including DGI (Velickovic et al., 2019), MVGRL (Hassani & Ahmadi, 2020), GRACE (Zhu et al., 2020b), GCA (Zhu et al., 2021), BGRL (Thakoor et al., 2021), CCA-SSG (Zhang et al., 2021) and AFGRL (Lee et al., 2021).

### B.1  TOTALLY AUGMENTATION-FREE WITH SINGLE BRANCH

Most of previous self-supervised learning models (Velickovic et al., 2019; Hassani & Ahmadi, 2020; Zhu et al., 2020b; 2021; Thakoor et al., 2021; Zhang et al., 2021) require carefully-defined graph augmentations to obtain positive pairs. However, as noted above, it is hard and costly to design task and dataset-specific graph augmentations. Our method LOCAL-GCL naturally avoids data augmentation through using the first-order neighborhood information of each node. Moreover, different from all previous methods that have two branches of models (double amounts of inputs, hidden variables, outputs, etc.), our approach only requires a single branch, which makes our method light-weighted.

### B.2  PROJECTOR/PREDICTOR/DISCRIMINATOR-FREE

Most of the previous methods require additional components beside the basic encoder for decent empirical results (Zhu et al., 2020b; 2021), to break symmetries for avoiding trivial solutions (Thakoor et al., 2021; Lee et al., 2021) or to estimate some score functions in their final objectives (Velickovic et al., 2019; Hassani & Ahmadi, 2020). Compared with them, LOCAL-GCL is much simpler, in both conceptual and practical senses, without using any parameterized model but the basic encoder.

### B.3  THEORETICALLY GROUNDED WITH LINEAR COMPLEXITY

Empirically, InfoNCE-based contrastive methods (Zhu et al., 2020b; 2021) often show better performance than DIM-based methods (Velickovic et al., 2019; Hassani & Ahmadi, 2020) yet suffers from the scalability issue. Recent non-contrastive methods (Thakoor et al., 2021; Lee et al., 2021) could maintain decent performance with linear model complexity through asymmetric structures, while the rationale behind their success still remains unclear (Zhang et al., 2021). As a contrastive model, LOCAL-GCL is theoretically grounded (through maximizing the mutual information between target node's embedding and its neighbor's embeddings), and its kernelized approximation of negative loss enables it to scale to large graphs with linear time and memory complexity with respect to the graph size.

## C  EXPERIMENT DETAILS

### C.1  DATASETS

The statistics of the used datasets are presented in Table 4, and brief introduction and settings are as follows:

`Cora`, `Citeseer`, `Pubmed` are three widely used node classification benchmarks (Sen et al., 2008; Namata et al., 2012). Each dataset consists one citation network, where nodes represent papers and edges represent a citation relationship from one node to another. We use the public split, where each class has fixed 20 nodes for training, another fixed 500 nodes and 1000 nodes are for validation/test respectively for evaluation.

Table 4: Statistics of benchmark datasets.

| Dataset | #Nodes | #Edges | #Classes | #Features |
|---|---|---|---|---|
| Cora | 2,708 | 10,556 | 7 | 1,433 |
| Citeseer | 3,327 | 9,228 | 6 | 3,703 |
| Pubmed | 19,717 | 88,651 | 3 | 500 |
| Coauthor-CS | 18,333 | 327,576 | 15 | 6,805 |
| Coauthor-Physics | 34,493 | 991,848 | 5 | 8,451 |
| Amazon-Computer | 13,752 | 574,418 | 10 | 767 |
| Amazon-Photo | 7,650 | 287,326 | 8 | 745 |
| Ogbn-Arxiv | 169,343 | 2,332,386 | 40 | 128 |
| Chameleon | 2,277 | 36,101 | 5 | 2,325 |
| Squirrel | 5,201 | 217,073 | 5 | 2,089 |
| Actor | 7,600 | 33,544 | 5 | 931 |

`Coauthor-CS`, `Coauthor-Physics` are co-authorship graphs based on the Microsoft Academic Graph from the KDD Cup 2016 challenge (Sinha et al., 2015). Nodes are authors, that are connected by an edge if they co-authored a paper; node features represent paper keywords for each author's papers, and class labels indicate most active fields of study for each author. As there is no public split for these datasets, we randomly split the nodes into train/validation/test (10%/10%/80%) sets.

`Amazon-Computer`, `Amazon-Photo` are segments of the Amazon co-purchase graph (McAuley et al., 2015), where nodes represent goods, edges indicate that two goods are frequently bought together; node features are bag-of-words encoded product reviews, and class labels are given by the product category. We also use a 10%/10%/80% split for these two datasets.

For simplicity, we use the processed version of these datasets provided by Deep Graph Library (Wang et al., 2019)[2]. One can easily acquire these datasets using the api provided by DGL.

`Ogbn-Arxiv` is a directed graph, representing the citation network between all Computer Science (CS) arXiv papers (Hu et al., 2020). Each node is an arXiv paper and each directed edge indicates that one paper cites another one. Each paper comes with a 128-dimensional feature vector obtained by averaging the embeddings of words in its title and abstract. The embeddings of individual words are computed by running the skip-gram over the MAG corpus. All papers are also associated with the year that the corresponding paper was published. We use the official split in our experiments.

`Chameleon` and `Squirrel` are Wikipedia networks introduced. Nodes represent web pages and edges represent hyperlinks between them. Node features represent several informative nouns in the Wikipedia pages. The task is to predict the average daily traffic of the web page.

`Actor` is the actor-only induced subgraph of the film-director-actor-writer network used in Pei et al. (2020). Each node corresponds to an actor, and the edge between two nodes denotes co-occurrence on the same Wikipedia page. Node features correspond to some keywords in the Wikipedia pages. The task is to classify the nodes into five categories in term of words of actor's Wikipedia.

For `Chameleon`, `Squirrel` and `Actor`, we use the raw data provide by the Geom-GCN (Pei et al., 2020) paper[3], and we use the 10-fold split provided.

## C.2 HYPER-PARAMETERS

We provide the detailed hyper-parameters on the seven benchmarks in Table 5. All hyper-parameters are selected through small grid search, and the search space is provided as follows:

- Training steps: {20, 50}
- Number of layers: {1, 2}
- Embedding dimension $d$: {512, 1024, 2048}
- Projection dimension $D$: {2048, 4096, 8192}

---

[2]https://docs.dgl.ai/en/0.6.x/api/python/dgl.data.html
[3]https://github.com/graphdml-uiuc-jlu/geom-gcn

Table 5: Details of hyper-parameters of the experimental results in Table 1

| Dataset | Local-GCL | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | Encoder | # Steps | # layers | lr | wd | $d$ | $D$ | $\tau$ |
| Cora | GCN | 50 | 2 | 5e-4 | 1e-6 | 2048 | 8192 | 0.5 |
| Citeseer | GCN | 20 | 1 | 1e-3 | 1e-4 | 2048 | 4096 | 0.5 |
| Pubmed | GCN | 50 | 2 | 5e-4 | 0 | 1024 | 8192 | 0.5 |
| Amazon-Computer | GCN | 50 | 2 | 5e-4 | 0 | 1024 | 8192 | 0.8 |
| Amazon-Photo | GCN | 50 | 2 | 5e-4 | 1e-6 | 2048 | 8192 | 0.5 |
| Coauthor-CS | MLP | 50 | 2 | 5e-4 | 1e-4 | 1024 | 4096 | 0.5 |
| Coauthor-Physics | MLP | 50 | 2 | 5e-4 | 0 | 1024 | 4096 | 0.7 |

- Temperature $\tau$: {0.5, 0.6, 0.7, 0.8, 0.9, 1.0}
- Learning rate: {5e-4, 1e-3, 5e-3}
- Weight decay: {0, 1e-6, 1e-4}

# D    REPRODUCIBILITY

We provide detailed codes and running instructions in the supplementary material.