Convergence for score-based generative modeling with polynomial complexity

Abstract

Score-based generative modeling (SGM) is a highly successful approach for learning a probability distribution from data and generating further samples. We prove the first polynomial convergence guarantees for the core mechanic behind SGM: drawing samples from a probability density p given a score estimate (an estimate of $\nabla \ln p$) that is accurate in $L^2(p)$. Compared to previous works, we do not incur error that grows exponentially in time or that suffers from a curse of dimensionality. Our guarantee works for any smooth distribution and depends polynomially on its log-Sobolev constant. Using our guarantee, we give a theoretical analysis of score-based generative modeling, which transforms white-noise input into samples from a learned data distribution given score estimates at different noise scales. Our analysis gives theoretical grounding to the observation that an annealed procedure is required in practice to generate good samples, as our proof depends essentially on using annealing to obtain a warm start at each step. Moreover, we show that a predictor-corrector algorithm gives better convergence than using either portion alone.

1 Introduction

A key task in machine learning is to learn a probability distribution from data, in a way that allows efficient generation of additional samples from the learned distribution. Score-based generative modeling (SGM) is one empirically successful approach that *implicitly* learns the probability distribution by learning how to transform white noise into the data distribution, and gives state-of-the-art performance for generating images and audio [SE19; Dat+19; Gra+19; SE20; Son+20b; Men+21; Son+21b; Son+21a; Jin+22]. It also yields a conditional generation process for inverse problems [DN21]. The basic idea behind score-based generative modeling is to first estimate the score function from data [Son+20a] and then to sample the distribution based on the learned score function. Other approaches for generative modeling include generative adversarial networks (GANs) [Goo+14; ACB17], normalizing flows [DSB16], variational autoencoders [KW19], and energy-based models [ZML16]. While score-based generative modeling has achieved great success, its theoretical analysis is still lacking and is the focus of our work.

1.1 Background

General framework. The *score function* of a distribution P with density p is defined as the gradient of the log-pdf, $\nabla \ln p$. Its significance arises from the fact that knowing the score function allows running a variety of sampling algorithms, based on discretizations of stochastic differential equations (SDE's), to sample from p. SGM consists of two steps: first, learning an estimate of the score function for a sequence of "noisy" versions of the data distribution P_{data}, and second, using

35 the score function in lieu of the gradient of the log-pdf in the chosen sampling algorithm. We now
36 describe each of these steps more precisely.

37 First, a method of adding noise to the data distribution is fixed; this takes the form of evolving a
38 (forward) stochastic differential equation (SDE) starting from the data distribution. We fix a se-
39 quence of noise levels $\sigma_1 < \cdots < \sigma_N$. For $\sigma \in \{\sigma_1, \ldots, \sigma_N\}$, let the resulting distributions be
40 P_{σ^2} and the distributions conditional on the starting data point be $P_{\sigma^2}(\cdot|x)$. Typically, σ_1 is cho-
41 sen so that $P_{\sigma_1^2} \approx P_{\text{data}}$ and $P_{\sigma_N^2}$ is close to some "prior" distribution that is easy to sample from,
42 such as $N(0, \sigma_N^2 I_d)$. While the score $\nabla \ln p_{\sigma^2}$ cannot be estimated directly, it turns out that an de-
43 noising objective that is equivalent to the score-matching objective can be calculated [SE19]. This
44 de-noising objective can be estimated from samples $(X, \widetilde{X})$ where $\widetilde{X} \sim P_{\sigma^2}(\cdot|x)$. The objective is
45 represented and optimized within an expressive function class, typically neural networks, to obtain
46 a L^2-estimate of the score, that is, $s_\theta(x, \sigma^2)$ such that

$$\mathbb{E}_{x \sim P_{\sigma^2}}[\|s_\theta(x, \sigma^2) - \nabla \ln p_{\sigma^2}(x)\|^2] \tag{1}$$

47 is small.

48 The reason we estimate the score function $\nabla \ln p_{\sigma^2}$ is that there are a variety of sampling
49 algorithms—based on simulating SDE's—that can sample from $\ln p$ given access to $\nabla \ln p$, includ-
50 ing Langevin Monte Carlo and Hamiltonian Monte Carlo. The second step is then to use the esti-
51 mated score function $s_\theta(x, t)$ in lieu of the exact gradient in the sampling algorithm to successively
52 obtain samples from $p_{\sigma_N^2}, \ldots, p_{\sigma_1^2}$. This sequence interpolates smoothly between the prior distri-
53 bution (e.g., $N(0, \sigma_N^2 I_d)$) and the the data distribution P_{data}; such an "annealing" or "homotopy"
54 method is required in practice to generate good samples [Son+20b].

55 **Examples of SGM's.** There have been several instantiations of this general approach. [SE19]
56 add gaussian noise to the data and then use Langevin diffusion at a discrete set of noise levels
57 $\sigma_N > \cdots > \sigma_1$ as the sampling algorithm. [Son+20b] take the continuous perspective and con-
58 sider a more general framework, where the forward process can be any reasonable SDE. Then a
59 natural *reverse SDE* evolves the final distribution $p_{\sigma_N^2}$ back to the data distribution; this process
60 can be simulated with the estimated score. They consider methods based on two different SDE's:
61 score-matching Langevin diffusion (SMLD) based on adding Gaussian noise and denosing diffusion
62 probabilistic models (DDPM) [Soh+15; HJA20], based on the Ornstein-Uhlenbeck process. Note
63 that a difference with MCMC-based methods is that these SDE's are evolved for a fixed amount of
64 time, rather than until convergence. However, they can be combined with MCMC-based methods
65 such as Langevin diffusion in the *predictor-corrector* approach for improved convergence. [DVK21]
66 include Hamiltonian dynamics: they augment the state space with a velocity variable and consider
67 a critically-damped version of the Ornstein-Uhlenbeck process. Finally, we note the work of [De
68 +21], who introduce the Diffusion Schrödinger Bridge method to learn a diffusion that more quickly
69 transforms the prior into the data distribution.

70 We will give a general analysis framework for SGM's that applies to the algorithms in both [SE19]
71 and [Son+20b].

1.2 Prior work and challenges for theory

73 Although the literature on convergence for Langevin Monte Carlo [DM17; CB18; Che+18; Dal17;
74 DK19; MMS20; EHZ21] and related sampling algorithms is extensive, prior works mainly consider
75 the case of exact or stochastic gradients. In contrast, by the structure of the loss function (1), the
76 score function learned in SGM is only accurate in $L^2(p)$. This poses a significant challenge for
77 analysis, as the stationary distribution of Langevin diffusion with $L^2(p)$-accurate gradient can be
78 arbitrarily far from p (see Appendix D). Hence, any analysis must be utilizing the short/medium-
79 term convergence, while overcoming the potential issue of long-term behavior of convergence to an
80 incorrect distribution.

81 [BMR20] give the first theoretical analysis of SGM, and in particular, Langevin Monte Carlo with
82 $L^2(p)$-accurate gradients. First, they show using uniform generalization bounds that optimizing
83 the de-noising autoencoder (DAE) objective does in fact give a $L^2(p)$-accurate score function, with
84 sample complexity depending on the complexity of the function class. They analyze convergence of
85 LMC in Wasserstein distance. However, the error they obtain (Theorem 13) only decreases as $\varepsilon^{1/d}$

where ε is the accuracy of the score estimate—so it suffers from the curse of dimensionality—and increases exponentially in the time that the process is run, the dimension, and the smoothness of the distribution, as in ODE/SDE discretization arguments that do not depend on contractivity.

[De +21] give an analysis for [Son+20b] in TV distance that requires a L^∞-accurate score function and depends exponentially on the amount of time the reverse SDE is run. Although exponential dependence is bad in general, it is mollified using their Diffusion Schrödinger Bridge (DSB) approach, as it allows running for a shorter, fixed amount of time, before the forward SDE converges to the prior distribution. However, this supposes that a good solution can be found for the DSB problem, and theoretical guarantees may be difficult to obtain.

We overcome the challenges of analysis with a $L^2(p)$-accurate gradient, and give the first analysis with only polynomial dependence on running time, dimension, and smoothness of the distribution, with rates that are a fixed power of ε. Our convergence result is in TV distance. We assume only smoothness conditions and a bounded log-Sobolev constant of the data distribution, a weaker condition than the dissipativity condition required by [BMR20]. We introduce a general framework for analysis of sampling algorithms given L^2-accurate gradients (score function) based on constructing a "bad set" with small measure and showing convergence of the discretized process conditioned on not hitting the bad set. We use our framework to give an end-to-end analysis for both the algorithms in [SE19] and [Son+20b], and illuminate the relative performance of different methods in practice.

1.3 Notation and organization

Through out the paper, $p(x) \propto e^{-V(x)}$ denotes the target distribution in $\mathbb{R}^d$ and $V : \mathbb{R}^d \to \mathbb{R}$ is referred to as the potential. We abuse notation by identifying a measure with its density when context allows. We write $a \wedge b$ and $a \vee b$ as shorthands for $\max\{a, b\}$ and $\min\{a, b\}$ respectively. We use $a = O(b)$ or $b = \Omega(a)$ to indicate that $a \le Cb$ for a universal constant $C > 0$. Also, we write $a = \Theta(b)$ if there are universal constants $c' > c > 0$ such that $cb \le a \le cb$, and the notation $\tilde{O}(\cdot)$ means it hides polylog factors in the parameters.

In Section 2 we explain our main results for Langevin Monte Carlo with $L^2(p)$-accurate score estimate and use it to derive convergence bounds for the annealed LMC method of [SE19]. In Section 3, we give our main results for the predictor-corrector algorithms of [Son+20b] based on simulating reverse SDE's. Our proofs are based on a common framework which we introduce in Section 4. Full proofs are in the appendix.

2 Results for Langevin dynamics with estimated score

Let $p(x) \propto e^{-V(x)}$ be a probability density on $\mathbb{R}^d$ such that V is C^1. Langevin diffusion with stationary distribution p is the stochastic process defined by the SDE

$$dx_t = -\nabla V(x_t)\, dt + \sqrt{2}dW_t.$$

The rate of convergence to p in χ^2 and KL divergences are given by the Poincaré and log-Sobolev constants of p, respectively; see Section E.1. To obtain the Langevin Monte Carlo (LMC) algorithm, we take the Euler-Murayama discretization of the SDE. We define LMC with score estimate $s(x) \approx -\nabla V(x)$ and step size h by

$$x_{(k+1)h} = x_{kh} + h \cdot s(x_{kh}) + \sqrt{2h} \cdot \xi_{kh}, \text{ where } \xi_{kh} \sim N(0, I_d). \tag{LMC-SE}$$

2.1 Langevin with L^2-accurate score estimate

Our first main result gives an error bound between the sampled distribution and p, assuming L^2-accurate score function estimate. To state it, we make the following assumptions on the density p and the score estimate s.

Assumption 1. *p is a probability density on $\mathbb{R}^d$ such that the following hold.*

    1. $\ln p$ is C^1 and L-smooth, that is, $\nabla \ln p$ is L-Lipschitz. We assume $L \ge 1$.

    2. p satisfies a log-Sobolev inequality with constant C_{LS}. We assume $C_{\mathrm{LS}} \ge 1$.

Assumption 2. *Let p be a given probability density on $\mathbb{R}^d$ such that $\ln p$ is C^1. The score estimate $s : \mathbb{R}^d \to \mathbb{R}^d$ satisfies the following.*

    1. s is a C^1 function that is L_s-Lipschitz. We assume $L_s \geq 1$.

    2. The error in the score estimate is bounded in L^2:

$$\|\nabla \ln p - s\|_{L^2(p)}^2 = \mathbb{E}_p[\|\nabla \ln p(x) - s(x)\|^2] \leq \varepsilon^2.$$

Theorem 2.1 (LMC with L^2-accurate score estimate). *Let $p : \mathbb{R}^d \to \mathbb{R}$ be a probability density satisfying Assumption 1 with $L \geq 1$ and $s : \mathbb{R}^d \to \mathbb{R}^d$ be a score estimate satisfying Assumption 2(2). Consider the accuracy requirement in* TV *and* χ^2: $0 < \varepsilon_{\mathrm{TV}} < 1$, $0 < \varepsilon_\chi < 1$, *and suppose furthermore the starting distribution satisfies $\chi^2(p_0\|p) \leq K_\chi^2$. Then if*

$$\varepsilon = O\left(\frac{\varepsilon_{\mathrm{TV}} \varepsilon_\chi^3}{dL^2 C_{\mathrm{LS}}^{5/2}(C_T \ln(2K_\chi/\varepsilon_\chi^2) \vee K_\chi)} \right),$$

then running (LMC-SE) *with score estimate s and step size $h = \Theta\left(\frac{\varepsilon_\chi^2}{dL^2 C_{\mathrm{LS}}} \right)$ for any time $T \in [T_{\min}, C_T T_{\min}]$, where $T_{\min} = \Theta\left(C_{\mathrm{LS}} \ln\left(\frac{2K_\chi}{\varepsilon_\chi^2} \right) \right)$, results in a distribution p_T such that p_T is $\varepsilon_{\mathrm{TV}}$-far in TV distance from a distribution $\overline{p}_T$, where $\overline{p}_T$ satisfies $\chi^2(\overline{p}_T\|p) \leq \varepsilon_\chi^2$. In particular, taking $\varepsilon_\chi = \varepsilon_{\mathrm{TV}}$, we have the error guarantee that $\mathrm{TV}(p_T, p) \leq 2\varepsilon_{\mathrm{TV}}$.*

Note that the error bound is only achieved when running LMC for a moderate time; this is consistent with the fact that the stationary distribution of LMC with a L^2-score estimate can be arbitrarily far from p. Note also that we need a warm start in χ^2-divergence, as the required accuracy for the score estimate is inversely proportional to K_χ. Intuitively, we must suffer from such a dependence because if the starting distribution is very far away, then there is no guarantee that $\|\ln p(x_t) - s(x_t)\|^2$ is small on average during the sampling algorithm. Finally, although we can state a result purely in terms of TV distance, we need this more precise formulation to prove a result for annealed Langevin dynamics.

2.2 Annealed Langevin dynamics with estimated score

In light of the warm start requirement in Theorem 2.1, we typically cannot directly sample from p_{data} or its approximation. Hence, [SE19] proposed using annealed Langevin dynamics: consider a sequence of noise levels $\sigma_N > \cdots > \sigma_1 \approx 0$ giving rise to a sequence of distributions $p_{\sigma_N^2}, \ldots, p_{\sigma_1^2} \approx p_{\mathrm{data}}$, where $p_{\sigma^2} = p * \varphi_{\sigma^2}$, φ_{σ^2} being the density of $N(0, \sigma^2 I_d)$. For large enough σ_N, $\varphi_{\sigma_N^2} \approx p_{\sigma_N^2}$ provides a warm start to $p_{\sigma_N^2}$. We then successively run LMC using score estimates for $p_{\sigma_k^2}$, with the approximate sample for $p_{\sigma_k^2}$ giving a warm start for $p_{\sigma_{k-1}^2}$. We obtain the following algorithm and error estimate.

Algorithm 1 Annealed Langevin dynamics with estimated score [SE19]

    INPUT: Noise levels $0 \leq \sigma_1 < \ldots < \sigma_M$; score function estimates $s(\cdot, \sigma_m)$ (estimates of $\nabla \ln(p * \varphi_{\sigma_m^2})$), step sizes h_m, and number of steps N_m for $1 \leq m \leq M$.
    Draw $x^{(M+1)} \sim N(0, \sigma_M^2 I_d)$.
    for m from M to 1 **do**
        Starting from $x_0^{(m)} = x^{(m+1)}$, run (LMC-SE) with $s(x, \sigma_m)$ and step size h_m for N_m steps, and let the final sample be $x^{(m)}$.
    end for
    OUTPUT: Return $x^{(1)}$, approximate sample from $p * \varphi_{\sigma_1^2}$.

Theorem 2.2 (Annealed LMC with L^2-accurate score estimate). *Let $p : \mathbb{R}^d \to \mathbb{R}$ be a probability density satisfying Assumption 1, and let $p_{\sigma^2} := p * \varphi_{\sigma^2}$. Suppose furthermore that $\nabla \ln p_{\sigma^2}$ is L-Lipschitz for every $\sigma \geq 0$. Given $\sigma_{\min} > 0$, there exists a sequence $\sigma_{\min} = \sigma_1 < \cdots < \sigma_M$ with*

162   $M = O\left(\sqrt{d}\log\left(\frac{dC_{\mathrm{LS}}}{\sigma_{\min}^2}\right)\right)$ *such that for each* m, *if*

$$\left\|\nabla\ln(p_{\sigma_m^2}) - s(\cdot,\sigma_m^2)\right\|_{L^2(p_{\sigma_m^2})}^2 = \mathbb{E}_{p_{\sigma_m^2}}\left[\left\|\nabla\ln p_{\sigma_m^2}(x) - s(x,\sigma_m^2)\right\|^2\right] \le \varepsilon^2.$$

$$\text{with } \varepsilon := \widetilde{O}\left(\frac{\varepsilon_{\mathrm{TV}}^{4.5}}{d^{1.25}L^2 C_{\mathrm{LS}}^{2.5}}\right),$$

163   *then* $x^{(1)}$ *is a sample from a distribution* q *such that* $\mathrm{TV}(q, p_{\sigma_1^2}) \le \varepsilon_{\mathrm{TV}}$.

164 Note that we assume a score estimate with error ε at all noise scales; this corresponds to using an
165 objective function that is a maximum of the score-matching objective over all noise levels, rather
166 than an average over all noise levels as more commonly used in practice. However, these two losses
167 are at most a factor of M apart.

168 The additional dependence on d and $\varepsilon_{\mathrm{TV}}$ in Theorem 2.2 compared to Theorem 2.1 comes from
169 requiring a sequence of $\widetilde{O}(\sqrt{d})$ noise levels and an additional factor in χ^2-divergence we suffer
170 at the beginning of each level m. In the next section, we will find that using a reverse SDE to
171 evolve the samples between the noise levels—called a *corrector* step—will improve the rate and
172 time complexity.

3   Results for reverse SDE's with estimated score

174 To improve the empirical performance of score-based generative modeling, [Son+20b] consider a
175 general framework where noise is injected into a data distribution p_{data} via a forward SDE,

$$d\tilde{x}_t = f(\tilde{x}_t, t)\,dt + g(t)\,dw_t,\ \ t \in [0, T],$$

176 where $\widetilde{x}_0 \sim \widetilde{p}_0 := p_{\mathrm{data}}$. Let $\widetilde{p}_t$ denote the distribution of $\widetilde{x}_t$ ($\widetilde{p}_t$ is used instead of p_t to distin-
177 guish with the Gaussian-convolved distribution used in Annealed Langevin dynamics as in §2.2).
178 Remarkably, $\widetilde{x}_t$ also satisfies a reverse-time SDE,

$$d\tilde{x}_t = [f(\tilde{x}_t, t) - g(t)^2 \nabla\ln\tilde{p}_t(\tilde{x}_t)]dt + g(t)\,d\tilde{w}_t,\ t \in [0, T], \tag{2}$$

179 where $\tilde{w}_t$ is a backward Brownian Motion [And82]. By carefully choosing f and g, we can expect
180 that $\tilde{p}_T$ is approximately equal to some prior distribution $\tilde{q}_T$ (e.g., a centered Gaussian) which we
181 can accurately sample from. Then we hope that starting with some $\tilde{y}_T \sim p_{\mathrm{prior}} = \tilde{q}_T \approx \tilde{p}_T$ and
182 running the reverse-time process, we will get a good sample $\tilde{y}_0 \sim \tilde{q}_0 \approx p_{\mathrm{data}}$.

183 The case where $f \equiv 0$ and $g \equiv 1$ recovers the simple case of convolving with a Gaussian as used
184 in §2.2; note, however that the reverse-time SDE differs from Langevin diffusion in having a larger
185 (and time-varying) drift relative to the diffusion. [Son+20b] highlight the following two special
186 cases. We will focus on DDPM while noting that our analysis applies more generically.

187 SMLD **Score-matching Langevin diffusion**: $f \equiv 0$. In this case, $\widetilde{p}_t = \widetilde{p}_0 * \varphi_{\int_0^t g(s)^2\,ds}$, so
188   [Son+20b] call this a variance-exploding (VE) SDE. As is common for annealing-based
189   algorithms, [SE19; Son+20b] suggest choosing an exponential schedule, so that $g(t) = ab^t$
190   for constants a, b. We take $p_{\mathrm{prior}} = N(0, \int_0^T g(s)^2\,ds \cdot I_d)$.

191 DDPM **Denoising diffusion probabilistic modeling**: $f(x, t) = -\frac{1}{2}g(t)^2 x$. This is an Ornstein-
192   Uhlenbeck process with time rescaling, $\widetilde{p}_t = M_{-\frac{1}{2}\int_0^t g(s)^2\,ds\sharp}\widetilde{p}_0 * \varphi_{1 - e^{-\int_0^t g(s)^2\,ds}}$, where
193       $M_\alpha(x) = \alpha x$. [Son+20b] call this a variance-preserving (VP) SDE, as the variance con-
194   verges towards I_d. Because it displays exponential convergence towards $N(0, I_d)$, it can
195   be run for a smaller amount of normalized time $\int_0^t g(s)^2\,ds$. [Son+20b] suggest the choice
196       $g(t) = \sqrt{b + \alpha t}$. We take $p_{\mathrm{prior}} = N(0, (1 - e^{-\int_0^t g(s)\,ds})I_d) \approx N(0, I_d)$.

197 To obtain an algorithm, we consider the following discretization and approximation of (2); note
198 that in all cases of interest the integrals can be analytically evaluated. We reverse time so that t
199 corresponds to $T - t$ of the forward process. As we are free to rescale time in the SDE, we assume

without loss of generality that the step sizes are constant. The predictor step is

$$z_{(k+1)h} = z_{kh} - \int_{kh}^{(k+1)h} \left[f(z_{kh}, T-t) - g(T-t)^2 \cdot s(z_{kh}, T-kh) \right] dt$$

$$+ \int_{kh}^{(k+1)h} g(T-t) \, dw_t, \quad \text{(P)}$$

where $\int_{kh}^{(k+1)h} g(T-t) \, dw_t$ is distributed as $N(0, \int_{kh}^{(k+1)h} g(T-t)^2 \, dt \cdot I_d)$. Following [Son+20b], we call these predictor steps as the samples aim to track the distributions $\widetilde{p}_{T-kh}$. (Note that we flip the time) For simplicity of presentation, we consider the case $g \equiv 1$, and omit the (polynomial) dependence on L.

Theorem 3.1 (Predictor with L^2-accurate score estimate, DDPM). *Let $p_{\text{data}} : \mathbb{R}^d \to \mathbb{R}$ be a probability density satisfying Assumption 1, and let $\widetilde{p}_t$ be the distribution resulting from evolving the forward SDE according to DDPM with $g \equiv 1$. Suppose furthermore that $\nabla \ln \widetilde{p}_t$ is L-Lipschitz for every $t \geq 0$, and that each $s(\cdot, t)$ satisfies Assumption 2. Then if*

$$\varepsilon = O\left(\frac{\varepsilon_{\text{TV}}^4}{(C_{\text{LS}}^2 + d)C_{\text{LS}}^{5/2}(\ln(C_{\text{LS}}d) \wedge C_{\text{LS}} \ln(1/\varepsilon_{\text{TV}}^2))} \right),$$

running (P) *starting from p_{prior} for time $T = \Theta\left(\ln(C_{\text{LS}}d) \vee C_{\text{LS}} \log\left(\frac{1}{\varepsilon_{\text{TV}}}\right) \right)$ and step size $h = \Theta\left(\frac{\varepsilon_\chi^2}{C_{\text{LS}}(C_{\text{LS}}^2 + d)} \right)$ results in a distribution q_T so that $\text{TV}(q_T, p_{\text{data}}) \leq \varepsilon_{\text{TV}}$. Here, the $O(\cdot)$ omits polynomial dependence on L and L_s.*

A more precise statement of the Theorem can be found in the Appendix. Although we state our theorem for DDPM, we describe in Appendix how it can be adapted to other SDE's like SMLD and the sub-VP SDE; the primary SDE-dependent bound we need is a bound on $\nabla \ln \frac{\widetilde{p}_t}{\widetilde{p}_{t+h}}$. Because the predictor is tracking a changing distribution p_t, we incur more error terms and worse dependence on parameters (C_{LS}, L) than in LMC (Theorem 2.1). Motivated by this, by interspersing the predictor steps with LMC steps—called *corrector* steps in this context—we give additional time for the process to mix, resulting in improved dependence on parameters.

Algorithm 2 Predictor-corrector method with estimated score [Son+20b]

INPUT: Time T, predictor step size h; number of corrector steps N per predictor step, corrector step sizes h_m

Draw $z_0 \sim p_{\text{prior}}$ from the prior distribution.

for m from 1 to T/h **do**

    (Predictor) Take a step of (P) to obtain z_{mh} from $z_{(m-1)h}$, with f, g as in SMLD or DDPM.

    (Corrector) Starting from $z_{mh,0} := z_{mh}$, run (LMC-SE) with $s(z, T - mh)$ and step size h_m for N steps, and let $z_{mh} \leftarrow z_{mh,N}$.

end for

OUTPUT: Return z_T, approximate sample from p_{data}.

Theorem 3.2 (Predictor-corrector with L^2-accurate score estimate). *Keep the setup of Theorem 3.1. Then for $\varepsilon_{\text{TV}} = O\left(\sqrt{\frac{d}{(C_{\text{LS}}^2 + d)\text{poly}(L)}} \right)$, if*

$$\varepsilon = O\left(\frac{\varepsilon_{\text{TV}}^4}{dL^2 C_{\text{LS}}^{5/2} \ln(1/\varepsilon_\chi^2)} \right), \quad (3)$$

then Algorithm 2 with appropriate choices of $T = \Theta\left(\ln(C_{\text{LS}}d) \vee C_{\text{LS}} \log\left(\frac{1}{\varepsilon_{\text{TV}}}\right) \right)$, N, corrector step sizes h_m and predictor step size h, produces a sample from a distribution q_T such that $\text{TV}(q_T, p_{\text{data}}) < \varepsilon_{\text{TV}}$.

The assumption on ε_{TV} is for convenience in stating our bound. In comparison to using the predictor step alone (Theorem 3.1), note that in the bound on ε, we obtain the improved rate of the corrector

step as in Theorem 2.1; this is because the additional error terms from the predictor step are exponentially damped by the corrector step and no longer dominating. In comparison to the Annealed Langevin sampler (Algorithm 1, Theorem 2.2), which can be viewed as using the corrector step alone, adding a predictor step provides a better warm start for the distribution at the next smaller noise level, resulting in better dependence on parameters. Thus the predictor-corrector algorithm combines the strengths of the predictor and corrector steps.

4 Theoretical framework and proof sketches

The main idea of our analysis framework is to convert a L^2 error guarantee to a L^∞ error guarantee by excluding a bad set, formalized in the following theorem.

Theorem 4.1. *Suppose $X_n \sim p_n$, $Z_n \sim q_n$, and $\overline{Z}_n \sim \overline{q}_n$ are $\mathcal{F}_n$-adapted random processes taking values in Ω, and $B_n \subseteq \Omega$ are sets such that the following hold for every $n \in \mathbb{N}_0$.*

1. If $X_k \in B_k^c$ for all $0 \le k \le n - 1$, then $Z_n = \overline{Z}_n$.

2. $\chi^2(\overline{q}_n || p_n) \le D_n^2$.

3. $\mathbb{P}(X_n \in B_n) \le \delta_n$.

Then the following hold.

$$\mathrm{TV}(q_n, \overline{q}_n) \le \sum_{k=0}^{n-1} (D_k^2 + 1)^{1/2} \delta_k^{1/2} \qquad \mathrm{TV}(p_n, q_n) \le D_n + \sum_{k=0}^{n-1} (D_k^2 + 1)^{1/2} \delta_k^{1/2} \qquad (4)$$

For our setting, we will take the "bad sets" B_n to be the set of x where $\|s_\theta(x) - \nabla \ln p\|$ is large, q_n to the be discretized process with estimated score, and $\overline{q}_n$ to the be discretized process with estimated score except in B_n where the error is large. Because $\overline{q}_n$ uses an L^∞-accurate score estimate, we can use existing techniques for analyzing Langevin Monte Carlo [VW19; EHZ21; Che+21] to bound $\chi^2(\overline{q}_n || p_n)$.

Proof. We bound using condition 1 and Cauchy-Schwarz:

$$\mathbb{P}\left(Z_n \neq \overline{Z}_n\right) \le \mathbb{P}\left(\bigcup_{k=1}^{n-1} \{X_k \in B_k\}\right) \le \sum_{k=0}^{n-1} \mathbb{P}(X_k \in B_k) = \sum_{k=0}^{n-1} \mathbb{E}_{q_k} \mathbb{1}_{B_k}$$

$$\le \left(\mathbb{E}_{p_k} \left(\frac{q_k}{p_k}\right)^2\right)^{1/2} (\mathbb{E}_{p_k} \mathbb{1}_{B_k})^{1/2} = \sum_{k=0}^{n-1} (D_k^2 + 1)^{1/2} \delta_k^{1/2}.$$

The second inequality then follows from the triangle inequality and Cauchy-Schwarz:

$$\mathrm{TV}(p_n, q_n) \le \mathrm{TV}(p_n, \overline{q}_n) + \mathrm{TV}(\overline{q}_n, q_n)$$

$$\le \sqrt{\chi^2(\overline{q}_n || p_n)} + \mathrm{TV}(\overline{q}_n, q_n) \le D_n + \sum_{k=0}^{n-1} (D_k^2 + 1)^{1/2} \delta_k^{1/2}. \qquad \square$$

It now remains to give χ^2 convergence bounds under L^∞-accurate score estimate. The following theorem may be of independent interest.

Theorem 4.2 (LMC under L^∞ bound on gradient error). *Let $p : \mathbb{R}^d \to \mathbb{R}$ be a probability density satisfying Assumption 1(1, 2) and $s : \mathbb{R}^d \to \mathbb{R}^d$ be a score estimate s with error bounded in L^∞: for some $\varepsilon_1 \le \sqrt{\frac{1}{48C_{\mathrm{LS}}}}$,*

$$\|\nabla \ln p - s\|_\infty = \max_{x \in \mathbb{R}^d} \|\nabla \ln p(x) - s(x)\|] \le \varepsilon_1.$$

Let $N \in \mathbb{N}_0$ and $0 < h \le \frac{1}{4392 d C_{\mathrm{LS}} L^2}$, and assume $L \ge 1$. Let q_{nh} denote the nth iterate of LMC with step size h score estimate s. Then

$$\chi^2(q_{(k+1)h} || p) \le \exp\left(-\frac{h}{4C_{\mathrm{LS}}}\right) \chi^2(q_{kh} || p) + 170 d L^2 h^2 + 5\varepsilon_1^2 h$$

and

$$\chi^2(q_{Nh}||p) \leq \exp\left(-\frac{Nh}{4C_{\mathrm{LS}}}\right)\chi^2(q_0||p) + 680dL^2hC_{\mathrm{LS}} + 20\varepsilon_1^2 C_{\mathrm{LS}} \leq \exp\left(-\frac{Nh}{4C_{\mathrm{LS}}}\right)\chi^2(q_0||p) + 1$$

Following [Che+21], we prove this by first defining a continuous-time interpolation q_t of the discrete process, and then deriving a differential inequality for $\chi^2(q_t||p)$ using the log-Sobolev inequality for p. Compared to [Che+21], we incur an extra error term arising from the inaccurate gradient.

This allows us to sketch the proof of Theorem 2.1; a complete proof is in Section B.

Proof sketch of Theorem 2.1. We first define the bad set where the error in the score estimate is large,

$$B := \{\|\nabla \ln p(x) - s(x)\| > \varepsilon_1\}$$

for some ε_1 to be chosen. Then by Chebyshev's inequality, $P(B) \leq \left(\frac{\varepsilon}{\varepsilon_1}\right)^2 =: \delta$. Let $\overline{q}_{nh}$ be the discretized process, but where the score estimate is set to be equal to $\nabla \ln p$ on B; note it agrees with q_{nh} as long as if has not hit B. Because $\overline{q}_{nh}$ uses a score estimate that has L^∞-error ε_1, Theorem 4.2 gives a bound for $\chi^2(\overline{q}_{Nh}||p)$. Then Theorem 4.1 gives

$$\mathrm{TV}(q_{nh}, \overline{q}_{nh}) \leq \sum_{k=0}^{n-1}(1 + \chi^2(\overline{q}_{kh}||p))^{1/2}P(B)^{1/2} \leq \left(\sum_{k=0}^{n-1}\exp\left(-\frac{kh}{8C_{\mathrm{LS}}}\right)\chi^2(q_0||p)^{1/2} + 1\right)\delta^{1/2}$$

The theorem then follows from choosing parameters so that $\chi^2(\overline{q}_T||p) \leq \varepsilon_\chi^2$ and $\mathrm{TV}(q_T, \overline{q}_T) \leq \varepsilon_{\mathrm{TV}}$. □

We remark that the main inefficiency in the proof comes from the use of Chebyshev's inequality, and a L^p bound on the error for $p > 2$ will improve the bound.

Proof sketch of Theorem 2.2. Choosing the sequence $\sigma_1 < \cdots < \sigma_M$ to be geometric with ratio $1 + \frac{1}{d}$ ensures that the χ^2-divergence between successive distributions $p_{\sigma_m^2}$ is $O(1)$. Then, choosing $\sigma_M^2 = \Omega(C_{\mathrm{LS}}d)$ ensures we have a warm start for the highest noise level: $\chi^2(p_{\mathrm{prior}}||p_{\sigma_M^2}) = O(1)$. This uses $O\left(\sqrt{d}\log\left(\frac{dC_{\mathrm{LS}}}{\sigma_{\min}^2}\right)\right)$ noise levels. Chebyshev's inequality can be used to show that the distribution of the final sample $x^{(m)}$ for $p_{\sigma_m^2}$ is $O(\varepsilon_{\mathrm{TV}}/M)$ close to a distribution that is $O(M/\varepsilon_{\mathrm{TV}})$ in χ^2-divergence from $p_{\sigma_{m+1}^2}$. This gives the warm start parameter $K_\chi = (M/\varepsilon_{\mathrm{TV}})^{1/2}$; substituting into Theorem 2.1 then gives the required bound for ε. Note that the TV errors accrued from each level add to $O(\varepsilon_{\mathrm{TV}})$. □

To analyze the corrector-based algorithms, we also first prove convergence bounds under L^∞-accurate score estimate.

Theorem 4.3 (Predictor steps under L^∞ bound on score estimate, DDPM). *Let $p : \mathbb{R}^d \to \mathbb{R}$ be a probability density satisfying Assumption 1 and $s(\cdot, t) : \mathbb{R}^d \to \mathbb{R}^d$ be a score estimate s with error bounded in L^∞ for each $t \in [0, T]$:*

$$\|\nabla \ln p - s(\cdot, t)\|_\infty = \max_{x \in \mathbb{R}^d}\|\nabla \ln \widetilde{p}_t(x) - s(x, t)\|\| \leq \varepsilon_1.$$

Consider DDPM with $g \equiv 1$, $T \geq 1 \vee \ln(C_{\mathrm{LS}}d)$, and $h = O\left(\frac{1}{C_{\mathrm{LS}}(C_{\mathrm{LS}}^2+d)}\right)$. Then

$$\chi^2(q_{(k+1)h}||p_{(k+1)h}) \leq \chi^2(q_{kh}||p_{kh})e^{-\frac{1}{8C_{\mathrm{LS}}}+8\varepsilon_1^2} + O(\varepsilon_1^2 h + (C_{\mathrm{LS}}^2 + d)h^2)$$

and if $\varepsilon_1 < \frac{1}{128C_{\mathrm{LS}}}$,

$$\chi^2(q_{Nh}||p_{Nh}) \leq e^{-\frac{Nh}{16C_{\mathrm{LS}}}}\chi^2(q_0||p_0) + O\left(C_{\mathrm{LS}}\left(\varepsilon_1^2 + (C_{\mathrm{LS}}^2 + d)h\right)\right),$$

where the $O(\cdot)$ omits polynomial dependence on L, L_s. Moreover, for $q_0 = p_{\mathrm{prior}}$, $\chi^2(q_0||p_0) \leq e^{-T/2}C_{\mathrm{LS}}d$.

We give a more precise statement in Section C. Note that unlike the case for LMC as in Theorem 4.2, the base density p_t is also evolving in time; this produces additional error terms and necessitates a more involved analysis, giving extra factors of L, L_s, C_{LS}. The additional error terms can be bounded using the Donsker-Varadhan variational principle, concentration for distributions satisfying LSI, and error bounds between p_t and p_{t+h} for small h.

Here, we only state the result about DDPM, which has better bounds than SMLD because both the forward and backwards processes exhibit better mixing properties: the warm start improves exponentially rather than inversely with T, and the log-Sobolev constant is uniformly bounded by that of p_{data} rather than increasing. However, the analysis in Section C can be directly applied to SMLD and other models as well.

Note that the choice of h is necessary for exponential decay of error; as if h is not small enough, we would get an exponential growing instead of decaying factor in the one-step error (See Section C for details). Such an h may however still be a suitable choice when used in conjunction with a corrector step. Moreover, as $\varepsilon_1 \to 0$, with appropriate choice of T and h, q_{Nh} and p_{Nh} can be made arbitrarily close.

Theorem 3.1 now follows from the L^∞ result (Theorem 4.3) in the same way that Theorem 2.1 follows from Theorem 4.2. To prove Theorem 3.2, we bound the χ^2-divergence of the iterates by interleaving the one-step χ^2 inequalities in Theorems 4.2 and 4.3 and choosing N, h, h_m appropriately.

5 Conclusion

We introduced a general framework to analyze SDE-based sampling algorithms given a L^2-error score estimate, and used it to obtain the first convergence bounds for several score-based generative models with polynomial complexity in all parameters. Our analysis can potentially be adapted to other SDE's and sampling algorithms beyond Langevin Monte Carlo. There is also room for improving our analysis to better use smoothing properties of the SDE's and compare different choices of the diffusion speed g.

We present several interesting further directions to explore. In addition to extending the analysis to other SGM's and comparing their theoretical performance (relative to each other as well as other approaches to generative modeling), we propose the following.

Analysis for multimodal distributions. Our assumption of a bounded log-Sobolev constant essentially limits the analysis to distributions that are close to unimodal. However, SGM's are empirically successful at modeling multimodal distributions [SE19], and in fact perform better with multimodal distributions than other approaches such as GAN's. Can we analyze the convergence for simple multimodal distributions, such as a mixture of distributions each with bounded log-Sobolev constant? Positive results on sampling from multimodal distributions such as [GLR18] suggest this is possible, as the sequence of noised distributions is natural for annealing and tempering methods (see [GLR18, Remark 7.2]).

Weakening conditions on the score estimate. The assumption that we have a score estimate that is $O(1)$-accurate in L^2, although weaker than the usual assumptions for theoretical analysis, is in fact still a strong condition in practice that seems unlikely to be satisfied (and difficult to check) when learning complex distributions such as distributions of images. What would a reasonable weaker condition be, and in what sense can we still obtain reasonable samples?

Guarantees for learning the score function. Our analysis assumes a L^2-estimate of the score function is given, but the question remains of when we can find such an estimate. What natural conditions on distributions allow their score functions to be learned by a neural network? Various works have considered the representability of data distributions by diffusion-like processes [TR19], but the questions of optimization and generalization appear more challenging.

References

[ACB17]   Martin Arjovsky, Soumith Chintala, and Léon Bottou. "Wasserstein generative adversarial networks". In: *International conference on machine learning*. PMLR. 2017, pp. 214–223.

[And82]   Brian DO Anderson. "Reverse-time diffusion equation models". In: *Stochastic Processes and their Applications* 12.3 (1982), pp. 313–326.

[BGL13]   Dominique Bakry, Ivan Gentil, and Michel Ledoux. *Analysis and geometry of Markov diffusion operators*. Vol. 348. Springer Science & Business Media, 2013.

[BMR20]   Adam Block, Youssef Mroueh, and Alexander Rakhlin. "Generative modeling with denoising auto-encoders and Langevin sampling". In: *arXiv preprint arXiv:2002.00107* (2020).

[CB18]   Xiang Cheng and Peter Bartlett. "Convergence of Langevin MCMC in KL-divergence". In: *Algorithmic Learning Theory*. PMLR. 2018, pp. 186–211.

[Cha04]   Djalil Chafaï. "Entropies, convexity, and functional inequalities, On Φ-entropies and Φ-Sobolev inequalities". In: *Journal of Mathematics of Kyoto University* 44.2 (2004), pp. 325–363.

[Che+18]   Xiang Cheng, Niladri S Chatterji, Peter L Bartlett, and Michael I Jordan. "Underdamped Langevin MCMC: A non-asymptotic analysis". In: *Conference on learning theory*. PMLR. 2018, pp. 300–323.

[Che+21]   Sinho Chewi, Murat A Erdogdu, Mufan Bill Li, Ruoqi Shen, and Matthew Zhang. "Analysis of Langevin Monte Carlo from Poincaré to Log-Sobolev". In: *arXiv preprint arXiv:2112.12662* (2021).

[Dal17]   Arnak S Dalalyan. "Theoretical guarantees for approximate sampling from smooth and log-concave densities". In: *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* 79.3 (2017), pp. 651–676.

[Dat+19]   Sumanth Dathathri, Andrea Madotto, Janice Lan, Jane Hung, Eric Frank, Piero Molino, Jason Yosinski, and Rosanne Liu. "Plug and play language models: A simple approach to controlled text generation". In: *arXiv preprint arXiv:1912.02164* (2019).

[De +21]   Valentin De Bortoli, James Thornton, Jeremy Heng, and Arnaud Doucet. "Diffusion Schrödinger bridge with applications to score-based generative modeling". In: *Advances in Neural Information Processing Systems* 34 (2021).

[DK19]   Arnak S Dalalyan and Avetik Karagulyan. "User-friendly guarantees for the Langevin Monte Carlo with inaccurate gradient". In: *Stochastic Processes and their Applications* 129.12 (2019), pp. 5278–5311.

[DM17]   Alain Durmus and Eric Moulines. "Nonasymptotic convergence analysis for the unadjusted Langevin algorithm". In: *The Annals of Applied Probability* 27.3 (2017), pp. 1551–1587.

[DN21]   Prafulla Dhariwal and Alexander Nichol. "Diffusion models beat gans on image synthesis". In: *Advances in Neural Information Processing Systems* 34 (2021).

[DSB16]   Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. "Density estimation using real nvp". In: *arXiv preprint arXiv:1605.08803* (2016).

[DVK21]   Tim Dockhorn, Arash Vahdat, and Karsten Kreis. "Score-Based Generative Modeling with Critically-Damped Langevin Diffusion". In: *arXiv preprint arXiv:2112.07068* (2021).

[EHZ21]   Murat A. Erdogdu, Rasa Hosseinzadeh, and Matthew S. Zhang. "Convergence of Langevin Monte Carlo in Chi-Squared and Renyi Divergence". In: *arXiv preprint arXiv:2007.11612* (2021).

[GLR18]   Rong Ge, Holden Lee, and Andrej Risteski. "Beyond log-concavity: provable guarantees for sampling multi-modal distributions using simulated tempering langevin monte carlo". In: *Proceedings of the 32nd International Conference on Neural Information Processing Systems*. 2018, pp. 7858–7867.

[Goo+14]   Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. "Generative adversarial nets". In: *Advances in neural information processing systems* 27 (2014).

[Gra+19] Will Grathwohl, Kuan-Chieh Wang, Jörn-Henrik Jacobsen, David Duvenaud, Moham-mad Norouzi, and Kevin Swersky. "Your classifier is secretly an energy based model and you should treat it like one". In: *arXiv preprint arXiv:1912.03263* (2019).

[HJA20] Jonathan Ho, Ajay Jain, and Pieter Abbeel. "Denoising diffusion probabilistic models". In: *Advances in Neural Information Processing Systems* 33 (2020), pp. 6840–6851.

[Jin+22] Bowen Jing, Gabriele Corso, Renato Berlinghieri, and Tommi Jaakkola. "Subspace Diffusion Generative Models". In: *arXiv preprint arXiv:2205.01490* (2022).

[KW19] Diederik P Kingma and Max Welling. "An introduction to variational autoencoders". In: *arXiv preprint arXiv:1906.02691* (2019).

[Men+21] Chenlin Meng, Yutong He, Yang Song, Jiaming Song, Jiajun Wu, Jun-Yan Zhu, and Stefano Ermon. "SDEdit: Guided image synthesis and editing with stochastic differen-tial equations". In: *International Conference on Learning Representations*. 2021.

[MMS20] Mateusz B Majka, Aleksandar Mijatović, and Łukasz Szpruch. "Nonasymptotic bounds for sampling algorithms without log-concavity". In: *The Annals of Applied Probability* 30.4 (2020), pp. 1534–1581.

[SE19] Yang Song and Stefano Ermon. "Generative Modeling by Estimating Gradients of the Data Distribution". In: *Proceedings of the 33rd Annual Conference on Neural Infor-mation Processing Systems*. 2019.

[SE20] Yang Song and Stefano Ermon. "Improved techniques for training score-based gener-ative models". In: *arXiv preprint arXiv:2006.09011* (2020).

[Soh+15] Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. "Deep unsupervised learning using nonequilibrium thermodynamics". In: *International Con-ference on Machine Learning*. PMLR. 2015, pp. 2256–2265.

[Son+20a] Yang Song, Sahaj Garg, Jiaxin Shi, and Stefano Ermon. "Sliced score matching: A scalable approach to density and score estimation". In: *Uncertainty in Artificial Intel-ligence*. PMLR. 2020, pp. 574–584.

[Son+20b] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Er-mon, and Ben Poole. "Score-Based Generative Modeling through Stochastic Differen-tial Equations". In: *International Conference on Learning Representations*. 2020.

[Son+21a] Yang Song, Conor Durkan, Iain Murray, and Stefano Ermon. "Maximum likelihood training of score-based diffusion models". In: *Advances in Neural Information Pro-cessing Systems* 34 (2021).

[Son+21b] Yang Song, Liyue Shen, Lei Xing, and Stefano Ermon. "Solving Inverse Prob-lems in Medical Imaging with Score-Based Generative Models". In: *arXiv preprint arXiv:2111.08005* (2021).

[TR19] Belinda Tzen and Maxim Raginsky. "Theoretical guarantees for sampling and infer-ence in generative models with latent diffusions". In: *Conference on Learning Theory*. PMLR. 2019, pp. 3084–3114.

[VW19] Santosh Vempala and Andre Wibisono. "Rapid convergence of the unadjusted langevin algorithm: Isoperimetry suffices". In: *Advances in neural information processing sys-tems* 32 (2019), pp. 8094–8106.

[ZML16] Junbo Zhao, Michael Mathieu, and Yann LeCun. "Energy-based generative adversarial network". In: *arXiv preprint arXiv:1609.03126* (2016).