Flow Chemistry as a Platform for Experimental Multi-objective Optimization of Heterogeneous Polymer Synthesis

Nicholas J. Warren

School of Chemical, Materials and Biological Engineering, University of Sheffield, Sir Robert Hadfield Building, Mappin Street, Sheffield, UK

Correspondence to: nicholas.warren@sheffield.ac.uk

Introduction

The traditional discovery of functional polymers has long been hindered by the vastness of chemical parameter space and the labor-intensive nature of Edisonian experimentation. Within the wider chemical synthesis community, automated reactors underpinned by AI-directed optimization frameworks have been shown to autonomously navigate multi-dimensional reaction spaces to achieve multi-objective goals. These so-called "self-driving laboratories" come in a variety of formats, ranging from static or mobile robots, gantry-based liquid handlers through to (micro)fluidic reactor platforms. [1-5] The latter technology typically uses automated liquid handling to control the flow of material through a temperature-controlled reactor geometry (normally a tube). The ability to easily automate these systems has resulted in a wide array of microfluidic self-driving labs for small-molecule chemistry and nanomaterials synthesis.[4, 6-8]

In polymer chemistry, flow has been used for anionic, free-radical and reversible deactivation radical polymerization.[9] Furthermore, the integration of online analytics has gradually evolved towards the ability to rapidly screen polymerisation parameter space;[10] conduct self-optimization campaigns to target molecular weights,[11] predefined monomer conversion[12] or conduct multi-objective Bayesian optimization.[13] Herein, we describe our work which has realised the ability to conduct self-optimization of heterogeneous polymerisation.

Self-driving polymerization platforms

Many industrially and academically important polymerization systems rely on the reaction occurring in a heterogeneous environment, which can be much more difficult to transfer into flow reactors. Our initial work focussed on transferring Reversible addition fragmentation chain transfer polymerization (RAFT) mediated Polymerization-Induced Self-Assembly (PISA) into flow. PISA involves the synthesis of an amphiphilic block copolymer which undergoes in-situ self-assembly to form well-defined nanoparticles. We first demonstrated this in flow for the polymerization of diacetone acrylamide in the presence of a polydimethylacrylamide precursor polymer using a rudimentary system comprising a pump and stainless-steel reactor. This was effectively used to synthesise nanoparticle dispersions but fouling of the stainless steel meant prolonged operation was not possible. [14] This was mitigated by moving to perfluoroalkane (PFA) tubing and using faster chemistry (using a more reactive initiator) which sped the reaction up to the extent full conversion could be achieved in 10 minutes (down from ~1h).[15] This "ultrafast" PISA process presented a model system for developing and evaluating a suite of online monitoring techniques suited to heterogeneous systems. Benchtop NMR was used to monitor conversion of this process in real-time, with subtle rate changes being discerned in the high-resolution data[16].

Figure 1. Overview of the RAFT-PISA for formation of nanoparticles, and the SDL integrating a flow reactor and online GPC, [1]H NMR spectroscopy and DLS. Reproduced from Knox et al, Polym. Chem., 2025,16, 1355-1364.[18]

Through the development of an in-line light scattering instrument in tandem with benchtop flow-NMR it was also possible to target particle size for a PISA process.[17]

Importantly, several of these established techniques, alongside our self-optimization workflow for RAFT solution polymerization[13]

provided the foundation for the evolution of a Self-driving lab for conducting PISA. The know-how developed facilitated the development of SDL for monitoring all critical parameters which determine the quality of the polymer nanomaterials produced via PISA.[18] This comprised a two-pump flow-reactor which led to a switching valve which extracted sample for online gel permeation chromatography (GPC; for molecular weight distribution determination), then directly through a benchtop NMR spectrometer (for conversion determination) and then via a second switching valve which extracted sample for dynamic light scattering (DLS; nanoparticle size and polydispersity determination).

Figure 2: Comparison of the three optimization algorithms selected for this work in targeting 80 nm particles (a) TSEMO, (b) RBFNN/RVEA and (c) EA-MOPSO. Reproduced from Knox et al, Polym. Chem., 2025,16, 1355-1364.[18]

This configuration allowed for the efficient navigation of a complex, multi-dimensional parameter space. Initially, this was exemplified through a full factorial 64 experiment screen which facilitated the ability to map the reaction parameter space in order to evaluate three optimization approaches with a view to achieving a series of optimization goals targeting: (1) maximum monomer conversion (2) minimum molar mass dispersity (3) targeting 80 nm nanoparticles (4) minimising particle polydispersity.

Initially, the mapped space was used as a model to evaluate the algorithms *in silico* including Thompson sampling efficient multi-objective optimization (TSEMO), radial basis function neural network/reference vector evolutionary algorithm (RBFNN/RVEA) and multi objective particle swarm optimization, hybridised with an evolutionary algorithm (EA-MOPSO). These were then effectively evaluated directly on the platform via a cloud-based framework to elucidate a series of Pareto-optimal samples. Whilst minimal difference in performance was

observed it was noted that each algorithm tended to explore different regions of the parameter space.

Figure 3: Outline of the autonomous flow reactor platform for conventional free-radical emulsion polymerization. Reproduced from Pittaway et al, Chem. Eng. J. 2025, 507, 160700.[19]

In our second-generation platform, a similar methodology was applied to free-radical emulsion polymerization of styrene.[19] In this case a different platform was developed to target a particle size, whilst minimising the concentration of key components (surfactant and seed-particles). Again, an *in silico* methodology was used to evaluate an adapted TSEMO optimization method which consecutively maximised and minimised particle size. This enabled a mapping of achievable particle sizes within a defined parameter space. This process was then executed on the physical platform providing a real insight into the feasible outcomes.

Figure 4: Fig. 9. *In silico* (left) and experimental (right) particle size mapping optimization campaigns to screen particle size. From Pittaway et al, Chem. Eng. J. 2025, 507, 160700.[19]

It is clear from this activity, that SDLs present an exciting opportunity in polymer chemistry. This is particularly relevant in a time where there is a critical need for sustainable, high-performing and affordable polymers.

Acknowledgments
The Engineering and Physical Sciences Research Council are thanked for funding this work through EPSRC grants EP/S000380/1 and EP/V0055089/2.

References
(1) Darvish, K.; Skreta, M.; Zhao, Y.; Yoshikawa, N.; Som, S.; Bogdanovic, M.; Cao, Y.; Hao, H.; Xu, H.; Aspuru-Guzik, A.; et al. ORGANA: A robotic assistant for automated chemistry experimentation and characterization. Matter 2025, 8

(2) Burger, B.; Maffettone, P. M.; Gusev, V. V.; Aitchison, C. M.; Bai, Y.; Wang, X.; Li, X.; Alston, B. M.; Li, B.; Clowes, R.; et al. A mobile robotic chemist. Nature 2020, 583 (7815), 237-241.

(3) Lo, S.; Baird, S. G.; Schrier, J.; Blaiszik, B.; Carson, N.; Foster, I.; Aguilar-Granda, A.; Kalinin, S. V.; Maruyama, B.; Politi, M.; et al. Review of low-cost self-driving laboratories in chemistry and materials science: the "frugal twin" concept. Digital Discovery 2024, 3 (5), 842-868,

(4) Mukhin, N.; Jha, P.; Abolhasani, M. The role of flow chemistry in self-driving labs. Matter 2025, 8 (7), 102205.

(5) Abolhasani, M.; Kumacheva, E. The rise of self-driving labs in chemical and materials sciences. Nature Synthesis 2023, 2 (6), 483-492.

(6) Wu, T.; Kheiri, S.; Hickman, R. J.; Tao, H.; Wu, T. C.; Yang, Z.-B.; Ge, X.; Zhang, W.; Abolhasani, M.; Liu, K.; et al. Self-driving lab for the photochemical synthesis of plasmonic nanoparticles with targeted structural and optical properties. Nature Communications 2025, 16 (1), 1473.

(7) Slattery, A.; Wen, Z.; Tenblad, P.; Sanjosé-Orduna, J.; Pintossi, D.; den Hartog, T.; Noël, T. Automated self-optimization, intensification, and scale-up of photocatalysis in flow. Science 2024, 383 (6681), eadj1817.

(8) Schweidtmann, A. M.; Clayton, A. D.; Holmes, N.; Bradford, E.; Bourne, R. A.; Lapkin, A. A. Machine learning meets continuous flow chemistry: Automated optimization towards the Pareto front of multiple objectives. Chemical Engineering Journal 2018, 352, 277-282.

(9) Reis, M. H.; Leibfarth, F. A.; Pitet, L. M. Polymerizations in Continuous Flow: Recent Advances in the Synthesis of Diverse Polymeric Materials. ACS Macro Letters 2020, 9 (1), 123-133.

(10) Zhang, B.; Mathoor, A.; Junkers, T. High Throughput Multidimensional Kinetic Screening in Continuous Flow Reactors. Angewandte Chemie International Edition 2023, 62 (38), e202308838.

(11) Rubens, M.; Vrijsen, J. H.; Laun, J.; Junkers, T. Precise Polymer Synthesis by Autonomous Self-Optimizing Flow Reactors. Angew Chem Int Ed Engl 2019, 58 (10), 3183-3187. DOI: 10.1002/anie.201810384

(12) Rubens, M.; Van Herck, J.; Junkers, T. Automated Polymer Synthesis Platform for Integrated Conversion Targeting Based on Inline Benchtop NMR. ACS Macro Letters 2019, 8 (11), 1437-1441.

(13) Knox, S. T.; Parkinson, S. J.; Wilding, C. Y. P.; Bourne, R. A.; Warren, N. J. Autonomous polymer synthesis delivered by multi-objective closed-loop optimization. Polymer Chemistry 2022, 13 (11), 1576-1585,

(14) Parkinson, S.; Hondow, N. S.; Conteh, J. S.; Bourne, R. A.; Warren, N. J. All-aqueous continuous-flow RAFT dispersion polymerisation for efficient preparation of diblock copolymer spheres, worms and vesicles. Reaction Chemistry & Engineering 2019, 4 (5), 852-861

(15) Parkinson, S.; Knox, S. T.; Bourne, R. A.; Warren, N. J. Rapid production of block copolymer nano-objects via continuous-flow ultrafast RAFT dispersion polymerisation. Polymer Chemistry 2020, 11 (20), 3465-3474

(16) Knox, S. T.; Parkinson, S.; Stone, R.; Warren, N. J. Benchtop flow-NMR for rapid online monitoring of RAFT and free radical polymerisation in batch and continuous reactors. Polymer Chemistry 2019, 10 (35), 4774-4778

(17) Pittaway, P. M.; Chingono, K. E.; Knox, S. T.; Martin, E.; Bourne, R. A.; Cayre, O. J.; Kapur, N.; Booth, J.; Capomaccio, R.; Pedge, N.; et al. Exploiting Online Spatially Resolved Dynamic Light Scattering and Flow-NMR for Automated Size Targeting of PISA-Synthesized Block Copolymer Nanoparticles. ACS Polymers Au 2025, 5 (1), 1-9.

(18) Knox, S. T.; Wu, K. E.; Islam, N.; O'Connell, R.; Pittaway, P. M.; Chingono, K. E.; Oyekan, J.; Panoutsos, G.; Chamberlain, T. W.; Bourne, R. A.; et al. Self-driving laboratory platform for many-objective self-optimization of polymer nanoparticle synthesis with cloud-integrated machine learning and orthogonal online analytics. Polymer Chemistry 2025,16, 1355-1364

(19) Pittaway, P. M.; Knox, S. T.; Cayre, O. J.; Kapur, N.; Golden, L.; Drillieres, S.; Warren, N. J. Self-driving laboratory for emulsion polymerization. Chemical Engineering Journal 2025, 50