Can Vision-Language Models Reason Beyond What They See?

Figure 1: **ImagineBench: beyond visual perception.** (a) VLMs perform well on visible evidence but struggle with imagined scene transformations. (b) Overall accuracy of five VLMs on **ImagineBench**, compared against the human baseline (91.38%). (c) External performance of Qwen3.5-4B-it and our LoRA supervised fine-tuned Imagine-Qwen, showing that imagination-oriented training improves reasoning ability and hallucination robustness.

Abstract

Mental imagery is a crucial human capability that enables humans to internally simulate visual, spatial, and conceptual states beyond immediate perception. Despite rapid progress in vision-language models (VLMs), their ability to reason beyond directly visible evidence remains underexplored. In this paper, we introduce **ImagineBench**, to our knowledge the first benchmark that systematically unifies multiple forms of grounded mental-imagery reasoning in VLMs. We first develop a taxonomy grounded in cognitive theory, covering five categories: *Event Progression*, *Perspective Transformation*, *Functional Intent*, *Counterfactual State*, and *Structural Completion*. Building on this taxonomy, we construct 19.8K high-quality, fully human-annotated samples across diverse visual scenarios. Each sample is designed and human-verified to require reasoning over a plausible unobserved state rather than direct extraction from visible evidence. Extensive experiments reveal a substantial gap between current VLMs and humans in grounded mental-imagery reasoning. We further show that supervised fine-tuning with ImagineBench improves held-out performance and transfers to external multimodal benchmarks, suggesting that mental-simulation supervision encourages more careful reasoning and reduces hallucination. These results establish mental imagery as a critical missing dimension in VLM evaluation and a promising route toward reliable multimodal intelligence capable of reasoning beyond what it sees.

1 Introduction

Vision-language models (VLMs) (Google Deep-Mind, 2025; OpenAI, 2025) have made remarkable progress in understanding, reasoning over, and generating multimodal content, enabling applications across robotics, biomedicine, and autonomous driving (Kim et al., 2024; Chen et al., 2024a). As their capabilities expand, evaluating VLMs has become increasingly important and challenging. Consequently, the benchmark landscape is rapidly evolving, with studies assessing models either comprehensively (Fu et al., 2024a; Liu et al., 2024b) or through targeted capabilities such as hallucination, spatial reasoning, and visual grounding (Guan

Type	Benchmark	Data				Imagination Capability					Eval.
		Samples	Ann.	Scope	Ans.	Event Prog.	Counter fact.	Struct. Comp.	Func. Intent	Persp. Trans.	LLM Judge
General	MM-Vet (Yu et al., 2024)	218	H	200 I	OE	✗	✗	✗	✗	✗	✓
	SEED-Bench-2 (Li et al., 2024b)	24K	H	27 D	MC	✗	✗	✗	✗	✗	✗
	BLINK (Fu et al., 2024c)	3.8K	H	14 T	MC	✗	✗	✗	✗	✗	✗
	MMMU (Yue et al., 2024)	11.5K	H	30 IT	MC/OE	✗	✗	✗	✗	✗	✗
	MMT-Bench (Ying et al., 2024)	31.3K	H+M	162 ST	MC	✗	✗	✗	✗	✗	✗
Specialized	CAPTURE (Pothiraj et al., 2025)	4.3K	H+M	2.1K I	Num	✗	✗	✓	✗	✗	✗
	All-Angles Bench (Yeh et al., 2025)	2.1K	H+M	90 S	MC	✗	✗	✗	✗	✓	✗
	MARS-Bench (Li et al., 2024d)	6.0K	H+M	1.0K I	MC	✗	✓	✗	✗	✗	✗
	SpinBench (Zhang et al., 2025)	2.9K	H+M	23 TV	MC	✗	✗	✗	✗	✓	✗
	MindCube (Yin et al., 2025)	21.2K	H+M	976 VG	MC	✗	✗	✗	✗	✓	✗
	Intentonomy (Jia et al., 2021)	14K	H	28 C	Lbl	✗	✗	✗	✓	✗	✗
ImagineBench (ours)		**19.8K**	**H**	**9.4K I**	**OE**	✓	✓	✓	✓	✓	✓

Table 1: Comparison our ImagineBench with VLM benchmarks on data collection, imagination capability coverage, and evaluation. **Scope**: I = images, D = dimensions, T = tasks, IT = image types, ST = subtasks, S = scenes, TV = task variants, VG = view groups, C = categories. **Ann.**: H = Human, M = Machine; **Ans.**: MC = multiple-choice, OE = open-ended, Num = numeric, Lbl = label. **LLM Judge**: LLM-based semantic scoring, not answer extraction.

et al., 2024; Du et al., 2024; Liu et al., 2023).

Despite this growing body of evaluation efforts, one important cognitive ability remains underexplored: mental imagery(Nanay, 2026; Finke, 1989). Mental imagery is a core cognitive capacity that enables humans to internally simulate visual, spatial, and conceptual states beyond immediate perception. It supports abstraction and planning by allowing us to reason about scenarios that are unseen yet mentally constructible (Paivio, 1971; Shepard and Metzler, 1971). This capability is essential for real-world scenarios, where visual answers may not be explicitly present in the image. Instead, solving the task may require constructing an internal representation of what could happen, what is hidden, or how a scene might change under certain conditions. This raises the central question of our work: Can VLMs reason beyond what they see?

However, existing multimodal benchmarks (Fu et al., 2024b) are not well suited to assess this dimension of intelligence. **Tab.1** shows that current benchmarks primarily test whether models can recognize or reason over what is explicitly present in the visual input (Ying et al., 2024; Chen et al., 2024b). While these benchmarks have been crucial for tracking progress, many tasks can be solved without constructing an imagined scene representation. Meanwhile, specialized benchmarks typically focus on individual abilities (Zhang et al., 2025; Jia et al., 2021) and do not fully capture the diverse forms of mental simulation. More importantly, the limitation is clear in **Fig. 1(a)**: even SOTA models that answer ordinary questions correctly, yet fail when required to simulate scene changes or adopt an imagined viewpoint. This gap highlights the urgent need for new evaluation frameworks that systematically measure imagination ability in diverse, dynamic, and partially observed environments.

To bridge this gap, we introduce ImagineBench, a comprehensive benchmark designed to assess whether VLMs can perform reasoning that depends on mental simulation. Unlike conventional benchmarks that often rely on directly observable evidence, ImagineBench focuses on cases that cannot be solved by perception alone and instead require the model to construct an internal representation beyond the given image. We systematically categorize mental imagery into five types: Counterfactual State, Event Progression, Functional Intent, Perspective Transformation, and Structural Completion. The benchmark spans diverse scenes, lighting and weather conditions, ensuring broad coverage of real-world scenarios with each sample human-annotated and verified to ensure that the answer must be inferred through mental simulation (as illustrated in **Fig.2(top)**). In this way, ImagineBench provides a principled foundation for evaluating and developing next-generation multimodal systems capable of reasoning beyond what they see.

Importantly, our goal is not only to diagnose the lack of mental imagery in current VLMs, but also to offer an initial pathway toward improving it. Cognitive studies suggest that mental simulation enables humans to evaluate hypothetical outcomes and make better-informed decisions before acting(Markman et al., 2007; Johnson-Laird, 2010). Inspired by this, we construct a high-quality, manually curated training set of diverse QA pairs re-

quiring explicit mental simulation, and introduce a simple supervised fine-tuning baseline. We assess the resulting imagination-oriented models on both ImagineBench and other multimodal benchmarks.

Through extensive experiments, we reveal two key findings. First, current VLMs still lag far behind humans in mental-imagery reasoning. As shown in **Fig. 1(b)**, even the strong proprietary model GPT-5-mini achieves only 62.40% on our ImagineBench, substantially below the human score of 91.38%. Second, fine-tuning on our training set yields clear gains on ImagineBench, demonstrating the effectiveness and high quality of the proposed data. These gains further transfer to other multimodal benchmarks, suggesting that imagination-oriented training can reduce hallucination and improve general reasoning ability, aligning with prior cognitive evidences (as shown in **Fig. 1(c)**). These findings underscore the value of ImagineBench not only as an evaluation benchmark, but also as a useful resource for enhancing the reasoning robustness and reliability of VLMs. In summary, our main contributions are as follows:

- **First attempt to comprehensively study mental imagery in VLMs**: We systematically investigate whether VLMs can reason beyond visible evidence through mental simulation.

- **ImagineBench:** We introduce a novel, high-quality, fully human-annotated benchmark with 19,880 samples, covering diverse visual conditions and five types of mental imagery.

- **Extensive experiments:** We show a large gap between current VLMs and humans, while demonstrating that simulation-oriented fine-tuning improves general reasoning performance and reduces hallucination, consistent with prior cognitive evidence.

2 Related Work

2.1 Large Vision-Language Models

Recent vision-language models (VLMs) (OpenAI, 2025; Google DeepMind, 2025; Qwen Team, 2026; Bai et al., 2025; Wang et al., 2025) have advanced rapidly in connecting visual perception with language understanding, supporting multimodal instruction following, caption generation, and complex reasoning. However, recent studies show that VLMs can still struggle with fine-grained visual perception and may rely on learned vision-language priors rather than image details (Vo et al.,

2025; Rahmanzadehgervi et al., 2024). In real-world scenarios, reasoning often requires going beyond perception. These abilities are closely tied to mental imagery, which involves constructing internal visual representations beyond direct observation. In this work, we investigate whether current VLMs exhibit such imagination-driven reasoning.

2.2 Multimodal Benchmarks

Existing benchmarks and surveys (Fu et al., 2024b; Li et al., 2024c) measure a wide range of abilities, from general VQA and multimodal reasoning (Fu et al., 2024a; Yu et al., 2024) to specialized tasks such as spatial reasoning, temporal reasoning, and hallucination detection (Li et al., 2025; Yi et al., 2019; Chen et al., 2022; Li et al., 2023). These efforts have been essential for understanding model progress and exposing limitations. However, many benchmarks still assume that the answer is grounded in what is visible or recoverable from observed inputs. As a result, current evaluation protocols (Yue et al., 2025; Chen et al., 2024b) remain insufficient for assessing mental imagery, where the model must go beyond perception and simulate unobserved states. ImagineBench complements prior benchmarks by shifting the focus from *reasoning over observed evidence* to *reasoning over what must be imagined*.

3 ImagineBench

3.1 Overview

We present **ImagineBench**, a comprehensive benchmark for evaluating imagination-oriented reasoning in VLMs. In constructing ImagineBench, we emphasize data quality, diversity, taxonomy design, and evaluation rigor. It contains 19.8K carefully curated and fully human-annotated QA pairs, with images collected from multiple sources to cover a broad range of scenarios that demand reasoning beyond perception. ImagineBench organizes tasks into five categories grounded in cognitive theory. Each item is manually designed and reviewed through multi-round annotation, ensuring accuracy, consistency, and minimal ambiguity. Through this design, ImagineBench provides a reliable testbed for measuring and advancing imagination-driven multimodal reasoning.

3.2 Taxonomy of Mental Imagery

Our taxonomy is motivated by two complementary perspectives. First, it is grounded in **cognitive**

Figure 2: Overview of ImagineBench. **(top)** Representative examples of the five imagination categories. **(bottom left)** Human-centered data construction workflow. **(bottom right)** Key dataset statistics and category distribution. Together, these panels summarize the taxonomy, annotation pipeline, and overall benchmark scale.

psychology: prior studies on mental imagery suggest that many reasoning tasks cannot be solved through direct observation alone (Shepard and Metzler, 1971; Finke, 1989). Humans use mental simulation to predict future states, transform spatial perspectives, infer hidden structures, and reason about hypothetical changes (Kosslyn, 1980; Decety and Grèzes, 2006), enabling flexible reasoning and decision-making beyond visible evidence. Importantly, **our focus is not on unconstrained creativity or arbitrary imagination, but on grounded mental imagery**, where the imagined state must remain consistent with the visual input and with basic physical, spatial, and functional constraints. Second, this focus is motivated by **real-world multimodal tasks**, where useful information is often incomplete or not directly visible, spanning common situations as well as more complex scenarios.

Guided by these considerations, we systematically categorize mental imagery into 5 types: Event Progression, Perspective Transformation, Functional Intent, Counterfactual State, and Structural Completion. Each type corresponds to **a distinct cognitive operation** and aims underexplored challenges in prior work, enabling us to assess a broader spectrum of mental imagery while remaining grounded in theory and real-world situations.

Event Progression (Zacks and Swallow, 2007; Zacks et al., 2007) concerns the ability to infer motion and temporal change from visual evidence. This ability is crucial for adaptive decision-making in dynamic environments, such as robotics, where agents must respond to unexpected changes.

Perspective Transformation (Finke, 1989; Paivio, 1971; Shepard and Metzler, 1971) evaluates spatial re-representation from an alternative viewpoint. This ability enables a better understanding of scene layout and supports flexible problem-solving.

Functional Intent (Talevich et al., 2017; Keil et al., 2007) evaluates the ability to infer latent functional relationships from visible objects, structures, or body postures. The focus is on utility, mechanical role, and purpose rather than emotional or psychological speculation. It is important because real-world reasoning often requires understanding not only what an object is, but how it can be used.

Counterfactual State (Epstude and Roese, 2008) assesses action-conditioned causal reasoning under hypothetical interventions. Models must infer how the observed scene would change if a specific condition were altered, requiring an understanding of causal dependencies rather than surface visual patterns. This ability supports more robust problem-solving and planning.

Structural Completion (Kanizsa, 1979) involves reasoning about missing, occluded, or partially observed structures. Models must complete plausible hidden structures using visible geome-

try, object relations, and structural regularities, an ability central to spatial understanding, design reasoning, and reasoning under partial observability.

This taxonomy balances theoretical coverage with practical applicability. Event Progression highlights temporal state projection; Functional Intent probes goal-directed affordance reasoning; Counterfactual State reflects hypothetical state reasoning; Structural Completion measures amodal structural inference; and Perspective Transformation evaluates spatial re-representation flexibility. Together, these dimensions form a principled framework for evaluating grounded mental-imagery reasoning in VLMs.

3.3 Data Curation

We design a human-centered data curation pipeline for constructing imagination-oriented reasoning samples. Unlike prior works whose answers are often grounded in visible evidence, our goal is to collect images that naturally require inferring plausible but unobserved states. As shown in **Fig. 2 (bottom left)**, the pipeline consists of three stages: image sourcing, QA annotation, and filtering. More details about annotation protocol in **Appendix A**.

Image Sourcing. We collect candidate images from two sources. First, we manually gather **web images** to ensure broad coverage of real-world scenarios; all selected images are licensed under MIT or CC-BY 4.0. Second, we sample from **existing datasets**, including COCO and VCR (Lin et al., 2014; Zellers et al., 2019), prioritizing images with clear object structures, rich context, and meaningful spatial or temporal cues. We then apply strict visual filtering to retain only suitable images. Specifically, an image is kept if it satisfies at least one criterion: (1) substantial partial occlusion requiring completion of hidden objects or body parts; (2) clear motion cues, such as motion blur or dynamic posture, supporting future-state inference; or (3) objects whose size, orientation, position, or state can be plausibly transformed. This filtering ensures that ImagineBench targets grounded mental imagery rather than standard visual recognition.

Human Annotation. All questions and answers are created by human annotators. For each taxonomy category, we randomly assign a group of three annotators. The first annotator writes an imagination-centered question and its answer. Images for which no valid question can be constructed

are discarded. The other two annotators then independently answer the question without seeing the first annotator's answer. This design allows us to verify whether the question is answerable and whether the imagined state is plausible.

Filtering Step. We use Fleiss' κ to quantify agreement among annotators, as designed for measuring nominal-scale agreement across multiple raters (Fleiss, 1971). Samples with high agreement are placed into the *yes* set, where Fleiss' $\kappa \geq 0.85$. Samples with moderate agreement are placed into the *hesitant* set, where Fleiss' $\kappa \approx 0.5$ and further review is required. The remaining samples are assigned to the *remove* set due to ambiguity, duplication, irrelevance, weak visual evidence, or inconsistency among annotators. For samples in the *hesitant* set, annotators conduct an additional revision round to refine the question and answer until consistency is reached. If consensus cannot be achieved after revision, the sample is discarded. Through this process, we retain only samples whose imagined states are plausible and consistently supported by human judgement. We use a category-stratified 90/10 train-test split, yielding 17,892 training samples and 1,988 test samples. Final data statistics are shown in **Fig. 2 (bottom right)**.

3.4 A Simple Baseline

Beyond diagnosing the limitations of current VLMs, we aim to explore whether mental imagery can be improved through targeted supervision. We therefore propose a simple baseline based on supervised fine-tuning using LoRA (Pareja et al., 2024; Hu et al., 2021) on our manually curated high-quality training set. We apply this procedure to two representative open-source VLMs, Qwen and InternVL (Bai et al., 2025; Zhu et al., 2025), and refer to the trained models as **Imagine-Qwen** and **Imagine-InternVL**, respectively. This baseline provides a lightweight and reproducible way to test if imagination-oriented training can enhance simulation-based and overall reasoning.

4 Experiments

4.1 Experimental Setup

We evaluate proprietary and open-source VLMs on the held-out test split of ImagineBench using an image-question input format. The evaluated models include Gemini-3-Flash (Google DeepMind, 2025), GPT-5-mini (OpenAI, 2025),

Model	Counterfactual	Event	Functional	Perspective	Structural	Overall
Human Baseline	91.20	94.33	89.50	93.10	88.75	91.38
Proprietary Foundation VLMs						
Gemini-3-Flash	**65.93**	72.67	**76.35**	**71.50**	**50.66**	**67.42**
GPT-5-mini	60.54	**75.33**	73.46	61.74	40.94	62.40
Open-source Foundation VLMs						
Gemma-4-31B-it	61.27	68.67	68.46	61.48	47.51	61.48
Ovis2-34B	55.15	69.00	64.81	55.67	39.37	56.80
Qwen3-VL-32B-Instruct	49.75	71.00	68.65	52.51	36.48	55.68
Molmo-72B	51.47	70.00	65.38	55.67	32.81	55.07
InternVL3.5-38B	49.75	66.67	60.58	55.41	29.66	52.41
Kimi-VL-A3B-Instruct	40.20	53.33	56.15	54.35	22.05	45.22
360VL-70B	42.65	53.33	52.69	50.66	24.41	44.75
LLaVA-NeXT-Yi-34B	39.22	52.67	55.96	50.40	23.88	44.42
LLaVA-OneVision-7B	38.83	45.77	44.88	47.69	21.44	40.34
Idefics2	33.72	41.12	33.79	48.46	17.68	34.97
Domain-Specific Fine-Tuning on ImagineBench						
Qwen3.5-4B-it	20.10	40.67	51.35	46.97	22.05	36.22
+ LoRA SFT (Imagine-Qwen)	38.24	58.33	58.46	48.28	35.17	47.70
Δ *Absolute Gain*	**+18.14**	**+17.66**	**+7.11**	**+1.31**	**+13.12**	**+11.48**
InternVL3-8B	33.09	45.67	48.46	41.95	18.37	38.41
+ LoRA SFT (Imagine-InternVL)	46.57	62.67	69.62	46.44	40.68	52.30
Δ *Absolute Gain*	**+13.48**	**+17.00**	**+21.16**	**+4.49**	**+22.31**	**+13.89**

Table 2: Main results (accuracy, %) on ImagineBench across five imagination categories. Models are partitioned into proprietary, open-source foundation, and fine-tuned groups. The best performance among foundation VLMs is highlighted in **bold**. The Δ rows report absolute percentage-point gains after LoRA supervised fine-tuning.

Gemma-4-31B-it (Google, 2026), Qwen3-VL-32B-Instruct (Bai et al., 2025), Molmo-72B (Deitke et al., 2025), Ovis2-34B (Lu et al., 2024), InternVL3.5-38B (Wang et al., 2025), Kimi-VL-A3B-Instruct (Kimi Team, 2025), 360VL-70B (Qihoo 360, 2024), LLaVA-NeXT-Yi-34B (Liu et al., 2024a), LLaVA-OneVision-7B (Li et al., 2024a), and Idefics2 (Laurençon et al., 2024). Open-source models are evaluated on servers with $2\times$ RTX A6000 48GB or $2\times$ A100 80GB SXM GPUs, while proprietary models are accessed through their official APIs. Fine-tuned variants use LoRA-based supervised fine-tuning (Pareja et al., 2024; Hu et al., 2021) on the ImagineBench training split, including Qwen3.5-4B-it (Qwen Team, 2026) and InternVL3-8B (Zhu et al., 2025). We also further report a human baseline on the same held-out split as a reference ceiling.

Evaluation protocol. We employ an LLM-as-judge protocol with Gemini-3-Flash (Google DeepMind, 2025) as an evaluator to assess model predictions and report both overall and category-level accuracy across the five imagination categories. Detailed experimental settings, human baseline results, and training configurations are provided in **Appendix B**.

4.2 Main Results

Current VLMs remain far from human-level mental imagery. Tab. 2 shows that the best model reaches only 67.42% overall accuracy, far below the 91.38% human baseline. Structural Completion is consistently the most difficult category, suggesting that amodal completion and off-screen reasoning remain major challenges, while Event Progression and Functional Intent are comparatively easier.

LoRA fine-tuning on ImagineBench yields large gains. As shown in **Tab. 2**, LoRA supervised fine-tuning approach substantially improves both Qwen3.5-4B-it and InternVL3-8B, demonstrating the effectiveness of our high-quality training set and the value of imagination-oriented supervision. The results suggest that larger model scale does not reliably predict stronger performance on ImagineBench, as some 70B-scale models underperform substantially smaller ones.

ImagineBench fine-tuning improves general reasoning and reduces hallucination, consistent with prior cognitive evidence. As shown in **Tab. 3**, both fine-tuned models improve across all four external evaluation dimensions. Specifically, Imagine-Qwen shows notable gains on MMMU-Pro (+4.28%), BLINK (+2.96%), and MMT-Bench (+2.69%), while Imagine-InternVL improves more

Group	Benchmark	Metric	Qwen Base	Imagine-Qwen	Qwen Δ	InternVL Base	Imagine-InternVL	InternVL Δ
Visual Perception								
	AI2D (Kembhavi et al., 2016)	Accuracy	83.84	84.42	+0.58	82.42	82.55	+0.13
	BLINK (Fu et al., 2024c)	Accuracy	69.63	72.59	+2.96	65.81	66.67	+0.85
	VSR (Liu et al., 2023)	Accuracy	83.33	84.37	+1.05	78.56	78.81	+0.25
Knowledge & Reasoning								
	MMMU (Yue et al., 2024)	Accuracy	53.40	54.80	+1.40	54.33	55.11	+0.78
	MMMU-Pro (Yue et al., 2025)	Accuracy	25.38	29.65	+4.28	30.81	30.98	+0.17
	MMStar (Chen et al., 2024b)	Accuracy	58.27	59.67	+1.40	64.00	65.13	+1.13
	MMT-Bench (Ying et al., 2024)	Accuracy	63.38	66.07	+2.69	62.00	62.13	+0.13
Spatial 3D & Navigation								
	RealWorldQA (xAI, 2024)	Accuracy	64.97	65.49	+0.52	64.84	65.75	+0.91
	MindCube-Tiny (Yin et al., 2025)	Accuracy	40.00	42.50	+2.50	38.29	39.14	+0.86
	EmbSpatial (Du et al., 2024)	Accuracy	71.65	73.05	+1.40	77.55	79.86	+2.31
Hallucination & Reliability								
	HallusionBench (Guan et al., 2024)	Q-Acc.	71.19	72.03	+0.84	43.67	47.12	+3.45
	POPE (Li et al., 2023)	Accuracy	90.00	90.50	+0.50	89.80	89.98	+0.18
	POPE (Li et al., 2023)	F1	90.53	90.91	+0.38	89.41	89.59	+0.18

Table 3: External benchmark results grouped by evaluation capability. Δ denotes the absolute percentage-point improvement of the LoRA fine-tuned model over the corresponding base model.

on spatial and reliability-oriented benchmarks, especially EmbSpatial (+2.31%) and HallusionBench (+3.45%). These results suggest that imagination-oriented supervision encourages more structured internal representations, leading to clearly stronger reasoning and fewer hallucination-prone responses, consistent with previous cognitive theories of mental simulation (Markman et al., 2007; Johnson-Laird, 2010; Hegarty, 2004).

4.3 Diagnostic Analysis

(a) Question difficulty. To inspect performance boundaries, we divide all test set into three tiers by model consensus: **Easy** (correctly answered by ≥ 8 of 10 evaluated models), **Medium** (5–7 models correct), and **Hard** (≤ 4 models correct). This yields 401 Easy, 789 Medium, and 798 Hard samples (as illustrated in **Tab. 4**).

On Easy samples, the strongest models converge near the performance ceiling ($\sim$93–95%), confirming that when sufficient visual scaffolding is present, VLMs can answer reliably. Furthermore, Medium samples are the most discriminative tier: Gemini-3-Flash leads at 73.8% while weaker open-source models fall below 50%, producing the largest inter-model spread of any tier. **Hard samples reveal the clearest failure boundary**: Gemini-3-Flash reaches only 15.9%, and most open-source models fall below 10%.

Notably, 10.7% of all test items, or 26.7% of the Hard tier, receive *zero* correct answers from all 10 evaluated models, indicating a systematically intractable subset for current VLMs. Hard items are unevenly distributed across categories, with Functional Intent containing the highest proportion of Hard items (52.2%) and Counterfactual State being

Model	Easy (401)	Medium (789)	Hard (798)	Overall (1,988)
Proprietary				
Gemini-3-Flash	**95.3**	**73.8**	**15.9**	**54.9**
GPT-5-mini	92.0	59.2	8.3	45.4
Open-source				
Gemma-4-31B-it	**95.3**	67.8	11.5	50.7
360VL-70B	93.9	55.4	15.5	47.2
InternVL3.5-38B	92.0	59.2	6.4	44.6
Ovis2-34B	**95.3**	56.9	4.3	43.6
LLaVA-NeXT-Yi-34B	86.9	55.1	10.6	43.6
Qwen3-VL-32B	94.4	55.8	4.8	43.1
Molmo-72B	85.0	54.3	5.7	41.0
Kimi-VL-A3B	78.9	47.9	8.4	38.3

Table 4: Accuracy (%) by difficulty tier. Easy, Medium, and Hard are defined by the number of models, out of 10, that answer correctly: Easy ≥ 8, Hard ≤ 4, and Medium otherwise. Bold marks the best score in each column; open-source models matching the top proprietary Easy score are also bolded.

more tractable (24.2%). Full per-category and per-taxonomy breakdowns are reported in **Appendix C**.

(b) Response length. Because ImagineBench uses open-ended answers with an LLM-as-judge evaluation protocol, we test whether accuracy is confounded by verbosity, focusing on Structural Completion as the hardest and most elaboration-prone category. **Accuracy is not explained by verbosity**: response length is only weakly correlated with accuracy (Pearson $r = 0.25$). Specifically, Molmo-72B produces the longest outputs on average (74.2 words) while scoring only 32.8%. Moreover, both Imagine-Qwen and Imagine-InternVL gains large improvements after LoRA SFT while decreasing its max length and also increasing its average response length, revealing that simulation-oriented training signal makes model think in more accurate and moderate thinking.

Model	SC Acc.	Avg. Len.	Max Len.
Gemini-3-Flash	**50.7**	20.1	222
Gemma-4-31B-it	47.5	20.4	128
GPT-5-mini	40.9	28.1	325
Ovis2-34B	39.4	37.0	185
Qwen3-VL-32B	36.5	51.2	273
Molmo-72B	32.8	**74.2**	412
InternVL3.5-38B	29.7	20.4	**525**
360VL-70B	24.4	4.9	38
LLaVA-NeXT-Yi-34B	23.9	7.5	75
Kimi-VL-A3B	22.1	14.7	314
LLaVA-OneVision-7B	21.4	6.7	53
Idefics2	17.7	6.2	72
Qwen3.5-4B	22.1	23.4	492
+ LoRA SFT	35.2	51.1	365
InternVL3-8B	18.4	16.7	154
+ LoRA SFT	40.7	18.3	67

Table 5: Structural Completion accuracy (SC Acc., %) and response length statistics for all evaluated models.

(c) Error analysis. To understand where VLMs break down, we manually examine 300 randomly sampled wrong predictions from Gemini-3-Flash and assign each case to the earliest identifiable failure point in a waterfall-style pipeline: textual understanding, perception, knowledge, reasoning, or execution.

Figure 3: Distribution of error types across 300 annotated wrong predictions from Gemini-3-Flash.

The resulting distribution is shown in **Fig. 3**. In our manual analysis of 300 sampled predictions, reasoning-stage failures account for the largest share of errors (43%), followed by perception errors at 27% and knowledge errors at 24%. Perception and knowledge failures may be mitigated through better visual grounding and broader training coverage, but reasoning errors are harder: the model often has the necessary information yet fails to integrate it into a correct conclusion. This gap between constructing a plausible imagined state and deriving its outcome is the defining challenge of ImagineBench.

Figure 4: An example of a reasoning error in a failed prediction from Gemini-3-Flash.

Fig. 4 presents a qualitative example of a reasoning error in the *Counterfactual State* category. Although Gemini-3-Flash correctly perceives the visible pizza pieces, it fails to apply the counterfactual condition in a grounded manner. This example shows that failures on ImagineBench are not always caused by poor visual perception; they can arise when models over-reason, hallucinate unnecessary assumptions, or fail to constrain their mental simulation to the evidence in the image. (Further details in **Appendix** D.)

5 Conclusion

In this work, we introduced ImagineBench, a comprehensive benchmark for assessing grounded mental-imagery reasoning in VLMs. Grounded in cognitive theory, ImagineBench covers 5 dimensions of mental imagery (Event Progression, Perspective Transformation, Functional Intent, Counterfactual State, and Structural Completion) and provides 19.8K fully human-annotated samples in diverse real-world scenarios that require models to reason beyond visible evidence. Our results reveal a substantial gap between current VLMs and humans, showing strong visual recognition does not necessarily imply the ability to mentally simulate unseen states. We further demonstrate imagination-oriented supervised fine-tuning substantially improves performance on ImagineBench and transfers to external multimodal benchmarks, suggesting mental-simulation supervision can strengthen reasoning robustness and reduce hallucination. These findings establish mental imagery as an important missing dimension in current VLM evaluation and a promising direction for building multimodal systems capable of reasoning beyond what they see.

Limitations

ImagineBench is limited by its current scale and linguistic scope. Since each example requires human annotators to design an imagination-oriented question, provide a plausible answer and pass agreement-based quality control, scaling the dataset is substantially more costly and time-consuming than automatic data collection. While this process improves reliability and ensures that examples require grounded mental imagery rather than surface-level recognition, it limits our ability to fully study data scaling. In addition, the benchmark is currently constructed in English, which may not capture multilingual commonsense, cultural priors, or language-specific reasoning patterns.

References

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, and 45 others. 2025. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*.

Li Chen, Penghao Wu, Kashyap Chitta, Bernhard Jaeger, Andreas Geiger, and Hongyang Li. 2024a. End-to-end autonomous driving: Challenges and frontiers. *Preprint*, arXiv:2306.16927.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, and Feng Zhao. 2024b. Are we on the right way for evaluating large vision-language models? In *Advances in Neural Information Processing Systems*.

Zhenfang Chen, Kexin Yi, Yunzhu Li, Mingyu Ding, Antonio Torralba, Joshua B. Tenenbaum, and Chuang Gan. 2022. ComPhy: Compositional physical reasoning of objects and events from videos. In *International Conference on Learning Representations (ICLR)*.

Jean Decety and Julie Grèzes. 2006. The power of simulation: Imagining one's own and other's behavior. *Brain Research*, 1079(1):4–14.

Matt Deitke, Christopher Clark, Sangho Lee, Rohun Tripathi, Yue Yang, Jae Sung Park, Mohammadreza Salehi, Niklas Muennighoff, Kyle Lo, Luca Soldaini, Jiasen Lu, Taira Anderson, Erin Bransom, Kiana Ehsani, Huong Ngo, YenSung Chen, Ajay Patel, Mark Yatskar, Chris Callison-Burch, and 31 others. 2025. Molmo and PixMo: Open weights and open data for state-of-the-art vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*.

Mengfei Du, Binhao Wu, Zejun Li, Xuanjing Huang, and Zhongyu Wei. 2024. EmbSpatial-bench: Benchmarking spatial understanding for embodied tasks with large vision-language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 346–355, Bangkok, Thailand. Association for Computational Linguistics.

Kai Epstude and Neal J Roese. 2008. The functional theory of counterfactual thinking. *Personality and social psychology review*, 12(2):168–192.

R.A. Finke. 1989. *Principles of Mental Imagery*. A Bradford book. MIT Press.

Joseph L. Fleiss. 1971. Measuring nominal scale agreement among many raters. *Psychological Bulletin*, 76(5):378–382.

Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Jinrui Yang, Xiawu Zheng, Ke Li, Xing Sun, Yunsheng Wu, and Rongrong Ji. 2024a. MME: A comprehensive evaluation benchmark for multimodal large language models. *arXiv preprint arXiv:2306.13394*.

Chaoyou Fu, Yi-Fan Zhang, Shukang Yin, Bo Li, Xinyu Fang, Sirui Zhao, Haodong Duan, Xing Sun, Ziwei Liu, Liang Wang, Caifeng Shan, and Ran He. 2024b. Mme-survey: A comprehensive survey on evaluation of multimodal llms. *Preprint*, arXiv:2411.15296.

Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoxuan Wang, Xudong Lin, Dan Roth, Noah A. Smith, Wei-Chiu Ma, and Ranjay Krishna. 2024c. BLINK: Multimodal large language models can see but not perceive. In *European Conference on Computer Vision*.

Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daumé III, and Kate Crawford. 2021. Datasheets for datasets. *Communications of the ACM*, 64(12):86–92.

Google. 2026. Gemma 4 Model Overview. https://ai.google.dev/gemma/docs/core.

Google DeepMind. 2025. Gemini 3 Flash Model Card. https://storage.googleapis.com/deepmind-media/Model-Cards/Gemini-3-Flash-Model-Card.pdf.

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, Dinesh Manocha, and Tianyi Zhou. 2024. HallusionBench: An advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*.

Mary Hegarty. 2004. Mechanical reasoning by mental simulation. *Trends in Cognitive Sciences*, 8(6):280–285.

Edward J. Hu, Yelong Shen, Phillip Wallis, Yeqing Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. LoRA: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*.

Menglin Jia, Zuxuan Wu, Austin Reiter, Claire Cardie, Serge Belongie, and Ser-Nam Lim. 2021. Intentonomy: A dataset and study towards human intent understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*.

Philip N. Johnson-Laird. 2010. Mental models and human reasoning. *Proceedings of the National Academy of Sciences*, 107(43):18243–18250.

Gaetano Kanizsa. 1979. *Organization in Vision: Essays on Gestalt Perception*. Praeger, New York.

Frank Keil, Marissa Greif, and Rebekkah Kerner. 2007. *A World Apart: How Concepts of the Constructed World Are Different in Representation and in Development*, pages 231–246.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. 2016. A diagram is worth a dozen images. In *European Conference on Computer Vision*, pages 235–251.

Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, Quan Vuong, Thomas Kollar, Benjamin Burchfiel, Russ Tedrake, Dorsa Sadigh, Sergey Levine, Percy Liang, and Chelsea Finn. 2024. Openvla: An open-source vision-language-action model. *Preprint*, arXiv:2406.09246.

Kimi Team. 2025. Kimi-VL technical report. *arXiv preprint arXiv:2504.07491*.

Stephen Michael Kosslyn. 1980. *Image and Mind*. Harvard University Press, Cambridge, MA.

Hugo Laurençon, Léo Tronchon, Matthieu Cord, and Victor Sanh. 2024. What matters when building vision-language models? In *Advances in Neural Information Processing Systems*.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. 2024a. LLaVA-OneVision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*.

Bohao Li, Yuying Ge, Yixiao Ge, Guangzhi Wang, Rui Wang, Ruimao Zhang, and Ying Shan. 2024b. SEED-Bench: Benchmarking multimodal large language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13299–13308.

Dingming Li, Hongxing Li, Zixuan Wang, Yuchen Yan, Hang Zhang, Siqi Chen, Guiyang Hou, Shengpei Jiang, Wenqi Zhang, Yongliang Shen, Weiming Lu, and Yueting Zhuang. 2025. ViewSpatial-Bench: Evaluating multi-perspective spatial localization in vision-language models. *arXiv preprint arXiv:2505.21500*.

Lin Li, Guikun Chen, Hanrong Shi, Jun Xiao, and Long Chen. 2024c. A survey on multimodal benchmarks: In the era of large ai models. *Preprint*, arXiv:2409.18142.

Yian Li, Wentao Tian, Yang Jiao, Jingjing Chen, Na Zhao, and Yu-Gang Jiang. 2024d. Look before you decide: Prompting active deduction of MLLMs for assumptive reasoning. *arXiv preprint arXiv:2404.12966*.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. 2023. Evaluating object hallucination in large vision-language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. 2014. Microsoft coco: Common objects in context. In *European Conference on Computer Vision*, pages 740–755. Springer.

Fangyu Liu, Guy Emerson, and Nigel Collier. 2023. Visual spatial reasoning. *Transactions of the Association for Computational Linguistics*, 11:635–651.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. 2024a. LLaVA-NeXT: Improved reasoning, ocr, and world knowledge. https://llava-vl.github.io/blog/2024-01-30-llava-next/.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, Kai Chen, and Dahua Lin. 2024b. MMBench: Is your multi-modal model an all-around player? In *European Conference on Computer Vision (ECCV)*.

Shiyin Lu, Yang Li, Qing-Guo Chen, Zhao Xu, Weihua Luo, Kaifu Zhang, and Han-Jia Ye. 2024. Ovis: Structural embedding alignment for multimodal large language model. *arXiv preprint arXiv:2405.20797*.

Keith Markman, Matthew Lindberg, and Adam Galinsky. 2007. Implications of counterfactual structure for creative generation and analytical problem solving. *Personality and Social Psychology Bulletin*, 33:312–324.

Bence Nanay. 2026. Mental Imagery. In Edward N. Zalta and Uri Nodelman, editors, *The Stanford Encyclopedia of Philosophy*, Spring 2026 edition. Metaphysics Research Lab, Stanford University.

OpenAI. 2025. GPT-5 System Card. https://openai.com/index/gpt-5-system-card/.

A. Paivio. 1971. *Imagery and Verbal Processes*. Holt, Rinehart and Winston.

Aldo Pareja, Nikhil Shivakumar Nayak, Hao Wang, Krishnateja Killamsetty, Shivchander Sudalairaj, Wenlong Zhao, Seungwook Han, Abhishek Bhandwaldar, Guangxuan Xu, Kai Xu, Ligong Han, Luke Inglis, and Akash Srivastava. 2024. Unveiling the secret recipe: A guide for supervised fine-tuning small llms. *Preprint*, arXiv:2412.13337.

Atin Pothiraj, Elias Stengel-Eskin, Jaemin Cho, and Mohit Bansal. 2025. CAPTURe: Evaluating spatial reasoning in vision language models via occluded object counting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*.

Qihoo 360. 2024. 360VL-70B. https://huggingface.co/qihoo360/360VL-70B.

Qwen Team. 2026. Qwen3.5-Omni: Scaling up, toward native omni-modal agi.

Pooyan Rahmanzadehgervi, Logan Bolton, Mohammad Reza Taesiri, and Anh Totti Nguyen. 2024. Vision language models are blind. In *Proceedings of the Asian Conference on Computer Vision*, pages 18–34.

Roger N. Shepard and Jacqueline Metzler. 1971. Mental rotation of three-dimensional objects. *Science*, 171(3972):701–703.

Jennifer R. Talevich, Stephen J. Read, David A. Walsh, Ravi Iyer, and Gurveen Chopra. 2017. Toward a comprehensive taxonomy of human motives. *PLOS ONE*, 12(2):1–32.

An Vo, Khai-Nguyen Nguyen, Mohammad Reza Taesiri, Vy Tuong Dang, Anh Totti Nguyen, and Daeyoung Kim. 2025. Vision language models are biased. *Preprint*, arXiv:2505.23941.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, Zhaokai Wang, Zhe Chen, Hongjie Zhang, Ganlin Yang, Haomin Wang, Qi Wei, Jinhui Yin, Wenhao Li, Erfei Cui, and 41 others. 2025. InternVL3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*.

xAI. 2024. RealWorldQA. Released with Grok-1.5 Vision Preview.

Chun-Hsiao Yeh, Chenyu Wang, Shengbang Tong, Ta-Ying Cheng, Ruoyu Wang, Tianzhe Chu, Yuexiang Zhai, Yubei Chen, Shenghua Gao, and Yi Ma. 2025. Seeing from another perspective: Evaluating multi-view understanding in MLLMs. *arXiv preprint arXiv:2504.15280*.

Kexin Yi, Chuang Gan, Yunzhu Li, Pushmeet Kohli, Jiajun Wu, Antonio Torralba, and Joshua B. Tenenbaum. 2019. CLEVRER: Collision events for video representation and reasoning. *arXiv preprint arXiv:1910.01442*.

Baiqiao Yin, Qineng Wang, Pingyue Zhang, Jianshu Zhang, Kangrui Wang, Zihan Wang, Jieyu Zhang, Keshigeyan Chandrasegaran, Han Liu, Ranjay Krishna, Saining Xie, Manling Li, Jiajun Wu, and Li Fei-Fei. 2025. MindCube: Spatial mental modeling from limited views. *arXiv preprint arXiv:2506.21458*.

Kaining Ying, Fanqing Meng, Jin Wang, Zhiqian Li, Han Lin, Yue Yang, Hao Zhang, Wenbo Zhang, Yuqi Lin, Shuo Liu, Jiayi Lei, Quanfeng Lu, Runjian Chen, Peng Xu, Renrui Zhang, Haozhe Zhang, Peng Gao, Yali Wang, Yu Qiao, and 3 others. 2024. MMT-Bench: A comprehensive multimodal benchmark for evaluating large vision-language models towards multitask AGI. In *International Conference on Machine Learning*.

Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao Wang, and Lijuan Wang. 2024. MM-Vet: Evaluating large multimodal models for integrated capabilities. In *International Conference on Machine Learning*.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, Cong Wei, Botao Yu, Ruibin Yuan, Renliang Sun, Ming Yin, Boyuan Zheng, Zhenzhu Yang, Yibo Liu, Wenhao Huang, and 3 others. 2024. MMMU: A massive multi-discipline multimodal understanding and reasoning benchmark for expert AGI. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, Yu Su, Wenhu Chen, and Graham Neubig. 2025. MMMU-Pro: A more robust multi-discipline multimodal understanding benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15134–15186, Vienna, Austria. Association for Computational Linguistics.

Jeffrey M Zacks, Nicole K Speer, Khena M Swallow, Todd S Braver, and Jeremy R Reynolds. 2007. Event perception: a mind-brain perspective. *Psychological bulletin*, 133(2):273.

Jeffrey M Zacks and Khena M Swallow. 2007. Event segmentation. *Current directions in psychological science*, 16(2):80–84.

Rowan Zellers, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. From recognition to cognition: Visual commonsense reasoning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6720–6731.

Yuyou Zhang, Radu Corcodel, Chiori Hori, Anoop Cherian, and Ding Zhao. 2025. SpinBench: Perspective and rotation as a lens on spatial reasoning in VLMs. *arXiv preprint arXiv:2509.25390*.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Yuchen Duan, Hao Tian, Weijie Su, Jie Shao, Zhangwei Gao, Erfei Cui, Yue Cao, Yangzhou Liu, Weiye Xu, Hao Li, Jiahao Wang, Han Lv, Dengnian Chen, and 28 others. 2025. In-ternVL3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*.

Can Vision-Language Models Reason Beyond What They See?

Supplementary Material

Table of Contents in Appendix

A Data Annotation Protocol

This appendix supplements Section 3.3 of the main paper by providing the full annotation protocol, including detailed guidelines given to annotators, the data format specification, the complete quality control pipeline with concrete examples of common errors, strategies for resolving ambiguous cases, annotator background and training, and ethical considerations.

A.1 Image Sourcing and Filtering

Section 3.3 describes the two image sources (web images and existing datasets) and the three filtering criteria at a high level. Here we provide additional operational details.

Web image collection. Web images were gathered through manual search on photo-sharing platforms with permissive licensing. We specifically targeted scenes with spatial complexity—cluttered indoor environments, multi-person outdoor activities, construction and workshop settings, and transportation scenes—as these naturally give rise to occlusion, motion, and functional configurations suitable for imagination-centered questions. All selected web images were individually verified to carry MIT or CC-BY 4.0 licenses. Images with watermarks, heavy post-processing, or artificial compositing were excluded.

Existing dataset sampling. From COCO (Lin et al., 2014) and VCR (Zellers et al., 2019), we sampled images using metadata-guided selection: prioritizing images tagged with multiple object categories, person-object interactions, or dynamic activities. We avoided images that are commonly used as examples in VLM papers or tutorials, to reduce the risk that models have been specifically trained or tested on these images.

Filtering implementation. The three filtering criteria described in the main paper (occlusion, motion cues, transformable configuration) were applied manually by two independent reviewers. An image passed filtering only if both reviewers agreed it satisfied at least one criterion. Disagreements were resolved by a third reviewer.

Task distribution. Filtered images were loaded into shared Google Sheets, with one sheet per taxonomy category. Each sheet contained the image filename and a hyperlink to the full-resolution image. Tasks were distributed in rounds of 50–100 images to prevent annotator fatigue, with rest periods between rounds.

A.2 General Guidelines

The following instructions were provided to all annotators and refined during pilot rounds. These expand on the brief description in Section 3.3 by specifying the concrete rules annotators followed.

Image examination. Before formulating a question, annotators were instructed to spend at least 10 seconds examining the image, identifying spatial relationships, physical configurations, motion cues, occlusion patterns, and functional arrangements. If the image does not support a valid imagination question for the assigned taxonomy category, the annotator marks it as SKIP.

Question design principles:

1. The question **must require imagination** to answer. If the answer can be directly read off the image through recognition, retrieval, or straightforward perception, the question is invalid.

2. The question must be **unambiguous**: there should be a single correct answer (or a small set of clearly equivalent answers).

3. The question must be **self-contained**: it should make sense without external context beyond the image.

4. Avoid questions that depend on cultural knowledge, emotional interpretation, or subjective judgment. Focus on physical, spatial, and functional reasoning.

5. The question should be **natural and specific**. Avoid overly generic prompts (e.g., "What would change?") in favor of targeted questions about specific objects, positions, or states (e.g., "If the bottom crate were removed, where would the top crate land?").

6. The question must **not be trivially solvable by common sense alone** without looking at the image. The image content must be necessary to arrive at the answer.

Answer writing rules:

1. Answers must be **concise**: typically 1–10 words for factual answers, up to 2 sentences for descriptive answers.

2. When describing spatial positions or directions, answers should **reference identifiable landmarks or objects in the scene** where possible (e.g., "to the left of the red car"), rather than using purely abstract directions (e.g., "to the left"). However, brief directional answers are acceptable when the spatial context is unambiguous from the question (e.g., Q: "Which direction would the ball roll?" A: "Downhill to the right" is acceptable).

3. In scenes with multiple relevant subjects, the answer should address the **primary subject(s) affected** by the imagined change. Annotators are encouraged to mention secondary subjects when their state change is significant, but this is not strictly required for every case.

4. Numeric answers should be **as precise as the image allows**. Exact counts are preferred when objects are clearly countable. For distances or measurements, reasonable approximations are acceptable (e.g., "about 2 meters").

5. Answers must be **physically grounded**: they should follow from observable cues in the image combined with basic physical laws (gravity, inertia, structural support) or geometric reasoning.

A.3 Data Format and Structure

Each annotated sample in the released dataset consists of four fields:

Field	Description
image	Filename of the source image (e.g., imagine_000028.jpg)
taxonomy	One of five categories: Counterfactual State, Event Progression, Functional Intent, Perspective Transformation, Structural Completion
question	The imagination-centered question
answer	The concise reference answer

Table 6: Data format for each sample in ImagineBench.

All text fields are in English. Images are stored as JPEG files at their original resolution. The dataset is distributed as a JSON file with one entry per sample, accompanied by an image directory.

A.4 Quality Control and Validation

Section 3.3 describes the agreement-based filtering at a high level. Here we detail the full four-stage quality control pipeline, including the expert review process and the specific error patterns we identified and corrected.

Three-annotator protocol. For each taxonomy category, a group of three annotators is randomly assigned. The first annotator (the *author*) writes the question and answer. The other two (the *validators*) independently answer the same question without seeing the author's response. The author's answer column is hidden in the Google Sheet during validation. This design tests whether the question is answerable, whether the imagined state is plausible, and whether independent annotators converge.

Stage 1: Agreement-based filtering. We compute Fleiss' κ (Fleiss, 1971) across the three annotators and sort samples into three bins, as described in Section 3.3. In practice, approximately 58% of samples fell into the *yes* set ($\kappa \geq 0.85$), 27% into the *hesitant* set ($\kappa \approx 0.5$), and 15% into the *remove* set.

Stage 2: Revision of hesitant samples. For hesitant samples, annotators reviewed the disagreement, identified the source of divergence (ambiguous question, multiple valid interpretations, or perceptual error), and revised the question or answer accordingly. After revision, the sample was re-evaluated. Approximately 65% of hesitant samples were successfully revised and retained; the remaining 35% were discarded because consensus could not be reached.

Stage 3: Expert review. A senior reviewer manually reviewed a random 20% subsample from each taxonomy category, checking for: correct taxonomy assignment, answer accuracy, spatial specificity, adherence to category-specific constraints (Appendix D), and question quality.

Stage 4: Systematic error correction. The expert review revealed several recurring error patterns that were then systematically searched for and corrected across the full dataset:

1. **Taxonomy confusion.** Misclassification between Counterfactual State and Event Progression was the most common error, as both involve physical state changes. The disambiguation rules in Appendix D.6 were applied. For example, a question asking "What would happen if the wind blew harder?" was reassigned from Counterfactual State to Event Progression, because it involves applying an external force rather than removing a support.

2. **Vague spatial descriptions.** Answers like "it would move to the left" were flagged when a spatial anchor was available in the image. These were revised to reference visible landmarks (e.g., "it would slide toward the table leg on the left"). However, answers were not rejected if no clear landmark existed and the direction was unambiguous from context.

3. **False motion attribution.** Some questions assumed motion for static objects (e.g., asking about the "trajectory" of a parked bicycle). These were revised to either state an explicit hypothetical force in the question or reassigned to a different category.

4. **Hallucinated visual details.** Some answers referenced objects or spatial features not present in the image. Annotators were required to re-examine the image and verify every factual claim.

5. **Single-subject bias.** In multi-person or multi-object scenes, some answers described only the most salient subject. These were revised when other subjects would also be meaningfully affected by the imagined change.

6. **Overly complex questions.** Questions requiring long chains of inference (more than two intermediate steps) were simplified or decomposed into separate questions.

A.5 Handling Ambiguities

Taxonomy boundary cases. When a question could plausibly belong to two categories, we applied the disambiguation rules in Appendix D.6. If the question remained ambiguous after applying the rules, it was revised to make the taxonomy assignment clear, or discarded. The most frequent boundary was between Counterfactual State and Event Progression (see Appendix D.6 for detailed examples).

Multiple valid answers. When a question admits multiple physically plausible answers (e.g., an object could tip either left or right), annotators were asked to select the single most likely outcome based on visible cues and state their reasoning. During evaluation, the LLM-as-judge protocol (Appendix B) accounts for semantic equivalence, tolerating minor phrasing differences.

Debatable physical outcomes. For cases where the physical outcome was genuinely ambiguous (e.g., no visible cue favoring one direction over another), the sample was discarded rather than forcing an arbitrary choice.

A.6 Annotator Demographics and Expertise

The annotation team consisted of graduate students in computer science at the authors' institution. All annotators are fluent in English and have prior experience with visual question answering or multimodal AI research.

Annotators completed a three-phase training program before the main annotation:

1. **Briefing** (1 hour): Overview of the five taxonomy categories, their definitions and anti-hallucination constraints, and the annotation guidelines above.

2. **Pilot round** (20 images): Each annotator's outputs were individually reviewed by a senior team member with detailed written feedback on each sample.

3. **Calibration round** (50 images): Inter-annotator agreement was measured. Annotators falling below $\kappa = 0.7$ on the calibration set received additional one-on-one feedback and repeated calibration before joining the main annotation effort.

All annotators were compensated through their institutional positions as research assistants. Participation was voluntary, and annotators could withdraw at any time.

A.7 Data Licensing and Copyright

Web images are released under MIT or CC-BY 4.0 licenses. COCO (Lin et al., 2014) images are under CC-BY 4.0. VCR (Zellers et al., 2019) images are under a research-only license. The ImagineBench question–answer annotations are original works released under CC-BY-NC-4.0.

A.8 Data Contamination Considerations

Models pre-trained on COCO or VCR may have seen ImagineBench source images. Three factors mitigate this concern: (1) all questions and answers are entirely novel and appear in no prior dataset; (2) imagination-oriented answers require constructing unobserved states through reasoning,

not retrieval from memorized associations; (3) web-collected images, which appear in no standard training set, serve as a contamination-free control group.

A.9 Ethical Considerations and Limitations

Annotator welfare. All annotators are graduate students compensated through institutional positions. Participation was voluntary with no time pressure. Tasks were distributed in batches of 50–100 images with breaks between rounds. Images depict everyday scenes without graphic, violent, or explicit content.

Potential misuse. Benchmark scores should not be interpreted as comprehensive measures of real-world reasoning or equated with genuine understanding. Failure analysis could theoretically inform adversarial attacks, though we believe transparent reporting benefits the research community.

Limitations. The five categories do not cover all forms of mental imagery (e.g., creative imagination, abstract analogy, long-horizon planning). All content is English-only. Only single static images are used. Cultural biases in object familiarity may exist despite diverse sourcing.

A.10 Datasheet for ImagineBench

We provide a datasheet following the framework of Gebru et al. (2021). Each question is reproduced verbatim from the original framework, followed by our response.

Motivation

For what purpose was the dataset created? To evaluate whether VLMs can reason beyond directly visible content by constructing and reasoning over plausible but unobserved states—a capability we term mental imagery.

Who created the dataset? Author names are withheld for anonymous review.

Who funded the creation of the dataset? Funding details will be disclosed in the camera-ready version.

Composition

What do the instances that comprise the dataset represent? Each instance consists of an image paired with a question and a concise reference answer. The question requires the model to imagine an unobserved state (e.g., a future position, a hidden structure, an alternative viewpoint) to produce the correct answer.

How many instances are there in total? 19,722 question–answer pairs across 9,395 unique images.

Does the dataset contain all possible instances or is it a sample? It is a curated sample. The dataset does not aim to exhaustively cover all imagination scenarios.

What data does each instance consist of? Four fields: image filename, taxonomy category, question (natural language), and answer (natural language).

Are there recommended data splits? Yes. Training: 17,734 instances. Validation: 1,988 instances. The split is stratified across all five categories.

Is any information missing from individual instances? No. All instances contain complete image–question–answer triples with category labels.

Are there any errors, sources of noise, or redundancies? All instances underwent multi-stage quality control (Section A.4). Residual noise may exist in boundary cases between taxonomy categories.

Does the dataset contain data that might be considered confidential? No. All images are from public sources with permissive licenses.

Does the dataset contain data that might be considered offensive? Images depict everyday scenes. No images containing graphic violence, nudity, or hate speech were included.

Does the dataset relate to people? Some images depict people in public or staged settings. No personally identifiable information is associated with any instance.

Collection Process

How was the data associated with each instance acquired? Images were collected from the web (MIT/CC-BY 4.0) and from COCO and VCR. Questions and answers were authored by human annotators following the protocol in Sections A.1–A.4.

Who was involved in the data collection process? Graduate students in computer science at the authors' institution (see Section A.6).

Over what timeframe was the data collected? Approximately four months in 2025–2026.

Were any ethical review processes conducted? No formal IRB review was required, as the study involves standard annotation labor without human subjects experimentation.

Preprocessing, Cleaning, and Labeling

Was any preprocessing/cleaning/labeling of the data done? Yes. Multi-stage quality control: Fleiss' κ-based agreement filtering, expert review of 20% subsample, and systematic correction of recurring error patterns (Section A.4).

Was the "raw" data saved in addition to the preprocessed data? Raw annotations before filtering are retained internally but not publicly released.

Is the software used to preprocess/clean/label the data available? The filtering and agreement computation scripts will be released with the dataset.

Uses

Has the dataset been used for any tasks already? Yes. This paper uses it to benchmark 14+ VLMs on imagination-driven reasoning and to train LoRA-based fine-tuned models.

What (other) tasks could the dataset be used for? Fine-tuning VLMs for imagination capabilities, studying the perception–imagination gap in multimodal models, curriculum learning, and probing individual cognitive dimensions.

Are there tasks for which the dataset should not be used? Training surveillance or monitoring systems; drawing conclusions about human cognitive abilities from model performance; any application that could harm individuals depicted in images.

Distribution

How will the dataset be distributed? Publicly released upon acceptance. URL withheld for anonymous review.

Will the dataset be distributed under a license? Annotations: CC-BY-NC-4.0. Images are subject to their original source licenses (CC-BY 4.0 for COCO and web images; research-only for VCR).

Do any export controls or other regulatory restrictions apply? No, to the best of our knowledge.

Maintenance

Who will be supporting/hosting/maintaining the dataset? The authors' research group (contact details withheld for review).

Will the dataset be updated? Errors discovered after release will be documented and corrected in versioned updates. All versions will remain available for reproducibility.

If others want to extend/build on the dataset, is there a mechanism for them to do so? Community contributions are welcome via the project's GitHub repository, which will be made available upon acceptance.

B Implementation Details

B.1 Prompts

To avoid prompting artifacts that may artificially improve reasoning performance, we enforce a strict direct-answer format for all models during evaluation.

Standardized Prompt Template

```
{image(s)}

{question}

Only provide the answer; no reasoning steps
in the answer.
If you are unsure, still provide an answer.

Answer:
```

LLM-Based Evaluator Prompt

Role
```
You are an AI Judge.  Compare the Model
Prediction with the Ground Truth.
```

Context
```
Question: "{question}"
Ground Truth: "{gt}"
Model Prediction: "{pred}"
```

Task

- Determine how well the `Model Prediction` matches the `Ground Truth` semantically.

- Ignore differences in case, punctuation, or minor phrasing.

- Score correctness on a continuous scale: 0.0 (totally wrong) to 1.0 (totally right), using increments of 0.1 only. Example valid scores: 0.0, 0.1, 0.2, ..., 0.9, 1.0.

- Choose the closest score that reflects the semantic match quality.

- `<AND>` requires all components to be present in the prediction.

- `<OR>` requires any one valid component to be present.

Output Format
```
{"score": 0.0  // one of 0.0, 0.1, ...,
0.9, 1.0}
```

Due to the open-ended nature of free-form answers, we employ an LLM-based judge to evaluate whether model predictions semantically match the reference answers. The judge scores each prediction on a continuous scale from 0.0 to 1.0, allowing partial credit for responses that are directionally correct but imprecise. Ground truth answers may include logical connectives: `<AND>` requires all stated components to be present, while `<OR>`

accepts any one valid component as sufficient for full credit.

For the error analysis described in Section **??**, we re-query Gemini-3-Flash with a chain-of-thought elicitation prompt that forces the model to externalize its reasoning across five ordered cognitive stages — textual understanding, perception, knowledge, reasoning, and execution — before committing to a final answer. This structured trace allows human annotators to identify the earliest stage at which an error can be pinpointed, following the sequential waterfall protocol described in Appendix C.6.

Chain-of-Thought Elicitation Prompt (Error Analysis)

```
{image(s)}

{question}

Before giving your final answer, reason
through the following cognitive
steps in order. Each step must be addressed
explicitly.
```

Step 1 — Textual Understanding:
```
What does the question ask? Identify all
key entities, constraints, and
conditions stated in the text.
```

Step 2 — Perception:
```
Describe what you observe in the image
relevant to the question. List all
visual    elements,    their    spatial
relationships, quantities, and states.
```

Step 3 — Knowledge:
```
What background knowledge or commonsense
facts are needed to answer
this question? State any relevant world
knowledge explicitly.
```

Step 4 — Reasoning:
```
Given  your  observations  and  knowledge
above, reason step-by-step toward
the answer. Apply any necessary inference,
simulation, or counterfactual
logic here.
```

Step 5 — Execution:
```
Formulate your final answer clearly and
concisely based solely on the
reasoning above.

Answer:
```

B.2 Hyperparameters

We used same setting and configurations for model evaluation in Tab. 7 and reported all hyperparameters we used to train 2 VLMs, Qwen and InternVL model, as follows:

Table 7: **Hyperparameters used in model decoding setting**.

Hyperparameter	Greedy Decoding (Main Evaluation)
Temperature	0.0
Top-k	1
Top-p	–
Seed	42
Number of Runs	1

Table 8: **Hyperparameters used to finetune models**.

Hyperparameter	InternVL3-8B LoRA	Qwen3.5-9B (4-bit) QLoRA
Epochs	2	2
GPUs	2×A6000 48GB	1×A6000 48GB
Per-device batch size	1	4
Gradient accumulation	4	4
Effective batch size	8	16
Learning rate	4e-5	3e-5
LR scheduler	cosine	cosine
Warmup ratio	0.03	0.03
Weight decay	0.05	0.00
Precision	bf16	fp16
Image size	448×448	448×448
Optimizer	AdamW	AdamW
Text encoder	trainable	trainable
Vision encoder	frozen	frozen
MLP projector	frozen	frozen
Base LLM weights	frozen	frozen
LoRA rank r	16	16
LoRA alpha	32	32
LoRA dropout	0.05	0.05
Trainable params	40,370,176	116,391,936
Total params	7,653,191,168	5,841,364,208
Trainable ratio	0.527%	1.993%

B.3 Models

To ensure full reproducibility, we report the exact model versions or checkpoints used in our experiments. For proprietary models accessed through APIs, we provide the official API identifiers. For open-source models, we report the exact Hugging-Face repository names or checkpoint identifiers whenever available.

Proprietary Models

- GPT-5 Mini: `gpt-5-mini`

- Gemini 3 Flash: `gemini-3-flash-preview`

Open-weighted Vision–Language Models

- Gemma 4 31B : `google/gemma-4-31B-it`

- Ovis2-34B: `AIDC-AI/Ovis2-34B`

- Qwen3-VL 32B Instruct: `Qwen/Qwen3-VL-32B-Instruct`

- Qwen3.5-4B: `Qwen/Qwen3.5-4B`

- Molmo 72B: `allenai/Molmo-72B-0924`

- InternVL3.5 38B: `OpenGVLab/InternVL3_5-38B`

- InternVL3 8B: `OpenGVLab/InternVL3-8B`

- Kimi-VL A3B Instruct: `moonshotai/Kimi-VL-A3B-Instruct`

- 360VL 70B: `qihoo360/360VL-70B`

- LLaVA-OneVision 7B: `llava-hf/llava-onevision-qwen2-7b-ov-hf`

- LLaVA-NeXT-Yi-34B: `llava-hf/llava-v1.6-34b-hf`

- IDEFICS2 8B: `HuggingFaceM4/idefics2-8b`

B.4 Evaluation Protocol and Meta-Evaluation

Meta-Evaluation of the LLM Judge. To ensure our automated evaluation strictly aligns with human judgment, we first conduct a meta-evaluation of the LLM-as-judge protocol. We randomly sample a subset of 100 instances and obtain human-annotated binary scores (correct/incorrect) for various model predictions. We then compare these gold-standard human scores against three automated evaluation setups: Gemini-only (Gemini-3-Flash), GPT-only (GPT-4o), and a GPT+Gemini ensemble (where the final score is the average of both models' outputs). We calculate the average absolute difference ($\bar{\Delta}$) between the automated evaluation scores and the human-annotated scores. A smaller discrepancy $\bar{\Delta}$ indicates stronger agreement with the human gold standard. The configuration yielding the lowest $\bar{\Delta}$ was selected as our primary evaluator for the main experiments.

Full Benchmark Evaluation. For the full ImagineBench evaluation, the selected judge determines whether an anonymized prediction is semantically equivalent to the reference answer. The evaluator is explicitly instructed to focus on semantic correctness and reasoning intent, ignoring minor variations in surface form, case, or punctuation. The judge assigns a continuous score from 0.0 to 1.0

Metric	Gemini Only	GPT Only	Ensemble (GPT + Gemini)
$\bar{\Delta}(\downarrow)$	0.06	0.09	0.07

Table 9: Averaged absolute differences ($\bar{\Delta}$) between various automated LLM evaluators and human-annotated scores on a random subset of 100 instances. A lower discrepancy indicates stronger agreement with the human gold standard.

Category	Human	Best Model	Gap
Counterfactual State	91.20	65.93	25.27
Event Progression	94.33	75.33	18.99
Functional Intent	89.50	76.35	13.15
Perspective Transf.	93.10	71.50	21.60
Structural Completion	88.75	50.66	38.09
Overall	**91.38**	**67.42**	**23.96**

Table 10: Human baseline vs. best foundation model (Gemini-3-Flash) per category. Gap = human $-$ model accuracy in percentage points.

in increments of 0.1; a score ≥ 0.5 is classified as a correct prediction. Full evaluation prompts provided to the LLM judge can be found in Section B.1.

Hardware. Open-source models are evaluated on servers equipped with either $2\times$ NVIDIA RTX A6000 48GB or $2\times$ NVIDIA A100 80GB SXM GPUs. Proprietary models are accessed through their official APIs. Fine-tuned variants use LoRA-based supervised fine-tuning on the ImagineBench training split, with training configurations detailed in Section B.2.

B.5 Human Performance Baseline

We report a human baseline on the same held-out validation split as a reference ceiling.

Participants. We recruited 5 human volunteers (N=5) from the authors' institution, comprising both undergraduate and graduate students with computer science backgrounds. All participants were familiar with visual reasoning tasks but had no prior exposure to ImagineBench, and none were involved in the construction or annotation of the benchmark (i.e., they are disjoint from the annotation team described in Section A.6). The 1,988 validation samples were evenly distributed across the five volunteers, with each participant answering approximately 398 questions. Each question was answered by a single participant.

Protocol. Each volunteer was shown an image and a question from the validation set and asked to provide a free-form answer. The same prompt template used for model evaluation was provided to participants for consistency. Participants were allowed unlimited time per question. No external tools, search engines, or reference materials were permitted.

Evaluation. Human answers were evaluated using the same LLM-as-judge protocol (Gemini-3-Flash) and the same scoring threshold (≥ 0.5) as model predictions, ensuring a directly comparable evaluation pipeline. As shown in Section B.4, our meta-evaluation on 100 randomly sampled instances yields an average absolute discrepancy of only $\bar{\Delta} = 0.06$ between the LLM judge and human-annotated gold-standard scores, confirming that the automated evaluator closely tracks human judgment and is unlikely to systematically over- or under-estimate human performance.

Per-category results. Table 10 reports the per-category human baseline alongside the best foundation model for direct comparison.

Analysis. Humans perform consistently across categories (range: 88.75%–94.33%, a spread of 5.58 pp), whereas the best model shows high variance (range: 50.66%–76.35%, a spread of 25.69 pp). This contrast suggests that imagination ability in humans is uniformly developed across cognitive operations, while current VLMs have sharply uneven capabilities.

The human–model gap varies substantially by category. Structural Completion shows the largest gap (38.09 pp), confirming that amodal completion of hidden structure is the most deficient capability in current models. Functional Intent shows the smallest gap (13.15 pp), suggesting that inferring object purpose from visual configuration is the imagination subskill closest to being addressed by current architectures. Counterfactual State (25.27 pp gap) is notably harder for models than Event Progression (18.99 pp), likely because counterfactual reasoning requires an additional hypothetical intervention step beyond simple temporal extrapolation.

Category	Count			Proportion (%)		
	Easy	Med.	Hard	Easy	Med.	Hard
Counterfactual State	109	207	101	26.1	49.6	24.2
Event Progression	14	140	145	4.7	46.8	48.5
Functional Intent	0	267	292	0.0	47.8	52.2
Perspective Transformation	254	16	108	67.2	4.2	28.6
Structural Completion	24	159	152	7.2	47.5	45.4
Overall	401	789	798	20.2	39.7	40.1

Table 11: Distribution of difficulty tiers across imagination categories. Functional Intent stands out with the highest concentration of Hard items (52.2%), reinforcing that goal-oriented, off-screen reasoning poses a systemic challenge to current architectures.

C   More Quantitative Results

This appendix dissects item difficulty across the five ImagineBench categories, isolating per-taxonomy distributions and fine-grained model performance on the Hard tier. All metrics are computed on the validation split ($N = 1,988$) and adhere strictly to the tier boundaries established in the main text.

C.1   Difficulty Tier Definition

We stratify the benchmark by model consensus, using the number of correct predictions k (out of 10 evaluated foundation VLMs) as a proxy for complexity:

$$\text{Easy} : k \geq 8$$
$$\text{Medium} : 5 \leq k \leq 7$$
$$\text{Hard} : k \leq 4$$

This partitioning yields 401 Easy items, 789 Medium items, and 798 Hard items.

C.2   Per-Category Difficulty Distribution

Table 11 provides a raw count and proportional breakdown of these tiers across individual imagination categories.

Core Insights. The distribution exposes a profound rift between spatial-geometric tracking and intent understanding. *Perspective Transformation* stands alone as the only category dominated by Easy items (67.2%). This high success rate stems from the fact that many viewpoint shifts yield a single, geometrically verifiable solution if the visible clues are sufficient. Intriguingly, this category exhibits a stark bimodal cliff, dropping to just 4.2% in the Medium tier, meaning these tasks are either immediately trivial or entirely intractable for current systems, with almost no middle ground.

Conversely, *Functional Intent* represents a hard floor for current VLMs, yielding *zero* Easy items.

Category	Univ. Hard	% of Hard
Counterfactual State	20	19.8
Event Progression	41	28.3
Functional Intent	95	32.5
Perspective Transformation	20	18.5
Structural Completion	37	24.3
Total	213	26.7

Table 12: Breakdown of Universally Hard items (0 out of 10 models correct). Functional Intent leads both in absolute volume and within-category density (32.5%).

This complete absence confirms that surface-level pattern matching or visual lookup is fundamentally insufficient for purpose-driven queries. With over half of its distribution (52.2%) classified as Hard, Functional Intent serves as the truest barometer for whether a model can reason beyond the frame.

C.3   Universally Hard Items

To isolate the absolute ceiling of the benchmark, we analyze the **Universally Hard** subset: the 213 items (26.7% of the Hard tier) that defeated all 10 foundation models simultaneously. Table 12 maps their distribution.

These items map the current boundary of visual intelligence. Defying scale, architectural variations, and proprietary training regimes alike, these failures point to a systemic deficit in mental simulation. Solving them requires complex, multi-step operations, such as amodal completion or rolling counterfactual inferences, that cannot be bypassed via statistical shortcuts. They remain an open invitation for future modeling paradigms.

C.4   Per-Model Accuracy on the Hard Tier by Category

Table 13 isolates performance on the Hard tier to evaluate how models handle the long tail of the benchmark.

The granular breakdown highlights several stark behaviors:

- **A uniform performance floor:** Overall accuracy peaks at just 15.9%, plummeting from the near-95% convergence seen on Easy items. This collapse confirms that Hard items demand a fundamentally different tier of cognitive processing.

- **Gemini-3-Flash's spatial edge:** Gemini-3-Flash dominates Perspective Transformation (38.9%), nearly doubling the average

Model	CF (n=101)	Event (n=145)	Func. (n=292)	Persp. (n=108)	Struct. (n=152)	Overall (n=798)
Proprietary models						
Gemini-3-Flash	25.8	9.7	6.1	**38.9**	18.0	15.9
GPT-5-mini	15.3	5.1	4.3	18.2	7.8	8.3
Open-source models						
360VL-70B	14.8	**16.8**	**14.4**	10.9	**20.5**	**15.5**
Gemma-4-31B-it	**24.2**	8.0	5.3	23.3	10.3	11.5
LLaVA-NeXT-Yi-34B	8.3	12.5	5.7	10.3	19.8	10.6
Kimi-VL-A3B	8.5	7.1	5.9	17.5	7.8	8.4
InternVL3.5-38B	14.1	4.9	2.5	8.9	8.9	6.4
Molmo-72B	10.8	6.4	3.7	10.1	2.0	5.7
Qwen3-VL-32B	8.4	0.6	2.6	14.1	3.9	4.8
Ovis2-34B	6.0	3.2	4.6	4.9	3.1	4.3

Table 13: Model accuracy (%) restricted entirely to Hard-tier items. CF = Counterfactual State; Func. = Functional Intent; Persp. = Perspective Transformation; Struct. = Structural Completion. Bold values indicate the top performer per column.

open-source score. This indicates significantly stronger geometric grounding and view-simulation capabilities.

- **360VL-70B's robust tail calibration:** Despite trailing on the full validation set, 360VL-70B secures the highest open-source Hard accuracy (15.5%) and leads across three categories (Event, Functional, Structural). This suggests a training distribution or architecture that is better calibrated for complex, low-frequency reasoning.

- **The Functional Intent bottleneck:** No model breaks past 14.4% on Functional Intent. This cross-architecture struggle solidifies purpose-driven, off-screen inference as the primary roadblock for contemporary VLMs.

C.5 Qualitative Nuances of the Difficulty Tiers

To anchor these numerical boundaries in tangible behaviors, we conducted a manual audit of 50 sampled items from both the Easy and Hard tiers.

Easy items typically present a closed, explicit problem space. The hypothetical change requested leaves exactly one visually verifiable answer that can be deduced from a single prominent element in the image, requiring zero mental alteration of the scene (e.g., *"If one horse walks away from the two visible, how many remain?"* requires basic arithmetic on existing visual counters). These items

verify text-image alignment and syntax comprehension rather than genuine simulation.

Hard items, by contrast, trigger an immediate failure in simple lookup strategies, requiring one or more of the following capabilities:

1. **Spatial relational simulation:** Mentally translocating an object or viewpoint and projecting the resulting occlusions or orientations.

2. **Amodal completion:** Inferring the unrendered segments of a scene and evaluating how transformations alter these hidden components.

3. **Multi-step counterfactual chaining:** Maintaining multiple hypothetical variables simultaneously in working memory and accurately tracking their cascading consequences.

4. **Fine-grained perceptual precision:** Resolving hyper-specific visual details, such as exact spatial intervals or micro-counts, where low-resolution embeddings fail.

This qualitative audit clarifies our main error analysis: the friction in Hard items is overwhelmingly a failure of *reasoning and simulation*, not of coarse perception or text parsing. The bottleneck remains the core engine of imagination itself.

Figure 5: Error distributions across the five ImagineBench task taxonomies for Gemini-3-Flash. Each pie chart corresponds to one task category, with slices representing the proportion of errors attributable to each cognitive failure mode: perception, reasoning, knowledge, execution, and textual understanding.

C.6 Extended Error Analysis

Figure 5 extends the aggregate analysis from Section 4.3 by breaking down the error distribution across each of the five ImagineBench task taxonomies: Structural Completion, Perspective Transformation, Event Progression, Functional Intent, and Counterfactual State. This per-taxonomy view reveals that while reasoning errors dominate overall, the relative contribution of each failure mode varies considerably depending on the type of imaginative reasoning demanded.

Structural Completion. In Structural Completion tasks, errors are distributed most broadly among the five categories, with perception (42.05%) constituting the plurality of failures. This is consistent with the nature of the task: correctly completing a structure from a partially observed scene requires precise spatial grounding. Reasoning errors (27.27%) and knowledge errors (23.86%) form the secondary cluster, with execution and textual failures accounting for a negligible share. The prominence of perceptual errors here suggests that current VLMs struggle to form sufficiently accurate spatial representations before reasoning can even begin.

Perspective Transformation. Perspective Transformation sees a marked shift toward reasoning dominance, with 68.63% of errors attributable to reasoning failures, the highest proportion of any taxonomy. Perception errors fall to 19.61%, and knowledge errors account for only 7.84%. This pattern indicates that the bottleneck is not in perceiving the scene but in mentally simulating the consequences of a viewpoint change. The model may correctly identify the objects and their arrangement, yet fail to apply the appropriate geometric transformation to derive the expected outcome. The low perceptual error rate confirms that this category is genuinely testing higher-order simulation rather than visual acuity.

Event Progression. Event Progression errors split primarily between reasoning (50.00%) and perception (28.95%), with knowledge errors at 15.79%. Temporal prediction requires the model to infer how a scene will evolve given its initial state, calling on both visual understanding and causal reasoning. The moderate perceptual contribution reflects that event inference is sensitive to correctly identifying the state of dynamic elements (e.g., motion, contact, physical configuration) before projecting forward. The absence of textual errors suggests that the linguistic component of these tasks poses minimal difficulty relative to the spatiotemporal reasoning they require.

Functional Intent. Functional Intent stands apart from all other taxonomies in its error profile: knowledge errors account for 48.28% of failures, by far the highest of any category, while reasoning and perception each contribute roughly a quarter (27.59% and 24.14%, respectively). This reflects the nature of the task: inferring why an object is arranged or used in a particular way requires drawing on encyclopedic knowledge about human practices, tool use, and artifact function. When this world knowledge is absent or incorrectly applied, reasoning cannot proceed correctly regardless of the quality of the visual percept. The result is a clear inversion of the typical taxonomy profile, making Functional Intent the most knowledge-bound category in ImagineBench.

Counterfactual State. Counterfactual State tasks exhibit a reasoning-heavy profile (53.85%) similar to Perspective Transformation and Event Progression, while also showing a noteworthy textual error contribution (6.15%), the highest of any taxonomy. Counterfactual reasoning requires the model to suppress the observed state of the world and reason from a hypothetical alternative, a cognitively demanding operation that appears to challenge both linguistic comprehension of the counterfactual premise and the subsequent causal chain derivation. The elevated textual error rate suggests that some failures originate in misinterpreting the conditional framing of the question, causing the model to reason correctly but from the wrong premise.

Cross-taxonomy patterns. Taken together, the per-taxonomy breakdowns expose a consistent hierarchy: reasoning is the dominant bottleneck in tasks requiring simulation or transformation (Perspective Transformation, Counterfactual State, Event Progression), while perception gates performance when spatial grounding is critical (Structural Completion), and knowledge is the primary barrier when the task demands real-world understanding of function and intent (Functional Intent). Execution and textual errors remain consistently low across all categories, confirming that the challenges ImagineBench poses are fundamentally cognitive rather than linguistic or formatting-related.

This taxonomy-level decomposition suggests that progress on ImagineBench will require targeted interventions rather than uniform capability improvements: better spatial grounding for Structural Completion, richer world-knowledge coverage for Functional Intent, and stronger causal and counterfactual simulation for the remaining categories. No single architectural change is likely to close the gap uniformly across all five task types.

D More Qualitative Results

E More Qualitative Results

List of samples

1. **Counterfactual State** If the first half of the pizza is eaten, how many pieces of pizza are left in the picture?

2. **Counterfactual State** If the person in the picture wasn't wearing a wetsuit, would they still fall into the water?

3. **Counterfactual State** If two candles are removed, how many candles are left?

4. **Counterfactual State** If an additional physical keyboard was added to the setup, how many keyboards would be in the picture?

5. **Counterfactual State** If the little bear moved in front of the big bear, where would it be from the camera's perspective?

6. **Counterfactual State** If no apples were cut, how many pieces would there be?

7. **Counterfactual State** If the person is not holding a cell phone, what is the person doing in the picture?

8. **Counterfactual State** If the person in the picture is not holding a cell phone, what is he doing?

9. **Counterfactual State** If the image showed a fleet of bicycles in the middle instead of an airplane, where would it be?

10. **Counterfactual State** If the pizza were cut into two equal halves, which one would be larger, one half of the pizza or the plate?

11. **Counterfactual State** If another slice were removed from the large plate, what shape would the remaining pizza be?

12. **Counterfactual State** If everyone except the skateboard holder puts on a cap, how many people are wearing caps in the picture?

13. **Event Progression** Should the taller girl release her grip, where would the umbrella shift to relative to the shorter girl's hands?

14. **Event Progression** Based on the tennis ball's current mid-air position and the player's follow-through posture, where will the ball be located in the next 1-2 seconds?

15. **Event Progression** Given the fire truck's forward momentum, where will its front bumper be positioned relative to the concrete barrier in the foreground in the next 1 second?

16. **Event Progression** As all three figures converge on the brick path by the pond, how will their formation shift in the next 2 seconds?

17. **Event Progression** As the person steps down from the truck cab, where will they be positioned relative to the man holding the door and the lamp post behind him?

18. **Event Progression** Based on the ball's current mid-air trajectory and the player, what will happen to the ball in the next second?

19. **Event Progression** If the standing person suddenly uses the hockey stick to push off the ground, in which direction will their upper body immediately lean?

20. **Event Progression** If the man in the light-colored coat in the foreground takes a step forward, where will his body be positioned relative to the crowd in the next 2 seconds?

21. **Functional Intent** What does this arrangement enable in practice?

22. **Functional Intent** Observe the design of the yellow pole on the tennis court. What is this setup mainly meant to do?

23. **Functional Intent** What practical role does this visible setup serve?

24. **Functional Intent** Observe the man on the left holding the metal device over his plate. What practical need does this motion address?

25. **Functional Intent** Observe the design of the bar stools. What is this setup mainly meant to do?

26. **Perspective Transformation** Imagine you are standing by the silver van in the background, looking directly at the elephant. Which specific side of the elephant would be facing you?

27. **Perspective Transformation** Imagine you are the man in the white shirt standing in the background, looking directly at the cow. Which specific side of the cow would be facing you?

28. **Perspective Transformation** Imagine you are the man in the black t-shirt looking directly at the woman sitting next to you. Which specific side of her body would be facing you?

29. **Perspective Transformation** Imagine you are standing in the dense green trees in the background, looking directly at the giraffe's head. Which specific side of its head would be facing you?

30. **Perspective Transformation** When you imagine yourself in a player's place, is his shadow visible to you?

31. **Perspective Transformation** Imagine you are standing in the exact position of the man in the suit, looking directly at the man in the purple shirt. Which side of his face would be directly facing you?

32. **Perspective Transformation** Considering both geometric alignment and orientation, is a dog positioned toward the right from a cat's standpoint?

33. **structural completion** Given the player's follow-through batting stance, which part of his body is hidden from view by his own torso?

34. **structural completion** Based on the player's follow-through swing, which specific facial features are definitively obscured from the camera's view by the arms and the bat?

35. **structural completion** Based on the position of the vertical car pillar, which specific part of the woman's upper body is hidden from view?

36. **structural completion** The man on the far left is cut off at the left edge of the frame. What physical extension must exist just beside this boundary?

37. **structural completion** Based on the camera's right profile angle, which specific anatomical parts of the man's head are definitively obscured from view by his own head?

38. **structural completion** Based on the position of the teddy bear wearing the hat, which specific anatomical part of the teddy bear on the left is completely hidden from view?

39. **structural completion** Based on the position of the sheep's head, which part of the woman's upper body is hidden from view?

40. **structural completion** Based on the position of the tennis racket, which specific facial features of the player are definitively obscured from view?

41. **structural completion** Looking at the orange flying frisbee in the center of the image, which specific body part of the boy wearing a white T-shirt and black pants (who is standing directly behind the frisbee's line of sight) is visually blocked by the frisbee?"

42. **structural completion** The wildebeest on the far right is partially cut off by the image frame. Which specific anatomical features of its head must logically exist immediately beyond the right boundary?

Question: If the first half of the pizza is eaten, how many pieces of pizza are left in the picture?

Taxonomy: Counterfactual State

Gemini 3 flash: 6
GPT 5 mini: 4
Gemma 4 31B: 4
Ovis2 34B: 4
InternVL3 8B: 5
InternVL3 8B Finetune: 5

Ground Truth: 4

Question: If the person in the picture wasn't wearing a wetsuit, would they still fall into the water?

Taxonomy: Counterfactual State

Gemini 3 flash: Yes.
GPT 5 mini: Yes
Gemma 4 31B: Yes
Ovis2 34B: Yes
InternVL3 8B: Yes
InternVL3 8B Finetune: yes

Ground Truth: no

Question: If two candles are removed, how many candles are left?

Taxonomy: Counterfactual State

Gemini 3 flash: 2
GPT 5 mini: 2
Gemma 4 31B: 2
Ovis2 34B: 2
InternVL3 8B: 3
InternVL3 8B Finetune: 2

Ground Truth: 3

Question: If an additional physical keyboard was added to the setup, how many keyboards would be in the picture?

Taxonomy: Counterfactual State

Gemini 3 flash: Answer: 3
GPT 5 mini: 3
Gemma 4 31B: 4
Ovis2 34B: 4
InternVL3 8B: 3
InternVL3 8B Finetune: 3

Ground Truth: 4

Question: If the little bear moved in front of the big bear, where would it be from the camera's perspective?

Taxonomy: Counterfactual State

Gemini 3 flash: left
GPT 5 mini: Between the camera and the big bear — closer to the camera.
Gemma 4 31B: To the left
Ovis2 34B: Closer to the camera
InternVL3 8B: left
InternVL3 8B Finetune: in front

Ground Truth: center

Question: If no apples were cut, how many pieces would there be?

Taxonomy: Counterfactual State

Gemini 3 flash: 1
GPT 5 mini: 0
Gemma 4 31B: 1
Ovis2 34B: 1
InternVL3 8B: 1
InternVL3 8B Finetune: 1

Ground Truth: 0

↑ Back to List of samples

Question: If the person is not holding a cell phone, what is the person doing in the picture?

Taxonomy: Counterfactual State

Gemini 3 flash: Taking a picture.
GPT 5 mini: taking a selfie
Gemma 4 31B: The person is holding a cell phone.
Ovis2 34B: The person is taking a mirror selfie with a different device.
InternVL3 8B: Taking a selfie
InternVL3 8B Finetune: standing

Ground Truth: looking in the mirror

Question: If the person in the picture is not holding a cell phone, what is he doing?

Taxonomy: Counterfactual State

Gemini 3 flash: Taking a picture.
GPT 5 mini: Taking a picture
Gemma 4 31B: The person in the picture is holding a cell phone.
Ovis2 34B: Taking a mirror selfie with a different device
InternVL3 8B: Taking a selfie
InternVL3 8B Finetune: looking in the mirror

Ground Truth: looking in the mirror

Question: If the image showed a fleet of bicycles in the middle instead of an airplane, where would it be?

Taxonomy: Counterfactual State

Gemini 3 flash: on the runway
GPT 5 mini: on the runway
Gemma 4 31B: "point": [682, 498]
Ovis2 34B: On the runway
InternVL3 8B: On the runway.
InternVL3 8B Finetune: left

Ground Truth: bike parking area

Question: If the pizza were cut into two equal halves, which one would be larger, one half of the pizza or the plate?

Taxonomy: Counterfactual State

Gemini 3 flash: one half of the pizza
GPT 5 mini: One half of the pizza
Gemma 4 31B: the plate
Ovis2 34B: One half of the pizza
InternVL3 8B: one half of the pizza
InternVL3 8B Finetune: half of the pizza

Ground Truth: the plate

Question: If another slice were removed from the large plate, what shape would the remaining pizza be?

Taxonomy: Counterfactual State

Gemini 3 flash: Circular
GPT 5 mini: semicircle
Gemma 4 31B: C-shape
Ovis2 34B: A pentagon
InternVL3 8B: Hexagon
InternVL3 8B Finetune: sector

Ground Truth: crescent

Question: If everyone except the skateboard holder puts on a cap, how many people are wearing caps in the picture?

Taxonomy: Counterfactual State

Gemini 3 flash: Answer: 6
GPT 5 mini: 5
Gemma 4 31B: 3
Ovis2 34B: 4
InternVL3 8B: 3
InternVL3 8B Finetune: 4

Ground Truth: 2

Question: Should the taller girl release her grip, where would the umbrella shift to relative to the shorter girl's hands?

Taxonomy: Event Progression

Gemini 3 flash: Answer: downward
GPT 5 mini: Downward and slightly toward the left, into the shorter girl's hands.
Gemma 4 31B: Downwards
Ovis2 34B: The umbrella would shift towards the taller girl's side.
InternVL3 8B: above
InternVL3 8B Finetune: The umbrella would shift downward and away from the shorter girl's hands, falling toward the ground between them.

Ground Truth: Dropping and leaning toward the shorter girl's side, with the canopy tilting down to roughly her shoulder height on the left.

Question: Based on the tennis ball's current mid-air position and the player's follow-through posture, where will the ball be located in the next 1-2 seconds?

Gemini 3 flash: On the tennis court.
GPT 5 mini: It will travel forward, cross the net, and bounce on the opponent's side slightly left of center near the service line.
Gemma 4 31B: Answer: Across the net on the opposite side of the court.
Ovis2 34B: The ball will be on the other side of the net, likely near the baseline.
InternVL3 8B: On the other side of the net.
InternVL3 8B Finetune: Hit the ground.

Ground Truth: Traveling over the net and landing in the opposite court, having been redirected by the player's backhand stroke away from the baseline area.

Question: Given the fire truck's forward momentum, where will its front bumper be positioned relative to the concrete barrier in the foreground in the next 1 second?

Taxonomy: Event Progression

Gemini 3 flash: Closer to the concrete barrier.
GPT 5 mini: The front bumper will pass the concrete barrier and be just beyond it (slightly to the right), clearing the barrier.
Gemma 4 31B: Further away from the concrete barrier.
Ovis2 34B: The front bumper will be past the concrete barrier.
InternVL3 8B: Closer to the concrete barrier.
InternVL3 8B Finetune: Closer to the barrier.

Ground Truth: Level with or just past the concrete barrier on the left, having closed most of the remaining distance along the driveway.

Question: As all three figures converge on the brick path by the pond, how will their formation shift in the next 2 seconds?

Taxonomy: Event Progression

Gemini 3 flash: The woman and the man in the light-colored suit will meet, while the man in black will move into a position directly behind her, creating a more compact and linear group.
GPT 5 mini: They'll close into a compact triangular grouping, with the man approaching stepping forward between and slightly behind the other two so all three are within arm's reach.
Gemma 4 31B: Answer: They will move closer together, forming a tighter group on the path.
Ovis2 34B: The man in the beige suit will turn to face the woman, and the man in the black suit will move closer to them, forming a triangular formation.
InternVL3 8B: The woman will step forward, the man in the suit will turn slightly towards her, and the man in the black suit will approach closer.
InternVL3 8B Finetune: The woman and man will stand side by side on the path, with the man's back to the camera and the woman facing him, while the man in the background closes the gap between them.

Ground Truth: Form a standing triangle on the brick path facing each other.

↑ Back to List of samples

Question: As the person steps down from the truck cab, where will they be positioned relative to the man holding the door and the lamp post behind him?

Taxonomy: Event Progression

Gemini 3 flash: In front of them.
GPT 5 mini: Between the man holding the door and the lamp post behind him.
Gemma 4 31B: Between the man holding the door and the lamp post.
Ovis2 34B: The person will be positioned to the right of the man holding the door and in front of the lamp post.
InternVL3 8B: In front of the man holding the door and the lamp post.
InternVL3 8B Finetune: On the sidewalk, between the man holding the door and the lamp post.

Ground Truth: Standing on the pavement between the open truck door and the lamp post, with the door holder just to their side and the lamp post directly behind them, all three elements — the exiting person, the door holder, and the post — compressed into the narrow strip of pavement between the truck and the kerb.

Question: Based on the ball's current mid-air trajectory and the player, what will happen to the ball in the next second?

Taxonomy: Event Progression

Gemini 3 flash: Answer: The ball will be hit by the player's racket.
GPT 5 mini: She will hit a backhand and return the ball over the net toward the opponent's side.
Gemma 4 31B: The player will hit the ball with the racket.
Ovis2 34B: The ball will be hit by the racket.
InternVL3 8B: The ball will be hit by the player.
InternVL3 8B Finetune: Hit the racket.

Ground Truth: Cross the net

Question: If the standing person suddenly uses the hockey stick to push off the ground, in which direction will their upper body immediately lean?

Taxonomy: Event Progression

Gemini 3 flash: Answer: Backward
GPT 5 mini: Backward
Gemma 4 31B: Backward
Ovis2 34B: Backwards
InternVL3 8B: Forward
InternVL3 8B Finetune: Forward.

Ground Truth: Lean away from stick.

Question: If the man in the light-colored coat in the foreground takes a step forward, where will his body be positioned relative to the crowd in the next 2 seconds?

Taxonomy: Event Progression

Gemini 3 flash: Answer: behind the crowd
GPT 5 mini: Directly into the crowd, standing in front of and partially obscuring the central group of people between the stalls.
Gemma 4 31B: He will be deeper into the crowd.
Ovis2 34B: The man in the light-colored coat will be closer to the crowd, likely positioned between the crowd and the leftmost stall, with his body oriented towards the crowd.
InternVL3 8B: In front of the crowd
InternVL3 8B Finetune: Further into the crowd.

Ground Truth: Deeper into the market.

Question: What does this arrangement enable in practice?

Taxonomy: Functional Intent

Gemini 3 flash: Answer: Anonymity
GPT 5 mini: To conceal her identity.
Gemma 4 31B: The woman's attire enables her to maintain anonymity and disguise her identity while moving through a public space.
Ovis2 34B: The arrangement enables the practice of capturing images.
InternVL3 8B: It enables the production of large quantities of goods with relatively little waste.
InternVL3 8B Finetune: To provide wind protection.

Ground Truth: To carry and protect camera equipment while keeping it easily accessible.

Question: Observe the design of the yellow pole on the tennis court. What is this setup mainly meant to do?

Taxonomy: Functional Intent

Gemini 3 flash: Adjust the net height for singles play.
GPT 5 mini: To serve as an obstacle/target simulating an opponent at the net so players practice passing shots and shot placement.
Gemma 4 31B: Answer: to hold tennis balls
Ovis2 34B: Support the net
InternVL3 8B: To mark the center of the court
InternVL3 8B Finetune: To mark the net height.

Ground Truth: To serve as training marker.

Question: What practical role does this visible setup serve?

Taxonomy: Functional Intent

Gemini 3 flash: Checkout counter for video rentals and a primary location for character interactions.
GPT 5 mini: A checkout/cashier counter for processing rentals/sales of videos (video rental transactions).
Gemma 4 31B: retail store checkout and customer service area
Ovis2 34B: Video rental
InternVL3 8B: selling
InternVL3 8B Finetune: To display merchandise for sale.

Ground Truth: To prohibit smoking inside the store.

Question: Observe the man on the left holding the metal device over his plate. What practical need does this motion address?

Taxonomy: Functional Intent

Gemini 3 flash: Sanitation/Hygiene (ensuring the cleanliness of his utensils)
GPT 5 mini: To season his food (sprinkle salt/pepper).
Gemma 4 31B: Seasoning food.
Ovis2 34B: The man is using a pepper grinder to season his food.
InternVL3 8B: To keep the plate warm
InternVL3 8B Finetune: To heat the food.

Ground Truth: To season his food.

Question: Observe the design of the bar stools. What is this setup mainly meant to do?

Taxonomy: Functional Intent

Gemini 3 flash: Make the actors look taller.
GPT 5 mini: Prevent patrons from moving the stools.
Gemma 4 31B: Provide seating for customers.
Ovis2 34B: Provide seating for patrons
InternVL3 8B: To allow patrons to sit close to the bar counter.
InternVL3 8B Finetune: To provide a stable seat.

Ground Truth: To facilitate temporary seating.

Question: Imagine you are standing by the silver van in the background, looking directly at the elephant. Which specific side of the elephant would be facing you?

Taxonomy: Perspective Transformation

Gemini 3 flash: Answer: right side
GPT 5 mini: The elephant's right side.
Gemma 4 31B: Right side
Ovis2 34B: The right side of the elephant would be facing you.
InternVL3 8B: The right side of the elephant would be facing you.
InternVL3 8B Finetune: The left side.

Ground Truth: The left side.

Question: Imagine you are the man in the white shirt standing in the background, looking directly at the cow. Which specific side of the cow would be facing you?

Taxonomy: Perspective Transformation

Gemini 3 flash: Left side
GPT 5 mini: the cow's right side
Gemma 4 31B: Right side
Ovis2 34B: The left side of the cow
InternVL3 8B: The head.
InternVL3 8B Finetune: The left side.

Ground Truth: The right side.

Question: Imagine you are the man in the black t-shirt looking directly at the woman sitting next to you. Which specific side of her body would be facing you?

Taxonomy: Perspective Transformation

Gemini 3 flash: Answer: right side
GPT 5 mini: Her right side
Gemma 4 31B: right
Ovis2 34B: Her right side
InternVL3 8B: Her left side.
InternVL3 8B Finetune: Her right side.

Ground Truth: Her left side.

Question: Imagine you are standing in the dense green trees in the background, looking directly at the giraffe's head. Which specific side of its head would be facing you?

Taxonomy: Perspective Transformation

Gemini 3 flash: Right side
GPT 5 mini: left side
Gemma 4 31B: Right side
Ovis2 34B: The right side of the giraffe's head would be facing you.
InternVL3 8B: Left side.
InternVL3 8B Finetune: The back side.

Ground Truth: Its left side.

Question: When you imagine yourself in a player's place, is his shadow visible to you?

Taxonomy: Perspective Transformation

Gemini 3 flash: Yes
GPT 5 mini: No
Gemma 4 31B: Yes
Ovis2 34B: No
InternVL3 8B: Yes
InternVL3 8B Finetune: No.

Ground Truth: No, under a player's egocentric frame of reference, his shadow is not visible.

Question: Imagine you are standing in the exact position of the man in the suit, looking directly at the man in the purple shirt. Which side of his face would be directly facing you?

Taxonomy: Perspective Transformation

Gemini 3 flash: Left side
GPT 5 mini: Right
Gemma 4 31B: Right
Ovis2 34B: Left
InternVL3 8B: Left side.
InternVL3 8B Finetune: His right side.

Ground Truth: The right side.

Question: Considering both geometric alignment and orientation, is a dog positioned toward the right from a cat's standpoint?

Taxonomy: Perspective Transformation

Gemini 3 flash: No
GPT 5 mini: yes
Gemma 4 31B: No
Ovis2 34B: No
InternVL3 8B: No
InternVL3 8B Finetune: Yes. The relative orientation between a dog and a cat indicates that a dog is to the right.

Ground Truth: That is accurate. If an observer occupied a cat's exact location, they would report a dog as being to their right.

Question: Given the player's follow-through batting stance, which part of his body is hidden from view by his own torso?

Taxonomy: structural completion

Gemini 3 flash: left arm
GPT 5 mini: right arm
Gemma 4 31B: Right arm
Ovis2 34B: The player's left hand
InternVL3 8B: Left leg
InternVL3 8B Finetune: His left hand.

Ground Truth: Right shoulder and arm.

Question: Based on the player's follow-through swing, which specific facial features are definitively obscured from the camera's view by the arms and the bat?

Taxonomy: structural completion

Gemini 3 flash: Nose and mouth
GPT 5 mini: Mouth (lips), chin, lower part of the nose, and lower cheeks
Gemma 4 31B: nan
Ovis2 34B: The player's eyes and mouth are definitively obscured from the camera's view by the arms and the bat.
InternVL3 8B: The player's eyes and mouth are obscured from the camera's view.
InternVL3 8B Finetune: Face and eyes.

Ground Truth: Eye and mouth

Question: Based on the position of the vertical car pillar, which specific part of the woman's upper body is hidden from view?

Taxonomy: structural completion

Gemini 3 flash: Right shoulder
GPT 5 mini: Her right eye
Gemma 4 31B: Shoulder
Ovis2 34B: The woman's right shoulder and upper arm are hidden from view.
InternVL3 8B: Her right shoulder and part of her right arm.
InternVL3 8B Finetune: Left shoulder and arm.

Ground Truth: Left shoulder.

Question: The man on the far left is cut off at the left edge of the frame. What physical extension must exist just beside this boundary?

Taxonomy: structural completion

Gemini 3 flash: his left arm
GPT 5 mini: an arm
Gemma 4 31B: The rest of his body.
Ovis2 34B: The man's left arm
InternVL3 8B: The man's body must extend just beside this boundary.
InternVL3 8B Finetune: His right arm.

Ground Truth: Right shoulder and arm

Question: Based on the camera's right profile angle, which specific anatomical parts of the man's head are definitively obscured from view by his own head?

Taxonomy: structural completion

Gemini 3 flash: his left eye and left ear
GPT 5 mini: Left eye, left eyebrow, left ear, left nostril/left side of the nose, left cheek, left temple, left jawline/side of chin, left side of mouth/lip, left side of forehead, left side of neck
Gemma 4 31B: Left ear, left eye, left cheek, left temple.
Ovis2 34B: The right eye, right ear, and right side of the nose.
InternVL3 8B: The left side of his face and the left side of his head.
InternVL3 8B Finetune: His left ear.

Ground Truth: right side of face.

Question: Based on the position of the teddy bear wearing the hat, which specific anatomical part of the teddy bear on the left is completely hidden from view?

Taxonomy: structural completion

Gemini 3 flash: Right ear
GPT 5 mini: the left teddy bear's right ear
Gemma 4 31B: Right ear
Ovis2 34B: The left ear
InternVL3 8B: Nose
InternVL3 8B Finetune: Left ear

Ground Truth: Its left ear.

Question: Based on the position of the sheep's head, which part of the woman's upper body is hidden from view?

Taxonomy: structural completion

Gemini 3 flash: right shoulder
GPT 5 mini: her left shoulder
Gemma 4 31B: the woman's right shoulder
Ovis2 34B: The woman's right shoulder
InternVL3 8B: Her right shoulder and part of her right arm.
InternVL3 8B Finetune: Left shoulder and chest.

Ground Truth: Left shoulder and arm

Question: Based on the position of the tennis racket, which specific facial features of the player are definitively obscured from view?

Taxonomy: structural completion

Gemini 3 flash: Right eye, right cheek, and bridge of the nose.
GPT 5 mini: Nose, mouth and chin
Gemma 4 31B: eyes, nose, and mouth
Ovis2 34B: The player's right eye and part of the nose are definitively obscured from view.
InternVL3 8B: Her eyes and nose.
InternVL3 8B Finetune: Left eye and nose.

Ground Truth: Left of her face

↑ Back to List of samples

Question: Looking at the orange flying frisbee in the center of the image, which specific body part of the boy wearing a white T-shirt and black pants (who is standing directly behind the frisbee's line of sight) is visually blocked by the frisbee?"

Taxonomy: structural completion

Gemini 3 flash: Stomach
GPT 5 mini: torso
Gemma 4 31B: leg
Ovis2 34B: The boy's head
InternVL3 8B: His right arm.
InternVL3 8B Finetune: His right arm.

Ground Truth: His hip.

Question: The wildebeest on the far right is partially cut off by the image frame. Which specific anatomical features of its head must logically exist immediately beyond the right boundary?

Taxonomy: structural completion

Gemini 3 flash: Answer: right ear and right horn
GPT 5 mini: The wildebeest's muzzle (nose and nostrils), mouth and lower jaw/chin, the right cheek and eye, the remainder/tips of its horns, and its right ear.
Gemma 4 31B: The right ear and the right side of its muzzle.
Ovis2 34B: The right ear, part of the right horn, and the right eye.
InternVL3 8B: Eyes, ears, and horns.
InternVL3 8B Finetune: Horns and forehead.

Ground Truth: Left ear and horn.