Mean Estimation with User-level Privacy under Data Heterogeneity

Abstract

A key challenge in many modern data analysis tasks is that user data is heterogeneous. Different users may possess vastly different numbers of data points. More importantly, it cannot be assumed that all users sample from the same underlying distribution. This is true, for example in language data, where different speech styles result in data heterogeneity. In this work we propose a simple model of heterogeneous user data that differs in both distribution and quantity of data, and we provide a method for estimating the population-level mean while preserving user-level differential privacy. We demonstrate asymptotic optimality of our estimator and also prove general lower bounds on the error achievable in our problem. In particular, while the optimal non-private estimator can be shown to be linear, we show that privacy constrains us to use a non-linear estimator.

1 Introduction

Many practical problems in statistical data analysis and machine learning deal with the setting in which each user generates multiple data points. In such settings the distribution of each user's data may be (somewhat) different and, furthermore, users may possess vastly different numbers of samples. This issue is one the key challenges in federated learning [19] leading to considerable interest in models and algorithms that address the issue.

As an example, consider the task of next-word prediction for a keyboard. Different users typing on a keyboard may have different styles of writing, leading to different distributions. There are aspects of the language that are common to all users, and likely additional aspects of style that are common to large groups of users. Thus while each user has their own data distribution, there are commonalities to all the distributions, and additional commonalities amongst distributions corresponding to subsets of users. Modeling and learning such relationships between users' distributions is crucial for building a better global model as well as for personalizing models for users.

The focus of this work is on differentially private algorithms for such settings. We assume that there is an unknown global meta-distribution $\mathcal{D}^\star$. For each user i, a personal data distribution $\mathcal{D}_i$ is chosen randomly from $\mathcal{D}^\star$ (for example, by sampling a set of parameters that define $\mathcal{D}_i$). Each user then receives some number k_i of i.i.d. samples from $\mathcal{D}_i$. The goal is to solve an analysis task relative to $\mathcal{D}^\star$, with an eye towards better modeling of each $\mathcal{D}_i$ even when k_i is small. This abstract setting can model many practical settings where the relationships between the $\mathcal{D}_i$'s take different forms. Indeed the standard loss in Federated learning is the unweighted average over users of a per-user loss function [19, Sec. 3.3.2]., which corresponds to learning $\mathcal{D}^\star$. Little theoretical work has been done in this setting and even the most basic statistical tasks are poorly understood. Thus we start by focusing on the fundamental problem of mean estimation in this setting. Specifically, in our model, $\mathcal{D}^\star$ is a distribution on the interval $[0, 1]$ with unknown mean p and unknown variance σ_p^2. Further, we assume that $\mathcal{D}_i$ is simply a Bernoulli distribution with mean $p_i \sim \mathcal{D}^\star$. Each sample from the

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Bernoulli distribution could represent whether or not the user has clicked on an ad shown in an app. Users are likely to use the app with different frequency and the probability of clicking on an ad is likely to vary among users.

Our main contribution is a differentially private algorithm that estimates p and σ_p in this setting. We first study this question in an idealized setting with known σ_p and no privacy constraints. Here the optimal non-private estimator for p_i is simple and linear: it is a weighted linear combination of the individual user means with weights that depend on the k_i's and on σ_p. The variance of this estimate is $\sigma_{ideal}^2 \approx (\sum_i \min(k_i, \sigma_p^{-2}))^{-1}$. This expression has a natural interpretation: this is the variance from using $\min(k_i, \sigma_p^2)$ samples from user i and averaging all the Bernoulli samples thus obtained. The restriction on using at most σ_p^{-2} samples from each user ensures that the estimator is not too affected by their individual mean p_i.

We show that under mild assumptions, there is no asymptotic price to privacy (and to not knowing σ_p). We provide a differentially private estimator for p with variance $O(\sigma_{ideal}^2)$. Interestingly, the estimator achieving this bound in the private setting is non-linear. Further, we show that σ_{ideal}^2 is near-optimal, under some mild technical conditions.

Our technical results highlight several of the challenges associated with ensuring user-level privacy when data is heterogeneous. For example, the optimal choice of weights for each user contribution itself depends on p and σ_p that we are trying to estimate. Further, we show a novel approach to proving lower bounds for private statistical estimation in the heterogenous setting. Our approach builds on the proof of the Cramer-Rao lower bound in statistics and we show how privacy terms can be incorporated in this approach to show near optimality of our algorithms for nearly every setting of k_i's. These tools and insights should be useful for modeling and designing algorithms for more involved data analysis tasks.

Our work lays the foundation for similar model-driven exploration in other settings. There have been attempts to handle heterogeneity by phrasing the problem as meta-learning or multi-task learning [19, Sec 3.3.3], which implicitly makes some assumptions about the different distributions. Our goal is to start with a more principled approach that makes explicit the assumptions on the relationship between different distributions and use that to derive the algorithm. For example, if were to model the D_i's as having means coming from a mixture of Gaussians, the estimation of cluster means would be a necessary step in an EM-type algorithm. Our choice of $\mathcal{D}_i$'s being Bernoulli is meant to capture discrete distribution learning problems that have been extensively studied in private federated settings. Our techniques are general and would extend naturally to real-valued settings where, e.g., $\mathcal{D}_i$ is a Gaussian with mean p_i and known variance. While we make minimal assumptions on $\mathcal{D}^\star$, our results asymptotically match the lower bounds for the case case of $\mathcal{D}^\star$ being Gaussian with known variance. Our techniques also extend in natural ways to higher dimensions.

1.1 Related Work

Frequency Estimation in the example-level privacy model has been well-studied in the central [13, 12] and local models [17, 14, 8, 1, 2]. Similarly, private mean estimation has been well studied in both central [13, 15] and local models [10, 9, 5] of privacy. These works have focused on providing example-level privacy (rather than user-level) in settings with homogeneous data, i.e., i.i.d. samples.

Liu et al. [22] recently studied the problem of learning discrete distributions in the homogeneous cases (same distribution and same number of samples per user) with user-level differential privacy and Levy et al. [21] extended such results to other statistical tasks. These works also consider the setting with different number of samples per user although only via a reduction to same number of samples by discarding the data of users that have less than the median number of samples and effectively only using the median number of samples from all the other users. This approach can be asymptotically suboptimal for many natural distributions of k_i's and is also likely to be worse in practice. Previously, McSherry and Mironov [25] showed how to build a (user-level) differentially private recommendation system, and McMahan et al. [24] showed how to train a language model with user-level differential privacy.

Mathematically, similar issues are addressed in meta-analysis [6, 31], where the heterogeneity comes from different studies instead of different users. The non-private approach of inverse variance weighting that we recap in Section 3 is standard in that context.

2 Model and Preliminaries

Let $\mathcal{D}$ be a distribution on $[0, 1]$ with (unknown) mean p and variance σ_p^2. We assume a population of $n \in \mathbb{N}$ users, where each user $i \in [n]$ has a hidden variable $p_i \sim \mathcal{D}$ and $k_i \in \mathbb{N}$ samples $x_i^1, \ldots, x_i^{k_i} \sim_{i.i.d.} Ber(p_i)$. That is, the samples of user i are i.i.d. from a Bernoulli distribution with parameter p_i, which we will denote $\mathcal{D}_i = Ber(p_i)$. Assume without loss of generality that individuals are sorted by their k_i, so that $k_1 \geq \cdots \geq k_n$. The samples x_i^j and hidden variables p_i of each user are unknown to the analyst, and we start with assuming that the k_i's are publicly known. In Appendix C, we extend our results to the general case where the k_i's are also private.

The analyst's goal is to estimate the population mean p with an estimator of minimum variance in a manner that is differentially private with respect to user data (p_i and $\{x_i^j\}$). Each user provides their own estimate of their p_i to the analyst based on their data x_i: $\widehat{p}_i = \frac{1}{k_i} \sum_{j=1}^{k_i} x_i^j$. The analyst can then aggregate these (possibly along with other information) into her estimate of p.

Let us first give some intuition for the distribution of these $\widehat{p}_i$. Let $\mathcal{D}(k)$ be the distribution that first samples $p_i \sim \mathcal{D}$, then samples $x_1, \cdots, x_k \sim Ber(p_i)$ and finally outputs $\widehat{p}_i = \frac{1}{k} \sum_{i=1}^{k} x_i$. The following lemma (proven in Appendix A) shows that the variance of $\widehat{p}_i$ is larger than σ_p^2 and transitions from $p(1-p)$ to σ_p^2 as k increases (equivalently as $\widehat{p}_i$ concentrates around p_i).

Lemma 2.1. *For all distributions $\mathcal{D}$ supported on $[0, 1]$ with mean p and variance σ_p^2, $\sigma_p^2 \leq p(1-p)$. Further, $\mathbb{E}[\mathcal{D}(k)] = p$ and $\mathrm{Var}(\mathcal{D}(k)) = \frac{1}{k} p(1-p) + \left(1 - \frac{1}{k}\right) \sigma_p^2$.*

We assume that k_i and p_i are independent, so the amount of data an individual has is independent of her data distribution. This is crucial for the problem setup: in order for learning from the heterogeneous population to be advantageous, there must a common meta-distribution is shared across all individuals in the population, rather than a meta-distribution only for each fixed k_i.

2.1 Differential Privacy

Differential privacy (DP) [13] informally limits the inferences that can be made about an individual as a result of computations on a large dataset containing their data. The definition of DP requires a pairwise *neighbouring relation* between datasets, and DP algorithms ensure that differences between all pairs of neighboring datasets should be hidden by the private algorithm.

In our setting where users have multiple data points, we must distinguish between *user-level* and *event-level* DP. The former considers D and D' neighbours if they differ on all data points associated with a single user, whereas the latter considers D and D' neighbours only if they differ on a *single* data point, regardless of the number of data points contributed by that user. Naturally, user-level DP provides substantially stronger privacy guarantees, and is often more challenging to achieve from a technical perspective. In this work, we will provide user-level DP guarantees.

Definition 2.2 (User-level (ϵ, δ)-Differential Privacy [13]). *Given $\epsilon \geq 0$, $\delta \in [0, 1]$ and a neighbouring relation $\sim$, a randomized mechanism $\mathcal{M} : \mathcal{X}^{k_1} \times \cdots \times \mathcal{X}^{k_n} \to \mathcal{Y}$ is (ϵ, δ)-differentially private if for all neighboring datasets $D \sim D' \in \mathcal{X}^{k_1} \times \cdots \times \mathcal{X}^{k_n}$, and all events $E \subseteq \mathcal{Y}$, $\Pr[\mathcal{M}(D) \in E] \leq e^\epsilon \cdot \Pr[\mathcal{M}(D') \in E] + \delta$, where the probabilities are taken over the random coins of $\mathcal{M}$. When $\delta = 0$, we refer to this as ϵ-differential privacy.*

One standard tool for achieving ϵ-differential privacy is the *Laplace Mechanism*. For a given function f to be evaluated on a dataset D, the Laplace Mechanism first computes $f(D)$ and then adds Laplace noise which depends on the *sensitivity* of f, defined for real-valued functions as $\Delta f = \max_{D, D' \text{ neighbors}} |f(D) - f(D')|$. The Laplace Mechanism outputs $\mathcal{M}_L(D, f, \epsilon) = f(D) + Lap(\Delta f/\epsilon)$ and is $(\epsilon, 0)$-DP.

3 A Non-Private Estimator

We begin by illustrating the procedure for computing an optimal estimator $\widehat{p}$ in the non-private setting. The general structure of the estimator will be the same in both settings. The analyst will compute the

---

Algorithm 1 Non-private Heterogeneous Mean Estimation

Input: number of users n, number of samples held by each user $(k_1, \ldots, k_n)$ $(k_i \geq k_{i+1})$, user-level estimates $(\widehat{p}_1, \cdots, \widehat{p}_n)$.

1: **Initial Estimates**
2: $\widehat{p}^{\text{initial}} = \sum_{i=9n/10}^{n} x_i^1$
3: $\widehat{\sigma}_p^2 = \frac{1}{\log n(\log n - 1)} \sum_{i,j \in [\log n]} (\widehat{p}_i - \widehat{p}_j)^2$

4: **Defining weights**
5: **for** $i = \log n$ to $9n/10$ **do**
6:     Compute $\widehat{\sigma}_i^2 = \frac{1}{k_i}(\widehat{p}^{\text{initial}} - (\widehat{p}^{\text{initial}})^2) + (1 - \frac{1}{k_i})\widehat{\sigma}_p^2$.
7:     $\widehat{w_i} = \frac{1/\widehat{\sigma}_i^2}{\sum_{j=\log n}^{9n/10} 1/\widehat{\sigma}_j^2}$

8: **Final Estimate**
9: **return** $\widehat{p}^{\text{realistic}} = \sum_{i=\log n}^{n} \widehat{w_i}\widehat{p}_i$

---

population-level mean estimate $\widehat{p}$ as a weighted linear combination of the user-level estimates $\widehat{p}_i$.[1] The key question is how to derive the weights so that individuals with more reliable estimates (i.e., larger k_i) have more influence over the final result.

Let σ_i^2 be the variance of $\widehat{p}_i$. In an idealized setting where the σ_i^2 are all known, the analyst can minimize the variance of the estimator by weighting each user's estimate $\widehat{p}_i$ proportionally to the inverse variance of their estimate. The weights are normalised to ensure the estimate is unbiased. This approach yields the following estimator, which is optimal in the non-private setting [16]:

$$\widehat{p}^{\text{ideal}} = \sum_{i=1}^{n} w_i^* \widehat{p}_i \text{ where } w_i^* = \frac{1/\sigma_i^2}{\sum_{j=1}^{n} 1/\sigma_j^2}. \tag{1}$$

In practice, the σ_i^2s are unknown, so the analyst must rely on estimates to assign weights. Fortunately, the user-level variance σ_i^2 can be expressed as a function of k_i and the population statistics p and σ_p^2, as shown in Lemma 2.1:

$$\sigma_i^2 = \frac{1}{k_i}(p - p^2) + (1 - \frac{1}{k_i})\sigma_p^2. \tag{2}$$

Now, p and σ_p^2 are also unknown but since they are population statistics, we can use simple estimators to obtain initial estimates. These initial statistics can then be used to define the weights, resulting in a refined estimate of the mean p. Specifically, as outlined in Algorithm 1, we split users into three groups. The $\log n$ individuals with the most data are used to produce an estimate of $\text{Var}(\mathcal{D}(k_{\log n}))$, which serves as a proxy for σ_p^2. The $1/10$th of individuals with the least data are used to produce an initial estimate of the mean p. The remaining $9n/10 - \log n$ individuals are used to produce the final estimate. We split the individuals into separate groups to ensure the initial estimates and the final estimate are independent so we can easily obtain variance bounds on the final estimate. The specific sizes of the three groups are heuristic, the exact fraction $1/10$ is not necessary. Under some mild conditions on $\mathcal{D}$, and if n is large enough, the error incurred by $\widehat{p}^{\text{realistic}}$ is within a constant factor of the error incurred by the ideal estimator $\widehat{p}^{\text{ideal}}$.[2]

4 A Framework for Private Estimators

We now turn to our main result, which is a framework for designing differentially private estimators for the mean p of the meta-distribution $\mathcal{D}$. We discussed in Section 3 the need for initial estimates of p and σ_p^2 to weight the contributions of the users. In the non-private setting, there are canonical, optimal choices of these estimators; the empirical mean and empirical variance. In the private setting, these choices are not canonical, and different estimators may perform better in different settings. There is a considerable literature exploring various mean and variance estimators for the homogeneous,

---

[1]In the non-private setting, this restriction is without loss of generality since the optimal estimator takes this form. In the private setting this is still near-optimal; see Section 5 for more details.

[2]This can be observed by viewing the non-private setting as a simplified version of the setting studied in Section 5, which proves near-optimality of (truncated) linear estimators for this problem.

164 single-data-point-per-user setting. As such, we leave the choice of the specific initial mean and
165 variance estimators as parameters of the framework. This allows us to focus on the nuances of the
166 heterogeneous setting, not addressed in prior work. In Appendix E, we give a specific pair of private
167 mean and variance estimators that provably perform well in our framework.

168 As in the previous section, we will define two estimators: a ideal estimator $\widehat{p}_\epsilon^{\text{ideal}}$ (only implementable
169 if all the σ_i^2 are known), and a realisable estimator $\widehat{p}_\epsilon^{\text{realistic}}$. The main result in this section (Theorem
170 4.1) is that under some mild conditions and assuming n is sufficiently large, there exists an (ϵ, δ)-DP
171 estimator $\widehat{p}_\epsilon^{\text{realistic}}$ (Algorithm 2) such that for some constant C, $\text{Var}(\widehat{p}_\epsilon^{\text{realistic}}) \leq C \cdot \text{Var}(\widehat{p}_\epsilon^{\text{ideal}})$.

4.1 The Complete Information Private Estimator

173 As in Section 3, we begin with a discussion of the ideal estimator if the σ_i were known. This ideal
174 estimator $\widehat{p}_\epsilon^{\text{ideal}}$ has a similar form to $\widehat{p}^{\text{ideal}}$ with some crucial differences. The first main distinction
175 is that Laplace noise is added to achieve DP, where the standard deviation of the noise must be scaled
176 to the sensitivity of the statistic. A natural solution would be to add noise directly to the non-private
177 estimator $\widehat{p}^{\text{ideal}}$, but the sensitivity of this statistic is too high. In fact, the worst case sensitivity of
178 $\widehat{p}^{\text{ideal}}$ is 1, which would result in the noise that completely masks the signal. Thus, the first change
179 we make is to limit the weight of any individual's contribution by setting $w_i = \frac{\min\{1/\sigma_i^2, T/\sigma_i\}}{\sum_{j=1}^n \min\{1/\sigma_j^2, T/\sigma_j\}}$
180 for some truncation parameter T. Intuitively, the parameter T controls the trade-off between variance
181 of the weighted sum of individual estimates (which is minimized by assigning high weight to low
182 variance estimators) and variance of the noise added for privacy (which is minimized by assigning
183 roughly equal weight to all users).

184 We make one final modification to lower the sensitivity of the statistic. Inspired by the Gaussian
185 mean estimator of [20], we truncate the individual contributions $\widehat{p}_i$ into a sub-interval of $[0, 1]$. The
186 truncation intervals $[a_i, b_i]$ are chosen to be as small as possible (to reduce the sensitivity and hence
187 the noise added for privacy), while simultaneously ensuring that $\widehat{p}_i \in [a_i, b_i]$ with high probability
188 (to avoid truncating relevant information for the estimation). In order to achieve this, we need a tail
189 bound on the distribution $\mathcal{D}$. To maintain generality for now, we assume there exists a known function
190 $f_\mathcal{D}^k(n, \sigma_p^2, \beta)$ that gives high-probability concentration guarantees of $\widehat{p}_i$ around p, and is defined such
191 that $\text{Pr}\left(\forall i, |\widehat{p}_i - p| \leq f_\mathcal{D}^{k_i}(n, \sigma_p^2, \beta)\right) \geq 1 - \beta$. Appendix F presents a more detailed discussion of
192 the structure of these concentration functions and how they may be estimated if they are unknown to
193 the analyst.

194 We can now describe the full information, or *ideal*, estimator $\widehat{p}_\epsilon^{\text{ideal}}$:

$$\widehat{p}_\epsilon^{\text{ideal}} = \sum_{i=1}^n w_i^* [\widehat{p}_i]_{a_i}^{b_i} + \text{Lap}\left(\frac{\max_i w_i^* |b_i - a_i|}{\epsilon}\right), \tag{3}$$

195 where $[\widehat{p}_i]_{a_i}^{b_i}$ denotes the projection of $\widehat{p}_i$ onto the interval $[a_i, b_i]$ and

$$a_i = p - f_\mathcal{D}^{k_i}(n, \sigma_p^2, \beta), \quad b_i = p + f_\mathcal{D}^{k_i}(n, \sigma_p^2, \beta), \quad \text{and} \quad w_i^* = \frac{\min\{1/\sigma_i^2, T^*/\sigma_i\}}{\sum_{j=1}^n \min\{1/\sigma_j^2, T^*/\sigma_j\}}. \tag{4}$$

196 We would like to choose the truncation parameter T^* to minimise the variance of the resulting
197 estimator:

$$\text{Var}(\widehat{p}_\epsilon^{\text{ideal}}) = \sum_{i=1}^n (w_i^*)^2 \text{Var}([\widehat{p}_i]_{a_i}^{b_i}) + \max_i \frac{(w_i^*)^2 |b_i - a_i|^2}{\epsilon^2}. \tag{5}$$

198 Although we do not know $\text{Var}([\widehat{p}_i]_{a_i}^{b_i})$ exactly, we do know that $[\widehat{p}_i]_{a_i}^{b_i} = \widehat{p}_i$ with high probability, and
199 thus we can approximate $\text{Var}([\widehat{p}_i]_{a_i}^{b_i})$ with σ_i. Throughout the remainder of the paper, we will assume
200 that β is chosen such that $\frac{1}{2}\sigma_i^2 \leq \text{Var}([\widehat{p}_i]_{a_i}^{b_i})$. Thus, we will approximate the optimal truncation
201 parameter by

$$T^* = \arg\min_T \sum_{i=1}^n (w_i^*)^2 \sigma_i^2 + \max_i \frac{(w_i^*)^2 |b_i - a_i|^2}{\epsilon^2}$$

$$= \arg\min_T \frac{1}{(\sum_{j=1}^n \min\{1/\sigma_j^2, T/\sigma_i\})^2} \left(\sum_{i=1}^n \min\{1/\sigma_i^2, T^2\} + \max_i \frac{\min\{1/\sigma_i^4, T^2/\sigma_i^2\} |b_i - a_i|^2}{\epsilon^2}\right). \tag{6}$$

We'll show in Section 5 that under some conditions on the Fisher information of $\mathcal{D}(k)$, $\widehat{p}_\epsilon^{\text{ideal}}$ is optimal up to logarithmic factors among all private unbiased estimators for heterogeneous mean estimation.

Example 1. *As a simple example, suppose that $p \in (\frac{1}{3}, \frac{2}{3})$, $\sigma_p = 1/\sqrt{n}$, and $k_i = \lceil \frac{n}{i} \rceil$. In this case, an asymptotically optimal non-private estimator averages all the $\sum k_i = O(n \log n)$ available samples. It can be shown that this gives us an unbiased estimator with standard deviation $\Theta(\frac{1}{\sqrt{n \log n}})$. A naive sensitivity-based noise addition method will give us privacy error $O(\frac{1}{\varepsilon \log n})$, since the weight of the first user in this average is $\Theta(1/\log n)$. Our truncation-based algorithm will truncate the ith user's contribution to a range of width $\sqrt{\frac{\log n}{k_i}} \approx \sqrt{\frac{i \log n}{n}}$. Applying our algorithm would then give us privacy error $\Theta(\frac{1}{\varepsilon \sqrt{n \log n}})$. In other words, for constant ε, privacy does not have an asymptotic cost. We remark that in this case, any uniform weighted average will incur asymptotically larger standard deviation $\Omega(\frac{1}{\sqrt{n}})$.*

4.2 Realizable Private Heterogeneous Mean Estimation

Our goal in this section is to design a realizable estimator $\widehat{p}_\epsilon^{\text{realistic}}$ that is competitive with the ideal estimator $\widehat{p}_\epsilon^{\text{ideal}}$. As in the non-private setting, we divide the individuals into three groups. The first group, consisting of the $n/10$ individuals with the lowest k_i will be used to compute the initial mean estimate $\widehat{p}_\epsilon^{\text{initial}}$. The $\log n$ individuals with the largest k_i will be used to compute the initial variance estimate $\widehat{\sigma}_p^2$. These initial estimates will be plugged into expressions to compute $\widehat{\sigma}_i^2$, $\widehat{a}_i$, and $\widehat{b}_i$ for the remaining individuals $\log n + 1 \leq i \leq 9n/10$. As in the non-private setting, the specific sizes of these groups are heuristic. The important thing is that the size of the first two groups are large enough that the resulting mean and variance estimates are sufficiently accurate, and the last group contains $\Theta(n)$-users whose k_i is above the median.

Since the estimate $\widehat{p}_\epsilon^{\text{initial}}$ used in $\widehat{a}_i$ and $\widehat{b}_i$ may had additional error up to α, we shift these estimates by an additive α to account for this error. Next, all of these intermediate estimates and the user-level mean estimates $\widehat{p}_i$ from users $\log n + 1 \leq i \leq 9n/10$ will be used to compute the optimal weight cutoff $\widehat{T}^*$, the optimal weights $\widehat{w}_i^*$ for each user $\log n + 1 \leq i \leq 9n/10$, and finally the estimator $\widehat{p}_\epsilon^{\text{realistic}}$ as a weighted sum of the truncated user-level estimates $[\widehat{p}_i]_{\widehat{a}_i}^{\widehat{b}_i}$ plus Laplace noise. This procedure is presented in full detail in Algorithm 2.

For the remainder of this section, we turn to establishing the accuracy requirements of $\texttt{mean}_{\epsilon,\delta}$ and $\texttt{variance}_{\epsilon,\delta}$ that ensure that the error of $\widehat{p}_\epsilon^{\text{realistic}}$ is within a constant factor of the error of $\widehat{p}_\epsilon^{\text{ideal}}$.

Theorem 4.1. *For any $\epsilon > 0$, $\delta \in [0,1]$, Algorithm 2 is (ϵ, δ)-DP. If,*

- *$\texttt{mean}_{\epsilon,\delta}$ is such that given $n/10$ samples from $\mathcal{D}$, with probability $1 - \beta$ $|p - \widehat{p}_\epsilon^{\text{initial}}| \leq f_{\mathcal{D}}^{k_i}(n, \sigma_p^2, \beta)$ and $\widehat{p}_\epsilon^{\text{initial}}(1 - \widehat{p}_\epsilon^{\text{initial}}) \in \left[\frac{1}{2}p(1-p), \frac{3}{2}p(1-p)\right]$,*

- *$\texttt{variance}_{\epsilon,\delta}$ is such that given $\log n$ samples from $\mathcal{D}(k)$, with probability $1 - \beta$, $\widehat{\sigma}_p^2 \in [\text{Var}(\mathcal{D}(k)), 8\text{Var}(\mathcal{D}(k))]$,*

- *the k_is are such that $\frac{k_1}{k_{n/2}} \leq \frac{n/2 - \log n}{\log n}$,*

then with probability $1 - 2\beta$, $\text{Var}(\widehat{p}_\epsilon^{\text{realistic}}) \leq C \cdot \text{Var}(\widehat{p}_\epsilon^{\text{ideal}})$ for some absolute constant C.

A full proof of Theorem 4.1 is given in Appendix B; we present intuition and a proof sketch here. The first two conditions of Theorem 4.1 ensure that the mean and variance estimates are sufficiently accurate to use in the remainder of the algorithm. Notice that the initial estimates do not need to be especially accurate. In fact, provided p is not too close to 0 or 1, the DP mean estimator that simply adds noise to the sample mean achieves the right accuracy (see Lemma E.1 for details). In Appendix E, we also give a DP variance estimator that achieves the desired accuracy guarantee using only $\log n$ samples, under some mild conditions (Lemma E.4). Thus the set of mean and variance estimators that satisfy the accuracy requirements of Theorem 4.1 are non-empty. We note that the constants $1/2$, $3/2$ and 8 in Theorem 4.1 are not intrinsic; any constant multiplicative factors will suffice. We also note that the specific sizes of the three groups outlined in Algorithm 2 are heuristic and can be varied to ensure that the initial estimator achieves the required accuracy.

Algorithm 2 Private Heterogeneous Mean Estimation

Input: (ϵ,δ)-DP mean estimator $\texttt{mean}_{\epsilon,\delta}$, (ϵ,δ)-DP variance estimator $\texttt{variance}_{\epsilon,\delta}$, number of users n, number of samples held by each user $(k_1,\ldots,k_n \ s.t. \ k_i \geq k_{i+1})$, user-level estimates $(\widehat{p}_1,\cdots,\widehat{p}_n)$, error guarantee on $\texttt{mean}_{\epsilon,\delta}$ $\alpha > 0$, and desired high probability bound $\beta \in [0,1]$.

1: **Initial Estimates**

2: $\widehat{p}_\epsilon^{\text{initial}} = \texttt{mean}_{\epsilon,\delta}(\mathrm{x}_{9n/10+1}^1,\cdots,\mathrm{x}_n^1)$

3: $\widehat{\sigma}_p^2 = \texttt{variance}_{\epsilon,\delta}(\widehat{p}_1,\cdots,\widehat{p}_{\log n})$

4: **Defining weights and truncation**

5: **for** $i = \log n + 1$ to $9n/10$ **do**

6:     Compute $\widehat{\sigma}_i^2 = \frac{1}{k_i}(\widehat{p}_\epsilon^{\text{initial}} - (\widehat{p}_\epsilon^{\text{initial}})^2) + (1 - \frac{1}{k_i})\widehat{\sigma}_p^2$.

7:     $\widehat{a}_i = \widehat{p}_\epsilon^{\text{initial}} - \alpha - f_{\mathcal{D}}^{k_i}(n,\widehat{\sigma_p^2},\beta)$

8:     $\widehat{b}_i = \widehat{p}_\epsilon^{\text{initial}} + \alpha + f_{\mathcal{D}}^{k_i}(n,\widehat{\sigma_p^2},\beta)$

9:

10: $\widehat{T}^* = \arg\min_T \dfrac{(\sum_{i=\log n+1}^{9n/10} \min\{\frac{1}{\widehat{\sigma}_i^2},T^2\} + \max_{\log n+1 \leq i \leq 9n/10} \frac{\min\{1/\widehat{\sigma}_i^4,T^2/\widehat{\sigma}_i^2\}|\widehat{b}_i - \widehat{a}_i|^2}{\epsilon^2})}{(\sum_{i=\log n+1}^{9n/10} \min\{1/\widehat{\sigma}_j^2,T/\widehat{\sigma}_i\})^2}$

11: **for** $i = \log n + 1$ to $9n/10$ **do**

12:     $\widehat{w}_i^* = \dfrac{\min\{1/\widehat{\sigma}_i^2,\widehat{T}^*/\widehat{\sigma}_i\}}{\sum_{j=\log n+1}^{9n/10} \min\{1/\widehat{\sigma}_j^2,\widehat{T}^*/\widehat{\sigma}_i\}}$

13: **Final Estimate**

14: $\Lambda = \max_{i\in[\log n+1,9n/10]} \dfrac{\min\{1/\widehat{\sigma}_i^2,\widehat{T}^*/\widehat{\sigma}_i\}|\widehat{b}_i - \widehat{a}_i|}{\sum_{j=\log n+1}^{9n/10} \min\{1/\widehat{\sigma}_j^2,\widehat{T}^*/\widehat{\sigma}_i\}}$

15: Sample $Y \sim \text{Lap}\left(\frac{\Lambda}{\epsilon}\right)$

16: **return** $\widehat{p}_\epsilon^{\text{realistic}} = \sum_{i=\log n+1}^{9n/10} \widehat{w}_i^* [\widehat{p}_i]_{\widehat{a}_i}^{\widehat{b}_i} + Y$

The final assumption ensures that the $\log n$ users with the most data can not estimate the mean of meta-distribution alone. Note that up to logarithmic factors, this condition simply requires that the number of data points held by the user with the most data is at most n times the number of data points of the median user. If n is large, then this is unlikely to be a limiting factor.

The main distinction between $\widehat{p}_\epsilon^{\text{ideal}}$ and $\widehat{p}_\epsilon^{\text{realistic}}$ is the use of the output of the estimators $\texttt{mean}_{\epsilon,\delta}$ and $\texttt{variance}_{\epsilon,\delta}$ to estimate σ_i^2, a_i and b_i. Thus, the main component of the proof of Theorem 4.1 is to show that the conditions stated in the theorem are enough to ensure that $\widehat{\sigma}_i^2$, $\widehat{a}_i$ and $\widehat{b}_i$ are sufficiently accurate.

Lemma 4.2. *Given $\widehat{p}_\epsilon^{\text{initial}}$, $\widehat{\sigma}_p^2$, and k_i, define $\widehat{\sigma}_i^2 = \frac{1}{k_i}\widehat{p}_\epsilon^{\text{initial}}(1 - \widehat{p}_\epsilon^{\text{initial}}) + \frac{k_i-1}{k_i}\widehat{\sigma}_p^2$. Under the conditions of Theorem 4.1, for all $i > \log n$, we have $\widehat{\sigma}_i^2 \in \left[\frac{1}{2}\sigma_i^2, 9.5\sigma_i^2\right]$ and $|\widehat{b}_i - \widehat{a}_i| \leq 4|b_i - a_i|$.*

A detailed proof of Lemma 4.2 is presented in Appendix B. Lemma 4.2 implies that the individual variance estimates used in the weights, and the truncation parameters are accurate up to constant multiplicative factors. The main ingredient left then is to show that using only a subset of the population in the final estimate only affects the performance up to a multiplicative factor. Under the assumption that $\frac{k_{\max}}{k_{\text{med}}} \leq \frac{n/2-\log n}{\log n}$, where $\sigma_{k_{\max}}^2 = \text{Var}(\widehat{p}_1)$ and $\sigma_{k_{\text{med}}}^2 = \text{Var}(\widehat{p}_{n/2})$ then

$$\sigma_{k_{\text{med}}}^2 = \frac{1}{k_{\text{med}}}p(1-p) + (1 - \frac{1}{k_{\text{med}}})\sigma_p^2 \leq \frac{n/2-\log n}{\log n}\sigma_{k_{\max}}^2. \tag{7}$$

We use this to show that for any truncation parameter T, $\sum_{i=1}^n \min\{\frac{1}{\sigma_i^2},\frac{T}{\sigma_i}\} \leq 4\sum_{i=\log n+1}^{9n/10} \min\{\frac{1}{\sigma_i^2},\frac{T}{\sigma_i}\}$. Using this, along with the bounds on estimated quantities from Lemma 4.2, we show that with high probability, the variance of the our estimator $\widehat{p}_\epsilon^{\text{realistic}}$ is within a constant factor of $\text{Var}(\widehat{p}_\epsilon^{\text{ideal}})$, as given in Equation (5).

We remark that this framework is amenable to being performed in a federated manner if one has private federated mean and variance estimators. Steps (6) - (8) and Step (12) can be performed locally. Steps (10) and the final sum in Step (16) would need to be altered to fit the federated framework.

272 We'll see in Appendix C that it is sufficient to replace Step (10) with an estimate of $\frac{1}{\sigma_{\log n}}$ (the inverse
273 standard deviation of the user with the $\log n$-th most data). The final step is then a simple addition
274 with output perturbation, which can be performed in a federated manner (e.g., [23, 19]).

275 In Appendix C, we extend this result to the case where k_is are private and unknown to the analyst
276 (Algorithm 3, Theorem C.1). We'll need considerably more machinery in this setting where both the
277 sensitivity of the final estimator and the truncation parameter T are data dependent.

5 Near Optimality and Lower Bounds

279 In Section 4, we showed that the variance of our realisable private estimator $\widehat{p}_\epsilon^{\text{realistic}}$ is within a
280 constant of that of the complete information estimator $\widehat{p}_\epsilon^{\text{ideal}}$. In this section, we will show that in
281 fact, $\widehat{p}_\epsilon^{\text{realistic}}$ performs as well (up to logarithmic factors) as the true optimal private estimator. We'll
282 also give a lower bound on the performance of the optimal estimator in terms of the k_i. This will give
283 us some intuition into the types of distributions of k_i's that benefit from this refined analysis.

5.1 Minimax Optimality of $\widehat{p}_\epsilon^{\text{realistic}}$

285 The goal of this section is to show that the estimator $\widehat{p}_\epsilon^{\text{realistic}}$ discussed in Section 4.2 is minimax
286 optimal up to logarithmic factors. In light of Theorem 4.1, it suffices to show that the estimator
287 $\widehat{p}_\epsilon^{\text{ideal}}$ is minimax optimal up to logarithmic factors. Let $\mathcal{P}$ be a parameterized family of distributions
288 $p \mapsto \mathcal{D}_p$, where $\mathbb{E}[\mathcal{D}_p] = p$ and $\mathcal{D}_p$ is supported on $[0, 1]$. For $p \in [0, 1]$ and $k \in \mathbb{N}$, let $\phi_{p,k}$ be the
289 probability density function of $\mathcal{D}_p(k)$.

290 Our lower bound will show that the estimation error must consist of a statistical term and a privacy
291 term. Such a lower bound thus must generalize a statistical lower bound. We will rely on the
292 Cramer-Rao approach to proving statistical lower bounds; as we show, it is particularly amenable to
293 incorporating a privacy term. This approach relates the variance of any unbiased estimator of the
294 mean of a distribution to the inverse of the Fischer information; the proof naturally extends to the case
295 where we are given samples from a set of distributions with the same mean but different variances,
296 as is the case in our setting. For many distributions of interest, e.g., Gaussian and Bernoulli, the
297 Fischer information of a single sample is the inverse of the variance, and we make that assumption
298 for $\mathcal{D}_p$. We also assume that the $\mathcal{D}_p$ has sub-Gaussian tails. Thus, as long as the set of permissible
299 meta-distributions includes distributions with this property, e.g., included truncated Gaussians, our
300 lower bound applies.

Theorem 5.1. *Let $\mathcal{P}$ be a parameterized family of distributions $p \mapsto \mathcal{D}_p$ and suppose that for all*
302 *$p \in [0, 1]$ and $k \in \mathbb{N}$, the Fisher information of $\phi_{p,k}$ is inversely proportional to the variance,*
303 *$\text{Var}(\mathcal{D}_p(k))$:*

$$\int (\tfrac{\partial}{\partial p} \log \phi_{p,k}(x))^2 \phi_{p,k}(x) dx = O(\tfrac{1}{\text{Var}(\mathcal{D}_p(k))}), \tag{8}$$

304 *and for all p, $n > 0$, $k \in \mathbb{N}$ and $\beta \in [1/3, 2/3]$, $f_{\mathcal{D}_p}^k(n, \sigma_p^2, \beta) = \tilde{O}(\text{Var}(\mathcal{D}_p(k)))$, then*

$$\max_{p \in [1/3, 2/3]} [\text{Var}_{\forall i \in [n], x_i \sim \mathcal{D}(k_i), M}(\widehat{p}_\epsilon^{\text{ideal}})] = \tilde{O}(\min_{M, \text{ unbiased}} \max_{p \in [1/3, 2/3]} [\text{Var}_{\forall i \in [n], x_i \sim \mathcal{D}(k_i), M}(M)]).$$

305 *Further, under the conditions of Theorem 4.1,*

$$\max_{p \in [1/3, 2/3]} [\text{Var}_{\forall i \in [n], x_i \sim \mathcal{D}(k_i), M}(\widehat{p}_\epsilon^{\text{realistic}})] = \tilde{O}(\min_{M, \text{ unbiased}} \max_{p \in [1/3, 2/3]} [\text{Var}_{\forall i \in [n], x_i \sim \mathcal{D}(k_i), M}(M)]).$$

306 We will prove Theorem 5.1 in three steps. The following class of noisy linear estimators, NLE, will act
307 as an intermediary in our proof. The notation σ_i denotes $\text{Var}(x_i)$, which accounts for the randomness
308 in generating x_i.

$$\text{NLE} = \{M_{\text{NL}}(\mathbf{x}; \mathbf{w}) = \textstyle\sum_{i=1}^n w_i x_i + \text{Lap}(\tfrac{\max_i w_i \sigma_i}{\epsilon}) \,\big|\, w_i \in [0, 1], \textstyle\sum_{i=1}^n w_i = 1\}.$$

309 Similar to $\widehat{p}_\epsilon^{\text{ideal}}$, this class of estimators is not realizable since we only have access to an estimate of
310 $\sigma_i = \text{Var}(\mathcal{D}_p(k_i))$. Additionally, the estimators in NLE are not necessarily ϵ-DP.

311 The proof Theorem 5.1 has three main steps outlined below. The proof of each Lemma is contained
312 in Appendix D. The first step is shown in Lemma 5.2, which shows that the weights used in $\widehat{p}_\epsilon^{\text{ideal}}$ are
313 optimal (i.e., variance-minimizing) among all estimators in the set NLE.

Lemma 5.2. *Given $\widehat{p}_i \sim \mathcal{D}_p(k_i)$ with variance σ_i^2 for all $i \in [n]$ and $w \in [0,1]^n$ such that $\sum_{i=1}^n w_i = 1$, let $\widehat{p} = \sum_{i=1}^n w_i \widehat{p}_i + \mathrm{Lap}(\frac{\max_i w_i \sigma_i}{\epsilon})$. The variance of $\widehat{p}$ is minimized by the following weights: $\tilde{w}_i^* = \frac{\min\{1/\sigma_i^2, T/\sigma_i\}}{\sum_{j=1}^n \min\{1/\sigma_j^2, T/\sigma_j\}}$ for some T.*

Since the threshold T^* in $\widehat{p}_\epsilon^{\mathrm{ideal}}$ was chosen to minimize $\mathrm{Var}(\widehat{p}_\epsilon^{\mathrm{ideal}})$, then we know that the weights w_i^* in $\widehat{p}_\epsilon^{\mathrm{ideal}}$ are optimal.

Now, let us turn to the second – and main – component of the proof of Theorem 5.1. Lemma 5.3 formalises the statement that an estimator inside the class NLE is minimax optimal among unbiased estimators. That is, for any unbiased estimator M, there exists an estimator $M_{\mathrm{NL}} \in$ NLE with lower worst-case variance.

Lemma 5.3. *Let $\mathcal{P}$ be a parameterized family of distributions $p \mapsto \mathcal{D}_p$ and suppose that $M :$ $[0,1]^n \to [0,1]$ is an ϵ-DP estimator such that for all $p \in [1/3, 2/3]$, (1) M is unbiased, $\mu_M(p) = p$, and (2) the Fisher information of ϕ_{p,k_i} is inversely proportional to the variance $\mathrm{Var}(\mathcal{D}_p(k_i))$, $\int (\frac{\partial}{\partial p} \log \phi_{p,k_i}(x_i))^2 \phi_{p,k_i}(x_i) dx_i = O(\frac{1}{\mathrm{Var}(\mathcal{D}_p(k_i))})$, then there exists an estimator $M_{\mathrm{NL}} \in$ NLE such that*
$$\max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\forall i \in [n], x_i \sim \mathcal{D}(k_i), M_{\mathrm{NL}}}(M_{\mathrm{NL}})] \leq O(\max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\forall i \in [n], x_i \sim \mathcal{D}(k_i), M}(M)]).$$

The final component needed for the proof of Theorem 5.1 is a translation from the estimators in NLE, which are not ϵ-DP to the corresponding ϵ-DP estimator. For any weight vector $\mathbf{w}$, we can define an ϵ-DP estimator by truncating the data point x_i and calibrating the noise appropriately:

$$M_{\mathrm{TNL}}(x_1, \cdots, x_n; \mathbf{w}) = \sum_{i=1}^n w_i[x_i]_{p-f_{\mathcal{D}}^{k_i}(n, \sigma_p^2, \beta)}^{p+f_{\mathcal{D}}^{k_i}(n, \sigma_p^2, \beta)} + \mathrm{Lap}(\frac{\max_i 2w_i f_{\mathcal{D}}^{k_i}(n, \sigma_p^2, \beta)}{\epsilon}). \quad (9)$$

Provided $f_{\mathcal{D}}^{k_i}(n, \sigma_p^2, \beta) \approx \mathrm{Var}(\mathcal{D}(k_i))$, the estimators M_{TNL} have approximately the same variance as the corresponding element of NLE, but are slightly biased. This is formalized in the following lemma.

Lemma 5.4. *For any distribution $\mathcal{D}$, $n > 0$ and $\beta \in [0,1]$, if for all k_i, $f_{\mathcal{D}}^{k_i}(n, \sigma_p^2, \beta) = \tilde{O}(\mathrm{Var}(\mathcal{D}(k_i)))$ then for any $\mathbf{w} \in [0,1]^n$ such that $\sum_{i=1}^n w_i = 1$, we have $\mathrm{Var}(M_{\mathrm{TNL}}(\cdot\,; \mathbf{w})) = \tilde{O}(\mathrm{Var}(M_{\mathrm{NL}}(\cdot\,; \mathbf{w})))$. Further, the bias of M_{TNL} is at most β.*

Finally, we have the tools to prove the main theorem in this section, Theorem 5.1:

$$\min_{M \text{ unbiased}} \max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\mathcal{D}_p}(M)] = \Omega(\min_{M \in \text{NLE}} \max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\mathcal{D}_p}(M)]) = \Omega(\max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\mathcal{D}_p}(p_\epsilon^{\mathrm{NLE}})])$$

$$= \tilde{\Omega}(\max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\mathcal{D}_p}(\widehat{p}_\epsilon^{\mathrm{ideal}})])$$

$$= \tilde{\Omega}(\max_{p \in [1/3, 2/3]}[\mathrm{Var}_{\mathcal{D}_p}(\widehat{p}_\epsilon^{\mathrm{realistic}})])$$

where $p_\epsilon^{\mathrm{NLE}} \in$ NLE has the same weights as $\widehat{p}_\epsilon^{\mathrm{ideal}}$. The equalities follow from Lemmas 5.3, 5.2, 5.4, and Theorem 4.1, respectively.

5.2 Minimax Lower Bound on Estimation Rate

In addition to establishing the near optimality of $\widehat{p}_\epsilon^{\mathrm{realistic}}$, we will also give a lower bound on minimax rate of estimation in terms of the parameters $k_1, \cdots, k_n$ and σ_p^2. Note that we can view the truncation of the weights w_i as establishing an effective upper bound on k_i. Given $k_1, \cdots, k_n \in \mathbb{N}$, and $\epsilon > 0$, let $k^* = \arg\min_k \frac{\frac{k}{\epsilon^2} + \sum_{i=1}^n \min\{k_i, k\}}{(\sum_{i=1}^n \min\{k_i, k\})^2}$. Intuitively, in the case that $\sigma_p = 0$, we want to use as many samples as possible, but one user contributing many samples leads to larger sensitivity and thus privacy cost. Limiting to k_{max} the number of samples per user allows us to limit the sensitivity to be about $w_{max}(1/\sqrt{k_{max}})$. Since w_i is proportional to the number of samples used, the variance when using at most k samples per user is the above expression being minimized. Our lower bound below is close to this value for reasonable k_i's.

Corollary 5.5. *Given $k_1, \cdots, k_n \in \mathbb{N}$, and σ_p, there exists a family of distributions $\mathcal{D}_p$ such that*

$$\min_{M, \text{ unbiased}} \max_{p \in [1/3, 2/3]} \mathrm{Var}_{\forall i \in [n], x_i \sim \mathcal{D}_p(k_i)}[M(x_1, \cdots, x_n)] \geq \tilde{\Omega}(\min\{\frac{\frac{k^*}{\epsilon^2} + \sum_{i=1}^n \min\{k_i, k^*\}}{(\sum_{i=1}^n \min\{k_i, \sqrt{k_i k^*}\})^2}, \frac{\sigma_p^2}{n}\}).$$

References

[1] Jayadev Acharya and Ziteng Sun. Communication complexity in locally private distribution estimation and heavy hitters. *arXiv preprint arXiv:1905.11888*, 2019.

[2] Jayadev Acharya, Ziteng Sun, and Huanyu Zhang. Hadamard response: Estimating distributions privately, efficiently, and with little communication. volume 89 of *Proceedings of Machine Learning Research*, pages 1120–1129. PMLR, 16–18 Apr 2019.

[3] Daniel Alabi, Audra McMillan, Jayshree Sarathy, Adam Smith, and Salil Vadhan. Differentially private simple linear regression, 2020.

[4] Hilal Asi and John C Duchi. Instance-optimality in differential privacy via approximate inverse sensitivity mechanisms. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 14106–14117. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/a267f936e54d7c10a2bb70dbe6ad7a89-Paper.pdf.

[5] Abhishek Bhowmick, John Duchi, Julien Freudiger, Gaurav Kapoor, and Ryan Rogers. Protection against reconstruction and its applications in private federated learning, 2019.

[6] Michael Borenstein, Larry V Hedges, Julian PT Higgins, and Hannah R Rothstein. *Introduction to meta-analysis*. John Wiley & Sons, 2021.

[7] Mark Bun, Kobbi Nissim, and Uri Stemmer. Simultaneous private learning of multiple concepts. 11 2015. doi: 10.1145/2840728.2840747.

[8] Wei-Ning Chen, Peter Kairouz, and Ayfer Özgür. Breaking the communication-privacy-accuracy trilemma. *arXiv preprint arXiv:2007.11707*, 2020.

[9] John Duchi and Ryan Rogers. Lower bounds for locally private estimation via communication complexity. In Alina Beygelzimer and Daniel Hsu, editors, *Proceedings of the Thirty-Second Conference on Learning Theory*, volume 99 of *Proceedings of Machine Learning Research*, pages 1161–1191, Phoenix, USA, 25–28 Jun 2019. PMLR. URL http://proceedings.mlr.press/v99/duchi19a.html.

[10] John C Duchi, Michael I Jordan, and Martin J Wainwright. Minimax optimal procedures for locally private estimation. *Journal of the American Statistical Association*, 113(521):182–201, 2018.

[11] Cynthia Dwork and Jing Lei. Differential privacy and robust statistics. In *Proceedings of the Forty-First Annual ACM Symposium on Theory of Computing*, STOC '09, page 371–380, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605585062.

[12] Cynthia Dwork and Aaron Roth. *The Algorithmic Foundations of Differential Privacy*, volume 9. 2014. URL http://dx.doi.org/10.1561/0400000042.

[13] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. volume Vol. 3876, pages 265–284, 01 2006. doi: 10.1007/11681878_14.

[14] Úlfar Erlingsson, Vasyl Pihur, and Aleksandra Korolova. RAPPOR: randomized aggregatable privacy-preserving ordinal response. In *ACM SIGSAC Conference on Computer and Communications Security*, pages 1054–1067, 2014.

[15] Moritz Hardt and Kunal Talwar. On the geometry of differential privacy. In *Proceedings of the Forty-Second ACM Symposium on Theory of Computing*, STOC '10, page 705–714, New York, NY, USA, 2010. Association for Computing Machinery. ISBN 9781450300506.

[16] Joachim Hartung, Guido Knapp, and Bimal Sinha. Statistical meta-analysis with applications. 08 2008. doi: 10.1002/9780470386347.

[17] Justin Hsu, Sanjeev Khanna, and Aaron Roth. Distributed private heavy hitters. In *International Colloquium on Automata, Languages, and Programming*, pages 461–472. Springer, 2012.

[18] Aaron Johnson and Vitaly Shmatikov. Privacy-preserving data exploration in genome-wide association studies. In *Proceedings of the 19th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '13, page 1079–1087, New York, NY, USA, 2013. Association for Computing Machinery. ISBN 9781450321747.

[19] Peter Kairouz, H. Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, Rafael G. L. D'Oliveira, Hubert Eichner, Salim El Rouayheb, David Evans, Josh Gardner, Zachary Garrett, Adrià Gascón, Badih Ghazi, Phillip B. Gibbons, Marco Gruteser, Zaid Harchaoui, Chaoyang He, Lie He, Zhouyuan Huo, Ben Hutchinson, Justin Hsu, Martin Jaggi, Tara Javidi, Gauri Joshi, Mikhail Khodak, Jakub Konecný, Aleksandra Korolova, Farinaz Koushanfar, Sanmi Koyejo, Tancrède Lepoint, Yang Liu, Prateek Mittal, Mehryar Mohri, Richard Nock, Ayfer Özgür, Rasmus Pagh, Hang Qi, Daniel Ramage, Ramesh Raskar, Mariana Raykova, Dawn Song, Weikang Song, Sebastian U. Stich, Ziteng Sun, Ananda Theertha Suresh, Florian Tramèr, Praneeth Vepakomma, Jianyu Wang, Li Xiong, Zheng Xu, Qiang Yang, Felix X. Yu, Han Yu, and Sen Zhao. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning*, 14(1–2):1–210, 2021. ISSN 1935-8237. doi: 10.1561/2200000083. URL http://dx.doi.org/10.1561/2200000083.

[20] Vishesh Karwa and Salil P. Vadhan. Finite sample differentially private confidence intervals. volume abs/1711.03908 of *Innovations in Theoretical Computer Science '18*, 2018.

[21] Daniel Levy, Ziteng Sun, Kareem Amin, Satyen Kale, Alex Kulesza, Mehryar Mohri, and Ananda Theertha Suresh. Learning with user-level privacy. In *Neural Information Processing Systems (NeurIPS 2021)*, 2021.

[22] Yuhan Liu, Ananda Theertha Suresh, Felix Xinnan X Yu, Sanjiv Kumar, and Michael Riley. Learning discrete distributions: user vs item-level privacy. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 20965–20976. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/f06edc8ab534b2c7ecbd4c2051d9cb1e-Paper.pdf.

[23] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-Efficient Learning of Deep Networks from Decentralized Data. In Aarti Singh and Jerry Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pages 1273–1282, Fort Lauderdale, FL, USA, 20–22 Apr 2017. PMLR.

[24] H. Brendan McMahan, Daniel Ramage, Kunal Talwar, and Li Zhang. Learning differentially private recurrent language models. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=BJ0hF1Z0b.

[25] Frank McSherry and Ilya Mironov. Differentially private recommender systems: Building privacy into the netflix prize contenders. In *Proceedings of the 15th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 627–636, 2009.

[26] Frank McSherry and Kunal Talwar. Mechanism design via differential privacy. In *48th Annual IEEE Symposium on Foundations of Computer Science (FOCS'07)*, pages 94–103, 2007. doi: 10.1109/FOCS.2007.66.

[27] Ion Mihoc and Cristina Fătu. Fisher's information measure and truncated normal distributions (ii). *Revue d'Analyse Numérique et de Théorie de l'Approximation*, 32, 01 2003.

[28] Frank Nielsen. *Cramér-Rao Lower Bound and Information Geometry*, pages 18–37. Hindustan Book Agency, Gurgaon, 2013. URL https://doi.org/10.1007/978-93-86279-56-9_2.

[29] Abhradeep Guha Thakurta and Adam Smith. Differentially private feature selection via stability arguments, and the robustness of the lasso. In Shai Shalev-Shwartz and Ingo Steinwart, editors, *Proceedings of the 26th Annual Conference on Learning Theory*, volume 30 of *Proceedings of Machine Learning Research*, pages 819–850, Princeton, NJ, USA, 12–14 Jun 2013. PMLR.

[30] Salil Vadhan. *The Complexity of Differential Privacy*, pages 347–450. 04 2017. ISBN 978-3-319-57047-1. doi: 10.1007/978-3-319-57048-8_7.

[31] Wikipedia contributors. Meta-analysis — Wikipedia, the free encyclopedia, 2021. URL `https://en.wikipedia.org/w/index.php?title=Meta-analysis&oldid=1023577278`. [Online; accessed May 2021].