UI-OCEANUS: Scaling GUI Agents with Synthetic Environmental Dynamics

Abstract

Scaling generalist GUI agents is hindered by the data scalability bottleneck of expensive human demonstrations and reliance on ungrounded synthetic teacher supervision. To transcend these limitations, we propose **UI-OCEANUS**, a framework that shifts the learning focus from mimicking high-level trajectories to learning interaction dynamics from executed transitions. Through a systematic investigation of self-supervised objectives, we identify that forward dynamics, defined as the generative prediction of future interface states, acts as the primary driver for scalability and outperforms inverse and backward objectives. **UI-OCEANUS** leverages this insight by converting low-cost autonomous exploration into high-density generative supervision to learn a semantic transition world model from executed transitions. Experimental evaluations across a series of models demonstrate consistent gains from our approach: models utilizing Continual Pre-Training (CPT) on synthetic dynamics outperform non-CPT baselines with an average success rate improvement of 7% on offline benchmarks, which amplifies to a 16.8% gain in real-world online navigation. Furthermore, we observe that navigation performance scales with synthetic data volume. These results suggest that grounding agents in forward predictive modeling offers a promising pathway to scalable GUI automation with cross-domain adaptability and compositional generalization.

1 Introduction

Generalist GUI agents (Qin et al., 2025; Wang et al., 2025; Wu et al., 2024b; Xu et al., 2025b; Hong et al., 2024) traditionally rely on Behavioral Cloning (BC) (Torabi et al., 2018; Rawles et al., 2023; Zhang et al., 2024; Lu et al., 2024; Chen et al., 2024) to map visual observations to actions. However, acquiring trajectory-level data is prohibitively expensive. Unlike static image-text pairs, valid execution traces require long-horizon

Figure 1: **Constructing Generalist GUI Agents via Scalable Transition World Model Learning.** (Top) We first establish a transition-aware representation by learning a forward dynamics objective. (Bottom) We then leverage this learned GUI transition world model to instantiate a generalist GUI agent through agentic post-training.

sequences where a single error can invalidate the entire trajectory. This sensitivity makes synthesizing reliable data difficult and necessitates labor-intensive human annotation (Zhang et al., 2025b; Rawles et al., 2023; Lu et al., 2024; Li et al., 2024), creating a major bottleneck for data scalability.

To bypass this bottleneck, recent approaches (Tang et al., 2025; Wu et al., 2024b) have adopted distillation-based Continual Pre-training (CPT), distilling knowledge from foundation models via static objectives like UI captioning (Li et al., 2020) or grounding (Cheng et al., 2024). Critically, these methods remain constrained by their reliance on ungrounded teacher supervision (Gou et al., 2021): they enhance the agent's *static semantic understanding* but fail to capture the *temporal dynamics* of the environment. For

Figure 2: Overview of the proposed **UI-OCEANUS** framework. **UI-OCEANUS** consists of four sequential stages: (1) **Scalable Acquisition**; (2) **Multi-Step Data Filtering Pipeline**; (3) **Grounded Instruction Generation**; and (4) **Training Implementation**.

instance, an agent might correctly identify a "submit" button (semantics) but stubbornly assume that clicking it leads to submission, failing to anticipate that an incomplete form will actually trigger a validation error (dynamics). Lacking such grounded interaction dynamics, these agents remain bound by static semantic priors, unable to adapt when dynamic environmental states contradict their shallow heuristics. Therefore, there is a pressing need for a scalable CPT objective that derives supervision directly from autonomous environmental feedback.

To address these limitations, we propose **UI-OCEANUS**, a self-supervised training framework designed to equip agents with a GUI transition world model (Figure 1). The core insight in **UI-OCEANUS** is that the underlying set of atomic transitions (i.e., single-step observation-action-outcome tuples) in the GUI environment is both relatively *finite* and inherently *self-supervised*, providing a natural task-agnostic scaling dimension for CPT. The *finite* nature ensures that the environmental dynamics can be efficiently explored without an expert policy model or explicit task goal to reach high coverage. The *self-supervised* nature enables the environment to act as an execution-based verifier where the observed transition following the action serves as the observed outcome of an executed action. Both features enable agents to utilize task-agnostic exploration heuristics (Wu et al., 2024a; Ran et al., 2023; Gu et al., 2019; Google, 2021;

Su et al., 2017) to efficiently harvest vast quantities of these atomic transitions. Crucially, these atomic transitions ground the learning process in the *interaction dynamics* of the interface first. This effectively separates the acquisition of interaction dynamics from the execution of user intent: the agent learns "what is possible" (dynamics) from massive synthetic data before learning "what is desirable" (intent) from scarce expert demonstrations.

To realize this framework, we develop a scalable data engine capable of converting low-cost autonomous exploration into high-density supervision. We systematically investigate the spectrum of environmental dynamics and uncover a critical insight: forward dynamics, defined as the generative prediction of future interface states, serves as the key objective enabling performance scaling with data volume, significantly outperforming inverse dynamics and backward dynamics. Consequently, **UI-OCEANUS** prioritizes *forward dynamics prediction* as the generative objective (Ha and Schmidhuber, 2018; Hafner et al., 2019). Technically, we capture raw interaction traces, isolate unique and meaningful atomic transitions via strict hashing filtering and semantic filtering, and employ a Visual-Language Model (VLM) to synthesize precise descriptions of environmental changes. Finally, we implement a two-stage training strategy: the model is first continually pre-trained on a mixture of GUI dynamics, grounding, and general data to establish a semantic transition world model, and

subsequently specialized via agentic post-training to align this transition-aware prior with complex instruction following.

We conduct extensive empirical evaluations within the WeChat mini-program ecosystem (Tencent, 2024), one of the world's largest and most diverse digital platforms. Hosting millions of distinct mini-programs for over a billion monthly active users (MAU), this ecosystem presents a virtually infinite space of interaction logic and visual layouts, demanding that agents capture transferable UI transition patterns rather than memorize specific app interfaces. Notably, **UI-OCEANUS** demonstrates consistent scalability on the WeChat mini-program offline benchmark, achieving an average improvement of +7% across seven different VLM backbones compared to strong baselines with identical Supervised Fine-Tuning. Crucially, these benefits are amplified in online navigation: **UI-OCEANUS** boosts the real-world success rate by 21.9% during the cold-start phase and maintains an average 15% lead even after both step-level and multi-step GRPO (Shao et al., 2024) alignment. To facilitate community auditing of this live online benchmark, we will release its instruction set, domain metadata, and evaluation protocol. Furthermore, our experiments yield three critical insights: (1) **Data scaling**: Performance scales log-linearly with synthetic data volume, showing no saturation up to 32B parameters and 3.2B tokens, confirming the scalability of atomic dynamics supervision. (2) **Mechanism**: Forward dynamics is more effective than inverse dynamics, as its higher predictive difficulty encourages the model to learn stronger semantic visual representations. (3) **Generalization**: The learned GUI transition world model captures transferable UI transition patterns effectively, enabling generalization to unseen mini-programs and Android environments, as well as compositional reasoning on complex multi-step tasks never seen during training.

We highlight main contributions as below:

- We pioneer a shift in GUI agent learning by separating the acquisition of atomic interaction dynamics from high-level instruction following. To the best of our knowledge, this is the first work to systematically scale environment dynamics as a self-supervised CPT objective for GUI agents, bypassing the data scalability limitations of trajectory-based behavioral cloning.

- We propose **UI-OCEANUS**, a scalable framework designed to mine training supervision directly from observed environmental transitions.

- We conduct extensive evaluations validating the performance scaling of **UI-OCEANUS**. Our results demonstrate generalization across both domains and horizons.

2 Background and Related Work

Generalist GUI agents autonomously execute user instructions by interacting with Graphical User Interfaces (GUIs), thereby significantly boosting user productivity in daily tasks (Wang et al., 2024). Pretrained from VLMs, generalist GUI agents are post-trained using Behavioral Cloning (BC) (Wu et al., 2024b; Lin et al., 2025a; Lu et al., 2024; Chen et al., 2024) or multi-step Reinforcement Learning (RL) (Ye et al., 2025; Xu et al., 2025a; Wang et al., 2025). However, post-training methods struggle under the capability ceiling of the base model (Zhang et al., 2025a; Yue et al., 2025), underscoring the necessity of Continual Pre-Training (CPT) prior to policy alignment. A fundamental challenge for CPT is the data scalability bottleneck, where collecting high-quality human demonstrations is prohibitively expensive. To bypass the challenge, existing research mainly uses the following two learning tasks in CPT: (1) static UI understanding task such as element grounding or screen captioning (Tang et al., 2025; Wu et al., 2024b), which requires powerful foundation models to label GUI screenshots and lacks grounding in real execution; (2) dynamic interacting with environments under instructions (Lin et al., 2025b; Sun et al., 2025; Ramrakhya et al., 2025; Pahuja et al., 2025), which is notoriously difficult due to the low yield rates for high-quality long-horizon samples. Our **UI-OCEANUS** proposes a new CPT task: learning on forward dynamics of atomic transitions. Such dynamic learning task enables **UI-OCEANUS** to reduce reliance on ungrounded teacher supervision while avoiding the fragility of long-horizon trajectory synthesis.

Conceptualizing the GUI as a dynamic system aligns with the broader literature on world models. In the specific GUI domain, prior works have explored this direction through visual state prediction (Luo et al., 2025; Wang* et al., 2025) and action prediction from state changes (Gao et al., 2025). However, there still lacks a scalable, task-

agnostic CPT objective for learning broad transition patterns. We distinguish our work by leveraging autonomous exploration and intrinsic environmental feedback to learn a GUI transition world model via CPT, establishing a transition-aware representation before agentic post-training.

Appendix B discusses related work in more detail.

3 The UI-OCEANUS Framework

To instantiate the transition formulation defined in Appendix A, we introduce **UI-OCEANUS**, a unified framework for learning GUI dynamics from large-scale autonomous interaction. As illustrated in Figure 2, **UI-OCEANUS** consists of four sequential stages:

3.1 Scalable Acquisition via Autonomous Exploration

We autonomously explore the WeChat miniprogram ecosystem to harvest open-domain transitions. Using a distributed fleet of 50 nodes, we employ a structured random walk policy: agents interact with UI elements identified via accessibility trees without human intervention. For each step t, we record the transition tuple (s_t, a_t, s_{t+1}), where $s_t = (I_t, X_t)$ denotes the screenshot and structural metadata. This process yielded over 20.8M raw transitions over one month.

3.2 Multi-Step Data Filtering Pipeline

We refine $\mathcal{D}_{\text{raw}}$ into a high-quality corpus $\mathcal{D}_{\text{cpt}}$ via a three-stage pipeline, with implementation details and filtering analysis provided in Appendix E: (1) **Structural Deduplication:** MinHash signatures on accessibility trees remove repeated content templates, reducing data to 8.2M. (2) **Visual Deduplication:** pixel-level pHash/dHash identify visually static transitions, narrowing it to 4.3M. (3) **Semantic Filtering:** A VLM filters system errors and rendering artifacts by verifying action-feedback consistency, resulting in a final set of 3.4M transitions.

3.3 Grounded Instruction Generation

For each filtered transition, we use a VLM interpreter(Qwen3-VL-235B-A22B-Instruct (Bai et al., 2025a)) to verbalize the observed pre-state, executed action, and post-state. Importantly, the interpreter does not synthesize the transition itself: both screenshots come from actual system execution. The resulting supervision trains the model to predict a textual description of the next UI state given the current screen and action. Appendix H analyzes the sensitivity of this interpreter stage to teacher model scale.

By generating instructions directly grounded in actual environmental state transitions, this stage produces large-scale, reliable, and high-fidelity data for CPT.

3.4 Training Implementation

3.4.1 Continual Pretraining

Using the curated dataset $\mathcal{D}_{\text{cpt}}$ and generated grounded instructions, we construct a unified training corpus designed to facilitate understanding of GUI dynamics.

We define three distinct categories of training tasks to comprehensively capture GUI dynamics:

Forward dynamics: Given the screenshot of an initial state and an action (either as an exact action or a natural-language summary), the model predicts the resulting GUI state description. *Input*: $\mathcal{V} = [I_t, a_t]$ or $\mathcal{V} = [I_t, u_t]$; *Target*: $\mathbf{y} = \mathcal{D}_{t+1}$.

Inverse dynamics: Given screenshots of the initial and resulting states, the model predicts the action connecting them. *Input*: $\mathcal{V} = [I_t, I_{t+1}]$; *Target*: $\mathbf{y} = u_t$ or $\mathbf{y} = a_t$.

Backward dynamics: Given the screenshot of a resulting state and an action summary, the model predicts a description of the initial GUI state. *Input*: $\mathcal{V} = [u_t, I_{t+1}]$; *Target*: $\mathbf{y} = \mathcal{D}_t$.

Data Mixing. We construct the final training set $\mathcal{D}_{\text{mix}}$ by strategically combining three distinct data sources: (1) GUI dynamics (70%): Informed by our ablation study (Section 4.3), we exclusively utilize Forward Dynamics ($I_t, a_t \rightarrow \mathcal{D}_{t+1}$) as the semantic transition world modeling objective; (2) General multimodal data (20%), which acts as a regularizer against catastrophic forgetting during GUI-specialized CPT; and (3) UI grounding data (10%). Appendix J reports evaluations on 11 public multimodal and reasoning benchmarks, showing largely preserved general capabilities with mild trade-offs on several tasks. We detail the specific training hyperparameters in Appendix I.1.

3.4.2 Agentic Post-training.

Following the CPT phase, we conduct an agentic post-training stage. In this phase, the model is fine-tuned on high-quality GUI agent trajectories to explicitly align the GUI transition world model with user intents, bridging the gap between transition-aware representations and task execution.

Table 1: **Scaling Laws of UI-OCEANUS.** Evaluation of Exact Match (EM) scores on the held-out offline benchmark. **UI-OCEANUS** achieves consistent performance gains across all seven model backbones.

Model	Size	Reference		UI-OCEANUS Data Scale (+ SFT)				
		Base (Zero-shot)	w/ grounding	0% (SFT)	12.5%	25%	50%	100% (Ours)
I. Qwen3-VL Series with **UI-OCEANUS**								
Qwen3-VL	2B	2.4	36.5	47.9	49.4	51.3	51.7	52.7
Qwen3-VL	4B	41.7	52.0	57.3	58.3	59.0	59.3	60.0
Qwen3-VL	8B	42.3	54.9	58.1	58.0	59.6	60.4	60.8
Qwen3-VL	32B	47.1	61.2	61.5	61.0	63.7	62.5	65.0
II. Qwen2.5-VL Series with **UI-OCEANUS**								
Qwen2.5-VL	3B	1.1	27.9	47.7	49.2	48.5	49.6	50.6
Qwen2.5-VL	7B	13.0	37.8	51.0	53.5	53.3	53.4	55.7
Qwen2.5-VL	32B	33.9	56.5	60.5	61.6	63.2	64.2	64.8

We detail the specific training hyperparameters in Appendix I.2.

4 Experiments

In this section, we systematically evaluate the **UI-OCEANUS** framework. Our evaluation is structured to answer four critical questions: (1) **Scalability.** Can autonomous exploration serve as a scalable data source that yields consistent performance gains? (Section 4.1) (2) **Online efficacy:** Does the learned GUI transition world model translate effectively to real-world online navigation and act as a persistent prior that synergizes with agentic post-training? (Section 4.2) (3) **Mechanism:** Which self-supervised objective yields the most significant performance gains for downstream GUI navigation? (Section 4.3) (4) **Transfer and generalization:** Does the learned GUI transition world model transfer beyond the WeChat ecosystem and support compositional transition prediction? (Section 4.4)

4.1 Scaling Laws of UI-OCEANUS

A central premise of our framework is that autonomous environmental feedback can overcome the data scarcity bottleneck. We first investigate the scaling properties of **UI-OCEANUS**.

4.1.1 Setup

Training configurations. During the CPT phase, we utilize the data mixture detailed in Section 3.4, totaling approximately 5M samples (3.2B tokens). For the subsequent agentic post-training phase, we employ 8K high-quality GUI navigation samples. To verify data scaling laws, we vary the volume of CPT data injected from 0% to 100%. **Evaluation Protocol.** To support large-scale experiments, we evaluate performance on a held-out offline benchmark comprising 8K diverse mini-program tasks not seen during training. Detailed dataset statistics are provided in Appendix K.1. Following prior works (Wu et al., 2024b; Zhang et al., 2024; Li et al., 2024), we report Exact Match (EM), which requires both the action type and its parameters to be correct. We assess performance across Qwen3-VL (Bai et al., 2025a) (2B, 4B, 8B, 32B) and Qwen2.5-VL (Bai et al., 2025b) (3B, 7B, 32B) families. We compare our method against two distinct baselines: (1) **Base Models:** We evaluate raw base models in a zero-shot setting. To decouple planning from grounding, we also report a "w/ grounding" setting, where an external specialized grounding model based on Qwen2.5-VL-32B is employed to predict an action based on the natural language action descriptions; (2) **SFT-only Baselines:** Models fine-tuned solely on the post-training data without any dynamics CPT (denoted as 0% data scale).

4.1.2 Results

As presented in Table 1 and visualized in Figure 3, our empirical findings validate scaling trends for GUI transition world models across both data and model dimensions.

Data scaling. We observe a consistent positive correlation between the volume of pre-training dynamics data and downstream performance. Starting

(a) Data scaling (b) Model scaling

Figure 3: Scaling behavior of Qwen3-VL series models.

Table 2: Online Evaluation across Training Stages.

| Training Stage | SR (%) | | Δ |
	w/o CPT	UI-OCEANUS	
Qwen3-VL-8B			
SFT + Step-level GRPO	27.5	**30.9**	+12.4%
Qwen2.5-VL-32B			
SFT (Cold Start)	24.2	**29.5**	+21.9%
+ Step-level GRPO	32.2	**38.9**	+20.8%
+ Multi-step GRPO	39.6	**44.3**	+11.9%

from the standard SFT baseline (0% data scale), the injection of our dynamics data yields consistent improvements across all model sizes, confirming that autonomous exploration serves as a scalable data source.

Model scaling. UI-OCEANUS demonstrates consistent scalability with model size. The performance gains over the SFT baseline remain consistent across all scales. This indicates that the learned interaction dynamics provide transferable transition-aware representations that complement even larger capacity models, rather than diminishing as model size grows.

Absence of saturation. Notably, we observe no signs of performance saturation across either dimension. Even at the maximal data scale(5M samples, 3.2B tokens) and model size (32B), the trend lines maintain their upward trajectory. This suggests that further scaling would likely yield continued gains.

4.2 Online Evaluation: Synergy with Post-Training

While offline metrics quantify predictive accuracy, the ultimate test lies in online execution. We investigate the effectiveness of UI-OCEANUS when integrated into a progressive post-training pipeline.

4.2.1 Setup

Training configurations. We conduct a comparative analysis between agents initialized with and without our proposed CPT (UI-OCEANUS vs. w/o CPT). The post-training pipeline consists of three progressive stages: (1) **SFT (cold start)**: Supervised fine-tuning using simple samples from the SFT dataset to establish basic instruction-following capabilities; (2) **Step-level GRPO**: Optimization on hard samples from the SFT dataset using dense step-wise rewards to refine complex reasoning; (3) **Multi-step GRPO**: Further aligning using approximately 1K instructions in the real environment, utilizing a VLM as an outcome reward model to provide sparse trajectory-level reward.

Evaluation protocol. We report the Success Rate (SR) on a held-out benchmark of 149 instructions covering diverse mini-programs (refer to Appendix K.2 for a detailed breakdown of domain coverage and task complexity). All evaluation episodes are executed in the real online environment, and task success is manually verified by human annotators to ensure rigorous correctness.

4.2.2 Results

As shown in Table 2, UI-OCEANUS provides a strong transition-aware initialization that synergizes effectively with the entire post-training pipeline.

Consistent gains across post-training stages. UI-OCEANUS establishes an immediate advantage in the initial SFT phase and, crucially, maintains this lead throughout the subsequent RL alignment steps. This persistence demonstrates that the transition-aware prior is not overwritten by optimization but rather facilitates more efficient policy learning.

Amplified benefits in online environments. Notably, the performance gains yielded by UI-OCEANUS are more pronounced in the online setting compared to the offline benchmark (Section 4.1), highlighting that our GUI transition world model equips the agent with a transition-aware prior useful for real-world interaction.

4.3 Mechanism: Forward Dynamics Helps Most

We dissect the contributions of different CPT objectives to understand the source of the performance gains.

4.3.1 Setup

Training configuration. To isolate the impact of objective formulation, we conduct controlled exper-

Table 3: **Ablation Study on Continual Pre-training Objectives.** We compare different dynamics tasks against the non-CPT baseline. Forward dynamics consistently achieve the highest performance across all scales.

Dynamics	Formulation	Qwen3-VL-2B		Qwen3-VL-4B		Qwen2.5-VL-3B		Overall	
		TM	EM	TM	EM	TM	EM	TM	EM
Baseline (w/o CPT)		75.9	47.9	79.2	57.3	75.7	47.7	76.9	51.0
Forward	$I_t, u_t \to \mathcal{D}_{t+1}$	**77.7**	**52.7**	**81.0**	**60.3**	76.7	48.8	**78.5**	53.9
	$I_t, a_t \to \mathcal{D}_{t+1}$	77.6	**52.7**	80.3	60.0	**76.9**	**50.6**	78.3	**54.4**
Inverse	$I_t, I_{t+1} \to u_t$	75.8	49.5	75.8	49.5	75.3	49.0	75.6	49.3
	$I_t, I_{t+1} \to a_t$	75.6	46.4	77.8	50.9	75.6	47.2	76.3	48.2
	$I_t, \mathcal{D}_{t+1} \to u_t$	76.3	50.2	79.0	57.4	76.2	48.3	77.2	52.0
	$I_t, \mathcal{D}_{t+1} \to a_t$	75.7	46.6	78.0	52.5	75.8	47.6	76.5	48.9
Backward	$u_t, I_{t+1} \to \mathcal{D}_t$	77.1	50.4	80.0	58.7	76.3	47.5	77.8	52.2

iments across three model scales (Qwen3-VL-2B, 4B, and Qwen2.5-VL-3B). We compare the three distinct categories of self-supervised tasks detailed in Section 3.4, while keeping the underlying UI transitions corpus constant (5M samples).

Evaluation protocol. We adhere to the identical SFT and evaluation dataset settings established in Section 4.1. In addition to the previously defined EM, we report Type Match (TM), which solely evaluates the classification accuracy of the predicted action type against the ground truth.

4.3.2 Results and Analysis

As detailed in Table 3, our ablation study reveals critical insights into how different transition objectives shape the agent's representations.

The effectiveness of forward dynamics. Forward dynamics dominates, with the simplest formulation $I_t, a_t \to \mathcal{D}_{t+1}$ objective achieving the highest EM (54.4%), clearly outperforming both standard inverse dynamics (48.2%) and backward dynamics (52.2%). Predicting *"what happens next"* forces the model to encode the state transition logic of the environment. Unlike methods employing separate world models for planning (Luo et al., 2025; Li et al., 2025), our approach uses this transition objective to shape the agent's representations directly, allowing the agent to benefit from transition-aware features without adding an external planning model.

Why inverse dynamics lags. The weaker performance of standard inverse dynamics is partly tied to its simpler target and different output-token distribution: it predicts sparse action labels and coordinates, while forward dynamics predicts richer future-state descriptions. The training loss curves in Figure 4 (Appendix F) are consistent with this

distinction, showing faster convergence for inverse dynamics under sparse action targets. We therefore treat the gap as an objective-level comparison rather than evidence that temporal direction alone explains performance. Additional target-density controls are reported in Appendix G; they preserve the advantage of future-state prediction.

4.4 Cross-Platform Transfer and Compositional Generalization

We evaluate two complementary forms of generalization: controlled transition generalization over one- and two-step UI transitions, followed by transfer to the public AndroidWorld benchmark.

4.4.1 Controlled Transition Generalization Setup

We further investigate whether the agent has merely memorized specific transition pairs or learned transition patterns capable of cross-domain transfer and compositional reasoning. To strictly assess this, we define two levels of tasks: Level 1 (L1, atomic) utilizes standard single-step transitions ($t \to t + 1$) to evaluate cross-domain transfer performance; Level 2 (L2, compositional) introduces multi-step chaining ($t \to t + 2$) that is never seen during training to assess compositional generalization, testing the ability to combine atomic GUI transition patterns for long-horizon prediction. We construct a controlled evaluation benchmark using atomic transitions from mini-programs, partitioned at the application level into seen and unseen groups. We randomly sample 1.2M transitions for training, while reserving 10K samples for L1 test sets and constructing 10K samples for L2 test sets within each group. To evaluate out-of-distribution (OOD) robustness, we additionally sample 10K random transitions from AndroidControl.

Table 4: **Cross-Domain and Compositional Generalization.** We evaluate the learned GUI transition world model across varying distribution shifts and reasoning horizons.

Lvl	Task	Model	Seen mini-P.	Unseen mini-P.	OOD Android
L1	Forward I_t, u_t $\to \mathcal{D}_{t+1}$	Qwen2.5-VL-7B	41.2	43.1	46.5
		Qwen2.5-VL-32B	48.5	49.6	**65.8**
		UI-OCEANUS-7B-F	**53.1**	**56.9**	49.1
	Inverse I_t, I_{t+1} $\to u_t$	Qwen2.5-VL-7B	17	18.4	31.1
		Qwen2.5-VL-32B	37	37.5	**67.3**
		UI-OCEANUS-7B-I	**62.3**	**58.9**	55.3
L2	Forward I_t, u_t, u_{t+1} $\to \mathcal{D}_{t+2}$	Qwen2.5-VL-7B	41.3	41.1	/
		Qwen2.5-VL-32B	46.9	46.3	/
		UI-OCEANUS-7B-F	**47.0**	**47.2**	/
	Inverse I_t, I_{t+2} $\to u_t$	Qwen2.5-VL-7B	6.7	6.2	/
		Qwen2.5-VL-32B	26.5	26.1	/
		UI-OCEANUS-7B-I	**38.7**	**37.6**	/

Table 5: **AndroidWorld Transfer. UI-OCEANUS** uses only mini-program transitions; both rows use identical AndroidControl SFT data.

Model	Base+SFT	UI-OCEANUS	Δ
Qwen2.5-VL-7B	11.2	**14.7**	+31.3%
Qwen2.5-VL-32B	19.8	**24.1**	+21.7%

Training configurations. We train two specialized variants of **UI-OCEANUS**-7B using the same data mixture as in Section 4.3. Specifically, **UI-OCEANUS**-7B-F is trained on L1 forward tasks ($I_t, u_t \to \mathcal{D}_{t+1}$), and **UI-OCEANUS**-7B-I is trained on L1 inverse tasks ($I_t, I_{t+1} \to u_t$). Both models are trained on approximately 1.7M total samples.

Evaluation protocol. We employ VLM-as-a-Judge to handle the open-ended nature of generative predictions. For forward dynamics, we explicitly query the model to predict 5 distinct UI elements of the outcome page to facilitate objective verification via a VLM judge. For inverse dynamics, the model infers the first action given the start and end states, with correctness verified by a VLM judge.

4.4.2 Controlled Transition Generalization Results

As shown in Table 4, **UI-OCEANUS** performs consistently across both domain shifts and reasoning horizons.

Cross-domain generalization. Our model exhibits strong transfer capabilities across distribution shifts. Notably, on L1 Forward tasks, **UI-OCEANUS**-7B achieves 56.9 on unseen mini-programs, surpassing the significantly larger Base-32B (49.6). This indicates that our method learns transferable interaction patterns rather than memorizing app-specific layouts. Furthermore, on the challenging OOD Android transition benchmark, **UI-OCEANUS**-7B consistently outperforms its base model across all tasks, suggesting transfer beyond mini-program layouts in this controlled setting.

Compositional generalization. Crucially, although trained strictly on single-step transitions, **UI-OCEANUS** exhibits strong compositional generalization on Level 2 tasks. This implies that **UI-OCEANUS** does not merely memorize single-step transitions but enables the agent to mentally "chain" atomic GUI transition patterns. This capability supports multi-step consequence prediction needed for long-horizon planning.

4.4.3 Cross-Platform Transfer on AndroidWorld

To assess cross-platform transfer on a public benchmark, we evaluate matched Qwen2.5-VL baselines on AndroidWorld after identical AndroidControl SFT. **UI-OCEANUS** uses the same SFT data but is initialized with CPT performed exclusively on WeChat mini-program transitions.

As shown in Table 5, despite using no Android transitions during CPT and only lightweight AndroidControl SFT, **UI-OCEANUS** achieves consistent gains across both model scales, suggesting that the learned transition representations capture interaction patterns that transfer beyond the source ecosystem.

5 Conclusion

We introduce **UI-OCEANUS**, a framework that overcomes the data scalability bottleneck by learning a GUI transition world model from autonomous exploration. By shifting from trajectory imitation to learning atomic interaction dynamics, we unlock a scalable CPT supervision source independent of human annotation. Our results identify forward dynamics as the critical objective for this capability, yielding log-linear performance scaling on the massive WeChat ecosystem with no signs of saturation up to 32B parameters and 3.2B tokens. By separating the acquisition of interaction dynamics from the execution of user intent, **UI-OCEANUS** provides a scalable pathway toward generalist GUI agents.

6 Limitations and Potential Risks

Our current formulation predicts textual descriptions of future GUI states rather than executable simulator states, visual tokens, or DOM-level representations. While this semantic transition objective is lower-resolution than pixel-level environment modeling, it aligns naturally with language-conditioned GUI agents, where instructions, reasoning traces, sub-goals, and actions are all expressed in natural language. Nevertheless, textual supervision may still omit fine-grained spatial details such as layouts, animations, or rendering dynamics. We therefore view **UI-OCEANUS** as a semantic state-transition world model rather than a complete executable world model. Extending transition-aware GUI pretraining toward richer multimodal representations remains important future work.

In addition, our large-scale CPT corpus is collected from the WeChat mini-program ecosystem. Although we observe positive transfer to Android-World, the strongest empirical evidence remains within the source platform. Our AndroidWorld experiments are intended to evaluate cross-platform transfer rather than benchmark-specific SOTA performance. Extending transition-aware pretraining to broader public GUI environments such as OS-World remains future work.

A separate concern is that increasingly capable GUI agents may introduce potential dual-use risks. In principle, sufficiently capable GUI automation systems could be misused to automate deceptive interactions, spam workflows, or phishing-style interface manipulation. While our work focuses on transition world modeling rather than autonomous deployment, we believe real-world GUI agents should incorporate appropriate safety constraints, permission mechanisms, and human oversight before deployment in high-stakes environments.

References

Anthropic. 2025a. Claude opus 4.5. Accessed: 2026-01-29.

Anthropic. 2025b. Claude sonnet 4.5. Accessed: 2026-01-29.

Mahmoud Assran, Quentin Duval, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, Yann LeCun, and Nicolas Ballas. 2023. Self-supervised learning from images with a joint-embedding predictive architecture. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15619–15629.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, and 45 others. 2025a. Qwen3-vl technical report.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, and 8 others. 2025b. Qwen2.5-vl technical report. *arXiv preprint arXiv:2502.13923*.

ByteDance-Seed. 2025. Seed1.8 model card: Towards generalized real-world agency. Accessed: 2026-01-29.

Wentong Chen, Junbo Cui, Jinyi Hu, Yujia Qin, Junjie Fang, Yue Zhao, Chongyi Wang, Jun Liu, Guirong Chen, Yupeng Huo, and 1 others. 2024. Guicourse: From general vision language models to versatile GUI agents. *arXiv preprint arXiv:2406.11317*.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. 2024. Seeclick: Harnessing GUI grounding for advanced visual GUI agents. *arXiv preprint arXiv:2401.10935*.

Longxi Gao, Li Zhang, and Mengwei Xu. 2025. Uishift: Enhancing vlm-based gui agents through self-supervised reinforcement learning. *arXiv preprint arXiv:2505.12493*.

Google. 2021. Android monkey. https://developer.android.com/studio/test/monkey. Accessed: 2026-01-03.

Google. 2025. Gemini 3 flash. Accessed: 2026-01-29.

Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. 2021. Knowledge distillation: A survey. *International journal of computer vision*, 129(6):1789–1819.

Tianxiao Gu, Chengnian Sun, Xiaoxing Ma, Chun Cao, Chang Xu, Yuan Yao, Qirun Zhang, Jian Lu, and Zhendong Su. 2019. Practical GUI testing of Android applications via model abstraction and refinement. In *ICSE*, pages 269–280.

David Ha and Jürgen Schmidhuber. 2018. World models. *arXiv preprint arXiv:1803.10122*, 2(3).

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. 2019. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*.

Danijar Hafner, Jurgis Pasukonis, Jimmy Ba, and Timothy Lillicrap. 2025. Mastering diverse control tasks through world models. *Nature*, pages 1–7.

Wenyi Hong, Weihan Wang, Qingsong Lv, Jiazheng Xu, Wenmeng Yu, Junhui Ji, Yan Wang, Zihan Wang, Yuxiao Dong, Ming Ding, and 1 others. 2024. Cogagent: A visual language model for GUI agents. In *CVPR*, pages 14281–14290.

Yann LeCun. 2022. A path towards autonomous machine intelligence version 0.9. 2, 2022-06-27. *Open Review*, 62(1):1–62.

Shufan Li, Konstantinos Kallidromitis, Akash Gokul, Yusuke Kato, Kazuki Kozuka, and Aditya Grover. 2025. Mobileworldbench: Towards semantic world modeling for mobile agents. *arXiv preprint arXiv:2512.14014*.

Wei Li, William E Bishop, Alice Li, Christopher Rawles, Folawiyo Campbell-Ajala, Divya Tyamagundlu, and Oriana Riva. 2024. On the effects of data scale on UI control agents. *NeurIPS*, 37:92130–92154.

Yang Li, Gang Li, Luheng He, Jingjie Zheng, Hong Li, and Zhiwei Guan. 2020. Widget captioning: Generating natural language description for mobile user interface elements. *arXiv preprint arXiv:2010.04295*.

Kevin Qinghong Lin, Linjie Li, Difei Gao, Zhengyuan Yang, Shiwei Wu, Zechen Bai, Stan Weixian Lei, Lijuan Wang, and Mike Zheng Shou. 2025a. Showui: One vision-language-action model for gui visual agent. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 19498–19508.

Musen Lin, Minghao Liu, Taoran Lu, Lichen Yuan, Yiwei Liu, Haonan Xu, Yu Miao, Yuhao Chao, and Zhaojian Li. 2025b. Gui-rewalk: Massive data generation for gui agent via stochastic exploration and intent-aware reasoning. *arXiv preprint arXiv:2509.15738*.

Quanfeng Lu, Wenqi Shao, Zitao Liu, Fanqing Meng, Boxuan Li, Botong Chen, Siyuan Huang, Kaipeng Zhang, Yu Qiao, and Ping Luo. 2024. GUI odyssey: A comprehensive dataset for cross-app GUI navigation on mobile devices. *arXiv preprint arXiv:2406.08451*.

Dezhao Luo, Bohan Tang, Kang Li, Georgios Papoudakis, Jifei Song, Shaogang Gong, Jianye Hao, Jun Wang, and Kun Shao. 2025. Vimo: A generative visual gui world model for app agents. *arXiv preprint arXiv:2504.13936*.

OpenAI. 2025. Update to gpt-5 system card: Gpt-5.2. Technical report, OpenAI. Accessed: 2026-01-29.

Vardaan Pahuja, Yadong Lu, Corby Rosset, Boyu Gou, Arindam Mitra, Spencer Whitehead, Yu Su, and Ahmed Hassan. 2025. Explorer: Scaling exploration-driven web trajectory synthesis for multimodal web agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 6300–6323.

Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, and 1 others. 2025. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*.

Ram Ramrakhya, Andrew Szot, Omar Attia, Yuhao Yang, Anh Nguyen, Bogdan Mazoure, Zhe Gan, Harsh Agrawal, and Alexander Toshev. 2025. Scaling synthetic task generation for agents via exploration. *arXiv preprint arXiv:2509.25047*.

Dezhi Ran, Hao Wang, Wenyu Wang, and Tao Xie. 2023. Badge: prioritizing UI events with hierarchical multi-armed bandits for automated UI testing. In *ICSE*, pages 894–905.

Christopher Rawles, Alice Li, Daniel Rodriguez, Oriana Riva, and Timothy Lillicrap. 2023. Androidinthewild: A large-scale dataset for Android device control. *NeurIPS*, 36:59708–59728.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Ting Su, Guozhu Meng, Yuting Chen, Ke Wu, Weiming Yang, Yao Yao, Geguang Pu, Yang Liu, and Zhendong Su. 2017. Guided, stochastic model-based gui testing of android apps. In *Proceedings of the 2017 11th joint meeting on foundations of software engineering*, pages 245–256.

Qiushi Sun, Kanzhi Cheng, Zichen Ding, Chuanyang Jin, Yian Wang, Fangzhi Xu, Zhenyu Wu, Chengyou Jia, Liheng Chen, Zhoumianze Liu, and 1 others. 2025. Os-genesis: Automating gui agent trajectory construction via reverse task synthesis. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5555–5579.

Liujian Tang, Shaokang Dong, Yijia Huang, Minqi Xiang, Hongtao Ruan, Bin Wang, Shuo Li, Zhiheng Xi, Zhihui Cao, Hailiang Pang, and 1 others. 2025. Magicgui: A foundational mobile gui agent with scalable data pipeline and reinforcement fine-tuning. *arXiv preprint arXiv:2508.03700*.

Tencent. 2024. Weixin mini program platform capabilities. Accessed: 2026-01-29.

Faraz Torabi, Garrett Warnell, and Peter Stone. 2018. Behavioral cloning from observation. *arXiv preprint arXiv:1805.01954*.

Haoming Wang, Haoyang Zou, Huatong Song, Jiazhan Feng, Junjie Fang, Junting Lu, Longxiang Liu, Qinyu Luo, Shihao Liang, Shijue Huang, and 1 others. 2025. Ui-tars-2 technical report: Advancing gui agent with multi-turn reinforcement learning. *arXiv preprint arXiv:2509.02544*.

Kangrui Wang*, Pingyue Zhang*, Zihan Wang*, Yaning Gao*, Linjie Li*, Qineng Wang, Hanyang Chen, Chi Wan, Yiping Lu, Zhengyuan Yang, Lijuan Wang, Ranjay Krishna, Jiajun Wu, Li Fei-Fei, Yejin Choi, and Manling Li. 2025. Vagen:reinforcing world model reasoning for multi-turn vlm agents.

Shuai Wang, Weiwen Liu, Jingxuan Chen, Yuqi Zhou, Weinan Gan, Xingshan Zeng, Yuhan Che, Shuai Yu, Xinlong Hao, Kun Shao, and 1 others. 2024. Gui agents with foundation models: A comprehensive survey. *arXiv preprint arXiv:2411.04890*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Mengzhou Wu, Hao Wang, Jun Ren, Yuan Cao, Yuetong Li, Alex Jiang, Dezhi Ran, Yitao Hu, Wei Yang, and Tao Xie. 2024a. Skill-adpative imitation learning for UI test reuse. *arXiv preprint arXiv:2409.13311*.

Zhiyong Wu, Zhenyu Wu, Fangzhi Xu, Yian Wang, Qiushi Sun, Chengyou Jia, Kanzhi Cheng, Zichen Ding, Liheng Chen, Paul Pu Liang, and 1 others. 2024b. Os-atlas: A foundation action model for generalist gui agents. *arXiv preprint arXiv:2410.23218*.

Yifan Xu, Xiao Liu, Xinghan Liu, Jiaqi Fu, Hanchen Zhang, Bohao Jing, Shudan Zhang, Yuting Wang, Wenyi Zhao, and Yuxiao Dong. 2025a. Mobilerl: Online agentic reinforcement learning for mobile gui agents. *Preprint*, arXiv:2509.18119.

Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tianbao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. 2025b. Aguvis: Unified pure vision agents for autonomous GUI interaction. In *ICML*.

Jiabo Ye, Xi Zhang, Haiyang Xu, Haowei Liu, Junyang Wang, Zhaoqing Zhu, Ziwei Zheng, Feiyu Gao, Junjie Cao, Zhengxi Lu, and 1 others. 2025. Mobile-agent-v3: Foundamental agents for gui automation. *arXiv preprint arXiv:2508.15144*.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. 2025. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*.

Charlie Zhang, Graham Neubig, and Xiang Yue. 2025a. On the interplay of pre-training, mid-training, and rl on reasoning language models. *Preprint*, arXiv:2512.07783.

Danyang Zhang, Situo Zhang, Ziyue Yang, Zichen Zhu, Zihan Zhao, Ruisheng Cao, Lu Chen, and Kai Yu. 2025b. Progrm: Build better gui agents with progress rewards. *arXiv preprint arXiv:2505.18121*.

Jiwen Zhang, Jihao Wu, Yihua Teng, Minghui Liao, Nuo Xu, Xiao Xiao, Zhongyu Wei, and Duyu Tang. 2024. Android in the zoo: Chain-of-action-thought for GUI agents. *arXiv preprint arXiv:2403.02713*.

Kai Zhang, Xiangchao Chen, Bo Liu, Tianci Xue, Zeyi Liao, Zhihan Liu, Xiyao Wang, Yuting Ning, Zhaorun Chen, Xiaohan Fu, and 1 others. 2025c. Agent learning via early experience. *arXiv preprint arXiv:2510.08558*.

A Problem Formulation

We formalize the GUI navigation problem not merely as trajectory execution, but as learning the underlying transition dynamics of the interface.

GUI as a state transition graph. We model the GUI environment as a directed state transition graph $\mathcal{G} = (\mathcal{S}, \mathcal{E})$. Each node $s \in \mathcal{S}$ represents a unique UI state, formally defined as a tuple $s = (I, X)$, where $I \in \mathbb{R}^{H \times W \times 3}$ is the pixel-level screenshot and X denotes structural metadata (e.g., the Accessibility Tree). A directed edge $e \in \mathcal{E}$ represents an atomic transition (s_t, a_t, s_{t+1}). Here, an action $a_t \in \mathcal{A}$ is defined as a tuple $a_t = (\tau, \theta)$, where τ denotes the operation type (e.g., *click*, *scroll*, *input*) and θ represents the corresponding parameters (e.g., screen coordinates or input text content), with the full specification of $\mathcal{A}$ detailed in Appendix D. Executing a_t on state s_t leads to state s_{t+1}.

Forward dynamics (outcome prediction). This objective serves as a proxy objective for a semantic transition world model, predicting the next state s_{t+1} given the current state s_t and action a_t. We formulate this by minimizing the negative log-likelihood:

$$\mathcal{L}_{\text{fwd}} = -\mathbb{E}_{(s_t, a_t, s_{t+1}) \sim \mathcal{D}}[\log P_\theta(s_{t+1} \mid s_t, a_t)] \tag{1}$$

Inverse dynamics (action inference). Inverse dynamics aims to infer the action a_t responsible for the transition between s_t and s_{t+1}. The loss function is defined as:

$$\mathcal{L}_{\text{inv}} = -\mathbb{E}_{(s_t, a_t, s_{t+1}) \sim \mathcal{D}}[\log P_\theta(a_t \mid s_t, s_{t+1})] \tag{2}$$

Backward dynamics (precondition inference). Complementary to forward dynamics, this objective learns to infer the precondition state s_t given the executed action a_t and the outcome s_{t+1}. We minimize:

$$\mathcal{L}_{\text{bwd}} = -\mathbb{E}_{(s_t, a_t, s_{t+1}) \sim \mathcal{D}}[\log P_\theta(s_t \mid s_{t+1}, a_t)] \tag{3}$$

B Extended Discussion on Related Work

This appendix extends the discussion of background and related work in Section 2.

B.1 Learning Paradigms for GUI Agents

Recent advancements in generalist GUI agents have primarily focused on refining policy optimization paradigms. While initial efforts relied on straightforward Behavioral Cloning (BC) (Wu et al., 2024b; Lin et al., 2025a; Lu et al., 2024; Chen et al., 2024), the field has rapidly shifted towards multi-step Reinforcement Learning (RL) (Ye et al., 2025; Xu et al., 2025a; Wang et al., 2025) integrated with Chain-of-Thought (CoT) (Wei et al., 2022) reasoning to handle non-stationary, long-horizon tasks. However, recent studies on RL reveal a critical bottleneck: RL alone struggles to surpass the inherent capability ceiling of the base model (Zhang et al., 2025a; Yue et al., 2025). This underscores the necessity of elevating the foundation model's intrinsic capabilities via Continual Pre-Training (CPT) prior to policy alignment. Existing CPT approaches for GUI agents, however, are largely confined to static UI understanding, such as element grounding or screen captioning (Tang et al., 2025; Wu et al., 2024b). While these methods improve perception, they fail to capture the interaction dynamics of the interface. Distinct from these static objectives, our work targets a dynamic objective: learning a GUI transition world model via CPT on atomic transitions. By grounding the model in the forward dynamics of the interface (i.e., predicting consequences), we provide a scalable path to learning transition-aware representations for generalist GUI agents.

B.2 Scalable Data Acquisition for GUI Agents

A fundamental challenge to training generalist GUI agents is the data scalability bottleneck of Behavioral Cloning (BC). Practically, collecting high-quality human demonstrations is prohibitively expensive. To bypass these limitations, the field has pivoted toward synthetic data generation, primarily following two directions. One line of work attempts to synthesize execution trajectories by deploying agents to interact with the environment under specific instructions (Lin et al., 2025b; Sun et al., 2025; Ramrakhya et al., 2025; Pahuja et al., 2025). However, due to the strict long-horizon dependencies of GUI tasks, generating valid data is notoriously difficult; a single intermediate error invalidates the entire trajectory, resulting in extremely low yield rates for high-quality samples. Alternatively, other approaches focus on static tasks such as screen captioning or VQA by leveraging powerful foundation models to label GUI screenshots (Qin et al., 2025; Wu et al., 2024b; Tang et al., 2025). Yet, this relies on model-based distillation, increasing the risk that the agent inherits teacher-model hallucinations and lacks objective grounding in real execution. In contrast, our **UI-OCEANUS** framework reduces reliance on ungrounded teacher supervision by grounding supervision in observed executed transitions. By treating state transitions as execution-based verification, we mitigate the fragility of long-horizon synthesis and the bias of distillation, enabling performance to scale with autonomous exploration.

B.3 World Models and Dynamics in Digital Interfaces

Conceptualizing the GUI as a dynamic system aligns with the broader literature on world models in model-based Reinforcement Learning and representation learning, where frameworks (Hafner et al., 2025; Assran et al., 2023; LeCun, 2022) enable agents to plan by modeling future latent states. In the specific domain of GUIs, prior works such as ViMo (Luo et al., 2025) and VAGEN (Wang* et al., 2025) have explored this direction through explicit visual state prediction, while GUI-Shift (Gao et al., 2025) employs an inverse dynamics objective to infer actions from state changes. Recent concurrent work (Zhang et al., 2025c) proposes utilizing implicit world modeling as an auxiliary task, yet remains constrained by local branching from expert demonstrations, lacking a scalable, task-agnostic Continual Pre-Training objective to learn broad transition patterns. We distinguish our work by leveraging autonomous exploration and intrinsic environmental feedback to learn a GUI transition world model via Continual Pre-Training, establishing a transition-aware representation before agentic post-training.

C Prompt Templates

We present the specific prompt templates utilized for the synthetic environmental dynamics Continual Pre-Training (CPT) of **UI-OCEANUS** and the downstream GUI agent navigation tasks.

C.1 Synthetic Environmental Dynamics Tasks

The CPT tasks are designed to enable the model to master the underlying transition dynamics of the GUI environment. We adopt the following notations: I_t denotes the screenshot at step t; u_t denotes the natural language description of the action; a_t denotes the atomic action (e.g., coordinates); and $\mathcal{D}_t$ denotes the textual description of the interface state.

Forward Dynamics ($I_t, u_t \rightarrow \mathcal{D}_{t+1}$ and $I_t, a_t \rightarrow \mathcal{D}_{t+1}$). This task requires the model to predict the future state description given the current image and an action.

> **Forward Dynamics Prompt Template**
>
> **System:** You are a GUI operation expert.
> **User:** <image> Given the current image and the action performed on the image, predict the subsequent page in terms of its content and functionality.
> **Input:** {action_summary} or {atomic_action}

Inverse Dynamics ($I_t, I_{t+1} \rightarrow u_t/a_t$). This task infers the action performed between two states.

> **Inverse Dynamics Prompt Template**
>
> **System:** You are a GUI operation expert.
> **User:** <image> <image> Given the before and after images, predict the operation performed by the user.
> **Constraint:** Describe the operation in natural language OR select from atomic actions (click $x\ y$, input $x\ y\ t$, scroll $x\ y\ direction$).

Inverse Dynamics with Goal ($I_t, \mathcal{D}_{t+1} \rightarrow u_t/a_t$). The agent infers the action required to reach a specific described state.

> **Inverse Dynamics (State Description) Prompt Template**
>
> **System:** You are a GUI operation expert.
> **User:** <image> Given the current interface image, predict the operation performed by the user that would lead to the page described below.
> **Target Description:** {after_screenshot_summary}

Backward Dynamics ($u_t, I_{t+1} \rightarrow \mathcal{D}_t$). This task reconstructs the previous state description.

> **Backward Dynamics Prompt Template**
>
> **System:** You are a GUI operation expert.
> **User:** <image> Given the resulting page image and the intermediate action description, predict the content and functionality of the previous page.
> **Input:** {action_summary}

C.2 GUI Navigation Task

For the downstream navigation task, we utilize a Chain-of-Thought (CoT) approach.

Navigation Prompt

<image> <image>
You are an advanced GUI navigation assistant capable of perceiving and interacting with mobile interfaces. The provided image sequence represents the history of operations, with the last image showing the current UI state.

Current Instruction: {instruction}
User History: {history}

Based on the visual context and history, predict the next optimal operation. Your output must strictly adhere to the following XML-style format:
```
<think>...</think>
<sub_goal>...</sub_goal>
<answer>...</answer>
```

1. Thinking Process (`<think>`)
Conduct a step-by-step reasoning process: (1) Analyze the current UI layout and identify interactive elements; (2) Verify if previous actions were successful; (3) Reflect on any potential errors or deviations; (4) Formulate a high-level strategy to align with the user's instruction.

2. Sub-goal Planning (`<sub_goal>`)
Translate your strategy into a concise, natural language description of the immediate next step (e.g., "Click the search icon on the top right", "Scroll down to find the settings").

3. Action (`<answer>`)
Map the sub-goal to a precise executable primitive from the following 5 categories:

1. `click x y` – Tap at coordinates (x, y).
2. `input x y t` – Focus at (x, y) and type text t.
3. `finish` – Terminate the task successfully.
4. `scroll x y dir` – Scroll from (x, y) in direction `dir`.
5. `wait` – Pause for system response.

C.3 Generalization Evaluation Prompts

To rigorously assess cross-domain transfer (Level 1) and compositional generalization (Level 2) as discussed in Section 4.4, we employ specialized prompt templates that facilitate objective verifica-

tion via a VLM judge.

Forward Dynamics Generalization (L1 & L2). Unlike the standard CPT objective which generates a holistic description, the evaluation prompts require the model to explicitly predict 5 distinct UI elements.

Forward Dynamics L1 (Atomic) Evaluation Prompt

System: You are a GUI operation expert.
User: <image> Given the current image and an action description, predict the 5 key elements that will appear on the subsequent page.
Action Description: {action_description}
Please output exactly five elements following the format below:
```
<element_1>Description of element 1,
be concise</element_1>
<element_2>Description of element 2,
be concise</element_2>
<element_3>Description of element 3,
be concise</element_3>
<element_4>Description of element 4,
be concise</element_4>
<element_5>Description of element 5,
be concise</element_5>
```

Inverse Dynamics Generalization (L2). For Level 2 Inverse Dynamics, the model must infer the initial action in a two-step chain, given only the start and end states (skipping the intermediate observation).

C.4 VLM-based Verification Judges

To automate the evaluation of open-ended generation in our generalization experiments (Section 4.4), we employ two distinct VLM judges. Both judges utilize a standardized structure to ensure rigorous and consistent verification.

Judge for Inverse Dynamics (Action Consistency). This judge evaluates whether the predicted action is visually and functionally equivalent to the ground truth (Binary Score: 0 or 1).

Judge for Forward Dynamics (Element Prediction). This judge evaluates the accuracy of the predicted next-state elements by calculating the precision of the top-5 predictions (Discrete Score: 0, 0.2, ..., 1).

D Action Space Specification

We define the action space $\mathcal{A}$ as a set of atomic operations supported by the agent. Each action is represented as a tuple $a_t = (\tau, \theta)$, where τ specifies the primitive type and θ contains the necessary parameters. The representation of spatial coordinates (x, y) adapts to the underlying vision-language backbone:

- **Qwen2.5-VL Series:** Utilizes **absolute pixel coordinates** $(x, y) \in [0, W] \times [0, H]$ based on the original screenshot resolution.

- **Qwen3-VL Series:** Utilizes **normalized coordinates** quantized to the integer range $[0, 1000]$.

The specific primitives and their parameter structures are summarized in Table 6.

Table 6: Definition of the Action Space.

Type (τ)	Params (θ)	Description
CLICK	(x, y)	Tap at pixel or normalized coordinates.
INPUT	(x, y, text)	Focus on the target element at (x, y) and type the provided text string.
SCROLL	(x, y, dir)	Scroll from (x, y) toward UP, DOWN, LEFT, or RIGHT.
FINISH	$\emptyset$	Terminate the current episode immediately.

E Details of Data Filtering Pipeline

This section details the implementation of the deduplication stages using Locality-Sensitive Hashing (LSH) for both graph-structured accessibility trees and high-dimensional screenshots.

E.1 Structural Transition Deduplication

To identify interface states with identical logic but varying content, we model transitions as sets of structural tokens.

Tokenization & MinHash. We extract tokens from the accessibility tree nodes based on semantic attributes (e.g., tag, xpath, events). A transition is represented by the union of hashed tokens from both the pre- and post-action states. We generate MinHash signatures to efficiently estimate Jaccard similarity, reducing variable-length token sets to fixed-length vectors.

LSH Indexing. We employ a banding strategy to index these signatures. Transitions colliding in any band are retrieved as candidates. We then verify candidates against a Jaccard similarity threshold, retaining only unique representatives for the final dataset.

E.2 Visual Transition Deduplication

For opaque components (e.g., WebViews), we utilize a composite visual fingerprinting strategy combining frequency and gradient domains.

Composite Hashing. For each transition, we concatenate the **Perceptual Hash (pHash)** and **Difference Hash (dHash)** of the start and end screenshots. This combination ensures robustness against rendering noise while remaining sensitive to significant layout changes.

Table 7: **Action distribution before and after filtering.**

Action	Raw	Filtered
Click	60.2%	71.6%
Input	7.0%	12.0%
Scroll	5.0%	9.9%
Back	27.8%	6.5%

Table 8: **Semantic filtering breakdown.** Percentages are measured within the semantic filtering stage.

Category	Disposition	Share
Loading screens	Removed	1.2%
Error screens	Removed	0.1%
Latency no-ops	Removed	16.3%
Auto-play changes	Removed	1.9%
Popups	Removed	1.4%
Aligned static transitions	Retained	8.1%

Clustering Strategy. We employ bit-sampling LSH to project high-dimensional hashes into lower-dimensional buckets for indexing. Candidates are clustered using a Union-Find data structure based on Hamming distance thresholds. For each connected component, the transition with the highest data source priority is retained.

E.3 Semantic Filtering

We utilize Qwen3-VL-235B-Instruct as a semantic verifier. The model is prompted to output a binary validity score, retaining only transitions where the screen changes logically correspond to the annotated action.

E.4 Filtering Analysis

We further analyze how filtering changes the transition corpus. As shown in Table 7, filtering concentrates high-information actions such as clicks, inputs, and scrolls, while pruning a large portion of repetitive back navigation.

State coverage. We track distinct path keys, a signal not used by the filters, to estimate state coverage changes. The total number of distinct path keys drops by only 4.3%, suggesting that filtering removes redundancy without collapsing macro-level state diversity. Rare paths with 1–5 occurrences retain 60% of their volume, while highly repetitive paths with more than 1000 occurrences drop to 4%, indicating that the pipeline primarily removes frequent duplicates.

Semantic filtering breakdown. Table 8 summarizes the semantic filtering stage. The removed cases are dominated by valid but action-disconnected events such as latency no-ops, rather than invalid screens. We also explicitly retain causally aligned but visually unchanged transitions to avoid removing interaction-relevant cases that are not visually salient.

F Training Dynamics Analysis

Figure 4 illustrates the training dynamics discussed in Section 4.3. The faster drop in Inverse Dynamics loss is consistent with its sparse action target being easier to fit, while Forward Dynamics maintains a higher loss level for longer. We treat this curve as a diagnostic of objective difficulty rather than a standalone explanation of the downstream gap; Appendix G provides target-density controls.

Figure 4: **Training Loss Comparison.** Inverse Dynamics (orange) converges faster under sparse action targets, while Forward Dynamics (blue) maintains a higher loss level for longer.

G Controlled Objective Comparisons

Table 9 reports additional controls for the objective comparison in Section 4.3. The dense rich-inverse objective augments inverse dynamics with synthesized CoT rationales generated in hindsight by Qwen3.5-VL-397B-A17B, making its output density comparable to forward and backward dynamics. These controls help disentangle temporal direction, output modality, and target-token volume.

Output richness. Rich inverse dynamics controls for target richness by replacing sparse action labels with dense CoT-and-action outputs. The dense target substantially improves over standard inverse dynamics (54.6 vs. 48.7 Avg EM), but still trails full-scale forward dynamics (56.4 Avg EM). This suggests that the advantage of future-state prediction is not solely explained by richer textual outputs.

Temporal direction. Backward dynamics uses a dense state-description target comparable to forward dynamics, but predicts the past state rather

Table 9: **Target-density controls for dynamics objectives.** The controlled objectives are evaluated on Qwen3-VL-2B and Qwen3-VL-4B. Standard inverse, backward, and 100% forward dynamics correspond to the main ablation; 12.5% forward dynamics is included as a target-token-volume control.

Objective	Target Type	Density	Tokens	Scale	2B EM	4B EM	Avg EM
Std. Inv.	Action	Sparse	$\sim$10	100%	46.4	50.9	48.7
Rich Inv.	CoT+Action	Dense	$\sim$100	100%	49.5	59.6	54.6
Backward	Past State	Dense	$\sim$80	100%	50.4	58.7	54.6
Forward	Future State	Dense	$\sim$80	12.5%	49.4	58.3	53.9
Forward	Future State	Dense	$\sim$80	100%	**52.7**	**60.0**	**56.4**

Table 10: **Teacher model preference study.** Percentages are measured over 1,000 randomly sampled transitions. Candidate order is randomized.

Challenger	Challenger Wins	Tie	235B Wins
Qwen3-VL-8B	15.6%	43.0%	41.4%
Qwen3-VL-32B	38.2%	43.1%	18.7%
Qwen3.5-397B-A17B	22.6%	49.0%	28.4%

than the future state. Forward dynamics remains stronger than backward dynamics at the same data scale (56.4 vs. 54.6 Avg EM), indicating that action-conditioned future prediction is the most effective objective among the variants tested.

Target-token volume. The 12.5% forward setting provides a coarse control for total target-token volume: $12.5\% \times 80 \approx 10$ tokens per original transition, matching the approximate token budget of standard inverse dynamics. Even under this reduced data scale, forward dynamics reaches 53.9 Avg EM, exceeding standard inverse dynamics at 48.7 Avg EM. This does not remove all differences in target content and structure, but it suggests that the gain is not simply due to the total number of target tokens.

H   Teacher Model Ablation

UI-OCEANUS uses a VLM as a linguistic interpreter of observed transitions rather than as a generator of transitions. Both the pre-state and post-state screenshots are produced by actual system execution, while the teacher verbalizes the observed transition into text supervision. To study sensitivity to teacher scale, we conduct a side-by-side preference study on 1,000 randomly sampled transitions. For each transition, we compare descriptions generated by a challenger teacher against Qwen3-VL-235B-A22B, randomize candidate order, and ask an independent Qwen3.5-397B-A17B judge to choose the better description or declare a tie.

The results show mid-scale saturation: Qwen3-VL-32B outperforms the 235B interpreter in this preference study, while the larger 397B model does not yield further gains. This supports a more modest interpretation of the teacher role. The supervision remains language-mediated and therefore still depends on an interpreter, but the core transition signal is grounded in executed UI state changes rather than generated by the teacher itself. Similarly, semantic filtering removes only about 21% of post-deduplication transitions and checks action-feedback consistency, a simpler task than producing the transition. We therefore revise the claim from eliminating teacher dependence to reducing reliance on extreme-scale teacher capabilities by grounding supervision in observed transitions.

I   Hyperparameter Settings

We detail the hyperparameter configurations for both the Continual Pre-Training (CPT) phase and the Agentic Post-Training phase.

I.1   Continual Pre-Training (CPT)

The hyperparameters for the CPT phase are summarized in Table 11.

Table 11: **Hyperparameters for Continual Pre-Training.**

Hyperparameter	32B Models	7B-8B Models	2B-4B Models
Optimizer		AdamW	
Global Batch Size	2048	1024	1024
Peak Learning Rate	1×10^{-5}	2×10^{-5}	3×10^{-5}
LR Scheduler		Cosine	
Warmup Ratio		0.03	
Max Sequence Length		4096	
Weight Decay	0.1	0.01	0.01
Epochs		1	

I.2   Agentic Post-Training: SFT

Table 12 lists the settings for the Supervised Fine-Tuning stage.

Table 13: **General benchmark preservation.** Positive values indicate improvements after **UI-OCEANUS** CPT.

Benchmark	Base	Ours	Δ
MMBench (EN)	86.46	83.36	-3.10
MMStar	67.93	67.20	-0.73
MMMU (dev)	57.30	59.30	+2.00
MMMU (val)	61.90	60.00	-1.90
MathVista	74.70	72.80	-1.90
AI2D	82.93	83.52	+0.59
OCRBench	832	839	+7
MMVet	78.07	77.34	-0.73
TextVQA	77.34	80.21	+2.87
DocVQA	90.35	91.70	+1.35
MMLU	79.45	79.17	-0.28
C-Eval	80.89	81.63	+0.74

Table 12: **Hyperparameters for SFT.**

Hyperparameter	32B Models	7B-8B Models	2B-4B Models
Optimizer		AdamW	
Global Batch Size		64	
Peak Learning Rate	3×10^{-6}	6×10^{-6}	1×10^{-5}
LR Scheduler		Constant	
Max Sequence Length		4096	
Weight Decay		0	
Epochs		2	

J General Capability Preservation

To assess whether GUI-specialized CPT harms general capabilities, we compare the Qwen2.5-VL-32B base model with its **UI-OCEANUS** CPT counterpart on 11 public multimodal and reasoning benchmarks, with MMMU reported separately on dev and val splits. As shown in Table 13, general performance is largely preserved, with mild regressions on several tasks and gains on structured visual understanding benchmarks such as TextVQA and DocVQA.

K Dataset Statistics and SOTA Comparisons

We provide detailed statistics for the datasets utilized in our experiments, alongside a performance comparison against state-of-the-art proprietary models to assess the ceiling of our framework.

K.1 Offline Scalability Benchmark

Data Distribution. Table 14 summarizes the distribution of action primitives in both the SFT training set and the held-out test set used in Section 4.1. The SFT training set reflects the natural frequency of user interactions (dominated by Click, 79%), whereas the evaluation benchmark is curated to ensure a balanced coverage, specifically increasing the representation of Scroll (9.8%) and Input (11.0%) to rigorously test generalization.

Table 14: **Statistics of Action Primitives (Offline).** Counts and percentages of action types in SFT training vs. test sets.

Action Type	SFT Training Set		Test Set	
	Count	Pct.	Count	Pct.
Click	6,229	79.0%	6,048	69.6%
Input	608	7.7%	954	11.0%
Finish	944	12.0%	839	9.6%
Scroll	105	1.3%	849	9.8%
Total	**7,886**	**100.0%**	**8,690**	**100.0%**

Comparison with Proprietary Models (Offline). Table 15 presents the performance comparison between our **UI-OCEANUS** framework and state-of-the-art proprietary models (including GPT-5.2, Claude-4.5-Opus, and Gemini-3-Flash) as well as large-scale open-weight baselines on the offline scalability benchmark.

K.2 Online Evaluation Benchmark

Complementing the offline metrics, our Online Benchmark used in Section 4.2 evaluates generalization in dynamic environments.

Diversity and Coverage. The benchmark comprises 149 instructions covering over 50 unique Mini-Programs (Table 16). It spans 7 domains, from high-frequency scenarios (e.g., Food) to long-tail services (e.g., Medical), supporting evaluation on transferable interaction patterns rather than memorized layouts.

Performance vs. Proprietary Models (Online). Table 17 presents the Success Rate (SR) on the online benchmark. We list the performance of **UI-OCEANUS** across three progressive post-training stages and compare them against representative external models, including state-of-the-art proprietary models.

Table 15: **Offline Benchmark Performance vs. Proprietary & Large-Scale Models.** We report Exact Match (EM) and Type Match (TM) scores across different model families.

Model	Exact Match (EM)	Type Match (TM)
Proprietary Models		
GPT-5.2 (OpenAI, 2025) (w/ Grounding)	61.1	76.9
Claude-4.5-Sonnet (Anthropic, 2025b) (w/ Grounding)	64.8	81.2
Claude-4.5-Opus (Anthropic, 2025a) (w/ Grounding)	**69.2**	82.7
Gemini-3-Flash (Google, 2025) (w/ Grounding)	**69.2**	82.0
Open-Weight Baselines		
Qwen2.5-VL-32B	33.9	56.6
Qwen2.5-VL-72B	51.4	77.2
Qwen3-VL-32B	47.1	79.2
Qwen3-VL-235B-A22B	47.5	79.4
Qwen2.5-VL-32B (w/ Grounding)	56.5	77.9
Qwen2.5-VL-72B (w/ Grounding)	56.8	77.2
Qwen3-VL-32B (w/ Grounding)	61.2	79.3
Qwen3-VL-235B-A22B (w/ Grounding)	61.5	79.3
Ours		
Qwen3-VL-32B + **UI-OCEANUS** (CPT+SFT)	65.0	81.1
Qwen2.5-VL-32B + **UI-OCEANUS** (CPT+SFT)	64.8	82.1
Qwen2.5-VL-32B + **UI-OCEANUS** (CPT+SFT+GRPO)	68.9	**84.5**

Table 16: **Domain Distribution of the Online Benchmark.** Covering 7 distinct categories with over 50 unique Mini-Programs.

Domain	Tasks	Representative mini-programs
Travel & Transport	25	Ctrip, Didi, Railway 12306
Food & Drink	21	Starbucks, KFC, Meituan, Heytea
Entertainment & Sports	15	Maoyan, Damai, Supermonkey, Golflive
Shopping & Logistics	13	JD.com, SF Express, Xianyu, Cainiao
Life Services	13	State Gov. Service, Beike, China Mobile
Medical & Health	11	Tencent Health
Office & Efficiency	8	Tencent Docs, Wenjuanxing, Tencent Meeting
Others	43	Diverse long-tail utilities
Total	**149**	**over 50 unique mini-programs**

Table 17: **Online Success Rate vs. Proprietary Models.** Comparison of Success Rate (SR) on live mini-programs between our progressive pipeline and external baselines.

Category	Model / Stage	SR (%)	Gap w/ Best Ours
Ours (32B)	**UI-OCEANUS** (SFT Cold Start)	29.5	-14.8
	+ Step-level GRPO	38.9	-5.4
	+ Multi-step GRPO	**44.3**	–
Proprietary & External Baselines	Seed-1.8 (ByteDance-Seed, 2025) (w/ Grounding)	27.5	-16.8
	Claude-4.5-Opus (Anthropic, 2025a) (w/ Grounding)	46.3	+2.0
	Gemini-3-Flash (Google, 2025) (w/ Grounding)	49.0	+4.7