Adding neuroplasticity to a CNN-based in-silico model of neurodegeneration

Abstract

The aim of this work was to enhance the biological feasibility of a deep convo-
lutional neural network-based *in-silico* model of neurodegeneration of the visual
system by adding neuroplasticity to it. Therefore, deep convolutional networks
were trained for object recognition tasks and progressively lesioned to simulate
the onset of posterior cortical atrophy, a condition that affects the visual cortex
in patients with Alzheimer's disease (AD). After each iteration of injury, the net-
works were retrained on the training set to simulate the continual plasticity of the
human brain, when affected by a neurodegenerative disease. More specifically, the
injured parts of the network remained injured while we investigated how the added
retraining steps were able to recover some of the model's baseline performance.
The results showed that with retraining, a model's object recognition abilities are
subject to a smoother decline with increasing injury levels than without retraining
and, therefore, more similar to the longitudinal cognition impairments of patients
diagnosed with AD. Moreover, with retraining, the injured model exhibits internal
activation patterns similar to those of the healthy baseline model compared to the
injured model without retraining. In conclusion, adding retraining to the *in-silico*
setup improves the biological feasibility considerably and could prove valuable to
test different rehabilitation approaches *in-silico*.

1 Introduction

Deep learning models have not only emerged as integral tools for solving many complex classification,
regression, and object recognition problems, but are also increasingly explored as potential tools to
model information processing in the brain (Lo Vercio et al., 2020; Yamins & DiCarlo, 2016). Deep
convolutional neural networks (DCNNs), a deep learning model architecture specifically designed
for solving computer vision problems, were originally inspired by the neuron and synaptic structure
found in the mammalian visual cortex (Rawat & Wang, 2017). The concepts used to inspire DCNNs
date back to early models of the visual system, postulated by Hubel and Wiesel (Hubel & Wiesel,
1962, 1968). A recent developing avenue that is still in its infancy is the use of deep learning models
as an abstraction of a cognitively healthy human brain, which is used as the basis for simulating
neurodegenerative diseases (Tuladhar et al., 2021; Moore et al., 2022). In this work, we build upon
previously established work using CNNs for simulating posterior cortical atrophy (PCA), a condition
that can accompany Alzheimer's disease (AD). PCA is caused by the accelerated degeneration and
thinning of visual cortical areas (i.e., V1, V2, V3, V4) and results in patients experiencing a loss of
visual recognition abilities (da Silva et al., 2017; Crutch et al., 2012). Since DCNNs were specifically
designed for object recognition and modelled following information processing in the mammalian
brain, neuronal injuries as seen in PCA can be intuitively modelled in DCNNs. DCNNs and human
neural activation data have been compared in various works, where the popular VGG19 model has

Submitted to 4th Workshop on Shared Visual Representations in Human and Machine Visual Intelligence
(SVRHM) at NeurIPS 2022. Do not distribute.

been found to exhibit one of the highest similarity metrics in terms of the Brain Score and Brain Hierarchy Score (Schrimpf et al., 2018; Nonaka et al., 2021). Thus, in this study, we use VGG19 as a baseline, cognitively healthy object recognition model.

While model compression and pruning is an active branch of deep learning research, our paradigm does not follow typical pruning methods that aim to reduce the number of parameters in a model while retaining full function (Choudhary et al., 2020). In contrast, we use progressive unstructured random pruning and retraining to simulate the cognitive effects of a neurodegenerative disease as a function of abnormal levels of atrophy. Previous research has established parallels between synaptic and neuronal pruning and the onset of posterior cortical atrophy (Moore et al., 2022). This study expands upon and improves Moore et al. (2022) by adding the crucial mechanism of simulated neuroplasticity as seen in Figure 1. We find that by adding iterative retraining with every pruning step of synaptic ablation, the decline of visual cognition is much smoother and more similar to what is seen in patients with AD (Mattsson et al., 2017).

Figure 1: Pipeline of progressive synaptic injury with the added mechanism of neuroplasticity. After each iteration of synaptic damage, the model is retrained on the original training split of data and evaluated.

2 Methods and Materials

2.1 Models and Data

The basis for the cognitively healthy object recognition model is a VGG19 model trained on the CIFAR10 dataset (Russakovsky et al., 2015). The VGG19 architecture is comprised of five convolutional blocks, each followed by a max-pooling layer, and three fully-connected dense layers ending in a softmax activation with ten nodes corresponding to the ten respective classes in the dataset. CIFAR10 is a commonly used dataset for computer vision research made up of 60,000 32x32 natural color images. The train/test split is 50,000 and 10,000 images, respectively. The dataset consists of ten classes: plane, car, bird, cat, deer, dog, frog, horse, ship, and truck, with 6000 images in each class. Our model was trained for 10 epochs with a learning rate of 0.001, using a batch size of 40, and a stochastic gradient descent optimizer. After training the model performs with a mean class-wise accuracy of 92.3% on the test set of images.

2.2 Synaptic Ablation and Retraining

Synaptic ablation was imposed on the network in a uniformly disperse and progressive manner as proposed in Moore et al. (2022). This 'injury' was implemented by setting weights from convolutional layers and dense layers in the network to zero, effectively severing the connections between nodes. This is akin to progression of synaptic damage seen in neurological diseases that accelerate atrophy rates in the brain such as posterior cortical atrophy. We imposed synaptic ablation at a step rate of $(1 - (1 - \gamma))^n$ where γ is the relative fraction of weights being ablated to the remaining uninjured weights in the network, and n is the number of iterations of injury. In our experiments, γ is set to 0.2 (20% of weights ablated) and n is set to 15 iterations. Following each iteration of injury, we

retrained the model on the training split of data using the same initial training parameters for 3 epochs to investigate how model performance could be regained.

2.3 Representational Dissimilarity Matrices

Representational dissimilarity matrices (RDMs) were computed to examine the changes in internal activations and representations of categorized data of both the injured and retrained networks when compared to the healthy network. RDMs were generated by pairwise comparison between activations of the network's penultimate layer for all test set images using Pearson's correlation coefficient. We constructed RDMs for each iteration of both network ablation and retraining, and then compared them to the healthy network's RDM using Kendall's tau correlation coefficient. This effectively enabled us to quantify the effects of both injury and retraining on internal activations of the network.

3 Results

3.1 Accuracy

The results showed that model performance is immediately affected by the first step of random synaptic injury (20% of synapses), leading to a large drop in mean class-wise accuracy from 92.3% accuracy achieved by the healthy model on the test set to a mere 14.3%. Interestingly, accuracy was massively regained after 3 epochs of training and was restored to 91.9% after the first training session. This pattern continued to repeat with each iteration of injury leading to a massive drop in accuracy, with the model tending to perform only at chance level (10% accuracy). However, retraining continued to improve model accuracy by a large margin, until 91% of initial synapses had been removed. After this point, the model could not compensate for the continuing imposed damage. These effects are shown in Figure 2A.

3.2 Representational Dissimilarity Matrices

In line with the results of the model accuracy evaluation, the internal representations of the model were able to regenerate and recover with retraining after injury. In the first iteration of damage and retraining (20% of synapses ablated), the injured model's correlation to the healthy RDM revealed a Kendall's tau of 0.18. After retraining for three epochs, the model was able to reconstruct activations more similar to those of the healthy model, resulting in a Kendall's tau value of 0.71. Figure 2B shows how retraining after each injury step leads to regaining category-distinguishable activations and a smooth cognitive decline. A qualitative examination also reveals how the network activations are affected through injury and retraining. As seen in Figure 3, the uninjured network initially had clearly defined activations grouped according to classes in the CIFAR10 dataset. Upon injury, the network lost this categorical representation and the RDMs became noisy. After retraining, however, categorical structure between the classes is regained. This trend continues progressively as injury and retraining steps are applied up until 89.3% of the network synapses are ablated, at which point there no longer remains a difference in Kendall's tau correlation between injured and retrained RDMs.

4 Discussion

The main finding of this study are that with the incorporation of retraining to simulate neuroplasticity after the progression of injury, the model's object recognition abilities progressively decline at a much smoother and slower rate than without retraining. This slow decline is akin to the degradation of cognitive abilities seen in patients with PCA and AD (Fox et al., 1999; Hodges et al., 1995; Jefferson et al., 2006). Previous works using DCNNs to model neurodegenerative diseases used a static injury paradigm that led to extreme loss of object recognition abilities even with low levels (i.e., 15-20%) of synapses injured (Tuladhar et al., 2021; Moore et al., 2022). Expanding upon this work, here we developed a framework that is able to simulate irreversible injury, while the unaffected filters and weights were subjected to 're- learning' processes using training data. We found that the retrained model is able to compensate for the damaged pathways (synapses) and reconstructs the original activation patterns of the healthy model when presented with images in the test set. We believe that the introduction of the biologically important concept of neuroplasticity, which equips our DCNN with a retraining mechanism, can be seen as an important step towards developing biologically more

Figure 2: (A) Model accuracy as a function of progressive damage and retraining. The model immediately has a substantial drop in accuracy after 20% of synapses are removed but regains function after retraining on the training set. (B) Kendall's tau is plotted as a function of injury to compare injured and retrained RDMs to the healthy network's RDM. A perfect correlation is Kendall's tau = 1. As injury is imposed, the RDMs become much less correlated; however, this graph demonstrates how retraining allows the model to recover internal activation patterns more like the healthy model.

Figure 3: A qualitative examination of RDMs as two iterations of injury and retraining are completed. Before injury, the model has distinct activations for each of the ten different classes. As injury and retraining is imposed, the activations first lose their categorical nature but are able to recover some of it with retraining.

120   meaningful in silico models of PCA. The development of this field of work has the potential to lead
121   to positive societal implications by increasing understanding around the progression of these diseases.
122   There are currently no foreseen negative impacts.

123   One limitation of this work is the rather simplistic dataset that was used for the experiments. CIFAR10
124   only contains ten relatively easily distinguishable classes of images. To capture the true capacity of
125   human vision more accurately, a dataset with considerably more complexity will be used in future
126   work. Another limitation are some notable differences in information processing between DCNNs and
127   the biological visual system (Lonnqvist et al., 2021). For example, in DCNNs a single convolutional
128   kernel is used to cover the whole visual receptive field. However, while this remains to be true, the
129   object recognition performance of DCNNs is comparable to that of humans and DCNNs have the

ability to predict neural activation in the primate visual cortex better than any other method to date (Cadieu et al., 2014; Yamins et al., 2014).

Crucial future directions for this work will be to further investigate the details surrounding the iterative retraining process, as well as more realistically represent disease progression. This investigation will allow for the exploration of rehabilitation strategies in terms of what methods of retraining enable in silico models to regain the most function. For example, we can provide models with training data that is directly related to the types of errors the models begin to make with initial injury. This could be compared against re-training strategies that would simply re-use all initial training data. In addition, it may be important to evaluate the effects of other variables such as training the network on new data rather than previously seen data, or adjusting the number of epochs used in one iteration of retraining. By probing these types of differences in network plasticity and recovery, it may be possible to identify optimal intervention strategies and relate these findings to rehabilitation techniques used in patients with dementia.

References

Charles F. Cadieu, Ha Hong, Daniel L. K. Yamins, Nicolas Pinto, Diego Ardila, Ethan A. Solomon, Najib J. Majaj, and James J. DiCarlo. Deep Neural Networks Rival the Representation of Primate IT Cortex for Core Visual Object Recognition. *PLoS Computational Biology*, 10(12), dec 2014. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1003963.

Tejalal Choudhary, Vipul Mishra, Anurag Goswami, and Jagannathan Sarangapani. A comprehensive survey on model compression and acceleration. *Artificial Intelligence Review*, 53(7):5113–5155, oct 2020. ISSN 0269-2821. doi: 10.1007/s10462-020-09816-7.

Sebastian J Crutch, Manja Lehmann, Jonathan M Schott, Gil D Rabinovici, Martin N Rossor, and Nick C Fox. Posterior cortical atrophy, feb 2012. ISSN 14744422.

Mari N.Maia da Silva, Rebecca S. Millington, Holly Bridge, Merle James-Galton, and Gordon T. Plant. Visual dysfunction in posterior cortical atrophy, aug 2017. ISSN 16642295.

N. C. Fox, R. I. Scahill, W. R. Crum, and M. N. Rossor. Correlation between rates of brain atrophy and cognitive decline in AD. *Neurology*, 52(8):1687–1689, may 1999. ISSN 00283878. doi: 10.1212/wnl.52.8.1687.

John R. Hodges, Naida Graham, and Karalyn Patterson. Charting the Progression in Semantic Dementia: Implications for the Organisation of Semantic Memory. *Memory*, 3(3-4):463–495, sep 1995. ISSN 14640686. doi: 10.1080/09658219508253161.

D. H. Hubel and T. N. Wiesel. Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of Physiology*, 160(1):106–154, jan 1962. ISSN 00223751. doi: 10.1113/jphysiol.1962.sp006837.

D. H. Hubel and T. N. Wiesel. Receptive fields and functional architecture of monkey striate cortex. *The Journal of Physiology*, 195(1):215–243, mar 1968. ISSN 00223751. doi: 10.1113/jphysiol.1968.sp008455.

Angela Jefferson, Lamia Barakat, Tania Giovannetti, Robert Paul, and Guila Glosser. Object perception impairments predict instrumental activities of daily living dependence in Alzheimer's disease. *Journal of Clinical and Experimental Neuropsychology*, 28(6):884–897, sep 2006. ISSN 13803395. doi: 10.1080/13803390591001034.

Lucas Lo Vercio, Kimberly Amador, Jordan J Bannister, Sebastian Crites, Alejandro Gutierrez, M. Ethan MacDonald, Jasmine Moore, Pauline Mouches, Deepthi Rajashekar, Serena Schimert, Nagesh Subbanna, Anup Tuladhar, Nanjia Wang, Matthias Wilms, Anthony Winder, and Nils D Forkert. Supervised machine learning tools: A tutorial for clinicians. *Journal of Neural Engineering*, 17(6):062001, dec 2020. ISSN 17412552. doi: 10.1088/1741-2552/abbff2.

Ben Lonnqvist, Alban Bornet, Adrien Doerig, and Michael H. Herzog. A comparative biology approach to DNN modeling of vision: A focus on differences, not similarities. *Journal of Vision*, 21(10):17, sep 2021. ISSN 1534-7362. doi: 10.1167/jov.21.10.17.

Niklas Mattsson, Ulf Andreasson, Henrik Zetterberg, and Kaj Blennow. Association of Plasma Neurofilament Light With Neurodegeneration in Patients With Alzheimer Disease. *JAMA Neurology*, 74(5):557, may 2017. ISSN 2168-6149. doi: 10.1001/jamaneurol.2016.6117.

Jasmine A. Moore, Anup Tuladhar, Zahinoor Ismail, Pauline Mouches, Matthias Wilms, and Nils D. Forkert. Dementia in Convolutional Neural Networks: Using Deep Learning Models to Simulate Neurodegeneration of the Visual System. *Neuroinformatics*, sep 2022. ISSN 1539-2791. doi: 10.1007/s12021-022-09602-6.

Soma Nonaka, Kei Majima, Shuntaro C. Aoki, and Yukiyasu Kamitani. Brain hierarchy score: Which deep neural networks are hierarchically brain-like? *iScience*, 24(9):103013, sep 2021. ISSN 25890042. doi: 10.1016/j.isci.2021.103013.

Waseem Rawat and Zenghui Wang. Deep convolutional neural networks for image classification: A comprehensive review, sep 2017. ISSN 1530888X.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision*, 115(3):211–252, dec 2015. ISSN 15731405. doi: 10.1007/s11263-015-0816-y.

Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J. Majaj, Rishi Rajalingham, Elias B. Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, Kailyn Schmidt, Daniel L.K. Yamins, and James J. DiCarlo. Brain-Score: Which Artificial Neural Network for Object Recognition is most Brain-Like? *bioRxiv*, 2018. ISSN 2692-8205. doi: 10.1101/407007.

Anup Tuladhar, Jasmine A. Moore, Zahinoor Ismail, and Nils D. Forkert. Modeling Neurodegeneration in silico With Deep Learning. *Frontiers in Neuroinformatics*, 15, nov 2021. ISSN 1662-5196. doi: 10.3389/fninf.2021.748370.

Daniel L.K. Yamins and James J. DiCarlo. Using goal-driven deep learning models to understand sensory cortex. *Nature Neuroscience*, 19(3):356–365, 2016. ISSN 15461726. doi: 10.1038/nn.4244.

Daniel L.K. Yamins, Ha Hong, Charles F. Cadieu, Ethan A. Solomon, Darren Seibert, and James J. DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences of the United States of America*, 111(23):8619–8624, jun 2014. ISSN 10916490. doi: 10.1073/pnas.1403112111.