# Conditionally Adaptive Multi-Task Learning: Improving Transfer Learning in NLP Using Fewer Parameters & Less Data

## Abstract

Multi-Task Learning (MTL) networks have emerged as a promising method for transferring learned knowledge across different tasks. However, MTL must deal with challenges such as: overfitting to low resource tasks, catastrophic forgetting, and negative task transfer, or learning interference. Often, in Natural Language Processing (NLP), a separate model per task is needed to obtain the best performance. However, many fine-tuning approaches are both parameter inefficient, i.e., potentially involving one new model per task, and highly susceptible to losing knowledge acquired during pretraining. We propose a novel Transformer based Adapter consisting of a new conditional attention mechanism as well as a set of task-conditioned modules that facilitate weight sharing. Through this construction, we achieve more efficient parameter sharing and mitigate forgetting by keeping half of the weights of a pretrained model fixed. We also use a new multi-task data sampling strategy to mitigate the negative effects of data imbalance across tasks. Using this approach, we are able to surpass single task fine-tuning methods while being parameter and data efficient (using around 66% of the data). Compared to other BERT Large methods on GLUE, our 8-task model surpasses other Adapter methods by 2.8% and our 24-task model outperforms by 0.7-1.0% models that use MTL and single task fine-tuning. We show that a larger variant of our single multi-task model approach performs competitively across 26 NLP tasks and yields state-of-the-art results on a number of test and development sets. Our code is publicly available[1].

## 1 Introduction

The introduction of deep, contextualized Masked Language Models (MLM)[2] trained on massive amounts of unlabeled data has led to significant advances across many different Natural Language Processing (NLP) tasks (Peters et al., 2018; Liu et al., 2019a). Much of these recent advances can be attributed to the now well-known BERT approach (Devlin et al., 2018). Substantial improvements over previous state-of-the-art results on the GLUE benchmark[3] (Wang et al., 2018) have been obtained by multiple groups using BERT models with task specific fine-tuning. The "BERT-variant + fine-tuning" formula has continued to improve over time with newer work constantly pushing the state-of-the-art forward on the GLUE benchmark. The use of a single neural architecture for multiple NLP tasks has shown promise long before the current wave of BERT inspired methods (Collobert & Weston, 2008) and recent work has argued that autoregressive language models (ARLMs) trained on large-scale datasets – such as the GPT family of models (Radford et al., 2018), are in practice multi-task learners (Brown et al., 2020). However, even with MLMs and ARLMs trained for multi-tasking, single task fine-tuning is usually also employed to achieve state-of-the-art performance on specific tasks of interest. Typically this fine-tuning process may entail: creating a task-specific fine-tuned model (Devlin et al., 2018), training specialized model components for task-specific predictions (Houlsby et al., 2019) or fine-tuning a single multi-task architecture (Liu et al., 2019b).

---

[1] https://github.com/CAMTL/CA-MTL
[2] For reader convenience, all acronyms in this paper are summarized in section A.1 of the Appendix.
[3] https://gluebenchmark.com/tasks

*Single-task* fine-tuning over all pretrained model parameters may have other issues. Recent analyses of such MLM have shed light on the linguistic knowledge that is captured in the hidden states and attention maps (Clark et al., 2019b; Tenney et al., 2019a; Merchant et al., 2020). Particularly, BERT has middle Transformer (Vaswani et al., 2017) layers that are typically the most transferable to a downstream task (Liu et al., 2019a). The model proxies the steps of the traditional NLP pipeline in a localizable way (Tenney et al., 2019a) — with basic syntactic information appearing earlier in the network, while high-level semantic information appearing in higher-level layers. Since pretraining is usually done on large-scale datasets, it may be useful, for a variety of downstream tasks, to conserve that knowledge. However, single task fine-tuning causes catastrophic forgetting of the knowledge

Figure 1: CA-MTL architecture uses (a) our uncertainty-based sampling algorithm (sec. 2.5) to choose task data. Then, the input tokens go through a frozen embedding layer, followed by (b) a Conditional Alignment layer (sec. 2.2). The rest contains frozen BERT layers followed by (c) the remaining trainable **task conditioned adapter layers**.

learned during MLM (Howard & Ruder, 2018). To preserve knowledge, freezing part of a pretrained network and using *Adapters* for new tasks have shown promising results (Houlsby et al., 2019).

Inspired by the human ability to transfer learned knowledge from one task to another new task, Multi-Task Learning (MTL) in a general sense (Caruana, 1997; Rajpurkar et al., 2016b; Ruder, 2017) has been applied in many fields outside of NLP. Caruana (1993) showed that a model trained in a *multi-task* manner can take advantage of the inductive transfer between tasks, achieving a better generalization performance. MTL has the advantage of computational/storage efficiency (Zhang & Yang, 2017), but training models in a multi-task setting is a balancing act; particularly with datasets that have different: **(a)** dataset sizes, **(b)** task difficulty levels, and **(c)** different types of loss functions. In practice, learning multiple tasks at once is challenging since negative transfer (Wang et al., 2019a), task interference (Wu et al., 2020; Yu et al., 2020) and catastrophic forgetting (Serrà et al., 2018) can lead to worse data efficiency, training stability and test performance across tasks compared to single task fine-tuning.

One of our objectives here is to understand if it is possible to outperform individually fine-tuned BERT-based models using only MTL. Towards that end, we seek to improve pretraining knowledge retention and multi-task inductive knowledge transfer. Our contributions consist of the following:

1. A new Transformer Attention Module using block-diagonal Conditional Attention (section 2.1) that allows the original query-key based attention to account for task-specific biases.
2. A new set of modules that adapt a pretrained MLM Transformer to new tasks, facilitate weight sharing in MTL, using:
   - A Conditional Alignment method that aligns the data of diverse tasks and that performs better than its unconditioned and higher capacity predecessor (section 2.2).
   - A Conditional Layer Normalization module that adapts layer normalization statistics to specific tasks (section 2.3) .
   - A Conditional Adapter that facilitates weight sharing and task-specific information flow from lower layers (Section 2.4).
3. A novel way to prioritize tasks with an uncertainty based multi-task data sampling method that helps balance the sampling of tasks during MTL to avoid catastrophic forgetting (see Section 2.5).

Architectural elements, mentioned in points 1 and 2 above, comprise a single adapter that is described by module in the methodology section. Our Conditional Adaptive Multi-Task Learning (CA-MTL) approach is illustrated in Figure 1. To the best of our knowledge, our work is the first to explore the use of a latent representation of tasks to modularize and adapt pretrained architectures. Further, we believe our work is also the first to examine uncertainty sampling for large-scale multi-task learning in NLP. We show the efficacy of CA-MTL by: **(a)** testing on 26 different tasks and **(b)** presenting state-of-the-art results on a number of test sets as well as superior performance against both single-task and MTL baselines. Moreover, we further demonstrate that our method has advantages over **(c)** other adapter networks, and **(d)** other MTL sampling methods. Finally, we provide ablations and separate analysis of the MT-Uncertainty Sampling technique in section 4.1 and of each component of the adapter in 4.2.

## 2 METHODOLOGY

This section is organized according to the two main MTL problems that we will tackle: (1) How to modularize a pretrained network with task latent representations? (2) How to balance different tasks in MTL? We define each task as: $\mathcal{T}_i \triangleq \{p_i(\mathbf{y}_i|\mathbf{x}_i, \mathbf{z}_i), \mathcal{L}_i, \tilde{p}_i(\mathbf{x}_i)\}$, where $\mathbf{z}_i$ is task $i$'s embedding, $\mathcal{L}_i$ is the task loss, and $\tilde{p}_i(\mathbf{x}_i)$ is the empirical distribution of the training data pair $\{\mathbf{x}_i, \mathbf{y}_i\}$, for $i \in \{1, \ldots, T\}$ and $T$ the number of supervised tasks. The MTL objective is:

$$\min_{\phi(\mathbf{z}), \theta_1, \ldots, \theta_T} \sum_{i=1}^{T} \mathcal{L}_i(f_{\phi(\mathbf{z}_i), \theta_i}(\mathbf{x}_i), \mathbf{y}_i) \tag{1}$$

where $f$ is the predictor function (includes encoder model and decoder heads), $\phi(\mathbf{z})$ are learnable generated weights conditioned on $\mathbf{z}$, and $\theta_i$ are task-specific parameters for the output decoder heads. We now present *five different modifications and extensions* that we have made to the generic Transformer architecture. In our ablation study of Table 1, we outline the effects of each component by reporting the average GLUE score for various configurations.

### 2.1 CONDITIONAL ATTENTION

Given $d$, the input dimensions, the query $\mathbf{Q}$, the key $\mathbf{K}$, and the value $\mathbf{V}$ as defined in Vaswani et al. (2017), we redefine the attention operation:

$$\text{Attention}(\mathbf{Q}, \mathbf{K}, \mathbf{V}, \mathbf{z}_i)) = \text{softmax}\left[\frac{\mathbf{Q}\mathbf{K}^T}{\sqrt{d}} + M(\mathbf{z}_i)\right]\mathbf{V}$$

$$M(\mathbf{z}_i) = \bigoplus_{n=1}^{N} A'_n(\mathbf{z}_i), \quad A'_n(\mathbf{z}_i) = A_n \gamma_i(\mathbf{z}_i) + \beta_i(\mathbf{z}_i),$$

where $L$ is the input sequence, $N$ the number of block matrices $A_n \in \mathbb{R}^{(L/N) \times (L/N)}$ along the diagonal of the attention matrix, and $M(\mathbf{z}_i) = \text{diag}(A'_1, \ldots, A'_N)$ a block diagonal conditional matrix. While the original attention matrix depends on the hidden states $h$, $M(\mathbf{z}_i)$ is a learnable

Figure 2: Conditional Matrix $M(\mathbf{z}_i)$ and a Transformer Attention Matrix from the Query/Key dot product are added before being applied to Value. The Conditional Matrix is not dependent on $\mathbf{h}$, the input hidden state, but only on $\mathbf{z}_i$, the task embedding.

weight matrix that only depends on the task embedding $\mathbf{z}_i \in \mathbb{R}^d$. $\gamma_i, \beta_i : \mathbb{R}^d \mapsto \mathbb{R}^{L^2/N^2}$ are Feature Wise Linear Modulation (Perez et al., 2018) functions. We also experimented with full-block Conditional Attention $\in \mathbb{R}^{L \times L}$. Not only did it have $N^2$ more parameters compared to the block-diagonal variant, but it also performed significantly worse on the GLUE development set (see FBA variant in table 15). It is possible that GLUE tasks derive a certain benefit from localized attention that is a consequence of $M(\mathbf{z}_i)$. With $M(\mathbf{z}_i)$, each element in a sequence can only attend to other elements in its subsequence of length $L/N$. In our experiments we used $N = d/L$. The full Conditional Attention mechanism used in our experiments is illustrated in Figure 2.

### 2.2 CONDITIONAL ALIGNMENT

Wu et al. (2020) showed that in MTL having $T$ separate alignment modules $R_1, \ldots, R_T$ increases BERT$_{\text{LARGE}}$ avg. scores on five GLUE tasks (CoLA, MRPC, QNLI, RTE, SST-2) by 2.35%. Inspired by this work, we found that adding a task conditioned alignment layer between the input embedding layer and the first BERT Transformer layer improved multi-task model performance. However, instead of having $T$ separate alignment matrices $R_i$ for each $T$ task, one alignment matrix $\hat{R}$ is generated as a function of the task embedding $z_i$. As in Wu et al. (2020), we tested this module on the same five GLUE tasks and with BERT$_{\text{LARGE}}$. Enabling task conditioned weight sharing across covariance alignment modules allows us to outperforms BERT$_{\text{LARGE}}$ by 3.61%. This is 1.26 % higher than having $T$ separate alignment matrices. Inserting $\hat{R}$ into BERT, yields the following encoder function $\hat{f}$:

$$\hat{f} = \sum_{t=1}^{T} g_{\theta_i}(E(\mathbf{x}_i)\hat{R}(\mathbf{z}_i)B), \qquad \hat{R}(\mathbf{z}_i) = R\gamma_i(\mathbf{z}_i) + \beta_i(\mathbf{z}_i) \tag{2}$$

122 where $\mathbf{x}_i \in \mathbb{R}^d$ is the layer input, $g_{\theta_i}$ is the decoder head function for task $i$ with weights $\theta_i$, $E$ the
123 frozen BERT embedding layer, $B$ the BERT Transformer layers and $R$ the linear weight matrix of
124 a single task conditioned alignment matrix. $\gamma_i, \beta_i : \mathbb{R}^d \mapsto \mathbb{R}^d$ are Feature Wise Linear Modulation
125 functions.

## 2.3 CONDITIONAL LAYER NORMALIZATION (CLN)

126

We extend the Conditional Batch Normalization idea from de Vries et al. (2017) to Layer Normalization (Ba et al., 2016). For task $\mathcal{T}_i$, $i \in \{1, \ldots, T\}$:

$$\mathbf{h}_i = \frac{1}{\sigma} \odot (\mathbf{a}_i - \mu) * \hat{\gamma}_i(\mathbf{z}_i) + \beta_i(\mathbf{z}_i), \qquad \hat{\gamma}_i(\mathbf{z}_i) = \boldsymbol{\gamma}' \gamma_i(\mathbf{z}_i) + \boldsymbol{\beta}' \tag{3}$$

127 where $\mathbf{h}_i$ is the CLN output vector, $\mathbf{a}_i$ are the preceding layer activations associated with task $i$, $\mu$
128 and $\sigma$ are the mean and the variance of the summed inputs within each layer as defined in Ba et al.
129 (2016). Conditional Layer Normalization is initialized with BERT's Layer Normalization affine
130 transformation weights and bias $\boldsymbol{\gamma}'$ and $\boldsymbol{\beta}'$ from the original formulation: $\mathbf{h} = \frac{1}{\sigma} \odot (\mathbf{a} - \mu) * \boldsymbol{\gamma}' + \boldsymbol{\beta}'$.
131 During training, the weight and bias functions of $\gamma_i(*)$ and $\beta_i(*)$ are always trained, while the
132 original Layer Normalization weight may be kept fixed. This module was added to account for task
133 specific rescaling of individual training cases. Layer Normalization normalizes the inputs across
134 features. The conditioning introduced in equation 2.3 allows us to modulate the normalization's
135 output based on a task's latent representation.

## 2.4 CONDITIONAL ADAPTERS

136

137 We created a task conditioned two layer feed-forward
138 neural network (called a Conditional Feed Forward or
139 CFF in Figure 3) with a bottleneck. The conditional
140 bottleneck layer follows the same transformation as
141 in equation 2. The adapter in Figure 3a is placed in-
142 side a Transformer layer. The conditional bottleneck
143 layer is also the main building block of the skip con-
144 nection seen in Figure 3b. This Conditional Adapter
145 allows lower layer information to flow upwards de-
146 pending on the task. Our intuition for introducing this
147 component is related to recent studies (Tenney et al.,
148 2019a) that showed that the "most important layers
149 for a given task appear at specific positions". As with
150 the other modules described so far, each task adap-
151 tation is created from the weights of a single shared
152 adapter that is modulated by the task embedding.

Figure 3: The Conditional Adapter in Figure a) is added to the top most Transformer layer of CA-MTL$_{\text{BASE}}$ and uses a CLN[1] and a conditional bottleneck. The Conditional Adapter in Figure b) is added alongside all Transformer layers in CA-MTL$_{\text{LARGE}}$. The connection at layer $j$ takes in the matrix sum of the Transformer layer output at $j$ and the previous connection's output at $j - 1$.

[1]CFF=Conditional Feed-Forward
CLN=Conditional Layer Norm

## 2.5 MULTI-TASK UNCERTAINTY SAMPLING

153

MT-Uncertainty Sampling is a task selection strategy that is inspired by Active Learning techniques. Our algorithm 1 in the Appendix, Section A.2. Similar to Active Learning, our algorithm first evaluates the model uncertain MT-Uncertainty Sampling uses Shannon Entropy, an uncertainty measure, to choose training examples by first doing forward pass through the model with $b \times T$ input samples. For an output classification prediction with $C_i$ possible classes and probabilities $(p_{i,1}, \ldots, p_{i,C_i})$, the Shannon Entropy $H_i$, for task $\mathcal{T}_i$ and $i \in \{1, \ldots, T\}$, our uncertainty measure $\mathcal{U}(\mathbf{x})$ are given by:

$$H_i = H_i(f_{\phi(\mathbf{z}_i), \theta_i}(\mathbf{x})) = -\sum_{c=1}^{C_i} p_c \log p_c, \qquad \mathcal{U}(x_i) = \frac{H_i(f_{\phi(\mathbf{z}_i), \theta_i}(\mathbf{x}))}{\hat{H} \times H'_i}, \tag{4}$$

$$\hat{H} = \max_{i \in \{1, \ldots, T\}} \bar{H}_i = \max \left[ \frac{1}{b} \sum_{\mathbf{x} \in \mathbf{x}_i} H_i \right], \qquad H'_i = -\sum_{c=1}^{C_i} \frac{1}{C_i} \log \left[ \frac{1}{C_i} \right], \tag{5}$$

where $\bar{H}_i$ is the average Shannon Entropy across $b$ samples of task $t$, $H_i'$, the Shannon entropy of choosing classes with uniform distribution and $\hat{H}$, the maximum of each task's average entropy over $b$ samples. $H_i'$ is normalizing factor that accounts for differing number of prediction classes (without the normalizing factor $H_i'$, tasks with a binary classification $C_i = 1$ were rarely chosen). Further, to limit high entropy outliers and to favor tasks with highest uncertainty, we normalize with $\hat{H}$. The measure in eq. 4 allows Algorithm 1 to choose $b$ samples from $b \times T$ candidates to train the model.

## 3 RELATED WORK

**Multi-Tasking in NLP and other fields** To take advantage of the potential positive transfer of knowledge from one task to another, several works have proposed carefully choosing which tasks to train as an intermediate step in NLP before single task fine-tuning (Bingel & Søgaard, 2017; Kerinec et al., 2018; Wang et al., 2019a; Standley et al., 2019; Pruksachatkun et al., 2020; Phang et al., 2018). The intermediate tasks are not required to perform well and are not typically evaluated jointly. In this work, all tasks are trained *jointly* and *all tasks used* are evaluated from a *single model*. In Natural Language Understanding (NLU), it is still the case that to get the best task performance one often needs a separate model per task (Clark et al., 2019c; McCann et al., 2018). At scale, Multilingual NMT systems (Aharoni et al., 2019) have also found that MTL model performance degrades as the number of tasks increases. We notice a similar trend in NLU with our baseline MTL model. Recently, approaches in MTL have tackled the problem by designing task specific decoders on top of a shared model (Liu et al., 2019b) or distilling multiple single-task models into one (Clark et al., 2019c). Nonetheless, such MTL approaches still involves single task fine-tuning. In this paper, we show that it is possible to achieve high performance in NLU without single task fine-tuning. MTL weight sharing algorithms such as Mixture-of-Experts (MoE) have found success in NLP (Lepikhin et al., 2020). CA-MTL can complement MoE since the Transformers multi-headed attention can be seen as a form of MoE (Peng et al., 2020). In Vision, MTL can also improve with optimization (Sener & Koltun, 2018) or gradient-based approaches (Chen et al., 2017; Yu et al., 2020).

**Adapters.** With single task fine-tuning, we have one model per task. *For $T$ tasks, we would need $T$ models, multiplying system memory requirements by $T$*. Adapter networks provide another promising avenue to limit the number of parameters needed when confronted with a large number of tasks. Adapters are trainable modules that are attached in specific locations of a pretrained network. This approach is useful with pretrained MLM models that have rich linguistic information (Tenney et al., 2019b; Clark et al., 2019b; Liu et al., 2019a; Tenney et al., 2019a). Recently, both Houlsby et al. (2019) added an adapter to a pretrained BERT model by fine-tuning the layer norms and adding feed forward bottlenecks in every Transformer layer. However, such methods adapt each task individually during the fine-tuning process. Unlike prior work, our method harnesses the vectorized representations of tasks to modularize a single pretrained model across all tasks. Stickland et al. (2019) and Tay et al. (2020) also mix both MTL and adapters with BERT and T5 encoder-decoder (Raffel et al., 2019b) respectively by creating local task modules that are controlled by a global task agnostic module. The main drawback is that a new set of non-shared parameters must be added when a new task is introduced. CA-MTL shares all parameters and is able to re-modulate existing weights with a new task embedding vector.

**Active Learning, Task Selection and Sampling** Our sampling technique is similar to the ones found in several active learning algorithms (Chen et al., 2006) that are based on Shannon entropy estimations. Reichart et al. (2008) and Ikhwantri et al. (2018) examined Multi-Task Active Learning (MTAL) using a two task annotation scenario and showed performance gains while needing less labeled data. Our approach is a substantially different variant of MTAL since it was developed for task selection. Instead of choosing one informative sample for $T$ different learners (or models) for each $T$ tasks, we choose $T$ tasks samples for *one model* to learn all tasks. Our algorithm differs in three ways: a) we use uncertainty sampling to maximize large scale MTL ($\gg 2$ tasks) performance via the modularization of a shared neural architecture; b) the algorithm weights each sample by the corresponding task score; c) the Shannon entropy is normalized to account for various losses (see equation 5). Recently, Glover & Hokamp (2019) explored task selection in MTL using learning policies based on counterfactual estimations (Charles et al., 2013). However, such method considers only fixed stochastic parameterized policies while our method *adapts* its selection criterion based on model uncertainty throughout the training process. Other than MTAL, Kendall et al. (2017) leveraged model uncertainty to balance MTL losses but not to select tasks as is proposed here.

## 4 EXPERIMENTS AND RESULTS

We show that our adapter of section 2 achieve parameter efficient transfer for 26 NLP tasks. We have organized our experiments and discussion of results in the following way for each section:

- 4.1- we study our MT Uncertainty Sampling vs other task sampling methods on a baseline model (without adapters). We also show how MT Uncertainty helps avoid catastrophic forgetting.
- 4.2- we analyze covariate shift and study ablations of CA-MTL modules. We observe higher average scores and lower score variance, revealing that CA-MTL helps mitigate negative task transfers. Input embeddings after Conditional Alignment exhibit improved task covariance similarity.
- 4.3- we test CA-MTL on 8 tasks, and observe improved performance compared to other Adapters.
- 4.4- we provide a simple method to "reconfigure" CA-MTL's weights on a new task using task embeddings which facilitates more efficient knowledge transfer. Specifically, CA-MTL delivers state-of-the-art results for the SciTail and SNLI evaluations in the low data regime.
- 4.5- we investigate large scale MTL on 24 tasks. CA-MTL exhibits higher performance with increased task count, demonstrating its ability to better balance model capacity. We compare with strong, BERT/RoBERTa-based, techniques that use both MTL and single task fine-tuning in Table 5. We find our approach again yields state-of-the-art results (see tables 6a, 6b, and 6c).

Our implementation of CA-MTL is based on HuggingFace (Wolf et al., 2019). Hyperparameters and our experimental set-up are outlined in A.5. To preserve the weights of the pretrained model, CA-MTL's bottom half Transformer layers are frozen in all experiments (except in section 4.4). We also tested different layer freezing configurations and found that freezing half the layers worked best on average (see Section A.7).

### 4.1 MULTI-TASK UNCERTAINTY SAMPLING

Our MT-Uncertainty sampling strategy, from section 2.5, is compared to 3 other task selection schemes: a) Counterfactual b) Task size c) Random. We used a $BERT_{BASE}$ (no adapters) on 200k iterations and with the same hyperparameters as in Glover & Hokamp (2019). For more information on Counterfactual task selection, we invite the reader to consult the full explanation in Glover & Hokamp (2019). For $T$ tasks and the dataset $D_i$ for tasks $i \in \{1, \ldots, T\}$, we rewrite the definitions of Random $\pi_{rand}$ and Task size $\pi_{|task|}$ sampling:

$$\pi_{rand} = 1/T, \quad \pi_{|task|} = |D_i| \left[ \sum_{i=1}^{T} |D_i| \right]^{-1} \quad (6)$$

In Figure 4, we see from the results that MT-Uncertainty converges faster by reaching the 80% average GLUE score line before other task sampling methods. Further, MT-Uncertainty maximum score on 200k iterations is at 82.2, which is 1.7% higher than Counterfactual sampling. The datasets in the GLUE benchmark offers a wide range of dataset sizes. This is useful to test how MT-Uncertainty manages a jointly trained low resource task (CoLA) and high resource task (MNLI). Figure 5 explains how catastrophic forgetting is curtailed by sampling tasks before performance drops. With $\pi_{rand}$, all of CoLA's

Figure 4: **MT-Uncertainty** vs. other task sampling strategies: median dev set scores on 8 GLUE tasks and using $BERT_{BASE}$. Data for the Counterfactual and Task Size policy $\pi_{|task|}$ (eq. 6) is from Glover & Hokamp (2019).

Figure 5: CoLA/MNLI Dev set scores and Entropy for $\pi_{rand}$ (left) and **MT-Uncertainty** (right).

tasks are sampled by iteration 500, at which point the larger MNLI dataset overtakes the learning process and CoLA's dev set performance starts to diminish. On the other hand, with MT-Uncertainty sampling, CoLA is sampled whenever Shannon entropy is higher than MNLI's. The model first assesses uncertain samples using Shannon Entropy then decides what data is necessary to train on. This process allows lower resource tasks to keep performance steady. We provide evidence in Figure

8 of A.2 that MT-Uncertainty is able to manage task difficulty — by choosing the most difficult tasks first.

## 4.2 Ablation and Module Analysis

In Table 1, we present the results of an ablation study to determine which elements of CA-MTL$_{\text{BERT-BASE}}$ had the largest positive gain on average GLUE scores. Starting from a MTL BERT$_{\text{BASE}}$ baseline trained using random task sampling ($\pi_{rand}$). Apart for the Conditional Adapter, each module as well as MT-Uncertainty lift overall performance and reduce variance across tasks. Please note that we also included

Table 1: Model ablation study[a] on the GLUE dev set. All models have the bottom half layers frozen.

| Model changes | Avg GLUE | $\sigma$ GLUE | % data used |
|---|---|---|---|
| BERT$_{\text{BASE}}$ MTL ($\pi_{rand}$) | 80.61 | 14.41 | 100 |
| + Conditional Attention | 82.41 | 10.67 | 100 |
| + Conditional Adapter | 82.90 | 11.27 | 100 |
| + CA and CLN | 83.12 | 10.91 | 100 |
| + MT-Uncertainty (CA-MTL$_{\text{BERT-BASE}}$) | **84.03** | **10.02** | 66.3 |

[a]CA=Conditional Alignment, CLN=Conditional Layer Normalization, $\sigma$=scores standard deviation across tasks.

accuracy/F1 scores for QQP, MRPC and Pearson/ Spearman correlation for STS-B to calculate score standard deviation $\sigma$. Intuitively, when negative task transfer occurs between two tasks, either (1) task interference is bidirectional and scores are both impacted, or (2) interference is unidirectional and only one score is impacted. We calculate $\sigma$ to get a complete picture of how task performance moves across the board. As we can see from Table 1, Conditional Attention, Conditional Alignment, Conditional Layer Normalization, MT-Uncertainty play roles in reducing $\sigma$ and increasing performance across tasks. This provides partial evidence of CA-MTL's ability to mitigating negative task transfer.

We show that Conditional Alignment can learn to capture covariate distribution differences with task embeddings co-learned from other adapter components of CA-MTL. In Figure 6, we arrive at similar conclusions as Wu et al. (2020), who proved that negative task transfer is reduced when task covariances are aligned. The authors provided a "covariance similarity score" to gauge covariance alignment. For task $i$ and $j$ with $m_i$ and $m_j$ data samples respectively, and given $d$ dimensional inputs to the first Transformer layer $X_i \in \mathbb{R}^{m_i \times d}$ and $X_j \in \mathbb{R}^{m_j \times d}$, we rewrite the steps to calculate the co-variance similarity score between task $i$ and $j$: (a) Take the covariance matrix $X_i^\top X_i$, (b) Find its best rank-$r_i$ approxima-tion $U_{i,r_i} D_{i,r_i} U_{i,r_i}^\top$, where $r_i$ is chosen to contain 99% of the singular values. (c) Apply steps (a), (b) to $X_j$, and compute the covariance similarity score $CovSim_{i,j}$:

Figure 6: Task performance vs. avg. covariance similarity scores (eq. 7) for MTL and CA-MTL.

$$CovSim_{i,j} := \frac{\|(U_{i,r_i} D_{i,r_i}^{1/2})^\top U_{j,r_j} D_{j,r_j}^{1/2}\|_F}{\|U_{i,r_i} D_{i,r_i}^{1/2}\|_F \cdot \|U_{j,r_j} D_{j,r_j}^{1/2}\|_F}. \quad CovSim_i = \frac{1}{T-1} \sum_{j \neq i} CovSim_{i,j} \quad (7)$$

Since we are training models with $T$ tasks, we take the average covariance similarity score $CovSim_i$ between task $i$ and all other tasks. We measure $CovSim_i$ using equation 7 between 9 single-task models trained on individual GLUE tasks. For each task in Figure 6, we measure the similarity score on the MTL trained BERT$_{\text{BASE}}$ baseline, e.g., CoLA (MTL), or CA-MTL$_{\text{BERT-BASE}}$ model, e.g., MNLI (CA-MTL). Our score improvement measure is the % difference between a single task model and MTL or CA-MTL on the particular task. We find that covariance similarity increases for 9 tasks and that performance increases for 7 out 9 tasks. These measurements confirm that the Conditional Alignment is able to align task covariance, thereby helping alleviate task interference.

## 4.3 Jointly training on 8 tasks: GLUE

In Table 2, we evaluate the performance of CA-MTL against single task fine-tuned models, MTL as well as the other BERT-based adapters on GLUE. As in Houlsby et al. (2019), MNLI$_m$ and MNLI$_{mm}$ are treated as separate tasks. Our results indicate that CA-MTL outperforms both the BASE adapter, PALS+Anneal Sampling (Stickland et al., 2019), and the LARGE adapter, Adapters-256 (Houlsby et al., 2019). Against single task (ST) models, CA-MTL is 1.3% higher than BERT$_{\text{BASE}}$, with 5 out 9 tasks equal or greater performance, and 0.7% higher than BERT$_{\text{LARGE}}$, with 3 out 9 tasks equal or greater performance. ST models, however, need 9 models or close to $9\times$ more parameters for all 9 tasks. We noted that CA-MTL$_{\text{BERT-LARGE}}$'s average score is driven by strong RTE scores. While RTE

283 benefits from MTL, this behavior may also be a side effect of layer freezing. In Table 15, we see that
284 CA-MTL has gains over ST on more and more tasks as we gradually unfreeze layers.

Table 2: Adapters with layer freezing vs. ST/MT on GLUE test set. F1 scores are reported for QQP/MRPC, Spearman's correlation for STS-B, accuracy on the matched/mismatch sets for MNLI, Matthew's correlation for CoLA and accuracy for other tasks. * Individual scores not available. ST=Single Task, MTL=Multitask, g.e.= greater or equal to. Results from: [1]Devlin et al. (2018) [2]Stickland et al. (2019). [3]Houlsby et al. (2019) .

| Method | Type | Total params | Trained params/task | # tasks g.e. ST | GLUE | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | CoLA | MNLI | MRPC | QNLI | QQP | RTE | SST-2 | STS-B | Avg |
| **Base Models — Test Server Results** | | | | | | | | | | | | | |
| BERT$_{BASE}$[1] | ST | 9.0× | 100% | — | 52.1 | 84.6/83.4 | 88.9 | 90.5 | 71.2 | 66.4 | 93.5 | 85.8 | 79.6 |
| BERT$_{BASE}$[2] | MTL | 1.0× | 11.1% | 2 | 51.2 | 84.0/83.4 | 86.7 | 89.3 | 70.8 | 76.6 | 93.4 | 83.6 | 79.9 |
| PALs+Anneal Samp.[2] | MTL | 1.13× | 12.5% | 4 | 51.2 | 84.3/83.5 | 88.7 | 90.0 | 71.5 | 76.0 | 92.6 | 85.8 | 80.4 |
| *CA-MTL*$_{BERT-BASE}$ (ours) | MTL | 1.12× | 5.6 % | **5** | 53.1 | 85.9/85.8 | 88.6 | 90.5 | 69.2 | 76.4 | 93.2 | 85.3 | **80.9** |
| **Large Models — Test Server Results** | | | | | | | | | | | | | |
| BERT$_{LARGE}$[1] | ST | 9.0× | 100% | — | 60.5 | 86.7/85.9 | 89.3 | 92.7 | 72.1 | 70.1 | 94.9 | 86.5 | 82.1 |
| Adapters-256[3] | ST | 1.3× | 3.6% | 3 | 59.5 | 84.9/85.1 | 89.5 | 90.7 | 71.8 | 71.5 | 94.0 | 86.9 | 80.0 |
| *CA-MTL*$_{BERT-LARGE}$ (ours) | MTL | 1.12× | 5.6% | 3 | 59.5 | 85.9/85.4 | 89.3 | 92.6 | 71.4 | 79.0 | 94.7 | 87.7 | **82.8** |

### 4.4 TRANSFER TO NEW TASKS

286 In Table 3 we examine the ability of our
287 method to quickly adapt to new tasks. We
288 performed domain adaptation on SciTail (Khot
289 et al., 2018) and SNLI (Bowman et al., 2015)

Table 3: Domain adaptation results on dev. sets for *BASE* models. [1]Liu et al. (2019b), [2]Jiang et al. (2020)

| % data used | SciTail | | | | SNLI | | | |
|---|---|---|---|---|---|---|---|---|
| | 0.1% | 1% | 10% | 100% | 0.1% | 1% | 10% | 100% |
| BERT$_{BASE}$[1] | 51.2 | 82.2 | 90.5 | 94.3 | 52.5 | 78.1 | 86.7 | 91.0 |
| MT-DNN[1] | 81.9 | 88.3 | 91.1 | 95.7 | 81.9 | 88.3 | 91.1 | 95.7 |
| MT-DNN$_{SMART}$[2] | 82.3 | 88.6 | 91.3 | **96.1** | 82.7 | 86.0 | **88.7** | **91.6** |
| CA-MTL$_{BERT}$ | **83.2** | **88.7** | **91.4** | 95.6 | **82.8** | **86.2** | 88.0 | 91.5 |

290 datasets using a CA-MTL$_{BASE}$ model trained on GLUE and a new linear decoder head. We tested
291 several pretrained and randomly initialized task embeddings in a zero-shot setting. The complete
292 set of experiments with all task embeddings can be found in the Appendix, Section A.4. We then
293 selected the best task embedding for our results in Table 3. STS-B and MRPC MTL-trained task
294 embeddings performed best on SciTail and SNLI respectively. CA-MTL$_{BERT-BASE}$ has faster adapta-
295 tion than MT-DNN$_{SMART}$ (Jiang et al., 2020) as evidenced by higher performances in low-resource
296 regimes (0.1% and 1% of the data). When trained on the complete dataset, CA-MTL$_{BERT-BASE}$ is on
297 par with MT-DNN$_{SMART}$. Unlike MT-DNN$_{SMART}$ however, we do not add context from a semantic
298 similarity model – MT-DNN$_{SMART}$ is built off HNN (He et al., 2019). Nonetheless, with a larger
299 model, CA-MTL surpasses MT-DNN$_{SMART}$ on the full SNLI and SciTail datasets in Table 6.

### 4.5 JOINTLY TRAINING ON 24 TASKS: GLUE/SUPER-GLUE, MRQA AND WNUT2017

301 **Effects of Scaling Task Count.** In Figure 7 we con-
302 tinue to test if CA-MTL mitigates *task interference*
303 by measuring GLUE average scores when progres-
304 sively adding 9 GLUE tasks, 8 Super-GLUE tasks
305 (Wang et al., 2019b), 6 MRQA tasks (Fisch et al.,
306 2019). Tasks are described in Appendix section A.3.
307 The results show that adding 23 tasks drops the per-
308 formance of our baseline MTL BERT$_{BASE}$ ($\pi_{rand}$).
309 MTL BERT increases by 4.3% when adding MRQA
310 but, with 23 tasks, the model performance drops by
311 1.8%. The opposite is true when CA-MTL modules
312 are integrated into the model. CA-MTL continues to

Figure 7: Effects of adding more datasets on avg GLUE scores. Experiments conducted on 3 epochs. When 23 tasks are trained jointly, performance of CA-MTL$_{BERT-BASE}$ continues to improve.

313 show gains with a large number of tasks and surpasses the baseline MTL model by close to 4% when
314 trained on 23 tasks.

315 **24-task CA-MTL.** We *jointly* trained large MTL baselines and CA-MTL models on GLUE/Super-
316 GLUE/MRQA and Named Entity Recognition (NER) WNUT2017 (Derczynski et al., 2017). Since
317 some dev. set scores are not provided and since RoBERTa results were reported with a median score
318 over 5 random seeds, we ran our own single seed ST/MTL baselines (marked "ReImp") for a fair
319 comparison. The dev. set numbers reported in Liu et al. (2019c) are displayed with our baselines in
320 Table 13. Results are presented in Table 4. We notice in Table 4 that even for large models, CA-MTL
321 provides large gains in performance on average over both ST and MTL models. For the BERT based
322 models, CA-MTL provides 2.3% gain over ST and higher scores on 17 out 24 tasks. For RoBERTa

based models, CA-MTL provides 1.2% gain over ST and higher scores on 15 out 24 tasks. We remind the reader that this is achieved with a single model. Even when trained with 16 other tasks, it is interesting to note that the MTL baseline perform better than the ST baseline on Super GLUE where most tasks have a small number of samples. Also, we used NER to test if we could still outperform the ST baseline on a token-level task, significantly different from other tasks. Unfortunately, while CA-MTL performs significantly better than the MTL baseline model, CA-MTL had not yet overfit on this particular task and could have closed the gap with the ST baselines with more training cycles.

**Comparisons with other methods.** In Table 5, CA-MTL$_{BERT}$ is compared to other Large BERT based methods that either use MTL + ST, such as MT-DNN (Liu et al., 2019b), intermediate tasks + ST, such as STILTS (Phang et al., 2018) or MTL model distillation + ST, such as BAM! (Clark et al., 2019c). Our method scores higher than MT-DNN on 5 of 9 tasks and by 1.0 % on avg. Against STITLS, CA-MTL realizes a 0.7 % avg. score gain, surpassing scores on 6 of 9 tasks. We also show that CA-MTL$_{RoBERTa}$ is within only 1.6 % of a RoBERTa ensemble of 5 to 7 models per task and that uses intermediate tasks.

Table 4: 24-task CA-MTL vs. ST and vs. 24-task MTL with frozen layers on GLUE, SuperGLUE, MRQA and NER development sets. ST=Single Task, MTL=Multitask, g.e.= greater or equal to. Details in section A.5.

| Model | Task Grouping | | | | Avg | # tasks | Total |
| | GLUE | SuperGLUE | MRQA | NER | | e.g. ST | Params |
|---|---|---|---|---|---|---|---|
| *BERT-LARGE models* | | | | | | | |
| ST$_{ReImp}$ | 84.5 | 68.9 | 79.7 | 54.1 | 76.8 | — | 24× |
| MTL$_{ReImp}$ | 83.2 | 72.1 | 77.8 | 42.2 | 76.4 | 9/24 | 1× |
| CA-MTL | 86.6 | 74.1 | 79.5 | 49.0 | 79.1 | **17/24** | 1.12× |
| *RoBERTa-LARGE models* | | | | | | | |
| ST$_{ReImp}$ | 88.2 | 76.5 | 83.6 | 57.8 | 81.9 | — | 24× |
| MTL$_{ReImp}$ | 86.0 | 78.6 | 80.7 | 49.3 | 80.7 | 7/24 | 1× |
| CA-MTL | 89.4 | 80.0 | 82.4 | 55.2 | 83.1 | **15/24** | 1.12× |

Using our 24-task CA-MTL large RoBERTa-based model, we report NER F1 scores on the WNUT2017 test set in Table 6a. We compare our result with RoBERTa$_{LARGE}$ and XLM-R$_{LARGE}$ (Nguyen et al., 2020) the current state-of-the-art (SOTA). Our model outperforms XLM-R$_{LARGE}$ by 1.6%, reaching a new state-of-the-art. Using domain adaptation as described in Section 4.4, we report results on the SciTail test set in Table 6b and SNLI test set

Table 5: Our 24-task CA-MTL vs. other large models on GLUE. F1 is reported for QQP/MRPC, Spearman's corr. for STS-B, Matthew's corr. for CoLA and accuracy for other tasks. *Split not available. **Uses intermediate task fine-tuning + ST.

| Model | GLUE tasks | | | | | | | | Avg |
| | CoLA | MNLI | MRPC | QNLI | QQP | RTE | SST-2 | STS-B | |
|---|---|---|---|---|---|---|---|---|---|
| *BERT-LARGE based models on Dev set.* | | | | | | | | | |
| MT-DNN | 63.5 | 87.1/86.7 | 91.0 | 92.9 | 89.2 | 83.4 | 94.3 | 90.6 | 85.6 |
| STILTS ** | 62.1 | 86.1* | 92.3 | 90.5 | 88.5 | 83.4 | 93.2 | 90.8 | 85.9 |
| BAM! | 61.8 | 87.0* | – | 92.5 | – | 82.8 | 93.6 | 89.7 | – |
| 24-task CA-MTL | 63.8 | 86.3/86.0 | 92.9 | 93.4 | 88.1 | 84.5 | 94.5 | 90.3 | **86.6** |
| *RoBERTa-LARGE based models on Test set.* | | | | | | | | | |
| RoBERTA** with Ensemble | 67.8 | 91.0/90.8 | 91.6 | 95.4 | 74.0 | 87.9 | 97.5 | 92.5 | **87.3** |
| 24-task CA-MTL | 62.2 | 89.0/88.4 | 92.0 | 94.7 | 72.3 | 86.2 | 96.3 | 89.8 | 85.7 |

in Table 6b. For SciTail, our model matches the current SOTA[4] ALUM (Liu et al., 2020), a RoBERTa large based model that additionally uses the SMART (Jiang et al., 2020) fine-tuning method. For SNLI, our model outperforms SemBert, the current SOTA[5].

# 5  CONCLUSION

Multi-task Learning (MTL) is promising for two main reasons. First, we can harness knowledge learned from other tasks to improve performance. Second, only one model is needed to solve multiple tasks, reducing the disk space requirements for downstream devices. In a large-scale 24-task NLP experiment, CA-MTL outperforms fully tuned single task models by 2.3% for BERT Large and by 1.2% for RoBERTa Large. When a BERT vanilla MTL model sees its performance drop as we increase the number of tasks, CA-MTL scores continue to climb. Each CA-MTL module that adapts a Transformer model is able to reduce performance variances between tasks, increase average scores and align covariances between tasks. This evidence shows that CA-MTL is able to mitigate task interference and promote more efficient parameter sharing. We showed that MT-Uncertainty is able to avoid degrading performances of low resource tasks. Tasks are sampled whenever the model sees entropy increase, helping avoid catastrophic forgetting. We think that improving the efficiency of our proposed MT-Uncertainty algorithm is a good objective for future work.

Table 6: CA-MTL test performance vs. SOTA.

**(a) WNUT2017**

| | F1 |
|---|---|
| RoBERTa$_{LARGE}$ | 56.9 |
| XLM-R$_{LARGE}$ | 57.1 |
| CA-MTL$_{RoBERTa}$ (ours) | **58.0** |

**(b) SciTail**

| | % Acc |
|---|---|
| MT-DNN | 94.1 |
| ALUM$_{RoBERTa}$ | 96.3 |
| ALUM$_{RoBERTa-SMART}$ | **96.8** |
| CA-MTL$_{RoBERTa}$ (ours) | **96.8** |

**(c) SNLI**

| | % Acc |
|---|---|
| MT-DNN | 91.6 |
| MT-DNN$_{SMART}$ | 91.7 |
| SemBERT | 91.9 |
| CA-MTL$_{RoBERTa}$ (ours) | **92.1** |

---

[4]https://leaderboard.allenai.org/scitail/submissions/public on 09/27/2020
[5]https://nlp.stanford.edu/projects/snli/ on 09/27/2020

# REFERENCES

Roee Aharoni, Melvin Johnson, and Orhan Firat. Massively multilingual neural machine translation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 3874–3884, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1388. URL https://www.aclweb.org/anthology/N19-1388.

Lei Jimmy Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization. *CoRR*, abs/1607.06450, 2016. URL http://arxiv.org/abs/1607.06450.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th annual international conference on machine learning*, pp. 41–48, 2009.

Joachim Bingel and Anders Søgaard. Identifying beneficial task relations for multi-task learning in deep neural networks. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pp. 164–169, Valencia, Spain, April 2017. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/E17-2026.

Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. A large annotated corpus for learning natural language inference. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. Association for Computational Linguistics, 2015.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv*, pp. arXiv–2005, 2020.

Rich Caruana. Multitask learning. *Mach. Learn.*, 28(1):41–75, July 1997. ISSN 0885-6125. doi: 10.1023/A:1007379606734. URL https://doi.org/10.1023/A:1007379606734.

Richard Caruana. Multitask learning: A knowledge-based source of inductive bias. In *Proceedings of the Tenth International Conference on Machine Learning*, pp. 41–48. Morgan Kaufmann, 1993.

Daniel Cer, Mona Diab, Eneko Agirre, Iñigo Lopez-Gazpio, and Lucia Specia. SemEval-2017 task 1: Semantic textual similarity multilingual and crosslingual focused evaluation. In *Proceedings of the 11th International Workshop on Semantic Evaluation (SemEval-2017)*, pp. 1–14, Vancouver, Canada, August 2017. Association for Computational Linguistics. doi: 10.18653/v1/S17-2001. URL https://www.aclweb.org/anthology/S17-2001.

Denis Charles, Max Chickering, and Patrice Simard. Counterfactual reasoning and learning systems: The example of computational advertising. *Journal of Machine Learning Research*, 14:3207–3260, November 2013.

Jinying Chen, Andrew Schein, Lyle Ungar, and Martha Palmer. An empirical study of the behavior of active learning for word sense disambiguation. In *Proceedings of the Human Language Technology Conference of the NAACL, Main Conference*, pp. 120–127, New York City, USA, June 2006. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/N06-1016.

Zhao Chen, Vijay Badrinarayanan, Chen-Yu Lee, and Andrew Rabinovich. Gradnorm: Gradient normalization for adaptive loss balancing in deep multitask networks. *CoRR*, abs/1711.02257, 2017. URL http://arxiv.org/abs/1711.02257.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 2924–2936, Minneapolis, Minnesota, June 2019a. Association for Computational Linguistics. doi: 10.18653/v1/N19-1300. URL https://www.aclweb.org/anthology/N19-1300.

Kevin Clark, Urvashi Khandelwal, Omer Levy, and Christopher D. Manning. What does BERT look at? an analysis of bert's attention. *CoRR*, abs/1906.04341, 2019b. URL http://arxiv.org/abs/1906.04341.

Kevin Clark, Minh-Thang Luong, Urvashi Khandelwal, Christopher D. Manning, and Quoc V. Le. Bam! born-again multi-task networks for natural language understanding. *CoRR*, abs/1907.04829, 2019c. URL http://arxiv.org/abs/1907.04829.

Edward Collins, Nikolai Rozanov, and Bingbing Zhang. Evolutionary data measures: Understanding the difficulty of text classification tasks. In *Proceedings of the 22nd Conference on Computational Natural Language Learning*, pp. 380–391, Brussels, Belgium, October 2018. Association for Computational Linguistics. doi: 10.18653/v1/K18-1037. URL https://www.aclweb.org/anthology/K18-1037.

Ronan Collobert and Jason Weston. A unified architecture for natural language processing: deep neural networks with multitask learning. In *ICML*, pp. 160–167, 2008. URL https://doi.org/10.1145/1390156.1390177.

Marie-Catherine de Marneffe, M. Simons, and J. Tonhauser. The commitmentbank: Investigating projection in naturally occurring discourse. 2019.

Harm de Vries, Florian Strub, Jeremie Mary, Hugo Larochelle, Olivier Pietquin, and Aaron C Courville. Modulating early visual processing by language. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 6594–6604. Curran Associates, Inc., 2017. URL http://papers.nips.cc/paper/7237-modulating-early-visual-processing-by-language.pdf.

Leon Derczynski, Eric Nichols, Marieke van Erp, and Nut Limsopatham. Results of the WNUT2017 shared task on novel and emerging entity recognition. In *Proceedings of the 3rd Workshop on Noisy User-generated Text*, pp. 140–147, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4418. URL https://www.aclweb.org/anthology/W17-4418.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805, 2018. URL http://arxiv.org/abs/1810.04805.

William B. Dolan and Chris Brockett. Automatically constructing a corpus of sentential paraphrases. In *Proceedings of the Third International Workshop on Paraphrasing (IWP2005)*, 2005. URL https://www.aclweb.org/anthology/I05-5002.

Matthew Dunn, Levent Sagun, Mike Higgins, V. Ugur Güney, Volkan Cirik, and Kyunghyun Cho. Searchqa: A new q&a dataset augmented with context from a search engine. *CoRR*, abs/1704.05179, 2017. URL http://arxiv.org/abs/1704.05179.

Adam Fisch, Alon Talmor, Robin Jia, Minjoon Seo, Eunsol Choi, and Danqi Chen. Mrqa 2019 shared task: Evaluating generalization in reading comprehension, 2019.

John Glover and Chris Hokamp. Task selection policies for multitask learning. *CoRR*, 2019. URL http://arxiv.org/abs/1907.06214.

Andrew Gordon, Zornitsa Kozareva, and Melissa Roemmele. SemEval-2012 task 7: Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In *\*SEM 2012: The First Joint Conference on Lexical and Computational Semantics – Volume 1: Proceedings of the main conference and the shared task, and Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation (SemEval 2012)*, pp. 394–398, Montréal, Canada, 7-8 June 2012. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/S12-1052.

Michelle Guo, Albert Haque, De-An Huang, Serena Yeung, and Li Fei-Fei. Dynamic task prioritization for multitask learning. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

Pengcheng He, Xiaodong Liu, Weizhu Chen, and Jianfeng Gao. A hybrid neural network model for commonsense reasoning. In *Proceedings of the First Workshop on Commonsense Inference in Natural Language Processing*, pp. 13–21, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-6002. URL https://www.aclweb.org/anthology/D19-6002.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for NLP. *CoRR*, abs/1902.00751, 2019. URL http://arxiv.org/abs/1902.00751.

Jeremy Howard and Sebastian Ruder. Universal language model fine-tuning for text classification. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 328–339, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1031. URL https://www.aclweb.org/anthology/P18-1031.

Fariz Ikhwantri, Samuel Louvan, Kemal Kurniawan, Bagas Abisena, Valdi Rachman, Alfan Farizki Wicaksono, and Rahmad Mahendra. Multi-task active learning for neural semantic role labeling on low resource conversational corpus. In *Proceedings of the Workshop on Deep Learning Approaches for Low-Resource NLP*, pp. 43–50, 2018.

Haoming Jiang, Pengcheng He, Weizhu Chen, Xiaodong Liu, Jianfeng Gao, and Tuo Zhao. SMART: Robust and efficient fine-tuning for pre-trained natural language models through principled regularized optimization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 2177–2190, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.197. URL https://www.aclweb.org/anthology/2020.acl-main.197.

Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1601–1611, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1147. URL https://www.aclweb.org/anthology/P17-1147.

Mandar Joshi, Danqi Chen, Yinhan Liu, Daniel S. Weld, Luke Zettlemoyer, and Omer Levy. Spanbert: Improving pre-training by representing and predicting spans. *CoRR*, abs/1907.10529, 2019. URL http://arxiv.org/abs/1907.10529.

Alex Kendall, Yarin Gal, and Roberto Cipolla. Multi-task learning using uncertainty to weigh losses for scene geometry and semantics. *CoRR*, abs/1705.07115, 2017. URL http://arxiv.org/abs/1705.07115.

Emma Kerinec, Chloé Braud, and Anders Søgaard. When does deep multi-task learning work for loosely related document classification tasks? In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 1–8, Brussels, Belgium, November 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-5401. URL https://www.aclweb.org/anthology/W18-5401.

Daniel Khashabi, Snigdha Chaturvedi, Michael Roth, Shyam Upadhyay, and Dan Roth. Looking beyond the surface: A challenge set for reading comprehension over multiple sentences. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 252–262, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1023. URL https://www.aclweb.org/anthology/N18-1023.

Tushar Khot, A. Sabharwal, and Peter Clark. Scitail: A textual entailment dataset from science question answering. In *AAAI*, 2018.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2015.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Matthew Kelcey, Jacob Devlin, Kenton Lee, Kristina N. Toutanova, Llion Jones, Ming-Wei Chang, Andrew Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: a benchmark for question answering research. *Transactions of the Association of Computational Linguistics*, 2019.

Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. Gshard: Scaling giant models with conditional computation and automatic sharding. *arXiv preprint arXiv:2006.16668*, 2020.

Hector J. Levesque. The winograd schema challenge. In *AAAI Spring Symposium: Logical Formalizations of Commonsense Reasoning*. AAAI, 2011. URL http://dblp.uni-trier.de/db/conf/aaaiss/aaaiss2011-6.html#Levesque11.

Nelson F. Liu, Matt Gardner, Yonatan Belinkov, Matthew E. Peters, and Noah A. Smith. Linguistic knowledge and transferability of contextual representations. *CoRR*, abs/1903.08855, 2019a. URL http://arxiv.org/abs/1903.08855.

Xiaodong Liu, Pengcheng He, Weizhu Chen, and Jianfeng Gao. Multi-task deep neural networks for natural language understanding. *CoRR*, abs/1901.11504, 2019b. URL http://arxiv.org/abs/1901.11504.

Xiaodong Liu, Hao Cheng, Pengcheng He, Weizhu Chen, Yu Wang, Hoifung Poon, and Jianfeng Gao. Adversarial training for large neural language models, 2020.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692, 2019c. URL http://arxiv.org/abs/1907.11692.

Bryan McCann, Nitish Shirish Keskar, Caiming Xiong, and Richard Socher. The natural language decathlon: Multitask learning as question answering. *arXiv preprint arXiv:1806.08730*, 2018.

Amil Merchant, Elahe Rahimtoroghi, Ellie Pavlick, and Ian Tenney. What happens to bert embeddings during fine-tuning? *arXiv preprint arXiv:2004.14448*, 2020.

Dat Quoc Nguyen, Thanh Vu, and Anh Tuan Nguyen. Bertweet: A pre-trained language model for english tweets. *arXiv preprint arXiv:2005.10200*, 2020.

Hao Peng, Roy Schwartz, Dianqi Li, and Noah A. Smith. A mixture of h - 1 heads is better than h heads. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 6566–6577, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.587. URL https://www.aclweb.org/anthology/2020.acl-main.587.

Ethan Perez, Florian Strub, Harm de Vries, Vincent Dumoulin, and Aaron C. Courville. Film: Visual reasoning with a general conditioning layer. In *AAAI*, 2018.

Matthew E. Peters, Mark Neumann, Luke Zettlemoyer, and Wen-tau Yih. Dissecting contextual word embeddings: Architecture and representation. *CoRR*, abs/1808.08949, 2018. URL http://arxiv.org/abs/1808.08949.

Jonas Pfeiffer, Aishwarya Kamath, Andreas Rücklé, Kyunghyun Cho, and Iryna Gurevych. Adapter-fusion: Non-destructive task composition for transfer learning, 2020.

Jason Phang, Thibault Févry, and Samuel R. Bowman. Sentence encoders on stilts: Supplementary training on intermediate labeled-data tasks. *CoRR*, abs/1811.01088, 2018. URL http://arxiv.org/abs/1811.01088.

Adam Poliak, Aparajita Haldar, Rachel Rudinger, J. Edward Hu, Ellie Pavlick, Aaron Steven White, and Benjamin Van Durme. Collecting diverse natural language inference problems for sentence representation evaluation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 67–81, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1007. URL https://www.aclweb.org/anthology/D18-1007.

Yada Pruksachatkun, Jason Phang, Haokun Liu, Phu Mon Htut, Xiaoyi Zhang, Richard Yuanzhe Pang, Clara Vania, Katharina Kann, and Samuel R Bowman. Intermediate-task transfer learning with pretrained models for natural language understanding: When and why does it work? *arXiv preprint arXiv:2005.00628*, 2020.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training. 2018.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer, 2019a.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer, 2019b.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 2383–2392, Austin, Texas, November 2016a. Association for Computational Linguistics. doi: 10.18653/v1/D16-1264. URL https://www.aclweb.org/anthology/D16-1264.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 2383–2392, Austin, Texas, November 2016b. Association for Computational Linguistics. doi: 10.18653/v1/D16-1264.

Roi Reichart, Katrin Tomanek, Udo Hahn, and Ari Rappoport. Multi-task active learning for linguistic annotations. In *Proceedings of ACL-08: HLT*, pp. 861–869, 2008.

Sebastian Ruder. An overview of multi-task learning in deep neural networks. *ArXiv*, abs/1706.05098, 2017.

Ozan Sener and Vladlen Koltun. Multi-task learning as multi-objective optimization. *CoRR*, abs/1810.04650, 2018. URL http://arxiv.org/abs/1810.04650.

Joan Serrà, Didac Suris, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *ICML*, pp. 4555–4564, 2018. URL http://proceedings.mlr.press/v80/serra18a.html.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pp. 1631–1642, Seattle, Washington, USA, October 2013. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/D13-1170.

Trevor Standley, Amir Roshan Zamir, Dawn Chen, Leonidas J. Guibas, Jitendra Malik, and Silvio Savarese. Which tasks should be learned together in multi-task learning? *CoRR*, abs/1905.07553, 2019. URL http://arxiv.org/abs/1905.07553.

Asa Cooper Stickland, Iain Murray, someone, and someone. BERT and PALs: Projected attention layers for efficient adaptation in multi-task learning. volume 97 of *Proceedings of Machine Learning Research*, pp. 5986–5995, Long Beach, California, USA, 09–15 Jun 2019. PMLR. URL http://proceedings.mlr.press/v97/stickland19a.html.

Yi Tay, Zhe Zhao, Dara Bahri, Donald Metzler, and Da-Cheng Juan. Hypergrid: Efficient multi-task transformers with grid-wise decomposable hyper projections. *arXiv preprint arXiv:2007.05891*, 2020.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. BERT rediscovers the classical NLP pipeline. *CoRR*, abs/1905.05950, 2019a. URL http://arxiv.org/abs/1905.05950.

Ian Tenney, Patrick Xia, Berlin Chen, Alex Wang, Adam Poliak, R. Thomas McCoy, Najoung Kim, Benjamin Van Durme, Samuel R. Bowman, Dipanjan Das, and Ellie Pavlick. What do you learn from context? probing for sentence structure in contextualized word representations. *CoRR*, abs/1905.06316, 2019b. URL `http://arxiv.org/abs/1905.06316`.

Adam Trischler, Tong Wang, Xingdi Yuan, Justin Harris, Alessandro Sordoni, Philip Bachman, and Kaheer Suleman. NewsQA: A machine comprehension dataset. In *Proceedings of the 2nd Workshop on Representation Learning for NLP*, pp. 191–200, Vancouver, Canada, August 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-2623. URL `https://www.aclweb.org/anthology/W17-2623`.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *CoRR*, abs/1706.03762, 2017. URL `http://arxiv.org/abs/1706.03762`.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 353–355, Brussels, Belgium, November 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-5446. URL `https://www.aclweb.org/anthology/W18-5446`.

Alex Wang, Jan Hula, Patrick Xia, Raghavendra Pappagari, R. Thomas McCoy, Roma Patel, Najoung Kim, Ian Tenney, Yinghui Huang, Katherin Yu, Shuning Jin, Berlin Chen, Benjamin Van Durme, Edouard Grave, Ellie Pavlick, and Samuel R. Bowman. Can you tell me how to get past sesame street? sentence-level pretraining beyond language modeling. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (ACL)*, 2019a.

Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. Superglue: A stickier benchmark for general-purpose language understanding systems. *CoRR*, abs/1905.00537, 2019b. URL `http://arxiv.org/abs/1905.00537`.

Alex Warstadt, Amanpreet Singh, and Samuel R. Bowman. Neural network acceptability judgments. *CoRR*, abs/1805.12471, 2018. URL `http://arxiv.org/abs/1805.12471`.

Adina Williams, Nikita Nangia, and Samuel Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1112–1122, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1101. URL `https://www.aclweb.org/anthology/N18-1101`.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface's transformers: State-of-the-art natural language processing. *CoRR*, abs/1910.03771, 2019. URL `http://arxiv.org/abs/1910.03771`.

Sen Wu, Hongyang R. Zhang, and Christopher Ré. Understanding and improving information transfer in multi-task learning. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=SylzhkBtDB`.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2369–2380, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1259. URL `https://www.aclweb.org/anthology/D18-1259`.

Tianhe Yu, Saurabh Kumar, Abhishek Gupta, Sergey Levine, Karol Hausman, and Chelsea Finn. Gradient surgery for multi-task learning. *arXiv preprint arXiv:2001.06782*, 2020.

667 Sheng Zhang, Xiaodong Liu, Jingjing Liu, Jianfeng Gao, Kevin Duh, and Benjamin Van Durme.
668    Record: Bridging the gap between human and machine commonsense reading comprehension.
669    *CoRR*, abs/1810.12885, 2018. URL `http://arxiv.org/abs/1810.12885`.

670 Yu Zhang and Qiang Yang. A survey on multi-task learning. *CoRR*, abs/1707.08114, 2017. URL
671    `http://arxiv.org/abs/1707.08114`.

# A   APPENDIX

## A.1   SUMMARY OF ACRONYMS

Acronyms of datasets and descriptions can be found below in section A.3.

Table 7: List of acronyms used in this paper.

| Acronym | Description |
|---------|-------------|
| ARLM | Autoregressive Language Models |
| CA-MTL | Conditional Adaptive Multi-Task Learning: our architecture |
| CFF | Conditional Feed-Forward: a feed-forward layer modulated by a conditioning vector |
| CLN | Conditional Layer Normalization in section 2.3 |
| EDM | Evolutionary Data Measures (Collins et al., 2018): a task difficulty estimate |
| GLUE | General Language Understanding Evaluation Wang et al. (2018): a benchmark with multiple datasets |
| QA | Question Answering |
| MT | Multi-Task |
| MTAL | Multi-Task Active Learning: finding the most informative instance for multiple learners (or models) |
| MLM | Masked Language Model: BERT Devlin et al. (2018) is an example of an MLM |
| MTL | Multi-Task Learning: "learning tasks in parallel while using a shared representation" (Caruana, 1997) |
| MRQA | Machine Reading for Question Answering Fisch et al. (2019): a benchmark with multiple datasets |
| NER | Named Entity Recognition |
| NLP | Natural Language Processing |
| SOTA | State of the art |
| ST | Single Task fine-tuning: all weights are typically updated |
| ST-A | ST with Adapter modules: one adapter per task is trained and pretrained weights are optionally updated |

## A.2   UNCERTAINTY SAMPLING: ALGORITHM AND ADDITIONAL RESULTS

---

**Algorithm 1:** Multi-task Uncertainty Sampling

---

**Input:** Training data $D_t$ for task $t \in [1, \ldots, T]$; batch size $b$; $C_t$ possible output classes for task $t$; $f := f_{\phi(\mathbf{z}_i), \theta_i}$ our model with weights $\phi, \theta_i$;

**Output:** $\mathcal{B}'$ - multi-task batch of size $b$

1   $\mathcal{B} \leftarrow \emptyset$

2   **for** $t \leftarrow 1$ **to** $T$ **do**

3      Generate $\mathbf{x}_t := \{x_{t,1}, \ldots, x_{t,b}\} \overset{\text{i.i.d.}}{\sim} D_t$

4      **for** $i \leftarrow 1$ **to** $b$ **do**

5         $\mathcal{H}_{t,i} \leftarrow -\sum_{c=1}^{C_i} p_c(f(x_{t,i})) \log p_c(f(x_{t,i}))$      ▷ Entropy of each sample

6

7      **end**

8      Compute $\bar{\mathcal{H}}_t \leftarrow \frac{1}{b} \sum_{\mathbf{x} \in \mathbf{x}_i} \mathcal{H}_{t,i}$      ▷ Average entropy for task $t$

9

10      Compute $H'_t \leftarrow -\sum_{c=1}^{C_t} \frac{1}{C_t} \log \left[ \frac{1}{C_t} \right]$      ▷ Max entropy (uniform distribution)

11

12      $\mathcal{B} \leftarrow \mathcal{B} \cup \mathbf{x}_t$ and $D_t \leftarrow D_t \setminus \mathbf{x}_t$

13      **if** $D_t = \emptyset$ **then**

14         Reload $D_t$

15      **end**

16      **for** $i \leftarrow 1$ **to** $b$ **do**

17         Compute: $\mathcal{U}_{t,i} \leftarrow \mathcal{H}_{t,i}/H'_t$      ▷ Uncertainty normalized with max entropy

18      **end**

19  **end**

20  Compute $\hat{\mathcal{H}} \leftarrow \max_{i \in \{1, \ldots, T\}} [\bar{\mathcal{H}}_t]$      ▷ Entropy of task with highest average entropy

21  Update $\mathcal{U}_{t,i} \leftarrow \mathcal{U}_{t,i}/\hat{\mathcal{H}}$      ▷ Normalize each sample's uncertainty measure

22  $\mathcal{B}' \leftarrow \text{top\_b}(\{\mathcal{U}_{t,i} | t \in [1, \ldots, T], i \in [1, \ldots, b]\})$      ▷ $b$ samples w/ highest uncertainty

 **Return:** With $\mathcal{B}'$, solve eq. 1 with gradient descent; updated model $f$

---

An advantage of our MT-Uncertainty Sampling approach is its ability to manage task difficulty. This is highlighted in Figure 8. In this experiment, we estimated task difficulty using the Evolutionary

Data Measures (EDM)[6] proposed by Collins et al. (2018). The task difficulty estimate relies on multiple dataset statistics such as the data size, class diversity, class balance and class interference. Interestingly, estimated task difficulty correlates with the first instance that the selection of a specific task occurs. Supposing that QNLI is an outlier, we notice that peaks in the data occur whenever tasks are first selected by MT Uncertainty sampling. This process follows the following order: 1. MNLI 2. CoLA 3. RTE 4. QQP 5. MRPC 6.SST-2, which is the order from highest task difficulty to lowest task difficulty using EDM. As opposed to Curriculum Learning (Bengio et al., 2009), MT-Uncertainty dynamically prioritizes the most difficult tasks. As also discovered in MTL vision work (Guo et al., 2018), this type of prioritization on more difficult tasks may explain MT-Uncertainty's improved performance over other task selection methods. In MTL, heuristics to balance tasks during training is typically done by weighting each task's loss differently. We see here how MT-Uncertainty is able to prioritize task difficulty.

While the EDM difficulty measure is shown to correlate well with model performance, it lacks precision. As reported in Collins et al. (2018), the average score achieved on the Yahoo Answers dataset is 69.9% and its difficulty is 4.51. The average score achieved on Yelp Full is 56.8%, 13.1% less than Yahoo Answers and its difficulty is 4.42. The authors mention that "This indicates that the difficulty measure in its current incarnation may be more effective at assigning a class of difficulty to datasets, rather than a regression-like value".

Figure 8: Task composition of MT-Uncertainty sampling and estimated task difficulty using EDM: number of training samples per task at each iteration for batch size of 32. The occurrence of first peaks and estimated difficulty follow the same order: From highest to lowest: MNLI > CoLA > RTE > QQP = MRPC > SST-2.

## A.3 DATASET DESCRIPTION

The datasets that were used for the domain adaptation experiments were SciTail[7] and SNLI[8]. We *jointly* trained a CA-MTL$_{RoBERTa-LARGE}$ model on 9 GLUE tasks, 8 Super-GLUE[9] tasks, 6 MRQA[10] tasks, and on WNUT2017[11] (Derczynski et al., 2017).

All GLUE tasks are binary classification, except STS-B (regression) and MNLI (three classes). We used the same GLUE data preprocessing as in Devlin et al. (2018).

---

[6]https://github.com/Wluper/edm

[7]https://allenai.org/data/scitail; Leaderboard can be found at: https://leaderboard.allenai.org/scitail/submissions/public

[8]https://nlp.stanford.edu/projects/snli/

[9]https://super.gluebenchmark.com/tasks

[10]https://github.com/mrqa/MRQA-Shared-Task-2019

[11]https://github.com/leondz/emerging_entities_17

Table 8: GLUE (Wang et al., 2018) dataset description.
References: [1]Warstadt et al. (2018), [2]Socher et al. (2013), [3]Dolan & Brockett (2005), [4]Cer et al. (2017), [5]Williams et al. (2018), [6]Wang et al. (2018), [7]Levesque (2011)

| Acronym | Corpus | \|Train\| | Task | Domain |
|---|---|---|---|---|
| CoLA[1] | Corpus of Linguistic Acceptability | 8.5K | acceptability | miscellaneous |
| SST-2[2] | Stanford Sentiment Treebank | 67K | sentiment detection | movie reviews |
| MRPC[3] | Microsoft Research Paraphrase Corpus | 3.7K | paraphrase detection | news |
| STS-B[4] | Semantic Textual Similarity Benchmark | 7K | textual similarity | miscellaneous |
| QQP | Quora Question Pairs | 364K | paraphrase detection | online QA |
| MNLI[5] | Multi-Genre NLI | 393K | inference | miscellaneous |
| RTE[6] | Recognition Textual Entailment | 2.5K | inference/entailment | news, Wikipedia |
| WNLI[7] | Winograd NLI | 634 | coreference | fiction books |

Table 9: Super-GLUE (Wang et al., 2019b) dataset description. References: [1]Clark et al. (2019a), [2]de Marneffe et al. (2019), [3]Gordon et al. (2012), [4]Khashabi et al. (2018), [5]Zhang et al. (2018), [6]Wang et al. (2019b), [7]Poliak et al. (2018), [8]Levesque (2011)

| Acronym | Corpus | \|Train\| | Task | Domain |
|---|---|---|---|---|
| BoolQ[1] | Boolean Questions | 9.4K | acceptability | Google queries, Wikipedia |
| CB[2] | CommitmentBank | 250 | sentiment detection | miscellaneous |
| COPA[3] | Choice of Plausible Alternatives | 400 | paraphrase detection | blogs, encyclopedia |
| MultiRC[4] | Multi-Sentence Reading Comprehension | 5.1K | textual similarity | miscellaneous |
| ReCoRD[5] | Reading Comprehension and Commonsense Reasoning | 101K | paraphrase detection | news |
| RTE[6] | Recognition Textual Entailment | 2.5K | inference | news, Wikipedia |
| WiC[7] | Word-in-Context | 6K | word sense disambiguation | WordNet, VerbNet |
| WSC[8] | Winograd Schema Challenge | 554 | coreference resolution | fiction books |

Table 10: MRQA (Fisch et al., 2019) dataset description. References: [1]Rajpurkar et al. (2016a), [2]Trischler et al. (2017), [3]Joshi et al. (2017), [4]Dunn et al. (2017), [5]Yang et al. (2018), [6]Kwiatkowski et al. (2019)

| Acronym | Corpus | \|Train\| | Task | Domain |
|---|---|---|---|---|
| SQuAD[1] | Stanford QA Dataset | 86.6K | crowdsourced questions | Wikipedia |
| NewsQA[2] | NewsQA | 74.2K | crowdsourced questions | news |
| TriviaQA[3] | TriviaQA | 61.7K | trivia QA | web snippets |
| SearchQA[4] | SearchQA | 117.4K | Jeopardy QA | web snippets |
| HotpotQA[5] | HotpotQA | 72.9K | crowdsourced questions | Wikipedia |
| Natural Questions[6] | Natural Questions | 104.7K | search logs | Wikipedia |

SuperGLUE has a more diverse task format than GLUE, which is mostly limited to sentence and sentence-pair classification. We follow the same preprocessing procedure as in Wang et al. (2019b). All tasks are binary classification tasks, except CB (three classes). Also, WiC and WSC are span based classification tasks. We used the same modified MRQA dataset and preprocessing steps that were used in Joshi et al. (2019). All MRQA tasks are span prediction tasks which seeks to identify start and end tokens of an answer span in the input text.

Table 11: SNLI (Bowman et al., 2015) and SciTail (Khot et al., 2018) datasets description.

| Acronym | Corpus | \|Train\| | Task | Domain |
|---|---|---|---|---|
| SNLI[1] | Stanford Natural Language Inference | 550.2k | inference | human-written English sentence pairs |
| SciTail[2] | Science and Entailment | 23.5K | entailment | Science question answering |

SNLI is a natural inference task where we predict three classes. Examples of three target labels are: Entailment, Contradiction, and Neutral (irrelevant). SciTail is a textual entailment dataset. The hypotheses in SciTail are created from multiple-choice science exams and the answer candidates (premise) are extracted from the web using information retrieval tools. SciTail is a binary true/false classification tasks that seeks to predict whether the premise entails the hypothesis. The two datasets are used only for domain adaptation in this study (see section A.4 for the details of our approach).

## A.4 ZERO-SHOT RESULTS ON SCITAIL AND SNLI

Table 12: CA-MTL is flexible and extensible to new tasks. However, CA-MTL is sensitive to the new task's embedding. We tested multiple task embeddings that worked best on either SciTail or SNLI by checking performance in a zero shot setting or using 0% of the data.

| Initialization of new task embedding layer | SciTail 0% of data | SNLI 0% of data |
|---|---|---|
| CoLA init | 43.0 | 34.0 |
| MNLI init | 24.2 | 33.0 |
| MRPC init | 34.5 | **45.5** |
| STS-B init | **46.9** | 33.2 |
| SST-2 init | 25.8 | 34.2 |
| QQP init | 31.7 | 37.3 |
| QNLI init | 32.0 | 38.0 |
| RTE init | 32.3 | 40.6 |
| WNLI init | 29.0 | 30.4 |
| Average init | 28.7 | 37.7 |
| Random init | 46.8 | 34.0 |
| Xavier init | 29.8 | 37.6 |

Before testing models on domain adaptation in section 4.4, we ran zero-shot evaluations on the development set of SciTail and SNLI. Table 12 outlines 8-task CA-MTL$_{\text{BERT-BASE}}$'s zero-shot transfer abilities when pretrained on GLUE with our MTL approach. We expand the task embedding layer to accommodate an extra task and explore various embedding initialization. We found that reusing STS-B and MRPC task embeddings worked best for SciTail and SNLI respectively.

## A.5 MORE EXPERIMENTAL DETAILS

We used a batch size of 32 and a seed of 12 in all experiments. We used Adam (Kingma & Ba, 2015) as the optimizer with a learning rate of 2e-5. We applied a learning rate decay with warm up over the first 10% of the training steps. Unless otherwise specified, we used 5 epochs, a seed of 12 and a sequence length of 128. Additional details are outlined in section . Our data prepossessing and linear decoder heads are the same as in Devlin et al. (2018). We used the same dropout rate of 0.1 in all layers. To run our experiments, we used either four NVIDIA P100 GPU for base models or four NVIDIA V100 GPU for larger ones. We did not perform parameter search. We do not use ensemble of models or task-specific tricks (Devlin et al., 2018; Liu et al., 2019b; Clark et al., 2019c). All models are either 12 Transformer layers for BASE and 24 Transformer layers for LARGE. Apart from CA-MTL, models trained in multi-task learning (BERT or RoBERTa without adapters) used random task sampling. For Table 1 and Figure 7, all BERT-based model have half their layers frozen (untrained) for a fair comparison of ablation results. For the 24-task MTL and CA-MTL models in Tables 4 and 5, we increased the input sequence length to 256 and used 8 epochs.

## A.6 BASELINES AND OTHER EXPERIMENTAL RESULTS

In this section, we present our baseline results for BERT, RoBERTa, CA-MTL as well as other models. Our single task results (ST) that we ran ourselves surpass other paper's reported scores in table 13. Liu et al. (2019c) reports random seed median scores for RoBERTa. However, our RoBERTa ST baseline **matches or surpasses** the original paper's scores **4 out 7 times** on the development set when scores are comparable (QQP F1 and STS-B spearman are not reported).

## A.7 SOME RESULTS ON LAYER FREEZING AND WITH FULL BLOCK ATTENTION.

All experiments in this section were run for only 5 epochs, exclusively on the GLUE dataset for the large BERT-based 8-task CA-MTL model. Results in Figure 15 reveal that...

Table 13: F1 scores are reported for QQP/MRPC, Spearman's correlation for STS-B, accuracy on the matched/mismatch sets for MNLI, Matthew's correlation for CoLA and accuracy for other tasks. ST=Single Task, MTL=Multitask. *QNLI v1 (we report v2) **F1 score or Spearman's correlation is not reported. ***Unknown random seeds. Results from: [1]Stickland et al. (2019) [2]Liu et al. (2019b) [3]Phang et al. (2018) [4]Liu et al. (2019c).

| Method | Total params | Trained params/task | GLUE | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | CoLA | MNLI | MRPC | QNLI | QQP | RTE | SST-2 | STS-B | Avg |
| **Base Models — Dev set Results** | | | | | | | | | | | |
| PALs+Anneal Samp.[1] | 1.13× | 12.5% | – | – | – | – | – | – | – | – | 81.70 |
| 8-task CA-MTL$_{BERT-BASE}$ (ours) | 1.12× | 5.6% | 60.9 | 82.7/83.1 | 88.9 | 90.7 | 90.3 | 79.1 | 91.9 | 88.8 | 84.03 |
| **BERT LARGE Models — Dev set Results** | | | | | | | | | | | |
| ST BERT-LARGE[2] | 9× | 100% | 60.5 | 86.7/85.9 | 89.3 | 92.7* | 89.3 | 70.1 | 94.9 | 86.5 | 84.0 |
| ST BERT-LARGE[3] | 9× | 100% | 62.1 | 86.2/86.2 | 92.3 | 89.4 | 88.5 | 70.0 | 92.5 | 90.1 | 84.1 |
| ST BERT-LARGE (ours) | 9× | 100% | 63.6 | 86.5/86.0 | 91.4 | 91.0 | 88.5 | 70.2 | 94.7 | 88.2 | 84.5 |
| 24-task CA-MTL$_{BERT-LARGE}$ (ours) | 1.12× | 5.6% | 63.8 | 86.3/86.0 | 92.9 | 93.4 | 88.1 | 84.5 | 94.5 | 90.3 | 86.6 |
| **RoBERTa LARGE Models — Dev set Results** | | | | | | | | | | | |
| RoBERTa-LARGE[4] (Median 5 runs)*** | 9× | 100% | 68.0 | 90.2 | 90.9 | 94.7 | ** | 86.6 | 96.4 | ** | – |
| ST RoBERTa-LARGE (ours) | 9× | 100% | 68.3 | 89.2/88.9 | 92.6 | 94.8 | 84.6 | 87.0 | 96.4 | 91.7 | 88.2 |
| 24-task CA-MTL$_{RoBERTa-LARGE}$ (ours) | 1.12× | 5.6% | 69.7 | 89.4/89.3 | 93.9 | 94.9 | 88.8 | 91.0 | 96.2 | 91.0 | 89.4 |

Table 14: Performance of **24-task CA-MTL$_{RoBERTa-LARGE}$** (see section 4.5) on Super-GLUE dev and MRQA test sets. ST = single task fine-tuning, A = trained with adapter modules. Results from: [1]Pfeiffer et al. (2020) [2]baseline in Raffel et al. (2019a) [3]Joshi et al. (2019)

(a)

| Super-GLUE Task Dev set | Fusion ST-A[1] | T5 ST[2] | T5 ST-A$_{2048}$[2] | **CA-MTL** |
|---|---|---|---|---|
| Params if ST | — | 220M | 115M | 370M |
| BoolQ | 76.2 | 76.6 | 74.5 | **86.0** |
| CB | 92.1 | 91.2 | 88.0 | **95.1** |
| COPA | — | 66.2 | 58.0 | **89.0** |
| MultiRC | — | 66.1 | 61.1 | **67.4** |
| ReCoRD | — | **69.0** | 66.7 | 68.7 |
| RTE | — | 76.3 | 76.6 | **91.0** |
| WSC | — | **78.6** | 76.0 | 70.2 |
| WiC | — | 68.0 | 71.1 | **72.3** |
| **Super-GLUE$_{avg}$** | — | 74.0 | 71.5 | **80.0** |

(b)

| MRQA Task Test set | T5 ST[2] | Span-BERT[3] | **CA-MTL** |
|---|---|---|---|
| Params if ST | 220M | 340M | 370M |
| HotpotQA | — | **83.0** | 81.1 |
| Natural Questions | — | 82.5 | **82.7** |
| NewsQA | — | 73.6 | **73.7** |
| TriviaQA | — | **83.6** | 81.0 |
| SearchQA | — | **84.8** | 83.2 |
| SQuAD v2 | 88.8 | 88.7 | **88.8** |
| **MRQA$_{avg}$** | — | **82.7** | 81.8 |

Table 15: **8-task CA-MTL$_{BERT-LARGE}$** (see section 4.3) for various layer freezing configurations. F1 scores are reported for QQP/MRPC, Spearman's correlation for STS-B, accuracy on the matched/mismatch sets for MNLI, Matthew's correlation for CoLA and accuracy for other tasks. FBA = Full Block Attention

| Method | % frozen layers | # tasks g.e ST | GLUE | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | CoLA | MNLI | MRPC | QNLI | QQP | RTE | SST-2 | STS-B | Avg |
| **LARGE Models — Dev set Results** | | | | | | | | | | | |
| ST BERT-LARGE (ours) | 0% | — | 63.6 | 86.5/86.0 | 91.4 | 91.0 | 88.5 | 70.2 | 93.1 | 88.2 | 84.3 |
| CA-MTL | 0% | 7 | 60.2 | 86.2/86.0 | 92.0 | 91.5 | 88.7 | 76.3 | 93.3 | 89.5 | 84.9 |
| CA-MTL | 25% | 6 | 63.7 | 86.1/85.8 | 89.1 | 91.2 | 88.6 | 79.7 | 92.9 | 88.5 | 85.1 |
| CA-MTL | 50% | 3 | 63.2 | 85.5/85.5 | 91.8 | 90.9 | 88.3 | 81.4 | 93.0 | 90.1 | 85.5 |
| CA-MTL FBA | 50% | 0 | 60.2 | 81.7/81.1 | 88.0 | 85.8 | 85.7 | 78.7 | 88.6 | 87.1 | 81.8 |