Neural Capacitance: A New Perspective of Neural Network Selection via Edge Dynamics

Abstract

Efficient model selection for identifying a suitable pre-trained neural network to a downstream task is a fundamental yet challenging task in deep learning. Current practice requires expensive computational costs in model training for performance prediction. In this paper, we propose a novel framework for neural network selection by analyzing the governing dynamics over synaptic connections (edges) during training. Our framework is built on the fact that back-propagation during neural network training is equivalent to the dynamical evolution of synaptic connections. Therefore, a converged neural network is associated with an equilibrium state of a networked system composed of those edges. To this end, we construct a network mapping ϕ, converting a neural network G_A to a directed line graph G_B that is defined on those edges in G_A. Next, we derive a *neural capacitance* metric β_{eff} as a predictive measure universally capturing the generalization capability of G_A on the downstream task using only a handful of early training results. We carried out extensive experiments using 17 popular pre-trained ImageNet models and five benchmark datasets, including CIFAR10, CIFAR100, SVHN, Fashion MNIST and Birds, to evaluate the fine-tuning performance of our framework. Our neural capacitance metric is shown to be a powerful indicator for model selection based only on early training results and is more efficient than state-of-the-art methods.

1 Introduction

Leveraging a pre-trained neural network (i.e., a source model) and fine-tuning it to solve a target task is a common and effective practice in deep learning, such as transfer learning. Transfer learning has been widely used to solve complex tasks in text and vision domains. In vision, models trained on ImageNet are leveraged to solve diverse tasks such as image classification and object detection. In text, language models that are trained on a large amount of public data comprising of books, Wikipedia etc are employed to solve tasks such as classification and language generation. Although such technique can achieve good performance on a target task, a fundamental yet challenging problem is how to select a suitable pre-trained model from a pool of candidates in an efficient manner. The naive solution of training each candidate fully with the target data can find the best pre-trained model but is infeasible due to considerable consumption on time and computation resources. This challenge motivates the need for an efficient predictive measure to capture the performance of a pre-trained model on the target task *based only on early training results* (e.g., predicting final model performance based on the statistics obtained from first few training epochs).

In order to implement an efficient neural network model selection, this paper proposes a novel edge dynamics based framework to forecast the predictive ability of a model with its cumulative information in the early phase of neural network (NN) training, as practised in learning curve prediction (Domhan et al., 2015; Chandrashekaran & Lane, 2017; Baker et al., 2017; Wistuba & Pedapati, 2020). Most of prior work on learning curve prediction aims to capture the trajectory of learning curves with a regression function of models' validation accuracy. Some of the previous algorithms developed in this field require training data from *additional* learning curves to train the predictors (Chandrashekaran & Lane, 2017; Baker et al., 2017; Wistuba & Pedapati, 2020). On the other hand, our model does not require any such data. It solely relies on the NN architecture. Ranking models according to their final accuracy after fine-tuning is a lot more challenging as the learning curves are very similar to each other.

The entire NN training process involves iterative updates of the weights of synaptic connections, according to one particular optimization algorithm, e.g., gradient descent or stochastic gradient descent (SGD) (Bottou, 2012; LeCun et al., 2015). In essence, many factors contribute to impact how weights are updated, including the training data, the neural architecture, the loss function, and the optimization algorithm. Moreover, weights evolving during NN training in many aspects can be viewed as a discrete dynamical system. The perspective of viewing NN training as a dynamical system has been studied by the community (Mei et al., 2018; Chang et al., 2018; Banburski et al., 2019; Dogra, 2020; Tano et al., 2020; Dogra & Redman, 2020; Feng & Tu, 2021), and many attempted to make some theoretical explanation of the convergence rate and generalization error bounds. In this paper, we will provide the first attempt in exploring its power in neural model selection.

One limitation of current approaches is that they concentrated on the macroscopic and collective behavior of the system, but lacks a dedicated examination of the individual interactions between the trainable weights or synaptic connections, which are crucial in understanding of the dependency of these weights, and how they co-evolve during training. To fill the gap, we study the system from a microscopic perspective, build edge dynamics of synaptic connections from SGD in terms of differential equations, from which we build an associated network as well. The edge dynamics induced from SGD is nonlinear and highly coupling. It will be very challenging to solve, considering millions of weights in many convolutional neural networks (CNNs), e.g., 16M weights in MobileNet (Howard et al., 2017) and 528M in VGG16 (Simonyan & Zisserman, 2014). Gao et al. (2016) proposed a universal topological metric for the associated network to decouple the system. The metric will be used for model selection in our approach, and it is shown to be powerful in search of the best predictive model. We illustrate our proposed framework in Fig.1.

The main contributions of our framework can be summarized as follows:

- View NN training as a dynamical system over synaptic connections, and first time investigate the interactions of synaptic connections in a microscopic perspective.
- Propose neural capacitance metric β_{eff} for neural network model selection.
- Empirical results of 17 pre-trained models on five benchmark datasets show that our β_{eff} based approach outperforms current learning curve prediction approaches.
- For rank prediction according to the performance of pre-trained models, our approach improves by 9.1/38.3/12.4/65.3/40.1% on CIFAR10/CIFAR100/SVHN/Fashion MNIST/Birds over the best baseline with observations from learning curves of length only 5 epochs.

2 RELATED WORK

Learning Curve Prediction. Chandrashekaran & Lane (2017) treated the current learning curve as an affine transformation of previous learning curves. They built an ensemble of transformations employing previous learning curves and the first few epochs of the current learning curve to predict the final accuracy of the current learning curve. Baker et al. (2017) proposed an SVM based learning curve predictor using features extracted from previous learning curves, including the architecture information such as number of layers, parameters, and training technique such as learning rate and learning rate decay. A separate SVM is used to predict the accuracy of a learning curve at a particular epoch. Domhan et al. (2015) trained an ensemble of parametric functions that observe the first few epochs of a learning curve and extrapolate it. Klein et al. (2017a) devised a Bayesian NN to model the functions that Domhan formulated to capture the structure of the learning curves more effectively. Wistuba & Pedapati (2020) developed a transfer learning based predictor that was trained on learning curves generated from other datasets. It is a NN based predictor that leverages architecture and dataset embeddings to capture the similarities between the architectures of various models and also the other datasets that it was trained on.

Dynamical System View of NNs. There are some valuable attempts to study the dynamics of NN training. Some prior work on SGD dynamics for deep NNs generally have a pre-assumption of the input distribution or how the labels are generated. They obtained global convergence for shallow NNs (Tian, 2017; Banburski et al., 2019). System identification itself is a complicated task (Haykin, 2010; Lillicrap et al., 2020). In studying the generalisation phenomenon of deep NNs, Goldt et al. (2019) formulated SGD with a set of differential equations. But, it is limited to over-parameterised two-layer NNs under the teacher-student framework. The teacher network determines how the labels

Figure 1: Illustration of our framework. **(a)** An example multilayer perceptron (MLP) G_A with three hidden layers is mapped to a directed line graph G_B, which is governed by an edge dynamics $\mathcal{B}$. Each node (dichromatic square) of G_B is associated with a synaptic connection linking two neurons (in different colors) from different layers of G_A. **(b)** A diagram of transfer learning from the source domain (left stack) to a target domain (right stack). The pre-trained model is modified by adding additional layers, i.e. installing a neural capacitance probe (NCP) unit, on top of the bottom layers. The NCP unit is frozen with a set of randomly initialized weights, and only the bottom layers are fine-tuned. **(c)** Observed partial learning curves (green line segments) of validation accuracy over the early-stage training epochs and the corresponding neural capacitance metric β_{eff} during fine-tuning. The predicted final accuracy at $\beta_{\text{eff}} \to 0$ (red dot) is used to select the best one from a set of models.

are generated. Also, some interesting phenomena (Frankle et al., 2020) have been observed during the early phase of NN training, such as trainable sparse sub-networks emerge (Frankle et al., 2019), gradient descent moves into a small subspace (Gur-Ari et al., 2018), and there exists a critical effective connection between layers (Achille et al., 2019). Bhardwaj et al. (2021) built a nice connection between NN architectures (with concatenation-type skip connections) and their performance, and proposed a new topological metric to identify NNs with similar accuracy. Many of these studies are built on dynamical system and network science. It will be a promising direction to study deep learning mechanism.

3 PRELIMINARIES

Dynamical System of a Network. Many real complex systems, e.g., plant-pollinator interactions (Waser & Ollerton, 2006) and the spread of COVID-19 (Thurner et al., 2020), can be described with networks (Mitchell, 2006; Barabási & Pósfai, 2016). Let $G = (V, E)$ be a network with node set V and edge set E. Assuming $n = |V|$, the interactions between nodes can be formulated as a set of differential equations

$$\dot{x}_i = f(x_i) + \sum_{j \in V} P_{ij} g(x_i, x_j), \forall i \in V, \tag{1}$$

where x_i is the state of node i. In real systems, it could be the abundance of a plant in ecological network, the infection rate of a person in epidemic network, or the expression level of a gene in

regulatory network. The term P is the adjacency matrix of G, where the entry P_{ij} indicates the interaction strength between nodes i and j. The functions $f(\cdot)$ and $g(\cdot, \cdot)$ capture the internal and external impacts on node i, respectively. Usually, they are nonlinear.

Let $\boldsymbol{x} = (x_1, x_2, \ldots, x_n)$. For a small network, given an initial state, one can run a forward simulation for an equilibrium state $\boldsymbol{x}^*$, such that $\dot{x}_i^* = f(x_i^*) + \sum_{j \in V} P_{ij} g(x_i^*, x_j^*) = 0$. However, when the size of the system goes up to millions or even billions, it will pose a big challenge to solve the coupled differential equations. The problem can be efficiently addressed by employing a mean-field technique (Gao et al., 2016), where a linear operator $\mathcal{L}_P(\cdot)$ is introduced to decouple the system. In specific, the operator depends on the adjacency matrix P and is defined as

$$\mathcal{L}_P(\boldsymbol{z}) = \frac{\mathbf{1}^T P \boldsymbol{z}}{\mathbf{1}^T P \mathbf{1}}, \tag{2}$$

where $\boldsymbol{z} \in \mathcal{R}^n$. Let $\boldsymbol{\delta}_{\text{in}} = P\mathbf{1}$ be nodes' in-degrees and $\boldsymbol{\delta}_{\text{out}} = \mathbf{1}^T P$ be nodes' out-degrees. For a weighted G, the degrees are weighted as well. Applying $\mathcal{L}_P(\cdot)$ to $\boldsymbol{\delta}_{\text{in}}$, it gives

$$\beta_{\text{eff}} = \mathcal{L}_P(\boldsymbol{\delta}_{\text{in}}) = \frac{\mathbf{1}^T P \boldsymbol{\delta}_{\text{in}}}{\mathbf{1}^T \boldsymbol{\delta}_{\text{in}}} = \frac{\boldsymbol{\delta}_{\text{out}}^T \boldsymbol{\delta}_{\text{in}}}{\mathbf{1}^T \boldsymbol{\delta}_{\text{in}}}, \tag{3}$$

which proves to be a powerful metric to measure the resilience of networks, and has been applied to make reliable inferences from incomplete networks (Jiang et al., 2020b;a). We use it to measure the predictive ability of a NN (see Section 4.3), whose training in essence is a dynamical system.

NN Training is a Dynamical System. Conventionally, training a NN is a nonlinear optimization problem. Because of the hierarchical structure of NNs, the training procedure is implemented by two alternate procedures: forward-propagation (**FP**) and back-propagation (**BP**), as described in Fig.1(**a**). During FP, data goes through the input layer, hidden layers, up to the output layer, which produces the predictions of the input data. The differences between the outputs and the labels of the input data are used to define an objective function $\mathcal{C}$, a.k.a training error function. BP proceeds to minimize $\mathcal{C}$, in a reverse way as did in FP, by propagating the error from the output layer down to the input layer. The trainable weights of synaptic connections are updated accordingly.

Let G_A be a NN, $\boldsymbol{w}$ be the flattened weight vector for G_A, and $\boldsymbol{z}$ be the set of activation values. As a whole, the training of G_A can be described with two coupled dynamics: $\mathcal{A}$ on G_A, and $\mathcal{B}$ on G_B, where nodes in G_A are neurons, and nodes in G_B are the synaptic connections. The coupling relation arises from the strong inter-dependency between $\boldsymbol{z}$ and $\boldsymbol{w}$: the states $\boldsymbol{z}$ (activation values or activation gradients) of G_A are the parameters of $\mathcal{B}$, and the states $\boldsymbol{w}$ of G_B are the trainable parameters of G_A. If we put the whole training process in the context of networked systems, $\mathcal{A}$ denotes a *node dynamics* because the states of nodes evolve during FP, and $\mathcal{B}$ expresses an *edge dynamics* because of the updates of edge weights during BP (Mei et al., 2018; Poggio et al., 2020a;b). Mathematically, we formulate the node and edge dynamics based on the gradients of $\mathcal{C}$:

$$(\mathcal{A}) \quad d\boldsymbol{z}/dt \approx h_{\mathcal{A}}(\boldsymbol{z}, t; \boldsymbol{w}) = -\nabla_{\boldsymbol{z}} \mathcal{C}(\boldsymbol{z}(t)), \tag{4}$$

$$(\mathcal{B}) \quad d\boldsymbol{w}/dt \approx h_{\mathcal{B}}(\boldsymbol{w}, t; \boldsymbol{z}) = -\nabla_{\boldsymbol{w}} \mathcal{C}(\boldsymbol{w}(t)), \tag{5}$$

where t denotes the training step. Let $a_i^{(\ell)}$ be the pre-activation of node i on layer ℓ, and $\sigma_\ell(\cdot)$ be the activation function of layer ℓ. Usually, the output activation function is a softmax. The hierarchical structure of G_A exerts some constraints over $\boldsymbol{z}$ for neighboring layers, i.e., $z_i^{(\ell)} = \sigma_\ell(a_i^{(\ell)}), 1 \le i \le n_\ell, \forall 1 \le \ell < L$ and $z_k^{(L)} = \exp\{a_k^{(L)}\} / \sum_j \exp\{a_j^{(L)}\}, 1 \le k \le n_L$, where n_ℓ is the total number of neurons on layer ℓ, and it is assumed that G_A has $L + 1$ layers. It also presents a dependency between $\boldsymbol{z}$ and $\boldsymbol{w}$. For example, when G_A is an MLP without bias, we have $a_i^{(\ell)} = \boldsymbol{w}_i^{(\ell)T} \boldsymbol{z}^{(\ell-1)}$, which builds an interconnection from G_A to G_B. It is obvious, given $\boldsymbol{w}$, the activation $\boldsymbol{z}$ satisfying all these constraints, also is a fixed point of $\mathcal{A}$. Meanwhile, an equilibrium state of $\mathcal{B}$ provides a set of optimal weights for G_A.

4 OUR FRAMEWORK

Given a NN G_A, both the architecture and the trainable parameters $\boldsymbol{w}$ can affect its predictive ability. Here we concentrate more on the impacts of $\boldsymbol{w}$, and the edge dynamics $\mathcal{B}$ over G_B (Fig.1**a**). To have a

well-defined G_B and identify an approximated edge dynamics $\mathcal{B}$, we quantify the interaction strength of synaptic connections with the second-order weight gradients of $\mathcal{C}$. Without loss of generality, hereinafter we assume G_A is an MLP with *rectified linear units* (ReLU) (Glorot et al., 2011) for all layers except the output layer, for which the softmax is used. Also, we assume that the NN training uses the categorical cross-entropy $\mathcal{C}$ as the objective function and SGD as the optimization algorithm.

4.1   LINE GRAPH G_B

We build a mapping scheme $\phi : G_A \mapsto G_B$, from a NN G_A to an associated graph G_B. The topology of the synaptic connections (edges) is established as a well-defined line graph proposed by Nepusz & Vicsek (2012), and nodes of G_B are the synaptic connections of G_A. More precisely, each node in G_B is associated with a trainable parameter in G_A. For an MLP, each synaptic connection is assigned a trainable weight, the edge set of G_A is also the set of synaptic connections of G_B. For a CNN, this one-to-one mapping from neurons on layer ℓ to layer $\ell + 1$ is replaced by a one-to-more mapping because of weight-sharing, e.g., a parameter in a convolutional filter is repeatedly used in FP and associated with multiple pairs of neurons from the two neighboring layers. Since the error gradients flow in a reversed direction, we reverse the corresponding links of the proposed line graph for G_B. In specific, given any pair of nodes in G_B, if they share an associated intersection neuron in FP propagation routes, a link with a reversed direction will be created for them. In Fig.1(**a**), we demonstrate how the mapping is performed on an example MLP. We have the topology of G_B in place, but the weights of links in G_B are not yet specified. To make up this missing components, we reveal the interactions of synaptic connections from SGD, quantify the interaction strengths and then define the weights of links in G_B accordingly. Related technical details are disclosed in next section.

4.2   EDGE DYNAMICS $\mathcal{B}$

In SGD, each time a small batch of samples are chosen to update $\boldsymbol{w}$, i.e., $\boldsymbol{w} \leftarrow \boldsymbol{w} - \alpha\nabla_{\boldsymbol{w}}\mathcal{C}$, where $\alpha > 0$ is the learning rate. When desired conditions are met, training is terminated.

We denote the activation gradients as $\boldsymbol{\delta}^{(\ell)} = [\partial\mathcal{C}/\partial z_1^{(\ell)}, \cdots, \partial\mathcal{C}/\partial z_{n_\ell}^{(\ell)}]^T \in \mathcal{R}^{n_\ell 1}$ and the derivatives of activation function σ for layer ℓ as $\boldsymbol{\sigma}'_\ell = [\sigma'_\ell(a_1^{(\ell)}), \cdots, \sigma'_\ell(a_{n_\ell}^{(\ell)})]^T \in \mathcal{R}^{n_\ell}$, $1 \leq \ell \leq L$. To understand how the weights $W^{(\ell)}$ affect each other, we explicitly expand $\boldsymbol{\delta}^{(\ell)}$:

$$\boldsymbol{\delta}^{(\ell)} = W^{(\ell+1)T}(W^{(\ell+2)T}(\cdots(W^{(L-1)T}(W^{(L)T}(\boldsymbol{z}^{(L)} - \boldsymbol{y})) \odot \boldsymbol{\sigma}'_{L-1})\cdots) \odot \boldsymbol{\sigma}'_{\ell+2}) \odot \boldsymbol{\sigma}'_{\ell+1}),$$

where $\odot$ is the Hadamard product. We find that parameters $W^{(\ell)}$ are associated with all accessible parameters on downstream layers, and such recursive relation defines a high-order hyper-network interaction (Casadiego et al., 2017) between any $W^{(\ell)}$ and the other parameters. The Hadamard product $\boldsymbol{x} \odot \boldsymbol{y}$ has an equivalent matrix multiplication form, i.e. $\boldsymbol{x} \odot \boldsymbol{y} = \Lambda(\boldsymbol{y})\boldsymbol{x}$, where $\Lambda(\boldsymbol{y})$ is a diagonal matrix consisting of the entries of $\boldsymbol{y}$ on the diagonal. Therefore, we have $\boldsymbol{\delta}^{(\ell)} = W^{(\ell+1)T}\Lambda(\boldsymbol{\sigma}'_{\ell+1})\boldsymbol{\delta}^{(\ell+1)}$ and $\boldsymbol{\delta}^{(\ell)} = W^{(\ell+1)T}\Lambda(\boldsymbol{\sigma}'_{\ell+1})W^{(\ell+2)T}\Lambda(\boldsymbol{\sigma}'_{\ell+2})\cdots W^{(L-1)T}\Lambda(\boldsymbol{\sigma}'_{L-1})W^{(L)T}(\boldsymbol{z}^{(L)} - \boldsymbol{y})$. For a ReLU $\sigma_\ell(\cdot)$, $\boldsymbol{\sigma}'_\ell$ is binary depending on the sign of the input pre-activation values $\boldsymbol{a}^{(\ell)}$ of layer ℓ. If $a_i^{(\ell)} \leq 0$, then $\sigma'_\ell(a_i^{(\ell)}) = 0$, blocking a BP propagation route of the prediction deviations $\boldsymbol{z}^{(L)} - \boldsymbol{y}$ and giving rise to *vanishing gradients*.

Our purpose is to build direct interactions between synaptic connections. It can be done by identifying which units provide direct physical interactions to a given unit and appear on the right hand side of its differential equation $\mathcal{B}$ in Eq. 4, and how much such interactions come into play. There are multiple routes to build up a direct interaction between any pair of network weights from different layers, as presented by the product terms in $\boldsymbol{\delta}^{(\ell)}$. However, the coupled interaction makes it an impossible task, which is well known as a *credit assignment problem* (Whittington & Bogacz, 2019; Lillicrap et al., 2020). We propose a remedy. The impacts of all the other units on $W^{(\ell)}$ is approximated by direct, local impacts from $W^{(\ell+1)}$, and the others' contribution as a whole is implicitly encoded in the activation gradient $\delta^{(\ell+1)}$.

Moreover, we have the weight gradient (see Appendix A for detailed derivation)

$$\boldsymbol{\nabla}_{W^{(\ell)}} = \Lambda(\boldsymbol{\sigma}'_\ell)\boldsymbol{\delta}^{(\ell)}\boldsymbol{z}^{(\ell-1)T} = \Lambda(\boldsymbol{\sigma}'_\ell)W^{(\ell+1)T}\Lambda(\boldsymbol{\sigma}'_{\ell+1})\boldsymbol{\delta}^{(\ell+1)}\boldsymbol{z}^{(\ell-1)T}, \tag{6}$$

---

[1]In some literature $\boldsymbol{\delta}^{(\ell)}$ is defined as gradients with respect to $\boldsymbol{a}^{(\ell)}$, which does not affect our analysis.

which shows the dependency of $W^{(\ell)}$ on $W^{(\ell+1)}$, and itself can be viewed as an explicit description of the dynamical system $\mathcal{B}$ in Eq. 4. Put it in terms of a differential equation, we have

$$dW^{(\ell)}/dt = -\Lambda(\boldsymbol{\sigma}'_\ell)W^{(\ell+1)T}\Lambda(\boldsymbol{\sigma}'_{\ell+1})\boldsymbol{\delta}^{(\ell+1)}\boldsymbol{z}^{(\ell-1)T}. \qquad (7)$$

Because of the mutual dependency of the weights and the activation values, it is hard to make an exact decomposition of the impacts of different parameters on $W^{(\ell)}$. However, in the gradient $\boldsymbol{\nabla}_{W^{(\ell)}}$, $W^{(\ell+1)}$ presents as an explicit term and contributes the direct impact on $W^{(\ell)}$. To capture such direct impact and derive the adjacency matrix P for G_B, we apply Taylor expansion on $\boldsymbol{\nabla}_{W^{(\ell)}}$

$$P^{(l,l+1)} = \partial^2 \mathcal{C}/\partial W^{(\ell)}\partial W^{(\ell+1)}, \qquad (8)$$

which defines the interaction strength between each pair of weights from layer $\ell+1$ to layer ℓ. See Appendix B for detailed derivation of P on MLP, and Appendix C on general NNs. Let $\boldsymbol{w} = (w_1, w_2, \ldots)$ be a flattened vector of all trainable weights of G_A. Given a pair of weights w_i and w_j, one from layer ℓ_1, another from layer ℓ_2. If $\ell_2 = \ell_1 + 1$, the entry P_{ij} is defined according to Eq. 8, otherwise $P_{ij} = 0$. Considering the scale of trainable parameters in G_A, P is very sparse.

Following Eq. 1, we build up the edge dynamics $\mathcal{B}$ for G_B:

$$dw_i/dt = f(w_i) + \sum_j P_{ij}g(w_i, w_j), \qquad (9)$$

with $f(w_i) = F(w_i^*)$ and $g(w_i, w_j) = w_j - w_j^*$. The value of weights at an equilibrium state $\{w_j^*\}$ is unknown, but it is a constant and does not affect computing of β_{eff}.

4.3 Neural Capacitance

According to Eq. 8, we have the weighted adjacency matrix P of G_B in place. Now we can quantify the total impact that a trainable parameter (or synaptic connection) receives from itself and the others, which corresponds to the weighted in-degrees $\boldsymbol{\delta}_{\text{in}} = P\mathbf{1}$. Applying $\mathcal{L}_P(\cdot)$ (see Eq. 3) to $\boldsymbol{\delta}_{\text{in}}$, we get a "counterpart" metric $\beta_{\text{eff}} = \mathcal{L}_P(\boldsymbol{\delta}_{\text{in}})$ to measure the predictive ability of a neural network G_A, as the resilience metric (see Eq. 3) does to a general network G (see **Dynamical System of a Network** in Section 3). If G_A is an MLP, we can explicitly write the entries of P, hence get a β_{eff} in explicit form

$$\beta_{\text{eff}} = \frac{\sum_{\ell=2}^{L-2}[\mathbf{1}^T\boldsymbol{z}^{(\ell-2)}] \times \mathbf{1}^T[\boldsymbol{z}^{(\ell-1)} \odot \boldsymbol{\sigma}'_{\ell-1}] \times \mathbf{1}^T[\boldsymbol{\delta}^{(\ell)} \odot \boldsymbol{\sigma}'_\ell] \times \mathbf{1}^T[\boldsymbol{\delta}^{(\ell+1)} \odot \boldsymbol{\sigma}'_{\ell+1}]}{\sum_{\ell=2}^{L-1}[\mathbf{1}^T\boldsymbol{z}^{(\ell-2)}] \times [\mathbf{1}^T\boldsymbol{\sigma}'_{\ell-1}] \times \mathbf{1}^T[\boldsymbol{\delta}^{(\ell)} \odot \boldsymbol{\sigma}'_\ell]}. \qquad (10)$$

For details of how to derive P and β_{eff} of an MLP, see Appendix B. Moreover, we prove in Theorem 1 below that as G_A converges, $\boldsymbol{\nabla}_W^{(\ell)}$ vanishes, and β_{eff} approaches zero (see Appendix D).

Theorem 1. *Let ReLU be the activation function of G_A. When G_A converges, then $\beta_{\text{eff}} = 0$.*

For an MLP G_A, it is possible to derive an analytical form of β_{eff}. However, it becomes extremely complicated for a deep NN with multiple convolutional layers. To realize β_{eff} for deep NNs in any form, we take advantage of the automatic differentiation implemented in TensorFlow[2]. Considering the number of parameters, it is still computationally expensive, and prohibitive to calculate a β_{eff} for the entire G_A. Because of this, we seek to derive a surrogate from partial of G_A. As shown in Section 4.4, we insert a *neural capacitance probe* (**NCP**) unit, i.e., putting additional lay-

---

Algorithm 1 Implement NCP and Compute β_{eff}

Input: A pre-trained model $\mathcal{F}_s = \{\mathcal{F}_s^{(1)}, \mathcal{F}_s^{(2)}\}$ with bottom layers $\mathcal{F}_s^{(1)}$ and output layer $\mathcal{F}_s^{(2)}$, a target dataset D_t, the maximum number of epochs T

1: Remove $\mathcal{F}_s^{(2)}$ from $\mathcal{F}_s$ and add on top of $\mathcal{F}_s^{(1)}$ an NCP unit $\mathcal{U}$ with multiple layers (Fig.1**b**)
2: Initialize with random weights and freeze $\mathcal{U}$
3: Train $\mathcal{F}_t = \{\mathcal{F}_s^{(1)}, \mathcal{U}\}$ by fine-tuning $\mathcal{F}_s^{(1)}$ on D_t for epochs of T
4: Compute β_{eff} according to Eq. 3

---

ers on top of the beheaded G_A (excluding the original output layer), and estimate the predictive ability of the entire G_A using β_{eff} of the NCP unit. Therefore, in the context of model selection from a pool of pre-trained models, if no confusion arises, we call β_{eff} a *neural capacitance*.

---

[2]https://www.tensorflow.org/

4.4 Model Selection with β_{eff}

Here we show a novel application of our proposed neural capacitance β_{eff} to model selection. With a few of observations collected from early phase of the fine-tuning, we predict and rank pre-trained models according to their accuracy, and select the best one.

Using a small learning rate, the models are fine-tuned by (i) removing the output layer of the pre-trained model, (ii) adding some layers on top of the remaining layers (Fig.1**b**). As shown in the pseudo-code Algorithm 1, the newly added layers $\mathcal{U}$ on top of the bottom layers of $\mathcal{F}_s$ are used as an NCP unit. The specifics of the NCP unit are detailed in Section 5. The NCP does not involve in fine-tuning, and is merely used to calculate β_{eff} of G_A, then to estimate the performance of G_A over the target domain D_t.

According to Theorem 1, when the model converges, $\beta_{\text{eff}} \to 0$. In an indirect way, the predictive ability of the model can be determined by the relation between the training β_{eff} and the validation accuracy I. Since both β_{eff} and I are available during fine-tuning, we collect a set of data points of these two in the early phase as the observations, and fit a regularized linear model $I = h(\beta_{\text{eff}}; \boldsymbol{\theta})$ with Bayesian ridge regression (Tipping, 2001), where $\boldsymbol{\theta}$ is the associated set of coefficients (see Appendix E for the technical details). The estimated predictor $I = h(\beta_{\text{eff}}; \theta^*)$ makes prediction of the final accuracy of models by setting $\beta_{\text{eff}} = 0$, i.e., $I^* = h(0; \theta^*)$, as shown in row 3 of Fig.2 for illustration of our β_{eff} based learning curve prediction over pre-trained models. For full training of the best model, one can either retain or remove the NCP and fine-tune the selected model.

5 Experiments and Results

Pre-trained models and datasets. In our experiments, 17 pre-trained ImageNet models implemented in Keras[3], including the AlexNet, two VGGs (VGG16 and VGG19), six ResNets (ResNet50, ResNet50V2, ResNet101, ResNet101V2, ResNet152 and ResNet152V2), three DenseNets (DenseNet121, DenseNet169 and DenseNet201), two MobileNets (MobileNet and MobileNetV2), two Inceptions (InceptionV3, InceptionResNetV2) and one Xception are evaluated to measure the performance of our approach. Four benchmark datasets CIFAR10, CIFAR100, SVHN, Fashion MNIST of size $32 \times 32 \times 3$, and one Kaggle challenge dataset Birds[4] of size $224 \times 224 \times 3$ are used, and their original train/test splits are adopted. In addition, 15K original training samples are set aside as validation set for each dataset.

Experimental setup. On top of each pre-trained model, we put an NCP unit composed of (1) a dense layer of size 256, (2) a dense layer of size 128, each of which follows (3) a batch normalization and is followed by (4) a dropout layer with a dropout probability of 0.4. Before fine-tuning, we initialize the NCP unit according to the Kaiming normal initialization approach (He et al., 2015).

We set a batch size of 64 and a learning rate of 0.001, fine-tune each pre-trained model for $T = 50$ epochs, and repeated it for 20 times. As shown in Fig.2, the pre-trained models are converged after the fine-tuning on CIFAR10. For each model, we collect the validation accuracy (blue stars in row 1) and β_{eff} on the training set (green squares in row 2) during the early stage of the fine-tuning to produce some observations (e.g., green squares in row 3 marked by the green box for 5 epochs), then use these observations to predict the test accuracy unseen before the fine-tuning terminates. For better illustration, learning curves are visualized on a log-scale.

Evaluation. Using a few of observations, we apply the Bayesian ridge regression to capture the relation between β_{eff} and the validation accuracy, and to estimate a learning curve predictor $I = h(\beta_{\text{eff}}; \boldsymbol{\theta}^*)$. The performance of the model can be immediately revealed as $I^* = h(\beta_{\text{eff}}^*; \boldsymbol{\theta}^*)$ with $\beta_{\text{eff}}^* = 0$. As shown in row 3 of Fig.2, the blue lines are estimated $h(\cdot; \boldsymbol{\theta})$, the true test accuracy at epoch 50 and the predicted accuracy are marked as red triangles and blue stars, respectively. Both the estimates and predictions are accurate.

We aim to select the best from a pool of candidates using available observations. A relative rank of these candidates matters more than their exact values of predicted accuracy. To evaluate and compare different approaches, we choose Spearman's rank correlation coefficient ρ as the metric, and calculate

---

[3]https://keras.io/api/applications/
[4]https://www.kaggle.com/gpiosenka/100-bird-species

Figure 2: Learning curves of five representative pre-trained models w.r.t accuracy (row 1) and β_{eff} (row 2). A regularized linear model $h(\cdot; \boldsymbol{\theta})$ (blue curve in row 3) is estimated with Bayesian ridge regression using a few of observations of β_{eff} on training set and validation accuracy I during early fine-tuning. The starting epoch t_0 of observations affects the fit of h, and is automatically determined according to BIC, and the true test accuracy at epoch 50 is predicted with $I^* = h(0; \boldsymbol{\theta}^*)$.

Figure 3: (a) Our β_{eff} based prediction of the validation accuracy versus the true test accuracy at epoch 50 of seven representative pre-trained models. Each shape is associated with one type of pre-trained models. Distinct models of the same type are marked in different colors. Because the accuracy of AlexNet is much lower than others, we exclude it for better visualization. Its predicted accuracy is 0.871, and the true test accuracy is 0.868. If it is included, $\rho = 0.93 > 0.92$. (b) Impacts of the starting epoch t_0 of the observations and (c) the number of training samples on the ranking performance of our β_{eff} based approach.

ρ over the true test accuracy at epoch 50 and the predicted accuracy I^* of a set of pre-trained models. In Fig.3(a), we report the specific true and predicted values for each model on CIFAR10, as well as the overall ranking performance measured by ρ. It indicates that our β-based model ranking is reliable with $\rho > 0.9$. For the results on all five datasets, see Appendix Fig.F.5.

The estimation quality of h determines how well the relation between I and β_{eff} is captured. Besides the regression method, the starting epoch t_0 of the observations also plays a role in the estimation. As shown in Fig.3(b), we evaluate the impact of t_0 on ρ of our approach. It goes as expected, when the length of learning curves is fixed, a higher t_0 usually produces a better ρ. Since our ultimate goal is to predict with the early observations, t_0 should also be constrained to a small value. To make the comparisons fair, we view t_0 as a hyper-parameter, and select it according to the Bayesian information criterion (BIC) (Friedman et al., 2001), as shown in row 3 of Fig.2.

Impact of size of training set. CIFAR10 has 50K original training and 10K testing samples. Generally, the 50K samples are further split into 35K for training and 15K for validation. In studying the dynamics of the NN training, it is essential to understand how varying the training size influences the effectiveness of our approach. We select the first $\{10,15,20,25,30\}$K of the original 50K samples as the training set of reduced size, and the last 10K samples as the validation set to fine-tune the pre-trained models for 50 epochs. As shown in Fig.3(c), we can use a training set of size as small as 25K to achieve similar performance to that uses all 35K training samples. It has an important implication for efficient NN training, because the size of required training set can be greatly reduced (around 30% in our experiment) while maintaining similar model ranking performance. To be noted

Figure 4: A comparison between our β_{eff} based approach and the baselines in model ranking.

that the true test accuracy used in computing ρ is the same test accuracy for the model trained from 35K training samples and it's shared by all the five cases $\{10,15,20,25,30\}$K in our analysis.

Ours. versus baselines. We select BGRN (Baker et al., 2017) and CL (Chandrashekaran & Lane, 2017) as the baselines, as well as two heuristic rules of using the last seen value (LSV) (Klein et al., 2017b) or the best seen value (BSV) of a learning curve for extrapolation.

We compare the model ranking performance of our approach with the baselines. As shown in Fig.4, using a few of observations, e.g., only 5 epochs, our approach can achieve 9.1/38.3/12.4/65.3/40.1% relative improvements over the best baseline on CIFAR10/CIFAR100/SVHN/Fashion MNIST/Birds.

Running time analysis. Our approach is efficient, especially for large and deep NNs. Different from the training task that involves a full FP and BP, i.e. $T_{\text{train}} = T_{\text{FP}} + T_{\text{BP}}$, computing β_{eff} only requires to compute the adjacency matrix P or the second order gradients according to Eq. 8 on the NCP unit, $T_{\beta_{\text{eff}}} = T_{\text{NCP}}$. Although the computation is complicated, the NCP unit is lightweight. The computing cost per epoch is comparable to the training time per epoch (see Appendix Fig.G.6). Let $T_{\beta_{\text{eff}}} = c \times T_{\text{train}}$. If $c > 1$, i.e., $T_{\beta_{\text{eff}}}$ is higher than T_{train}, vice versa. Considering the required epochs, our approach needs k observations, and takes $T_{\text{ours}} = k \times T_{\beta_{\text{eff}}}$. To obtain the ground-truth final accuracy by running K epochs, it takes $T_{\text{full}} = K \times T_{\text{train}}$. If $T_{\text{full}} > T_{\text{ours}}$, our β_{eff} based prediction is cheaper than "just training longer". It indicates that $K \times T_{\text{train}} - k \times T_{\beta_{\text{eff}}} = (K - c \times k) \times T_{\text{train}} > 0$, saving us $K - c \times k$ more training epochs.

We perform a running time analysis of the two tasks with $4\times$ NVIDIA Tesla V100 SXM2 32GB, and visualize the related times in Appendix Fig.G.6. On average $c = T_{\beta_{\text{eff}}}/T_{\text{train}} \approx 1.3$, computing β_{eff} takes 1.3 times of the training per epoch. But the efforts are paying off, as we can predict the final accuracy by observing only $k = 10$ of $K = 100$ full training epochs, T_{ours} is only 13% of T_{full}.

When the observations are used for learning curve prediction, the heuristics LSV and BSV directly take one observation (last or best) as the predicted value, so they are mostly computationally cheap but have suboptimal model ranking performances. Relatively, BGRN and CL are more time-consuming because both require to train a predictor with a set of full learning curves from other models. Our approach also estimates a predictor, but does not need any external learning curves. Here we assume that each model is observed for only $k = 5$ epochs, and conduct a running time analysis of these approaches over learning curve prediction, including estimating a predictor. As shown in Appendix Table G.1, our approach applies Bayesian ridge regression to efficiently estimate the predictor $I = h(\beta_{\text{eff}}; \boldsymbol{\theta})$, taking comparable time as BGRN, significantly less than CL, but performs best in model ranking. In contrast, the most expensive CL, does not perform well, sometimes even worst.

6   CONCLUSION AND DISCUSSION

We present a new perspective of NN model selection by directly exploring the dynamical evolution of synaptic connections during NN training. In our framework, the SGD algorithm based NN training is formulated as $\mathcal{B}$, a set of differential equations, to capture the mutual interaction and dependency of synaptic connections. Therefore, a networked system is built by converting an NN G_A to a line graph G_B, and G_B is governed by the dynamics $\mathcal{B}$. Also, we propose a straightforward measurement of the interaction strength for pairs of synaptic connections, and hence induce a definition of link weights in G_B. Moreover, a topological property of G_B named *neural capacitance* β_{eff} is developed and shown to be an effective metric in predicting the ranking of a set of pre-trained models based on early training results.

There are two important research directions that we intend to explore in the future. (i) Simplify the adjacency matrix P to capture the dependency and mutual interaction between synaptic connections, e.g., approximate gradients using local information (Jaderberg et al., 2017), and (ii) design an efficient algorithm to directly optimize NN architectures based on β_{eff}.

REFERENCES

Alessandro Achille, Matteo Rovere, and Stefano Soatto. Critical learning periods in deep networks. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Bowen Baker, Otkrist Gupta, Ramesh Raskar, and Nikhil Naik. Accelerating neural architecture search using performance prediction. *arXiv preprint arXiv:1705.10823*, 2017.

Andrzej Banburski, Qianli Liao, Brando Miranda, Lorenzo Rosasco, Fernanda De La Torre, Jack Hidary, and Tomaso Poggio. Theory III: Dynamics and generalization in deep networks. *arXiv preprint arXiv:1903.04991*, 2019.

Albert-László Barabási and Márton Pósfai. *Network Science*. Cambridge University Press, 2016.

Kartikeya Bhardwaj, Guihong Li, and Radu Marculescu. How does topology influence gradient propagation and model performance of deep networks with densenet-type skip connections? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13498–13507, 2021.

Léon Bottou. Stochastic gradient descent tricks. In *Neural networks: Tricks of the Trade*, pp. 421–436. Springer, 2012.

Jose Casadiego, Mor Nitzan, Sarah Hallerberg, and Marc Timme. Model-free inference of direct network interactions from nonlinear collective dynamics. *Nature Communications*, 8(1):1–10, 2017.

Akshay Chandrashekaran and Ian R Lane. Speeding up hyper-parameter optimization by extrapolation of learning curves using previous builds. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 477–492. Springer, 2017.

Bo Chang, Minmin Chen, Eldad Haber, and H Chi. AntisymmetricRNN: A dynamical system view on recurrent neural networks. In *International Conference on Learning Representations*, 2018.

Akshunna S Dogra. Dynamical systems and neural networks. *arXiv preprint arXiv:2004.11826*, 2020.

Akshunna S. Dogra and William Redman. Optimizing neural networks via Koopman operator theory. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 2087–2097. Curran Associates, Inc., 2020.

Tobias Domhan, Jost Tobias Springenberg, and Frank Hutter. Speeding up automatic hyperparameter optimization of deep neural networks by extrapolation of learning curves. In *Twenty-fourth International Joint Conference on Artificial Intelligence*, 2015.

Yu Feng and Yuhai Tu. Phases of learning dynamics in artificial neural networks: in the absence or presence of mislabeled data. *Machine Learning: Science and Technology*, 2021.

Jonathan Frankle, Gintare Karolina Dziugaite, Daniel M Roy, and Michael Carbin. Stabilizing the lottery ticket hypothesis. *arXiv preprint arXiv:1903.01611*, 2019.

Jonathan Frankle, David J Schwab, and Ari S Morcos. The early phase of neural network training. *arXiv preprint arXiv:2002.10365*, 2020.

Jerome Friedman, Trevor Hastie, Robert Tibshirani, et al. *The elements of statistical learning*, volume 1. Springer series in statistics New York, 2001.

Jianxi Gao, Baruch Barzel, and Albert-László Barabási. Universal resilience patterns in complex networks. *Nature*, 530(7590):307–312, 2016.

Xavier Glorot, Antoine Bordes, and Yoshua Bengio. Deep sparse rectifier neural networks. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pp. 315–323. JMLR Workshop and Conference Proceedings, 2011.

Sebastian Goldt, Madhu Advani, Andrew M Saxe, Florent Krzakala, and Lenka Zdeborová. Dynamics of stochastic gradient descent for two-layer neural networks in the teacher-student setup. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Guy Gur-Ari, Daniel A Roberts, and Ethan Dyer. Gradient descent happens in a tiny subspace. *arXiv preprint arXiv:1812.04754*, 2018.

Simon Haykin. *Neural Networks and Learning Machines*. Pearson Education India, 2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on ImageNet classification. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1026–1034, 2015.

Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. MobileNets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

Max Jaderberg, Wojciech Marian Czarnecki, Simon Osindero, Oriol Vinyals, Alex Graves, David Silver, and Koray Kavukcuoglu. Decoupled neural interfaces using synthetic gradients. In *International Conference on Machine Learning*, pp. 1627–1635. PMLR, 2017.

Chunheng Jiang, Jianxi Gao, and Malik Magdon-Ismail. Inferring degrees from incomplete networks and nonlinear dynamics. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20*, pp. 3307–3313. International Joint Conferences on Artificial Intelligence Organization, 2020a.

Chunheng Jiang, Jianxi Gao, and Malik Magdon-Ismail. True nonlinear dynamics from incomplete networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 131–138, 2020b.

Aaron Klein, Stefan Falkner, Simon Bartels, Philipp Hennig, and Frank Hutter. Fast Bayesian optimization of machine learning hyperparameters on large datasets. In *Artificial Intelligence and Statistics*, pp. 528–536. PMLR, 2017a.

Aaron Klein, Stefan Falkner, Jost Tobias Springenberg, and Frank Hutter. Learning curve prediction with Bayesian neural networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017b.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

Timothy P Lillicrap, Adam Santoro, Luke Marris, Colin J Akerman, and Geoffrey Hinton. Backpropagation and the brain. *Nature Reviews Neuroscience*, pp. 1–12, 2020.

David JC MacKay. Bayesian interpolation. *Neural Computation*, 4(3):415–447, 1992.

Song Mei, Andrea Montanari, and Phan-Minh Nguyen. A mean field view of the landscape of two-layer neural networks. *Proceedings of the National Academy of Sciences*, 115(33):E7665–E7671, 2018.

Melanie Mitchell. Complex systems: Network thinking. *Artificial Intelligence*, 170(18):1194–1212, 2006.

Tamás Nepusz and Tamás Vicsek. Controlling edge dynamics in complex networks. *Nature Physics*, 8(7):568–573, 2012.

Tomaso Poggio, Andrzej Banburski, and Qianli Liao. Theoretical issues in deep networks. *Proceedings of the National Academy of Sciences*, 117(48):30039–30045, 2020a.

Tomaso Poggio, Qianli Liao, and Andrzej Banburski. Complexity control by gradient descent in deep networks. *Nature Communications*, 11(1):1–5, 2020b.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Mauricio E Tano, Gavin D Portwood, and Jean C Ragusa. Accelerating training in artificial neural networks with dynamic mode decomposition. *arXiv preprint arXiv:2006.14371*, 2020.

Stefan Thurner, Peter Klimek, and Rudolf Hanel. A network-based explanation of why most covid-19 infection curves are linear. *Proceedings of the National Academy of Sciences*, 117(37):22684–22689, 2020.

Yuandong Tian. An analytical formula of population gradient for two-layered relu network and its applications in convergence and critical point analysis. In *International Conference on Machine Learning*, pp. 3404–3413. PMLR, 2017.

Michael E Tipping. Sparse Bayesian learning and the relevance vector machine. *Journal of Machine Learning Research*, 1(Jun):211–244, 2001.

Nickolas M Waser and Jeff Ollerton. *Plant-pollinator interactions: from specialization to generalization*. University of Chicago Press, 2006.

James CR Whittington and Rafal Bogacz. Theories of error back-propagation in the brain. *Trends in Cognitive Sciences*, 23(3):235–250, 2019.

Martin Wistuba and Tejaswini Pedapati. Learning to rank learning curves. In *International Conference on Machine Learning*, pp. 10303–10312. PMLR, 2020.

A   ERROR GRADIENTS

Let G_A be an MLP. To understand the learning mechanism, we take a sample x with label y, and go through the entire training procedure, including a forward pass FP and a backward pass BP. To be convenient, we rewrite $z^{(0)} = x$ as the inputs, let $z^{(1)}$ and $z^{(L-1)}$ be the activations of the first and the last hidden layers, respectively, and let $z^{(L)}$ be the outputs. The MLP is a parameterized model $\hat{y} = z^{(L)} = F_w(x)$ with $w = (W^{(1)}, W^{(2)}, \ldots, W^{(L)})$, where $W^{(\ell)}$ is the weight matrix of synaptic connections from layer $\ell - 1$ to layer ℓ, and $1 \leq \ell \leq L$. Suppose there are n_ℓ neurons on layer ℓ, $W^{(\ell)}$ has the size $n_\ell \times n_{\ell-1}$. The inputs x are fed into MLP, after a forward pass from layer 1 down to layer $L - 1$ and layer L. Each neuron receives a cumulative input signal from the previous layer, and sends an activated signal to a downstream layer. Let σ_ℓ be the activation function of layer ℓ, $a_i^{(\ell)} = w_i^{(\ell)T} z^{(\ell-1)}$ be the pre-activation value of neuron i on layer ℓ, we have $z_i^{(\ell)} = \sigma_\ell(a_i^{(\ell)})$ with $w_i^{(\ell)}$ being the ith row of $W^{(\ell)}$, $1 \leq i \leq n_\ell$. The output activation function σ_L is generally a softmax function, i.e. $z_i^{(L)} = \exp\{a_i^{(L)}\}/\sum_j \exp\{a_j^{(L)}\}$, and $z^{(L)}$ is a probability distribution over n_L classes, i.e. $\mathbf{1}^T z^{(L)} = 1$.

With the predictions $z^{(L)}$ and the ground truth y, we can calculate the prediction error $\mathcal{C}(z^{(L)}, y)$, which is often a cross entropy loss, i.e. $\mathcal{C}(z^{(L)}, y) = -\sum_i y_i \log z_i^{(L)}$. To minimize $\mathcal{C}$, BP is applied, and the weights w are updated backward, from the output layer up to the first hidden layer.

Now we derive the gradients for a close examination. First, we get the derivatives of $\mathcal{C}$ w.r.t $z^{(L)}$ and $W^{(L)}$. Because $z_i^{(L)} = \exp\{a_i^{(L)}\}/\sum_j \exp\{a_j^{(L)}\}$, we get the gradient of the output $z_k^{(L)}$ w.r.t $w_{ij}^{(L)}$:

$$\partial z_k^{(L)}/\partial w_{ij}^{(L)} = z_k^{(L)}(\delta_{ki} - z_i^{(L)})z_j^{(L-1)},$$

where $\delta_{ki} = 1$ if $k = i$, otherwise $\delta_{ki} = 0$.

On layer L, we get the derivatives of $\mathcal{C}$ w.r.t $z^{(L)}$ and $W^{(L)}$:

$$\frac{\partial \mathcal{C}}{\partial z_i^{(L)}} = -\frac{y_i}{z_i^{(L)}}; \quad \frac{\partial \mathcal{C}}{\partial w_{ij}^{(L)}} = \sum_k \frac{\partial \mathcal{C}}{\partial z_k^{(L)}} \frac{\partial z_k^{(L)}}{\partial w_{ij}^{(L)}} = (z_i^{(L)} - y_i)z_j^{(L-1)} \tag{11}$$

Then, we examine layer $L - 1$. The activation function σ_{L-1} associates to a pair of neurons $u_i^{(L-1)}$ on layer $L - 1$ and $u_j^{(L-2)}$ on layer $L - 2$ with a unique connection weight $w_{ij}^{(L-1)}$. Since $z_i^{(L)} = \exp\{a_i^{(L)}\}/\sum_j \exp\{a_j^{(L)}\}$ and $z_i^{(L-1)} = \sigma_{L-1}(a_i^{(L-1)})$, we get $\partial z_k^{(L)}/\partial z_i^{(L-1)} = z_k^{(L)}(w_{ki}^{(L)} - \sum_j z_j^{(L)}w_{ji}^{(L)}) = z_k^{(L)}(w_{ki}^{(L)} - w_{*i}^{(L)T}z^{(L)})$, and

$$\partial z_i^{(L-1)}/\partial w_{ij}^{(L-1)} = z_j^{(L-2)}\sigma_{L-1}'(a_i^{(L-1)}).$$

The derivatives of $\mathcal{C}$ are

$$\begin{aligned}
\frac{\partial \mathcal{C}}{\partial z_i^{(L-1)}} &= \sum_k \frac{\partial \mathcal{C}}{\partial z_k^{(L)}} \frac{\partial z_k^{(L)}}{\partial z_i^{(L-1)}} = \sum_k y_k(w_{*i}^{(L)T}z^{(L)} - w_{ki}^{(L)}) = w_{*i}^{(L)T}(z^{(L)} - y), \\
\frac{\partial \mathcal{C}}{\partial w_{ij}^{(L-1)}} &= \frac{\partial \mathcal{C}}{\partial z_i^{(L-1)}} \frac{\partial z_i^{(L-1)}}{\partial w_{ij}^{(L-1)}} = w_{*i}^{(L)T}(z^{(L)} - y)z_j^{(L-2)}\sigma_{L-1}'(a_i^{(L-1)}).
\end{aligned}$$

On layer ℓ, where $1 \leq \ell \leq L - 2$, we get $\partial z_k^{(\ell+1)}/\partial z_i^{(\ell)} = w_{ki}^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})$ and

$$\begin{aligned}
\frac{\partial \mathcal{C}}{\partial z_i^{(\ell)}} &= \sum_k \frac{\partial \mathcal{C}}{\partial z_k^{(\ell+1)}} \frac{\partial z_k^{(\ell+1)}}{\partial z_i^{(\ell)}} = \sum_k \frac{\partial \mathcal{C}}{\partial z_k^{(\ell+1)}} w_{ki}^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)}), \\
\frac{\partial \mathcal{C}}{\partial w_{ij}^{(\ell)}} &= \frac{\partial \mathcal{C}}{\partial z_i^{(\ell)}} \frac{\partial z_i^{(\ell)}}{\partial w_{ij}^{(\ell)}} = \frac{\partial \mathcal{C}}{\partial z_i^{(\ell)}} z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)}),
\end{aligned}$$

according to the relations $z_i^{(\ell+1)} = \sigma_{\ell+1}(a_i^{(\ell+1)})$ and $z_i^{(\ell)} = \sigma_\ell(a_i^{(\ell)})$.

Let $\delta^{(\ell)} = [\partial \mathcal{C}/\partial z_1^{(\ell)}, \cdots, \partial \mathcal{C}/\partial z_{n_\ell}^{(\ell)}]^T \in \mathcal{R}^{n_\ell}$, $\sigma_\ell' = [\sigma_\ell'(a_1^{(\ell)}), \cdots, \sigma_\ell'(a_{n_\ell}^{(\ell)})]^T \in \mathcal{R}^{n_\ell}$, $1 \leq \ell \leq L$. The gradients can be written in a dense form:

$$\begin{aligned}
\nabla_{W^{(L)}} &= (z^{(L)} - y)z^{(L-1)T} \in \mathcal{R}^{n_L \times n_{L-1}}, \\
\delta^{(L-1)} &= W^{(L)T}(z^{(L)} - y) \in \mathcal{R}^{n_{L-1}}, \\
\nabla_{W^{(L-1)}} &= (\delta^{(L-1)} \odot \sigma_{L-1}')z^{(L-2)T} \in \mathcal{R}^{n_{L-1} \times n_{L-2}}, \\
\delta^{(\ell)} &= W^{(\ell+1)T}(\delta^{(\ell+1)} \odot \sigma_{\ell+1}') \in \mathcal{R}^{n_\ell}, \\
\nabla_{W^{(\ell)}} &= (\delta^{(\ell)} \odot \sigma_\ell')z^{(\ell-1)T} \in \mathcal{R}^{n_\ell \times n_{\ell-1}}.
\end{aligned} \tag{12}$$

B   WEIGHTED DEGREES OF G_B

We examine three hidden layers $\{\ell - 1, \ell, \ell + 1\}$ of G_A and three neurons on these layers $\{j, i, k\}$. Let $w_{ki}^{(\ell+1)}$ connects the neuron k on layer $\ell + 1$ to the neuron i on layer ℓ, $w_{ij}^{(\ell)}$ be the synaptic connection weight between the neuron j on layer ℓ and the neuron i on layer $\ell - 1$, and $w_{jm}^{(\ell-1)}$ connects the neuron j on layer $\ell - 1$ and the neuron m on layer $\ell - 2$.

Now we have a close look at $\partial\mathcal{C}/\partial w_{ij}^{(\ell)}$. According to the chain rule, we have

$$\frac{\partial\mathcal{C}}{\partial w_{ij}^{(\ell)}} = \frac{\partial\mathcal{C}}{\partial z_i^{(\ell)}}\frac{\partial z_i^{(\ell)}}{\partial w_{ij}^{(\ell)}} = \delta_i^{(\ell)}z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)}) = z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)})\sum_k \delta_k^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})w_{ki}^{(\ell+1)}.$$

The gradient term $\delta_k^{(\ell+1)} = \partial\mathcal{C}/\partial z_k^{(\ell+1)}$ is a highly coupled function of all accessible synaptic connection weights of $w_{ij}^{(\ell)}$ on the forward propagation route from $z_i^{(\ell)}$ to the output neurons. To ease the analysis, we simplify it with a numerical value or a synthetic one with no synaptic connection weight included. Therefore, the summation term can be viewed as a simple linear function of all synaptic connection weights $w_{ki}^{(\ell+1)}$ associated with neuron i on layer ℓ, and the associated coefficient is $p\{w_{ki}^{(\ell+1)}, w_{ij}^{(\ell)}\} = z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)})\delta_k^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})$, which defines the edge weights from $w_{ki}^{(\ell+1)}$ to $w_{ij}^{(\ell)}$ on G_B. Similarly, we have the edge weight from $w_{ij}^{(\ell)}$ to $w_{jm}^{(\ell-1)}$, i.e., $p\{w_{ij}^{(\ell)}, w_{jm}^{(\ell-1)}\} = z_m^{(\ell-2)}\sigma_{\ell-1}'(a_j^{(\ell-1)})\delta_i^{(\ell)}\sigma_\ell'(a_i^{(\ell)})$. Therefore, we are able to calculate the in-degree and out-degree of $w_{ij}^{(\ell)}$, which are defined as the sum of the weights of all in-bound connections to $w_{ij}^{(\ell)}$ and the sum of the weights of all out-bound connections from $w_{ij}^{(\ell)}$, i.e.

$$\delta_{\text{in}}(w_{ij}^{(\ell)}) = z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)})\Big[\sum_k \delta_k^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})\Big], \tag{13}$$

$$\delta_{\text{out}}(w_{ij}^{(\ell)}) = \Big[\sum_m z_m^{(\ell-2)}\Big]\sigma_{\ell-1}'(a_j^{(\ell-1)})\delta_i^{(\ell)}\sigma_\ell'(a_i^{(\ell)}). \tag{14}$$

There are several exceptions, including the first hidden ($\ell = 1$), the last hidden ($\ell = L - 1$) and the output ($\ell = L$) layers. For the output layer, we have

$$\frac{\partial\mathcal{C}}{\partial w_{ij}^{(L)}} = \sum_k \frac{\partial\mathcal{C}}{\partial z_k^{(L)}}\frac{\partial z_k^{(L)}}{\partial w_{ij}^{(L)}} = z_j^{(L-1)}(z_i^{(L)} - y_i). \tag{15}$$

Because σ_L is softmax, no explicit relation regarding $w_{ij}^{(L)}$ can be built. It implies that no well-defined in-bound connections to $w_{ij}^{(L)}$, i.e., $\delta_{\text{in}}(w_{ij}^{(L)}) = 0$. But, we can build the connections from $w_{ij}^{(L)}$ to $w_{jm}^{(L-1)}$. It is easy to derive

$$\frac{\partial\mathcal{C}}{\partial w_{ij}^{(L-1)}} = \frac{\partial\mathcal{C}}{\partial z_i^{(L-1)}}\frac{\partial z_i^{(L-1)}}{\partial w_{ij}^{(L-1)}} = z_j^{(L-2)}\sigma_{L-1}'(a_i^{(L-1)})\sum_k(z_k^{(L)} - y_k)w_{ki}^{(L)}. \tag{16}$$

From the perspective of $w_{ij}^{(L-1)}$, we get $p\{w_{ki}^{(L)}, w_{ij}^{(L-1)}\} = z_j^{(L-2)}\sigma_{L-1}'(a_i^{(L-1)})(z_k^{(L)} - y_k)$; from the perspective of $w_{ij}^{(L)}$, we have $p\{w_{ij}^{(L)}, w_{jm}^{(L-1)}\} = z_m^{(L-2)}\sigma_{L-1}'(a_j^{(L-1)})(z_i^{(L)} - y_i)$. So we have

$$\begin{aligned}
\delta_{\text{out}}(w_{ij}^{(L)}) &= \Big[\sum_m z_m^{(L-2)}\Big]\sigma_{L-1}'(a_j^{(L-1)})(z_i^{(L)} - y_i), \\
\delta_{\text{in}}(w_{ij}^{(L-1)}) &= z_j^{(L-2)}\sigma_{L-1}'(a_i^{(L-1)})\sum_k(z_k^{(L)} - y_k) = 0, \\
\delta_{\text{out}}(w_{ij}^{(L-1)}) &= \Big[\sum_m z_m^{(L-3)}\Big]\sigma_{L-2}'(a_j^{(L-2)})\delta_i^{(L-1)}\sigma_{L-1}'(a_i^{(L-1)}).
\end{aligned}$$

The softmax $\sigma_L(\cdot)$ makes the output values sum up to one, i.e., $\sum_k y_k = 1$, and $\delta_{\text{in}}(w_{ij}^{(L-1)}) = 0$. Now, we examine the first hidden layer. Similar to the output layer, there is no well-defined out-bound connections for $w_{ij}^{(1)}$, $\delta_{\text{out}}(w_{ij}^{(1)}) = 0$. Setting $\ell = 1$ in Eq. 13, we can get the in-degree of $w_{ij}^{(1)}$

$$\delta_{\text{in}}(w_{ij}^{(1)}) = z_j^{(0)}\sigma_1'(a_i^{(1)})\Big[\sum_k \delta_k^{(2)}\sigma_2'(a_k^{(2)})\Big].$$

Based on our definition of the weights of G_B, when the number of layers is small, it is trivial that $\beta_{\text{eff}} = 0$. To get a non-trivial β_{eff}, we identify the minimum number of hidden layers in G_A. First, we examine a G_A with one hidden layer, i.e. $L = 2$, whose degrees are

$$
\begin{aligned}
\delta_{\text{in}}(w_{ij}^{(1)}) &= \delta_{\text{out}}(w_{ij}^{(1)}) = \delta_{\text{in}}(w_{ij}^{(2)}) = 0, \\
\delta_{\text{out}}(w_{ij}^{(2)}) &= \big[\textstyle\sum_m z_m^{(0)}\big]\sigma_1'(a_j^{(1)})(z_i^{(2)} - y_i).
\end{aligned}
$$

Since the degrees sum up to zero, $\beta_{\text{eff}} = 0$, regardless of how many hidden neurons in G_A.

If G_A only has two hidden layers, i.e. $L = 3$, the in-degrees are

$$
\begin{aligned}
\delta_{\text{in}}(w_{ij}^{(1)}) &= z_j^{(0)}\sigma_1'(a_i^{(1)})\big[\textstyle\sum_{k=1}^{n_2}\delta_k^{(2)}\sigma_2'(a_k^{(2)})\big], \\
\delta_{\text{in}}(w_{ij}^{(2)}) &= \delta_{\text{in}}(w_{ij}^{(3)}) = 0.
\end{aligned}
$$

The out-degrees are summarized as follows:

$$
\begin{aligned}
\delta_{\text{out}}(w_{ij}^{(1)}) &= 0, \\
\delta_{\text{out}}(w_{ij}^{(2)}) &= \big[\textstyle\sum_{m=1}^{n_0} z_m^{(0)}\big]\sigma_1'(a_j^{(1)})\delta_i^{(2)}\sigma_2'(a_i^{(2)}), \\
\delta_{\text{out}}(w_{ij}^{(3)}) &= \big[\textstyle\sum_{m=1}^{n_1} z_m^{(1)}\big]\sigma_2'(a_j^{(2)})(z_i^{(3)} - y_i).
\end{aligned}
$$

The total degree may be non-zero, but $\beta_{\text{eff}} = 0$ alway holds.

Therefore, the minimum number of hidden layers required for a well-defined β_{eff} is three, i.e., $L \geq 4$. We summarize the in-degrees

$$
\begin{aligned}
\delta_{\text{in}}(w_{ij}^{(1)}) &= z_j^{(0)}\sigma_1'(a_i^{(1)})\big[\textstyle\sum_k\delta_k^{(2)}\sigma_2'(a_k^{(2)})\big], \\
\delta_{\text{in}}(w_{ij}^{(\ell)}) &= z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)})\big[\textstyle\sum_k\delta_k^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})\big], \forall 1 < \ell < L - 1, \\
\delta_{\text{in}}(w_{ij}^{(L-1)}) &= 0, \\
\delta_{\text{in}}(w_{ij}^{(L)}) &= 0.
\end{aligned}
$$

and the out-degrees

$$
\begin{aligned}
\delta_{\text{out}}(w_{ij}^{(1)}) &= 0, \\
\delta_{\text{out}}(w_{ij}^{(\ell)}) &= \big[\textstyle\sum_m z_m^{(\ell-2)}\big]\sigma_{\ell-1}'(a_j^{(\ell-1)})\delta_i^{(\ell)}\sigma_\ell'(a_i^{(\ell)}), \forall 1 < \ell < L - 1, \\
\delta_{\text{out}}(w_{ij}^{(L-1)}) &= \big[\textstyle\sum_m z_m^{(L-3)}\big]\sigma_{L-2}'(a_j^{(L-2)})\delta_i^{(L-1)}\sigma_{L-1}'(a_i^{(L-1)}), \\
\delta_{\text{out}}(w_{ij}^{(L)}) &= \big[\textstyle\sum_m z_m^{(L-2)}\big]\sigma_{L-1}'(a_j^{(L-1)})(z_i^{(L)} - y_i).
\end{aligned}
$$

It is easy to derive

$$
\begin{aligned}
\boldsymbol{\delta}_{\text{in}}^T\boldsymbol{\delta}_{\text{out}} &= \textstyle\sum_{i,j}\sum_{1<\ell<L-1}\delta_{\text{in}}(w_{ij}^{(\ell)})\delta_{\text{out}}(w_{ij}^{(\ell)}) \\
&= \textstyle\sum_{i,j}\sum_{1<\ell<L-1}\big[\sum_m z_m^{(\ell-2)}\big]z_j^{(\ell-1)}\sigma_{\ell-1}'(a_j^{(\ell-1)})[\sigma_\ell'(a_i^{(\ell)})]^2\delta_i^{(\ell)}\big[\sum_k\delta_k^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})\big], \\
&= \textstyle\sum_{1<\ell<L-1}[\mathbf{1}^T z^{(\ell-2)}]\times\mathbf{1}^T[z^{(\ell-1)}\odot\boldsymbol{\sigma}_{\ell-1}']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell)}\odot\boldsymbol{\sigma}_\ell'^2]\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell+1)}\odot\boldsymbol{\sigma}_{\ell+1}'].
\end{aligned}
$$

Now, we move forward to compute the total degree

$$
\begin{aligned}
\mathbf{1}^T\boldsymbol{\delta}_{\text{in}} &= \textstyle\sum_{ij} z_j^{(0)}\sigma_1'(a_i^{(1)})\big[\sum_k\delta_k^{(2)}\sigma_2'(a_k^{(2)})\big] + \sum_{ij}\sum_{1<\ell<L-1} z_j^{(\ell-1)}\sigma_\ell'(a_i^{(\ell)})\big[\sum_k\delta_k^{(\ell+1)}\sigma_{\ell+1}'(a_k^{(\ell+1)})\big], \\
&= [\mathbf{1}^T z^{(0)}]\times[\mathbf{1}^T\boldsymbol{\sigma}_1']\times\mathbf{1}^T[\boldsymbol{\delta}^{(2)}\odot\boldsymbol{\sigma}_2'] + \textstyle\sum_{1<\ell<L-1}[\mathbf{1}^T z^{(\ell-1)}]\times[\mathbf{1}^T\boldsymbol{\sigma}_\ell']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell+1)}\odot\boldsymbol{\sigma}_{\ell+1}'], \\
&= \textstyle\sum_{1\leq\ell<L-1}[\mathbf{1}^T z^{(\ell-1)}]\times[\mathbf{1}^T\boldsymbol{\sigma}_\ell']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell+1)}\odot\boldsymbol{\sigma}_{\ell+1}'].
\end{aligned}
$$

The definitions of in-degree and out-degree ensure that $\mathbf{1}^T\boldsymbol{\delta}_{\text{in}} = \mathbf{1}^T\boldsymbol{\delta}_{\text{out}}$ must hold. Let's prove it:

$$
\begin{aligned}
\mathbf{1}^T\boldsymbol{\delta}_{\text{out}} &= \textstyle\sum_{i,j}\big[\sum_{1<\ell\leq L-1}\sum_m z_m^{(\ell-2)}\sigma_{\ell-1}'(a_j^{(\ell-1)})\delta_i^{(\ell)}\sigma_\ell'(a_i^{(\ell)}) + \sum_m z_m^{(L-2)}\sigma_{L-1}'(a_j^{(L-1)})(z_i^{(L)} - y_i)\big], \\
&= \textstyle\sum_{1<\ell\leq L-1}[\mathbf{1}^T z^{(\ell-2)}]\times[\mathbf{1}^T\boldsymbol{\sigma}_{\ell-1}']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell)}\odot\boldsymbol{\sigma}_\ell'] = \mathbf{1}^T\boldsymbol{\delta}_{\text{in}}.
\end{aligned}
$$

With the fact that $\boldsymbol{\sigma}_\ell'^2 = \boldsymbol{\sigma}_\ell'$ for ReLU, according to Eq. 3, we have

$$
\beta_{\text{eff}} = \frac{\sum_{\ell=2}^{L-2}[\mathbf{1}^T z^{(\ell-2)}]\times\mathbf{1}^T[z^{(\ell-1)}\odot\boldsymbol{\sigma}_{\ell-1}']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell)}\odot\boldsymbol{\sigma}_\ell']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell+1)}\odot\boldsymbol{\sigma}_{\ell+1}']}{\sum_{\ell=2}^{L-1}[\mathbf{1}^T z^{(\ell-2)}]\times[\mathbf{1}^T\boldsymbol{\sigma}_{\ell-1}']\times\mathbf{1}^T[\boldsymbol{\delta}^{(\ell)}\odot\boldsymbol{\sigma}_\ell']}.
$$

C   DERIVATION OF ADJACENCY MATRIX P OF G_B

The right hand side (RHS) of Eq. 6 is a function of $W^{(\ell+1)}$, and denoted as $F(W^{(\ell+1)})$. Here we derive the strength of the impact from $W^{(\ell+1)}$ and other weights $W^{(-\ell)} = (W^{(0)}, W^{(1)}, \dots, W^{(\ell)}, W^{(\ell+2)}, \dots, W^{(L)})$ for building the edge dynamics. Let $W = (W^{(\ell+1)}, W^{(-\ell)})$ and $F(W) = dW^{(\ell)}/dt$. We denote $\hat{W}^{(-\ell)}$ as the current states of $W^{(-\ell)}$), $W^{*(\ell+1)}$ as an equilibrium point, and $W^* = (W^{*(\ell+1)}, \hat{W}^{(-\ell)})$. According to the Taylor expansion, we linearize F at W^* and have

$$dW^{(\ell)}/dt \approx F(W^*) + \frac{\partial F(W^{*(\ell+1)}, \hat{W}^{(-\ell)})}{\partial W^{(\ell+1)}}(W^{(\ell+1)} - W^{*(\ell+1)}) + \frac{\partial F(W^{*(\ell+1)}, \hat{W}^{(-\ell)})}{\partial W^{(-\ell)}}(W^{(-\ell)} - \hat{W}^{(-\ell)}).$$

The last term on the RHS can be cancelled out when the realizations of $W^{(-\ell)}$ take the current states of $W^{(-\ell)}$, i.e. $\hat{W}^{(-\ell)}$. The gradient is simplified as

$$dW^{(\ell)}/dt \approx F(W^*) + \frac{\partial F(W^{*(\ell+1)}, \hat{W}^{(-\ell)})}{\partial W^{(\ell+1)}}(W^{(\ell+1)} - W^{*(\ell+1)}).$$

The term $\partial F(W^{*(\ell+1)}, \hat{W}^{(-\ell)})/\partial W^{(\ell+1)} = \partial^2 \mathcal{C}(W^{*(\ell+1)}, \hat{W}^{(-\ell)})/\partial W^{(\ell)}\partial W^{(\ell+1)}$ effectively captures the interaction strengths between $W^{(\ell)}$ and $W^{(\ell+1)}$, because it measures how much F is affected by a unit perturbation on $W^{(\ell+1)}$. Usually, $W^{*(\ell+1)}$ are not available before updating $W^{(\ell+1)}$ following the update of $W^{(\ell)}$, we use the current states of $W^{(\ell+1)}$ instead. The system can be viewed as a realization of the general Eq. 1, with linear $f(W^{(\ell)}) = F(W^*)$ and $g(W^{(\ell)}, W^{(\ell+1)}) = W^{*(\ell+1)} - W^{(\ell+1)}$. Now, we can immediately have the adjacency matrix P of G_B with $P^{(l,l+1)} = \partial^2 \mathcal{C}(W^{(\ell+1)}, \hat{W}^{(-\ell)})/\partial W^{(\ell)}\partial W^{(\ell+1)}, \forall 1 \leq \ell \leq L$.

D   PROOF OF THEOREM 1

The second order gradient $P^{(l,l+1)} = \partial^2 \mathcal{C}/\partial W^{(\ell)}\partial W^{(\ell+1)}$ is proposed to measure the interaction strength between $W^{(\ell)}$ and $W^{(\ell+1)}$, $\forall 1 \leq \ell \leq L$. Considering an MLP, and assume that each activation function σ_ℓ is ReLU for $\ell < L$, when G_A converges, $\boldsymbol{\nabla}_W^{(\ell)}$ vanishes, i.e., $\boldsymbol{\nabla}_W^{(\ell)} = (\boldsymbol{\delta}^{(\ell)} \odot \boldsymbol{\sigma}'^{\ell})z^{(\ell-1)T} = \mathbf{0}$ (see Eq. 12 in Appendix B). It indicates that $(\boldsymbol{\delta}^{(\ell)} \odot \boldsymbol{\sigma}'^{\ell})_i z_j^{(\ell-1)} = 0$, i.e., either $(\boldsymbol{\delta}^{(\ell)} \odot \boldsymbol{\sigma}'^{\ell})_i = 0$ or $z_j^{(\ell-1)} = 0$, $\forall (i,j)$. According to Eq. 10, the numerator involves the product of terms $\boldsymbol{\delta}^{(\ell)} \odot \boldsymbol{\sigma}'^{\ell}$ and $z^{(\ell-1)}$, which are zeros, so $\beta_{\text{eff}} = 0$.

E   BAYESIAN RIDGE REGRESSION

Ridge regression introduces an ℓ_2-regularization to linear regression, and solves the problem

$$\arg\min_{\boldsymbol{\theta}}(\boldsymbol{y} - X\boldsymbol{\theta})^T(\boldsymbol{y} - X\boldsymbol{\theta}) + \lambda\|\boldsymbol{\theta}\|_2^2, \tag{17}$$

where $X \in \mathcal{R}^{n \times d}$, $\boldsymbol{y} \in \mathcal{R}^n$, $\boldsymbol{\theta} \in \mathcal{R}^d$ is the associated set of coefficients, the hyper-parameter $\lambda > 0$ controls the impact of the penalty term $\|\boldsymbol{\theta}\|_2^2$.

Bayesian ridge regression introduces uninformative priors over the hyper-parameters of the model, and estimates a probabilistic model of the problem in Eq. 17. Usually, the ordinary least squares method posits the conditional distribution of $\boldsymbol{y}$ to be a Gaussian, i.e., $p(\boldsymbol{y}|X,\boldsymbol{\theta}) = \mathcal{N}(\boldsymbol{y}|X\boldsymbol{\theta}, \sigma^2 I_d)$, where $\sigma > 0$ is a hyper-parameter to be tuned, and I_d is a $d \times d$ identity matrix. Moreover, if we assume a spherical Gaussian prior $\boldsymbol{\theta}$, i.e., $p(\boldsymbol{\theta}) = \mathcal{N}(\boldsymbol{\theta}|0, \tau^2 I_d)$, where $\tau > 0$ is another hyper-parameter to be estimated from the data at hand. According to Bayes' theorem, $p(\boldsymbol{\theta}|X,\boldsymbol{y}) \propto p(\boldsymbol{\theta})p(\boldsymbol{y}|X,\boldsymbol{\theta})$, the estimates of the model are made by maximizing the posterior distribution $p(\boldsymbol{\theta}|X,\boldsymbol{y})$, i.e.,

$$\arg\max_{\boldsymbol{\theta}}\log p(\boldsymbol{\theta}|X,\boldsymbol{y}) = \arg\max_{\boldsymbol{\theta}}\log\mathcal{N}(\boldsymbol{y}|X\boldsymbol{\theta}, \sigma^2 I_d) + \log\mathcal{N}(\boldsymbol{\theta}|\mathbf{0}, \tau^2 I_d),$$

which is a maximum-a-posteriori (MAP) estimation of the ridge regression when $\lambda = \sigma^2/\tau^2$. All $\boldsymbol{\theta}$, λ and τ are estimated jointly during the fit of the model, and $\sigma = \tau\sqrt{\lambda}$.

To estimate $I = h(\beta_{\text{eff}}; \boldsymbol{\theta})$, we use scikit-learn[5], which is built on the algorithm described in Tipping (2001) updating the regularization parameters λ and τ according to MacKay (1992).

F RANKING PERFORMANCE ON ALL FIVE DATASETS

Figure F.5: Predictions of the validation accuracy of pre-trained models on all five datasets based on β_{eff} v.s. true test accuracy of these models after fine-tuning for 50 epochs. The Spearman's ranking correlation ρ is used to quantify the performance in model selection. Each shape is associated with one type of pre-trained models. Distinct models of the same type are marked in different colors. To be noted, each includes AlexNet in computing ρs.

G RUNNING TIME ANALYSIS

Figure G.6: Training time per epoch versus computing time for β_{eff} per epoch over all 17 pre-trained models and five datasets discussed in the main text. Each data point is associated with one pre-trained model over one dataset. The relative cost of our approach in computing β_{eff} with respect to training more epochs can be measured by $c = T_{\beta_{\text{eff}}}/T_{\text{train}}$. On average, it is $\bar{c} \approx 1.3$ (slope of the pink line).

Table G.1: Running time (in seconds) in learning curve prediction, including estimation of a predictor (if necessary, e.g., Ours, CL and BGRN).

Dataset	Ours	BGRN	LSV	BSV	CL
CIFAR10	0.491	0.610	0.059	0.049	3966.128
CIFAR100	0.414	0.628	0.051	0.045	5256.478
SVHN	0.506	0.607	0.074	0.044	4690.507
Fashion MNIST	0.493	0.625	0.057	0.046	4552.194
Birds	0.460	0.636	0.071	0.044	4734.992

---

[5] https://scikit-learn.org/stable/modules/generated/sklearn.linear_model.BayesianRidge.html