VectorAdam for Rotation Equivariant Geometry Optimization

Abstract

The rise of geometric problems in machine learning has necessitated the development of equivariant methods, which preserve their output under the action of rotation or some other transformation. At the same time, the Adam optimization algorithm has proven remarkably effective across machine learning and even traditional tasks in geometric optimization. In this work, we observe that naively applying Adam to optimize vector-valued data is *not* rotation equivariant, due to per-coordinate moment updates, and in fact this leads to significant artifacts and biases in practice. We propose to resolve this deficiency with *VectorAdam*, a simple modification which makes Adam rotation-equivariant by accounting for the vector structure of optimization variables. We demonstrate this approach on problems in machine learning and traditional geometric optimization, showing that equivariant VectorAdam resolves the artifacts and biases of traditional Adam when applied to vector-valued data, with equivalent or even improved rates of convergence.

1 Introduction

Over the last decades, gradient-based optimization has enabled rapid progress in machine learning and related fields. To tackle the problems caused by large variance of network weight gradients, researchers have developed adaptive variants of stochastic gradient descent such as Adam [11], which adaptively rescale the step size based on per-scalar gradient statistics to accelerate convergence.

In the field of computer graphics and geometry processing, we also see an increasing use of Adam to optimize geometric energies. For example, the progress in differentiable rendering made derivatives on rendering parameters such as geometry, lighting and texture parameters amenable to these gradient-based optimization techniques. Two recent differentiable rendering works [20, 14] default to Adam for their experiments. Recently, we also see the successful use of a customized Adam algorithm for optimizing geometric interpolation weights [29]. This work taps into this trend and takes a closer look at the use of Adam in geometry machine learning and optimization problems.

Unfortunately, Adam—typically applied to optimize individual network weights—does not account for the vector nature of geometric data and their gradients. In particular, we show that Adam updates depend on the coordinate system chosen to represent vector-valued data, even if the minimized loss function is coordinate invariant, which leads to undesirable artifacts and biases.

We propose *VectorAdam*, a solution that extends Adam's per-scalar operations to vectors. We test VectorAdam on a number of machine learning and geometric optimization problems including geometry and texture optimization through differentiable rendering, adversarial descent, surface parameterization, and Laplacian smoothing. We find that like regular Adam, VectorAdam outperforms traditional first-order gradient descent, yet unlike regular Adam it is provably rotation equivariant.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

2 Related Work

Many techniques have been proposed for gradient-based optimization in machine learning and in numerical computing more broadly (see [26] for a general survey). We will primarily consider *first order* methods, which take as input only the gradient of the objective function with respect to the unknown parameters, and produce as output updated parameters after the optimization step. For large neural networks, loss gradients are often estimated stochastically on a subset of the loss function [23], however optimizers are generally agnostic to how the input gradients are computed. VectorAdam is no exception and works with stochastic samples or full gradients.

Numerical Optimization The most direct approach is to simply update the parameters directly via (stochastic) gradient descent, but this approach can be improved in many respects. In numerical optimization literature, techniques like momentum [18] and line search [21] offer accelerated convergence over basic gradient descent. More advanced techniques such as BFGS [8, 16] and conjugate gradient [10] make higher-order approximations of the objective landscape, while still taking only gradients as input.

Optimization in Machine Learning Machine learning, and in particular the training of deep neural networks, demands optimizers which have low computational overhead, scale to very high dimensional problems, avoid full loss computation, and naturally escape from shallow local minima. Here, many optimizers have been developed following the basic pattern of tracking $O(1)$ additional data associated with each parameter to smooth and rescale gradients to generate updates [6, 31, 28, 11]. All of these methods can be shown to have various strengths, but Adam [11] has emerged as a particularly popular black-box optimizer for machine learning. The crux of our work is to identify a key flaw in Adam when optimizing geometric problems in machine learning and beyond, and to present a simple resolution. We focus primarily on Adam due to its ubiquity and recent relevance in geometric optimization more broadly, but our core insights could be applied to many other gradient-based optimization schemes in much the same way.

Variants of Adam A number of variants have been proposed to improve Adam's performance in training neural networks. For example, NAdam [5] incorporates Nestorov momentum into Adam's formulation to improve rate of convergence, and RAdam [17] introduces a term to rectify the variance of the adaptive learning rate, among many others. Most similar to this work, Zhang et al. [34] (also published as [33]) propose ND-Adam, which preserves the direction of weight vectors during updates to improve generalization. Like our approach, Zhang et al. explicitly leverage the vector structure of optimization variables. However, their approach does so for the sake of generalization and memory savings rather than equivariance, and it produces magnitude-only updates to vectors which are unsuitable for geometric problems where points must move freely through space.

Adam in Geometry Recent work in 3D geometry processing has leveraged Adam to great effect, adjusting the algorithm for the problem domain. Nicolet et al. [19] proposed UniformAdam, which takes the infinity norm of the second momentum term, improving performance for differentiable rendering tasks. Wang et al. [29] customized their own Adam optimizer by resetting the momentum terms regularly in the optimization process, outperforming traditional L-BFGS on a challenging benchmark. This work aims to further this trend of Adam as a general optimization tool by modifying it to have the rotation-equivariance properties which are fundamental to geometric computing.

Rotation Invariance and Equivariance This work contributes to the fruitful study of invariance and equivariance in geometric machine learning [1]. When some transformation is applied to the input, an *invariant* method produces the same output, while an *equivariant* produces equivalently-transformed output. In our context, one expects that if the input to a geometric optimization problem is rotated, the output will be identical up to the same rotation—the optimizer is equivariant. Many novel invariant and equivariant layers, architectures, losses, and regularizers have been developed across geometric machine learning (see [27, 30, 7, 12, 3, 22, 32, 9, 15, 4], among many others). In this work, we argue that *optimizers* deserve the same treatment.

3 Background and Motivation

3.1 Adaptive Moment Estimation (Adam)

Given an objective function f parameterized by θ and its gradient g, the first-order optimization algorithm Adam adaptively rescales gradients of its tth iteration using rolling estimations of first (m) and second moments (v) dictated by the following rules: for each scalar variable θ_i,

$$
\begin{aligned}
g_i &\leftarrow \partial f / \partial \theta_i \\
m_i &\leftarrow \beta_1 m_i + (1 - \beta_1) g_i \\
v_i &\leftarrow \beta_2 v_i + (1 - \beta_2) g_i^2 \\
\theta_i &\leftarrow \theta_i - \alpha \left(\frac{m_i}{1 - \beta_1^t} \right) \Big/ \left(\sqrt{\frac{v_i}{1 - \beta_2^t}} + \epsilon \right)
\end{aligned}
\tag{1}
$$

where $\beta_1, \beta_2, \epsilon$ are Adam's hyperparameter constants[11] and α is the specified learning rate.

Adam's optimization step is invariant to any uniform re-scaling of the gradients' magnitudes. The gradient is adjusted take a value of roughly ± 1, bounding the effective step size by the learning rate α. This makes it particularly suitable for problems with gradients of large variance and unknown scaling, such as neural network optimization.

3.2 Problems in Geometry Optimization

In recent years, we also see an increasing use of Adam in geometry optimization problems such as differentiable rendering [13, 20, 14]. In this problem domain, the target parameters are usually geometric quantities such as vertex positions of a triangle mesh, surface normal vectors, and camera positions. For all of these quantities, the vector form of their gradients encodes important geometric information that are tied to the specific coordinate system in which the problem is embedded.

However, traditional Adam, originally devised for network weight optimization, does not account for the vector nature of gradients in geometry problems. The optimization process is thus not rotation equivariant—a fundamental property expected in practice—and furthermore optimization may be more unstable. Figure 1, shows an example of traditional Adam's component-wise operations creating self-intersections and axis-aligned artifacts, observed in an inverse rendering problem.

Adam   VectorAdam

Figure 1: Geometric optimization results on two sample inputs arising in a differentiable rendering task. Ordinary Adam results in axis-aligned artifacts, which are resolved by using VectorAdam instead.

When we consider gradients vector-wise, regular Adam's uniform re-scaling does not preserve the norm and the direction of the gradients. In most cases, Adam's algorithm re-scales gradient to the magnitude of ± 1, restricting each optimization step within a trust region of the current parameter defined by the size of the learning rate α [11].

This, however, is problematic in a geometry optimization context. When all components of a gradient vector are re-scaled to be of magnitude 1, the gradient vector snaps to the diagonal direction of the coordinate system as shown in Figure 2, changing its original direction.

For example, consider the case where three parameters within θ form a vertex position $[x, y, z]$ in a geometry optimization problem. Denote its corresponding gradient vector $[g_x, g_y, g_z]$. The first Adam step $t = 1$ after m, v are initialized with zeroes is re-written in terms of this vector-valued quantity as

$$
\begin{aligned}
{}[m_x, m_y, m_z] &= (1 - \beta_1)[g_x, g_y, g_z] \\
[v_x, v_y, v_z] &= (1 - \beta_2)[g_x^2, g_y^2, g_z^2]
\end{aligned}
\tag{2}
$$

126 and the step update for this vertex on the first iteration becomes:

$$\Delta[x, y, z] = -\alpha \left[g_x \Big/ \left(\sqrt{g_x^2} + \epsilon \right), \, g_y \Big/ \left(\sqrt{g_y^2} + \epsilon \right), \, g_z \Big/ \left(\sqrt{g_z^2} + \epsilon \right) \right]$$
$$\approx -\alpha \left[\text{sign}(g_x), \text{sign}(g_y), \text{sign}(g_z) \right]. \tag{3}$$

127 That is, for any non-vanishing gradient values, a vertex will be updated along some diagonal of the
128 underlying coordinate system ($-\alpha[1,1,1]$, $-\alpha[-1,1,-1]$, etc.). This effect creates a bias toward the
129 corners of the coordinate system not just on the first iteration, but also throughout the optimization
130 process (see the histograms in Figure 6 for experimental evidence).

131 If a gradient vector indicates how the algorithm should, for example, move a vertex in a 3D coordinate
132 system to reach the optimal shape, the original Adam optimizer thus changes not only the magnitude
133 but also the direction of each step. The optimization process then suffers from the loss of important
134 geometric information encoded by the original gradient vectors' directions.

4   VectorAdam

136 We propose VectorAdam, a first-order rotation-
137 equivariant optimizer for geometry optimiza-
138 tions. It tackles the aforementioned flaw of
139 Adam for geometry optimization, by modify-
140 ing Adam's per-scalar operation to operate on
141 vectors. As shown in Figure 2, our proposed
142 VectorAdam rescales the gradients vector-wise
143 while preserving direction, making the optimiza-
144 tion process rotation equivariant and stable.

Original Gradients   Adam   VectorAdam

Figure 2: Adam's per-scalar adaptive momentum scaling results in uneven vector norm and direction inconsistency when the gradients have vector structures, while our VectorAdam scales the vector norm evenly and preserves the gradient direction.

145 More specifically, we note that the problems discussed above with the original Adam algorithm stem
146 from the per-scalar calculation of the second moment v. VectorAdam modifies the second moment
147 update to be the square of the *vector norm* per gradient vector instead of taking the per-scalar square.
148 The algorithm then proceeds with the regular bias correction and updates the gradients vector-wise
149 with corresponding products of vector first moments and scalar second moments. This has a welcome
150 side-effect of requiring a factor of n less memory for storing moments of n-dimensional vector
151 parameters. Without loss of generality a description of VectorAdam is provided in Algorithm 1
152 assuming all parameters in θ can be arranged as an m-long list of n-dimensional vectors. If the
153 optimization involves quantities of varying vector dimension n, the algorithm can be applied in
154 tandem to each, noting that for the scalar $n = 1$ case VectorAdam reduces to ordinary Adam.

155 Let's reconsider our 3D vertex example above, applied to the first step of optimization after initializing
156 $\vec{m}, v$ to 0. With VectorAdam, the first, zero-initialized iteration reduces to

$$[m_x, m_y, m_z] = (1 - \beta_1)[g_x, g_y, g_z]$$
$$v = (1 - \beta_2) \left\| [g_x, g_y, g_z] \right\|^2 \tag{4}$$

157 The corresponding VectorAdam step update for this vertex becomes

$$\Delta[x, y, z] = -\alpha \left[g_x, g_y, g_z \right] / \left\| [g_x, g_y, g_z] \right\|, \tag{5}$$

158 that is, the unit-length direction of the vertex's gradient scaled by the learning rate α. Thus,
159 VectorAdam preserves the *direction* of the original gradients while roughly normalizing their *magni-*
160 *tude*. This achieves the vector-wise analogue of the original Adam's action on scalar-wise gradients.

Algorithm 1 VectorAdam: minimizing f over m parameters, each an n-dimensional vector.

Require: α: step size
Require: $\beta_1, \beta_2 \in [0, 1)$: Adam's exponential decay rates for the moment estimates
Require: $\epsilon > 0$: Adam's numerical fudge factor
Require: $f(\theta)$: (stochastic) objective function
Require: θ: Initial parameter vector of shape $m \times n$
  $m \leftarrow \mathbb{0}$ (Initialize 1^{st} moment vector of shape $m \times n$)
  $v \leftarrow \mathbb{0}$ (Initialize 2^{nd} moment vector of shape $m \times 1$)
  $t \leftarrow 0$ (Initialize timestep)
  while θ_t not converged **do**
    $t \leftarrow t + 1$
    $g \leftarrow \nabla_\theta f(\theta)$ (Get current gradients of shape $m \times n$)
    for $i \in [1, m]$ **do** (Iterate through each vector quantity in rows of θ)
      $\vec{m}_i \leftarrow \beta_1 \vec{m}_i + (1 - \beta_1)\vec{g}_i$
      $v_i \leftarrow \beta_2 v_i + (1 - \beta_2)\|\vec{g}_i\|_2^2$
      $\hat{\vec{m}}_i \leftarrow \vec{m}_i/(1 - \beta_1^t)$
      $\hat{v}_i \leftarrow v_i/(1 - \beta_2^t)$
      $\vec{\theta}_i \leftarrow \vec{\theta}_i - \alpha \hat{\vec{m}}_i/(\sqrt{\hat{v}_i} + \epsilon)$
    end for
  end while
  return θ

4.1 Properties of VectorAdam

The key property which makes VectorAdam suitable for geometric optimization problem is its rotation equivariance: when the input data is rotated, the output of the optimizer will be identical up to the same rotation, at every step of optimization.

To formalize this property, we consider a function `VectorAdam` which evaluates one update step of Algorithm 1 on a single parameter vector θ with first and second moment terms denoted by $\vec{m}, v$

$$\vec{\theta}, \vec{m}, v \leftarrow \texttt{VectorAdam}_f(\theta, \vec{m}, v) \qquad \vec{\theta} \in \mathbb{R}^n, \vec{m} \in \mathbb{R}^n, v \in \mathbb{R} \tag{6}$$

for some given rotation invariant objective f, and internal optimizer parameters $\alpha, \beta_1, \beta_2, \epsilon$.

Proposition 1 (VectorAdam is rotation equivariant). *For any rotation $R \in SO(n)$, let*

$$\vec{\theta}^*, \vec{m}^*, v^* \leftarrow \textit{VectorAdam}_f(\theta, \vec{m}, v) \quad and \quad \vec{\theta}', \vec{m}', v' \leftarrow \textit{VectorAdam}_f(R\theta, R\vec{m}, v).$$

Then `VectorAdam` satisfies $\vec{\theta}' = R\vec{\theta}^*$, $\vec{m}' = R\vec{m}^*$, and $v' = v^*$. Because each step of `VectorAdam` is equivariant, the parameters $\vec{\theta}$ after any sequence of optimization steps are equivariant as well.

Proof. Since f is rotation invariant, its gradient is rotation equivariant, i.e. $\nabla f(R\theta) = R\nabla f(\theta)$. Substituting in to the update step then shows the equivariance of $\vec{m}$

$$\vec{m}' = \beta_1 R\vec{m} + (1 - \beta_1)R\vec{g} = R(\beta_1\vec{m} + (1 - \beta_1)\vec{g}) = R\vec{m}^* \tag{7}$$

and likewise for the invariance of v

$$v' = \beta_2 v + (1 - \beta_2)\|R\vec{g}\|_2^2 = \beta_2 v + (1 - \beta_2)\|\vec{g}\|_2^2 = v^* \tag{8}$$

and the same trivially holds for their rescaled counterparts $\hat{\vec{m}}' = R\hat{\vec{m}}^*$ and $\hat{v}' = \hat{v}^*$. This then yields the equivariance of $\vec{\theta}$ as

$$\vec{\theta}' = R\vec{\theta} - \alpha\hat{\vec{m}}'/(\sqrt{\hat{v}'} + \epsilon) = R(\vec{\theta} - \alpha\hat{\vec{m}}^*/(\sqrt{\hat{v}^*} + \epsilon)) = R\vec{\theta}^*. \tag{9}$$

Induction on these relations with the base case $\vec{m} = 0$ and $v = 0$ then furthermore implies that the same equivariance holds for any sequence of successive optimization steps by `VectorAdam`.

$\square$

Figure 4: Laplacian regularization on 2D and 3D spherical meshes demonstrates the coordinate system bias of Adam, which changes gradients directions and magnitude breaking the intrinsic symmetry of this problem setup. VectorAdam maintains symmetry.

5 Experiments and Applications

We now compare the performance of Adam and VectorAdam in a range of optimization problems in machine learning and traditional geometric optimization context. These experiments demonstrate the undesirable coordinate-system bias and artifacts caused by Adam's per-coordinate update rules, and show how VectorAdam solves this problem while achieving equivalent or even improved quality and convergence rate. All experiments are performed in PyTorch on an NVIDIA RTX 2080 GPU.

5.1 Geometric Optimization

Vector-valued data are especially common in geometric optimization problems, in which the gradients, also structured by vectors, carry important geometric signals for the problem at hand. We consider Laplacian regularization, adverserial descent, deformation energy optimization, and several inverse rendering tasks, all of which leverage first-order gradient-based optimization. Our VectorAdam yields stable and rotation equivariant optimization, and often arrives at a better result by preserving the geometric signals encoded by the gradient vectors.

Laplacian Regularization   Laplacian regularization on a mesh is widely-used in geometric optimization problems to prevent mesh self-intersections. It is an intrinsic energy term that does not depend on the rotation of the shape. In this experiment, we use both Adam and VectorAdam to directly minimize the Laplacian regularization loss on a mesh. We observe that Adam's per-coordinate moment updates introduces undesirable axis-aligned distortion to the

Figure 3: We optimize for Laplacian smoothing loss on a canonical mesh and a rotated mesh with both Adam and our VectorAdam. The output of ordinary Adam is significantly altered by the rotation, while our VectorAdam yields an identical update up to rotation, as expected.

Laplacian regularization. In Figure 4, Adam's optimization steps shrink the original sphere in 3D, or circle in 2D, to a diamond shape after a few optimization steps, which aligns with the diagonal bias we discussed before. In addition, in Figure 3, we show that Adam's gradient update is not rotation equivariant, resulting in a different updated mesh given a rotated input mesh. In contrast, VectorAdam follows the geometric intuition and shrinks the sphere, or circle, smoothly across the surface in Figure 4 and updates the rotated input mesh identically in Figure 3.

2D ARAP Optimization

Gradient Descent   VectorAdam   Adam

(a) Gradients at first update step

3D Point Cloud Classification Adversarial Optimization

VectorAdam   Adam

(b) 2D gradient direction histogram

Figure 6: On the left, we optimize the ARAP energy for a triangle mesh with 200 vertices for 100 iterations with 1000 randomly rotated initial configurations. (a) shows the gradients at first optimization step from Adam and VectorAdam. (b) shows the histograms of the angular distribution of these 20M gradient directions. Gradient Descent and VectorAdam exhibit their rotation equivariance by presenting a uniform distribution, while Adam presents a biased distribution with spikes at $45°$ angles. On the right in (c), we observe similar coordinate-system bias on a input point cloud, when adverserially optimize inputs to a 3D classifier.

213 **Deformation**   We also experiment with two
214 common deformation energy optimizations in
215 2D. More specifically, we minimize the sym-
216 metric Dirichlet energy and as-rigid-as-possible
217 energy on a deformed 2D mesh given a reference
218 mesh.

219 As-rigid-as-possible energy measures the local
220 stretching and squashing of the triangles given
221 a deformed mesh and a reference mesh [25].
222 We optimize the ARAP energy for a 2D trian-
223 gle mesh and visualize the per-vertex gradient
224 vectors for the first optimization step in the top
225 left panel of Figure 6. Gradient Descent has no
226 coordinate-system bias, but wide range in step
227 scales. If the gradient vector for a particular ver-
228 tex is $[x\,y]$, then the first VectorAdam step will
229 normalize this to $-\alpha\widehat{[x\,y]}$. Accordingly, these

Figure 5: Log loss curves with symmetric Dirichlet energy [24] optimization with rotated inputs. We show that our VectorAdam follow the same descent path as desired while Adam's descent path varies across rotated inputs.

230 uniform-length steps show no coordinate-system bias. Meanwhile, the first step of Adam will take a
231 step of $-\alpha[\text{sign}(x)\,\text{sign}(y)]$, thus exhibiting extreme bias to the $45°$ directions.

232 Symmetric Dirichlet energy is an alternative way of measuring triangle distortions between a deformed
233 mesh and the reference mesh. Similar to the Laplacian regularization, the energy is intrinsic to the
234 mesh, and therefore rotation invariant. We optimize for symmetric Dirichlet energy 16 times with the
235 input mesh rotated by a different angle and plot the loss curves in Figure 5. As shown in the Figure 5,
236 VectorAdam follow the same optimization path regardless of the starting orientation, whereas Adam
237 produces different optimization paths. VectorAdam achieves equivalent convergence rate and final
238 quality as traditional Adam.

Figure 8: For a shading-based inverse reconstruction of the Nefertiti bust, Hausdorff distance between optimized mesh and target mesh across multiple runs with learning rates in the range of [9e-6, 1e-5] shows that VectorAdam consistently outperforms Adam. We observe that qualitatively Adam more often results in tangled surface self-intersections which are difficult to recover from (red), whereas this VectorAdam result does not suffer from this problem.

Adversarial Descent   Similar challenges occur in the context of geometric machine learning. One such example is adversarially optimizing input data to minimize or maximize a classifier's prediction, a process which is vulnerable to Adam's coordinate bias. Here, we trained a point cloud classifier from the rotation-equivariant Vector Neuron architecture [4] on the ModelNet40 dataset [2], and adversarially optimize an input point cloud to minimize the classifcation loss. In figure 6, *right*, Adam's gradient updates exhibit the diagonal bias while VectorAdam preserves the directions.

Inverse Rendering   Research progress in differentiable rendering in recent years has made image-based inverse geometry optimization a popular problem. Within this problem domain, we experiment with shading-based inverse geometry and texture reconstruction. Both of these problems optimize vector-valued parameters, i.e. vertex positions and RGB color vectors.

For geometry reconstruction, we run the same experiments as in [19], which optimize a sphere to match against rendering of a Nerfertiti bust. More specifically, we run the optimization 8 times with different learning rates in the range of 9e-6 and 1e-5, and show the Hausdorff distances between the optimized mesh and the target mesh in Figure 8 during optimization. Quantitatively, VectorAdam's optimized mesh consistently achieves better, i.e. lower, Hausdorff distance with the reference mesh. Qualitatively, we observe more self-intersecting faces in Adam's optimized mesh as highlighted in red.

Figure 7: Log loss curves for environment map reconstruction with Adam and VectorAdam, over 200 runs. The idea of VectorAdam also benefits optimization of non-geometric quantities that have vector structures such as RGB colors.

We note that an Adam variant called UniformAdam was proposed in [19], which also preserves gradient direction by taking the infinity norm of the second moment estimation. However, UniformAdam is not rotation equivariant as the per-coordinate infinity norm changes under rotation. Our VectorAdam can easily be modified in a similar way while preserving the property of rotation equivariance by taking the infinity norm over gradient vector norms in the second moment estimation.

In addition, we also extend our experiment to non-geometric vector-valued data with the problem of texture reconstruction. We run the same texture reconstruction script, as provided by [13], 200 times with different initializations. In Figure 7, we show VectorAdam consistently arrives at better texture result while achieving better convergence rate. This shows that our insight on formulating optimizer by vectors can also benefit other non-geometric problems with vector-valued data. In future work, we are interested in investigating the meaning of rotation in-/equi-variance in color space.

6 Conclusion

Our proposed VectorAdam alleviates the identified coordinate-system dependency flaw of Adam. We proved rotation equivariance of VectorAdam theoretically and demonstrated its implications for popular tasks in machine learning and geometric optimization more broadly.

One limitation of our approach is that it can only be applied to problems where the degrees of freedom are explicitly vector-valued quantities such as positional coordinates. In principle, some neural networks which take geometric coordinates as input likely suffer from similar coordinate-dependence bias under the traditional Adam optimizer, but it is not yet clear how to apply our observations to the setting of optimizing these networks' weights. Additionally, the theoretical underpinnings for Adam have primarily been investigated in the stochastic optimization case; some of the direct geometric tasks considered here would benefit from more analysis to understand why Adam and VectorAdam prove so effective. In this work, we have focused on rotations and low-dimensional problems in geometry processing. In future work, we are further interested in investigating invariances and equivariances to other transformation groups and high-dimensional vector or tensor spaces.

We hope that our attention to rotation equivariance for *optimizers* encourages further development of coordinate-free geometric optimization within the evolving machinery of continuous optimization and deep learning.

References

[1] Michael M Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *arXiv preprint arXiv:2104.13478*, 2021.

[2] Angel X Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.

[3] Chao Chen, Guanbin Li, Ruijia Xu, Tianshui Chen, Meng Wang, and Liang Lin. Clusternet: Deep hierarchical cluster network with rigorously rotation-invariant representation for point cloud analysis. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4994–5002, 2019.

[4] Congyue Deng, Or Litany, Yueqi Duan, Adrien Poulenard, Andrea Tagliasacchi, and Leonidas Guibas. Vector Neurons: A General Framework for SO(3)-Equivariant Networks. *arXiv:2104.12229 [cs]*, April 2021. arXiv: 2104.12229.

[5] Timothy Dozat. Incorporating nesterov momentum into adam. 2016.

[6] John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(7), 2011.

[7] Carlos Esteves, Christine Allen-Blanchette, Ameesh Makadia, and Kostas Daniilidis. Learning so (3) equivariant representations with spherical cnns. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 52–68, 2018.

[8] Roger Fletcher. Practical methods of optimization, 1987. *John and Sons, Chichester*, 1987.

[9] Fabian Fuchs, Daniel Worrall, Volker Fischer, and Max Welling. Se (3)-transformers: 3d roto-translation equivariant attention networks. *Advances in Neural Information Processing Systems*, 33:1970–1981, 2020.

[10] Magnus R Hestenes and Eduard Stiefel. Methods of conjugate gradients for solving. *Journal of research of the National Bureau of Standards*, 49(6):409, 1952.

[11] Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. *arXiv:1412.6980 [cs]*, January 2017. arXiv: 1412.6980.

[12] Risi Kondor, Zhen Lin, and Shubhendu Trivedi. Clebsch–gordan nets: a fully fourier space spherical convolutional neural network. *Advances in Neural Information Processing Systems*, 31, 2018.

[13] Samuli Laine, Janne Hellsten, Tero Karras, Yeongho Seol, Jaakko Lehtinen, and Timo Aila. Modular primitives for high-performance differentiable rendering. *ACM Transactions on Graphics*, 39(6):1–14, November 2020.

[14] Tzu-Mao Li, Miika Aittala, Frédo Durand, and Jaakko Lehtinen. Differentiable monte carlo ray tracing through edge sampling. *ACM Transactions on Graphics (TOG)*, 37(6):1–11, 2018.

[15] Xianzhi Li, Ruihui Li, Guangyong Chen, Chi-Wing Fu, Daniel Cohen-Or, and Pheng-Ann Heng. A rotation-invariant framework for deep point cloud analysis. *IEEE Transactions on Visualization and Computer Graphics*, 2021.

[16] Dong C Liu and Jorge Nocedal. On the limited memory bfgs method for large scale optimization. *Mathematical programming*, 45(1):503–528, 1989.

[17] Liyuan Liu, Haoming Jiang, Pengcheng He, Weizhu Chen, Xiaodong Liu, Jianfeng Gao, and Jiawei Han. On the variance of the adaptive learning rate and beyond. *arXiv preprint arXiv:1908.03265*, 2019.

[18] Yurii E Nesterov. A method for solving the convex programming problem with convergence rate $O(1/k^2)$. In *Dokl. akad. nauk Sssr*, volume 269, pages 543–547, 1983.

[19] Baptiste Nicolet, Alec Jacobson, and Wenzel Jakob. Large steps in inverse rendering of geometry. *ACM Transactions on Graphics*, 40(6):1–13, December 2021.

[20] Merlin Nimier-David, Delio Vicini, Tizian Zeltner, and Wenzel Jakob. Mitsuba 2: A retargetable forward and inverse renderer. *ACM Transactions on Graphics (TOG)*, 38(6):1–17, 2019.

[21] Jorge Nocedal and Stephen J Wright. *Numerical optimization*. Springer, 1999.

[22] Adrien Poulenard, Marie-Julie Rakotosaona, Yann Ponty, and Maks Ovsjanikov. Effective rotation-invariant point cnn with spherical harmonics kernels. In *2019 International Conference on 3D Vision (3DV)*, pages 47–56. IEEE, 2019.

[23] Herbert Robbins and Sutton Monro. A stochastic approximation method. *The annals of mathematical statistics*, pages 400–407, 1951.

[24] Jason Smith and Scott Schaefer. Bijective parameterization with free boundaries. *ACM Transactions on Graphics (TOG)*, 34(4):1–9, 2015.

[25] Olga Sorkine and Marc Alexa. As-rigid-as-possible surface modeling. In *Symposium on Geometry processing*, volume 4, pages 109–116, 2007.

[26] Shiliang Sun, Zehui Cao, Han Zhu, and Jing Zhao. A survey of optimization methods from a machine learning perspective. *IEEE transactions on cybernetics*, 50(8):3668–3681, 2019.

[27] Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

[28] Tijmen Tieleman and G Hinton. Divide the gradient by a running average of its recent magnitude. coursera neural netw. *Mach. Learn*, 6:26–31, 2012.

[29] Yu Wang and Justin Solomon. Fast quasi-harmonic weights for geometric data interpolation. *ACM Transactions on Graphics (TOG)*, 40(4):1–15, 2021.

[30] Maurice Weiler, Mario Geiger, Max Welling, Wouter Boomsma, and Taco S Cohen. 3d steerable cnns: Learning rotationally equivariant features in volumetric data. *Advances in Neural Information Processing Systems*, 31, 2018.

[31] Matthew D Zeiler. Adadelta: an adaptive learning rate method. *arXiv preprint arXiv:1212.5701*, 2012.

[32] Zhiyuan Zhang, Binh-Son Hua, David W Rosen, and Sai-Kit Yeung. Rotation invariant convolutions for 3d point clouds deep learning. In *2019 International Conference on 3D Vision (3DV)*, pages 204–213. IEEE, 2019.

[33] Zijun Zhang. Improved Adam Optimizer for Deep Neural Networks. In *2018 IEEE/ACM 26th International Symposium on Quality of Service (IWQoS)*, pages 1–2, June 2018. ISSN: 1548-615X.

[34] Zijun Zhang, Lin Ma, Zongpeng Li, and Chuan Wu. Normalized direction-preserving adam. *arXiv preprint arXiv:1709.04546*, 2017.