Faster proximal algorithms for matrix optimization using Jacobi-based eigenvalue methods

Abstract

We consider proximal splitting algorithms for convex optimization problems over matrices. A significant computational bottleneck in many of these algorithms is the need to compute a full eigenvalue or singular value decomposition at each iteration for the evaluation of a proximal operator.

In this paper we propose to use an old and surprisingly simple method due to Jacobi to compute these eigenvalue and singular value decompositions, and we demonstrate that it can lead to substantial gains in terms of computation time compared to standard approaches. We rely on three essential properties of this method: (a) its ability to exploit an approximate decomposition as an initial point, which in the case of iterative optimization algorithms can be obtained from the previous iterate; (b) its parallel nature which makes it a great fit for hardware accelerators such as GPUs, now common in machine learning, and (c) its simple termination criterion which allows us to trade-off accuracy with computation time. We demonstrate the efficacy of this approach on a variety of algorithms and problems, and show that, on a GPU, we can obtain 5 to 20x speed-ups in the evaluation of proximal operators compared to standard CPU or GPU linear algebra routines. Our findings are supported by new theoretical results providing guarantees on the approximation quality of proximal operators obtained using approximate eigenvalue or singular value decompositions.

1   Introduction

Many problems in statistics and learning can be formulated as convex optimization over matrices. This includes kernel learning [LCB+04], low-rank matrix recovery [RFP10, CR09], sparse covariance selection [BGdN06, FHT08], community detection [BBV16], and many others. Proximal splitting algorithms such as (accelerated) proximal gradient methods [Nes03, BT09], or the alternating direction method of multipliers (ADMM) [EB92, BPC11], are among the most popular methods to deal with large-scale instances of such problems. These methods solve generic convex optimization problems of the form

$$\min_{X \in E} \ F(X) + G(X) \tag{1}$$

via calls to the *proximal operators* of F and/or G. When the variable X is a symmetric or rectangular matrix, it is often the case that the functions F and/or G are symmetric functions of the eigenvalues or singular values of X; i.e., so-called *spectral or othogonally-invariant functions*. Typical examples are $F(X) = I(X \succeq 0) = \sum_{i=1}^{n} I(\lambda_i(X) \geq 0)$ the convex indicator function for the positive semidefinite cone, or $F(X) = \|X\|_* = \sum_{i=1}^{n} \sigma_i(X)$ the nuclear norm.

Computing the proximal operator of such spectral functions F requires a full eigenvalue/singular value decomposition which contributes a large computational cost of at least n^3 floating-point

operations per iteration. The most common algorithms for such decompositions are the QR method, and the divide-and-conquer algorithm [GVL13] which are implemented in linear algebra packages (LAPACK) that are used in standard numerical computing software such as MATLAB or NumPy.

Contributions In this paper we propose to use a simple and lesser known method due to Jacobi from 1846 [Jac46] for the computation of these decompositions. Several features of this method make it suitable for its use within iterative proximal methods:

    (i) It can effectively exploit an initial approximate decomposition of the target matrix. In iterative proximal methods, the eigenvectors/singular vectors from the previous iterate are often a very good initial point that almost diagonalize the matrix of the current iterate.

    (ii) The method can be very easily parallelized, and is a very good fit for parallel hardware accelerators, notably GPUs, which are now very common in machine learning.

    (iii) It has a simple termination criterion that allows us to trade-off computation time with the accuracy of the desired decomposition.

The present paper has two main contributions. First, we establish new theoretical results providing guarantees on the approximation quality of the proximal operator of a convex spectral function when computed with an approximate eigenvalue/singular value decomposition. When combined with existing results on the convergence of proximal splitting methods with inexact proximal oracles, we are able to appropriately set the tolerance of Jacobi-based methods and gain computation time, while guaranteeing global convergence of the optimization method. Second, we demonstrate using the observations above, and on a variety of problems and splitting algorithms, that the method of Jacobi on a GPU can yield speed-ups of 5-20x in the evaluation of proximal operators of spectral functions, compared to standard approaches on CPU and GPU.

Related work The papers [CV18] and [JV21] consider proximal splitting algorithms with a generalized Bregman divergence (i.e., different than the squared Euclidean distance), and show that these proximal operators can sometimes be evaluated without explicitly computing a full eigenvalue decomposition. If ϕ is a strongly-convex function, the ϕ-proximal operator of F is defined by

$$\mathrm{prox}_F^\phi(y; a) = \mathrm{argmin}_x \left\{ F(x) + \langle a, x \rangle + \phi(x) - \langle \nabla \phi(y), x \rangle \right\}.$$

The paper [CV18] considers optimization problems over symmetric positive semidefinite Toeplitz matrices and shows that by choosing ϕ to be the kernel for the so-called Itakura-Saito distance one can compute the generalized proximal operator in $O(n^2)$ time, instead of $O(n^3)$. In [JV21] it is shown that for sparse semidefinite programs, an adequate choice of ϕ leads to a proximal operator that can be computed at the cost of a Cholesky decomposition of a sparse matrix which in general is much smaller than the cost of a full eigenvalue decomposition. Concerning sparse semidefinite programs, there has been a lot of work on devising fast ADMM algorithms using the clique decomposition method [FKMN01], e.g., [ZFP+20, MKL15]. We note that these contributions are specific to sparse semidefinite programs and are complementary to the present paper because they still require an eigenvalue decomposition to be computed at each iteration, which can be done via Jacobi-based methods. Finally let us mention that there are first-order methods that do not require a full eigenvalue decomposition at each iteration but only the computation of the smallest eigenvalue(s)/eigenvector(s) at each iteration such as e.g., [HR00, Ren14, YTF+21] and for which Lanczos methods are more suited.

Organization In Section 2 we recall some necessary background material about convex spectral functions and their proximal operators. In Section 3 we present the Jacobi method to diagonalize symmetric matrices, and explain how it can be used with proximal algorithms. In Section 4 we show that approximate eigenvalue/singular value decompositions yield guaranteed approximations of proximal operators for spectral functions. Finally we illustrate the approach presented in this paper with numerical experiments in Section 5.

2 Background

In this section we present some notations and background results concerning spectral functions. If $f : E \to \mathbb{R}$ is a convex function on Euclidean space E we let $\partial f(x)$ be the subdifferential of

84 f at x, namely $\partial f(x) = \{g \in E : f(y) \geq f(x) + \langle g, y - x \rangle\}$. An element $g \in \partial f(x)$ is called a
85 subgradient of f at x. The *proximal operator* of f at y is defined as

$$\text{prox}_f(y) = \text{argmin}_{x \in E} \left\{ f(x) + (1/2)\|x - y\|^2 \right\}.$$

86 We let $\mathbf{S}^n$ be the Euclidean space of $n \times n$ symmetric matrices with the trace inner product $\langle X, Y \rangle =$
87 $\text{tr}(XY)$. We let $\mathbf{S}^n_+$ (resp. $\mathbf{S}^n_{++}$) be the cone of positive semidefinite (resp. definite) matrices in $\mathbf{S}^n$.
88 Also $O(n)$ denotes the set of $n \times n$ orthogonal matrices.

Spectral functions   A function $F : \mathbf{S}^n \to \mathbb{R}$ of symmetric matrices is called *spectral* if there
90 is a permutation-invariant function $f : \mathbb{R}^n \to \mathbb{R}$ such that $F(X) = f(\lambda(X))$ where $\lambda(X) =$
91 $(\lambda_1(X), \ldots, \lambda_n(X))$ is the vector of eigenvalues of X (in any order). It is clear that spectral
92 functions are orthogonally-invariant, i.e., $F(U^T X U) = F(X)$, because $U^T X U$ and X have the
93 same eigenvalues; conversely any orthogonally-invariant function F is the spectral function associated
94 to the permutation-invariant function $f(x) = F(\text{diag}(x))$. The main remarkable fact that we will use
95 about spectral functions is a result due to Davis [Dav57], which asserts that F is convex as soon as f
96 is, and gives a variational formula for F certifying this convexity.

97 **Theorem 1** ([Dav57], see also [BTN01, p.282, claim D]). *Let $f : \mathbb{R}^n \to \mathbb{R}$ be a permutation-*
98 *invariant function, and let $F : \mathbf{S}^n \to \mathbb{R}$, $F(X) = f(\lambda(X))$ be the associated spectral function. If f*
99 *is convex on $\mathbb{R}^n$, then F is convex on $\mathbf{S}^n$, and we have the following variational formulation for F:*

$$F(X) = \max_{U \in O(n)} f(\text{diag}(U^T X U)). \tag{2}$$

100 An important, and well-known consequence of the theorem above, is that the proximal operator of F
101 can be obtained from that of f, namely for any $Y \in \mathbf{S}^n$ we have

$$\text{prox}_F(Y) = U \text{diag}(\text{prox}_f(y)) U^T$$

102 where $Y = U \text{diag}(y) U^T$ is an eigenvalue decomposition of Y.

103 **Functions of singular values**   Similar results hold for functions $F : \mathbb{R}^{m \times n} \to \mathbb{R}$ of rectangular
104 matrices that are orthogonally-invariant, i.e., $F(UXV) = F(X)$ for all $U \in O(m)$ and $V \in O(n)$.
105 Any such function can be written as $F(X) = f(\sigma(X))$ where $\sigma(X) \in \mathbb{R}^{\min(m,n)}$ is the vector of
106 singular values and $f : \mathbb{R}^{\min(m,n)} \to \mathbb{R}$ is an *absolutely symmetric* function, i.e., it is invariant under
107 *signed permutations*: $f(\eta_1 x_{\pi(1)}, \ldots, \eta_k x_{\pi(k)}) = f(x_1, \ldots, x_k)$ for $\eta_i = \pm 1$ and π a permutation of
108 $\{1, \ldots, k\}$ where $k = \min(m, n)$ [Lew95]. In this case too, it holds that F is convex as soon as f is,
109 and we have:

$$F(X) = \max_{U \in O(m), V \in O(n)} f(\text{diag}(U^T X V)). \tag{3}$$

110 The variational formulas (2) and (3) are a consequence of well-known results concerning majorization
111 relations between the diagonal of a matrix and its eigenvalues or singular values [MOA79, Chapter 9].
112 For completeness we have included a proof of these formulas in the supplementary material. We refer
113 the reader to [PB14, Section 6.7] and references therein for more details on the proximal operator of
114 spectral and orthogonally-invariant functions.

3   Jacobi-based methods for eigenvalue and singular value decompositions

116 In this section we present Jacobi-based methods to compute eigenvalue and singular value decompo-
117 sitions, and explain how they can be used in proximal optimization algorithms. For concreteness we
118 will focus on the eigenvalue decomposition of symmetric matrices, but as will be clear, the extension
119 to the SVD of rectangular matrices will be straightforward.

3.1   The method

121 Jacobi eigenvalue methods compute the eigenvalue decomposition of a real symmetric matrix by
122 iteratively eliminating off-diagonal elements using *Givens rotations*. More precisely, let A be a
123 $n \times n$ real symmetric matrix that we want to diagonalize. The Jacobi method begins by selecting
124 an off-diagonal index (i, j), with $i < j$, such that $|A_{ij}| > 0$, and constructs a 2×2 rotation matrix

125 $\begin{bmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{bmatrix}$ that diagonalizes the 2×2 submatrix $\begin{bmatrix} A_{ii} & A_{ij} \\ A_{ij} & A_{jj} \end{bmatrix}$. The rotation matrix can be embedded

126 in a larger $n \times n$ Givens rotation matrix at indices (i, j) which is otherwise equal to the identity

127 matrix:

$$\begin{cases} G_{ii} = G_{jj} = \cos\theta \\ G_{ij} = \sin\theta, G_{ji} = -\sin\theta \end{cases} \quad \text{and} \quad G_{pq} = \delta_{p,q} \quad \text{for } p \notin \{i, j\} \text{ or } q \notin \{i, j\},$$

128 where $\delta_{p,q} = 1$ if $p = q$ and 0 otherwise. This Givens rotation matrix satisfies $(GAG^T)_{ij} = 0$.

129 The Jacobi algorithm then proceeds by updating $A \leftarrow GAG^T$ and performs the same process until

130 a convergence criterion is satisfied. Usually the convergence criterion is given in terms of $\text{off}(A)$,

131 defined to be the square root of the sum of the off-diagonal elements of A:

$$\text{off}(A) := \sqrt{\sum_{1 \leq i \neq j \leq n} A_{ij}^2}. \tag{4}$$

The algorithm can thus be summarized as follows:

Algorithm 1: Jacobi method for diagonalizing symmetric matrix A

---

while *off$(A) \geq$ tolerance* **do**

    choose an off-diagonal index (i, j) such that $|A_{ij}| > 0$

    construct a Givens matrix G such that $(GAG^T)_{ij} = 0$

    update $A \leftarrow GAG^T$

end

132

133 In the classical Jacobi method, the off-diagonal entry (i, j) selected at each iteration is the one for

134 which $|A_{ij}|$ is largest. It can be easily shown that with this choice, the quantity $\text{off}(A)$ satisfies after

135 one iteration

$$\text{off}(GAG^T)^2 \leq (1 - 1/N) \, \text{off}(A)^2$$

136 where $N = n(n-1)/2$. As such $\text{off}(A)$ converges linearly to 0. It has been shown by Schönhage,

137 and van Kempen [Sch64, VK66a] that the method actually attains quadratic convergence locally.

138 **Cyclic method**   The classical Jacobi method requires searching for a largest element among the

139 off-diagonal elements at each iteration. For an $n \times n$ matrix the cost of this step is $\mathcal{O}(n^2)$ flops. Cyclic

140 Jacobi methods instead cycle through all off-diagonal elements of the matrix in some fixed order,

141 computing the associated Givens matrices and updating accordingly. The algorithm proceeds by

142 *sweeps*, where in each sweep each off-diagonal entry is processed exactly once. Various convergence

143 results have been proved for cyclic methods most notably local quadratic convergence, see e.g.,

144 [FH60, Wil62, VK66b]. In practice, the number of sweeps needed to diagonalize a matrix of size

145 $n \lesssim 1000$ is usually no more than 15.

146 **Parallelization**   The cyclic Jacobi method can be easily parallelized. Indeed, instead of eliminating

147 a single off-diagonal entry at each iteration, one can eliminate in parallel $\lfloor n/2 \rfloor$ off-diagonal entries

148 that correspond to distinct rows/columns. More precisely by selecting indices $(i_1, j_1), \ldots, (i_m, j_m)$

149 where $m = \lfloor n/2 \rfloor$ such that $i_1, j_1, i_2, j_2, \ldots, i_m, j_m$ are all distinct one can compute in parallel

150 the m Givens rotations that are needed to eliminate the entries $A_{i_1 j_1}, \ldots, A_{i_m j_m}$. A single sweep

151 can then be performed in $n - 1$ steps where at each step $k = 1, \ldots, n - 1$ one chooses indices

152 $(i_1[k], j_1[k]), \ldots, (i_m[k], j_m[k])$ that are pairwise distinct in such a way that all the off-diagonal

153 entries are processed at least once. For more details on the choice of these indices we refer the reader

154 to [GVL13, Section 8.5].

155 **Other eigenvalue algorithms**   In general, the Jacobi method is not competitive with more tradi-

156 tional eigenvalue algorithms such as the QR method or the divide-and-conquer method. Count-

157 ing floating point operations only, the QR method is roughly equivalent to two sweeps of Jacobi

158 [GVL13, TBI97]. One important difference between the Jacobi method and QR/divide-and-conquer

159 algorithms is that the latter start by putting the matrix A into tridiagonal form by a sequence of

160 orthogonal (Householder) transformations, whereas the Jacobi method operates on A directly. One

consequence of this is that the Jacobi method can have faster convergence if $\text{off}(A)$ is small, whereas this is not the case of other algorithms that start by a reduction into tridiagonal form. This ability to exploit an approximate diagonalization of A is what makes the Jacobi method particularly interesting for iterative optimization algorithms.

Singular value decomposition   The Jacobi algorithm can be very easily adapted to compute the singular value decomposition of rectangular matrices. The idea is to solve a sequence of 2×2 SVD problems, instead of 2×2 symmetric eigenvalue problems. This leads to the two-sided Jacobi SVD algorithm. Another approach, called the one-sided Jacobi SVD algorithm, performs orthogonal transformations on the right to make the columns of A orthogonal, by iteratively orthogonalizing pairs of columns. From there, one can extract the singular values as the Euclidean norms of the columns of A, and the left singular vector matrix easily. We refer the reader to [GVL13, Section 8.6.4] for more details and references.

3.2   Jacobi-based methods in proximal algorithms

We now explain how the Jacobi method can be used in iterative optimization algorithms for the computation of proximal operators of spectral functions. The main idea is to use the eigenvector matrix from the previous iteration as a warm-start for the current iterate. More precisely, assume that at iteration k one needs to compute the proximal operator $\text{prox}_F(Y_k)$ where $F : \mathbf{S}^n \to \mathbb{R}$ is the spectral function associated to the permutation-invariant function $f : \mathbb{R}^n \to \mathbb{R}$. We proceed as follows:

- Let U_{k-1} be the orthogonal eigenvector matrix computed at iterate $k-1$
- Apply the Jacobi method to $U_{k-1}^T Y_k U_{k-1}$ with tolerance ϵ_k. This returns an orthogonal matrix W such that
$$\text{off}(W^T U_{k-1}^T Y_k U_{k-1} W) \le \epsilon_k$$
- Set $U_k = U_{k-1} W$ (eigenvector matrix of Y_k) and $y_k = \text{diag}(U_k^T Y_k U_k)$ (eigenvalues of Y_k)
- Output $U_k \, \text{diag}(\text{prox}_f(y_k)) U_k^T$ as the proximal operator $\text{prox}_F(Y_k)$.

As we demonstrate in the numerical experiments section below, a very small number of sweeps (often just one, and sometimes none) are in general needed to converge to the eigenvalue decomposition of Y_k in the second step above, because the matrix $U_{k-1}^T Y_k U_{k-1}$ is usually very close to being diagonal, especially after the first few iterations of the optimization algorithm.

It is straightforward to extend the warm-start approach described here to the situation where we want to compute singular value decompositions, and we omit the details for brevity.

Remark 1. *When numerically implementing the procedure above, we noticed that accumulation of errors can cause the columns of U_k not to be normalized after a large number of iterations. We found that a simple rescaling of its columns fixes this issue.*

4   Approximate proximal evaluation

Most proximal algorithms (e.g., ADMM, proximal gradient method, ...) are still convergent even if only an approximation of the proximal operator is computed at each iteration, provided the approximation quality suitably decays to zero, see e.g., [EB92, SRB11, Yao16, BTB20]. A natural question is to understand how the tolerance parameter of the Jacobi method ϵ_k affects the approximation quality of the proximal operator $\text{prox}_F(Y_k)$? This section addresses this question.

Measures of quality of prox   There are multiple ways to quantify the approximation quality of a proximal operator, see e.g., [BTB20] which compiles a list of different ways that were considered in the literature. In this section we will focus on two simple notions that have been used in convergence guarantees for proximal splitting methods. Let $F : E \to \mathbb{R}$ be a convex function for which we want to compute the prox at a point $Y \in E$. Let
$$\Phi(X; Y) = F(X) + (1/2)\|X - Y\|_F^2$$
be the prox objective so that $\text{prox}_F(Y) = \text{argmin}_{X \in E} \Phi(X; Y)$. If $\hat{X} \in E$ is a candidate value for $\text{prox}_F(Y)$ the two measures of approximations we consider are: (i) Euclidean distance to

the true prox, i.e., $\delta = \|\hat{X} - \mathrm{prox}_F(Y)\|_F$ and (ii) suboptimality in prox objective value, i.e., $\eta = \Phi(\hat{X}; Y) - \Phi(\mathrm{prox}_F(Y); Y)$. The former notion was used e.g., to guarantee convergence of ADMM algorithms, assuming that the sequence of errors (δ_k) is summable [EB92, Yao16]; and the latter was used in [SRB11] to guarantee convergence of (fast) proximal gradient methods, under a decaying assumption on (η_k).

Remark 2. *Note that since Φ is 1-strongly convex we always have the inequality:*

$$\Phi(\hat{X}; Y) - \Phi(\mathrm{prox}_F(Y); Y) \geq \frac{1}{2}\|\hat{X} - \mathrm{prox}_F(Y)\|^2. \tag{5}$$

This means that any bound on the approximation quality in terms of prox objective value, implies a bound on the approximation quality using the Euclidean norm.

Approximate prox using approximate eigenvalue/singular decomposition Our main result gives bounds on the quality of the prox of any convex spectral function computed using an approximate eigenvalue decomopsition. More precisely, assume that $F : \mathbf{S}^n \to \mathbb{R}$ is a convex spectral function of symmetric matrices associated to the permutation-invariant function $f(x_1, \ldots, x_n)$. Let $Y \in \mathbf{S}^n$ for which we want to compute $\mathrm{prox}_F(Y)$. We know that $\mathrm{prox}_F(Y) = U\,\mathrm{prox}_f(y)U^T$ where $y = (y_1, \ldots, y_n)$ is the vector of eigenvalues of Y, and U is the orthogonal matrix that diagonalizes Y. Assume that $\hat{U}$ is an orthogonal matrix such that $\mathrm{off}(\hat{U}^T Y \hat{U}) \leq \epsilon$, i.e.,

$$\hat{U}^T Y \hat{U} = \mathrm{diag}(\hat{y}) + E \quad \text{where} \quad \begin{cases} \|E\|_F \leq \epsilon \\ E_{ii} = 0 \text{ for } i = 1, \ldots, n. \end{cases} \tag{6}$$

Our main theoretical result, stated below, quantifies the error in the approximation $\hat{X} \approx \mathrm{prox}_F(Y)$ where

$$\hat{X} = \hat{U}\,\mathrm{diag}(\mathrm{prox}_f(\hat{y}))\hat{U}^T. \tag{7}$$

Theorem 2. *Under the assumptions above, we have:*
(i) $\|\hat{X} - \mathrm{prox}_F(Y)\|_F \leq \epsilon$; and
(ii) $\Phi(\hat{X}; Y) - \Phi(\mathrm{prox}_F(Y); Y) \leq \epsilon^2/2$.

A similar result can be stated for orthogonally-invariant functions of rectangular matrices.

Theorem 3. *Let $F : \mathbb{R}^{m \times n} \to \mathbb{R}$ be a convex orthogonally-invariant function associated with the absolutely-symmetric function $f(x) = F(\mathrm{diag}(x))$ defined on $\mathbb{R}^{\min(m,n)}$. Let $Y \in \mathbb{R}^{m \times n}$, and assume that $\hat{U} \in O(m)$ and $V \in O(n)$ are orthogonal matrices such that*

$$\hat{U}^T Y \hat{V} = \mathrm{diag}(\hat{y}) + E \quad \text{where} \quad \begin{cases} \|E\|_F \leq \epsilon \\ E_{ii} = 0 \text{ for } i = 1, \ldots, \min(m,n). \end{cases}$$

Then, with $\hat{X} = \hat{U}\,\mathrm{diag}(\mathrm{prox}_f(\hat{y}))\hat{V}^T$, the following holds:
(i) $\|\hat{X} - \mathrm{prox}_F(Y)\|_F \leq \epsilon$, and
(ii) $\Phi(\hat{X}; Y) - \Phi(\mathrm{prox}_F(Y); Y) \leq \epsilon^2/2$.

The proofs of both theorems are in the supplementary material. Some remarks are in order:

- Inequality (i) generalizes the main result in [GNR20].[1] The main result in [GNR20] shows that when F is the indicator function of the positive semidefinite cone (so that prox_F is the Euclidean projection on $\mathbf{S}_+^n$) then $\|\hat{X} - \mathrm{prox}_F(Y)\|_F \leq \sqrt{2}\epsilon$. Our result significantly generalizes the latter to the proximal operator of arbitrary convex spectral functions F.

- Note that inequality (i) actually follows from (ii) by (5).

Implications If we combine our result with [EB92] and [SRB11] we get guarantees on the convergence rates of ADMM and (fast) proximal gradient methods, when the proximal operator are evaluated using Jacobi-based methods. To illustrate this, consider for instance the following optimization over symmetric matrices

$$\min_{X \in \mathbf{S}^n} F(X) + G(X) \tag{8}$$

---

[1]We note that the proof of inequality (i) does not actually use the assumption that $E_{ii} = 0$ for $i = 1, \ldots, n$.

where $F(X)$ is a convex spectral function and $G(X)$ is convex and smooth with L-Lipschitz gradient. Consider the (accelerated) proximal gradient method

$$X_{k+1} = \text{prox}_{L^{-1}F}(Z - (1/L)\nabla G(Z)) \tag{9}$$

where $Z = X_k$ for the standard proximal gradient method, and $Z = X_k + \frac{k-1}{k+2}(X_k - X_{k-1})$ for the accelerated version. Assume that the proximal operator in (9) is evaluated approximately according to (6)-(7) with accuracy ϵ_k. Then, using [SRB11, Props. 1 and 2] and Theorem 2(ii), we immediately get: (a) if (ϵ_k) is summable (e.g., $\epsilon_k = O(1/k^{1+\delta})$) then the (basic) proximal gradient method converges at a rate $O(1/k)$ to the optimal value of (8); and (b) if $(k\epsilon_k)$ is summable (e.g., $\epsilon_k = O(1/k^{2+\delta})$) then the accelerated proximal gradient method converges at a rate $O(1/k^2)$ to the optimal value of (8). For the ADMM algorithm, we can combine the result of [EB92, Theorem 8] with Theorem 2(i) to guarantee convergence when (ϵ_k) is summable.

5 Numerical experiments

In this section we present numerical experiments with Jacobi-based methods on different problems and splitting algorithms. We use the parallel version of the Jacobi method implemented on GPU, and available through the NVIDIA CUSOLVER library [NVI20] in the functions `syevj` and `gesvdj` for symmetric eigenvalue decomposition and singular value decomposition respectively. We compare it with the standard functions on both CPU/GPU implemented in LAPACK/CUSOLVER's functions `syevd` and `gesvd`. All our code is in Python and the latter functions are invoked respectively by NumPy's [HMvdW+20] and CuPy's [OUN+17] functions `linalg.eigh` and `linalg.svd`. All the code needed to run the experiments is available in the supplementary material.

The GPU we used is a NVIDIA TITAN Xp with CUDA 11.0, and the CPU is an Intel Core i5-6500 with 4 cores at 3.20 GHz and 32GB RAM, running Ubuntu 18.04. For GPU computations (default eigenvalue solver and Jacobi's method) we use 32-bit floats, instead of 64-bit doubles, which are much faster on GPU. On the examples we have tried this had little or no effect on the quality of the solutions, especially because we are looking at problems where moderate accuracy is satisfactory.

Before showing the results on optimization problems, we first compare in Table 1 the time needed for a single Jacobi sweep vs. the time needed for a full eigenvalue (resp. singular value) decomposition using NumPy/CuPy's `linalg.eigh` (resp. `linalg.svd`), on a random Gaussian $n \times n$ matrix. For symmetric eigenvalue decompositions, we note that for matrices of size ~ 500, one sweep of Jacobi is about 10x faster than the default methods. For singular value decomposition the ratio is more pronounced and attains 40x for matrices of size ~ 2000.

	Symmetric eigenvalue decomposition			*Singular value decomposition*		
n	default (CPU)	default (GPU)	**jacobi-1sw (GPU)**	default (CPU)	default (GPU)	**jacobi-1sw (GPU)**
128	2.18	5.91	**0.83**	3.75	12.23	**1.14**
256	6.86	12.72	**1.43**	12.93	39.93	**1.85**
512	26.24	31.78	**3.29**	62.46	107.47	**3.99**
1024	152.44	63.28	**11.45**	385.59	476.22	**15.17**
2048	1180.78	163.62	**59.94**	3453.76	3,223.60	**77.18**

Table 1: Times, in milliseconds, for one sweep of the Jacobi method on a GPU vs. full eigenvalue/singular-value decomposition using the default method on CPU/GPU.

5.1 Sparse inverse covariance selection

We consider here the well-known statistical problem of estimating an unknown covariance matrix $\Sigma \in \mathbf{S}_{++}^n$ from samples $x_1, \ldots, x_N \in \mathbb{R}^n$ of a Gaussian distribution $\mathcal{N}(0, \Sigma)$, under the assumption that Σ^{-1} is sparse. The approach proposed in [BGdN06, FHT08] consists of solving the following convex optimization problem:

$$\min_{X \in \mathbf{S}_{++}^n} \text{tr}(\hat{S}X) - \log \det X + \lambda \|X\|_1 \tag{10}$$

where $\lambda > 0$ is a regularization parameter, $\hat{S} \in \mathbf{S}_+^n$ is the given empirical covariance matrix, and $\|X\|_1 = \sum_{ij} |X_{ij}|$ is the entrywise ℓ_1-norm of X. The ADMM algorithm is one of the most popular methods for this problem, see e.g., [SMG10, BPC11] and references therein. The problem (10) can be naturally put in the splitting form (1) with $F(X) = \mathrm{tr}(\hat{S}X) - \log \det X$ and $G(X) = \lambda\|X\|_1$. The ADMM iterates can be written as:

$$\begin{cases} X_{k+1} = \mathrm{prox}_{-\rho \log \det}(Z_k - U_k - \rho\hat{S}) \\ Z_{k+1} = \mathsf{S}_{\lambda/\rho}(X_{k+1} + U_k) \\ U_{k+1} = U_k + X_{k+1} - Z_{k+1} \end{cases} \tag{11}$$

where the proximal operator of $-\rho \log \det$ is $\mathrm{prox}_{-\rho \log \det}(Y) = V \mathrm{diag}\left((y + \sqrt{y^2 + 4\rho})/2 \right) V^T$ where $Y = V \mathrm{diag}(y)V^T$ is the eigenvalue decomposition of Y; and S_t is the entrywise soft-thresholding operation defined by $\mathsf{S}_t(x) = 0$ if $|x| \leq t$ and $x - \mathrm{sign}(x)t$ otherwise. The main computational cost in the iterations (11) is the proximal update rule for X_k which requires the eigenvalue decomposition of $Z_k - U_k - \rho\hat{S}$ at each iteration. We can use the Jacobi method to compute this eigenvalue decomposition, using the previous iterate's orthogonal transformation as a warm start, as suggested in Section 3.2.

We have implemented this approach with different values of n in the range 200-1000, where the covariance matrix $\Sigma \in \mathbf{S}_{++}^n$ was chosen to be a banded matrix with constant bandwidth $k = 5$. We have used the parameters and stopping criterion of the Matlab implementation of (11) from [BPC11] available at `https://web.stanford.edu/~boyd/papers/admm/`. We compare the Jacobi method with the standard routines in linear algebra packages for eigenvalue decomposition on CPU and GPU (NumPy/CuPy's `linalg.eigh`).

The results of the numerical experiments are shown in Table 2. Depending on the size of the matrix, the Jacobi method can be more than 5x faster than the standard approaches on both CPU and GPU. The tolerance we have used for the Jacobi method is $\epsilon_k = 0.1/(1 + k^{2.5})$. We see that the average number of sweeps per iteration is < 1 confirming the fact that the eigenvector matrix from iterate $k - 1$ is a good initial point for the k'th iterate.

	iterations			X-update time per iter (ms)			
n	default (CPU)	default (GPU)	jacobi (GPU)	default (CPU)	default (GPU)	**jacobi (GPU)**	sweeps/iter
200	308	308	311	4.25	6.46	**1.8**	0.96
400	269	269	269	16.19	17.96	**3.09**	0.95
600	248	248	252	38.20	30.43	**5.69**	0.95
800	236	236	239	78.33	43.15	**9.41**	0.95
1000	227	227	230	135.23	63.81	**14.84**	0.94

Table 2: Sparse covariance selection problem. Time per iteration for the computation of the X-proximal update in (11) using the Jacobi method compared to the standard approaches on CPU/GPU. The tolerance used for Jacobi's method is $\epsilon_k = 0.1/(1 + k^{2.5})$.

5.2 Semidefinite programming

We consider here semidefinite programs in primal-dual form,

$$\min_{x \in \mathbb{R}^n, S \in \mathbf{S}^k} c^T x \qquad\qquad \max_{Y \in \mathbf{S}^k} -\mathrm{tr}(BY)$$
$$\text{s.t.} \quad \sum_{i=1}^n x_i A_i + S = B, \; S \succeq 0 \qquad \text{s.t.} \quad Y \succeq 0, \; \langle A_i, Y \rangle = -c_i \; (i = 1, \ldots, n) \tag{12}$$

where $c \in \mathbb{R}^n$, $A_1, \ldots, A_n \in \mathbf{S}^k$ and $B \in \mathbf{S}^k$. A primal-dual ADMM-based algorithm was proposed in [OCPB16] and implemented in the SCS package [OCPB19]. Each iteration of the algorithm consists of two steps, one projection onto a linear subspace, and one projection onto the positive semidefinite cone $\mathbf{S}_+^k$. The projection step can be computed using the Jacobi-based method. Table 3 shows the time per iteration required for the projection step using Jacobi's method compared to the default approaches, on random instances of (12). We set the tolerance for the Jacobi method to be $\epsilon_k = 0.1/(1 + k^{2.5})$ and we see that the time spent in the computation of the projection on the positive semidefinite is up to 5x faster than the default approaches, and that the number of sweeps per iteration is not more than 1.

	iterations			proj time/iter (ms)				linsolve/iter (ms)
k	default (CPU)	default (GPU)	jacobi (GPU)	default (CPU)	default (GPU)	**jacobi (GPU)**	sweeps per iter	
200	60	60	70	4.42	7.1	**2.04**	0.74	2.49
400	80	80	90	16.78	18.33	**3.06**	0.62	9.30
600	90	90	130	39.97	32.11	**5.47**	0.58	20.30
800	90	90	140	79.70	44.6	**10.06**	0.51	35.92
1000	150	150	150	139.71	65.87	**15.69**	0.49	54.55

Table 3: Semidefinite programming using primal-dual ADMM approach of [OCPB16] on random instances of (12) where $n = 3k$, $B = I_k$, and the A_i are sparse random matrices with density $\sim k$. Time per iteration (in milliseconds) to compute projection of $k \times k$ symmetric matrix on the positive semidefinite cone using the Jacobi method vs. standard approaches on CPU/GPU. The tolerance used for Jacobi's method is $\epsilon_k = 0.1/(1 + k^{2.5})$. For comparison, we also show the time needed for the linear system solve at each iteration (in milliseconds). We used the same termination criterion as the one in [OCPB16], with a tolerance of 10^{-3} on the normalized primal and dual residuals, and duality gap.

5.3 Nuclear norm minimization using the proximal gradient method

We consider the low-rank matrix recovery problem

$$\min_{X \in \mathbb{R}^{n \times n}} (1/2)\|\mathcal{A}(X) - b\|_2^2 + \lambda\|X\|_* \tag{13}$$

where $\mathcal{A} : \mathbb{R}^{n \times n} \to \mathbb{R}^m, b \in \mathbb{R}^m$, λ is the regularization parameter, and $\|X\|_* = \sum_{i=1}^n \sigma_i(X)$ is the nuclear norm. A popular method for solving (13) is the (fast) proximal gradient method, with iterates:

$$X_{k+1} = \mathsf{SVT}_{t\lambda}(Z - t\mathcal{A}^*(\mathcal{A}(Z) - b)) \tag{14}$$

where $t > 0$ is the step size, and $\mathsf{SVT}_{t\lambda}$ is the proximal operator associated to the nuclear norm which is given by the soft-thresholding of singular values. In the standard proximal gradient method, we take $Z = X_k$ in (14), whereas for the fast proximal gradient method we take $Z = X_k + \frac{k-1}{k+2}(X_k - X_{k-1})$. Clearly, the main computational cost in the implementation of (14) is to compute the singular value decomposition of a $n \times n$ matrix.

Table 4 shows the result of using the fast proximal gradient method with the Jacobi-based method vs. the default SVD routines on CPU/GPU for the computation of the proximal operator, on random matrix-completion instances of (13). The number of iterations was fixed and set to 1000, and we used $\epsilon_k = 1/(1 + k^{2.5})$ as the tolerance for the Jacobi method at iteration k. We observe here that for $n = 1000$ we get a speed-up of more than 20x compared to both the CPU and GPU methods.

	objective			SVD time per iter (ms)			
n	default CPU	default GPU	jacobi GPU	default CPU	default GPU	**jacobi GPU**	jacobi sweeps per iter
200	$7.64e+1$	$7.64e+1$	$7.64e+1$	9.11	17.23	**2.23**	1.05
400	$3.15e+2$	$3.15e+2$	$3.15e+2$	42.39	52.76	**3.57**	0.96
600	$7.24e+2$	$7.24e+2$	$7.26e+2$	71.32	105.04	**6.08**	0.92
800	$1.29e+3$	$1.29e+3$	$1.30e+3$	153.37	177.55	**9.60**	0.92
1000	$1.99e+3$	$1.99e+3$	$2.00e+3$	309.75	327.59	**13.89**	0.81

Table 4: Nuclear norm minimization using fast proximal gradient method (14). Time to compute the SVD at each iteration using the Jacobi's method vs. the default methods on CPU/GPU. The tolerance for the Jacobi's method at iteration k was set to $\epsilon_k = 1/(1 + k^{2.5})$. Objective value is after 1000 iterations.

References

[BBV16]   Afonso S Bandeira, Nicolas Boumal, and Vladislav Voroninski. On the low-rank approach for semidefinite programs arising in synchronization and community detection. In *Conference on learning theory*, pages 361–382. PMLR, 2016.

[BGdN06] Onureena Banerjee, Laurent El Ghaoui, Alexandre d'Aspremont, and Georges Natsoulis. Convex optimization techniques for fitting sparse gaussian graphical models. In *Proceedings of the 23rd international conference on Machine learning*, pages 89–96, 2006.

[BPC11]   Stephen Boyd, Neal Parikh, and Eric Chu. *Distributed optimization and statistical learning via the alternating direction method of multipliers*. Now Publishers Inc, 2011.

[BT09]   Amir Beck and Marc Teboulle. A fast iterative shrinkage-thresholding algorithm for linear inverse problems. *SIAM Journal on Imaging Sciences*, 2(1):183–202, 2009.

[BTB20]   Mathieu Barré, Adrien Taylor, and Francis Bach. Principled analyses and design of first-order methods with inexact proximal operators. *arXiv preprint arXiv:2006.06041*, 2020.

[BTN01]   Aharon Ben-Tal and Arkadi Nemirovski. *Lectures on modern convex optimization: analysis, algorithms, and engineering applications*. SIAM, 2001.

[CR09]   Emmanuel J Candès and Benjamin Recht. Exact matrix completion via convex optimization. *Foundations of Computational mathematics*, 9(6):717–772, 2009.

[CV18]   Hsiao-Han Chao and Lieven Vandenberghe. Entropic proximal operators for nonnegative trigonometric polynomials. *IEEE Transactions on Signal Processing*, 66(18):4826–4838, 2018.

[Dav57]   Chandler Davis. All convex invariant functions of hermitian matrices. *Archiv der Mathematik*, 8(4):276–278, 1957.

[EB92]   Jonathan Eckstein and Dimitri P Bertsekas. On the Douglas-Rachford splitting method and the proximal point algorithm for maximal monotone operators. *Mathematical Programming*, 55(1):293–318, 1992.

[FH60]   George Elmer Forsythe and Peter Henrici. The cyclic Jacobi method for computing the principal values of a complex matrix. *Transactions of the American Mathematical Society*, 94(1):1–23, 1960.

[FHT08]   Jerome Friedman, Trevor Hastie, and Robert Tibshirani. Sparse inverse covariance estimation with the graphical lasso. *Biostatistics*, 9(3):432–441, 2008.

[FKMN01] Mituhiro Fukuda, Masakazu Kojima, Kazuo Murota, and Kazuhide Nakata. Exploiting sparsity in semidefinite programming via matrix completion i: General framework. *SIAM Journal on Optimization*, 11(3):647–674, 2001.

[GNR20]   Paul J Goulart, Yuji Nakatsukasa, and Nikitas Rontsis. Accuracy of approximate projection to the semidefinite cone. *Linear Algebra and its Applications*, 594:177–192, 2020.

[GVL13]   Gene H Golub and Charles F Van Loan. *Matrix computations*, volume 3. JHU press, 2013.

[HMvdW+20] Charles R. Harris, K. Jarrod Millman, Stéfan J. van der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J. Smith, Robert Kern, Matti Picus, Stephan Hoyer, Marten H. van Kerkwijk, Matthew Brett, Allan Haldane, Jaime Fernández del Río, Mark Wiebe, Pearu Peterson, Pierre Gérard-Marchant, Kevin Sheppard, Tyler Reddy, Warren Weckesser, Hameer Abbasi, Christoph Gohlke, and Travis E. Oliphant. Array programming with NumPy. *Nature*, 585(7825):357–362, September 2020.

[HR00]   Christoph Helmberg and Franz Rendl. A spectral bundle method for semidefinite programming. *SIAM Journal on Optimization*, 10(3):673–696, 2000.

[Jac46]   Carl Gustav Jacob Jacobi. Über ein leichtes Verfahren die in der Theorie der Säcularstörungen vorkommenden Gleichungen numerisch aufzulösen. *J. Reine Angew. Math*, 30:51–95, 1846.

[JV21]   Xin Jiang and Lieven Vandenberghe. Bregman primal–dual first-order method and application to sparse semidefinite programming. 2021.

[LCB+04] Gert RG Lanckriet, Nello Cristianini, Peter Bartlett, Laurent El Ghaoui, and Michael I Jordan. Learning the kernel matrix with semidefinite programming. *Journal of Machine learning research*, 5(Jan):27–72, 2004.

[Lew95]   Adrian S Lewis. The convex analysis of unitarily invariant matrix functions. *Journal of Convex Analysis*, 2(1):173–183, 1995.

[MKL15]   Ramtin Madani, Abdulrahman Kalbat, and Javad Lavaei. ADMM for sparse semidefinite programming with applications to optimal power flow problem. In *2015 54th IEEE Conference on Decision and Control (CDC)*, pages 5932–5939. IEEE, 2015.

[MOA79]   Albert W Marshall, Ingram Olkin, and Barry C Arnold. *Inequalities: theory of majorization and its applications*, volume 143. Springer, 1979.

[Nes03]   Yurii Nesterov. *Introductory lectures on convex optimization: A basic course*, volume 87. Springer Science & Business Media, 2003.

[NVI20]   NVIDIA. cusolver library, 2020. `https://docs.nvidia.com/pdf/CUSOLVER_Library.pdf`.

[OCPB16]   B. O'Donoghue, E. Chu, N. Parikh, and S. Boyd. Conic optimization via operator splitting and homogeneous self-dual embedding. *Journal of Optimization Theory and Applications*, 169(3):1042–1068, June 2016.

[OCPB19]   B. O'Donoghue, E. Chu, N. Parikh, and S. Boyd. SCS: Splitting conic solver, version 2.1.3. `https://github.com/cvxgrp/scs`, November 2019.

[OUN+17]   Ryosuke Okuta, Yuya Unno, Daisuke Nishino, Shohei Hido, and Crissman Loomis. CuPy: A NumPy-Compatible Library for NVIDIA GPU Calculations. In *Proceedings of Workshop on Machine Learning Systems (LearningSys) in The Thirty-first Annual Conference on Neural Information Processing Systems (NIPS)*, 2017.

[PB14]   Neal Parikh and Stephen Boyd. Proximal algorithms. *Foundations and Trends in optimization*, 1(3):127–239, 2014.

[Ren14]   James Renegar. Efficient first-order methods for linear programming and semidefinite programming. *arXiv preprint arXiv:1409.5832*, 2014.

[RFP10]   Benjamin Recht, Maryam Fazel, and Pablo A Parrilo. Guaranteed minimum-rank solutions of linear matrix equations via nuclear norm minimization. *SIAM review*, 52(3):471–501, 2010.

[Sch64]   A Schönhage. Zur quadratischen Konvergenz des Jacobi-Verfahrens. *Numerische Mathematik*, 1964.

[SMG10]   Katya Scheinberg, Shiqian Ma, and Donald Goldfarb. Sparse inverse covariance selection via alternating linearization methods. *arXiv preprint arXiv:1011.0097*, 2010.

[SRB11]   Mark Schmidt, Nicolas Le Roux, and Francis Bach. Convergence rates of inexact proximal-gradient methods for convex optimization. *Neural Information Processing Systems*, 2011.

[TBI97]   Lloyd N Trefethen and David Bau III. *Numerical linear algebra*, volume 50. SIAM, 1997.

[Tho77]   Robert C Thompson. Singular values, diagonal elements, and convexity. *SIAM Journal on Applied Mathematics*, 32(1):39–63, 1977.

[VK66a]   HPM Van Kempen. On the convergence of the classical jacobi method for real symmetric matrices with non-distinct eigenvalues. *Numerische Mathematik*, 9(1):11–18, 1966.

[VK66b]   HPM Van Kempen. On the quadratic convergence of the special cyclic Jacobi method. *Numerische Mathematik*, 9(1):19–22, 1966.

[Wil62]   J. H. Wilkinson. Note on the Quadratic Convergence of the Cyclic Jacobi Process. *Numerische Mathematik 4, 296– 300*, 1962.

[Yao16]   Wang Yao. *Approximate versions of the alternating direction method of multipliers*. PhD thesis, Rutgers University-Graduate School-New Brunswick, 2016.

[YTF+21]   Alp Yurtsever, Joel A Tropp, Olivier Fercoq, Madeleine Udell, and Volkan Cevher. Scalable semidefinite programming. *SIAM Journal on Mathematics of Data Science*, 3(1):171–200, 2021.

[ZFP+20]   Yang Zheng, Giovanni Fantuzzi, Antonis Papachristodoulou, Paul Goulart, and Andrew Wynn. Chordal decomposition in operator-splitting methods for sparse semidefinite programs. *Mathematical Programming*, 180(1):489–532, 2020.