Informative Outlier Matters: Robustifying Out-of-distribution Detection Using Outlier Mining

Abstract

Detecting out-of-distribution (OOD) inputs is critical for safely deploying deep learning models in an open-world setting. However, existing OOD detection solutions can be brittle in the open world, facing various types of adversarial OOD inputs. While methods leveraging auxiliary OOD data have emerged, our analysis reveals a key insight that the majority of auxiliary OOD examples may not meaningfully improve the decision boundary of the OOD detector. In this paper, we provide a theoretically motivated method, *Adversarial Training with informative Outlier Mining* (ATOM), which improves the robustness of OOD detection. We show that, by mining informative auxiliary OOD data, one can significantly improve OOD detection performance, and somewhat surprisingly, generalize to unseen adversarial attacks. ATOM achieves state-of-the-art performance under a broad family of natural and perturbed OOD evaluation tasks. For example, on the CIFAR-10 in-distribution dataset, ATOM reduces the FPR95 by up to 57.99% under adversarial OOD inputs, surpassing the previous best baseline by a large margin.

1 Introduction

Out-of-distribution (OOD) detection has become an indispensable part of building reliable open-world machine learning models (Amodei et al., 2016). An OOD detector determines whether an input is from the same distribution as the training data, or a different distribution (*i.e.*, out-of-distribution). The performance of the OOD detector is central for safety-critical applications such as autonomous driving (Eykholt et al., 2018) or rare disease identification (Blauwkamp et al., 2019).

Despite exciting progress made in OOD detection, previous methods mostly focused on natural OOD data (Hendrycks & Gimpel, 2016; Liang et al., 2018; Lee et al., 2018; Lakshminarayanan et al., 2017; Hendrycks et al., 2018; Mohseni et al., 2020). Scant attention has been paid to the robustness aspect of OOD detection. Recent works (Hein et al., 2019; Sehwag et al., 2019; Bitterwolf et al., 2020) considered worst-case OOD detection under adversarial perturbations (Papernot et al., 2016; Goodfellow et al., 2014; Biggio et al., 2013; Szegedy et al., 2013). For example, an OOD image (*e.g.*, mailbox) can be perturbed to be misclassified by the OOD detector as in-distribution (traffic sign data). Such an adversarial OOD example is then passed to the image classifier and trigger undesirable prediction and action (*e.g.*, speed limit 70). Therefore, it remains an important question to make out-of-distribution detection algorithms robust in the presence of small perturbations to OOD inputs.

In this paper, we begin with formally formulating the task of robust OOD detection and providing theoretical analysis in a simple Gaussian data model. While recent OOD detection methods (Hendrycks et al., 2018; Hein et al., 2019; Meinke & Hein, 2019; Mohseni et al., 2020) have leveraged auxiliary OOD data, they often sample randomly uniformly from the auxiliary dataset. Contrary to the common practice, our analysis reveals a key insight that *the majority of auxiliary OOD examples may not provide useful information to improve the decision boundary of OOD detector*. Under a Gaussian model of the data, we theoretically show that using outlier mining improves the error bound of OOD detector in the presence of non-informative auxiliary OOD data.

Motivated by this insight, we propose *Adversarial Training with informative Outlier Mining* (ATOM), which justifies the theoretical intuitions above and achieves state-of-the-art performance on a broad family of natural and perturbed OOD evaluation tasks for modern neural networks. We show that, by

Figure 1: When deploying an image classification system (OOD detector $G(x)$ + image classifier $f(x)$) in an open world, there can be multiple types of out-of-distribution examples. We consider a broad family of OOD inputs, including (a) natural OOD, (b) adversarially perturbed OOD under L_∞ norm perturbation, and (c) corruption attacked OOD. In (b-d), a perturbed OOD input (e.g., a perturbed mailbox image) can mislead the OOD detector to classify it as an in-distribution sample. This can trigger the downstream image classifier $f(x)$ to predict it as one of the in-distribution classes (e.g., speed limit 70). Through *adversarial training with informative outlier mining* (ATOM), our method can robustify the decision boundary of OOD detector $G(x)$, which leads to improved performance across all types of OOD inputs. Solid lines are actual computation flow.

carefully choosing which OOD data to train on, one can significantly improve the robustness of an OOD detector, and somewhat surprisingly, generalize to unseen adversarial attacks.

To evaluate our method, we provide a unified robustness evaluation framework for OOD detection, and compare extensively with eight competitive OOD detection methods. Unlike existing methods, ATOM demonstrates robustness across various types of OOD inputs considered. On CIFAR-10, our method outperforms the best baseline ACET (Hein et al., 2019) by **53.9%** (FPR) under L_∞-norm attacked OOD inputs, and by **41.67%** under unknown corruption attacked OOD inputs. Finally, while almost every method fails under the strongest compositional attack, our method reduces the FPR by **57.99%**. We perform ablation analysis, and observe consistent performance improvement using different in-distribution datasets, auxiliary datasets and neural network architectures.

In summary, our contributions are:

- Firstly, we contribute theoretical analysis formalizing the intuition of mining hard outliers for improving the robustness of OOD detection.
- Secondly, we contribute a theoretically motivated method, ATOM, which leads to state-of-the-art performance on both clean and perturbed OOD inputs. We conduct extensive evaluations and ablation analysis to demonstrate the effectiveness of informative outlier sampling.
- Lastly, we provide a unified evaluation framework that allows future research examining the robustness of OOD detection algorithms under a broad family of OOD inputs, as illustrated in Figure 1.

2 PROBLEM STATEMENT

In this section, we formulate the problem of robust out-of-distribution detection, as well as a unified evaluation framework for this problem.

Preliminaries. We consider a training dataset $\mathcal{D}_{\text{in}}^{\text{train}}$ drawn i.i.d. from a data distribution $P_{\boldsymbol{X},Y}$, where $\boldsymbol{X}$ is the sample space and $Y = \{1, 2, \cdots, K\}$ is the set of labels. A classifier $f(\mathbf{x})$ is trained on the in-distribution, $P_{\boldsymbol{X}}$, the marginal distribution of $P_{\boldsymbol{X},Y}$. The OOD examples are revealed during test time, which are from a different distribution $Q_{\boldsymbol{X}}$, potentially with perturbations added. The task of

robust out-of-distribution detection is to learn a detector $G : \mathbf{x} \to \{-1, 1\}$, which outputs 1 for $\mathbf{x}$ from $P_{\mathbf{X}}$ and output -1 for a clean or perturbed OOD example $\mathbf{x}$ from $Q_{\mathbf{X}}$.

Formally, let $\Omega(\mathbf{x})$ be a set of small perturbations on an OOD example $\mathbf{x}$. The detector is evaluated on $\mathbf{x}$ from $P_{\mathbf{X}}$ and on the worst-case input inside $\Omega(\mathbf{x})$ for an OOD example from $Q_{\mathbf{X}}$. The false negative rate (FNR) and false positive rate (FPR) are defined as:

$$\text{FNR}(G) = \mathbb{E}_{\mathbf{x} \sim P_{\mathbf{X}}} \mathbb{I}[G(\mathbf{x}) = -1], \quad \text{FPR}(G; Q_{\mathbf{X}}, \Omega) = \mathbb{E}_{\mathbf{x} \sim Q_{\mathbf{X}}} \max_{\delta \in \Omega(\mathbf{x})} \mathbb{I}[G(\mathbf{x} + \delta) = 1]. \quad (1)$$

Note that no data from the test OOD distribution $Q_{\mathbf{X}}$ are available for training. As common in previous work, we assume that we have an auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ from another distribution $U_{\mathbf{X}}$. The difference between auxiliary and test OOD data leads to our insight in the next section.

Robust OOD Evaluation Tasks. We consider the following family of OOD inputs, for which we provide visualizations in Appendix C.5:

- **Natural OOD**: This is equivalent to the classic OOD evaluation with clean input $\mathbf{x}$, and $\Omega = \emptyset$.

- L_∞ **attacked OOD (white-box)**: We consider small L_∞-norm bounded perturbations on $\mathbf{x}$ (Madry et al., 2017; Athalye et al., 2018), which induce the model to produce high confidence scores (or low OOD scores) for OOD inputs. We denote the adversarial perturbations by $\Omega_{\infty, \epsilon}(\mathbf{x})$, where ϵ is the adversarial budget. We provide attack algorithms for all eight OOD detection methods in Appendix C.4.

- **Corruption attacked OOD (black-box)**: We consider a more realistic type of attack based on common corruptions (Hendrycks & Dietterich, 2019), which could appear naturally in the physical world. For each OOD image, we generate 75 corrupted images (15 corruption types $\times$ 5 severity levels), and then select the one with the lowest OOD score.

- **Compositionally attacked OOD (white-box)**: Lastly, we consider applying L_∞-norm bounded attack and corruption attack jointly to an input $\mathbf{x}$, as considered in (Laidlaw & Feizi, 2019).

3 THEORETICAL ANALYSIS UNDER A GAUSSIAN MODEL

In this section, we provide the theoretical insights of outlier mining by considering a simplified Gaussian data model. In what follows, we first describe our Gaussian data model. We then demonstrate that using auxiliary OOD data can improve the error bound of an OOD detector, compared with the case without. Lastly, we show that outlier mining can be critical when the auxiliary data contains non-informative data due to its difference from the test OOD distribution, and that outlier mining technique can identify informative OOD data to improve the OOD detection performance.

Gaussian Data Model. Given $\mu \in \mathbb{R}^d, \sigma > 0, \nu > 0$, we consider the following model:

- In-distribution $P_{\mathbf{X}}$: $\mathcal{N}(\mu, \sigma^2 I)$; The in-distribution data $\{\mathbf{x}_i\}_{i=1}^n$ is drawn from $P_{\mathbf{X}}$.
- Out-of-distribution $Q_{\mathbf{X}}$ can be any distribution from the family $\mathcal{Q} = \{\mathcal{N}(-\mu + v, \sigma^2 I) : v \in \mathbb{R}^d, \|v\|_2 \le \nu\}$.
- Hypothesis class of OOD detector: $\mathcal{G} = \{G_\theta(\mathbf{x}) = \text{sign}(\theta^\top \mathbf{x}) : \theta \in \mathbb{R}^d\}$.

A concrete instance of the Gaussian data model is defined by a set of parameter values for d, μ, σ, and ν. We consider the FNR and the FPR under ℓ_∞ perturbations of magnitude ϵ. Since $Q_{\mathbf{X}}$ is not accessible at training time, our goal is to bound $\sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(G; Q_{\mathbf{X}}, \Omega_{\infty, \epsilon}(\mathbf{x}))$.

While the Gaussian model may be much simpler than the practical data distributions, its simplicity is desirable for our analytical purpose for demonstrating the insights. Furthermore, the analysis in this simple model has implications for more complicated and practical methods, which we present in Section 4. Due to lack of space, proofs are deferred to Appendix B, in which we also give additional bounds without assuming that the data is drawn from a Gaussian distribution.

First, without auxiliary data, we lower bound the sample size and show that *any* algorithm must have *large* errors with less samples. Let $\mathbb{A}_n$ denote any algorithm mapping a dataset S of n i.i.d. samples from in-distribution $P_{\mathbf{X}}$ to a detector $\mathbb{A}_n(S) \in \mathcal{G}$.

Proposition 1. *(Bound without auxiliary data) For any $\epsilon \in (0, 1/2)$ and any integer $n_0 > 0$, there exist a family of instances of the Gaussian data model, such that if $n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{16 \log d}$, then for any algorithm $\mathbb{A}_n$, there exists an instance in the family with*

$$\mathbb{E}\left\{ \text{FNR}(\mathbb{A}_n(S)) + \sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(\mathbb{A}_n(S); Q_{\mathbf{X}}, \Omega_{\infty, \epsilon}(\mathbf{x})) \right\} \geq \frac{1}{4}(1 - d^{-1}). \quad (2)$$

Auxiliary Outliers Improve the Detection Performance. Now we turn to the case where we have auxiliary OOD data $\{\tilde{\mathbf{x}}_i\}_{i=1}^{n'}$. We consider the following two distributions of auxiliary OOD data: (1) the ideal case when $U_{\mathbf{X}}$ consists of informative auxiliary data, and (2) the less ideal case when auxiliary OOD data U_{mix} contains both informative and non-informative points. Specifically:

- $U_{\mathbf{X}}$ is defined by $\mathcal{N}(-\mu + v, \sigma^2 I)$, where v is drawn uniformly at random from the ball $\{v : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$. So $U_{\mathbf{X}}$ is a uniform mixture of the possible test OOD distributions.
- U_{mix} is a uniform mixture of $\mathcal{N}(-\mu, \sigma^2 I)$ and $\mathcal{N}(\mu_o, \sigma^2 I)$ with $\mu_o = 10\mu$.

In the ideal case, $U_{\mathbf{X}}$ is a distribution that is similar to the test OOD distribution so its samples are informative for learning. In contrast, U_{mix} consists of non-informative outliers far from in-distribution (most points in $\mathcal{N}(\mu_o, \sigma^2 I)$), and also more informative ones. We first provide an error bound under the ideal case. Consider the detector $G_{\hat{\theta}_{n,n'}}$ given by $\hat{\theta}_{n,n'} = \frac{1}{n+n'}\left(\sum_{i=1}^n \mathbf{x}_i - \sum_{i=1}^{n'} \tilde{\mathbf{x}}_i\right)$.

Proposition 2. *(Error bound with ideal auxiliary data) Consider the same family of instances as in Preposition 1, with n' auxiliary OOD data from $U_{\mathbf{X}}$ specified above. If $n \geq n_0$ and $n' \geq n_0 \cdot 4\epsilon^2 \sqrt{d/n_0}$, then*

$$\mathbb{E}_{\hat{\theta}_{n,n'}} \text{FNR}(G_{\hat{\theta}_{n,n'}}) \leq 10^{-3}, \quad \mathbb{E}_{\hat{\theta}_{n,n'}} \sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(G_{\hat{\theta}_{n,n'}}; Q_{\mathbf{X}}, \Omega_{\infty, \epsilon}(\mathbf{x})) \leq 10^{-3}. \quad (3)$$

(The error bound in the proposition can be made arbitrarily small and with high probability. The current bound is presented for simplicity.) Proposition 1 and 2 together show the benefit of the auxiliary data. To see this, consider the interesting case of high dimensional data where d is sufficiently large so that $\frac{\epsilon^2 \sqrt{d/n_0}}{16 \log d} > 1$. If $n_0 \leq n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{16 \log d}$, then Proposition 1 shows that no algorithm can get small errors without auxiliary data, while Proposition 2 shows a simple algorithm using auxiliary data can get small errors.

Informative Outlier Matters. We now show outlier mining can be critical when the auxiliary data contains non-informative data. Specifically, we consider the simple example where the auxiliary data are from the less ideal distribution U_{mix}. Importantly, the distribution U_{mix} models the case where the auxiliary data has some non-informative outliers, and also with a small probability mass of samples (e.g., tail of $\mathcal{N}(-\mu, \sigma^2 I)$) in the support of in-distribution. In this case, the method in Proposition 2 no longer provides a low error bound with $\mathbb{E}[\hat{\theta}_{n,n'}] = -7\mu/4$, since $\hat{\theta}_{n,n'}$ is misled by auxiliary data from $\mathcal{N}(\mu_o, \sigma^2 I)$ or tail of $\mathcal{N}(-\mu, \sigma^2 I)$ in the support of in-distribution.

We now present a simple mining method which only tries to pick points with *mild* confidence scores. This removes non-informative outliers. Specifically, we first use in-distribution data to get an intermediate solution: $\hat{\theta}_{\text{int}} = \frac{1}{n}\sum_{i=1}^n \mathbf{x}_i$. Then, we select outliers $\tilde{\mathbf{x}}$ whose confidence scores $f(\tilde{\mathbf{x}}) = 1/(1 + e^{-\tilde{\mathbf{x}}^\top \hat{\theta}_{\text{int}}/d})$ fall in an interval $[a, b]$. The final solution $\hat{\theta}_{\text{om}}$ is -1 times the average of the selected outliers.

Proposition 3. *(Error bound with outlier mining.) Consider the same family of instances as in Proposition 2, with n' auxiliary OOD data from U_{mix} specified above. There exist thresholds a and b for $\hat{\theta}_{\text{om}}$ and a universal constant $c > 0$ such that if $n \geq c(n_0 \log d + \sqrt{dn_0})$ and $n' \geq (d + n_0 \cdot 4\epsilon^2)\sqrt{d/n_0}$, then $\hat{\theta}_{\text{om}}$ has the same error guarantees as in Proposition 2.*

Intuitively, the mining method removes the misleading points (most points in $\mathcal{N}(\mu_o, \sigma^2 I)$ and tail of $\mathcal{N}(-\mu, \sigma^2 I)$ in the support of in-distribution). Outliers selected in this way are mostly informative and thus give an accurate final detector, which justifies outlier mining in the presence of non-informative data. We note that our analysis and the result also hold for many other auxiliary data distributions U_{mix}, and the particular U_{mix} used here is for the simplicity of demonstration; see the appendix for more discussions. In the following section, we design a practical algorithm based on this insight and present empirical evidence of its effectiveness.

|(a) OOD score distribution | (b) highest OOD scores | (c) lowest OOD scores |

Figure 2: On CIFAR-10, we train a DenseNet with objective (4) for 100 epochs **without** informative outlier mining. At epoch 30, we randomly sample 400,000 data points from $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, and plot the OOD score frequency distribution (a). We observe that the model quickly converges to solution where OOD score distribution becomes dominated by *easy* examples with score closer to 1, as shown in (b). Therefore, training on these easy OOD data points can no longer help improve the decision boundary of OOD detector. (c) shows the hardest examples mined from TinyImages w.r.t CIFAR-10.

4   ATOM: ADVERSARIAL TRAINING WITH INFORMATIVE OUTLIER MINING

In this section, we introduce *Adversarial Training with informative Outlier Mining* (ATOM), a theoretically motivated method for robust OOD detection. We first present the adversarial training objective and then describe how we use informative outlier mining to robustify OOD detection.

Training Objective. We consider a $(K+1)$-way classifier network $\hat{f}$, where the $(K+1)$-th class label indicates out-of-distribution class. Denote by $\hat{F}_\theta(\mathbf{x})$ the softmax output of $\hat{f}$ on $\mathbf{x}$. The robust training objective is given by

$$\underset{\theta}{\text{minimize}} \quad \mathbb{E}_{(\mathbf{x},y)\sim\mathcal{D}_{\text{in}}^{\text{train}}}[\ell(\mathbf{x}, y; \hat{F}_\theta)] + \lambda \cdot \mathbb{E}_{\mathbf{x}\sim\mathcal{D}_{\text{out}}^{\text{train}}} \max_{\mathbf{x}'\in\Omega_{\infty,\epsilon}(\mathbf{x})}[\ell(\mathbf{x}', K+1; \hat{F}_\theta)], \quad (4)$$

where ℓ is the cross entropy loss, and $\mathcal{D}_{\text{out}}^{\text{train}}$ is the OOD training dataset. We use Projected Gradient Descent (PGD) (Madry et al., 2017) to solve the inner max of the objective, and apply it to half of a minibatch while keeping the other half clean to ensure performance on both clean and perturbed data. Once trained, the OOD detector $G(\mathbf{x})$ can be constructed by:

$$G(\mathbf{x}) = \begin{cases} -1 & \text{if } \hat{F}(\mathbf{x})_{K+1} \geq \gamma, \\ 1 & \text{if } \hat{F}(\mathbf{x})_{K+1} < \gamma, \end{cases} \quad (5)$$

where γ is the threshold, and in practice can be chosen on the in-distribution data so that a high fraction of the test examples are correctly classified by G. We call $\hat{F}(\mathbf{x})_{K+1}$ the *OOD score* of $\mathbf{x}$. For an input that is labeled as in-distribution by G, one can obtain its semantic label using $F(\mathbf{x})$:

$$F(\mathbf{x}) = \underset{y\in\{1,2,\cdots,K\}}{\arg\max} \hat{F}(\mathbf{x})_y \quad (6)$$

Informative Outlier Mining. Motivated by our theoretical analysis in Section 3, we propose to adaptively choose OOD training examples where the detector is uncertain about. We provide the complete training algorithm using informative outlier mining in Algorithm 1. Our method is different from random sampling as used in previous works (Hendrycks et al., 2018; Hein et al., 2019; Meinke & Hein, 2019; Mohseni et al., 2020). Specifically, during each training epoch, we randomly sample N data points from the auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, and use the current model to infer the OOD scores[1]. Next, we sort the data points according to the OOD scores and select a subset of $n < N$ data points, starting with the qN^{th} data in the sorted list. We then use the selected samples as OOD training data $\mathcal{D}_{\text{out}}^{\text{train}}$ for the next epoch of training. Intuitively, q determines the *informativeness* of the sampled points w.r.t the OOD detector. The larger q is, the less informative those sampled examples

---

[1]Since the inference stage can be fully parallel, outlier mining can be applied with relatively low overhead.

Algorithm 1 ATOM: Adversarial Training with informative Outlier Mining

---

input $\mathcal{D}_{\text{in}}^{\text{train}}, \mathcal{D}_{\text{out}}^{\text{auxiliary}}, \hat{F}_\theta, m, N, n, q$
output F, G

   for $t = 1, 2, \cdots, m$ **do**

      Randomly sample N data points from $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ to get a candidate set $\mathcal{S}$.

      Compute OOD scores on $\mathcal{S}$ using current model $\hat{F}_\theta$ to get set $V = \{\hat{F}(\mathbf{x})_{K+1} \mid \mathbf{x} \in \mathcal{S}\}$.

      Sort scores in V from the lowest to the highest.

      $\mathcal{D}_{\text{out}}^{\text{train}} \leftarrow V[qN : qN + n]$ $\triangleright \{q \in [0, 1 - n/N]\}$

      Train $\hat{F}_\theta$ for one epoch using the training objective of (4).

   end for

   Build G and F using (5) and (6) respectively.

---

become. Note that informative outlier mining is performed on (non-adversarial) auxiliary OOD data. Selected examples are then used in the robust training objective (4).

To see how informative outlier mining alone improves the OOD detection, we also consider the following objective without adversarial training:

$$\underset{\theta}{\text{minimize}} \quad \mathbb{E}_{(\mathbf{x},y)\sim\mathcal{D}_{\text{in}}^{\text{train}}}[\ell(\mathbf{x}, y; \hat{F}_\theta)] + \lambda \cdot \mathbb{E}_{\mathbf{x}\sim\mathcal{D}_{\text{out}}^{\text{train}}}[\ell(\mathbf{x}, K+1; \hat{F}_\theta)], \qquad (7)$$

which we name *Natural Training with informative Outlier Mining* (NTOM).

5 EXPERIMENTS

In this section, we describe our experimental setup (Section 5.1) and show that ATOM can substantially improve OOD detection performance on both clean data and adversarially perturbed inputs. We also conducted extensive ablation analysis to explore different aspects of our algorithm.

5.1 SETUP

In-distribution Datasets. We use SVHN (Netzer et al., 2011), CIFAR-10, and CIFAR-100 (Krizhevsky et al., 2009) datasets as in-distribution datasets.

Auxiliary OOD Datasets. By default, we use 80 Million Tiny Images (TinyImages) (Torralba et al., 2008) as $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, which is a common setting in prior works. We also use ImageNet-RC, a variant of ImageNet (Chrabaszcz et al., 2017) as an alternative auxiliary OOD dataset.

Out-of-distribution Datasets. For OOD test dataset, we follow the procedure in (Liang et al., 2018; Hendrycks et al., 2018) and use six different natural image datasets. For CIFAR-10 and CIFAR-100, we use SVHN, Textures (Cimpoi et al., 2014), Places365 (Zhou et al., 2017), LSUN (crop), LSUN (resize) (Yu et al., 2015), and iSUN (Xu et al., 2015). For SVHN, we use CIFAR-10, Textures, Places365, LSUN (crop), LSUN (resize), and iSUN. Besides natural image datasets, we also consider Gaussian Noise and Uniform Noise as OOD test data.

Hyperparameters. The hyperparameter q is chosen on a separate validation set from TinyImages, which does not depend on test-time OOD data (see Appendix C.7). Based on the validation results in Table 4, we set $q = 0$ for SVHN, $q = 0.125$ for CIFAR-10 and $q = 0.5$ for CIFAR-100. To ensure fair comparison, in each epoch, ATOM uses the same amount of outlier data as OE, where n is twice larger than the in-distribution data size (i.e., 50,000). For all experiments, we set $\lambda = 1$. For CIFAR-10 and CIFAR-100, we set $N = 400,000$, and $n = 100,000$; For SVHN, we set $N = 586,056$, and $n = 146,514$. More details about experimental set up are in Appendix C.1.

Evaluation Metrics. We measure the following metrics: the false positive rate (FPR) at 5% false negative rate (FNR) and the area under the receiver operating characteristic curve (AUROC).

5.2 RESULTS

How does ATOM compare to existing solutions? We show in Table 1 that ATOM outperforms competitive OOD detection methods on both natural and perturbed OOD evaluation tasks. All the

$\mathcal{D}_{in}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
SVHN	MSP	38.84	93.57	99.68	68.48	99.89	1.39	100.00	0.19
	ODIN	31.45	93.52	97.11	63.21	99.86	0.61	100.00	0.05
	Mahalanobis	22.80	95.57	93.14	60.78	97.33	8.89	99.89	0.23
	SOFL	0.06	99.98	3.78	99.07	75.31	46.78	99.81	2.75
	OE	0.60	99.88	23.44	96.23	69.36	52.19	99.65	1.27
	ACET	0.49	99.91	17.03	97.23	29.33	86.75	99.85	5.13
	CCU	0.50	99.90	24.17	96.11	52.17	62.24	99.42	1.60
	ROWL	2.04	98.87	55.03	72.37	77.24	61.27	99.79	**50.00**
	NTOM (ours)	**0.04**	**99.98**	**2.87**	**99.16**	60.28	64.06	99.78	1.50
	ATOM (ours)	0.07	99.97	5.47	98.52	**7.02**	**98.00**	**96.33**	49.52
CIFAR-10	MSP	50.54	91.79	100.00	58.35	100.00	13.82	100.00	13.67
	ODIN	21.65	94.66	99.37	51.44	99.99	0.18	100.00	0.01
	Mahalanobis	26.95	90.30	91.92	43.94	95.07	12.47	99.88	1.58
	SOFL	2.78	99.04	62.07	88.65	99.98	1.01	100.00	0.76
	OE	3.66	98.82	56.25	90.66	99.94	0.34	99.99	0.16
	ACET	12.28	97.67	66.93	88.43	74.45	78.05	96.88	53.71
	CCU	3.39	98.92	56.76	89.38	99.91	0.35	99.97	0.21
	ROWL	25.03	86.96	94.34	52.31	99.98	49.49	100.00	49.48
	NTOM (ours)	1.87	**99.28**	30.58	94.67	99.90	1.22	99.99	0.45
	ATOM (ours)	**1.69**	99.20	**25.26**	**95.29**	20.55	88.94	38.89	86.71
CIFAR-100	MSP	78.05	76.11	100.00	30.04	100.00	2.25	100.00	2.06
	ODIN	56.77	83.62	100.00	36.95	100.00	0.14	100.00	0.00
	Mahalanobis	42.63	87.86	95.92	42.96	95.44	15.87	99.86	2.08
	SOFL	43.36	91.21	99.93	45.23	100.00	0.35	100.00	0.27
	OE	49.21	88.05	99.96	45.01	100.00	0.94	100.00	0.59
	ACET	50.93	89.29	99.53	54.19	76.27	59.45	99.71	38.63
	CCU	43.04	90.95	99.90	48.34	100.00	0.75	100.00	0.48
	ROWL	93.35	53.02	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	36.94	92.61	98.17	65.70	99.97	0.76	100.00	0.16
	ATOM (ours)	**32.30**	**93.06**	**93.15**	**71.96**	**38.72**	**88.03**	**93.44**	**69.15**

Table 1: Comparison with competitive OOD detection methods. We use DenseNet as network architecture for all methods. We evaluate on four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 5.1. **Bold** numbers are superior results. Additional results on a different architecture, WideResNet, are provided in Appendix C.10.

numbers reported are averaged over six different OOD test datasets described in Sec. 5.1. First, on clean OOD data, ATOM outperforms current state-of-the-art method SOFL (Mohseni et al., 2020). On CIFAR-10, our method outperforms the best baseline ACET (Hein et al., 2019) by **53.9%** (FPR) under the L_∞ attacked OOD task. While ACET is somewhat brittle under unknown attacks, our method can generalize surprisingly well to unknown corruption attacked OOD inputs, outperforming the best baseline by **30.99%** measured by FPR. Finally, while almost every method fails under the strongest compositional attack, our method reduces the FPR by **57.99%**. The performance is noteworthy since our method is not trained explicitly on corrupted OOD inputs. Our training method leads to improved OOD detection while preserving classification performance on in-distribution data. Consistent performance improvement is observed on other in-distribution datasets (SVHN and CIFAR-100), alternative network architecture (WideResNet), and with alternative auxiliary dataset (ImageNet-RC).

How does ATOM compare to NTOM? We perform an ablation study that isolates the effect of adversarial training. In Table 1, we show that NTOM achieves comparable performance as ATOM on natural OOD and corruption attacked OOD. However, NTOM is less robust under L_∞ OOD (with 79.35% reduction in FPR on CIFAR-10) and compositional OOD inputs. This underlies the importance of having both adversarial training and outlier mining (ATOM) for overall good performance.

How does the choice of auxiliary OOD dataset affect the performance? To see this, we additionally experiment with using ImageNet-RC as auxiliary OOD data. We observe consistent improvement of ATOM, and in many cases with performance better than using TinyImages. For example, on CIFAR-100, the FPR under natural OOD inputs is reduced from 32.20% (w/ TinyImages) to 15.49% (w/ ImageNet-RC). Interestingly, in all three datasets, using $q = 0$ (hardest outliers) yields the optimal performance since there is substantially less near-duplicates between ImageNet-RC and

in-distribution data. This ablation suggests that ATOM's success does not depend on a particular auxiliary dataset. Full results are provided in Table 6 (Appendix C.9).

How does the sampling parameter affect performance? Table 5 (Appendix C.8) shows the performance with different sampling parameter q. For all three datasets, training on OOD inputs primarily with large OOD scores (*i.e.*, too easy examples with $q = 0.75$) worsens the performance, which suggests the necessity to include examples on which the OOD detector is uncertain about. We also show that using informative outlier mining overall works better than random sampling under properly chosen q. Interestingly, in setting where the in-distribution data and auxiliary OOD data are disjoint (*e.g.*, SVHN/TinyImages), $q = 0$ is optimal, which suggests that the hardest outliers are mostly useful for training. However, in a more realistic setting, the auxiliary OOD data can almost always contain data similar to in-distribution data (*e.g.*, CIFAR/TinyImages). Even without removing near-duplicates exhaustively, ATOM can adaptively avoid training on those near-duplicates of in-distribution data (e.g. using $q = 0.125$ for CIFAR-10 and $q = 0.5$ for CIFAR-100).

6 RELATED WORK

We summarize the most related work here and present extended literature review in Appendix A.

OOD Detection. Hendrycks & Gimpel introduced a baseline approach for OOD detection using the maximum softmax probability from a pre-trained network. Several works attempt to improve the OOD uncertainty estimation by using deep ensembles (Lakshminarayanan et al., 2017), the calibrated softmax score (Liang et al., 2018), and the Mahalanobis distance-based confidence score (Lee et al., 2018). Generative models can be used for OOD detection by checking if a sample lies in the low-density regions. However, as shown by Nalisnick et al., deep generative models can assign a high likelihood to out-of-distribution data. They can be more effective for detection using alternative metrics (Choi & Jang, 2018), likelihood ratio (Ren et al., 2019; Serrà et al., 2019), and modified training technique (Hendrycks et al., 2018). Pope et al. shows that flow-based generative models are sensitive under adversarial attacks. We mainly considered discriminative-based approaches, which can be more competitive due to the availability of label information and auxiliary data.

Adversarial Robustness of OOD Detection. Adversarial examples (Goodfellow et al., 2014; Papernot et al., 2016; Biggio et al., 2013; Szegedy et al., 2013) have received considerable attention in recent years. Many defense methods have been proposed, and one of the most effective methods is adversarial training (Madry et al., 2017). Carmon et al.; Najafi et al.; Zhai et al.; Uesato et al. show that unlabeled data can improve adversarial robustness for classification, which inspires our analysis. But we focus on roubst OOD detection where the auxiliary and test OOD distributions can differ.

OOD detection in the adversarial context have previously been studied in (Hein et al., 2019; Sehwag et al., 2019). However, these papers are primarily concerned with L_∞ norm bounded adversarial attacks, while our evaluation also includes common image corruption attacks. Besides, Meinke & Hein; Hein et al. only evaluate adversarial robustness of OOD detection on random noise images, while we also evaluate it on natural OOD images. Hein et al. has theoretically analyzed why ReLU networks can yield high-confidence but wrong predictions for OOD data. Meinke & Hein has shown the first provable guarantees for worst-case OOD detection on some balls around uniform noise, and Bitterwolf et al. recently studied the provable guarantees for worst-case OOD detection not only for noise but also for images from related but different image classification tasks.

7 CONCLUSION

In this paper, we propose Adversarial Training with informative Outlier Mining (ATOM), a method that enhances the robustness of the OOD detector. We show the merit of adaptively selecting the OOD training examples which the OOD detector is uncertain about. Extensive experiments show ATOM can significantly improve the decision boundary of the OOD detector, achieving state-of-the-art performance under a broad family of *clean and perturbed* OOD evaluation tasks. We also provide theoretical analysis that justifies the benefits of outlier mining. Further, our unified evaluation framework allows future research to examine the robustness of the OOD detector. We hope our research can raise more attention to a broader view of robustness in out-of-distribution detection.

REFERENCES

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. *arXiv preprint arXiv:1802.00420*, 2018.

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 79(1-2):151–175, 2010.

Petra Bevandić, Ivan Krešo, Marin Oršić, and Siniša Šegvić. Discriminative out-of-distribution detection for semantic segmentation. *arXiv preprint arXiv:1808.07703*, 2018.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Joint European conference on machine learning and knowledge discovery in databases*, pp. 387–402. Springer, 2013.

Julian Bitterwolf, Alexander Meinke, and Matthias Hein. Provable worst case guarantees for the detection of out-of-distribution data. *arXiv preprint arXiv:2007.08473*, 2020.

Timothy A Blauwkamp, Simone Thair, Michael J Rosen, Lily Blair, Martin S Lindner, Igor D Vilfan, Trupti Kawli, Fred C Christians, Shivkumar Venkatasubrahmanyam, Gregory D Wall, et al. Analytical and clinical validation of a microbial cell-free dna sequencing test for infectious disease. *Nature microbiology*, 4(4):663–674, 2019.

Maxime Bucher, Stéphane Herbin, and Frédéric Jurie. Hard negative mining for metric learning based zero-shot classification. In *European Conference on Computer Vision*, pp. 524–531. Springer, 2016.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled data improves adversarial robustness. In *Advances in Neural Information Processing Systems*, pp. 11190–11201, 2019.

Hyunsun Choi and Eric Jang. Generative ensembles for robust anomaly detection. 2018.

Patryk Chrabaszcz, Ilya Loshchilov, and Frank Hutter. A downsampled variant of imagenet as an alternative to the cifar datasets. *arXiv preprint arXiv:1707.08819*, 2017.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(Jul):2121–2159, 2011.

Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1625–1634, 2018.

Pedro F Felzenszwalb, Ross B Girshick, David McAllester, and Deva Ramanan. Object detection with discriminatively trained part-based models. *IEEE transactions on pattern analysis and machine intelligence*, 32(9):1627–1645, 2009.

Spyros Gidaris and Nikos Komodakis. Object detection via a multi-region and semantic segmentation-aware cnn model. In *Proceedings of the IEEE international conference on computer vision*, pp. 1134–1142, 2015.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 41–50, 2019.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

Dan Hendrycks, Mantas Mazeika, and Thomas G Dietterich. Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*, 2018.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Cassidy Laidlaw and Soheil Feizi. Functional adversarial attacks. In *Advances in Neural Information Processing Systems*, pp. 10408–10418, 2019.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in neural information processing systems*, pp. 6402–6413, 2017.

Kimin Lee, Honglak Lee, Kibok Lee, and Jinwoo Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. *arXiv preprint arXiv:1711.09325*, 2017.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems*, pp. 7167–7177, 2018.

Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *6th International Conference on Learning Representations, ICLR 2018*, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. In *Advances in Neural Information Processing Systems*, pp. 7047–7058, 2018.

Alexander Meinke and Matthias Hein. Towards neural networks that provably know when they don't know. *arXiv preprint arXiv:1909.12180*, 2019.

Sina Mohseni, Mandar Pitale, JBS Yadawa, and Zhangyang Wang. Self-supervised learning for generalizable out-of-distribution detection. 2020.

Amir Najafi, Shin-ichi Maeda, Masanori Koyama, and Takeru Miyato. Robustness to adversarial perturbations in learning from incomplete data. In *Advances in Neural Information Processing Systems*, pp. 5541–5551, 2019.

Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? *arXiv preprint arXiv:1810.09136*, 2018.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Aristotelis-Angelos Papadopoulos, Mohammad Reza Rajati, Nazim Shaikh, and Jiamian Wang. Outlier exposure with confidence control for out-of-distribution detection. *arXiv preprint arXiv:1906.03509*, 2019.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In *2016 IEEE European symposium on security and privacy (EuroS&P)*, pp. 372–387. IEEE, 2016.

Phillip Pope, Yogesh Balaji, and Soheil Feizi. Adversarial robustness of flow-based generative models. *arXiv preprint arXiv:1911.08654*, 2019.

Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pp. 14680–14691, 2019.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data. In *Advances in Neural Information Processing Systems*, pp. 5014–5026, 2018.

Vikash Sehwag, Arjun Nitin Bhagoji, Liwei Song, Chawin Sitawarin, Daniel Cullina, Mung Chiang, and Prateek Mittal. Analyzing the robustness of open-world machine learning. In *Proceedings of the 12th ACM Workshop on Artificial Intelligence and Security*, pp. 105–116, 2019.

Joan Serrà, David Álvarez, Vicenç Gómez, Olga Slizovskaia, José F Núñez, and Jordi Luque. Input complexity and out-of-distribution detection with likelihood-based generative models. *arXiv preprint arXiv:1909.11480*, 2019.

Abhinav Shrivastava, Abhinav Gupta, and Ross Girshick. Training region-based object detectors with online hard example mining. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 761–769, 2016.

Akshayvarun Subramanya, Suraj Srinivas, and R Venkatesh Babu. Confidence estimation in deep neural networks via density modelling. *arXiv preprint arXiv:1707.07013*, 2017.

Kah-Kay Sung. Learning and example selection for object and pattern detection. 1996.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Esteban G Tabak and Cristina V Turner. A family of nonparametric density estimation algorithms. *Communications on Pure and Applied Mathematics*, 66(2):145–164, 2013.

Antonio Torralba, Rob Fergus, and William T Freeman. 80 million tiny images: A large data set for nonparametric object and scene recognition. *IEEE transactions on pattern analysis and machine intelligence*, 30(11):1958–1970, 2008.

Jonathan Uesato, Jean-Baptiste Alayrac, Po-Sen Huang, Robert Stanforth, Alhussein Fawzi, and Pushmeet Kohli. Are labels required for improving adversarial robustness? *arXiv preprint arXiv:1905.13725*, 2019.

Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. In *Advances in neural information processing systems*, pp. 4790–4798, 2016.

Pingmei Xu, Krista A Ehinger, Yinda Zhang, Adam Finkelstein, Sanjeev R Kulkarni, and Jianxiong Xiao. Turkergaze: Crowdsourcing saliency with webcam based eye tracking. *arXiv preprint arXiv:1504.06755*, 2015.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Runtian Zhai, Tianle Cai, Di He, Chen Dan, Kun He, John Hopcroft, and Liwei Wang. Adversarially robust generalization just requires more unlabeled data. *arXiv preprint arXiv:1906.00555*, 2019.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE transactions on pattern analysis and machine intelligence*, 40(6):1452–1464, 2017.

Supplementary Material

Informative Outlier Matters: Robustifying Out-of-distribution Detection Using Outlier Mining

A   COMPLETE RELATED WORK

Robustness of OOD Detection. Worst-case aspects of OOD detection have previously been studied in (Hein et al., 2019; Sehwag et al., 2019). However, these papers are primarily concerned with L_∞ norm bounded adversarial attacks, while our evaluation also includes common image corruption attacks. Besides, Meinke & Hein; Hein et al. only evaluate adversarial robustness of OOD detection on random noise images, while we also evaluate it on natural OOD images. Hein et al. (2019) has theoretically analyzed why ReLU networks can yield high-confidence but wrong predictions for OOD data. Meinke & Hein has shown the first provable guarantees for worst-case OOD detection on some balls around uniform noise, and Bitterwolf et al. recently studied the provable guarantees for worst-case OOD detection not only for noise but also for images from related but different image classification tasks. In this paper, we propose ATOM which achieves state-of-the-art performance on a broader family of clean and perturbed OOD inputs. The key difference of our method compared to prior work is introducing the informative outlier mining technique, which could significantly improve the generalization and robustness of OOD detection.

Discriminative Based Out-of-Distribution Detection. Hendrycks & Gimpel introduced a baseline approach for OOD detection using the maximum softmax probability from a pre-trained network. Several works attempt to improve the OOD uncertainty estimation by using deep ensembles (Lakshminarayanan et al., 2017), the calibrated softmax score (Liang et al., 2018), and the Mahalanobis distance-based confidence score (Lee et al., 2018). Some methods also modify the neural networks by re-training or fine-tuning on some auxiliary anomalous data that are either realistic (Hendrycks et al., 2018; Mohseni et al., 2020; Papadopoulos et al., 2019) or artificially generated by GANs (Lee et al., 2017). Many other works (Subramanya et al., 2017; Malinin & Gales, 2018; Bevandić et al., 2018) also regularize the model to have lower confidence for anomalous examples.

Generative Modeling Based Out-of-distribution Detection. Generative models (Dinh et al., 2016; Kingma & Welling, 2013; Rezende et al., 2014; Van den Oord et al., 2016; Tabak & Turner, 2013) can be alternative approaches for detecting OOD examples, as they directly estimate the in-distribution density and can declare a test sample to be out-of-distribution if it lies in the low-density regions. However, as shown by Nalisnick et al., deep generative models can assign a high likelihood to out-of-distribution data. Deep generative models can be more effective for out-of-distribution detection using alternative metrics (Choi & Jang, 2018), likelihood ratio (Ren et al., 2019; Serrà et al., 2019), and modified training technique (Hendrycks et al., 2018). Recently, Pope et al. shows that flow-based generative models are sensitive under adversarial attacks. Note that we mainly considered discriminative-based approaches, which can be more competitive due to the availability of label information (and, in some cases, auxiliary OOD data (Hein et al., 2019; Hendrycks et al., 2018; Meinke & Hein, 2019; Mohseni et al., 2020)).

Adversarial Robustness. Adversarial examples (Goodfellow et al., 2014; Papernot et al., 2016; Biggio et al., 2013; Szegedy et al., 2013) have received considerable attention in recent years. Many defense methods have been proposed to mitigate this problem. One of the most effective methods is adversarial training (Madry et al., 2017), which uses robust optimization techniques to render deep learning models resistant to adversarial attacks. Carmon et al.; Najafi et al.; Zhai et al.; Uesato et al. show that unlabeled data can improve adversarial robustness for classification. In particular, the analysis in Carmon et al. (2019) has inspired our analysis in the Gaussian data model. But these studies are for robust classification, while our work focuses on roubst OOD detection where the key challenge is that the auxiliary OOD and test OOD distributions can differ.

Hard Example Mining. Hard example mining was introduced in the work (Sung, 1996) for training face detection models, where they gradually grow the set of background examples by selecting those examples for which the detector triggers a false alarm. The idea has been used extensively for object detection literature (Felzenszwalb et al., 2009; Gidaris & Komodakis, 2015; Shrivastava et al., 2016). Bucher et al. uses hard negative mining for zero-shot classification. To the best of our knowledge, we are the first to explore hard example mining for out-of-distribution detection.

B   Theoretical Analysis

This section provides some theoretical analysis of our method. First, Section B.1 studies a concrete distributional model of the data. It rigorously justifies the benefit of auxiliary OOD data and the benefit of our outlier mining technique in this data model. In particular, it proves that without auxiliary OOD data *any* algorithm will need a lot of data from the in-distribution to achieve reasonable error, while with auxiliary OOD data a simple algorithm can already achieve a small error with far less in-distribution data. This confirms the potential benefit of using auxiliary OOD data. Furthermore, it proves a natural method without outlier mining fails while the outlier mining method succeeds. This demonstrates that not all auxiliary data are useful and our outlier mining can help to discover useful ones for robust OOD detection.

Towards better understanding in more general settings without assuming the Gaussian data model, Section B.2 provides a generic error bound in, giving some insight on why auxiliary OOD data in training time can help detection of outliers from a different distribution in test time.

B.1   Analysis in a Gaussian Model

To understand how the outlier training data affect the generalization, we study a concrete distributional model, which is inspired by the models in (Schmidt et al., 2018; Carmon et al., 2019). In this model, we establish in Section B.1.2 a separation of the in-distribution sample sizes needed in the two cases: with and without auxiliary OOD data for training. We also demonstrate in Section B.1.3 the benefit of outlier mining when the auxiliary OOD data consists of uninformative outliers.

While the theoretical model is simple (in fact, much simpler than the practical data distributions), its simplicity is actually desired for our analytical purpose. More precisely, the separation of the sample sizes under this simple model suggests the same phenomenon can happen in more complicated models. This then means the auxiliary OOD data not only help training but are *necessary* for obtaining detectors with reasonable performance when in-distribution data is limited.

Gaussian Model.   To specify a distributional model for our robust OOD formulation, we need in-distribution $P_{\mathbf{X}}$, family of OOD distributions $\mathcal{Q}$, and the hypothesis class $\mathcal{H}$ for the OOD detector G. When auxiliary OOD data is available, we also need to specify their distribution $U_{\mathbf{X}}$. Let $\mu \in \mathbb{R}^d$ be the mean vector, $\sigma > 0$ be the variance parameter, and $\nu > 0$ be a parameter. In our (μ, σ, ν)-Gaussian model:

- $P_{\mathbf{X}}$ is $\mathcal{N}(\mu, \sigma^2 I)$.
- $\mathcal{Q} = \{\mathcal{N}(-\mu + v, \sigma^2 I) : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$.
- $\mathcal{H} = \{G_\theta(x) = \text{sign}(\theta^\top \mathbf{x}) : \theta \in \mathbb{R}^d\}$. Here $G_\theta(\mathbf{x}) = 1$ means it predicts x to be an in-distribution example, and $G_\theta(\mathbf{x}) = -1$ means it predicts an OOD example.

We are interested in the False Negative Rate $\text{FNR}(G)$ and worst False Positive Rate $\sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(G; Q_{\mathbf{X}}, \Omega_{\infty, \epsilon}(\mathbf{x}))$ over $Q_{\mathbf{X}} \in \mathcal{Q}$ under ℓ_∞ perturbations of magnitude ϵ. For simplicity, we denote them as $\text{FNR}(G)$ and $\text{FPR}(G; Q_{\mathbf{X}})$ in our proofs.

Parameter Setting.   The model parameters are set such that:

1. There exists a classifier that achieves very low errors FPR and FNR.
2. We need n in-distribution data from $P_{\mathbf{X}}$ to learn a classifier with non-trivial robust errors.
3. Using n_0 in-distribution examples from $P_{\mathbf{X}}$ and n' auxiliary OOD data from $U_{\mathbf{X}}$ where n_0 is much smaller than n, we can learn a classifier with non-trivial robust errors.

Here n_0, n, n' are sample sizes whose values are specified later in our analysis.

The family of instances of the Gaussian data model used for our analysis is as follows. First, fix an integer $n_0 > 0$, and an $\epsilon \in (0, 1/2)$, then set the following parameter values:

$$d \gg n_0/\epsilon^4 + n_0 \log^2 d, \quad \|\mu\|_2^2 \in \left(\frac{9d}{10}, \frac{11d}{10}\right), \quad \sigma^2 = \sqrt{dn_0}, \quad \nu \leq \|\mu\|_2/4. \tag{8}$$

To interpret the parameter setting, one can view n_0, ϵ as fixed and d/n_0 as a large number.

B.1.1 EXISTENCE OF ROBUST CLASSIFIERS

We give closed forms of the errors, and show that using $\theta = \mu$ gives small errors under the chosen setting in equation 8. The calculation largely follows that in (Carmon et al., 2019) with some slight modification.

Closed Forms of the Errors. By definition, the FNR of a detector G_θ (on $P_{\mathbf{X}}$) is:

$$\mathrm{FNR}(G_\theta) = \mathbb{P}_{\mathbf{x} \sim P_{\mathbf{X}}}[\theta^\top \mathbf{x} \leq 0] = \mathbb{P}_{\mathbf{x} \sim P_{\mathbf{X}}}\left[\mathcal{N}\left(\frac{\mu^\top \theta}{\sigma\|\theta\|_2}, 1\right) \leq 0\right] =: \Phi\left(\frac{\mu^\top \theta}{\sigma\|\theta\|_2}\right) \tag{9}$$

where

$$\Phi(\mathbf{x}) := \frac{1}{\sqrt{2\pi}} \int_{\mathbf{x}}^{\infty} e^{-t^2/2} dt \tag{10}$$

is the Gaussian error function.

Given a test OOD distribution $Q_v = \mathcal{N}(-\mu + v, \sigma^2 I)$, the robust FPR of G_θ on Q_v is:

$$\mathrm{FPR}(G_\theta; Q_v) = \mathbb{P}_{\mathbf{x} \sim Q_v}\left[\inf_{\|\delta\|_\infty \leq \epsilon} \theta^\top(\mathbf{x} + \delta) \geq 0\right] \tag{11}$$

$$= \mathbb{P}_{\mathbf{x} \sim Q_v}\left[\theta^\top \mathbf{x} + \epsilon\|\theta\|_1 \geq 0\right] \tag{12}$$

$$= \mathbb{P}_{\mathbf{x} \sim Q_v}\left[\mathcal{N}((\mu + v)^\top \theta, (\sigma\|\theta\|_2)^2) \geq -\epsilon\|\theta\|_1\right] \tag{13}$$

$$= \Phi\left(\frac{(\mu + v)^\top \theta}{\sigma\|\theta\|_2} - \frac{\epsilon\|\theta\|_1}{\sigma\|\theta\|_2}\right). \tag{14}$$

Then the worst robust FPR of G_θ on $\mathcal{Q}$ is:

$$\sup_{Q_v \in \mathcal{Q}} \mathrm{FPR}(G_\theta; Q_v) = \sup_{\|v\|_2 \leq \nu} \Phi\left(\frac{(\mu + v)^\top \theta}{\sigma\|\theta\|_2} - \frac{\epsilon\|\theta\|_1}{\sigma\|\theta\|_2}\right) \tag{15}$$

$$= \Phi\left(\frac{\mu^\top \theta}{\sigma\|\theta\|_2} - \frac{\nu}{\sigma} - \frac{\epsilon\|\theta\|_1}{\sigma\|\theta\|_2}\right) \tag{16}$$

$$\leq \Phi\left(\frac{\mu^\top \theta}{\sigma\|\theta\|_2} - \frac{\nu}{\sigma} - \frac{\epsilon\sqrt{d}}{\sigma}\right). \tag{17}$$

Small Errors of G_μ. Given the closed forms, we can now show that G_μ achieves small FNR and FPR in our parameter setting.

$$\mathrm{FNR}(G_\mu) = \Phi\left(\frac{\|\mu\|_2}{\sigma}\right) \leq \Phi\left(\sqrt{\frac{11}{10}}\left(\frac{d}{n_0}\right)^{1/4}\right) \leq e^{-\frac{11}{20}\sqrt{d/n_0}}. \tag{18}$$

$$\sup_{Q_v \in \mathcal{Q}} \mathrm{FPR}(G_\mu; Q_v) \leq \Phi\left(\frac{\|\mu\|_2}{\sigma} - \frac{\nu}{\sigma} - \frac{\epsilon\sqrt{d}}{\sigma}\right) \tag{19}$$

$$\leq \Phi\left(\left(\sqrt{\frac{11}{10}} - \frac{1}{4} - \epsilon\right)\left(\frac{d}{n_0}\right)^{1/4}\right) \leq e^{-\frac{1}{32}\sqrt{d/n_0}}. \tag{20}$$

Therefore, in the regime $d/n_0 \gg 1$, the detector G_μ achieves both small FNR on $P_{\mathbf{X}}$ and robust FPR on any test OOD distribution in $\mathcal{Q}$.

B.1.2 BENEFIT OF AUXILIARY OOD DATA

We will first consider the case when auxiliary OOD data are not available, and give an upper bound (Proposition 4) and a lower bound (Proposition 1). We will then consider the case when auxiliary OOD data are used, and give an upper bound (Proposition 2). Comparing Proposition 1 and Proposition 2 will then justify the benefit of the auxiliary OOD data.

Learning Without Auxiliary OOD Data. Given in-distribution data $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n$, we consider the detector $G_{\hat{\theta}_n}$ given by

$$\hat{\theta}_n = \frac{1}{n} \sum_{i=1}^{n} \mathbf{x}_i. \tag{21}$$

As shown in the closed form solutions, the key factor determining the errors is $\frac{\mu^\top \hat{\theta}_n}{\sigma \|\hat{\theta}_n\|_2}$. To bound this term, we follow the proof of Lemma 1 in (Carmon et al., 2019) and slightly generalizes to the following:

Lemma 1. *There exist numerical constants c_0, c_1, c_2 such that under parameter setting equation 8 and $d/n_0 > c_0$,*

$$\frac{\mu^\top \hat{\theta}_n}{\sigma \|\hat{\theta}_n\|_2} \geq \frac{9}{10} \left(\sqrt{\frac{n_0}{d}} + \frac{n_0}{n} \left(1 + c_1 \left(\frac{n_0}{d} \right)^{1/8} \right) \right)^{-1/2} \tag{22}$$

with probability $\geq 1 - e^{-c_2(d/n_0)^{1/4} \min\{n, (d/n_0)^{1/4}\}}$.

This lemma leads to the following guarantee about learning the OOD detector from in-distribution data only. The error bound 10^{-3} is chosen for simplicity of the statement, but it can be made to arbitrarily small values. Furthermore, the error bound can be made with high probability, while we present the expectation error bound for simplicity.

Proposition 4. *For the same family of instances as in Proposition 1, if $n \geq n_0 \cdot 4\epsilon^2 \sqrt{d/n_0}$, then*

$$\mathbb{E}_{\hat{\theta}_n} \mathrm{FNR}(G_{\hat{\theta}_n}) \leq 10^{-3}, \quad \mathbb{E}_{\hat{\theta}_n} \sup_{Q_\mathbf{x} \in \mathcal{Q}} \mathrm{FPR}(G_{\hat{\theta}_n}; Q_\mathbf{x}, \Omega_{\infty,\epsilon}(\mathbf{x})) \leq 10^{-3}. \tag{23}$$

Proof. By Lemma 1, we have

$$\frac{\mu^\top \hat{\theta}_n}{\sigma \|\hat{\theta}_n\|_2} \geq \frac{9}{10} \left(2 \left(\sqrt{\frac{n_0}{n}} + \sqrt{\frac{n_0}{d}} \right) \right)^{-1/2} \tag{24}$$

with probability $\geq 1 - e^{-c_2(d/n_0)^{1/4} \min\{n, (d/n_0)^{1/4}\}}$. The proposition then comes from the parameter setting equation 8 and the closed form expressions equation 9 and equation 15 of the errors. $\square$

Next we show that the above sample size is nearly optimal (up to a logarithmic factor). That is, a sample size of order $n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{\log d}$ is necessary for *all algorithms* to obtain both non-trivial robust FPR and FNR. We emphasize that this lower bound is information theoretic, i.e., it holds without restriction on the computational power of the learning algorithm and the hypothesis class used for the OOD detector. In particular, it applies not only to the linear classifier considered in Proposition 4 but also to any other learning algorithms.

Proposition 1. *(Bound without auxiliary data) For any $\epsilon \in (0, 1/2)$ and any integer $n_0 > 0$, there exist a family of instances of the Gaussian data model, such that if $n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{16 \log d}$, then for any algorithm $\mathbb{A}_n$, there exists an instance in the family with*

$$\mathbb{E} \left\{ \mathrm{FNR}(\mathbb{A}_n(S)) + \sup_{Q_\mathbf{x} \in \mathcal{Q}} \mathrm{FPR}(\mathbb{A}_n(S); Q_\mathbf{x}, \Omega_{\infty,\epsilon}(\mathbf{x})) \right\} \geq \frac{1}{4}(1 - d^{-1}). \tag{2}$$

Proof. The key for the proof is the observation that robust classification is a special case of our robust OOD problem. More precisely, consider the following robust classification problem. The data $(\mathbf{x}, y)$ with $\mathbf{x} \in \mathbb{R}^d$ and $y \in \{-1, +1\}$ is generated as follows: first draw y uniformly at random, and then draw $\mathbf{x}$ from $\mathcal{N}(y \cdot \mu, \sigma^2 I)$. Given training data $\{(\mathbf{x}_i, y_i)\}_{i=1}^{n}$, the goal is to find classifier $f_\theta(\mathbf{x}) = \mathrm{sign}(\theta^\top \mathbf{x})$ with small robust classification error

$$\mathrm{err}_{\infty,\epsilon}(f_\theta) = \mathbb{E}_{(\mathbf{x},y)} \max_{\|\delta\|_\infty \leq \epsilon} \mathbb{I}[f_\theta(\mathbf{x} + \delta) \neq y]$$

under ℓ_∞ perturbation of magnitude ϵ. It has been shown that (Theorem 6 in (Schmidt et al., 2018) or Theorem 1 in (Carmon et al., 2019)) that when $\mu \sim \mathcal{N}(0, I)$ and $n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{8 \log d}$ and with the parameter setting equation 8, for any learning algorithm $\mathbb{A}_n$

$$\mathbb{E}\mathrm{err}_{\infty,\epsilon}(\mathbb{A}_n(S)) \geq \frac{1}{2}(1 - d^{-1}). \tag{25}$$

Now consider the following variant of the robust OOD problem in the proposition. Suppose $\mu \sim \mathcal{N}(0, I)$. Suppose besides the data from $P_{\mathbf{X}}$, we also have n i.i.d. samples from a test OOD distribution $Q_0 = \mathcal{N}(-\mu, \sigma^2 I)$. Then the above robust classification problem can be reduced to this variant of robust OOD, by viewing the in-distribution data as with label $+1$ and viewing outliers as with label -1. Furthermore, it is clear that the sum of the FNR and FPR is larger than the robust classification error. Then

$$\mathbb{E}\left\{\mathrm{FNR}(\mathbb{A}_n(S)) + \mathrm{FPR}(\mathbb{A}_n(S); Q_0)\right\} \geq \frac{1}{2}(1 - d^{-1}). \tag{26}$$

When d is sufficiently large, we have μ satisfies the condition in equation 8 with probability at least $9/10$. Then

$$\mathbb{E}\left\{\mathrm{FNR}(\mathbb{A}_n(S)) + \mathrm{FPR}(\mathbb{A}_n(S); Q_0) \quad \middle| \quad \|\mu\|_2^2 \in (9d/10, 11d/10)\right\} \geq \frac{1}{4}(1 - d^{-1}). \tag{27}$$

After conditioning, this variant can be reduced to the original robust OOD problem in the proposition and furthermore $Q_0 \in \mathcal{Q}$. Furthermore, the fact that the expectation over the conditional distribution of μ is large implies that there exist an instance of μ with a large error. The statement then follows. $\square$

Learning With Auxiliary OOD Data. Assuming we have access to auxiliary OOD data from a distribution $U_{\mathbf{X}}$ where:

- $U_{\mathbf{X}}$ is defined by the following distribution: first draw v uniformly at random from the ball $\{v : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$, then draw $\tilde{\mathbf{x}}$ from $\mathcal{N}(-\mu + v, \sigma^2 I)$.

Roughly speaking, $U_{\mathbf{X}}$ is a uniform mixture of distributions in $\mathcal{Q}$.

Given in-distribution data $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n$ from $P_{\mathbf{X}}$ and auxiliary OOD data $\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \ldots, \tilde{\mathbf{x}}_{n'}$ from $U_{\mathbf{X}}$, we consider the detector $G_{\hat{\theta}_{n,n'}}$ given by

$$\hat{\theta}_{n,n'} = \frac{1}{n}\sum_{i=1}^{n} \mathbf{x}_i - \frac{1}{n'}\sum_{i=1}^{n'} \tilde{\mathbf{x}}_i. \tag{28}$$

We will show that with $n = n_0$ and sufficiently large n', the detector has small errors.

Again, as shown in the closed form solutions, the key factor determining the errors is $\frac{\mu^\top \hat{\theta}_{n,n'}}{\sigma \|\hat{\theta}_{n,n'}\|_2}$. The following lemma bounds this term.

Lemma 2. *There exist numerical constants c_0, c_1, c_2 such that under parameter setting equation 8 and $d/n_0 > c_0$,*

$$\frac{\mu^\top \hat{\theta}_{n,n'}}{\sigma \|\hat{\theta}_{n,n'}\|_2} \geq \frac{9}{10}\left(\sqrt{\frac{n_0}{d}} + \frac{n_0}{n + n'}\left(1 + c_1\left(\frac{n_0}{d}\right)^{1/8}\right)\right)^{-1/2} \tag{29}$$

with probability $\geq 1 - e^{-c_2(d/n_0)^{1/4}\min\{n+n',(d/n_0)^{1/4}\}} - e^{-c_2 n'}$.

Proof. The proof follows the argument of Lemma 1 in (Carmon et al., 2019) but needs some modifications accommodating the difference in learning θ. Recall the generation of $\mathbf{x}'_i$: first draw v_i uniformly at random from the ball $\mathbb{B}(\nu) := \{v : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$, then draw $\bar{\mathbf{x}}'_i$ from $\mathcal{N}(\mu, \sigma^2 I)$, and finally let $\mathbf{x}'_i = v_i - \bar{\mathbf{x}}'_i$. So we have

$$\hat{\theta}_{n,n'} = \frac{1}{n + n'}\left(\sum_{i=1}^{n}\mathbf{x}_i + \sum_{i=1}^{n'}\bar{\mathbf{x}}'_i\right) - \frac{1}{n + n'}\left(\sum_{i=1}^{n'} v_i\right) \tag{30}$$

$$= \mu + \delta + \delta_v \tag{31}$$

where

$$\delta = \frac{1}{n+n'}\left(\sum_{i=1}^{n}\mathbf{x}_i + \sum_{i=1}^{n'}\bar{\mathbf{x}'}_i\right) - \mu \sim \mathcal{N}(0, \frac{\sigma^2}{n+n'}I), \tag{32}$$

$$\delta_v = -\frac{1}{n+n'}\left(\sum_{i=1}^{n'}v_i\right). \tag{33}$$

To lower bound the term $\frac{\mu^\top \hat{\theta}_{n,n'}}{\|\hat{\theta}_{n,n'}\|_2}$, we upper bound its squared inverse:

$$\frac{\|\hat{\theta}_{n,n'}\|_2^2}{(\mu^\top \hat{\theta}_{n,n'})^2} = \frac{\|\mu + \delta + \delta_v\|_2^2}{(\|\mu\|_2^2 + \mu^\top\delta + \mu^\top\delta_v)^2} \tag{34}$$

$$= \frac{1}{\|\mu\|_2^2} + \frac{\|\delta + \delta_v\|_2^2 - \frac{1}{\|\mu\|_2^2}(\mu^\top\delta + \mu^\top\delta_v)^2}{(\|\mu\|_2^2 + \mu^\top\delta + \mu^\top\delta_v)^2} \tag{35}$$

$$\leq \frac{1}{\|\mu\|_2^2} + \frac{2\|\delta\|_2^2 + 2\|\delta_v\|_2^2}{(\|\mu\|_2^2 + \mu^\top\delta + \mu^\top\delta_v)^2}. \tag{36}$$

For δ, we have

$$\|\delta\|_2^2 \sim \frac{\sigma^2}{n+n'}\chi_d^2 \quad \text{and} \quad \frac{\mu^\top\delta}{\|\mu\|_2} \sim \mathcal{N}\left(0, \frac{\sigma^2}{n+n'}\right). \tag{37}$$

So standard concentration bounds give

$$\mathbb{P}\left(\|\delta\|_2^2 \geq \frac{\sigma^2}{n+n'}\left(d+\frac{1}{\sigma}\right)\right) \leq e^{-d/8\sigma^2} \quad \text{and} \quad \mathbb{P}\left(\frac{\mu^\top\delta}{\|\mu\|_2} \geq (\sigma\|\mu\|)^{1/2}\right) \leq 2e^{-(n+n')\|\mu\|_2/2\sigma}. \tag{38}$$

For δ_v, by subguassian concentration bounds, we have

$$\mathbb{P}\left(\|\delta_v\|_2 \geq \frac{C\nu}{\sqrt{n'}}\right) \leq e^{-cn'} \tag{39}$$

for some numeric constants c and C. Suppose the event $\|\delta_v\|_2 < \frac{C\nu}{\sqrt{n'}}$ is true. Then

$$|\mu^\top\delta_v| \leq \|\mu\|_2\|\delta_v\|_2 \leq \frac{C\nu\|\mu\|_2}{\sqrt{n'}}. \tag{40}$$

Plugging the concentration bounds in equation 34 and doing the same manipulation leads to the bound. To finish the proof, we also need to show $\mu^\top\hat{\theta}_{n,n'} > 0$, which can be shown by the same argument as in (Carmon et al., 2019). □

We then get the following guarantee. Again, the error bound 10^{-3} is chosen for simplicity of the statement, but it can be made to arbitrarily small values.

Proposition 2. *(Error bound with ideal auxiliary data) Consider the same family of instances as in Preposition 1, with n' auxiliary OOD data from $U_\mathbf{X}$ specified above. If $n \geq n_0$ and $n' \geq n_0 \cdot 4\epsilon^2\sqrt{d/n_0}$, then*

$$\mathbb{E}_{\hat{\theta}_{n,n'}}\text{FNR}(G_{\hat{\theta}_{n,n'}}) \leq 10^{-3}, \quad \mathbb{E}_{\hat{\theta}_{n,n'}}\sup_{Q_\mathbf{X}\in\mathcal{Q}}\text{FPR}(G_{\hat{\theta}_{n,n'}}; Q_\mathbf{X}, \Omega_{\infty,\epsilon}(\mathbf{x})) \leq 10^{-3}. \tag{3}$$

Proof. The proposition comes from Lemma 2, the parameter setting equation 8, and the closed form expressions equation 9 and equation 15 of the errors. □

B.1.3 BENEFIT OF OUTLIER MINING

The above Gaussian example shows the benefit of having auxiliary OOD data for training. All the auxiliary OOD data given in the example are implicitly related to the ideal parameter for the detector $\theta^* = \mu$ and thus are informative for learning the detector. However, this may not be the case in practice: typically only part of the auxiliary OOD data are informative, while the remaining are not very useful or even can be harmful for the learning. In this section, we study such an example, and shows that how outlier mining can help to identify informative data and improve the learning performance.

Suppose the algorithm gets n in-distribution data $\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n\}$ i.i.d. from $P_{\mathbf{X}}$ and n' auxiliary OOD data $\{\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \ldots, \tilde{\mathbf{x}}_{n'}\}$ for training. Instead of from $U_{\mathbf{X}}$ specified above, the auxiliary OOD data are i.i.d. from the distribution U_{mix}.

- U_{mix} is a uniform mixture of $\mathcal{N}(-\mu, \sigma^2 I)$ and $\mathcal{N}(\mu_o, \sigma^2 I)$ for $\mu_o = 10\mu$.

That is, the distribution is defined by the following process: with probability $1/2$ sample the outlier from the informative part $\mathcal{N}(-\mu, \sigma^2 I)$, and with probability $1/2$ sample the outlier from the uninformative part $\mathcal{N}(\mu_o, \sigma^2 I)$. We also note that $\mu_0 = 10\mu$ is chosen for simplicity of analysis. μ_0 can also be $c\mu$ for some sufficiently large $c > 1$, or even $\mu_o = c\mu + c'\mu_\perp$ for a sufficiently large $c > 1$, a small c' and a unit vector $\mu_\perp$ perpendicular to μ. Our analysis still go through with such assumptions.

Naïve Method Without Outlier Mining. It is clear that naïvely applying the method in the previous section can lead to high errors: with n in-distribution examples from $P_{\mathbf{X}}$ and $n' = n$ auxiliary OOD data from U_{mix}, when $n \to \infty$, we have $\hat{\theta}_{n,n'} \to -7\mu/4$ which has the worst errors among all detectors.

With Outlier Mining. Here we analyze the following algorithm using the outlier mining approach. The algorithm is simpler than what we used in Section 4 but shares the same intuition.

First, we use the n in-distribution data points to get an intermediate solution:

$$\hat{\theta}_{\mathrm{int}} = \frac{1}{n} \sum_{i=1}^{n} \mathbf{x}_i. \tag{41}$$

We define the confidence score of a point $\tilde{\mathbf{x}}$ being in-distribution as:

$$f(\tilde{\mathbf{x}}) = \sigma(t) = \frac{1}{1 + e^{-t}}, \quad \text{where} \ \ t(\tilde{\mathbf{x}}) = \frac{\tilde{\mathbf{x}}^\top \hat{\theta}_{\mathrm{int}}}{d}. \tag{42}$$

Here $\sigma(t) = \frac{1}{1+e^{-t}}$ is the sigmoid function. We then select outlier training data whose confidence fall into an interval $[a, b]$ and use them to learn the final solution:

$$\hat{\theta}_{\mathrm{om}} = \frac{\sum_{i=1}^{n'} (-\tilde{\mathbf{x}}_i) \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}}{\sum_{i=1}^{n'} \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}} \tag{43}$$

where $\mathbb{I}\{\cdot\}$ is the indicator function.

Proposition 3. *(Error bound with outlier mining.) Consider the same family of instances as in Proposition 2, with n' auxiliary OOD data from U_{mix} specified above. There exist thresholds a and b for $\hat{\theta}_{\mathrm{om}}$ and a universal constant $c > 0$ such that if $n \geq c(n_0 \log d + \sqrt{dn_0})$ and $n' \geq (d + n_0 \cdot 4\epsilon^2)\sqrt{d/n_0}$, then $\hat{\theta}_{\mathrm{om}}$ has the same error guarantees as in Proposition 2.*

Proof. Let $a = \sigma(-3/2), b = \sigma(-1/2)$. By definition we have

$$\delta_{\mathrm{om}} := \hat{\theta}_{\mathrm{om}} - \mu = \frac{\sum_{i=1}^{n'} (-\mu - \tilde{\mathbf{x}}_i) \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}}{\sum_{i=1}^{n'} \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}}. \tag{44}$$

By the closed form expressions equation 9 and equation 15 of the errors, it is sufficient to lower bound the key term $\frac{\mu^\top \hat{\theta}_{\mathrm{om}}}{\|\hat{\theta}_{\mathrm{om}}\|_2}$, which comes down to show that δ_{om} is small.

First, let's consider $\hat{\theta}_{\text{int}}$. Let $\delta_{\text{int}} := \hat{\theta}_{\text{int}} - \mu$. Then

$$\|\delta_{\text{int}}\|_2^2 \sim \frac{\sigma^2}{n}\chi_d^2 \quad \text{and} \quad \frac{\mu^\top \delta_{\text{int}}}{\|\mu\|_2} \sim \mathcal{N}\left(0, \frac{\sigma^2}{n}\right). \tag{45}$$

So standard concentration bounds give

$$\mathbb{P}\left(\|\delta_{\text{int}}\|_2^2 \geq \frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)\right) \leq e^{-d/8\sigma^2} \quad \text{and} \quad \mathbb{P}\left(\frac{|\mu^\top \delta_{\text{int}}|}{\|\mu\|_2} \geq \sqrt{\frac{d}{n}}\right) \leq 2e^{-d/2\sigma^2}. \tag{46}$$

So with probability $\geq 1 - 3e^{-d/8\sigma^2}$ over the randomness of the n in-distribution points, we have the good event $\mathcal{G}_{\text{int}}$: $\|\delta_{\text{int}}\|_2^2 \leq \frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)$ and $\frac{|\mu^\top \delta_{\text{int}}|}{\|\mu\|_2} \leq \sqrt{\frac{d}{n}}$.

Now, condition on a fix $\hat{\theta}_{\text{int}}$ satisfying $\mathcal{G}_{\text{int}}$, and consider $\hat{\theta}_{\text{om}}$. Define

$$z_i := -\mu - \tilde{\mathbf{x}}_i, \tag{47}$$
$$\mathbb{I}_{0i} := \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}, \tag{48}$$
$$\mathbb{I}_{1i} := \mathbb{I}\{\tilde{\mathbf{x}}_i \text{ is from } \mathcal{N}(-\mu, \sigma^2 I)\}, \tag{49}$$
$$\mathbb{I}_{2i} := \mathbb{I}\{\tilde{\mathbf{x}}_i \text{ is from } \mathcal{N}(\mu_o, \sigma^2 I)\}. \tag{50}$$

For simplicity, let's omit the subscript i and consider a sample $\tilde{\mathbf{x}}$ from U_{mix}, and the corresponding variables $z, \mathbb{I}_0, \mathbb{I}_1$, and $\mathbb{I}_2$. Since $\mathbb{I}_1 + \mathbb{I}_2 = 1$,

$$(-\mu - \tilde{\mathbf{x}})\mathbb{I}\{f(\tilde{\mathbf{x}}) \in [a, b]\} = z\mathbb{I}_0\mathbb{I}_1 + z\mathbb{I}_0\mathbb{I}_2. \tag{51}$$

Case 1. Let's first consider the case when $\tilde{\mathbf{x}}$ is from $\mathcal{N}(-\mu, \sigma^2 I)$. More precisely, we condition on a fixed $\hat{\theta}_{\text{int}}$ and condition on $\mathbb{I}_1 = 1$. Then $z \sim \mathcal{N}(0, \sigma^2 I)$ and it can be decomposed along the direction $\bar{\theta}_{\text{int}} := \hat{\theta}_{\text{int}}/\|\hat{\theta}_{\text{int}}\|_2$ as follows:

$$z = s \cdot \bar{\theta}_{\text{int}} + z_2 \tag{52}$$

where $s \sim \mathcal{N}(0, \sigma^2)$ and z_2 is a Gaussian distribution in the subspace orthogonal to $\bar{\theta}_{\text{int}}$. Then

$$t(\tilde{\mathbf{x}}) = \frac{\tilde{\mathbf{x}}^\top \hat{\theta}_{\text{int}}}{d} = -\frac{\mu^\top \hat{\theta}_{\text{int}}}{d} - \frac{s\|\hat{\theta}_{\text{int}}\|_2}{d}. \tag{53}$$

Therefore, we have

$$\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] = \mathbb{E}[s \cdot \bar{\theta}_{\text{int}}\mathbb{I}_0|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] + \mathbb{E}[z_2\mathbb{I}_0|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] \tag{54}$$

Clearly the second term is 0 since $z_2\mathbb{I}_0$ is symmetric. So

$$\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] = \mathbb{E}[s \cdot \bar{\theta}_{\text{int}}\mathbb{I}\{f(\tilde{\mathbf{x}}) \in [a, b]\}|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] \tag{55}$$

$$= \mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}\right] \cdot \bar{\theta}_{\text{int}} \tag{56}$$

$$= \mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right] \cdot \bar{\theta}_{\text{int}} \tag{57}$$

where

$$a' = -\frac{\mu^\top \hat{\theta}_{\text{int}}}{\|\hat{\theta}_{\text{int}}\|_2} - \frac{\sigma^{-1}(b)d}{\|\hat{\theta}_{\text{int}}\|_2} \tag{58}$$

$$= \frac{-2\mu^\top \hat{\theta}_{\text{int}} + d}{2\|\hat{\theta}_{\text{int}}\|_2} \tag{59}$$

$$= \frac{-2\mu^\top \delta_{\text{int}} - 2\|\mu\|_2^2 + d}{2\|\hat{\theta}_{\text{int}}\|_2}, \tag{60}$$

$$b' = -\frac{\mu^\top \hat{\theta}_{\text{int}}}{\|\hat{\theta}_{\text{int}}\|_2} - \frac{\sigma^{-1}(a)d}{\|\hat{\theta}_{\text{int}}\|_2} \tag{61}$$

$$= \frac{-2\mu^\top \hat{\theta}_{\text{int}} + 3d}{2\|\hat{\theta}_{\text{int}}\|_2} \tag{62}$$

$$= \frac{-2\mu^\top \delta_{\text{int}} - 2\|\mu\|_2^2 + 3d}{2\|\hat{\theta}_{\text{int}}\|_2}. \tag{63}$$

By the bound on $|\mu^\top \delta_{\text{int}}|$, we have

$$|\mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right]| \leq \int_{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(8/10 - 4/\sqrt{n})}^{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(12/10 + 4/\sqrt{n})} \sigma t \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{64}$$

$$\leq \frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2} \cdot \sigma \cdot \frac{2d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2} \cdot \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{d}{4\sigma\|\hat{\theta}_{\text{int}}\|_2}\right)^2}. \tag{65}$$

Given the bound on $\|\delta_{\text{int}}\|_2^2$, we have

$$\|\hat{\theta}_{\text{int}}\|_2 \leq \|\mu\|_2 + \|\delta_{\text{int}}\|_2 \leq \|\mu\|_2 + \sqrt{\frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)} \leq \|\mu\|_2 + \sqrt{\frac{2\sigma^2 d}{n}}, \tag{66}$$

$$\|\hat{\theta}_{\text{int}}\|_2 \geq \|\mu\|_2 - \|\delta_{\text{int}}\|_2 \geq \|\mu\|_2 - \sqrt{\frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)} \geq \|\mu\|_2 - \sqrt{\frac{2\sigma^2 d}{n}}. \tag{67}$$

Since $n \geq C n_0 \log d$ and $d \geq C^2 n_0 \log^2 d$ for a sufficiently large C, we have

$$\frac{\sigma^2\|\hat{\theta}_{\text{int}}\|_2^2}{d^2} \leq \frac{\sigma^2 d (11/10 + \sqrt{2\sigma^2/n})^2}{d^2} \leq 4\sqrt{\frac{n_0}{d}} + \frac{8n_0}{n} \leq \frac{12}{C \log d} \tag{68}$$

and thus

$$|\mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right]| \leq \frac{d^2}{\sigma\|\hat{\theta}_{\text{int}}\|_2^2} \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{d}{4\sigma\|\hat{\theta}_{\text{int}}\|_2}\right)^2} \tag{69}$$

$$\leq \frac{d^2}{\sigma\|\hat{\theta}_{\text{int}}\|_2^2} e^{-\frac{d^2}{32\sigma^2\|\hat{\theta}_{\text{int}}\|_2^2}} \tag{70}$$

$$\leq \frac{1}{d^2}. \tag{71}$$

Combining with $\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1|\mathbb{I}_1 = 0, \hat{\theta}_{\text{int}}] = 0$ we get

$$\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1|\hat{\theta}_{\text{int}}] = c_1 \cdot \bar{\theta}_{\text{int}} \tag{72}$$

for some c_1 satisfying $|c_1| \leq 1/d^2$. Furthermore, $z\mathbb{I}_0\mathbb{I}_1 \mid \hat{\theta}_{\text{int}}$ is truncated Gaussian and thus is sub-Gaussian with sub-Gaussian norm bounded by σ. Then by sub-Gaussian concentration bounds, we have

$$\mathbb{P}\left(\left|\sum_{i=1}^{n'} \mu^\top z_i \mathbb{I}_{0i}\mathbb{I}_{1i} - \sum_{i=1}^{n'} \mu^\top \mathbb{E}[z_i\mathbb{I}_{0i}\mathbb{I}_{1i}|\hat{\theta}_{\text{int}}]\right| \geq \sqrt{n'd} \mid \hat{\theta}_{\text{int}}\right) \leq e^{-cd/\sigma^2}, \tag{73}$$

$$\mathbb{P}\left(\left\|\sum_{i=1}^{n'} z_i\mathbb{I}_{0i}\mathbb{I}_{1i}\right\|_2 \geq 4\sigma\sqrt{n'd} + 2\sqrt{n'd} \mid \hat{\theta}_{\text{int}}\right) \leq e^{-d/\sigma^2}. \tag{74}$$

for some constant $c > 0$. In other words, with probability $\geq 1 - 2e^{-cd/\sigma^2}$, we have

$$\left|\sum_{i=1}^{n'} \mu^\top z_i\mathbb{I}_{0i}\mathbb{I}_{1i}\right| \leq \sqrt{n'd} + \frac{n'}{d^{3/2}}, \tag{75}$$

$$\left\|\sum_{i=1}^{n'} z_i\mathbb{I}_{0i}\mathbb{I}_{1i}\right\|_2 \leq 6\sigma\sqrt{n'd}. \tag{76}$$

Conditioned on $\mathbb{I}_1 = 1$, we also have

$$\mathbb{E}[\mathbb{I}_0 \mathbb{I}_1 | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] = \mathbb{P}(s \in [a', b']) \tag{77}$$

$$\geq \int_{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(-8/10+4/\sqrt{n})}^{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(8/10-4/\sqrt{n})} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{78}$$

$$\geq 1 - 2\int_{\frac{d}{4\sigma\|\hat{\theta}_{\text{int}}\|_2}}^{+\infty} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{79}$$

$$\geq 1 - 2\int_{\frac{\sqrt{C\log d}}{12}}^{+\infty} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{80}$$

$$\geq 1 - \frac{1}{d}. \tag{81}$$

Let $m = \frac{n'}{2}\left(1 - \frac{1}{d}\right)$. Then by Chernoff's bound, we have

$$\mathbb{P}\left(\left|\sum_{i=1}^{n'} \mathbb{I}_{0i}\mathbb{I}_{1i} - m\right| \geq \frac{1}{2}m\right) \leq e^{-c'm} \tag{82}$$

for an absolute constant $c' > 0$. That is, with probality $\geq 1 - e^{-cn'}$, we have $\sum_{i=1}^{n'} \mathbb{I}_{0i}\mathbb{I}_{1i} \geq n'/5$.

Case 2. Next, let's consider the case when $\tilde{\mathbf{x}}$ is from $\mathcal{N}(\mu_o, \sigma^2 I)$. More precisely, we condition on a fixed $\hat{\theta}_{\text{int}}$ and condition on $\mathbb{I}_2 = 1$. Similar to case 1, we have

$$z = -11\mu + s \cdot \bar{\theta}_{\text{int}} + z_2 \tag{83}$$

where $s \sim \mathcal{N}(0, \sigma^2)$ and z_2 is a Gaussian distribution in the subspace orthogonal to $\bar{\theta}_{\text{int}}$. So

$$\mathbb{E}[(z + 11\mu)\mathbb{I}_0\mathbb{I}_2 | \mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}] = \mathbb{E}[s\mathbb{I}_0 | \mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}] \cdot \bar{\theta}_{\text{int}}. \tag{84}$$

For this,

$$\mathbb{E}[s\mathbb{I}\{f(\tilde{\mathbf{x}}) \in [a, b]\} | \mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}] \cdot \bar{\theta}_{\text{int}} = \mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a'', b'']\}\right] \cdot \bar{\theta}_{\text{int}} \tag{85}$$

where

$$a'' = \frac{-20\mu^\top \delta_{\text{int}} - 20\|\mu\|_2^2 + d}{2\|\hat{\theta}_{\text{int}}\|_2}, \tag{86}$$

$$b'' = \frac{-20\mu^\top \delta_{\text{int}} - 20\|\mu\|_2^2 + 3d}{2\|\hat{\theta}_{\text{int}}\|_2}. \tag{87}$$

By the bound on $|\mu^\top \delta_{\text{int}}|$ and $\|\delta_{\text{int}}\|_2$, we have

$$|\mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a'', b'']\}\right]| \leq \left|\int_{\frac{-d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(21+20/\sqrt{n})}^{\frac{-d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(15-20/\sqrt{n})} \sigma t \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt\right| \tag{88}$$

$$\leq \frac{8d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2} \sigma \frac{22d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2} \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{14d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}\right)^2} \tag{89}$$

$$\leq \frac{44d^2}{\sigma\|\hat{\theta}_{\text{int}}\|_2^2} e^{-\frac{20d^2}{\sigma^2\|\hat{\theta}_{\text{int}}\|_2^2}} \tag{90}$$

$$\leq \frac{1}{d^2}. \tag{91}$$

We also have

$$\left| \mathbb{E}\left[\mathbb{I}_0 \mathbb{I}_2 | \mathbb{I}_2 = 1, \hat{\theta}_{\mathrm{int}} \right] \right| = |\mathbb{E}\left[\mathbb{I}\{s \in [a'', b'']\} \right]| \tag{92}$$

$$\leq \int_{\frac{-d}{2\sigma\|\hat{\theta}_{\mathrm{int}}\|_2}(21+20/\sqrt{n})}^{\frac{-d}{2\sigma\|\hat{\theta}_{\mathrm{int}}\|_2}(15-20/\sqrt{n})} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{93}$$

$$\leq \frac{d}{2\sigma\|\hat{\theta}_{\mathrm{int}}\|_2}(6 + 40/\sqrt{n}) \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{14d}{2\sigma\|\hat{\theta}_{\mathrm{int}}\|_2}\right)^2} \tag{94}$$

$$\leq \frac{1}{d^3}. \tag{95}$$

Combining the above, we have

$$\mathbb{E}[(z + 11\mu)\mathbb{I}_0\mathbb{I}_2 | \hat{\theta}_{\mathrm{int}}] = c_1 \cdot \bar{\theta}_{\mathrm{int}} \tag{96}$$

for a constant c_1 satisfying $|c_1| \leq 1/d^2$. Furthermore, $(z + 11\mu)\mathbb{I}_0\mathbb{I}_2 \mid \hat{\theta}_{\mathrm{int}}$ is truncated Gaussian and thus is sub-Gaussian with sub-Gaussian norm bounded by σ. Then by sub-Gaussian concentration bounds, we have

$$\mathbb{P}\left(\left| \sum_{i=1}^{n'} \mu^\top (z_i + 11\mu)\mathbb{I}_{0i}\mathbb{I}_{2i} - \sum_{i=1}^{n'} \mu^\top \mathbb{E}[(z_i + 11\mu)\mathbb{I}_{0i}\mathbb{I}_{2i}|\hat{\theta}_{\mathrm{int}}] \right| \geq \sqrt{n'd} \mid \hat{\theta}_{\mathrm{int}} \right) \leq e^{-cd/\sigma^2}, \tag{97}$$

$$\mathbb{P}\left(\left\| \sum_{i=1}^{n'} (z_i + 11\mu)\mathbb{I}_{0i}\mathbb{I}_{2i} \right\|_2 \geq 4\sigma\sqrt{n'd} + 2\sqrt{n'd} \mid \hat{\theta}_{\mathrm{int}} \right) \leq e^{-d/\sigma^2}, \tag{98}$$

for some constant $c > 0$. Also by Hoeffding's bound, we have

$$\mathbb{P}\left(\left| \sum_{i=1}^{n'} \mathbb{I}_{0i}\mathbb{I}_{2i} - \sum_{i=1}^{n'} \mathbb{E}[\mathbb{I}_{0i}\mathbb{I}_{2i}|\hat{\theta}_{\mathrm{int}}] \right| \geq \sqrt{n'd/\sigma^2} \mid \hat{\theta}_{\mathrm{int}} \right) \leq 2e^{-2d/\sigma^2}. \tag{99}$$

In other words, with probability $\geq 1 - 4e^{-cd/\sigma^2}$, we have

$$\left| \sum_{i=1}^{n'} \mu^\top z_i \mathbb{I}_{0i}\mathbb{I}_{2i} \right| \leq \sqrt{n'd} + 22d\sqrt{n'd}\sigma^2 + \frac{n'}{d^2}\sqrt{d} + 22d \cdot \frac{n'}{d^3} \leq \sqrt{n'd}\left(1 + \frac{22d}{\sigma}\right) + \frac{n'}{d^{3/2}}, \tag{100}$$

$$\left\| \sum_{i=1}^{n'} z_i \mathbb{I}_{0i}\mathbb{I}_{2i} \right\|_2 \leq 6\sigma\sqrt{n'd} + 22\sqrt{d}\left(\sqrt{\frac{n'd}{\sigma^2}} + \frac{n'}{d^3}\right) \leq \sqrt{n'd}\left(6\sigma + 22\sqrt{\frac{d}{\sigma^2}}\right) + \frac{22n'}{d^{5/2}}. \tag{101}$$

Combining equation 73, equation 74, equation 82 and equation 100, equation 101 together, we get with probability $\geq 1 - Ce^{-cd/\sigma^2}$,

$$|\mu^\top \delta_{\mathrm{om}}| \leq C\sqrt{\frac{d}{n'}}\left(1 + \frac{22d}{\sigma}\right) + \frac{C}{d^{3/2}}, \tag{102}$$

$$\|\delta_{\mathrm{om}}\|_2 \leq C\sqrt{\frac{d}{n'}}\left(6\sigma + 22\sqrt{\frac{d}{\sigma^2}}\right) + \frac{C}{d^{5/2}}. \tag{103}$$

Then $\frac{\mu^\top \hat{\theta}_{\text{om}}}{\|\hat{\theta}_{\text{om}}\|_2}$ can be lower bounded by

$$\frac{\mu^\top \hat{\theta}_{\text{om}}}{\|\hat{\theta}_{\text{om}}\|_2} = \frac{\mu^\top \mu + \mu^\top \delta_{\text{om}}}{\|\mu + \delta_{\text{om}}\|_2} \tag{104}$$

$$\geq \frac{\mu^\top \mu + \mu^\top \delta_{\text{om}}}{\|\mu\|_2 + \|\delta_{\text{om}}\|_2} \tag{105}$$

$$\geq \frac{d(1 - 1/\sqrt{d})}{\sqrt{d}(1 + 1/\sqrt{d})} \tag{106}$$

$$\geq \sqrt{d}\left(1 - \frac{2}{\sqrt{d}}\right). \tag{107}$$

The proof is completed by plugging the above into the closed form expressions equation 9 and equation 15 of the errors. □

B.2 A GENERAL ERROR BOUND

The interesting questions related to our method are: **(1)** why auxiliary OOD data from $U_\mathbf{X}$ helps? **(2)** why the detector G trained on $U_\mathbf{X}$ generalizes to different OOD distributions $Q_\mathbf{X}$ in test time?

To see what $Q_\mathbf{X}$ can benefit from the auxiliary OOD data, we adopt the domain adaption framework (Ben-David et al., 2010). Recall that in domain adaptation there are two domains s, t, each being a distribution over the input space $\mathcal{X}$ and label space $\{-1, 1\}$. A classifier is trained on s then applied on t. At a high level, we view our OOD detection problem as classification, where the source domain s is $P_\mathbf{X}$ with labels 1 and $U_\mathbf{X}$ with labels -1, and the target domain t is $P_\mathbf{X}$ with labels 1 and $Q_\mathbf{X}$ with label -1.

We focus on the FPR metric below; the argument for FNR is similar. Suppose we learn the OOD detector from a hypothesis class $\mathcal{G}$. Following Ben-David et al. (2010), we define (a variant) of the divergence of $Q_\mathbf{X}$ and $U_\mathbf{X}$ w.r.t. the hypothesis class $\mathcal{G}$ as

$$d_\mathcal{G}(Q_\mathbf{X}, U_\mathbf{X}) = \sup_{G, G' \in \mathcal{G}} v(G, G'; Q_\mathbf{X}) - v(G, G'; U_\mathbf{X})$$

where

$$v(G, G'; D) = \text{FPR}(G; D, \Omega) - \text{FPR}(G'; D, \Omega)$$

is the error difference of G and G' on the distribution D.

The divergence upper bounds the change of the hypothesis error difference between $Q_\mathbf{X}$ and $U_\mathbf{X}$. If it is small, then for any $G, G' \in \mathcal{G}$ where G has a smaller error than G' in $U_\mathbf{X}$, we know that G will also have a smaller (or not too larger) error than G' in $Q_\mathbf{X}$. That is, if the divergence is small, then the ranking of the hypotheses w.r.t. the error is roughly the same in both distributions. This *rank-preserving* property thus makes sure that a good hypothesis learned in $U_\mathbf{X}$ will also be good for $Q_\mathbf{X}$.

Now we show that, if $d_\mathcal{G}(Q_\mathbf{X}, U_\mathbf{X})$ is small (i.e., $Q_\mathbf{X}$ and $U_\mathbf{X}$ are aligned w.r.t. the class $\mathcal{G}$), then a detector G with small FPR on $U_\mathbf{X}$ will also have small FPR on $Q_\mathbf{X}$.

Proposition 5. *For any $G \in \mathcal{G}$,*

$$\text{FPR}(G; Q_\mathbf{X}, \Omega) \leq \inf_{G^* \in \mathcal{G}} \text{FPR}(G^*; Q_\mathbf{X}, \Omega) + \text{FPR}(G; U_\mathbf{X}, \Omega) + d_\mathcal{G}(Q_\mathbf{X}, U_\mathbf{X}).$$

Proof. For simplicity, we omit Ω from $\text{FPR}(G; Q_\mathbf{X}, \Omega)$. For any $G^* \in \mathcal{G}$, we have

$$\text{FPR}(G; Q_\mathbf{X}) = \text{FPR}(G^*; Q_\mathbf{X}) + \text{FPR}(G; Q_\mathbf{X}) - \text{FPR}(G^*; Q_\mathbf{X}) \tag{108}$$

$$= \text{FPR}(G^*; Q_\mathbf{X}) + \text{FPR}(G; U_\mathbf{X}) - \text{FPR}(G^*; U_\mathbf{X}) \tag{109}$$

$$+ [(\text{FPR}(G; Q_\mathbf{X}) - \text{FPR}(G^*; Q_\mathbf{X})) - (\text{FPR}(G; U_\mathbf{X}) - \text{FPR}(G^*; U_\mathbf{X}))]. \tag{110}$$

The last term is

$$(\text{FPR}(G; Q_\mathbf{X}) - \text{FPR}(G^*; Q_\mathbf{X})) - (\text{FPR}(G; U_\mathbf{X}) - \text{FPR}(G^*; U_\mathbf{X})) \tag{111}$$

$$= v(G, G^*; Q_\mathbf{X}) - v(G, G^*; U_\mathbf{X}) \tag{112}$$

$$\leq d_\mathcal{G}(Q_\mathbf{X}, U_\mathbf{X}). \tag{113}$$

Figure 3: An illustration example to explain why $U_{\mathbf{X}}$ helps to get a good detector G_r. With $U_{\mathbf{X}}$, we can prune away hypotheses G_r for any $r \geq 1.9$. Thus, the resulting detector G_r can detect OOD samples from $Q_{\mathbf{X}}$ successfully and robustly.

Therefore,

$$\mathrm{FPR}(G; Q_{\mathbf{X}}) \leq \mathrm{FPR}(G^*; Q_{\mathbf{X}}) + \mathrm{FPR}(G; U_{\mathbf{X}}) + d_{\mathcal{G}}(Q_{\mathbf{X}}, U_{\mathbf{X}}). \tag{114}$$

Taking $\inf$ over $G^* \in \mathcal{G}$ completes the proof. $\qquad\square$

The error of the detector is bounded by three terms: the best error, the error on the training distributions, and the divergence between $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$. Assuming that there exists a ground-truth detector with a small test error, and that the optimization can lead to a small training error, the test error is then characterized by the divergence. So in this case, as long as the rankings of the hypotheses (according to the error) on $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ are similar, detectors learned on $U_{\mathbf{X}}$ can generalize to $Q_{\mathbf{X}}$.

An illustration example. In this example, the in-distribution $P_{\mathbf{X}}$ is uniform over the disk around the origin in $\mathbb{R}^2$ with radius 1, $U_{\mathbf{X}}$ is uniform over the disk around $(0, 3)$ with radius 1, and $Q_{\mathbf{X}}$ is uniform over the disk around $(3, 0)$ with radius 1. Assume the adversary budget is $\epsilon = 0.1$, i.e., $\Omega_{\infty,\epsilon} = \{\|\delta\|_{\infty} \leq 0.1\}$. The hypothesis class for the detector contains all functions of the form $G_r(x) = 2\mathbb{I}[\|x\|_2 \leq r] - 1$ with parameter r. See Figure 3.

The example first shows the effect of the auxiliary OOD data: $U_{\mathbf{X}}$ helps prune away hypotheses G_r for any $r \geq 1.9$. Furthermore, it also shows how learning over $U_{\mathbf{X}}$ can generalize to $Q_{\mathbf{X}}$. Although $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ have non-overlapping supports, $U_{\mathbf{X}}$ helps to calibrate the error of the hypotheses, so any good detector trained on $P_{\mathbf{X}}$ and $U_{\mathbf{X}}$ can be used for distinguishing $P_{\mathbf{X}}$ and $Q_{\mathbf{X}}$. Formally, the $d_{\mathcal{G}}$ is small in Proposition 5.

The analysis also shows the importance of training on *perturbed* instances from the auxiliary OOD data $U_{\mathbf{X}}$. Not using perturbation is equivalent to using $\Omega = \{\mathbf{0}\}$. In this case, the analysis shows that it only guarantees the error on *unperturbed* instances from $Q_{\mathbf{X}}$, even if $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ has small divergence and the learned detector can have small training error on $U_{\mathbf{X}}$.

C DETAILS OF EXPERIMENTS

C.1 EXPERIMENTAL SETTINGS

Software and Hardware. We run all experiments with PyTorch and NVIDIA GeForce RTX 2080Ti GPUs.

Number of Evaluation Runs. We run all experiments once with fixed random seeds.

In-distribution Datasets. We use SVHN (Netzer et al., 2011), CIFAR-10 and CIFAR-100 (Krizhevsky et al., 2009) as in-distribution datasets. SVHN has 10 classes and contains 73,257 training images. CIFAR-10 and CIFAR-100 have 10 and 100 classes, respectively. Both datasets consist of 50,000 training images and 10,000 test images.

Auxiliary OOD Datasets. We provide the details of auxiliary OOD datasets below. For each auxiliary OOD dataset, we use random cropping with padding of 4 pixels to generate 32×32 images, and further augment the data by random horizontal flipping. We don't use any image corruptions to augment the data.

1. **TinyImages.** 80 Million Tiny Images (TinyImages) (Torralba et al., 2008) is a dataset that contains 79,302,017 images collected from the Web. The images in the dataset are stored as 32×32 color images. Since CIFAR-10 and CIFAR-100 are labeled subsets of the TinyImages dataset, we need to remove those images in the dataset that belong to CIFAR-10 or CIFAR-100. We follow the same deduplication procedure as in (Hendrycks et al., 2018) and remove all examples in this dataset that appear in CIFAR-10 or CIFAR-100. Even after deduplication, the auxiliary OOD dataset may still contain some in-distribution data if we use CIFAR-10 or CIFAR-100 as in-distribution datasets, but the fraction of them is low.

2. **ImageNet-RC.** We use the downsampled ImageNet dataset (ImageNet64×64) (Chrabaszcz et al., 2017), which is a downsampled variant of the original ImageNet dataset. It contains 1,281,167 images with image size of 64×64 and 1,000 classes. Some of the classes overlap with CIFAR-10 or CIFAR-100 classes. Since we don't use any label information from the dataset, we can say that the auxiliary OOD dataset is unlabeled. Since we randomly crop the 64×64 images into 32×32 images with padding of 4 pixels, with high probability, the resulting images won't contain objects belonging to the in-distribution classes even if the original images contain objects belonging to those classes. Therefore, we still can have a lot of OOD data for training and the fraction of in-distribution data in the auxiliary OOD dataset is low. We call this auxiliary OOD dataset ImageNet-RC.

OOD Test Datasets. We provide the details of OOD test datasets below. All images are of size 32×32.

1. **SVHN.** The SVHN dataset (Netzer et al., 2011) contains color images of house numbers. There are ten classes of digits `0`-`9`. The original test set has 26,032 images. We randomly select 1,000 test images for each class and form a new test dataset of 10,000 images for evaluation.

2. **Textures.** The Describable Textures Dataset (DTD) (Cimpoi et al., 2014) contains textural images in the wild. We include the entire collection of 5640 images for evaluation.

3. **Places365.** The Places365 dataset (Zhou et al., 2017) contains large-scale photographs of scenes with 365 scene categories. There are 900 images per category in the test set. We randomly sample 10,000 images from the test set for evaluation.

4. **LSUN (crop) and LSUN (resize).** The Large-scale Scene UNderstanding dataset (LSUN) has a testing set of 10,000 images of 10 different scenes (Yu et al., 2015). We construct two datasets, `LSUN-C` and `LSUN-R`, by randomly cropping image patches of size 32×32 and downsampling each image to size 32×32, respectively.

5. **iSUN.** The iSUN (Xu et al., 2015) consists of a subset of SUN images. We include the entire collection of 8925 images in iSUN.

6. **CIFAR-10.** We use the test set of CIFAR-10, which contains 10,000 images.

7. **Gaussian Noise.** The synthetic Gaussian noise dataset consists of 10,000 random 2D Gaussian noise images, where each RGB value of every pixel is sampled from an i.i.d Gaussian distribution with mean 0.5 and unit variance. We further clip each pixel value into the range [0,1].

8. **Uniform Noise.** The synthetic uniform noise dataset consists 10,000 images where each RGB value of every pixel is independently and identically sampled from a uniform distribution on [0,1].

Architectures and Training Configurations. We use the state-of-the-art neural network architecture DenseNet (Huang et al., 2017) and WideResNet (Zagoruyko & Komodakis, 2016). For DenseNet, we follow the same setup as in (Huang et al., 2017), with depth $L = 100$, growth rate $k = 12$ (Dense-BC) and dropout rate 0. For WideResNet, we also follow the same setup as in (Zagoruyko & Komodakis, 2016), with depth of 40 and widening parameter $k = 4$ (WRN-40-4). All neural networks are trained with stochastic gradient descent with Nesterov momentum (Duchi et al., 2011;

Method	Training	Evaluation
MSP	2.5 h	4 h
ODIN	2.5 h	4 h
Mahalanobis	2.5 h	20 h
SOFL	14 h	4 h
OE	5 h	4 h
ACET	17 h	4 h
CCU	6.7 h	4 h
ROWL	24 h	4 h
ATOM (ours)	21 h	4 h

Table 2: The estimated average runtime for each result. We use DenseNet as network architecture. h means hour. For MSP, ODIN, and Mahalanobis, we use standard training. The evaluation includes four OOD detection tasks listed in Section 2.

Kingma & Ba, 2014). We set momentum 0.9 and ℓ_2 weight decay with a coefficient of 10^{-4} for all model training. Specifically, for SVHN, we train the networks for 20 epochs and the initial learning rate of 0.1 decays by 0.1 at $10, 15, 18$ epoch; for CIFAR-10 and CIFAR-100, we train the networks for 100 epochs and the initial learning rate of 0.1 decays by 0.1 at $50, 75, 90$ epoch. In ATOM and NTOM, we use batch size 64 for in-distribution data and 128 for out-of-distribution data. To solve the inner max of the robust training objective in ATOM, we use PGD with $\epsilon = 8/255$, the number of iterations of 5, the step size of $2/255$, and random start.

C.2 AVERAGE RUNTIME

We run our experiments using a single GPU on a machine with 4 GPUs and 32 cores. The estimated average runtime for each method is summarized in Table 2.

C.3 OOD DETECTION METHODS

We consider eight common OOD detection methods listed in Table 3 and describe each method in detail below.

Maximum Softmax Probability (MSP). Hendrycks & Gimpel propose to use $\max_i F_i(x)$ as confidence scores to detect OOD examples, where $F(x)$ is the softmax output of the neural network.

ODIN. Liang et al. computes calibrated confidence scores using temperature scaling and input perturbation techniques. In all of our experiments, we set temperature scaling parameter $T = 1000$. We choose perturbation magnitude η by validating on 1000 images randomly sampled from in-distribution test set $\mathcal{D}_{\text{in}}^{\text{test}}$ and 1000 images randomly sampled from auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, which does not depend on prior knowledge of test OOD datasets. For DenseNet, we set $\eta = 0.0006$ for SVHN, $\eta = 0.0016$ for CIFAR-10, and $\eta = 0.0012$ for CIFAR-100. For WideResNet, we set $\eta = 0.0002$ for SVHN, $\eta = 0.0006$ for CIFAR-10, and $\eta = 0.0012$ for CIFAR-100.

Mahalanobis. Lee et al. propose to use Mahalanobis distance-based confidence scores to detect OOD samples. Following Lee et al., we use 1000 examples randomly selected from in-distribution test set $\mathcal{D}_{\text{in}}^{\text{test}}$ and adversarial examples generated by FGSM (Goodfellow et al., 2014) on them with perturbation size of 0.05 to train the Logistic Regression model and tune the noise perturbation magnitude η. η is chosen from $\{0.0, 0.01, 0.005, 0.002, 0.0014, 0.001, 0.0005\}$, and the optimal parameters are chosen to minimize the FPR at FNR 5%.

Outlier Exposure (OE). Outlier Exposure (Hendrycks et al., 2018) makes use of a large, auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ to enhance the performance of existing OOD detection. We train from scratch with $\lambda = 0.5$, and use in-distribution batch size of 64 and out-distribution batch size of 128 in our experiments. Other training parameters are specified in Section C.1.

Self-Supervised OOD Feature Learning (SOFL). Mohseni et al. add an auxiliary head to the network and train in for the OOD detection task. They first use a full-supervised training to learn in-distribution training data for the main classification head and then a self-supervised training with OOD training set for the auxiliary head. Following the original setting, we set $\lambda = 5$ and use an

	MSP	ODIN	Mahalanobis	SOFL	OE	ACET	CCU	ROWL	ATOM (ours)
Natural OOD	✓	✓	✓	✓	✓	✓	✓	✓	✓
L_∞ OOD	✗	✗	✗	✗	✗	✓	✓	✓	✓
Corruption OOD	✗	✗	✗	✗	✗	✗	✗	✗	✓
Comp. OOD	✗	✗	✗	✗	✗	✗	✗	✗	✓

Table 3: Common OOD detection methods and a family of natural and perturbed OOD examples we considered.

in-distribution batch size of 64 and an out-distribution batch size of 320 in all of our experiments. In SVHN and CIFAR-10, we use 5 reject classes, while in CIFAR-100, we use 10 reject classes. We first train the model with the full-supervised learning using the training parameters specified in Section C.1 and then continue to train with the self-supervised OOD feature learning using the same training parameters. We use the large, auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ as out-of-distribution training dataset.

Adversarial Confidence Enhancing Training (ACET). Hein et al. propose Adversarial Confidence Enhancing Training to enforce low model confidence for the OOD data point, as well as worst-case adversarial example in the neighborhood of an OOD example. We use the large, auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ as an OOD training dataset instead of using random noise data for a fair comparison. In all of our experiments, we set $\lambda = 1.0$. For both in-distribution and out-distribution, we use a batch size of 128. To solve the inner max of the training objective, we also apply PGD with $\epsilon = 8/255$, the number of iterations of 5, the step size of $2/255$, and random start to a half of a minibatch while keeping the other half clean to ensure proper performance on both perturbed and clean OOD examples for a fair comparison. Other training parameters are specified in Section C.1.

Certified Certain Uncertainty (CCU). Certified Certain Uncertainty (Meinke & Hein, 2019) gives guarantees on the confidence of the classifier decision far away from the training data. We use the same training set up as in the paper and code, except we use our training configurations specified in Section C.1.

Robust Open-World Deep Learning (ROWL). Sehwag et al. propose to introduce additional background classes for OOD datasets and perform adversarial training on both the in- and out-of-distribution datasets to achieve robust open-world classification. When an input is classified as the background classes, it is considered as an OOD example. Thus, ROWL gives binary OOD scores (either 0 or 1) to the inputs. In our experiments, we only have one background class and randomly sample data points from the large, auxiliary OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ to form the OOD dataset. To ensure data balance across classes, we include 7,325 OOD data points for SVHN, 5,000 OOD data points for CIFAR-10 and 500 OOD data points for CIFAR-100. During training, we mix the in-distribution data and OOD data, and use a batch size of 128. To solve the inner max of the training objective, we use PGD with $\epsilon = 8/255$, the number of iterations of 5, the step size of $2/255$, and random start. Other training parameters are specified in Section C.1.

C.4 ADVERSARIAL ATTACKS FOR OOD DETECTION METHODS

We propose adversarial attack objectives for different OOD detection methods. We consider a family of adversarial perturbations for the OOD inputs: (1) L_∞-norm bounded attack (white-box attack); (2) common image corruptions attack (black-box attack); (3) compositional attack which combines common image corruptions attack and L_∞ norm bounded attack (white-box attack).

L_∞ **norm bounded attack.** For data point $\mathbf{x} \in \mathbb{R}^d$, the L_∞ norm bounded perturbation is defined as

$$\Omega_{\infty,\epsilon}(\mathbf{x}) = \{\delta \in \mathbb{R}^d \mid \|\delta\|_\infty \leq \epsilon \wedge \mathbf{x} + \delta \text{ is valid}\}, \tag{115}$$

where ϵ is the adversarial budget. $\mathbf{x} + \delta$ is considered valid if the values of $\mathbf{x} + \delta$ are in the image pixel value range.

For MSP, ODIN, OE, ACET, and CCU methods, we propose the following attack objective to generate adversarial OOD example on a clean OOD input $\mathbf{x}$:

$$\mathbf{x}' = \underset{\mathbf{x}' \in \Omega_{\infty,\epsilon}(\mathbf{x})}{\arg\max} -\frac{1}{K} \sum_{i=1}^{K} \log F(\mathbf{x}')_i \tag{116}$$

where $F(\mathbf{x})$ is the softmax output of the classifier network.

For Mahalanobis method, we propose the following attack objective to generate adverasrial OOD example on OOD input $\mathbf{x}$:

$$\mathbf{x}' = \underset{\mathbf{x}' \in \Omega_{\infty, \epsilon}(\mathbf{x})}{\arg \max} -\log \frac{1}{1 + e^{-(\sum_\ell \alpha_\ell M_\ell(\mathbf{x}') + b)}}, \tag{117}$$

where $M_\ell(\mathbf{x}')$ is the Mahalanobis distance-based confidence score of $\mathbf{x}'$ from the ℓ-th feature layer, $\{\alpha_\ell\}$ and b are the parameters of the logistic regression model.

For SOFL method, we propose the following attack objective to generate adversarial OOD example for an input $\mathbf{x}$:

$$\mathbf{x}' = \underset{\mathbf{x}' \in \Omega_{\infty, \epsilon}(\mathbf{x})}{\arg \max} -\log \sum_{i=K+1}^{K+R} \bar{F}(\mathbf{x}')_i \tag{118}$$

where $\bar{F}(\mathbf{x})$ is the softmax output of the whole neural network (including auxiliary head) and R is the number of reject classes.

For ROWL and ATOM method, we propose the following attack objective to generate adverasrial OOD example on OOD input $\mathbf{x}$:

$$\mathbf{x}' = \underset{\mathbf{x}' \in \Omega_{\infty, \epsilon}(\mathbf{x})}{\arg \max} -\log \hat{F}(\mathbf{x}')_{K+1} \tag{119}$$

where $\hat{F}(\mathbf{x})$ is the softmax output of the (K+1)-way neural network.

Due to computational concerns, by default, we will use PGD with $\epsilon = 8/255$, the number of iterations of 40, the step size of 1/255 and random start to solve these attack objectives. We also perform ablation study experiments on the attack strength for ACET and ATOM, see Appendix C.11.

Common Image Corruptions attack. We use common image corruptions introduced in (Hendrycks & Dietterich, 2019). We apply 15 types of algorithmically generated corruptions from noise, blur, weather, and digital categories to each OOD image. Each type of corruption has five levels of severity, resulting in 75 distinct corruptions. Thus, for each OOD image, we generate 75 corrupted images and then select the one with the lowest OOD score (or highest confidence score to be in-distribution). Note that we only need the outputs of the OOD detectors to construct such adversarial OOD examples; thus it is a black-box attack.

Compositional Attack. For each OOD image, we first apply common image corruptions attack, and then apply the L_∞-norm bounded attack to generate adversarial OOD examples.

C.5 VISUALIZATIONS OF FOUR TYPES OF OOD SAMPLES

We show visualizations of four types of OOD samples in Figure 4.

C.6 HISTOGRAM OF OOD SCORES

In Figure 5, we show histogram of OOD scores for model snapshots trained on CIFAR-10 (in-distribution) using objective (4) **without** informative outlier mining. We plot every ten epochs for a model trained for a total of 100 epochs. We observe that the model quickly converges to a solution where OOD score distribution becomes dominated by *easy* examples with scores closer to 1. This is exacerbated as the model is trained for longer.

C.7 CHOOSE BEST Q USING VALIDATION DATASET

We create a validation OOD dataset by sampling 10,000 images from the 80 Million Tiny Images (Torralba et al., 2008), which is disjoint from our training data. We choose q from $\{0, 0.125, 0.25, 0.5, 0.75\}$. The results on the validation dataset are shown in Table 4. We select the best model based on the average FPR at 5% FNR across four types of OOD inputs. Based on the results, the optimal q is 0 for SVHN, 0.125 for CIFAR-10 and 0.5 for CIFAR-100.

(a) Natural OOD   (b) L_∞ OOD

(c) Corruption OOD   (d) Comp. OOD

Figure 4: Examples of four types of OOD samples.

C.8 Effect of Informative Outlier Mining and the Sampling Parameter q

We perform an ablation study that isolates the effect of informative outlier mining. We also vary the sampling interval with different q to see how it affects the performance. The results are shown in Table 5.

C.9 Effect of Auxiliary OOD Datasets

We present results in Table 6, where we use an alternative auxiliary OOD dataset ImageNet-RC. The details of ImageNet-RC is provided in Section C.1. We use the same hyperparameters as used in training with TinyImages auxiliary data. For all three in-distribution datasets, we find that using $q = 0$ results in the optimal performance.

$\mathcal{D}_{in}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
SVHN	ATOM (q=0.0)	**0.01**	99.97	**4.02**	98.50	**8.08**	98.14	**96.79**	43.77
	ATOM (q=0.125)	2.16	99.39	36.62	94.79	62.38	73.20	99.98	4.62
	ATOM (q=0.25)	1.87	99.38	41.86	94.20	75.85	57.75	100.00	1.26
	ATOM (q=0.5)	2.73	99.18	45.02	93.85	83.01	49.38	99.99	1.96
	ATOM (q=0.75)	4.97	98.83	56.51	92.13	85.98	40.89	100.00	1.16
CIFAR-10	ATOM (q=0.0)	5.34	98.35	43.61	91.85	22.08	92.81	59.17	83.56
	ATOM (q=0.125)	**4.77**	98.31	**27.49**	94.24	**5.42**	98.19	**29.02**	93.76
	ATOM (q=0.25)	5.70	98.11	28.13	93.68	19.28	95.71	40.68	91.17
	ATOM (q=0.5)	8.83	97.66	39.74	91.53	9.80	97.42	44.10	90.45
	ATOM (q=0.75)	12.42	97.02	45.85	90.53	13.40	96.83	46.30	90.42
CIFAR-100	ATOM (q=0.0)	44.85	91.58	98.76	64.78	53.17	85.26	98.95	58.38
	ATOM (q=0.125)	36.75	92.90	96.22	73.33	38.79	91.42	96.33	71.74
	ATOM (q=0.25)	**34.66**	92.62	94.13	73.86	**35.84**	91.24	94.33	70.35
	ATOM (q=0.5)	35.04	91.36	**89.28**	71.78	36.76	90.21	**89.57**	70.62
	ATOM (q=0.75)	43.49	87.95	91.80	62.47	59.34	78.00	92.94	58.53

Table 4: Evaluate models on validation dataset. We use DenseNet as network architecture. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets mentioned in section 5.1. **Bold** numbers are superior results.

$\mathcal{D}_{in}^{test}$	Model	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
SVHN	ATOM (rand. sample)	0.35	99.91	13.09	97.50	11.72	96.63	98.66	40.48
	ATOM (q=0.0)	0.07	99.97	5.47	98.52	7.02	98.00	96.33	49.52
	ATOM (q=0.125)	1.30	99.63	34.97	94.97	39.61	82.92	99.92	6.30
	ATOM (q=0.25)	1.36	99.60	41.98	94.30	52.39	71.34	99.97	1.35
	ATOM (q=0.5)	2.11	99.46	44.85	93.84	59.72	65.59	99.97	3.15
	ATOM (q=0.75)	2.91	99.26	51.33	93.07	66.20	57.16	99.96	2.04
CIFAR-10	ATOM (rand. sample)	2.65	99.11	42.28	91.94	44.31	68.64	65.17	72.62
	ATOM (q=0.0)	2.24	99.20	40.46	92.86	36.80	73.11	66.15	73.93
	ATOM (q=0.125)	1.69	99.20	25.26	95.29	20.55	88.94	38.89	86.71
	ATOM (q=0.25)	2.34	99.12	22.71	95.29	24.93	94.83	41.58	91.56
	ATOM (q=0.5)	4.03	98.97	33.93	93.51	22.39	95.16	45.11	90.56
	ATOM (q=0.75)	5.35	98.77	41.02	92.78	21.87	93.37	43.64	91.98
CIFAR-100	ATOM (rand. sample)	51.50	89.62	99.70	58.61	70.33	58.84	99.80	34.98
	ATOM (q=0.0)	44.38	91.92	99.76	60.12	68.32	65.75	99.80	49.85
	ATOM (q=0.125)	26.91	94.97	98.35	71.53	34.66	87.54	98.42	68.52
	ATOM (q=0.25)	32.43	93.93	97.71	72.61	40.37	82.68	97.87	65.19
	ATOM (q=0.5)	32.30	93.06	93.15	71.96	38.72	88.03	93.44	69.15
	ATOM (q=0.75)	38.56	91.20	97.59	58.53	62.66	78.70	97.97	54.89

Table 5: Ablation study on informative outlier mining. We use DenseNet as network architecture. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets mentioned in section 5.1. We **do not** use OOD test set for tuning q. Please refer to Table 4 for validation results.

C.10 Effect of Network Architecture

We perform experiments to evaluate different OOD detection methods using WideResNet, see Table 7. For both ATOM and NTOM, we use the same hyperparameters as those selected for DenseNet and find that it also leads to good results.

C.11 Effect of PGD Attack Strength

To see the effect of using stronger PGD attacks, we evaluate ACET (best baseline) and ATOM on L_∞ attacked OOD and compositionally attacked OOD inputs with 100 iterations and 5 random restarts. Results are provided in Table 8. Under stronger PGD attack, ATOM outperforms ACET.

C.12 Evaluation on Random Noise OOD Data

We report the performance of OOD detectors using DenseNet on random noise OOD test datasets in Table 9 (SVHN), Table 10 (CIFAR-10) and Table 11 (CIFAR-100).

$\mathcal{D}_{in}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
SVHN	MSP	38.84	93.57	99.68	68.48	99.89	1.39	100.00	0.19
	ODIN	31.45	93.52	97.11	63.21	99.86	0.61	100.00	0.05
	Mahalanobis	22.80	95.57	93.14	60.78	97.33	8.89	99.89	0.23
	SOFL	**0.02**	**99.99**	**5.93**	**98.57**	58.53	68.85	67.34	61.42
	OE	0.13	99.96	15.76	97.51	68.76	49.57	98.80	6.21
	ACET	0.31	99.94	29.02	95.65	2.37	99.51	30.58	95.20
	CCU	0.17	99.96	18.64	96.94	45.38	69.14	92.30	20.88
	ROWL	2.04	98.87	55.03	72.37	77.24	61.27	99.79	50.00
	NTOM (ours)	**0.02**	**99.99**	6.39	98.54	59.27	68.53	58.12	72.08
	ATOM (ours)	**0.02**	**99.99**	7.03	98.38	**0.14**	**99.95**	**7.30**	**98.32**
CIFAR-10	MSP	50.54	91.79	100.00	58.35	100.00	13.82	100.00	13.67
	ODIN	21.65	94.66	99.37	51.44	99.99	0.18	100.00	0.01
	Mahalanobis	26.95	90.30	91.92	43.94	95.07	12.47	99.88	1.58
	SOFL	6.96	98.71	22.30	95.89	97.61	12.39	99.74	7.49
	OE	9.70	98.35	49.84	91.76	91.30	43.88	98.82	31.12
	ACET	10.72	98.01	53.85	90.19	17.10	96.01	55.21	89.78
	CCU	10.30	98.25	44.42	92.34	93.02	20.88	99.17	9.95
	ROWL	25.03	86.96	94.34	52.31	99.98	49.49	100.00	49.48
	NTOM (ours)	**4.01**	**99.17**	**15.13**	**97.14**	96.89	11.42	99.87	3.18
	ATOM (ours)	4.08	99.14	16.17	96.94	**7.46**	**98.50**	**18.35**	**96.60**
CIFAR-100	MSP	78.05	76.11	100.00	30.04	100.00	2.25	100.00	2.06
	ODIN	56.77	83.62	100.00	36.95	100.00	0.14	100.00	0.00
	Mahalanobis	42.63	87.86	95.92	42.96	95.44	15.87	99.86	2.08
	SOFL	20.95	96.06	73.33	83.31	93.41	12.90	99.98	3.36
	OE	18.52	95.27	86.83	66.95	96.27	18.79	99.97	4.88
	ACET	19.79	94.76	81.63	70.04	26.23	91.46	81.95	69.67
	CCU	19.44	95.05	84.11	69.09	84.89	35.85	99.61	15.67
	ROWL	93.35	53.02	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	18.09	96.74	66.61	87.97	86.88	15.40	99.98	0.77
	ATOM (ours)	**15.49**	**97.18**	**57.79**	**89.49**	**18.32**	**96.57**	**58.49**	**89.36**

Table 6: Comparison with competitive OOD detection methods. We use ImageNet-RC as the auxiliary OOD dataset (see section C.1 for the details) for SOFL, OE, ACET, CCU, NTOM and ATOM. We use DenseNet as network architecture for all methods. We evaluate on four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 5.1. **Bold** numbers are superior results.

C.13 PERFORMANCE OF OOD DETECTOR AND CLASSIFIER ON IN-DISTRIBUTION DATA

We summarize the performance of OOD detector $G(x)$ and image classifier $f(x)$ on in-distribution test data. See Table 12 for DenseNet and Table 13 for WideResNet. From the results, we can see that ATOM improves the OOD detection performance while achieving in-distribution classification accuracy that is on par with a pre-trained network.

C.14 COMPLETE EXPERIMENTAL RESULTS

We report the performance of OOD detectors using DenseNet on each of the six natural OOD test datasets in Table 14 (SVHN), Table 15 (CIFAR-10) and Table 16 (CIFAR-100).

$\mathcal{D}_{in}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
SVHN	MSP	42.78	91.15	99.99	51.84	100.00	0.15	100.00	0.05
	ODIN	43.65	89.37	99.85	44.43	100.00	0.06	100.00	0.00
	Mahalanobis	6.94	98.47	80.91	78.92	93.44	39.42	99.70	2.69
	SOFL	**0.02**	**99.99**	**2.41**	**99.36**	85.25	39.32	99.28	2.85
	OE	0.58	99.87	21.97	96.00	70.66	47.36	96.63	5.87
	ACET	0.43	99.92	18.12	97.11	20.75	89.55	99.66	1.80
	CCU	0.71	99.86	30.96	94.40	73.37	41.82	99.83	0.44
	ROWL	1.46	99.13	45.18	77.28	86.95	56.39	99.94	49.90
	NTOM (ours)	**0.02**	**99.99**	2.46	99.27	70.38	52.43	99.79	1.01
	ATOM (ours)	0.08	99.96	4.18	98.65	**5.93**	**98.47**	**95.50**	**62.00**
CIFAR-10	MSP	53.81	91.10	100.00	50.30	100.00	5.48	100.00	5.43
	ODIN	36.25	91.18	99.95	31.78	100.00	0.04	100.00	0.00
	Mahalanobis	23.93	92.48	86.78	56.90	85.75	42.63	99.22	17.51
	SOFL	2.15	**99.14**	38.03	93.35	99.99	0.43	100.00	0.24
	OE	3.03	98.83	56.00	91.19	99.97	0.26	100.00	0.04
	ACET	3.19	98.74	35.78	94.25	40.22	89.52	56.08	87.76
	CCU	2.61	98.75	36.31	93.75	99.93	0.86	99.99	0.41
	ROWL	17.21	90.79	86.09	56.35	99.94	49.43	99.99	49.40
	NTOM (ours)	1.86	99.10	23.77	94.58	99.92	0.84	99.96	0.33
	ATOM (ours)	**1.50**	98.87	**13.17**	**96.36**	**33.66**	**90.89**	**40.07**	**88.99**
CIFAR-100	MSP	81.92	74.32	100.00	28.10	100.00	3.20	100.00	3.14
	ODIN	68.76	79.13	100.00	26.44	100.00	0.15	100.00	0.01
	Mahalanobis	43.48	86.02	95.78	42.25	95.83	17.41	99.92	3.55
	SOFL	66.57	89.11	99.99	59.64	99.99	0.30	100.00	0.10
	OE	46.14	91.16	99.96	58.55	100.00	1.80	100.00	1.69
	ACET	46.79	91.67	99.76	62.48	95.66	41.38	99.99	36.65
	CCU	48.35	91.41	99.95	57.94	100.00	0.44	100.00	0.38
	ROWL	96.93	51.34	100.00	49.81	100.00	49.81	100.00	49.81
	NTOM (ours)	37.94	92.14	97.09	66.93	99.99	1.04	99.99	0.13
	ATOM (ours)	**30.52**	**93.90**	**94.46**	**74.96**	**44.30**	**89.68**	**95.06**	**74.25**

Table 7: Comparison with competitive OOD detection methods. We use WideResNet as network architecture for all methods. We evaluate on four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 5.1. **Bold** numbers are superior results.

$\mathcal{D}_{in}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		L_∞ OOD		Comp. OOD	
SVHN	ACET	33.64	83.89	99.90	2.84
	ATOM (ours)	**8.33**	**97.37**	**98.56**	**35.32**
CIFAR-10	ACET	76.66	76.29	97.08	51.35
	ATOM (ours)	**26.88**	**83.78**	**42.86**	**83.56**
CIFAR-100	ACET	87.13	48.77	99.82	33.67
	ATOM (ours)	**45.11**	**82.32**	**93.74**	**65.88**

Table 8: Evaluation on L_∞ attacked OOD and compositionally attacked OOD inputs with strong PGD attack (100 iterations and 5 random restarts). We use DenseNet as network architecture for all methods. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 5.1. **Bold** numbers are superior results.

Figure 5: On CIFAR-10, we train the model with objective (4) for 100 epochs **without** informative outlier mining. For every 10 epochs, we randomly sample 400,000 data points from the large auxiliary OOD dataset and use the current model snapshot to calculate the OOD scores.

$\mathcal{D}_{out}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
Gaussian Noise	MSP	56.30	90.16	100.00	55.70	100.00	5.25	100.00	0.14
	ODIN	58.49	88.24	100.00	44.91	100.00	0.87	100.00	0.01
	Mahalanobis	**0.00**	99.92	97.34	77.03	1.51	98.73	100.00	0.00
	SOFL	**0.00**	**100.00**	0.02	99.93	**0.00**	99.98	100.00	0.42
	OE	**0.00**	**100.00**	0.93	99.74	**0.00**	**100.00**	98.71	2.20
	ACET	**0.00**	**100.00**	**0.00**	**99.98**	**0.00**	99.99	98.80	17.98
	CCU	**0.00**	99.99	0.11	99.94	**0.00**	99.97	**34.14**	65.91
	ROWL	**0.00**	99.89	3.83	97.97	**0.00**	99.89	91.98	53.90
	NTOM (ours)	**0.00**	**100.00**	0.03	99.94	**0.00**	**100.00**	100.00	0.72
	ATOM (ours)	**0.00**	**100.00**	**0.00**	99.96	**0.00**	**100.00**	63.53	**93.40**
Uniform Noise	MSP	53.63	90.75	100.00	52.67	100.00	0.05	100.00	0.00
	ODIN	59.07	87.96	100.00	39.84	100.00	0.00	100.00	0.00
	Mahalanobis	**0.00**	99.73	99.99	56.02	100.00	20.33	100.00	0.00
	SOFL	**0.00**	**100.00**	0.35	99.74	39.53	91.58	100.00	0.01
	OE	**0.00**	**100.00**	5.83	98.88	0.09	99.98	99.97	0.16
	ACET	**0.00**	**100.00**	0.32	99.70	**0.00**	99.99	100.00	1.17
	CCU	**0.00**	**100.00**	4.04	99.19	**0.00**	99.97	99.82	0.18
	ROWL	**0.00**	99.89	17.44	91.17	0.19	99.80	100.00	49.89
	NTOM (ours)	**0.00**	**100.00**	0.11	99.86	0.22	99.87	100.00	0.01
	ATOM (ours)	**0.00**	**100.00**	**0.00**	**99.92**	**0.00**	**100.00**	**99.79**	**74.58**

Table 9: Comparison with competitive OOD detection methods. We use SVHN as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.

$\mathcal{D}_{out}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
Gaussian Noise	MSP	100.00	77.69	100.00	73.29	100.00	69.73	100.00	52.56
	ODIN	97.30	89.00	100.00	81.48	100.00	71.12	100.00	34.99
	Mahalanobis	**0.00**	**100.00**	**0.00**	**99.95**	**0.00**	**100.00**	85.03	23.21
	SOFL	**0.00**	99.99	48.06	94.12	0.03	98.83	100.00	4.42
	OE	**0.00**	99.91	0.05	98.48	**0.00**	99.08	99.65	32.44
	ACET	**0.00**	99.94	**0.00**	99.74	**0.00**	99.87	**0.04**	99.40
	CCU	**0.00**	98.84	0.09	98.09	0.85	97.21	84.47	69.56
	ROWL	0.71	99.13	100.00	49.48	99.99	49.48	100.00	49.48
	NTOM (ours)	**0.00**	99.97	0.08	98.90	**0.00**	99.87	99.12	37.97
	ATOM (ours)	**0.00**	99.93	**0.00**	99.65	**0.00**	99.93	0.21	**99.54**
Uniform Noise	MSP	99.67	86.55	100.00	76.54	100.00	71.48	100.00	36.82
	ODIN	91.48	90.73	100.00	79.19	100.00	51.93	100.00	13.86
	Mahalanobis	**0.00**	**100.00**	**0.00**	**99.94**	**0.00**	**100.00**	99.84	22.25
	SOFL	**0.00**	99.75	95.82	86.22	100.00	69.89	100.00	4.39
	OE	**0.00**	99.89	0.02	98.62	33.05	92.41	99.98	29.62
	ACET	**0.00**	99.95	**0.00**	99.22	**0.00**	99.88	**36.48**	**95.06**
	CCU	**0.00**	98.50	0.87	97.78	94.68	86.27	99.70	48.18
	ROWL	97.14	50.91	100.00	49.48	100.00	49.48	100.00	49.48
	NTOM (ours)	**0.00**	99.97	1.42	98.08	28.41	95.94	100.00	2.88
	ATOM (ours)	**0.00**	99.93	**0.00**	99.07	**0.00**	99.93	91.81	45.48

Table 10: Comparison with competitive OOD detection methods. We use CIFAR-10 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages.

$\mathcal{D}_{out}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		**Corruption OOD**		L_∞ **OOD**		**Comp. OOD**	
	MSP	100.00	18.62	100.00	11.90	100.00	5.29	100.00	2.04
	ODIN	100.00	16.53	100.00	12.57	100.00	2.57	100.00	1.55
Gaussian	Mahalanobis	**0.00**	**100.00**	**0.00**	**99.82**	**0.00**	**100.00**	99.18	**81.79**
Noise	SOFL	**0.00**	**100.00**	100.00	70.93	4.56	98.30	100.00	0.17
	OE	3.69	97.53	100.00	64.71	67.00	92.45	100.00	1.60
	ACET	**0.00**	99.02	22.38	95.49	0.14	97.68	99.71	75.87
	CCU	100.00	50.78	100.00	47.92	100.00	37.06	100.00	35.25
	ROWL	0.54	99.42	100.00	49.69	99.37	50.01	100.00	49.69
	NTOM (ours)	**0.00**	99.95	30.60	95.57	**0.00**	99.92	100.00	30.10
	ATOM (ours)	**0.00**	99.98	**0.00**	99.06	**0.00**	99.98	**86.43**	52.84
	MSP	99.99	37.86	100.00	16.59	100.00	2.45	100.00	1.67
	ODIN	100.00	31.77	100.00	20.56	100.00	0.48	100.00	0.40
Uniform	Mahalanobis	**0.00**	**100.00**	**0.00**	**99.69**	**0.00**	**100.00**	100.00	32.70
Noise	SOFL	**0.00**	99.99	100.00	68.28	99.98	79.63	100.00	0.59
	OE	0.19	99.21	100.00	57.39	100.00	55.40	100.00	0.62
	ACET	**0.00**	99.43	64.94	93.48	95.10	91.27	98.47	**57.60**
	CCU	30.96	95.93	100.00	71.51	100.00	46.37	100.00	5.29
	ROWL	98.45	50.46	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	**0.00**	99.79	64.35	94.08	99.97	87.14	100.00	18.81
	ATOM (ours)	**0.00**	99.98	0.04	98.44	**0.00**	99.98	**89.90**	41.34

Table 11: Comparison with competitive OOD detection methods. We use CIFAR-100 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages.

$\mathcal{D}_{\text{in}}^{\text{test}}$	Method	FNR	Pred. Acc.	End-to-end. Pred. Acc.
SVHN	MSP	5.01	95.83	93.00
	ODIN	5.01	95.83	92.44
	Mahalanobis	5.01	95.83	91.50
	SOFL	5.01	96.45	92.81
	OE	5.01	95.93	93.11
	ACET	5.01	95.58	92.79
	CCU	5.01	95.85	92.95
	ROWL	0.22	95.23	95.23
	NTOM (ours)	5.01	95.75	91.99
	ATOM (ours)	5.01	96.09	91.95
CIFAR-10	MSP	5.01	94.39	91.76
	ODIN	5.01	94.39	91.00
	Mahalanobis	5.01	94.39	89.72
	SOFL	5.01	95.11	91.60
	OE	5.01	94.79	91.86
	ACET	5.01	91.48	88.61
	CCU	5.01	94.89	91.88
	ROWL	1.04	93.18	93.18
	NTOM (ours)	5.01	95.42	91.57
	ATOM (ours)	5.01	95.20	91.33
CIFAR-100	MSP	5.01	75.05	73.87
	ODIN	5.01	75.05	73.72
	Mahalanobis	5.01	75.05	71.12
	SOFL	5.01	74.37	72.62
	OE	5.01	75.28	73.74
	ACET	5.01	74.43	72.72
	CCU	5.01	76.04	74.60
	ROWL	0.62	72.51	72.51
	NTOM (ours)	5.01	74.88	72.47
	ATOM (ours)	5.01	75.06	72.72

Table 12: The performance of OOD detector and classifier on in-distribution test data. We use DenseNet for all methods. We use three metrics: FNR, Prediction Accuracy and End-to-end Prediction Accuracy. We pick the threshold for the OOD detectors such that 95% of in-distribution test data points are classified as in-distribution. Prediction Accuracy measures the accuracy of the classifier on in-distribution test data. End-to-end Prediction Accuracy measures the accuracy of the open world classification system (detector+classifier), where an example is classified correctly if and only if the detector treats it as in-distribution and the classifier predicts its label correctly.

$\mathcal{D}_{in}^{test}$	Method	FNR	Pred. Acc.	End-to-end. Pred. Acc.
SVHN	MSP	5.01	95.61	92.91
	ODIN	5.01	95.61	92.49
	Mahalanobis	5.01	95.61	91.34
	SOFL	5.01	95.65	92.34
	OE	5.01	95.76	92.91
	ACET	5.01	95.96	93.13
	CCU	5.01	95.83	93.05
	ROWL	0.27	95.87	95.87
	NTOM (ours)	5.01	95.76	91.98
	ATOM (ours)	5.01	95.96	91.82
CIFAR-10	MSP	5.01	94.92	92.38
	ODIN	5.01	94.92	91.60
	Mahalanobis	5.01	94.92	90.27
	SOFL	5.01	95.98	92.45
	OE	5.01	95.51	92.35
	ACET	5.01	95.33	92.47
	CCU	5.01	95.63	92.46
	ROWL	1.21	93.91	93.91
	NTOM (ours)	5.01	95.89	91.97
	ATOM (ours)	5.01	95.89	92.20
CIFAR-100	MSP	5.01	76.61	75.46
	ODIN	5.01	76.61	75.16
	Mahalanobis	5.01	76.61	72.61
	SOFL	5.01	75.12	73.78
	OE	5.01	75.58	74.47
	ACET	5.01	75.61	74.60
	CCU	5.01	76.36	75.34
	ROWL	0.39	75.94	75.94
	NTOM (ours)	5.01	76.30	74.04
	ATOM (ours)	5.01	77.51	75.32

Table 13: The performance of OOD detector and classifier on in-distribution test data. We use WideResNet for all methods. We use three metrics: FNR, Prediction Accuracy and End-to-end Prediction Accuracy. We pick the threshold for the OOD detectors such that 95% of in-distribution test data points are classified as in-distribution. Prediction Accuracy measures the accuracy of the classifier on in-distribution test data. End-to-end Prediction Accuracy measures the accuracy of the open world classification system (detector+classifier), where an example is classified correctly if and only if the detector treats it as in-distribution and the classifier predicts its label correctly.

$\mathcal{D}_{out}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		**Corruption OOD**		L_∞ **OOD**		**Comp. OOD**	
LSUN-C	MSP	33.90	94.01	99.59	68.76	99.94	0.82	100.00	0.11
	ODIN	28.40	93.77	97.37	59.61	99.90	0.38	100.00	0.01
	Mahalanobis	0.20	99.64	79.20	80.24	98.01	10.95	99.99	0.07
	SOFL	**0.00**	**100.00**	**2.10**	**99.38**	68.89	54.15	99.98	0.31
	OE	**0.00**	**100.00**	23.06	96.38	54.03	77.79	99.91	0.52
	ACET	**0.00**	**100.00**	20.48	96.75	0.09	99.97	99.85	4.76
	CCU	**0.00**	**100.00**	22.26	96.46	35.10	80.37	99.92	0.55
	ROWL	2.50	98.64	75.48	62.15	96.22	51.78	99.99	**49.90**
	NTOM (ours)	**0.00**	**100.00**	2.64	99.06	54.69	75.51	99.99	0.17
	ATOM (ours)	**0.00**	**100.00**	16.71	96.91	**0.00**	**100.00**	**97.85**	39.64
LSUN-R	MSP	44.84	92.75	99.93	66.82	100.00	1.22	100.00	0.11
	ODIN	36.84	92.91	98.53	62.91	100.00	0.25	100.00	0.01
	Mahalanobis	18.35	96.64	98.92	54.27	99.04	10.01	100.00	0.00
	SOFL	**0.00**	**100.00**	0.55	99.75	49.23	77.50	99.88	4.77
	OE	0.02	**100.00**	9.44	98.34	41.86	79.82	99.91	1.54
	ACET	**0.00**	**100.00**	5.36	98.87	2.60	99.35	99.96	7.00
	CCU	**0.00**	**100.00**	9.44	98.46	12.25	94.36	98.90	2.78
	ROWL	0.01	99.89	22.57	88.61	39.54	80.12	99.68	50.05
	NTOM (ours)	**0.00**	**100.00**	**0.12**	**99.82**	22.97	91.97	99.97	2.34
	ATOM (ours)	**0.00**	**100.00**	0.13	99.67	**0.09**	**99.97**	**96.08**	**63.20**
iSUN	MSP	40.78	93.57	99.85	68.88	99.99	1.37	100.00	0.14
	ODIN	31.98	93.97	97.70	64.77	99.99	0.29	100.00	0.01
	Mahalanobis	19.73	96.25	98.35	56.95	98.73	10.21	100.00	0.01
	SOFL	**0.00**	**100.00**	0.75	99.70	56.78	69.82	99.87	4.39
	OE	0.01	**100.00**	9.50	98.36	45.45	76.08	99.76	1.72
	ACET	0.01	**100.00**	6.17	98.84	4.90	98.52	99.92	6.96
	CCU	0.02	**100.00**	9.94	98.32	17.36	90.54	99.13	2.56
	ROWL	0.04	99.87	24.43	87.68	44.62	77.58	99.29	50.24
	NTOM (ours)	**0.00**	**100.00**	0.38	**99.77**	30.90	87.40	99.98	2.26
	ATOM (ours)	**0.00**	**100.00**	0.24	99.59	**0.25**	**99.94**	**95.20**	**61.70**
Textures	MSP	41.91	92.08	99.33	61.77	99.45	2.84	100.00	0.44
	ODIN	40.48	89.91	97.36	52.69	99.29	2.14	100.00	0.27
	Mahalanobis	24.34	94.15	85.94	62.00	88.83	17.73	99.38	1.27
	SOFL	0.34	**99.91**	11.83	97.47	89.36	23.54	99.20	2.42
	OE	2.73	99.50	43.05	92.51	84.36	26.88	98.32	2.72
	ACET	2.55	99.54	32.55	94.67	64.57	58.46	99.40	5.73
	CCU	2.22	99.57	41.86	92.46	78.09	31.94	98.58	2.31
	ROWL	7.85	95.96	71.17	64.30	89.73	55.02	99.77	**50.01**
	NTOM (ours)	0.27	99.90	**9.18**	**97.97**	81.17	35.06	98.76	2.74
	ATOM (ours)	0.41	99.83	11.31	97.66	**28.81**	**90.97**	**91.61**	49.35
Places365	MSP	36.14	94.37	99.60	71.71	99.99	1.03	100.00	0.14
	ODIN	26.84	95.01	96.25	68.40	99.99	0.32	100.00	0.01
	Mahalanobis	34.83	93.95	98.14	55.70	99.64	1.97	100.00	0.00
	SOFL	**0.00**	**99.99**	3.46	99.09	94.58	26.96	99.96	1.98
	OE	0.37	99.91	27.78	95.86	94.97	26.54	99.99	0.47
	ACET	0.15	99.96	19.28	97.06	49.09	83.63	99.99	2.65
	CCU	0.27	99.95	29.12	95.65	83.26	39.88	100.00	0.59
	ROWL	0.97	99.41	67.26	66.26	96.67	51.56	100.00	**49.89**
	NTOM (ours)	**0.00**	**99.99**	2.39	**99.21**	87.35	46.68	99.99	0.48
	ATOM (ours)	**0.00**	**99.99**	**2.31**	98.59	**5.60**	**98.71**	**98.74**	38.95
CIFAR-10	MSP	35.45	94.66	99.79	72.97	100.00	1.07	100.00	0.19
	ODIN	24.15	95.54	95.45	70.89	100.00	0.28	100.00	0.01
	Mahalanobis	39.35	92.80	98.28	55.52	99.70	2.47	100.00	0.01
	SOFL	0.01	**99.99**	3.99	99.03	93.00	28.70	99.95	2.60
	OE	0.48	99.89	27.79	95.92	95.49	26.02	99.98	0.63
	ACET	0.21	99.94	18.32	97.18	54.71	80.56	99.98	3.69
	CCU	0.47	99.91	32.40	95.34	86.98	36.35	99.98	0.79
	ROWL	0.84	99.47	69.28	65.25	96.68	51.55	100.00	**49.89**
	NTOM (ours)	**0.00**	99.98	2.53	**99.17**	84.60	47.74	100.00	0.99
	ATOM (ours)	**0.00**	99.98	**2.14**	98.72	**7.39**	**98.42**	**98.51**	44.28

Table 14: Comparison with competitive OOD detection methods. We use SVHN as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.

$\mathcal{D}_{out}^{test}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
LSUN-C	MSP	27.34	96.30	100.00	71.57	100.00	13.75	100.00	13.68
	ODIN	1.89	99.50	98.94	71.86	100.00	0.06	100.00	0.00
	Mahalanobis	14.82	94.63	93.31	46.23	98.07	8.04	99.99	1.36
	SOFL	0.39	99.40	56.07	93.02	100.00	2.36	100.00	1.96
	OE	0.97	99.52	40.85	93.99	99.99	0.36	100.00	0.19
	ACET	1.76	99.42	31.46	95.40	45.54	90.57	88.09	70.84
	CCU	0.62	**99.65**	33.44	94.56	99.97	0.31	100.00	0.05
	ROWL	10.92	94.02	91.67	53.64	100.00	49.48	100.00	49.48
	NTOM (ours)	0.27	99.59	20.32	96.31	99.95	3.12	100.00	0.36
	ATOM (ours)	**0.25**	99.53	**16.38**	**96.75**	**0.38**	**99.49**	**17.27**	**96.49**
LSUN-R	MSP	43.89	93.93	100.00	64.26	100.00	13.74	100.00	13.66
	ODIN	3.29	99.20	98.96	63.83	100.00	0.14	100.00	0.00
	Mahalanobis	7.43	97.88	98.71	39.24	94.59	16.62	100.00	0.45
	SOFL	1.67	99.29	56.41	90.62	100.00	0.55	100.00	0.43
	OE	0.99	99.43	51.55	92.25	99.99	0.15	100.00	0.02
	ACET	3.87	99.10	77.90	87.37	70.50	**84.01**	99.87	48.53
	CCU	1.53	99.28	57.03	90.53	100.00	0.04	100.00	0.10
	ROWL	36.03	81.47	98.72	50.12	100.00	49.48	100.00	49.48
	NTOM (ours)	**0.38**	**99.57**	17.84	**96.76**	100.00	0.20	100.00	0.27
	ATOM (ours)	0.41	99.33	**16.77**	96.63	52.76	71.84	50.33	75.18
iSUN	MSP	46.18	93.58	100.00	62.76	99.99	13.95	100.00	13.67
	ODIN	4.45	99.00	98.90	62.14	100.00	0.33	100.00	0.01
	Mahalanobis	8.58	98.00	98.10	42.96	89.64	22.78	100.00	0.74
	SOFL	2.24	99.22	53.99	90.97	100.00	0.51	100.00	0.50
	OE	1.14	99.40	48.25	92.46	99.97	0.13	100.00	0.02
	ACET	6.16	98.59	75.36	87.00	78.59	**79.84**	99.63	47.11
	CCU	1.74	99.27	52.44	91.10	100.00	0.05	100.00	0.08
	ROWL	35.44	81.76	97.02	50.97	100.00	49.48	100.00	49.48
	NTOM (ours)	**0.63**	**99.59**	16.25	**96.90**	99.99	0.32	100.00	0.38
	ATOM (ours)	0.66	99.34	**15.10**	96.79	52.48	68.44	**51.94**	**72.08**
Textures	MSP	64.66	87.64	100.00	51.85	100.00	14.14	100.00	13.72
	ODIN	52.45	84.81	99.56	38.20	99.95	0.56	100.00	0.07
	Mahalanobis	25.39	92.20	71.42	61.60	88.85	17.24	99.27	3.60
	SOFL	3.78	99.04	56.81	89.38	99.88	2.06	99.98	1.36
	OE	6.24	98.43	53.32	88.83	99.68	1.40	99.95	0.68
	ACET	11.74	97.96	54.41	90.52	64.49	77.66	94.26	55.24
	CCU	5.83	98.45	54.61	86.33	99.49	1.68	99.84	0.99
	ROWL	19.33	89.82	82.87	58.04	99.89	49.53	99.98	49.49
	NTOM (ours)	2.27	99.42	24.66	95.09	99.49	3.63	99.95	1.67
	ATOM (ours)	**1.81**	**99.47**	**20.05**	**95.92**	**10.05**	**96.47**	**29.01**	**91.40**
Places365	MSP	62.03	88.29	100.00	57.68	100.00	13.66	100.00	13.66
	ODIN	43.84	90.45	99.89	52.81	100.00	0.01	100.00	0.00
	Mahalanobis	85.77	65.76	99.47	22.75	99.79	1.93	100.00	0.66
	SOFL	7.73	97.81	61.66	88.07	100.00	0.47	100.00	0.27
	OE	11.08	97.00	67.91	87.39	100.00	0.03	100.00	0.01
	ACET	18.63	95.97	79.42	85.00	93.09	66.83	99.61	46.19
	CCU	8.49	97.63	67.68	85.75	100.00	0.03	100.00	0.03
	ROWL	43.76	77.60	97.67	50.64	100.00	49.48	100.00	49.48
	NTOM (ours)	6.63	**97.94**	37.01	92.75	100.00	0.06	100.00	0.04
	ATOM (ours)	**6.30**	97.92	**31.44**	**93.41**	**6.96**	**97.78**	**32.99**	**92.93**
SVHN	MSP	59.15	90.99	100.00	41.97	100.00	13.67	100.00	13.66
	ODIN	23.96	95.00	100.00	19.78	100.00	0.00	100.00	0.00
	Mahalanobis	19.73	93.33	90.52	50.89	99.48	8.18	100.00	2.67
	SOFL	0.85	99.47	87.50	79.85	100.00	0.13	100.00	0.07
	OE	1.55	99.16	75.62	89.02	100.00	0.01	100.00	0.02
	ACET	31.50	94.99	83.04	85.25	94.49	69.42	99.81	54.36
	CCU	2.14	99.25	75.34	88.01	100.00	0.00	100.00	0.00
	ROWL	4.73	97.12	98.09	50.43	100.00	49.48	100.00	49.48
	NTOM (ours)	1.06	99.59	67.40	90.23	100.00	0.01	100.00	0.00
	ATOM (ours)	**0.69**	**99.63**	**51.84**	**92.22**	**0.69**	**99.63**	**51.81**	**92.18**

Table 15: Comparison with competitive OOD detection methods. We use CIFAR-10 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.

$\mathcal{D}_{\text{out}}^{\text{test}}$	Method	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑	FPR (5% FNR) ↓	AUROC ↑
		Natural OOD		Corruption OOD		L_∞ OOD		Comp. OOD	
LSUN-C	MSP	62.03	84.78	100.00	32.47	100.00	2.52	100.00	2.31
	ODIN	15.47	97.34	100.00	42.25	100.00	0.20	100.00	0.01
	Mahalanobis	47.44	93.47	98.80	58.23	98.94	15.07	99.97	3.01
	SOFL	17.38	96.66	100.00	51.59	100.00	1.10	100.00	0.58
	OE	14.75	97.33	99.91	54.29	100.00	1.61	100.00	0.64
	ACET	14.60	97.41	98.65	67.81	23.07	95.35	98.88	56.02
	CCU	**12.03**	**97.84**	99.60	61.24	100.00	0.86	100.00	0.50
	ROWL	88.67	55.35	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	20.61	96.58	95.91	83.28	100.00	1.31	100.00	0.25
	ATOM (ours)	21.40	96.31	**79.72**	**87.67**	**21.50**	**96.26**	**79.98**	**87.11**
LSUN-R	MSP	77.48	76.40	100.00	32.21	100.00	1.94	100.00	1.78
	ODIN	34.81	93.37	100.00	45.41	100.00	0.22	100.00	0.00
	Mahalanobis	**14.87**	97.06	99.89	31.14	94.81	24.18	100.00	0.37
	SOFL	50.27	90.28	99.88	50.12	100.00	0.11	100.00	0.20
	OE	56.25	84.35	99.96	41.17	100.00	0.70	100.00	0.52
	ACET	56.35	88.17	99.50	51.85	98.67	18.64	99.74	22.45
	CCU	38.44	91.83	99.94	50.62	100.00	0.59	100.00	0.47
	ROWL	88.25	55.57	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	37.92	94.31	99.11	65.00	100.00	0.36	100.00	0.06
	ATOM (ours)	17.93	96.94	**95.72**	**71.51**	**31.39**	**87.38**	**95.87**	**66.15**
iSUN	MSP	78.87	75.69	100.00	31.83	100.00	2.08	100.00	1.82
	ODIN	38.92	92.15	100.00	43.43	100.00	0.31	100.00	0.00
	Mahalanobis	**16.46**	**96.75**	99.76	33.38	89.71	28.16	100.00	0.38
	SOFL	53.51	89.27	99.96	48.75	100.00	0.19	100.00	0.21
	OE	61.59	81.51	99.99	39.94	100.00	0.81	100.00	0.54
	ACET	60.49	86.80	99.70	49.61	98.54	19.92	99.94	23.51
	CCU	40.97	90.89	99.98	49.21	100.00	0.79	100.00	0.44
	ROWL	90.42	54.48	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	43.66	93.24	99.51	61.40	100.00	0.41	100.00	0.02
	ATOM (ours)	20.09	96.62	**97.05**	**68.31**	**35.70**	**85.87**	**97.13**	**63.16**
Textures	MSP	85.57	70.08	100.00	25.93	100.00	2.63	100.00	2.28
	ODIN	83.58	70.71	100.00	27.30	100.00	0.11	100.00	0.01
	Mahalanobis	**34.59**	89.82	**78.35**	62.36	89.27	20.33	99.18	5.43
	SOFL	57.00	87.35	99.73	44.11	99.98	0.59	100.00	0.34
	OE	59.86	86.17	99.88	42.95	99.98	1.45	100.00	0.73
	ACET	62.02	86.26	99.70	49.02	83.17	63.61	99.86	40.58
	CCU	60.80	86.34	99.88	44.90	100.00	1.39	100.00	0.62
	ROWL	97.00	51.19	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	38.21	**91.06**	95.34	66.86	99.82	2.43	100.00	0.60
	ATOM (ours)	40.11	90.28	90.21	**69.99**	**47.27**	**82.52**	**91.45**	**65.91**
Places365	MSP	83.65	73.71	100.00	32.13	100.00	1.83	100.00	1.91
	ODIN	79.19	76.48	100.00	39.16	100.00	0.00	100.00	0.00
	Mahalanobis	94.64	59.52	99.80	19.43	99.96	1.13	100.00	0.50
	SOFL	60.49	**87.57**	100.00	40.25	100.00	0.06	100.00	0.15
	OE	58.37	86.39	100.00	50.83	100.00	0.57	100.00	0.54
	ACET	56.26	86.75	99.66	57.36	83.60	72.35	99.83	44.27
	CCU	**55.23**	87.21	100.00	44.03	100.00	0.46	100.00	0.43
	ROWL	96.86	51.26	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	56.54	84.27	99.33	57.32	100.00	0.01	100.00	0.02
	ATOM (ours)	56.52	84.53	**96.65**	**63.43**	**58.68**	**82.50**	**96.68**	**62.36**
SVHN	MSP	80.71	76.00	100.00	25.69	100.00	2.47	100.00	2.29
	ODIN	88.66	71.65	100.00	24.17	100.00	0.00	100.00	0.00
	Mahalanobis	47.78	90.54	**98.93**	53.25	99.96	6.34	100.00	2.78
	SOFL	**21.50**	96.15	100.00	36.59	100.00	0.07	100.00	0.16
	OE	44.47	92.58	100.00	40.86	100.00	0.53	100.00	0.57
	ACET	55.86	90.36	100.00	49.51	70.55	86.86	99.99	44.93
	CCU	50.79	91.59	100.00	40.01	100.00	0.41	100.00	0.40
	ROWL	98.88	50.25	100.00	49.69	100.00	49.69	100.00	49.69
	NTOM (ours)	24.67	**96.20**	99.83	60.37	100.00	0.01	100.00	0.00
	ATOM (ours)	37.78	93.68	99.54	**70.86**	**37.78**	**93.68**	**99.55**	**70.23**

Table 16: Comparison with competitive OOD detection methods. We use CIFAR-100 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) L_∞ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.