# ATOM: Robust Out-of-distribution Detection via Informative Outlier Mining

## Abstract

Detecting out-of-distribution (OOD) inputs is critical for safely deploying deep learning models in an open-world setting. However, existing OOD detection solutions can be brittle under small adversarial perturbations. In this paper, we propose a simple and effective method, *Adversarial Training with informative Outlier Mining* (ATOM), to robustify OOD detection. Our key observation is that while unlabeled data can be used as auxiliary OOD training data, the majority of these data points are not informative to improve the decision boundary of the OOD detector. We show that, by carefully choosing which outliers to train on, one can significantly improve the robustness of the OOD detector, and somewhat surprisingly, generalize to some adversarial attacks not seen during training. We provide additionally a unified evaluation framework that allows future research examining the robustness of OOD detection algorithms. ATOM achieves state-of-the-art performance under a broad family of natural and perturbed OOD evaluation tasks, surpassing previous methods by a large margin. Finally, we provide theoretical insights for the benefit of auxiliary unlabeled data and outlier mining.

## 1 Introduction

Out-of-distribution (OOD) detection has become an indispensable part of building reliable open-world machine learning models (Amodei et al., 2016). An OOD detector determines whether an input is from the same distribution as the training data, or a different distribution (out-of-distribution). The performance of the OOD detector is central for safety-critical applications such as autonomous driving (Eykholt et al., 2018) or rare disease identification (Blauwkamp et al., 2019).

Despite exciting progress made in OOD detection, previous methods mostly focused on natural OOD data (Hendrycks & Gimpel, 2016; Liang et al., 2017; Lee et al., 2018; Lakshminarayanan et al., 2017; Hendrycks et al., 2018; Mohseni et al., 2020). Scant attention has been paid to the robustness aspect of OOD detection. Recent work by Hein et al. and Sehwag et al. considered worst-case OOD detection under adversarial perturbations (Papernot et al., 2016; Goodfellow et al., 2014; Biggio et al., 2013; Szegedy et al., 2013). For example, an OOD image (e.g., mailbox) can be perturbed to be misclassified by the OOD detector as in-distribution (traffic sign data). Such an adversarial OOD example is then passed to the image classifier and trigger undesirable prediction and action (e.g., speed limit 70). Therefore, the failure mode leads to the following important question: how can we make out-of-distribution detection algorithm robust in the presence of small perturbations to OOD inputs?

Motivated by this, we propose a method called *Adversarial Training with informative Outlier Mining* (ATOM), which achieves state-of-the-art performance on a broad family of natural and perturbed OOD inputs. Our key observation is that while unlabeled data provides the abundance of OOD data to train on, the majority OOD examples can be too easy to provide useful information and meaningfully improve the decision boundary of OOD detector. We show that, by carefully choosing which OOD data to train on, one can significantly improve the robustness of an OOD detector, and somewhat surprisingly, generalize to unseen adversarial attacks.

**Contributions.** We provide a unified framework that allows examining the robustness of OOD detection algorithms under a broad family of OOD inputs, as illustrated in Figure 1. Our evaluation goes beyond previous approaches that primarily focus on natural OOD inputs. Under this taxonomy, we extensively examine the robustness of eight common OOD detection methods (we provide

Figure 1: When deploying an image classification system (OOD detector $G(x)$ + image classifier $f(x)$) in an open world, there can be multiple types of out-of-distribution examples. We consider a broad family of OOD inputs, including (a) natural OOD, (b) adversarially perturbed OOD under $L_\infty$ norm perturbation, and (c) corruption attacked OOD. In (b-d), a perturbed OOD input (e.g., a perturbed mailbox image) can mislead the OOD detector to classify it as an in-distribution sample. This can trigger the downstream image classifier $f(x)$ to predict it as one of the in-distribution classes (e.g., speed limit 70). Through *adversarial training with informative outlier mining* (ATOM), our method can robustify the decision boundary of OOD detector $G(x)$, which leads to improved performance across all types of OOD inputs. Solid lines are actual computation flow.

description for each method in Appendix B.3). Our experiments reveal that existing methods have heterogeneous performance across various types of perturbations. In particular, we show that methods relying on pre-trained neural networks (Hendrycks & Gimpel, 2016; Liang et al., 2017; Lee et al., 2018) are fragile across all types of perturbations. While ACET (Hein et al., 2019) provides robustness against adversarial OOD examples generated by $L_\infty$-norm bounded attacks, we observe that such defense can be somewhat brittle when we switch to attacks not seen during training.

To this end, we devise a simple and effective method, ATOM, which improves the OOD detection performance on both clean data and perturbed inputs. The key idea of our method is to adaptively choose informative OOD training examples that the OOD detector is mildly uncertain about. When evaluating on natural OOD data, our method outperforms state-of-the-art method (Mohseni et al., 2020) on all datasets. On CIFAR-10, our method outperforms the best baseline ACET (Hein et al., 2019) by **53.9%** (FPR) under $L_\infty$-norm attacked OOD inputs. Our method can also generalize surprisingly well to unknown corrupted OOD inputs, outperforming the best baseline by **30.99%** measured by FPR. Finally, while almost every method fails under the strongest compositional attack, our method reduces the FPR by **57.99%**. Our training method leads to improved OOD detection while maintaining similar classification accuracy on in-distribution data as a pre-trained model. We conduct ablation analysis to explore the effect of informative outlier sampling.

Lastly, we provide theoretical analysis formalizing the intuition behind our method. Under a Gaussian model of the data, we show that the auxiliary data can significantly reduce the in-distribution sample size needed. We also show that using outlier mining helps learn a correct detector in the presence of non-informative examples. These theoretical results justify using auxiliary unlabeled data and outlier mining for robust OOD detection.

## 2 PROBLEM STATEMENT

In this section, we describe the problem of robust out-of-distribution detection, as well as a unified evaluation framework for this problem.

**Preliminaries.** We consider a training dataset $\mathcal{D}_{\text{in}}^{\text{train}}$ drawn i.i.d. from a data distribution $P_{\boldsymbol{X},Y}$, where $\boldsymbol{X}$ is the sample space and $Y = \{1, 2, \cdots, K\}$ is the set of labels. An image classifier $f(\mathbf{x})$ is trained on the in-distribution, $P_{\boldsymbol{X}}$, the marginal distribution of $P_{\boldsymbol{X},Y}$. The OOD examples are

revealed during test time, which are from a different distribution $Q_X$, potentially with perturbations added. The task of *robust out-of-distribution detection* is to learn a detector $G : \mathbf{x} \to \{-1, 1\}$, which outputs 1 for $\mathbf{x}$ from $P_X$ and output $-1$ for a clean or perturbed OOD example $\mathbf{x}$ from $Q_X$.

Formally, let $\Omega(\mathbf{x})$ be a set of small perturbations on an OOD example $\mathbf{x}$. The detector is evaluated on $\mathbf{x}$ from $P_X$ and on the worst-case input inside $\Omega(\mathbf{x})$ for an OOD example from $Q_X$. The false negative rate (FNR) and false positive rate (FPR) are defined as:

$$\text{FNR}(G) = \mathbb{E}_{\mathbf{x} \sim P_X} \mathbb{I}[G(\mathbf{x}) = -1], \quad \text{FPR}(G; Q_X, \Omega) = \mathbb{E}_{\mathbf{x} \sim Q_X} \max_{\delta \in \Omega(\mathbf{x})} \mathbb{I}[G(\mathbf{x} + \delta) = 1]. \quad (1)$$

Note that during training, the algorithm has no data from the unknown outlier distribution $Q_X$. As in previous work, we consider the case that the algorithm have access to an auxiliary outlier dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ from another distribution $U_X$. So the key difference from typical robust classification tasks is that the outlier distribution $Q_X$ in test time is unknown in training time (even in the case with auxiliary data, $Q_X$ can be different from $U_X$). This leads to significant challenges, e.g., our experiments show that simply applying adversarial training does not lead to satisfactory performance. Our empirical and theoretical evidence (Figure 1 and Section 5) show that since $Q_X$ can be different from $U_X$, only part of the data from $U_X$ is useful. This crucial insight then leads to our design of a simple but very effective algorithm described soon in Section 3.

**Robust OOD Evaluation Tasks.** We consider the following family of OOD inputs:

- **Natural OOD**: This is equivalent to the classic OOD evaluation where clean input $\mathbf{x}$ is used and $\Omega = \varnothing$.
- $L_\infty$ **attacked OOD (white-box)**: We consider small $L_\infty$-norm bounded perturbations on $\mathbf{x}$ (Madry et al., 2017; Athalye et al., 2018), which induce the model to produce high confidence scores (or low OOD scores) for OOD inputs. The set of adversarial perturbations is $\Omega_{\infty,\epsilon}(\mathbf{x})$, where $\epsilon$ is the adversarial budget. We provide attack algorithms for all eight OOD detection methods in Appendix B.4.
- **Corruption attacked OOD (black-box)**: We consider a more realistic type of attack based on common corruptions (Hendrycks & Dietterich, 2019), which could appear naturally in the physical world. Some corruptions include noise, blur, and weather, etc. We provide details in Appendix B.4.
- **Compositionally attacked OOD (white-box)**: Lastly, we consider applying $L_\infty$-norm bounded attack and corruption attack jointly to an input $\mathbf{x}$, as considered in (Laidlaw & Feizi, 2019).

We show visualizations for four types of OOD samples in Appendix B.5. In Table 4, we list common OOD detection methods and corresponding OOD inputs considered. To our knowledge, we are the first to examine the performance of OOD methods under all four types of perturbations.

## 3 ATOM: Adversarial Training with Informative Outlier Mining

In this section, we introduce our method, *Adversarial Training with informative Outlier Mining* (ATOM), for robust OOD detection. In what follows, we first describe the adversarial training objective and then introduce how we use informative outlier mining to improve the learning.

**Training Objective.** We consider a $(K + 1)$-way classifier network $\hat{f}$, where the $(K + 1)$-th class label indicates out-of-distribution class. Denote by $\hat{F}_\theta(\mathbf{x})$ the softmax output of $\hat{f}$ on $\mathbf{x}$. The robust training objective is given by

$$\underset{\theta}{\text{minimize}} \quad \mathbb{E}_{(\mathbf{x}, y) \sim \mathcal{D}_{\text{in}}^{\text{train}}}[\ell(\mathbf{x}, y; \hat{F}_\theta)] + \lambda \cdot \mathbb{E}_{\mathbf{x} \sim \mathcal{D}_{\text{out}}^{\text{train}}} \max_{\mathbf{x}' \in \Omega_{\infty,\epsilon}(\mathbf{x})}[\ell(\mathbf{x}', K + 1; \hat{F}_\theta)], \quad (2)$$

where $\ell$ is the cross entropy loss, and $\mathcal{D}_{\text{out}}^{\text{train}}$ is the OOD training dataset. We use Projected Gradient Descent (PGD) (Madry et al., 2017) to solve the inner max of the objective, and apply it to half of a minibatch while keeping the other half clean to ensure proper performance on both clean and perturbed data. Once trained, the OOD detector $G(\mathbf{x})$ can be constructed by:

$$G(\mathbf{x}) = \begin{cases} -1 & \text{if } \hat{F}(\mathbf{x})_{K+1} \geq \gamma, \\ 1 & \text{if } \hat{F}(\mathbf{x})_{K+1} < \gamma, \end{cases} \quad (3)$$

(a) OOD score distribution     (b) highest OOD scores     (c) lowest OOD scores

Figure 2: On CIFAR-10, we train a DenseNet with objective (2) for 100 epochs **without** informative outlier mining. At epoch 30, we randomly sample 400,000 data points from $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, and plot the OOD score frequency distribution (a). We observe that the model quickly converges to solution where OOD score distribution becomes dominated by *easy* examples with score closer to 1, as shown in (b). Therefore, training on these easy OOD data points can no longer help improve the decision boundary of OOD detector. We also observe that training on *too hard* examples with score closer to 0 might be harmful since those examples resemble in-distribution data (c).

where $\gamma$ is the threshold, and in practice can be chosen on the in-distribution data so that a high fraction of test examples are correctly classified by $G$. We call $\hat{F}(\mathbf{x})_{K+1}$ the *OOD score* of $\mathbf{x}$. For an input that is labeled as in-distribution by $G$, one can obtain its semantic label using $F(\mathbf{x})$:

$$F(\mathbf{x}) = \underset{y \in \{1,2,\cdots,K\}}{\arg\max} \ \hat{F}(\mathbf{x})_y \tag{4}$$

**Informative Outlier Mining.** When training a neural network, we may not have data from the test out-of-distribution $Q_{\mathbf{X}}$, but instead, have an unlabeled auxiliary dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ from distribution $U_{\mathbf{X}}$. While unlabeled data gives rise to the abundance of OOD data to train, we observe that the above training objective quickly converges to the solution where OOD training data yield high OOD scores (see Figure 2). Continuing the training process on these OOD data points can no longer provide meaningful information that improves the decision boundary of the OOD detector.

Motivated by this, we propose to adaptively choose OOD training examples where the detector is mildly uncertain about. We provide the complete training algorithm using informative outlier mining in Algorithm 1. Our method is different from random sampling as used in previous works (Hendrycks et al., 2018; Hein et al., 2019; Meinke & Hein, 2019; Mohseni et al., 2020). Specifically, during each training epoch, we randomly sample $N$ data points from the unlabeled OOD dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, and use the current model to infer the OOD scores[1]. After that, we sort the data points according to the OOD scores and select a subset of $n < N$ data points, starting with the $qN^{\text{th}}$ data in the sorted list. We then use the selected samples as OOD training data $\mathcal{D}_{\text{out}}^{\text{train}}$ for the next epoch of training. Intuitively, $q$ determines the *informativeness* of the sampled points w.r.t the OOD detector. The larger $q$ is, the less informative those sampled examples become. We report ablation analysis in more detail in Section 4.2.

Note that informative outlier mining is performed on (non-adversarial) unlabeled data. Selected examples are then used in the robust training objective (2). To see how informative outlier mining alone improves the robust OOD detection, we also consider the following objective without adversarial training:

$$\underset{\theta}{\text{minimize}} \quad \mathbb{E}_{(\mathbf{x},y) \sim \mathcal{D}_{\text{in}}^{\text{train}}}[\ell(\mathbf{x}, y; \hat{F}_\theta)] + \lambda \cdot \mathbb{E}_{\mathbf{x} \sim \mathcal{D}_{\text{out}}^{\text{train}}}[\ell(\mathbf{x}, K+1; \hat{F}_\theta)], \tag{5}$$

We call the method using objective (5) *Natural Training with informative Outlier Mining* (NTOM). For NTOM, we will use the same hyperparameters as those selected for ATOM. Both our empirical and theoretical studies reveal the importance of outlier mining for the robust OOD detection task.

---

[1]Since the inference stage can be fully parallel, outlier mining can be applied with relatively low overhead.

---

**Algorithm 1** ATOM: Adversarial Training with informative Outlier Mining.

---

**input** $\mathcal{D}_{\text{in}}^{\text{train}}, \mathcal{D}_{\text{out}}^{\text{auxiliary}}, \hat{F}_\theta, m, N, n, q$
**output** $F, G$
    **for** $t = 1, 2, \cdots, m$ **do**
        Randomly sample $N$ data points from $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ to get a candidate set $\mathcal{S}$.
        Compute OOD scores on $\mathcal{S}$ using current model $\hat{F}_\theta$ to get set $V = \{\hat{F}(\mathbf{x})_{K+1} \mid \mathbf{x} \in \mathcal{S}\}$.
        Sort scores in $V$ from the lowest to the highest.
        $\mathcal{D}_{\text{out}}^{\text{train}} \leftarrow V[qN : qN + n]$        $\triangleright \{q \in [0, 1 - n/N]\}$
        Train $\hat{F}_\theta$ for one epoch using the training objective of (2).
    **end for**
    Build $G$ and $F$ using (3) and (4) respectively.

---

## 4 EXPERIMENTS

In this section, we describe our experimental setup (Section 4.1) and show that ATOM can substantially improve OOD detection performance on both clean data and adversarially perturbed inputs. We conducted extensive ablation analysis to explore the effect of informative outlier mining (Section **??**).

### 4.1 SETUP

**In-distribution Datasets.** We use SVHN (Netzer et al., 2011), CIFAR-10, and CIFAR-100 (Krizhevsky et al., 2009) datasets as in-distribution datasets.

**Auxiliary Datasets.** By default, we will use 80 Million Tiny Images (Torralba et al., 2008) as $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$, which is a common setting in prior works. We also use another auxiliary dataset ImageNet (Chrabaszcz et al., 2017) for training and the results are shown in Appendix B.8

**Out-of-distribution Datasets.** For OOD test dataset, we follow the procedure in (Liang et al., 2017; Hendrycks et al., 2018) and use six different natural image datasets. If the in-distribution dataset is CIFAR-10 or CIFAR-100, we use SVHN, Textures (Cimpoi et al., 2014), Places365 (Zhou et al., 2017), LSUN (crop), LSUN (resize) (Yu et al., 2015), and iSUN (Xu et al., 2015). If the in-distribution dataset is SVHN, we use CIFAR-10, Textures, Places365, LSUN (crop), LSUN (resize), and iSUN. Besides natural image datasets, we also consider Gaussian Noise and Uniform Noise as OOD test data, and show results in Appendix B.11.

**Hyperparameters.** The hyperparameter $q$ is chosen on a separate validation set from Tiny Images (Torralba et al., 2008), which does not depend on test-time OOD data (see Appendix B.7). Based on the validation results in Table 5, we set $q = 0$ for SVHN, $q = 0.125$ for CIFAR-10 and $q = 0.5$ for CIFAR-100. To ensure fair comparison, in each epoch, ATOM uses the same amount of outlier data as OE, where $n$ is twice larger than the in-distribution data size (i.e., 50,000). For all experiments, we set $\lambda = 1$. For CIFAR-10 and CIFAR-100, we set $N = 400,000$, and $n = 100,000$; For SVHN, we set $N = 586,056$, and $n = 146,514$.

**Evaluation Metrics.** We measure the following metrics: the false positive rate (FPR) at 5% false negative rate (FNR) and the area under the receiver operating characteristic curve (AUROC).

More details about experimental set up are in Appendix B.1.

### 4.2 RESULTS

**How does ATOM compare to existing solutions?** We show in Table 6 that ATOM outperforms competitive OOD detection methods on both natural and perturbed OOD evaluation tasks. All the numbers reported are averaged over six different OOD test datasets described in Sec. 4.1. First, on natural OOD data, ATOM outperforms current state-of-the-art method SOFL (Mohseni et al., 2020). On CIFAR-10, our method outperforms the best baseline ACET (Hein et al., 2019) by **53.9%** (FPR) under the $L_\infty$ attacked OOD task. While ACET is somewhat brittle under unknown attacks, our method can generalize surprisingly well to unknown corruption attacked OOD inputs, outperforming the best baseline by **30.99%** measured by FPR. Finally, while almost every method fails under the strongest compositional attack, our method reduces the FPR by **57.99%**. The performance

| $\mathcal{D}_{in}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| **SVHN** | MSP | 38.84 | 93.57 | 99.68 | 68.48 | 99.89 | 1.39 | 100.00 | 0.19 |
| | ODIN | 31.45 | 93.52 | 97.11 | 63.21 | 99.86 | 0.61 | 100.00 | 0.05 |
| | Mahalanobis | 22.80 | 95.57 | 93.14 | 60.78 | 97.33 | 8.89 | 99.89 | 0.23 |
| | SOFL | 0.06 | 99.98 | 3.78 | 99.07 | 75.31 | 46.78 | 99.81 | 2.75 |
| | OE | 0.60 | 99.88 | 23.44 | 96.23 | 69.36 | 52.19 | 99.65 | 1.27 |
| | ACET | 0.49 | 99.91 | 17.03 | 97.23 | 29.33 | 86.75 | 99.85 | 5.13 |
| | CCU | 0.50 | 99.90 | 24.17 | 96.11 | 52.17 | 62.24 | 99.42 | 1.60 |
| | ROWL | 2.04 | 98.87 | 55.03 | 72.37 | 77.24 | 61.27 | 99.79 | **50.00** |
| | NTOM (ours) | **0.04** | **99.98** | **2.87** | **99.16** | 60.28 | 64.06 | 99.78 | 1.50 |
| | ATOM (ours) | 0.07 | 99.97 | 5.47 | 98.52 | **7.02** | **98.00** | **96.33** | 49.52 |
| **CIFAR-10** | MSP | 50.54 | 91.79 | 100.00 | 58.35 | 100.00 | 13.82 | 100.00 | 13.67 |
| | ODIN | 21.65 | 94.66 | 99.37 | 51.44 | 99.99 | 0.18 | 100.00 | 0.01 |
| | Mahalanobis | 26.95 | 90.30 | 91.92 | 43.94 | 95.07 | 12.47 | 99.88 | 1.58 |
| | SOFL | 2.78 | 99.04 | 62.07 | 88.65 | 99.98 | 1.01 | 100.00 | 0.76 |
| | OE | 3.66 | 98.82 | 56.25 | 90.66 | 99.94 | 0.34 | 99.99 | 0.16 |
| | ACET | 12.28 | 97.67 | 66.93 | 88.43 | 74.45 | 78.05 | 96.88 | 53.71 |
| | CCU | 3.39 | 98.92 | 56.76 | 89.38 | 99.91 | 0.35 | 99.97 | 0.21 |
| | ROWL | 25.03 | 86.96 | 94.34 | 52.31 | 99.98 | 49.49 | 100.00 | 49.48 |
| | NTOM (ours) | 1.87 | **99.28** | 30.58 | 94.67 | 99.90 | 1.22 | 99.99 | 0.45 |
| | ATOM (ours) | **1.69** | 99.20 | **25.26** | **95.29** | 20.55 | 88.94 | 38.89 | 86.71 |
| **CIFAR-100** | MSP | 78.05 | 76.11 | 100.00 | 30.04 | 100.00 | 2.25 | 100.00 | 2.06 |
| | ODIN | 56.77 | 83.62 | 100.00 | 36.95 | 100.00 | 0.14 | 100.00 | 0.00 |
| | Mahalanobis | 42.63 | 87.86 | 95.92 | 42.96 | 95.44 | 15.87 | 99.86 | 2.08 |
| | SOFL | 43.36 | 91.21 | 99.93 | 45.23 | 100.00 | 0.35 | 100.00 | 0.27 |
| | OE | 49.21 | 88.05 | 99.96 | 45.01 | 100.00 | 0.94 | 100.00 | 0.59 |
| | ACET | 50.93 | 89.29 | 99.53 | 54.19 | 76.27 | 59.45 | 99.71 | 38.63 |
| | CCU | 43.04 | 90.95 | 99.90 | 48.34 | 100.00 | 0.75 | 100.00 | 0.48 |
| | ROWL | 93.35 | 53.02 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 36.94 | 92.61 | 98.17 | 65.70 | 99.97 | 0.76 | 100.00 | 0.16 |
| | ATOM (ours) | **32.30** | **93.06** | **93.15** | **71.96** | 38.72 | 88.03 | **93.44** | **69.15** |

Table 1: Comparison with competitive OOD detection methods. We use DenseNet as network architecture for all methods. We evaluate on four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 4.1. **Bold** numbers are superior results. Additional ablation results on a different architecture, WideResNet, are provided in Appendix B.9.

is noteworthy since our method is not trained explicitly on corrupted OOD inputs. Consistent performance improvement is observed on other in-distribution datasets (SVHN and CIFAR-100).

**How does ATOM compare to NTOM?** We perform an ablation study that isolates the effect of adversarial training. In Table 6, we show that NTOM achieves comparable performance as ATOM on natural OOD and corruption attacked OOD. However, NTOM is less robust under $L_\infty$ OOD (with 79.35% reduction in FPR on CIFAR-10). This underlies the importance of having both adversarial training and outlier mining (ATOM) for overall good performance.

**How does informative outlier mining compare to random sampling?** We further perform an ablation study that isolates the effect of informative outlier mining. In Table 2, we show that using informative outlier mining overall works better than random sampling. For example, on CIFAR-10, our method ($q = 0.125$) achieves FPR 25.26% under unseen corrupted OOD inputs, compared to random sampling (42.28%). On natural OOD inputs, our method ($q = 0.125$) reduces the FPR by 26.91% on more complex dataset CIFAR-100. This suggests that using adversarial training alone without informative outlier mining leads to suboptimal performance. We provide theoretical reasoning for the benefit of outlier mining in Section 5.

**How does the sampling parameter affect performance?** Table 2 shows the performance where we vary the sampling interval with different $q$. For all three datasets, training on OOD inputs primarily with large OOD scores (i.e., too easy examples with $q = 0.75$) worsens the performance, which suggests the necessity to include examples on which the OOD detector is uncertain. Interestingly, in setting where the in-distribution data and auxiliary data are disjoint (e.g. SVHN/80M TinyImages), $q = 0$ is optimal, which means the hardest outliers are selected for training. However, in more realistic settings, the auxiliary data can almost always contain data similar to in-distribution data (e.g. CIFAR/80M TinyImages). Even without removing near-duplicates exhaustively, ATOM can

adaptively avoid training on those near-duplicates of in-distribution data (e.g. using $q = 0.125$ for CIFAR-10 and $q = 0.5$ for CIFAR-100).

| $\mathcal{D}_{\text{in}}^{\text{test}}$ | Model | FPR (5% FNR) $\downarrow$ | AUROC $\uparrow$ | FPR (5% FNR) $\downarrow$ | AUROC $\uparrow$ | FPR (5% FNR) $\downarrow$ | AUROC $\uparrow$ | FPR (5% FNR) $\downarrow$ | AUROC $\uparrow$ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| SVHN | ATOM (rand. sample) | 0.35 | 99.91 | 13.09 | 97.50 | 11.72 | 96.63 | 98.66 | 40.48 |
| | ATOM (q=0.0) | 0.07 | 99.97 | 5.47 | 98.52 | 7.02 | 98.00 | 96.33 | 49.52 |
| | ATOM (q=0.125) | 1.30 | 99.63 | 34.97 | 94.97 | 39.61 | 82.92 | 99.92 | 6.30 |
| | ATOM (q=0.25) | 1.36 | 99.60 | 41.98 | 94.30 | 52.39 | 71.34 | 99.97 | 1.35 |
| | ATOM (q=0.5) | 2.11 | 99.46 | 44.85 | 93.84 | 59.72 | 65.59 | 99.97 | 3.15 |
| | ATOM (q=0.75) | 2.91 | 99.26 | 51.33 | 93.07 | 66.20 | 57.16 | 99.96 | 2.04 |
| CIFAR-10 | ATOM (rand. sample) | 2.65 | 99.11 | 42.28 | 91.94 | 44.31 | 68.64 | 65.17 | 72.62 |
| | ATOM (q=0.0) | 2.24 | 99.20 | 40.46 | 92.86 | 36.80 | 73.11 | 66.15 | 73.93 |
| | ATOM (q=0.125) | 1.69 | 99.20 | 25.26 | 95.29 | 20.55 | 88.94 | 38.89 | 86.71 |
| | ATOM (q=0.25) | 2.34 | 99.12 | 22.71 | 95.29 | 24.93 | 94.83 | 41.58 | 91.56 |
| | ATOM (q=0.5) | 4.03 | 98.97 | 33.93 | 93.51 | 22.39 | 95.16 | 45.11 | 90.56 |
| | ATOM (q=0.75) | 5.35 | 98.77 | 41.02 | 92.78 | 21.87 | 93.37 | 43.64 | 91.98 |
| CIFAR-100 | ATOM (rand. sample) | 51.50 | 89.62 | 99.70 | 58.61 | 70.33 | 58.84 | 99.80 | 34.98 |
| | ATOM (q=0.0) | 44.38 | 91.92 | 99.76 | 60.12 | 68.32 | 65.75 | 99.80 | 49.85 |
| | ATOM (q=0.125) | 26.91 | 94.97 | 98.35 | 71.53 | 34.66 | 87.54 | 98.42 | 68.52 |
| | ATOM (q=0.25) | 32.43 | 93.93 | 97.71 | 72.61 | 40.37 | 82.68 | 97.87 | 65.19 |
| | ATOM (q=0.5) | 32.30 | 93.06 | 93.15 | 71.96 | 38.72 | 88.03 | 93.44 | 69.15 |
| | ATOM (q=0.75) | 38.56 | 91.20 | 97.59 | 58.53 | 62.66 | 78.70 | 97.97 | 54.89 |

Table 2: Ablation study on informative outlier mining. We use DenseNet as network architecture. $\uparrow$ indicates larger value is better, and $\downarrow$ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets mentioned in section 4.1. We **do not** use OOD test set for tuning $q$. Please refer to Table 5 for validation results.

## 5 THEORETICAL INSIGHTS

There are two key aspects to our algorithms: (i) Leveraging vast auxiliary outlier data to reduce the in-distribution sample complexity, and (ii) Mining the informative outliers so that we train with outliers that are neither too easy (providing no useful information), nor too hard (which may conflict with the in-distribution data). In this section we provide analysis in a simple Gaussian data model in which both points manifest rigorously. While the Gaussian model may be much simpler than the practical data distributions, its simplicity is actually desired for our analytical purpose of demonstrating the insights. Furthermore, the analysis in this simple model also have implications for more complicated and practical models (see the remark after Proposition 2 for details). Due to lack of space, proofs are deferred to Appendix A, in which we also give additional bounds without assuming Gaussian data.

**Gaussian data model.** Given $\mu \in \mathbb{R}^d, \sigma > 0, \nu > 0$, in our model: (1) $P_{\mathbf{X}}$ is $\mathcal{N}(\mu, \sigma^2 I)$; (2) $Q_{\mathbf{X}}$ can be any distribution from the family $\mathcal{Q} = \{\mathcal{N}(-\mu + v, \sigma^2 I) : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$; (3) the hypothesis class of the OOD detectors is $\mathcal{G} = \{G_\theta(\mathbf{x}) = \text{sign}(\theta^\top \mathbf{x}) : \theta \in \mathbb{R}^d\}$. We also assume the following parameter values (unless otherwise stated): first choose an integer $n_0 > 0$, then let

$$\epsilon \in (0, 1/2), \quad \|\mu\|_2^2 = d \gg n_0/\epsilon^4, \quad \sigma^2 = \sqrt{dn_0}, \quad \nu \leq \|\mu\|_2/4. \tag{6}$$

The parameters ensure the existence of a suitable detector and enable analysis of the benefit of the auxiliary outlier data for training. We consider the FNR and the FPR under $\ell_\infty$ perturbations of magnitude $\epsilon$. $Q_{\mathbf{X}}$ is not accessible in training time, so we should bound $\sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(G; Q_{\mathbf{X}})$.

**Auxiliary outlier data reduces in-distribution sample complexity.** Given only in-distribution data $\{\mathbf{x}_i\}_{i=1}^n$, we show a lower bound of the sample size: *any* algorithm cannot achieve non-trivial errors with less samples.

**Proposition 1.** *Let $\mathbb{A}_n$ be any learning algorithm mapping a dataset $S$ consisting of $n$ i.i.d. samples from $P_{\mathbf{X}}$ to a detector $\mathbb{A}_n(S)$. Let $\mu$ be drawn from $\mathcal{N}(0, I)$. If $n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{16 \log d}$, then*

$$\mathbb{E}\left\{\text{FNR}(\mathbb{A}_n(S)) + \sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(\mathbb{A}_n(S); Q_{\mathbf{X}}, \Omega_{\infty, \epsilon}(\mathbf{x}))\right\} \geq \frac{1}{2}(1 - d^{-1}) \tag{7}$$

*where the expectation is with respect to the randomness in $S$ and $\mathbb{A}_n$.*

Now we turn to the case where we additionally have auxiliary data $\{\tilde{\mathbf{x}}_i\}_{i=1}^{n'}$ from a distribution $U_\mathbf{X}$, which we use for better estimating the OOD detector. Specifically, $U_\mathbf{X}$ is defined by first drawing $v$ uniformly at random from the ball $\{v : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$, then drawing $\tilde{\mathbf{x}}$ from $\mathcal{N}(-\mu + v, \sigma^2 I)$. Consider the detector $G_{\hat{\theta}_{n,n'}}$ given by $\hat{\theta}_{n,n'} = \frac{1}{n+n'}\left(\sum_{i=1}^n \mathbf{x}_i - \sum_{i=1}^{n'} \tilde{\mathbf{x}}_i\right).$

**Proposition 2.** *There exists a universal constant $c$ such that for the parameter setting equation 6 with $\sqrt{d/n_0} \geq c/\epsilon^2$, we have that if $n \geq n_0$ and $n' \geq n_0 \cdot 4\epsilon^2\sqrt{d/n_0}$, then*

$$\mathbb{E}_{\hat{\theta}_{n,n'}}\mathrm{FNR}(G_{\hat{\theta}_{n,n'}}) \leq 10^{-3}, \quad \mathbb{E}_{\hat{\theta}_{n,n'}}\sup_{Q_\mathbf{X} \in \mathcal{Q}}\mathrm{FPR}(G_{\hat{\theta}_{n,n'}}; Q_\mathbf{X}, \Omega_{\infty,\epsilon}(\mathbf{x})) \leq 10^{-3}. \tag{8}$$

Proposition 1 and 2 together show a separation of the in-distribution sample sizes for the cases with and without auxiliary outliers. Note that the separation of the sample sizes in this simple model suggests the same phenomenon can happen in more complicated and practical settings, since a lower bound in a simple model also holds in more general models. This then means the auxiliary outlier data not only can help training but, in fact, can be *necessary* for obtaining detectors with good performance given limited in-distribution data.

**Outlier mining is important.** All the data from $U_\mathbf{X}$ are implicitly related to the parameter for the ideal detector $\theta^* = \mu$ and thus are informative for learning. However, this may not be the case in practice: typically only part of the auxiliary data are informative, while the remaining are not very useful or even harmful for learning (see Figure 2). Here we study such an example, and shows that outlier mining can identify informative data and improve the performance. Here the auxiliary outliers are from the distribution $U_{\mathrm{mix}}$, a uniform mixture of $\mathcal{N}(-\mu, \sigma^2 I)$ and $\mathcal{N}(-\mu_o, \sigma^2 I)$ with $\mu_o = 10\mu$. Importantly, the distribution $U_{\mathrm{mix}}$ models the case where we have vast unlabeled data, yet with some easy outliers far from in-distribution (most points in $\mathcal{N}(-\mu_o, \sigma^2 I)$), and also with a small probability mass of samples (e.g., tail of $\mathcal{N}(-\mu, \sigma^2 I)$) in the support of in-distribution. Clearly, without outlier mining, $\hat{\theta}_{n,n'}$ has high errors.

We now consider a method which only tries to pick points with *mild* confidence scores, which thus removes too easy outliers (e.g., most points from $\mathcal{N}(-\mu_o, \sigma^2 I)$), and too difficult outliers (e.g., some points from the tail of $\mathcal{N}(-\mu, \sigma^2 I)$). Specifically, we first use in-distribution data to get an intermediate solution: $\hat{\theta}_{\mathrm{int}} = \frac{1}{n}\sum_{i=1}^n \mathbf{x}_i$. Then, we select outliers $\tilde{\mathbf{x}}$ whose confidence scores $f(\tilde{\mathbf{x}}) = 1/(1 + e^{-\tilde{\mathbf{x}}^\top \hat{\theta}_{\mathrm{int}}/d})$ fall in an interval $[a, b]$. The final solution $\hat{\theta}_{\mathrm{om}}$ is $-1$ times the average of the selected outliers. We can prove then that this method yields a good detector:

**Proposition 3.** *There exist thresholds $a$ and $b$ for $\hat{\theta}_{\mathrm{om}}$, and a universal constant $c$ such that for the parameter setting equation 6 with $\sqrt{d/n_0} \geq c(\log d + 1/\epsilon^2)$, we have that if $n \geq cn_0\log d$ and $n' \geq (d + n_0 \cdot 4\epsilon^2)\sqrt{d/n_0}$, then $\hat{\theta}_{\mathrm{om}}$ has the same error guarantees as in Proposition 2.*

Intuitively, outliers selected in this way are mostly informative and thus give an accurate final detector, which justifies outlier mining in the presence of non-informative data.

## 6 RELATED WORK

**Robustness of OOD Detection.** Worst-case aspects of OOD detection have previously been studied in (Hein et al., 2019; Sehwag et al., 2019). However, these papers are primarily concerned with $L_\infty$ norm bounded adversarial attacks, while our evaluation also includes common image corruption attacks. Besides, Meinke & Hein; Hein et al. only evaluate adversarial robustness of OOD detection on random noise images, while we also evaluate it on natural OOD images. Meinke & Hein has shown the first provable guarantees for worst-case OOD detection on some balls around uniform noise, and Bitterwolf et al. recently studied the provable guarantees for worst-case OOD detection not only for noise but also for images from related but different image classification tasks. In this paper, we propose ATOM which achieves state-of-the-art performance on a broader family of clean and perturbed OOD inputs. The key difference of our method compared to prior work is introducing the informative outlier mining technique, which could significantly improve the generalization and robustness of OOD detection.

**Discriminative Based Out-of-Distribution Detection.** Hendrycks & Gimpel introduced a baseline approach for OOD detection using the maximum softmax probability from a pre-trained network.

Several works attempt to improve the OOD uncertainty estimation by using deep ensembles (Lakshminarayanan et al., 2017), the calibrated softmax score (Liang et al., 2017), and the Mahalanobis distance-based confidence score (Lee et al., 2018). Some methods also modify the neural networks by re-training or fine-tuning on some auxiliary anomalous data that are either realistic (Hendrycks et al., 2018; Mohseni et al., 2020; Papadopoulos et al., 2019) or artificially generated by GANs (Lee et al., 2017). Many other works (Subramanya et al., 2017; Malinin & Gales, 2018; Bevandić et al., 2018) also regularize the model to have lower confidence for anomalous examples.

**Generative Modeling Based Out-of-distribution Detection.** Generative models (Dinh et al., 2016; Kingma & Welling, 2013; Rezende et al., 2014; Van den Oord et al., 2016; Tabak & Turner, 2013) can be alternative approaches for detecting OOD examples, as they directly estimate the in-distribution density and can declare a test sample to be out-of-distribution if it lies in the low-density regions. However, as shown by Nalisnick et al., deep generative models can assign a high likelihood to out-of-distribution data. Deep generative models can be more effective for out-of-distribution detection using alternative metrics (Choi & Jang, 2018), likelihood ratio (Ren et al., 2019; Serrà et al., 2019), and modified training technique (Hendrycks et al., 2018). Recently, Pope et al. shows that flow-based generative models are sensitive under adversarial attacks. Note that we mainly considered discriminative-based approaches, which can be more competitive due to the availability of label information (and, in some cases, auxiliary outlier data (Hein et al., 2019; Hendrycks et al., 2018; Meinke & Hein, 2019; Mohseni et al., 2020)).

**Adversarial Robustness.** Adversarial examples (Goodfellow et al., 2014; Papernot et al., 2016; Biggio et al., 2013; Szegedy et al., 2013) have received considerable attention in recent years. Many defense methods have been proposed to mitigate this problem. One of the most effective methods is adversarial training (Madry et al., 2017), which uses robust optimization techniques to render deep learning models resistant to adversarial attacks. Carmon et al. shows that unlabeled data can improve adversarial robustness on in-distribution via self-training. Our method is also related to self-training, but our focus is to improve the generalization and robustness of OOD detection.

**Hard Example Mining.** Hard example mining was introduced in the work (Sung, 1996) for training face detection models, where they gradually grow the set of background examples by selecting those examples for which the detector triggers a false alarm. The idea has been used extensively for object detection literature (Felzenszwalb et al., 2009; Gidaris & Komodakis, 2015; Shrivastava et al., 2016). Bucher et al. uses hard negative mining for zero-shot classification. To the best of our knowledge, we are the first to explore hard example mining for out-of-distribution detection.

# 7 CONCLUSION

In this paper, we propose Adversarial Training with informative Outlier Mining (ATOM), a method that enhances the robustness of the OOD detector. We show the merit of adaptively selecting the OOD training examples which the OOD detector is mildly uncertain about. Extensive experiments show ATOM can significantly improve the decision boundary of the OOD detector, achieving state-of-the-art performance under a broad family of *clean and perturbed* OOD evaluation tasks. We also provide theoretical analysis that justifies the benefits of outlier mining. Further, our unified evaluation framework allows future research to examine the robustness of the OOD detector. We hope our research can raise more attention to a broader view of robustness in out-of-distribution detection.

REFERENCES

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. *arXiv preprint arXiv:1802.00420*, 2018.

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 79(1-2):151–175, 2010.

Petra Bevandić, Ivan Krešo, Marin Oršić, and Siniša Šegvić. Discriminative out-of-distribution detection for semantic segmentation. *arXiv preprint arXiv:1808.07703*, 2018.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Joint European conference on machine learning and knowledge discovery in databases*, pp. 387–402. Springer, 2013.

Julian Bitterwolf, Alexander Meinke, and Matthias Hein. Provable worst case guarantees for the detection of out-of-distribution data. *arXiv preprint arXiv:2007.08473*, 2020.

Timothy A Blauwkamp, Simone Thair, Michael J Rosen, Lily Blair, Martin S Lindner, Igor D Vilfan, Trupti Kawli, Fred C Christians, Shivkumar Venkatasubrahmanyam, Gregory D Wall, et al. Analytical and clinical validation of a microbial cell-free dna sequencing test for infectious disease. *Nature microbiology*, 4(4):663–674, 2019.

Maxime Bucher, Stéphane Herbin, and Frédéric Jurie. Hard negative mining for metric learning based zero-shot classification. In *European Conference on Computer Vision*, pp. 524–531. Springer, 2016.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled data improves adversarial robustness. In *Advances in Neural Information Processing Systems*, pp. 11190–11201, 2019.

Hyunsun Choi and Eric Jang. Generative ensembles for robust anomaly detection. 2018.

Patryk Chrabaszcz, Ilya Loshchilov, and Frank Hutter. A downsampled variant of imagenet as an alternative to the cifar datasets. *arXiv preprint arXiv:1707.08819*, 2017.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(Jul):2121–2159, 2011.

Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1625–1634, 2018.

Pedro F Felzenszwalb, Ross B Girshick, David McAllester, and Deva Ramanan. Object detection with discriminatively trained part-based models. *IEEE transactions on pattern analysis and machine intelligence*, 32(9):1627–1645, 2009.

Spyros Gidaris and Nikos Komodakis. Object detection via a multi-region and semantic segmentation-aware cnn model. In *Proceedings of the IEEE international conference on computer vision*, pp. 1134–1142, 2015.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 41–50, 2019.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

Dan Hendrycks, Mantas Mazeika, and Thomas G Dietterich. Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*, 2018.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Cassidy Laidlaw and Soheil Feizi. Functional adversarial attacks. In *Advances in Neural Information Processing Systems*, pp. 10408–10418, 2019.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in neural information processing systems*, pp. 6402–6413, 2017.

Kimin Lee, Honglak Lee, Kibok Lee, and Jinwoo Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. *arXiv preprint arXiv:1711.09325*, 2017.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems*, pp. 7167–7177, 2018.

Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. *arXiv preprint arXiv:1706.02690*, 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. In *Advances in Neural Information Processing Systems*, pp. 7047–7058, 2018.

Alexander Meinke and Matthias Hein. Towards neural networks that provably know when they don't know. *arXiv preprint arXiv:1909.12180*, 2019.

Sina Mohseni, Mandar Pitale, JBS Yadawa, and Zhangyang Wang. Self-supervised learning for generalizable out-of-distribution detection. 2020.

Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? *arXiv preprint arXiv:1810.09136*, 2018.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Aristotelis-Angelos Papadopoulos, Mohammad Reza Rajati, Nazim Shaikh, and Jiamian Wang. Outlier exposure with confidence control for out-of-distribution detection. *arXiv preprint arXiv:1906.03509*, 2019.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In *2016 IEEE European symposium on security and privacy (EuroS&P)*, pp. 372–387. IEEE, 2016.

Phillip Pope, Yogesh Balaji, and Soheil Feizi. Adversarial robustness of flow-based generative models. *arXiv preprint arXiv:1911.08654*, 2019.

Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pp. 14680–14691, 2019.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data. In *Advances in Neural Information Processing Systems*, pp. 5014–5026, 2018.

Vikash Sehwag, Arjun Nitin Bhagoji, Liwei Song, Chawin Sitawarin, Daniel Cullina, Mung Chiang, and Prateek Mittal. Analyzing the robustness of open-world machine learning. In *Proceedings of the 12th ACM Workshop on Artificial Intelligence and Security*, pp. 105–116, 2019.

Joan Serrà, David Álvarez, Vicenç Gómez, Olga Slizovskaia, José F Núñez, and Jordi Luque. Input complexity and out-of-distribution detection with likelihood-based generative models. *arXiv preprint arXiv:1909.11480*, 2019.

Abhinav Shrivastava, Abhinav Gupta, and Ross Girshick. Training region-based object detectors with online hard example mining. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 761–769, 2016.

Akshayvarun Subramanya, Suraj Srinivas, and R Venkatesh Babu. Confidence estimation in deep neural networks via density modelling. *arXiv preprint arXiv:1707.07013*, 2017.

Kah-Kay Sung. Learning and example selection for object and pattern detection. 1996.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Esteban G Tabak and Cristina V Turner. A family of nonparametric density estimation algorithms. *Communications on Pure and Applied Mathematics*, 66(2):145–164, 2013.

Antonio Torralba, Rob Fergus, and William T Freeman. 80 million tiny images: A large data set for nonparametric object and scene recognition. *IEEE transactions on pattern analysis and machine intelligence*, 30(11):1958–1970, 2008.

Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. In *Advances in neural information processing systems*, pp. 4790–4798, 2016.

Pingmei Xu, Krista A Ehinger, Yinda Zhang, Adam Finkelstein, Sanjeev R Kulkarni, and Jianxiong Xiao. Turkergaze: Crowdsourcing saliency with webcam based eye tracking. *arXiv preprint arXiv:1504.06755*, 2015.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE transactions on pattern analysis and machine intelligence*, 40(6):1452–1464, 2017.

# Supplementary Material

## Robust Out-of-distribution Detection via Informative Outlier Mining

## A  THEORETICAL ANALYSIS

This section provides some theoretical analysis of our method. First, Section A.1 provides a generic error bound in, giving some insight on why auxiliary outlier data in training time can help detection of outliers from a different distribution in test time. Then, to perform finer-grain analysis and obtain better insights, Section A.2 studies a concrete distributional model of the data. It rigorously justifies the benefit of auxiliary data and the benefit of our outlier mining technique in this data model. In particular, it proves that without auxiliary outlier data *any* algorithm will need a lot of data from the in-distribution to achieve reasonable error, while with auxiliary outlier data a simple algorithm can already achieve a small error with far less in-distribution data. Furthermore, it proves a natural method without outlier mining fails while the outlier mining method succeeds.

### A.1  A GENERAL ERROR BOUND

The interesting questions related to our method are: **(1)** why auxiliary data from $U_{\mathbf{X}}$ helps? **(2)** why the detector $G$ trained on $U_{\mathbf{X}}$ generalizes to different OOD distributions $Q_{\mathbf{X}}$ in test time?

To see what $Q_{\mathbf{X}}$ can benefit from the auxiliary data, we adopt the domain adaption framework (Ben-David et al., 2010). Recall that in domain adaptation there are two domains $s, t$, each being a distribution over the input space $\mathcal{X}$ and label space $\{-1, 1\}$. A classifier is trained on $s$ then applied on $t$. At a high level, we view our OOD detection problem as classification, where the source domain $s$ is $P_{\mathbf{X}}$ with labels 1 and $U_{\mathbf{X}}$ with labels $-1$, and the target domain $t$ is $P_{\mathbf{X}}$ with labels 1 and $Q_{\mathbf{X}}$ with label $-1$.

We focus on the FPR metric below; the argument for FNR is similar. Suppose we learn the OOD detector from a hypothesis class $\mathcal{G}$. Following Ben-David et al. (2010), we define (a variant) of the divergence of $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ w.r.t. the hypothesis class $\mathcal{G}$ as

$$d_{\mathcal{G}}(Q_{\mathbf{X}}, U_{\mathbf{X}}) = \sup_{G, G' \in \mathcal{G}} v(G, G'; Q_{\mathbf{X}}) - v(G, G'; U_{\mathbf{X}})$$

where

$$v(G, G'; D) = \mathrm{FPR}(G; D, \Omega) - \mathrm{FPR}(G'; D, \Omega)$$

is the error difference of $G$ and $G'$ on the distribution $D$.

The divergence upper bounds the change of the hypothesis error difference between $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$. If it is small, then for any $G, G' \in \mathcal{G}$ where $G$ has a smaller error than $G'$ in $U_{\mathbf{X}}$, we know that $G$ will also have a smaller (or not too larger) error than $G'$ in $Q_{\mathbf{X}}$. That is, if the divergence is small, then the ranking of the hypotheses w.r.t. the error is roughly the same in both distributions. This *rank-preserving* property thus makes sure that a good hypothesis learned in $U_{\mathbf{X}}$ will also be good for $Q_{\mathbf{X}}$.

Now we show that, if $d_{\mathcal{G}}(Q_{\mathbf{X}}, U_{\mathbf{X}})$ is small (i.e., $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ are aligned w.r.t. the class $\mathcal{G}$), then a detector $G$ with small FPR on $U_{\mathbf{X}}$ will also have small FPR on $Q_{\mathbf{X}}$.

**Proposition 4.** *For any $G \in \mathcal{G}$,*

$$\mathrm{FPR}(G; Q_{\mathbf{X}}, \Omega) \leq \inf_{G^* \in \mathcal{G}} \mathrm{FPR}(G^*; Q_{\mathbf{X}}, \Omega) + \mathrm{FPR}(G; U_{\mathbf{X}}, \Omega) + d_{\mathcal{G}}(Q_{\mathbf{X}}, U_{\mathbf{X}}).$$

*Proof.* For simplicity, we omit $\Omega$ from $\mathrm{FPR}(G; Q_{\mathbf{X}}, \Omega)$. For any $G^* \in \mathcal{G}$, we have

$$\mathrm{FPR}(G; Q_{\mathbf{X}}) = \mathrm{FPR}(G^*; Q_{\mathbf{X}}) + \mathrm{FPR}(G; Q_{\mathbf{X}}) - \mathrm{FPR}(G^*; Q_{\mathbf{X}}) \tag{9}$$

$$= \mathrm{FPR}(G^*; Q_{\mathbf{X}}) + \mathrm{FPR}(G; U_{\mathbf{X}}) - \mathrm{FPR}(G^*; U_{\mathbf{X}}) \tag{10}$$

$$+ [(\mathrm{FPR}(G; Q_{\mathbf{X}}) - \mathrm{FPR}(G^*; Q_{\mathbf{X}})) - (\mathrm{FPR}(G; U_{\mathbf{X}}) - \mathrm{FPR}(G^*; U_{\mathbf{X}}))]. \tag{11}$$

Figure 3: An illustration example to explain why $U_{\mathbf{X}}$ helps to get a good detector $G_r$. With $U_{\mathbf{X}}$, we can prune away hypotheses $G_r$ for any $r \geq 1.9$. Thus, the resulting detector $G_r$ can detect OOD samples from $Q_{\mathbf{X}}$ successfully and robustly.

The last term is

$$(\mathrm{FPR}(G; Q_{\mathbf{X}}) - \mathrm{FPR}(G^*; Q_{\mathbf{X}})) - (\mathrm{FPR}(G; U_{\mathbf{X}}) - \mathrm{FPR}(G^*; U_{\mathbf{X}})) \qquad (12)$$
$$= v(G, G^*; Q_{\mathbf{X}}) - v(G, G^*; U_{\mathbf{X}}) \qquad (13)$$
$$\leq d_{\mathcal{G}}(Q_{\mathbf{X}}, U_{\mathbf{X}}). \qquad (14)$$

Therefore,

$$\mathrm{FPR}(G; Q_{\mathbf{X}}) \leq \mathrm{FPR}(G^*; Q_{\mathbf{X}}) + \mathrm{FPR}(G; U_{\mathbf{X}}) + d_{\mathcal{G}}(Q_{\mathbf{X}}, U_{\mathbf{X}}). \qquad (15)$$

Taking $\inf$ over $G^* \in \mathcal{G}$ completes the proof. $\qquad \square$

The error of the detector is bounded by three terms: the best error, the error on the training distributions, and the divergence between $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$. Assuming that there exists a ground-truth detector with a small test error, and that the optimization can lead to a small training error, the test error is then characterized by the divergence. So in this case, as long as the rankings of the hypotheses (according to the error) on $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ are similar, detectors learned on $U_{\mathbf{X}}$ can generalize to $Q_{\mathbf{X}}$.

**An illustration example.** In this example, the in-distribution $P_{\mathbf{X}}$ is uniform over the disk around the origin in $\mathbb{R}^2$ with radius 1, $U_{\mathbf{X}}$ is uniform over the disk around $(0, 3)$ with radius 1, and $Q_{\mathbf{X}}$ is uniform over the disk around $(3, 0)$ with radius 1. Assume the adversary budget is $\epsilon = 0.1$, i.e., $\Omega_{\infty, \epsilon} = \{\|\delta\|_\infty \leq 0.1\}$. The hypothesis class for the detector contains all functions of the form $G_r(x) = 2\mathbb{I}[\|x\|_2 \leq r] - 1$ with parameter $r$. See Figure 3.

The example first shows the effect of the auxiliary outlier data: $U_{\mathbf{X}}$ helps prune away hypotheses $G_r$ for any $r \geq 1.9$. Furthermore, it also shows how learning over $U_{\mathbf{X}}$ can generalize to $Q_{\mathbf{X}}$. Although $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ have non-overlapping supports, $U_{\mathbf{X}}$ helps to calibrate the error of the hypotheses, so any good detector trained on $P_{\mathbf{X}}$ and $U_{\mathbf{X}}$ can be used for distinguishing $P_{\mathbf{X}}$ and $Q_{\mathbf{X}}$. Formally, the $d_{\mathcal{G}}$ is small in Proposition 4.

The analysis also shows the importance of training on *perturbed* instances from the unlabeled data $U_{\mathbf{X}}$. Not using perturbation is equivalent to using $\Omega = \{\mathbf{0}\}$. In this case, the analysis shows that it only guarantees the error on *unperturbed* instances from $Q_{\mathbf{X}}$, even if $Q_{\mathbf{X}}$ and $U_{\mathbf{X}}$ has small divergence and the learned detector can have small training error on $U_{\mathbf{X}}$.

## A.2   ANALYSIS IN A GAUSSIAN MODEL

To understand how the outlier training data affect the generalization, we study a concrete distributional model, which is inspired by the models in (Schmidt et al., 2018; Carmon et al., 2019). In this model, we establish in Section A.2.2 a separation of the in-distribution sample sizes needed in the two cases:

with and without auxiliary outlier data for training. We also demonstrate in Section A.2.3 the benefit of outlier mining when the auxiliary data consists of uninformative outliers.

While the theoretical model is simple (in fact, much simpler than the practical data distributions), its simplicity is actually desired for our analytical purpose. More precisely, the separation of the sample sizes under this simple model suggests the same phenomenon can happen in more complicated models. This then means the auxiliary outlier data not only help training but are *necessary* for obtaining detectors with reasonable performance when in-distribution data is limited.

**Gaussian Model.** To specify a distributional model for our robust OOD formulation, we need in-distribution $P_{\mathbf{X}}$, family of OOD distributions $\mathcal{Q}$, and the hypothesis class $\mathcal{H}$ for the OOD detector $G$. When auxiliary data is available, we also need to specify their distribution $U_{\mathbf{X}}$. Let $\mu \in \mathbb{R}^d$ be the mean vector, $\sigma > 0$ be the variance parameter, and $\nu > 0$ be a parameter. In our $(\mu, \sigma, \nu)$-Gaussian model:

- $P_{\mathbf{X}}$ is $\mathcal{N}(\mu, \sigma^2 I)$.
- $\mathcal{Q} = \{\mathcal{N}(-\mu + v, \sigma^2 I) : v \in \mathbb{R}^d, \|v\|_2 \le \nu\}$.
- $\mathcal{H} = \{G_\theta(x) = \text{sign}(\theta^\top \mathbf{x}) : \theta \in \mathbb{R}^d\}$. Here $G_\theta(\mathbf{x}) = 1$ means it predicts $x$ to be an in-distribution example, and $G_\theta(\mathbf{x}) = -1$ means it predicts an OOD example.

We are interested in the False Negative Rate $\text{FNR}(G)$ and worst False Positive Rate $\sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \text{FPR}(G; Q_{\mathbf{X}}, \Omega_{\infty,\epsilon}(\mathbf{x}))$ over $Q_{\mathbf{X}} \in \mathcal{Q}$ under $\ell_\infty$ perturbations of magnitude $\epsilon$. For simplicity, we denote them as $\text{FNR}(G)$ and $\text{FPR}(G; Q_{\mathbf{X}})$ in our proofs.

**Parameter Setting.** The model parameters are set such that:

1. There exists a classifier that achieves very low errors FPR and FNR.

2. We need $n_1$ in-distribution data from $P_{\mathbf{X}}$ to learn a classifier with non-trivial robust errors.

3. Using $n_0$ in-distribution examples from $P_{\mathbf{X}}$ and $n_{\text{out}}$ auxiliary outliers from $U_{\mathbf{X}}$ where $n_0$ is much smaller than $n_1$, we can learn a classifier with non-trivial robust errors.

Here $n_0, n_1, n_{\text{out}}$ are sample sizes whose values are specified later in our analysis.

To achieve the three goals, the following parameter values are used (repeating equation 6):

$$\epsilon \in (0, 1/2), \quad \|\mu\|_2^2 = d \gg n_0/\epsilon^4, \quad \sigma^2 = \sqrt{dn_0}, \quad \nu \le \|\mu\|_2/4. \tag{16}$$

To interpret the parameter setting, one can view $\epsilon$ as fixed and $d/n_0$ as a large number. In the following subsections, we show how these three goals are achieved.

### A.2.1 EXISTENCE OF ROBUST CLASSIFIERS

We give closed forms of the errors, and show that using $\theta = \mu$ gives small errors under the chosen parameter setting in equation 6.

**Closed Forms of the Errors.** By definition, the FNR of a detector $G_\theta$ (on $P_{\mathbf{X}}$) is:

$$\text{FNR}(G_\theta) = \mathbb{P}_{\mathbf{x} \sim P_{\mathbf{X}}}[\theta^\top \mathbf{x} \le 0] = \mathbb{P}_{\mathbf{x} \sim P_{\mathbf{X}}}\left[\mathcal{N}\left(\frac{\mu^\top \theta}{\sigma\|\theta\|_2}, 1\right) \le 0\right] =: \Phi\left(\frac{\mu^\top \theta}{\sigma\|\theta\|_2}\right) \tag{17}$$

where

$$\Phi(\mathbf{x}) := \frac{1}{\sqrt{2\pi}} \int_{\mathbf{x}}^{\infty} e^{-t^2/2} dt \tag{18}$$

is the Gaussian error function.

Given a test OOD distribution $Q_v = \mathcal{N}(-\mu + v, \sigma^2 I)$, the robust FPR of $G_\theta$ on $Q_v$ is:

$$\text{FPR}(G_\theta; Q_v) = \mathbb{P}_{\mathbf{x} \sim Q_v} \left[ \inf_{\|\delta\|_\infty \leq \epsilon} \theta^\top (\mathbf{x} + \delta) \geq 0 \right] \tag{19}$$

$$= \mathbb{P}_{\mathbf{x} \sim Q_v} \left[ \theta^\top \mathbf{x} + \epsilon \|\theta\|_1 \geq 0 \right] \tag{20}$$

$$= \mathbb{P}_{\mathbf{x} \sim Q_v} \left[ \mathcal{N}((\mu + v)^\top \theta, (\sigma \|\theta\|_2)^2) \geq -\epsilon \|\theta\|_1 \right] \tag{21}$$

$$= \Phi \left( \frac{(\mu + v)^\top \theta}{\sigma \|\theta\|_2} - \frac{\epsilon \|\theta\|_1}{\sigma \|\theta\|_2} \right). \tag{22}$$

Then the worst robust FPR of $G_\theta$ on $\mathcal{Q}$ is:

$$\sup_{Q_v \in \mathcal{Q}} \text{FPR}(G_\theta; Q_v) = \sup_{\|v\|_2 \leq \nu} \Phi \left( \frac{(\mu + v)^\top \theta}{\sigma \|\theta\|_2} - \frac{\epsilon \|\theta\|_1}{\sigma \|\theta\|_2} \right) \tag{23}$$

$$= \Phi \left( \frac{\mu^\top \theta}{\sigma \|\theta\|_2} - \frac{\nu}{\sigma} - \frac{\epsilon \|\theta\|_1}{\sigma \|\theta\|_2} \right) \tag{24}$$

$$\leq \Phi \left( \frac{\mu^\top \theta}{\sigma \|\theta\|_2} - \frac{\nu}{\sigma} - \frac{\epsilon \sqrt{d}}{\sigma} \right). \tag{25}$$

**Small Errors of $G_\mu$.** Given the closed forms, we can now show that $G_\mu$ achieves small FNR and FPR in our parameter setting.

$$\text{FNR}(G_\mu) = \Phi \left( \frac{\|\mu\|_2}{\sigma} \right) = \Phi \left( \left( \frac{d}{n_0} \right)^{1/4} \right) \leq e^{-\frac{1}{2} \sqrt{d/n_0}}. \tag{26}$$

$$\sup_{Q_v \in \mathcal{Q}} \text{FPR}(G_\mu; Q_v) \leq \Phi \left( \frac{\|\mu\|_2}{\sigma} - \frac{\nu}{\sigma} - \frac{\epsilon \sqrt{d}}{\sigma} \right) \tag{27}$$

$$\leq \Phi \left( \left( 1 - \frac{1}{4} - \epsilon \right) \left( \frac{d}{n_0} \right)^{1/4} \right) \leq e^{-\frac{1}{32} \sqrt{d/n_0}}. \tag{28}$$

Therefore, in the regime $d/n_0 \gg 1$, the detector $G_\mu$ achieves both small FNR on $P_{\mathbf{X}}$ and robust FPR on any test OOD distribution in $\mathcal{Q}$.

### A.2.2 BENEFIT OF AUXILIARY OUTLIER DATA

We will first consider the case when auxiliary outlier data are not available, and give an upper bound (Proposition 5) and a lower bound (Proposition 1). We will then consider the case when auxiliary outlier data are used, and give an upper bound (Proposition 2). Comparing Proposition 1 and Proposition 2 will then justify the benefit of the auxiliary outlier data.

**Learning Without Auxiliary Outlier Data.** Given in-distribution data $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n$, we consider the detector $G_{\hat{\theta}_n}$ given by

$$\hat{\theta}_n = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i. \tag{29}$$

As shown in the closed form solutions, the key factor determining the errors is $\frac{\mu^\top \hat{\theta}_n}{\sigma \|\hat{\theta}_n\|_2}$. To bound this term, we cite the following lemma from existing work:

**Lemma 1** (Lemma 1 in (Carmon et al., 2019) ). *There exist numerical constants $c_0, c_1, c_2$ such that under parameter setting equation 6 and $d/n_0 > c_0$,*

$$\frac{\mu^\top \hat{\theta}_n}{\sigma \|\hat{\theta}_n\|_2} \geq \left( \sqrt{\frac{n_0}{d}} + \frac{n_0}{n} \left( 1 + c_1 \left( \frac{n_0}{d} \right)^{1/8} \right) \right)^{-1/2} \tag{30}$$

*with probability $\geq 1 - e^{-c_2 (d/n_0)^{1/4} \min\{n, (d/n_0)^{1/4}\}}$.*

This lemma leads to the following guarantee about learning the OOD detector from in-distribution data only. The error bound $10^{-3}$ is chosen for simplicity of the statement, but it can be made to arbitrarily small values.

**Proposition 5.** *There exists a universal constant $c$ such that for the parameter setting equation 6 with $\sqrt{d/n_0} \geq c/\epsilon^2$, we have that if $n \geq n_0 \cdot 4\epsilon^2 \sqrt{d/n_0}$, then*

$$\mathbb{E}_{\hat{\theta}_n} \mathrm{FNR}(G_{\hat{\theta}_n}) \leq 10^{-3}, \quad \mathbb{E}_{\hat{\theta}_n} \sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \mathrm{FPR}(G_{\hat{\theta}_n}; Q_{\mathbf{X}}, \Omega_{\infty,\epsilon}(\mathbf{x})) \leq 10^{-3}. \tag{31}$$

*Proof.* By Lemma 1, we have

$$\frac{\mu^\top \hat{\theta}_n}{\sigma \|\hat{\theta}_n\|_2} \geq \left( 2\left( \sqrt{\frac{n_0}{n}} + \sqrt{\frac{n_0}{d}} \right) \right)^{-1/2} \tag{32}$$

with probability $\geq 1 - e^{-c_2(d/n_0)^{1/4} \min\{n, (d/n_0)^{1/4}\}}$. The proposition then comes from the parameter setting equation 6 and the closed form expressions equation 17 and equation 23 of the errors. $\square$

Next we show that the above sample size is nearly optimal (up to a logarithmic factor). That is, a sample size of order $n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{\log d}$ is necessary for *all algorithms* to obtain both non-trivial robust FPR and FNR. We emphasize that this lower bound is information theoretic, i.e., it holds without restriction on the computational power of the learning algorithm and the hypothesis class used for the OOD detector. In particular, it applies not only to the linear classifier considered in Proposition 5 but also to any other learning algorithms.

**Proposition 1.** *Let $\mathbb{A}_n$ be any learning algorithm mapping a dataset $S$ consisting of $n$ i.i.d. samples from $P_{\mathbf{X}}$ to a detector $\mathbb{A}_n(S)$. Let $\mu$ be drawn from $\mathcal{N}(0, I)$. If $n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{16 \log d}$, then*

$$\mathbb{E}\left\{ \mathrm{FNR}(\mathbb{A}_n(S)) + \sup_{Q_{\mathbf{X}} \in \mathcal{Q}} \mathrm{FPR}(\mathbb{A}_n(S); Q_{\mathbf{X}}, \Omega_{\infty,\epsilon}(\mathbf{x})) \right\} \geq \frac{1}{2}(1 - d^{-1}) \tag{7}$$

*where the expectation is with respect to the randomness in $S$ and $\mathbb{A}_n$.*

*Proof.* The key for the proof is the observation that robust classification is a special case of our robust OOD problem. More precisely, consider the following robust classification problem. The data $(\mathbf{x}, y)$ with $\mathbf{x} \in \mathbb{R}^d$ and $y \in \{-1, +1\}$ is generated as follows: first draw $y$ uniformly at random, and then draw $\mathbf{x}$ from $\mathcal{N}(y \cdot \mu, \sigma^2 I)$. Given training data $\{(\mathbf{x}_i, y_i)\}_{i=1}^n$, the goal is to find classifier $f_\theta(\mathbf{x}) = \mathrm{sign}(\theta^\top \mathbf{x})$ with small robust classification error

$$\mathrm{err}_{\infty,\epsilon}(f_\theta) = \mathbb{E}_{(\mathbf{x}, y)} \max_{\|\delta\|_\infty \leq \epsilon} \mathbb{I}[f_\theta(\mathbf{x} + \delta) \neq y]$$

under $\ell_\infty$ perturbation of magnitude $\epsilon$. It has been shown that (Theorem 6 in (Schmidt et al., 2018) or Theorem 1 in (Carmon et al., 2019)) that when $\mu \sim \mathcal{N}(0, I)$ and $n \leq n_0 \cdot \frac{\epsilon^2 \sqrt{d/n_0}}{8 \log d}$ and with the parameter setting equation 6, for any learning algorithm $\mathbb{A}_n$

$$\mathbb{E}\mathrm{err}_{\infty,\epsilon}(\mathbb{A}_n(S)) \geq \frac{1}{2}(1 - d^{-1}). \tag{33}$$

Now consider the following variant of the robust OOD problem in the proposition. Suppose besides the data from $P_{\mathbf{X}}$, we also have $n$ i.i.d. samples from a test OOD distribution $Q_0 = \mathcal{N}(-\mu, \sigma^2 I)$. Then the above robust classification problem can be reduced to this variant of robust OOD, by viewing the in-distribution data as with label $+1$ and viewing outliers as with label $-1$. Furthermore, it is clear that the sum of the FNR and FPR is larger than the robust classification error. Then

$$\mathbb{E}\left\{ \mathrm{FNR}(\mathbb{A}_n(S)) + \mathrm{FPR}(\mathbb{A}_n(S); Q_0) \right\} \geq \frac{1}{2}(1 - d^{-1}). \tag{34}$$

Since this variant can be reduced to the original robust OOD problem in the proposition and furthermore $Q_0 \in \mathcal{Q}$, the statement then follows. $\square$

**Learning With Auxiliary Outlier Data.** Assuming we have access to auxiliary outliers from a distribution $U_{\mathbf{X}}$ where:

- $U_{\mathbf{X}}$ is defined by the following distribution: first draw $v$ uniformly at random from the ball $\{v : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$, then draw $\tilde{\mathbf{x}}$ from $\mathcal{N}(-\mu + v, \sigma^2 I)$.

Roughly speaking, $U_{\mathbf{X}}$ is a uniform mixture of distributions in $\mathcal{Q}$.

Given in-distribution data $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n$ from $P_{\mathbf{X}}$ and auxiliary outliers $\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \ldots, \tilde{\mathbf{x}}_{n'}$ from $U_{\mathbf{X}}$, we consider the detector $G_{\hat{\theta}_{n,n'}}$ given by

$$\hat{\theta}_{n,n'} = \frac{1}{n} \sum_{i=1}^{n} \mathbf{x}_i - \frac{1}{n'} \sum_{i=1}^{n'} \tilde{\mathbf{x}}_i. \tag{35}$$

We will show that with $n = n_0$ and sufficiently large $n'$, the detector has small errors.

Again, as shown in the closed form solutions, the key factor determining the errors is $\frac{\mu^\top \hat{\theta}_{n,n'}}{\sigma \|\hat{\theta}_{n,n'}\|_2}$. The following lemma bounds this term.

**Lemma 2.** *There exist numerical constants $c_0, c_1, c_2$ such that under parameter setting equation 6 and $d/n_0 > c_0$,*

$$\frac{\mu^\top \hat{\theta}_{n,n'}}{\sigma \|\hat{\theta}_{n,n'}\|_2} \geq \left( \sqrt{\frac{n_0}{d}} + \frac{n_0}{n+n'} \left( 1 + c_1 \left( \frac{n_0}{d} \right)^{1/8} \right) \right)^{-1/2} \tag{36}$$

*with probability $\geq 1 - e^{-c_2 (d/n_0)^{1/4} \min\{n+n', (d/n_0)^{1/4}\}} - e^{-c_2 n'}$.*

*Proof.* The proof follows the argument of Lemma 1 in (Carmon et al., 2019) but needs some modifications accommodating the difference in learning $\theta$. Recall the generation of $\mathbf{x}'_i$: first draw $v_i$ uniformly at random from the ball $\mathbb{B}(\nu) := \{v : v \in \mathbb{R}^d, \|v\|_2 \leq \nu\}$, then draw $\bar{\mathbf{x}}'_i$ from $\mathcal{N}(\mu, \sigma^2 I)$, and finally let $\mathbf{x}'_i = v_i - \bar{\mathbf{x}}'_i$. So we have

$$\hat{\theta}_{n,n'} = \frac{1}{n+n'} \left( \sum_{i=1}^{n} \mathbf{x}_i + \sum_{i=1}^{n'} \bar{\mathbf{x}}'_i \right) - \frac{1}{n+n'} \left( \sum_{i=1}^{n'} v_i \right) \tag{37}$$

$$= \mu + \delta + \delta_v \tag{38}$$

where

$$\delta = \frac{1}{n+n'} \left( \sum_{i=1}^{n} \mathbf{x}_i + \sum_{i=1}^{n'} \bar{\mathbf{x}}'_i \right) - \mu \sim \mathcal{N}\left(0, \frac{\sigma^2}{n+n'} I\right), \tag{39}$$

$$\delta_v = -\frac{1}{n+n'} \left( \sum_{i=1}^{n'} v_i \right). \tag{40}$$

To lower bound the term $\frac{\mu^\top \hat{\theta}_{n,n'}}{\|\hat{\theta}_{n,n'}\|_2}$, we upper bound its squared inverse:

$$\frac{\|\hat{\theta}_{n,n'}\|_2^2}{(\mu^\top \hat{\theta}_{n,n'})^2} = \frac{\|\mu + \delta + \delta_v\|_2^2}{(\|\mu\|_2^2 + \mu^\top \delta + \mu^\top \delta_v)^2} \tag{41}$$

$$= \frac{1}{\|\mu\|_2^2} + \frac{\|\delta + \delta_v\|_2^2 - \frac{1}{\|\mu\|_2^2}(\mu^\top \delta + \mu^\top \delta_v)^2}{(\|\mu\|_2^2 + \mu^\top \delta + \mu^\top \delta_v)^2} \tag{42}$$

$$\leq \frac{1}{\|\mu\|_2^2} + \frac{2\|\delta\|_2^2 + 2\|\delta_v\|_2^2}{(\|\mu\|_2^2 + \mu^\top \delta + \mu^\top \delta_v)^2}. \tag{43}$$

For $\delta$, we have

$$\|\delta\|_2^2 \sim \frac{\sigma^2}{n+n'} \chi_d^2 \quad \text{and} \quad \frac{\mu^\top \delta}{\|\mu\|_2} \sim \mathcal{N}\left(0, \frac{\sigma^2}{n+n'}\right). \tag{44}$$

So standard concentration bounds give

$$\mathbb{P}\left(\|\delta\|_2^2 \geq \frac{\sigma^2}{n+n'}\left(d+\frac{1}{\sigma}\right)\right) \leq e^{-d/8\sigma^2} \text{ and } \mathbb{P}\left(\frac{\mu^\top\delta}{\|\mu\|_2} \geq (\sigma\|\mu\|)^{1/2}\right) \leq 2e^{-(n+n')\|\mu\|_2/2\sigma}.$$

$$(45)$$

For $\delta_v$, by subguassian concentration bounds, we have

$$\mathbb{P}\left(\|\delta_v\|_2 \geq \frac{C\nu}{\sqrt{n'}}\right) \leq e^{-cn'} \tag{46}$$

for some numeric constants $c$ and $C$. Suppose the event $\|\delta_v\|_2 < \frac{C\nu}{\sqrt{n'}}$ is true. Then

$$|\mu^\top\delta_v| \leq \|\mu\|_2\|\delta_v\|_2 \leq \frac{C\nu\|\mu\|_2}{\sqrt{n'}}. \tag{47}$$

Plugging the concentration bounds in equation 41 and doing the same manipulation leads to the bound. To finish the proof, we also need to show $\mu^\top\hat{\theta}_{n,n'} > 0$, which can be shown by the same argument as in (Carmon et al., 2019). □

We then get the following guarantee. Again, the error bound $10^{-3}$ is chosen for simplicity of the statement, but it can be made to arbitrarily small values.

**Proposition 2.** *There exists a universal constant $c$ such that for the parameter setting equation 6 with $\sqrt{d/n_0} \geq c/\epsilon^2$, we have that if $n \geq n_0$ and $n' \geq n_0 \cdot 4\epsilon^2\sqrt{d/n_0}$, then*

$$\mathbb{E}_{\hat{\theta}_{n,n'}}\mathrm{FNR}(G_{\hat{\theta}_{n,n'}}) \leq 10^{-3}, \quad \mathbb{E}_{\hat{\theta}_{n,n'}} \sup_{Q_\mathbf{X} \in \mathcal{Q}} \mathrm{FPR}(G_{\hat{\theta}_{n,n'}}; Q_\mathbf{X}, \Omega_{\infty,\epsilon}(\mathbf{x})) \leq 10^{-3}. \tag{8}$$

*Proof.* The proposition comes from Lemma 2, the parameter setting equation 6, and the closed form expressions equation 17 and equation 23 of the errors. □

### A.2.3 BENEFIT OF OUTLIER MINING

The above Gaussian example shows the benefit of having auxiliary outlier data for training. All the auxiliary data given in the example are implicitly related to the ideal parameter for the detector $\theta^* = \mu$ and thus are informative for learning the detector. However, this may not be the case in practice: typically only part of the auxiliary outlier data are informative, while the remaining are not very useful or even can be harmful for the learning. In this section, we study such an example, and shows that how outlier mining can help to identify informative data and improve the learning performance.

Suppose the algorithm gets $n$ in-distribution data $\{\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_n\}$ i.i.d. from $P_\mathbf{X}$ and $n'$ auxiliary outliers $\{\tilde{\mathbf{x}}_1, \tilde{\mathbf{x}}_2, \ldots, \tilde{\mathbf{x}}_{n'}\}$ for training. Instead of from $U_\mathbf{X}$ specified above, the auxiliary outliers are i.i.d. from the distribution $U_{\mathrm{mix}}$.

- $U_{\mathrm{mix}}$ is a uniform mixture of $\mathcal{N}(-\mu, \sigma^2 I)$ and $\mathcal{N}(-\mu_o, \sigma^2 I)$ for $\mu_o = 10\mu$.

That is, the distribution is defined by the following process: with probability $1/2$ sample the outlier from the informative part $\mathcal{N}(-\mu, \sigma^2 I)$, and with probability $1/2$ sample the outlier from the uninformative part $\mathcal{N}(-\mu_o, \sigma^2 I)$. We also note that $\mu_0 = 10\mu$ is chosen for simplicity of analysis. $\mu_0$ can also be $c\mu$ for some sufficiently large $c > 1$, or even $\mu_o = c\mu + c'\mu_\perp$ for a sufficiently large $c > 1$, a small $c'$ and a unit vector $\mu_\perp$ perpendicular to $\mu$.

**Naïve Method Without Outlier Mining.** It is clear that naïvely applying the method in the previous section can lead to high errors: with $n$ in-distribution examples from $P_\mathbf{X}$ and $n' = n$ auxiliary outliers from $U_{\mathrm{mix}}$, when $n \to \infty$, we have $\hat{\theta}_{n,n'} \to -7\mu/4$ which has the worst errors among all detectors.

**With Outlier Mining.** Here we analyze the following algorithm using the outlier mining approach. The algorithm is simpler than what we used in Section 3 but shares the same intuition.

First, we use the $n$ in-distribution data points to get an intermediate solution:

$$\hat{\theta}_{\text{int}} = \frac{1}{n} \sum_{i=1}^{n} \mathbf{x}_i. \tag{48}$$

We define the confidence score of a point $\tilde{\mathbf{x}}$ being in-distribution as:

$$f(\tilde{\mathbf{x}}) = \sigma(t) = \frac{1}{1 + e^{-t}}, \quad \text{where} \quad t(\tilde{\mathbf{x}}) = \frac{\tilde{\mathbf{x}}^\top \hat{\theta}_{\text{int}}}{d}. \tag{49}$$

Here $\sigma(t) = \frac{1}{1+e^{-t}}$ is the sigmoid function. We then select outlier training data whose confidence fall into an interval $[a, b]$ and use them to learn the final solution:

$$\hat{\theta}_{\text{om}} = \frac{\sum_{i=1}^{n'} (-\tilde{\mathbf{x}}_i) \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}}{\sum_{i=1}^{n'} \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}} \tag{50}$$

where $\mathbb{I}\{\cdot\}$ is the indicator function.

**Proposition 3.** *There exist thresholds $a$ and $b$ for $\hat{\theta}_{\text{om}}$, and a universal constant $c$ such that for the parameter setting equation 6 with $\sqrt{d/n_0} \geq c(\log d + 1/\epsilon^2)$, we have that if $n \geq cn_0 \log d$ and $n' \geq (d + n_0 \cdot 4\epsilon^2)\sqrt{d/n_0}$, then $\hat{\theta}_{\text{om}}$ has the same error guarantees as in Proposition 2.*

*Proof.* Let $a = \sigma(-3/2), b = \sigma(-1/2)$. By definition we have

$$\delta_{\text{om}} := \hat{\theta}_{\text{om}} - \mu = \frac{\sum_{i=1}^{n'} (-\mu - \tilde{\mathbf{x}}_i) \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}}{\sum_{i=1}^{n'} \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}}. \tag{51}$$

By the closed form expressions equation 17 and equation 23 of the errors, it is sufficient to lower bound the key term $\frac{\mu^\top \hat{\theta}_{\text{om}}}{\|\hat{\theta}_{\text{om}}\|_2}$, which comes down to show that $\delta_{\text{om}}$ is small.

First, let's consider $\hat{\theta}_{\text{int}}$. Let $\delta_{\text{int}} := \hat{\theta}_{\text{int}} - \mu$. Then

$$\|\delta_{\text{int}}\|_2^2 \sim \frac{\sigma^2}{n} \chi_d^2 \quad \text{and} \quad \frac{\mu^\top \delta_{\text{int}}}{\|\mu\|_2} \sim \mathcal{N}\left(0, \frac{\sigma^2}{n}\right). \tag{52}$$

So standard concentration bounds give

$$\mathbb{P}\left(\|\delta_{\text{int}}\|_2^2 \geq \frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)\right) \leq e^{-d/8\sigma^2} \quad \text{and} \quad \mathbb{P}\left(\frac{|\mu^\top \delta_{\text{int}}|}{\|\mu\|_2} \geq \sqrt{\frac{d}{n}}\right) \leq 2e^{-d/2\sigma^2}. \tag{53}$$

So with probability $\geq 1 - 3e^{-d/8\sigma^2}$ over the randomness of the $n$ in-distribution points, we have the good event $\mathcal{G}_{\text{int}}$: $\|\delta_{\text{int}}\|_2^2 \leq \frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)$ and $\frac{|\mu^\top \delta_{\text{int}}|}{\|\mu\|_2} \leq \sqrt{\frac{d}{n}}$.

Now, condition on a fix $\hat{\theta}_{\text{int}}$ satisfying $\mathcal{G}_{\text{int}}$, and consider $\hat{\theta}_{\text{om}}$. Define

$$z_i := -\mu - \tilde{\mathbf{x}}_i, \tag{54}$$

$$\mathbb{I}_{0i} := \mathbb{I}\{f(\tilde{\mathbf{x}}_i) \in [a, b]\}, \tag{55}$$

$$\mathbb{I}_{1i} := \mathbb{I}\{\tilde{\mathbf{x}}_i \text{ is from } \mathcal{N}(-\mu, \sigma^2 I)\}, \tag{56}$$

$$\mathbb{I}_{2i} := \mathbb{I}\{\tilde{\mathbf{x}}_i \text{ is from } \mathcal{N}(-\mu_o, \sigma^2 I)\}. \tag{57}$$

For simplicity, let's omit the subscript $i$ and consider a sample $\tilde{\mathbf{x}}$ from $U_{\text{mix}}$, and the corresponding variables $z, \mathbb{I}_0, \mathbb{I}_1$, and $\mathbb{I}_2$. Since $\mathbb{I}_1 + \mathbb{I}_2 = 1$,

$$(-\mu - \tilde{\mathbf{x}})\mathbb{I}\{f(\tilde{\mathbf{x}}) \in [a, b]\} = z\mathbb{I}_0\mathbb{I}_1 + z\mathbb{I}_0\mathbb{I}_2. \tag{58}$$

**Case 1.** Let's first consider the case when $\tilde{\mathbf{x}}$ is from $\mathcal{N}(-\mu, \sigma^2 I)$. More precisely, we condition on a fixed $\hat{\theta}_{\text{int}}$ and condition on $\mathbb{I}_1 = 1$. Then $z \sim \mathcal{N}(0, \sigma^2 I)$ and it can be decomposed along the direction $\bar{\theta}_{\text{int}} := \hat{\theta}_{\text{int}} / \|\hat{\theta}_{\text{int}}\|_2$ as follows:

$$z = s \cdot \bar{\theta}_{\text{int}} + z_2 \tag{59}$$

where $s \sim \mathcal{N}(0, \sigma^2)$ and $z_2$ is a Gaussian distribution in the subspace orthogonal to $\bar{\theta}_{\text{int}}$. Then

$$t(\tilde{\mathbf{x}}) = \frac{\tilde{\mathbf{x}}^\top \hat{\theta}_{\text{int}}}{d} = -\frac{\mu^\top \hat{\theta}_{\text{int}}}{d} - \frac{s\|\hat{\theta}_{\text{int}}\|_2}{d}. \tag{60}$$

Therefore, we have

$$\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1 | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] = \mathbb{E}[s \cdot \bar{\theta}_{\text{int}}\mathbb{I}_0 | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] + \mathbb{E}[z_2\mathbb{I}_0 | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] \tag{61}$$

Clearly the second term is $0$ since $z_2\mathbb{I}_0$ is symmetric. So

$$\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1 | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] = \mathbb{E}[s \cdot \bar{\theta}_{\text{int}}\mathbb{I}\{f(\tilde{\mathbf{x}}) \in [a, b]\} | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] \tag{62}$$

$$= \mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\} | \mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}\right] \cdot \bar{\theta}_{\text{int}} \tag{63}$$

$$= \mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right] \cdot \bar{\theta}_{\text{int}} \tag{64}$$

where

$$a' = -\frac{\mu^\top \hat{\theta}_{\text{int}}}{\|\hat{\theta}_{\text{int}}\|_2} - \frac{\sigma^{-1}(b)d}{\|\hat{\theta}_{\text{int}}\|_2} \tag{65}$$

$$= \frac{-2\mu^\top \hat{\theta}_{\text{int}} + d}{2\|\hat{\theta}_{\text{int}}\|_2} \tag{66}$$

$$= \frac{-2\mu^\top \delta_{\text{int}} - d}{2\|\hat{\theta}_{\text{int}}\|_2}, \tag{67}$$

$$b' = -\frac{\mu^\top \hat{\theta}_{\text{int}}}{\|\hat{\theta}_{\text{int}}\|_2} - \frac{\sigma^{-1}(a)d}{\|\hat{\theta}_{\text{int}}\|_2} \tag{68}$$

$$= \frac{-2\mu^\top \hat{\theta}_{\text{int}} + 3d}{2\|\hat{\theta}_{\text{int}}\|_2} \tag{69}$$

$$= \frac{-2\mu^\top \delta_{\text{int}} + d}{2\|\hat{\theta}_{\text{int}}\|_2}. \tag{70}$$

By the bound on $|\mu^\top \delta_{\text{int}}|$, we have

$$\left|\mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right]\right| \leq \int_{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(1-2/\sqrt{n})}^{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(1+2/\sqrt{n})} \sigma t \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{71}$$

$$\leq \sigma \frac{d}{\sigma\|\hat{\theta}_{\text{int}}\|_2} \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(1-2/\sqrt{n})\right)^2} \tag{72}$$

$$\leq \frac{d}{\|\hat{\theta}_{\text{int}}\|_2} e^{-\frac{d^2}{32\sigma^2\|\hat{\theta}_{\text{int}}\|_2^2}} \tag{73}$$

Given the bound on $\|\delta_{\text{int}}\|_2^2$, we have

$$\|\hat{\theta}_{\text{int}}\|_2 \leq \|\mu\|_2 + \|\delta_{\text{int}}\|_2 \leq \sqrt{d} + \sqrt{\frac{\sigma^2}{n}\left(d + \frac{1}{\sigma}\right)} \leq \sqrt{d} + \sqrt{\frac{2\sigma^2 d}{n}}. \tag{74}$$

Since $n \geq Cn_0 \log d$ and $d \geq C^2 n_0 \log^2 d$ for a sufficiently large $C$, we have

$$\frac{\sigma^2 \|\hat{\theta}_{\text{int}}\|_2^2}{d^2} \leq \frac{\sigma^2 d(1 + \sqrt{2\sigma^2/n})^2}{d^2} \leq 2\sqrt{\frac{n_0}{d}} + \frac{4n_0}{n} \leq \frac{6}{C \log d} \tag{75}$$

and thus

$$|\mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right]| \leq \frac{1}{d^2}. \tag{76}$$

Combining with $\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1|\mathbb{I}_1 = 0, \hat{\theta}_{\text{int}}] = 0$ we get

$$\mathbb{E}[z\mathbb{I}_0\mathbb{I}_1|\hat{\theta}_{\text{int}}] = c_1 \cdot \bar{\theta}_{\text{int}} \tag{77}$$

for some $c_1$ satisfying $|c_1| \leq 1/d^2$. Furthermore, $z\mathbb{I}_0\mathbb{I}_1 \mid \hat{\theta}_{\text{int}}$ is truncated Gaussian and thus is sub-Gaussian with sub-Gaussian norm bounded by $\sigma$. Then by sub-Gaussian concentration bounds, we have

$$\mathbb{P}\left(\left|\sum_{i=1}^{n'} \mu^\top z_i \mathbb{I}_{0i}\mathbb{I}_{1i} - \sum_{i=1}^{n'} \mu^\top \mathbb{E}[z_i\mathbb{I}_{0i}\mathbb{I}_{1i}|\hat{\theta}_{\text{int}}]\right| \geq \sqrt{n'd} \mid \hat{\theta}_{\text{int}}\right) \leq e^{-cd/\sigma^2}, \tag{78}$$

$$\mathbb{P}\left(\left\|\sum_{i=1}^{n'} z_i\mathbb{I}_{0i}\mathbb{I}_{1i}\right\|_2 \geq 4\sigma\sqrt{n'd} + 2\sqrt{n'd} \mid \hat{\theta}_{\text{int}}\right) \leq e^{-d/\sigma^2}. \tag{79}$$

for some constant $c > 0$. In other words, with probability $\geq 1 - 2e^{-cd/\sigma^2}$, we have

$$\left|\sum_{i=1}^{n'} \mu^\top z_i\mathbb{I}_{0i}\mathbb{I}_{1i}\right| \leq \sqrt{n'd} + \frac{n'}{d^{3/2}}, \tag{80}$$

$$\left\|\sum_{i=1}^{n'} z_i\mathbb{I}_{0i}\mathbb{I}_{1i}\right\|_2 \leq 6\sigma\sqrt{n'd}. \tag{81}$$

Conditioned on $\mathbb{I}_1 = 1$, we also have

$$\mathbb{E}[\mathbb{I}_0\mathbb{I}_1|\mathbb{I}_1 = 1, \hat{\theta}_{\text{int}}] = \mathbb{P}(s \in [a', b']) \tag{82}$$

$$\geq \int_{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(-1+2/\sqrt{n})}^{\frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(1-2/\sqrt{n})} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{83}$$

$$\geq 1 - 2\int_{\frac{d}{4\sigma\|\hat{\theta}_{\text{int}}\|_2}}^{+\infty} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{84}$$

$$\geq 1 - 2\int_{\frac{\sqrt{C\log d}}{12}}^{+\infty} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{85}$$

$$\geq 1 - \frac{1}{d}. \tag{86}$$

Let $m = \frac{n'}{2}\left(1 - \frac{1}{d}\right)$. Then by Chernoff's bound, we have

$$\mathbb{P}\left(\left|\sum_{i=1}^{n'} \mathbb{I}_{0i}\mathbb{I}_{1i} - m\right| \geq \frac{1}{2}m\right) \leq e^{-c'm} \tag{87}$$

for an absolute constant $c' > 0$. That is, with probality $\geq 1 - e^{-cn'}$, we have $\sum_{i=1}^{n'} \mathbb{I}_{0i}\mathbb{I}_{1i} \geq n'/5$.

**Case 2.** Next, let's consider the case when $\tilde{\mathbf{x}}$ is from $\mathcal{N}(-\mu_o, \sigma^2 I)$. More precisely, we condition on a fixed $\hat{\theta}_{\text{int}}$ and condition on $\mathbb{I}_2 = 1$. Similar to case 1, we have

$$z = 9\mu + s \cdot \bar{\theta}_{\text{int}} + z_2 \tag{88}$$

where $s \sim \mathcal{N}(0, \sigma^2)$ and $z_2$ is a Gaussian distribution in the subspace orthogonal to $\bar{\theta}_{\text{int}}$. So

$$\mathbb{E}[(z - 9\mu)\mathbb{I}_0\mathbb{I}_2|\mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}] = \mathbb{E}[s\mathbb{I}_0|\mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}] \cdot \bar{\theta}_{\text{int}}. \tag{89}$$

For this,

$$\mathbb{E}[s\mathbb{I}\{f(\tilde{\mathbf{x}}) \in [a,b]\}|\mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}] \cdot \bar{\theta}_{\text{int}} = \mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a'', b'']\}\right] \cdot \bar{\theta}_{\text{int}} \tag{90}$$

where

$$a'' = \frac{-20\mu^{\top}\delta_{\text{int}} - 19d}{2\|\hat{\theta}_{\text{int}}\|_2}, \tag{91}$$

$$b'' = \frac{-20\mu^{\top}\delta_{\text{int}} - 17d}{2\|\hat{\theta}_{\text{int}}\|_2}. \tag{92}$$

By the bound on $|\mu^{\top}\delta_{\text{int}}|$ and $\|\delta_{\text{int}}\|_2$, we have

$$\left|\mathbb{E}\left[s \cdot \mathbb{I}\{s \in [a', b']\}\right]\right| \leq \left|\int_{\frac{-d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(19+20/\sqrt{n})}^{\frac{-d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(17-20/\sqrt{n})} \sigma t \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt\right| \tag{93}$$

$$\leq \sigma \frac{20d}{\sigma\|\hat{\theta}_{\text{int}}\|_2} \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{16d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}\right)^2} \tag{94}$$

$$\leq \frac{20d}{\|\hat{\theta}_{\text{int}}\|_2} e^{-\frac{32d^2}{\sigma^2\|\hat{\theta}_{\text{int}}\|_2^2}} \tag{95}$$

$$\leq \frac{1}{d^2}. \tag{96}$$

We also have

$$\left|\mathbb{E}\left[\mathbb{I}_0\mathbb{I}_2|\mathbb{I}_2 = 1, \hat{\theta}_{\text{int}}\right]\right| = \left|\mathbb{E}\left[\mathbb{I}\{s \in [a', b']\}\right]\right| \tag{97}$$

$$\leq \int_{\frac{-d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(19+20/\sqrt{n})}^{\frac{-d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(17-20/\sqrt{n})} \frac{1}{\sqrt{2\pi}} e^{-t^2/2} dt \tag{98}$$

$$\leq \frac{d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}(2 + 40/\sqrt{n}) \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{16d}{2\sigma\|\hat{\theta}_{\text{int}}\|_2}\right)^2} \tag{99}$$

$$\leq \frac{1}{d^3}. \tag{100}$$

Combining the above, we have

$$\mathbb{E}[(z - 9\mu)\mathbb{I}_0\mathbb{I}_2|\hat{\theta}_{\text{int}}] = c_1 \cdot \bar{\theta}_{\text{int}} \tag{101}$$

for a constant $c_1$ satisfying $|c_1| \leq 1/d^2$. Furthermore, $(z - 9\mu)\mathbb{I}_0\mathbb{I}_2 \mid \hat{\theta}_{\text{int}}$ is truncated Gaussian and thus is sub-Gaussian with sub-Gaussian norm bounded by $\sigma$. Then by sub-Gaussian concentration bounds, we have

$$\mathbb{P}\left(\left|\sum_{i=1}^{n'}\mu^{\top}(z_i - 9\mu)\mathbb{I}_{0i}\mathbb{I}_{2i} - \sum_{i=1}^{n'}\mu^{\top}\mathbb{E}[(z_i - 9\mu)\mathbb{I}_{0i}\mathbb{I}_{2i}|\hat{\theta}_{\text{int}}]\right| \geq \sqrt{n'd} \mid \hat{\theta}_{\text{int}}\right) \leq e^{-cd/\sigma^2}, \tag{102}$$

$$\mathbb{P}\left(\left\|\sum_{i=1}^{n'}(z_i - 9\mu)\mathbb{I}_{0i}\mathbb{I}_{2i}\right\|_2 \geq 4\sigma\sqrt{n'd} + 2\sqrt{n'd} \mid \hat{\theta}_{\text{int}}\right) \leq e^{-d/\sigma^2}, \tag{103}$$

for some constant $c > 0$. Also by Hoeffding's bound, we have

$$\mathbb{P}\left(\left|\sum_{i=1}^{n'}\mathbb{I}_{0i}\mathbb{I}_{2i} - \sum_{i=1}^{n'}\mathbb{E}[\mathbb{I}_{0i}\mathbb{I}_{2i}|\hat{\theta}_{\text{int}}]\right| \geq \sqrt{n'd/\sigma^2} \mid \hat{\theta}_{\text{int}}\right) \leq 2e^{-2d/\sigma^2}. \tag{104}$$

In other words, with probability $\geq 1 - 4e^{-cd/\sigma^2}$, we have

$$\left|\sum_{i=1}^{n'}\mu^{\top}z_i\mathbb{I}_{0i}\mathbb{I}_{2i}\right| \leq \sqrt{n'd} + 9d\sqrt{n'd}\sigma^2 + \frac{n'}{d^2}\sqrt{d} + 9d \cdot \frac{n'}{d^3} \leq \sqrt{n'd}\left(1 + \frac{9d}{\sigma}\right) + \frac{n'}{d^{3/2}}, \tag{105}$$

$$\left\|\sum_{i=1}^{n'}z_i\mathbb{I}_{0i}\mathbb{I}_{2i}\right\|_2 \leq 6\sigma\sqrt{n'd} + 9\sqrt{d}\left(\sqrt{\frac{n'd}{\sigma^2}} + \frac{n'}{d^3}\right) \leq \sqrt{n'd}\left(6\sigma + 9\sqrt{\frac{d}{\sigma^2}}\right) + \frac{9n'}{d^{5/2}}. \tag{106}$$

Combining equation 78equation 79equation 87 and equation 105equation 106 together, we get with probability $\geq 1 - Ce^{-cd/\sigma^2}$,

$$|\mu^\top \delta_{\mathrm{om}}| \leq C\sqrt{\frac{d}{n'}}\left(1 + \frac{9d}{\sigma}\right) + \frac{C}{d^{3/2}}, \tag{107}$$

$$\|\delta_{\mathrm{om}}\|_2 \leq C\sqrt{\frac{d}{n'}}\left(6\sigma + 9\sqrt{\frac{d}{\sigma^2}}\right) + \frac{C}{d^{5/2}}. \tag{108}$$

Then $\frac{\mu^\top \hat{\theta}_{\mathrm{om}}}{\|\hat{\theta}_{\mathrm{om}}\|_2}$ can be lower bounded by

$$\frac{\mu^\top \hat{\theta}_{\mathrm{om}}}{\|\hat{\theta}_{\mathrm{om}}\|_2} = \frac{\mu^\top \mu + \mu^\top \delta_{\mathrm{om}}}{\|\mu + \delta_{\mathrm{om}}\|_2} \tag{109}$$

$$\geq \frac{\mu^\top \mu + \mu^\top \delta_{\mathrm{om}}}{\|\mu\|_2 + \|\delta_{\mathrm{om}}\|_2} \tag{110}$$

$$\geq \frac{d(1 - 1/\sqrt{d})}{\sqrt{d}(1 + 1/\sqrt{d})} \tag{111}$$

$$\geq \sqrt{d}\left(1 - \frac{2}{\sqrt{d}}\right). \tag{112}$$

The proof is completed by plugging the above into the closed form expressions equation 17 and equation 23 of the errors. □

## B  DETAILS OF EXPERIMENTS

### B.1  EXPERIMENTAL SETTINGS

**Software and Hardware.** We run all experiments with PyTorch and NVDIA GeForce RTX 2080Ti GPUs.

**Number of Evaluation Runs.** We run all experiments once with fixed random seeds.

**In-distribution Datasets.** We use SVHN (Netzer et al., 2011), CIFAR-10 and CIFAR-100 (Krizhevsky et al., 2009) as in-distribution datasets. SVHN has 10 classes and contains 73,257 training images. CIFAR-10 and CIFAR-100 have 10 and 100 classes, respectively. Both datasets consist of 50,000 training images and 10,000 test images.

**Auxiliary Datasets.** We provide the details of auxiliary datasets below. For each auxiliary dataset, we use random cropping with padding of 4 pixels to generate $32 \times 32$ images, and further augment the data by random horizontal flipping. We don't use any image corruptions to augment the data.

1. **80M Tiny Images.** 80 Million Tiny Images (Torralba et al., 2008) is a dataset that contains 79,302,017 images collected from the Web. The images in the dataset are stored as $32 \times 32$ color images. Since CIFAR-10 and CIFAR-100 are labeled subsets of the 80 Million Tiny Images dataset, we need to remove those images in the dataset that belong to CIFAR-10 or CIFAR-100. We follow the same deduplication procedure as in (Hendrycks et al., 2018) and remove all examples in this dataset that appear in CIFAR-10 or CIFAR-100. This auxiliary dataset may contain some in-distribution data, but the fraction of them is low.

2. **ImageNet.** We use the downsampled ImageNet dataset (ImageNet$64 \times 64$) (Chrabaszcz et al., 2017), which is a downsampled version of the original ImageNet dataset. It contains 1,281,167 images with image size of $64 \times 64$ and 1,000 classes. Some of the classes have overlapping with CIFAR-10 or CIFAR-100 classes. Since we don't remove any images from the auxiliary set, it may contains some in-distribution data if we use CIFAR-10 or CIFAR-100 as in-distribution datasets. Also, we don't use the label information of the auxiliary set. Thus, we can say that the auxiliary dataset is unlabeled. Since we randomly crop the $64 \times 64$ images into $32 \times 32$ images with padding of 4 pixels, the resulting images may not contain objects belonging to the in-distribution classes even if the original images contain objects belonging to those classes. Therefore, we still can have enough OOD data for training and the fraction of in-distribution data in the auxiliary set is low.

**OOD Test Datasets.** We provide the details of OOD test datasets below. All images are of size $32 \times 32$.

1. **SVHN.** The SVHN dataset (Netzer et al., 2011) contains color images of house numbers. There are ten classes of digits `0-9`. The original test set has 26,032 images. We randomly select 1,000 test images for each class and form a new test dataset of 10,000 images for evaluation.

2. **Textures.** The Describable Textures Dataset (DTD) (Cimpoi et al., 2014) contains textural images in the wild. We include the entire collection of 5640 images for evaluation.

3. **Places365.** The Places365 dataset (Zhou et al., 2017) contains large-scale photographs of scenes with 365 scene categories. There are 900 images per category in the test set. We randomly sample 10,000 images from the test set for evaluation.

4. **LSUN (crop) and LSUN (resize).** The Large-scale Scene UNderstanding dataset (LSUN) has a testing set of 10,000 images of 10 different scenes (Yu et al., 2015). We construct two datasets, `LSUN-C` and `LSUN-R`, by randomly cropping image patches of size $32 \times 32$ and downsampling each image to size $32 \times 32$, respectively.

5. **iSUN.** The iSUN (Xu et al., 2015) consists of a subset of SUN images. We include the entire collection of 8925 images in iSUN.

6. **CIFAR-10.** We use the test set of CIFAR-10, which contains 10,000 images.

7. **Gaussian Noise.** The synthetic Gaussian noise dataset consists of 10,000 random 2D Gaussian noise images, where each RGB value of every pixel is sampled from an i.i.d Gaussian distribution with mean 0.5 and unit variance. We further clip each pixel value into the range [0,1].

8. **Uniform Noise.** The synthetic uniform noise dataset consists 10,000 images where each RGB value of every pixel is independently and identically sampled from a uniform distribution on [0,1].

**Architectures and Training Configurations.** We use the state-of-the-art neural network architecture DenseNet (Huang et al., 2017) and WideResNet (Zagoruyko & Komodakis, 2016). For DenseNet, we follow the same setup as in (Huang et al., 2017), with depth $L = 100$, growth rate $k = 12$ (Dense-BC) and dropout rate 0. For WideResNet, we also follow the same setup as in (Zagoruyko & Komodakis, 2016), with depth of 40 and widening parameter $k = 4$ (WRN-40-4). All neural networks are trained with stochastic gradient descent with Nesterov momentum (Duchi et al., 2011; Kingma & Ba, 2014). We set momentum 0.9 and $\ell_2$ weight decay with a coefficient of $10^{-4}$ for all model training. Specifically, for SVHN, we train the networks for 20 epochs and the initial learning rate of 0.1 decays by 0.1 at 10, 15, 18 epoch; for CIFAR-10 and CIFAR-100, we train the networks for 100 epochs and the initial learning rate of 0.1 decays by 0.1 at 50, 75, 90 epoch. We use batch size 64 for in-distribution data and 128 for out-of-distribution data. To solve the inner max of the robust training objective, we use PGD with $\epsilon = 8/255$, the number of iterations of 5, the step size of $2/255$, and random start.

## B.2 Average Runtime

We run our experiments using a single GPU on a machine with 4 GPUs and 32 cores. The estimated average runtime for each method is summarized in Table 3.

## B.3 OOD Detection Methods

We consider eight common OOD detection methods listed in Table 4 and describe each method in detail below.

**Maximum Softmax Probability (MSP).** Hendrycks & Gimpel propose to use $\max_i F_i(x)$ as confidence scores to detect OOD examples, where $F(x)$ is the softmax output of the neural network.

**ODIN.** Liang et al. computes calibrated confidence scores using temperature scaling and input perturbation techniques. In all of our experiments, we set temperature scaling parameter $T = 1000$. We choose perturbation magnitude $\eta$ by validating on 1000 images randomly sampled from in-distribution test set $\mathcal{D}_{\text{in}}^{\text{test}}$ and 1000 images randomly sampled from auxiliary outlier dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$,

| Method | Training | Evaluation |
|--------|----------|------------|
| MSP | 2.5 h | 4 h |
| ODIN | 2.5 h | 4 h |
| Mahalanobis | 2.5 h | 20 h |
| SOFL | 14 h | 4 h |
| OE | 5 h | 4 h |
| ACET | 17 h | 4 h |
| CCU | 6.7 h | 4 h |
| ROWL | 24 h | 4 h |
| ATOM (ours) | 21 h | 4 h |

Table 3: The estimated average runtime for each result. We use DenseNet as network architecture. $h$ means hour. For MSP, ODIN, and Mahalanobis, we use standard training. The evaluation includes four OOD detection tasks listed in Section 2.

| | MSP | ODIN | Mahalanobis | SOFL | OE | ACET | CCU | ROWL | ATOM (ours) |
|---|-----|------|-------------|------|----|------|-----|------|-------------|
| Natural OOD | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| $L_\infty$ OOD | ✗ | ✗ | ✗ | ✗ | ✗ | ✓ | ✓ | ✓ | ✓ |
| Corruption OOD | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✓ |
| Comp. OOD | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✓ |

Table 4: Common OOD detection methods and a family of natural and perturbed OOD examples we considered.

which does not depend on prior knowledge of test OOD datasets. For DenseNet, we set $\eta = 0.0006$ for SVHN, $\eta = 0.0016$ for CIFAR-10, and $\eta = 0.0012$ for CIFAR-100. For WideResNet, we set $\eta = 0.0002$ for SVHN, $\eta = 0.0006$ for CIFAR-10, and $\eta = 0.0012$ for CIFAR-100.

**Mahalanobis.** Lee et al. propose to use Mahalanobis distance-based confidence scores to detect OOD samples. Following Lee et al., we use 1000 examples randomly selected from in-distribution test set $\mathcal{D}_{in}^{test}$ and adversarial examples generated by FGSM (Goodfellow et al., 2014) on them with perturbation size of 0.05 to train the Logistic Regression model and tune the noise perturbation magnitude $\eta$. $\eta$ is chosen from $\{0.0, 0.01, 0.005, 0.002, 0.0014, 0.001, 0.0005\}$, and the optimal parameters are chosen to minimize the FPR at FNR 5%.

**Outlier Exposure (OE).** Outlier Exposure (Hendrycks et al., 2018) makes use of a large, unlabeled dataset $\mathcal{D}_{out}^{auxiliary}$ to enhance the performance of existing OOD detection. We train from scratch for 100 epochs with $\lambda = 0.5$, and use in-distribution batch size of 64 and out-distribution batch size of 128 in our experiments.

**Self-Supervised OOD Feature Learning (SOFL).** Mohseni et al. add an auxiliary head to the network and train in for the OOD detection task. They first use a full-supervised training to learn in-distribution training data for the main classification head and then a self-supervised training with OOD training set for the auxiliary head. Following the original setting, we set $\lambda = 5$ and use an in-distribution batch size of 64 and an out-distribution batch size of 320 in all of our experiments. In CIFAR-10, we use 5 reject classes, while in CIFAR-100, we use 10 reject classes. In CIFAR-10 and CIFAR-100, we train the model for 100 epochs with the full-supervised training and then continue to train for 100 epochs with the self-supervised OOD feature learning. We use the large, unlabeled dataset $\mathcal{D}_{out}^{auxiliary}$ as out-of-distribution training dataset.

**Adversarial Confidence Enhancing Training (ACET).** Hein et al. propose Adversarial Confidence Enhancing Training to enforce low model confidence for the OOD data point, as well as worst-case adversarial example in the neighborhood of an OOD example. We use the large, unlabeled dataset $\mathcal{D}_{out}^{auxiliary}$ as an OOD training dataset instead of using random noise data for a fair comparison. In all of our experiments, we train for 100 epochs and set $\lambda = 1.0$. For both in-distribution and out-distribution, we use a batch size of 128. To solve the inner max of the training objective, we also apply PGD with $\epsilon = 8/255$, the number of iterations of 5, the step size of $2/255$, and random start to a half of a minibatch while keeping the other half clean to ensure proper performance on both perturbed and clean OOD examples for a fair comparison.

**Certified Certain Uncertainty (CCU).** Certified Certain Uncertainty (Meinke & Hein, 2019) gives guarantees on the confidence of the classifier decision far away from the training data. We use the same training set up as in the paper and code, except for an architectural difference (DenseNet or WideResNet).

**Robust Open-World Deep Learning (ROWL).**   Sehwag et al.  propose to introduce additional background classes for OOD datasets and perform adversarial training on both the in- and out-of-distribution datasets to achieve robust open-world classification. When an input is classified as the background classes, it is considered as an OOD example. Thus, ROWL gives binary OOD scores (either 0 or 1) to the inputs. In our experiments, we only have one background class and randomly sample data points from the large, unlabeled dataset $\mathcal{D}_{\text{out}}^{\text{auxiliary}}$ to form the OOD dataset. To ensure data balance across classes, we include 5,000 OOD data points for CIFAR-10; while for CIFAR-100, we include 500 OOD data points. During training, we mix the in-distribution data and OOD data, use a batch size of 128, and train for 100 epochs. To solve the inner max of the training objective, we use PGD with $\epsilon = 8/255$, the number of iterations of 5, the step size of $2/255$, and random start.

### B.4   Adversarial Attacks for OOD Detection Methods

We propose adversarial attack objectives for different OOD detection methods. We consider a family of adversarial perturbations for the OOD inputs: (1) $L_\infty$-norm bounded attack (white-box attack); (2) common image corruptions attack (black-box attack); (3) compositional attack which combines common image corruptions attack and $L_\infty$ norm bounded attack (white-box attack).

$L_\infty$ **norm bounded attack.** For data point $\mathbf{x} \in \mathbb{R}^d$, the $L_\infty$ norm bounded perturbation is defined as

$$\Omega_{\infty,\epsilon}(\mathbf{x}) = \{\delta \in \mathbb{R}^d \mid \|\delta\|_\infty \leq \epsilon \wedge \mathbf{x} + \delta \text{ is valid}\}, \tag{113}$$

where $\epsilon$ is the adversarial budget. $\mathbf{x} + \delta$ is considered valid if the values of $\mathbf{x} + \delta$ are in the image pixel value range.

For MSP, ODIN, OE, ACET, and CCU methods, we propose the following attack objective to generate adversarial OOD example on a clean OOD input $\mathbf{x}$:

$$\mathbf{x}' = \operatorname*{arg\,max}_{\mathbf{x}' \in \Omega_{\infty,\epsilon}(\mathbf{x})} -\frac{1}{K} \sum_{i=1}^{K} \log F(\mathbf{x}')_i \tag{114}$$

where $F(\mathbf{x})$ is the softmax output of the classifier network.

For Mahalanobis method, we propose the following attack objective to generate adverasrial OOD example on OOD input $\mathbf{x}$:

$$\mathbf{x}' = \operatorname*{arg\,max}_{\mathbf{x}' \in \Omega_{\infty,\epsilon}(\mathbf{x})} -\log \frac{1}{1 + e^{-(\sum_\ell \alpha_\ell M_\ell(\mathbf{x}') + b)}}, \tag{115}$$

where $M_\ell(\mathbf{x}')$ is the Mahalanobis distance-based confidence score of $\mathbf{x}'$ from the $\ell$-th feature layer, $\{\alpha_\ell\}$ and $b$ are the parameters of the logistic regression model.

For SOFL method, we propose the following attack objective to generate adversarial OOD example for an input $\mathbf{x}$:

$$\mathbf{x}' = \operatorname*{arg\,max}_{\mathbf{x}' \in \Omega_{\infty,\epsilon}(\mathbf{x})} -\log \sum_{i=K+1}^{K+R} \bar{F}(\mathbf{x}')_i \tag{116}$$

where $\bar{F}(\mathbf{x})$ is the softmax output of the whole neural network (including auxiliary head) and $R$ is the number of reject classes.

For ROWL and ATOM method, we propose the following attack objective to generate adverasrial OOD example on OOD input $\mathbf{x}$:

$$\mathbf{x}' = \operatorname*{arg\,max}_{\mathbf{x}' \in \Omega_{\infty,\epsilon}(\mathbf{x})} -\log \hat{F}(\mathbf{x}')_{K+1} \tag{117}$$

where $\hat{F}(\mathbf{x})$ is the softmax output of the (K+1)-way neural network.

| $\mathcal{D}_{in}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| **SVHN** | ATOM (q=0.0) | **0.01** | 99.97 | **4.02** | 98.50 | **8.08** | 98.14 | **96.79** | 43.77 |
| | ATOM (q=0.125) | 2.16 | 99.39 | 36.62 | 94.79 | 62.38 | 73.20 | 99.98 | 4.62 |
| | ATOM (q=0.25) | 1.87 | 99.38 | 41.86 | 94.20 | 75.85 | 57.75 | 100.00 | 1.26 |
| | ATOM (q=0.5) | 2.73 | 99.18 | 45.02 | 93.85 | 83.01 | 49.38 | 99.99 | 1.96 |
| | ATOM (q=0.75) | 4.97 | 98.83 | 56.51 | 92.13 | 85.98 | 40.89 | 100.00 | 1.16 |
| **CIFAR-10** | ATOM (q=0.0) | 5.34 | 98.35 | 43.61 | 91.85 | 22.08 | 92.81 | 59.17 | 83.56 |
| | ATOM (q=0.125) | **4.77** | 98.31 | **27.49** | 94.24 | **5.42** | 98.19 | **29.02** | 93.76 |
| | ATOM (q=0.25) | 5.70 | 98.11 | 28.13 | 93.68 | 19.28 | 95.71 | 40.68 | 91.17 |
| | ATOM (q=0.5) | 8.83 | 97.66 | 39.74 | 91.53 | 9.80 | 97.42 | 44.10 | 90.45 |
| | ATOM (q=0.75) | 12.42 | 97.02 | 45.85 | 90.53 | 13.40 | 96.83 | 46.30 | 90.42 |
| **CIFAR-100** | ATOM (q=0.0) | 44.85 | 91.58 | 98.76 | 64.78 | 53.17 | 85.26 | 98.95 | 58.38 |
| | ATOM (q=0.125) | 36.75 | 92.90 | 96.22 | 73.33 | 38.79 | 91.42 | 96.33 | 71.74 |
| | ATOM (q=0.25) | **34.66** | 92.62 | 94.13 | 73.86 | **35.84** | 91.24 | 94.33 | 70.35 |
| | ATOM (q=0.5) | 35.04 | 91.36 | **89.28** | 71.78 | 36.76 | 90.21 | **89.57** | 70.62 |
| | ATOM (q=0.75) | 43.49 | 87.95 | 91.80 | 62.47 | 59.34 | 78.00 | 92.94 | 58.53 |

Table 5: Evaluate models on validation dataset. We use DenseNet as network architecture. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets mentioned in section 4.1. **Bold** numbers are superior results.

Due to computational concerns, by default, we will use PGD with $\epsilon = 8/255$, the number of iterations of 40, the step size of 1/255 and random start to solve these attack objectives. We also perform ablation study experiments on the attack strength for ACET and ATOM, see Appendix B.10.

**Common Image Corruptions attack.** We use common image corruptions introduced in (Hendrycks & Dietterich, 2019). We apply 15 types of algorithmically generated corruptions from noise, blur, weather, and digital categories to each OOD image. Each type of corruption has five levels of severity, resulting in 75 distinct corruptions. Thus, for each OOD image, we generate 75 corrupted images and then select the one with the lowest OOD score (or highest confidence score to be in-distribution). Note that we only need the outputs of the OOD detectors to construct such adversarial OOD examples; thus it is a black-box attack.

**Compositional Attack.** For each OOD image, we first apply common image corruptions attack, and then apply the $L_\infty$-norm bounded attack to generate adversarial OOD examples.

## B.5 Visualizations of Four Types of OOD Samples

We show visualizations of four types of OOD samples in Figure 4.

## B.6 Histogram of OOD Scores

In Figure 5, we show histogram of OOD scores for model snapshots trained on CIFAR-10 (in-distribution) using objective (2) **without** informative outlier mining. We plot every ten epochs for a model trained for a total of 100 epochs. We observe that the model quickly converges to a solution where OOD score distribution becomes dominated by *easy* examples with scores closer to 1. This is exacerbated as the model is trained for longer.

## B.7 Choose Best q Using Validation Dataset

We create a validation OOD dataset by sampling 10,000 images from the 80 Million Tiny Images (Torralba et al., 2008), which is disjoint from our training data. We choose $q$ from $\{0, 0.125, 0.25, 0.5, 0.75\}$. The results on the validation dataset are shown in Table 5. We select the best model based on the average FPR at 5% FNR across four types of OOD inputs. Based on the results, the optimal $q$ is 0 for SVHN, 0.125 for CIFAR-10 and 0.5 for CIFAR-100.

(a) Natural OOD

(b) $L_\infty$ OOD

(c) Corruption OOD

(d) Comp. OOD

Figure 4: Examples of four types of OOD samples.

## B.8   EFFECT OF AUXILIARY DATASETS

## B.9   EFFECT OF NETWORK ARCHITECTURE

We perform experiments to evaluate different OOD detection methods using WideResNet, see Table 7. For both ATOM and NTOM, we use the same hyperparameters as those selected for DenseNet and find that it also leads to good results.

## B.10   EFFECT OF PGD ATTACK STRENGTH

We evaluate ACET and ATOM on $L_\infty$ attacked OOD and compositionally attacked OOD inputs with strong PGD attack (100 iterations and 5 random restarts), see Table 8 for comparisons.

## B.11   EVALUATION ON RANDOM NOISE OOD DATA

We report the performance of OOD detectors using DenseNet on random noise OOD test datasets in Table 9 (SVHN), Table 10 (CIFAR-10) and Table 11 (CIFAR-100).

| $\mathcal{D}_{in}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| **SVHN** | MSP | 38.84 | 93.57 | 99.68 | 68.48 | 99.89 | 1.39 | 100.00 | 0.19 |
| | ODIN | 31.45 | 93.52 | 97.11 | 63.21 | 99.86 | 0.61 | 100.00 | 0.05 |
| | Mahalanobis | 22.80 | 95.57 | 93.14 | 60.78 | 97.33 | 8.89 | 99.89 | 0.23 |
| | SOFL | | | | | | | | |
| | OE | | | | | | | | |
| | ACET | | | | | | | | |
| | CCU | | | | | | | | |
| | ROWL | 2.04 | 98.87 | 55.03 | 72.37 | 77.24 | 61.27 | 99.79 | 50.00 |
| | NTOM (ours) | | | | | | | | |
| | ATOM (ours) | | | | | | | | |
| **CIFAR-10** | MSP | 50.54 | 91.79 | 100.00 | 58.35 | 100.00 | 13.82 | 100.00 | 13.67 |
| | ODIN | 21.65 | 94.66 | 99.37 | 51.44 | 99.99 | 0.18 | 100.00 | 0.01 |
| | Mahalanobis | 26.95 | 90.30 | 91.92 | 43.94 | 95.07 | 12.47 | 99.88 | 1.58 |
| | SOFL | 3.10 | 99.28 | 17.06 | 96.73 | 93.38 | 14.35 | 99.49 | 6.49 |
| | OE | 9.70 | 98.35 | 49.84 | 91.76 | 91.30 | 43.88 | | |
| | ACET | 10.72 | 98.01 | 53.85 | 90.19 | 17.10 | 96.01 | 55.21 | 89.78 |
| | CCU | 10.30 | 98.25 | 44.42 | 92.34 | 93.02 | 20.88 | 99.17 | 9.95 |
| | ROWL | 25.03 | 86.96 | 94.34 | 52.31 | 99.98 | 49.49 | 100.00 | 49.48 |
| | NTOM (ours) | | | | | | | | |
| | ATOM (ours) | | | | | | | | |
| **CIFAR-100** | MSP | 78.05 | 76.11 | 100.00 | 30.04 | 100.00 | 2.25 | 100.00 | 2.06 |
| | ODIN | 56.77 | 83.62 | 100.00 | 36.95 | 100.00 | 0.14 | 100.00 | 0.00 |
| | Mahalanobis | 42.63 | 87.86 | 95.92 | 42.96 | 95.44 | 15.87 | 99.86 | 2.08 |
| | SOFL | | | | | | | | |
| | OE | | | | | | | | |
| | ACET | | | | | | | | |
| | CCU | | | | | | | | |
| | ROWL | 93.35 | 53.02 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | | | | | | | | |
| | ATOM (ours) | | | | | | | | |

Table 6: Comparison with competitive OOD detection methods. We use ImageNet as auxiliary training dataset for SOFL, OE, ACET, CCU, NTOM and ATOM. We use DenseNet as network architecture for all methods. We evaluate on four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 4.1. **Bold** numbers are superior results.

## B.12 PERFORMANCE OF OOD DETECTOR AND CLASSIFIER ON IN-DISTRIBUTION DATA

We summarize the performance of OOD detector $G(x)$ and image classifier $f(x)$ on in-distribution test data. See Table 12 for DenseNet and Table 13 for WideResNet.

## B.13 COMPLETE EXPERIMENTAL RESULTS

We report the performance of OOD detectors using DenseNet on each of the six natural OOD test datasets in Table 14 (SVHN), Table 15 (CIFAR-10) and Table 16 (CIFAR-100).

| $\mathcal{D}_{in}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| SVHN | MSP | 42.78 | 91.15 | 99.99 | 51.84 | 100.00 | 0.15 | 100.00 | 0.05 |
| | ODIN | 43.65 | 89.37 | 99.85 | 44.43 | 100.00 | 0.06 | 100.00 | 0.00 |
| | Mahalanobis | 6.94 | 98.47 | 80.91 | 78.92 | 93.44 | 39.42 | 99.70 | 2.69 |
| | SOFL | **0.02** | **99.99** | **2.41** | **99.36** | 85.25 | 39.32 | 99.28 | 2.85 |
| | OE | 0.58 | 99.87 | 21.97 | 96.00 | 70.66 | 47.36 | 96.63 | 5.87 |
| | ACET | 0.43 | 99.92 | 18.12 | 97.11 | 20.75 | 89.55 | 99.66 | 1.80 |
| | CCU | 0.71 | 99.86 | 30.96 | 94.40 | 73.37 | 41.82 | 99.83 | 0.44 |
| | ROWL | 1.46 | 99.13 | 45.18 | 77.28 | 86.95 | 56.39 | 99.94 | 49.90 |
| | NTOM (ours) | **0.02** | **99.99** | 2.46 | 99.27 | 70.38 | 52.43 | 99.79 | 1.01 |
| | ATOM (ours) | 0.08 | 99.96 | 4.18 | 98.65 | **5.93** | **98.47** | **95.50** | **62.00** |
| CIFAR-10 | MSP | 53.81 | 91.10 | 100.00 | 50.30 | 100.00 | 5.48 | 100.00 | 5.43 |
| | ODIN | 36.25 | 91.18 | 99.95 | 31.78 | 100.00 | 0.04 | 100.00 | 0.00 |
| | Mahalanobis | 23.93 | 92.48 | 86.78 | 56.90 | 85.75 | 42.63 | 99.22 | 17.51 |
| | SOFL | 2.15 | **99.14** | 38.03 | 93.35 | 99.99 | 0.43 | 100.00 | 0.24 |
| | OE | 3.03 | 98.83 | 56.00 | 91.19 | 99.97 | 0.26 | 100.00 | 0.04 |
| | ACET | 3.19 | 98.74 | 35.78 | 94.25 | 40.22 | 89.52 | 56.08 | 87.76 |
| | CCU | 2.61 | 98.75 | 36.31 | 93.75 | 99.93 | 0.86 | 99.99 | 0.41 |
| | ROWL | 17.21 | 90.79 | 86.09 | 56.35 | 99.94 | 49.43 | 99.99 | 49.40 |
| | NTOM (ours) | 1.86 | 99.10 | 23.77 | 94.58 | 99.92 | 0.84 | 99.96 | 0.33 |
| | ATOM (ours) | **1.50** | 98.87 | **13.17** | **96.36** | **33.66** | **90.89** | **40.07** | **88.99** |
| CIFAR-100 | MSP | 81.92 | 74.32 | 100.00 | 28.10 | 100.00 | 3.20 | 100.00 | 3.14 |
| | ODIN | 68.76 | 79.13 | 100.00 | 26.44 | 100.00 | 0.15 | 100.00 | 0.01 |
| | Mahalanobis | 43.48 | 86.02 | 95.78 | 42.25 | 95.83 | 17.41 | 99.92 | 3.55 |
| | SOFL | 66.57 | 89.11 | 99.99 | 59.64 | 99.99 | 0.30 | 100.00 | 0.10 |
| | OE | 46.14 | 91.16 | 99.96 | 58.55 | 100.00 | 1.80 | 100.00 | 1.69 |
| | ACET | 46.79 | 91.67 | 99.76 | 62.48 | 95.66 | 41.38 | 99.99 | 36.65 |
| | CCU | 48.35 | 91.41 | 99.95 | 57.94 | 100.00 | 0.44 | 100.00 | 0.38 |
| | ROWL | 96.93 | 51.34 | 100.00 | 49.81 | 100.00 | 49.81 | 100.00 | 49.81 |
| | NTOM (ours) | 37.94 | 92.14 | 97.09 | 66.93 | 99.99 | 1.04 | 99.99 | 0.13 |
| | ATOM (ours) | **30.52** | **93.90** | **94.46** | **74.96** | **44.30** | **89.68** | **95.06** | **74.25** |

Table 7: Comparison with competitive OOD detection methods. We use WideResNet as network architecture for all methods. We evaluate on four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 4.1. **Bold** numbers are superior results.

| $\mathcal{D}_{in}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|
| | | $L_\infty$ OOD | | Comp. OOD | |
| SVHN | ACET | 33.64 | 83.89 | 99.90 | 2.84 |
| | ATOM (ours) | **8.33** | **97.37** | **98.56** | **35.32** |
| CIFAR-10 | ACET | 76.66 | 76.29 | 97.08 | 51.35 |
| | ATOM (ours) | **26.88** | **83.78** | **42.86** | **83.56** |
| CIFAR-100 | ACET | 87.13 | 48.77 | 99.82 | 33.67 |
| | ATOM (ours) | **45.11** | **82.32** | **93.74** | **65.88** |

Table 8: Evaluation on $L_\infty$ attacked OOD and compositionally attacked OOD inputs with strong PGD attack (100 iterations and 5 random restarts). We use DenseNet as network architecture for all methods. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages and are averaged over six natural OOD test datasets described in section 4.1. **Bold** numbers are superior results.

Figure 5: On CIFAR-10, we train the model with objective (2) for 100 epochs **without** informative outlier mining. For every 10 epochs, we randomly sample 400,000 data points from the large unlabeled dataset and use the current model snapshot to calculate the OOD scores.

| $\mathcal{D}_{out}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| | MSP | 56.30 | 90.16 | 100.00 | 55.70 | 100.00 | 5.25 | 100.00 | 0.14 |
| Gaussian Noise | ODIN | 58.49 | 88.24 | 100.00 | 44.91 | 100.00 | 0.87 | 100.00 | 0.01 |
| | Mahalanobis | **0.00** | 99.92 | 97.34 | 77.03 | 1.51 | 98.73 | 100.00 | 0.00 |
| | SOFL | **0.00** | **100.00** | 0.02 | 99.93 | **0.00** | 99.98 | 100.00 | 0.42 |
| | OE | **0.00** | **100.00** | 0.93 | 99.74 | **0.00** | **100.00** | 98.71 | 2.20 |
| | ACET | **0.00** | **100.00** | **0.00** | **99.98** | **0.00** | 99.99 | 98.80 | 17.98 |
| | CCU | **0.00** | 99.99 | 0.11 | 99.94 | **0.00** | 99.97 | **34.14** | 65.91 |
| | ROWL | **0.00** | 99.89 | 3.83 | 97.97 | **0.00** | 99.89 | 91.98 | 53.90 |
| | NTOM (ours) | **0.00** | **100.00** | 0.03 | 99.94 | **0.00** | **100.00** | 100.00 | 0.72 |
| | ATOM (ours) | **0.00** | **100.00** | **0.00** | 99.96 | **0.00** | **100.00** | 63.53 | **93.40** |
| | MSP | 53.63 | 90.75 | 100.00 | 52.67 | 100.00 | 0.05 | 100.00 | 0.00 |
| Uniform Noise | ODIN | 59.07 | 87.96 | 100.00 | 39.84 | 100.00 | 0.00 | 100.00 | 0.00 |
| | Mahalanobis | **0.00** | 99.73 | 99.99 | 56.02 | 100.00 | 20.33 | 100.00 | 0.00 |
| | SOFL | **0.00** | **100.00** | 0.35 | 99.74 | 39.53 | 91.58 | 100.00 | 0.01 |
| | OE | **0.00** | **100.00** | 5.83 | 98.88 | 0.09 | 99.98 | 99.97 | 0.16 |
| | ACET | **0.00** | **100.00** | 0.32 | 99.70 | **0.00** | 99.99 | 100.00 | 1.17 |
| | CCU | **0.00** | **100.00** | 4.04 | 99.19 | **0.00** | 99.97 | 99.82 | 0.18 |
| | ROWL | **0.00** | 99.89 | 17.44 | 91.17 | 0.19 | 99.80 | 100.00 | 49.89 |
| | NTOM (ours) | **0.00** | **100.00** | 0.11 | 99.86 | 0.22 | 99.87 | 100.00 | 0.01 |
| | ATOM (ours) | **0.00** | **100.00** | **0.00** | **99.92** | **0.00** | **100.00** | **99.79** | **74.58** |

Table 9: Comparison with competitive OOD detection methods. We use SVHN as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.

| $\mathcal{D}_{out}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| | MSP | 100.00 | 77.69 | 100.00 | 73.29 | 100.00 | 69.73 | 100.00 | 52.56 |
| Gaussian Noise | ODIN | 97.30 | 89.00 | 100.00 | 81.48 | 100.00 | 71.12 | 100.00 | 34.99 |
| | Mahalanobis | **0.00** | **100.00** | **0.00** | **99.95** | **0.00** | **100.00** | 85.03 | 23.21 |
| | SOFL | **0.00** | 99.99 | 48.06 | 94.12 | 0.03 | 98.83 | 100.00 | 4.42 |
| | OE | **0.00** | 99.91 | 0.05 | 98.48 | **0.00** | 99.08 | 99.65 | 32.44 |
| | ACET | **0.00** | 99.94 | **0.00** | 99.74 | **0.00** | 99.87 | **0.04** | 99.40 |
| | CCU | **0.00** | 98.84 | 0.09 | 98.09 | 0.85 | 97.21 | 84.47 | 69.56 |
| | ROWL | 0.71 | 99.13 | 100.00 | 49.48 | 99.99 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | **0.00** | 99.97 | 0.08 | 98.90 | **0.00** | 99.87 | 99.12 | 37.97 |
| | ATOM (ours) | **0.00** | 99.93 | **0.00** | 99.65 | **0.00** | 99.93 | 0.21 | **99.54** |
| | MSP | 99.67 | 86.55 | 100.00 | 76.54 | 100.00 | 71.48 | 100.00 | 36.82 |
| Uniform Noise | ODIN | 91.48 | 90.73 | 100.00 | 79.19 | 100.00 | 51.93 | 100.00 | 13.86 |
| | Mahalanobis | **0.00** | **100.00** | **0.00** | **99.94** | **0.00** | **100.00** | 99.84 | 22.25 |
| | SOFL | **0.00** | 99.75 | 95.82 | 86.22 | 100.00 | 69.89 | 100.00 | 4.39 |
| | OE | **0.00** | 99.89 | 0.02 | 98.62 | 33.05 | 92.41 | 99.98 | 29.62 |
| | ACET | **0.00** | 99.95 | **0.00** | 99.22 | **0.00** | 99.88 | **36.48** | **95.06** |
| | CCU | **0.00** | 98.50 | 0.87 | 97.78 | 94.68 | 86.27 | 99.70 | 48.18 |
| | ROWL | 97.14 | 50.91 | 100.00 | 49.48 | 100.00 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | **0.00** | 99.97 | 1.42 | 98.08 | 28.41 | 95.94 | 100.00 | 2.88 |
| | ATOM (ours) | **0.00** | 99.93 | **0.00** | 99.07 | **0.00** | 99.93 | 91.81 | 45.48 |

Table 10: Comparison with competitive OOD detection methods. We use CIFAR-10 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages.

| $\mathcal{D}_{out}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | **Natural OOD** | | **Corruption OOD** | | $L_\infty$ **OOD** | | **Comp. OOD** | |
| Gaussian Noise | MSP | 100.00 | 18.62 | 100.00 | 11.90 | 100.00 | 5.29 | 100.00 | 2.04 |
| | ODIN | 100.00 | 16.53 | 100.00 | 12.57 | 100.00 | 2.57 | 100.00 | 1.55 |
| | Mahalanobis | **0.00** | **100.00** | **0.00** | **99.82** | **0.00** | **100.00** | 99.18 | **81.79** |
| | SOFL | **0.00** | **100.00** | 100.00 | 70.93 | 4.56 | 98.30 | 100.00 | 0.17 |
| | OE | 3.69 | 97.53 | 100.00 | 64.71 | 67.00 | 92.45 | 100.00 | 1.60 |
| | ACET | **0.00** | 99.02 | 22.38 | 95.49 | 0.14 | 97.68 | 99.71 | 75.87 |
| | CCU | 100.00 | 50.78 | 100.00 | 47.92 | 100.00 | 37.06 | 100.00 | 35.25 |
| | ROWL | 0.54 | 99.42 | 100.00 | 49.69 | 99.37 | 50.01 | 100.00 | 49.69 |
| | NTOM (ours) | **0.00** | 99.95 | 30.60 | 95.57 | **0.00** | 99.92 | 100.00 | 30.10 |
| | ATOM (ours) | **0.00** | 99.98 | **0.00** | 99.06 | **0.00** | 99.98 | **86.43** | 52.84 |
| Uniform Noise | MSP | 99.99 | 37.86 | 100.00 | 16.59 | 100.00 | 2.45 | 100.00 | 1.67 |
| | ODIN | 100.00 | 31.77 | 100.00 | 20.56 | 100.00 | 0.48 | 100.00 | 0.40 |
| | Mahalanobis | **0.00** | **100.00** | **0.00** | **99.69** | **0.00** | **100.00** | 100.00 | 32.70 |
| | SOFL | **0.00** | 99.99 | 100.00 | 68.28 | 99.98 | 79.63 | 100.00 | 0.59 |
| | OE | 0.19 | 99.21 | 100.00 | 57.39 | 100.00 | 55.40 | 100.00 | 0.62 |
| | ACET | **0.00** | 99.43 | 64.94 | 93.48 | 95.10 | 91.27 | 98.47 | **57.60** |
| | CCU | 30.96 | 95.93 | 100.00 | 71.51 | 100.00 | 46.37 | 100.00 | 5.29 |
| | ROWL | 98.45 | 50.46 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | **0.00** | 99.79 | 64.35 | 94.08 | 99.97 | 87.14 | 100.00 | 18.81 |
| | ATOM (ours) | **0.00** | 99.98 | 0.04 | 98.44 | **0.00** | 99.98 | **89.90** | 41.34 |

Table 11: Comparison with competitive OOD detection methods. We use CIFAR-100 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages.

| $\mathcal{D}_{\text{in}}^{\text{test}}$ | Method | FNR | Pred. Acc. | End-to-end. Pred. Acc. |
|---|---|---|---|---|
| **SVHN** | MSP | 5.01 | 95.83 | 93.00 |
| | ODIN | 5.01 | 95.83 | 92.44 |
| | Mahalanobis | 5.01 | 95.83 | 91.50 |
| | SOFL | 5.01 | 96.45 | 92.81 |
| | OE | 5.01 | 95.93 | 93.11 |
| | ACET | 5.01 | 95.58 | 92.79 |
| | CCU | 5.01 | 95.85 | 92.95 |
| | ROWL | 0.22 | 95.23 | 95.23 |
| | NTOM (ours) | 5.01 | 95.75 | 91.99 |
| | ATOM (ours) | 5.01 | 96.09 | 91.95 |
| **CIFAR-10** | MSP | 5.01 | 94.39 | 91.76 |
| | ODIN | 5.01 | 94.39 | 91.00 |
| | Mahalanobis | 5.01 | 94.39 | 89.72 |
| | SOFL | 5.01 | 95.11 | 91.60 |
| | OE | 5.01 | 94.79 | 91.86 |
| | ACET | 5.01 | 91.48 | 88.61 |
| | CCU | 5.01 | 94.89 | 91.88 |
| | ROWL | 1.04 | 93.18 | 93.18 |
| | NTOM (ours) | 5.01 | 95.42 | 91.57 |
| | ATOM (ours) | 5.01 | 95.20 | 91.33 |
| **CIFAR-100** | MSP | 5.01 | 75.05 | 73.87 |
| | ODIN | 5.01 | 75.05 | 73.72 |
| | Mahalanobis | 5.01 | 75.05 | 71.12 |
| | SOFL | 5.01 | 74.37 | 72.62 |
| | OE | 5.01 | 75.28 | 73.74 |
| | ACET | 5.01 | 74.43 | 72.72 |
| | CCU | 5.01 | 76.04 | 74.60 |
| | ROWL | 0.62 | 72.51 | 72.51 |
| | NTOM (ours) | 5.01 | 74.88 | 72.47 |
| | ATOM (ours) | 5.01 | 75.06 | 72.72 |

Table 12: The performance of OOD detector and classifier on in-distribution test data. We use DenseNet for all methods. We use three metrics: FNR, Prediction Accuracy and End-to-end Prediction Accuracy. We pick the threshold for the OOD detectors such that 95% of in-distribution test data points are classified as in-distribution. Prediction Accuracy measures the accuracy of the classifier on in-distribution test data. End-to-end Prediction Accuracy measures the accuracy of the open world classification system (detector+classifier), where an example is classified correctly if and only if the detector treats it as in-distribution and the classifier predicts its label correctly.

| $\mathcal{D}_{\text{in}}^{\text{test}}$ | Method | FNR | Pred. Acc. | End-to-end. Pred. Acc. |
|---|---|---|---|---|
| | MSP | 5.01 | 95.61 | 92.91 |
| | ODIN | 5.01 | 95.61 | 92.49 |
| | Mahalanobis | 5.01 | 95.61 | 91.34 |
| | SOFL | 5.01 | 95.65 | 92.34 |
| **SVHN** | OE | 5.01 | 95.76 | 92.91 |
| | ACET | 5.01 | 95.96 | 93.13 |
| | CCU | 5.01 | 95.83 | 93.05 |
| | ROWL | 0.27 | 95.87 | 95.87 |
| | NTOM (ours) | 5.01 | 95.76 | 91.98 |
| | ATOM (ours) | 5.01 | 95.96 | 91.82 |
| | MSP | 5.01 | 94.92 | 92.38 |
| | ODIN | 5.01 | 94.92 | 91.60 |
| | Mahalanobis | 5.01 | 94.92 | 90.27 |
| | SOFL | 5.01 | 95.98 | 92.45 |
| **CIFAR-10** | OE | 5.01 | 95.51 | 92.35 |
| | ACET | 5.01 | 95.33 | 92.47 |
| | CCU | 5.01 | 95.63 | 92.46 |
| | ROWL | 1.21 | 93.91 | 93.91 |
| | NTOM (ours) | 5.01 | 95.89 | 91.97 |
| | ATOM (ours) | 5.01 | 95.89 | 92.20 |
| | MSP | 5.01 | 76.61 | 75.46 |
| | ODIN | 5.01 | 76.61 | 75.16 |
| | Mahalanobis | 5.01 | 76.61 | 72.61 |
| | SOFL | 5.01 | 75.12 | 73.78 |
| **CIFAR-100** | OE | 5.01 | 75.58 | 74.47 |
| | ACET | 5.01 | 75.61 | 74.60 |
| | CCU | 5.01 | 76.36 | 75.34 |
| | ROWL | 0.39 | 75.94 | 75.94 |
| | NTOM (ours) | 5.01 | 76.30 | 74.04 |
| | ATOM (ours) | 5.01 | 77.51 | 75.32 |

Table 13: The performance of OOD detector and classifier on in-distribution test data. We use WideResNet for all methods. We use three metrics: FNR, Prediction Accuracy and End-to-end Prediction Accuracy. We pick the threshold for the OOD detectors such that 95% of in-distribution test data points are classified as in-distribution. Prediction Accuracy measures the accuracy of the classifier on in-distribution test data. End-to-end Prediction Accuracy measures the accuracy of the open world classification system (detector+classifier), where an example is classified correctly if and only if the detector treats it as in-distribution and the classifier predicts its label correctly.

| $\mathcal{D}_{out}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| LSUN-C | MSP | 33.90 | 94.01 | 99.59 | 68.76 | 99.94 | 0.82 | 100.00 | 0.11 |
| | ODIN | 28.40 | 93.77 | 97.37 | 59.61 | 99.90 | 0.38 | 100.00 | 0.01 |
| | Mahalanobis | 0.20 | 99.64 | 79.20 | 80.24 | 98.01 | 10.95 | 99.99 | 0.07 |
| | SOFL | **0.00** | **100.00** | **2.10** | **99.38** | 68.89 | 54.15 | 99.98 | 0.31 |
| | OE | **0.00** | **100.00** | 23.06 | 96.38 | 54.03 | 77.79 | 99.91 | 0.52 |
| | ACET | **0.00** | **100.00** | 20.48 | 96.75 | 0.09 | 99.97 | 99.85 | 4.76 |
| | CCU | **0.00** | **100.00** | 22.26 | 96.46 | 35.10 | 80.37 | 99.92 | 0.55 |
| | ROWL | 2.50 | 98.64 | 75.48 | 62.15 | 96.22 | 51.78 | 99.99 | **49.90** |
| | NTOM (ours) | **0.00** | **100.00** | 2.64 | 99.06 | 54.69 | 75.51 | 99.99 | 0.17 |
| | ATOM (ours) | **0.00** | **100.00** | 16.71 | 96.91 | **0.00** | **100.00** | **97.85** | 39.64 |
| LSUN-R | MSP | 44.84 | 92.75 | 99.93 | 66.82 | 100.00 | 1.22 | 100.00 | 0.11 |
| | ODIN | 36.84 | 92.91 | 98.53 | 62.91 | 100.00 | 0.25 | 100.00 | 0.01 |
| | Mahalanobis | 18.35 | 96.64 | 98.92 | 54.27 | 99.04 | 10.01 | 100.00 | 0.00 |
| | SOFL | **0.00** | **100.00** | 0.55 | 99.75 | 49.23 | 77.50 | 99.88 | 4.77 |
| | OE | 0.02 | **100.00** | 9.44 | 98.34 | 41.86 | 79.82 | 99.91 | 1.54 |
| | ACET | **0.00** | **100.00** | 5.36 | 98.87 | 2.60 | 99.35 | 99.96 | 7.00 |
| | CCU | **0.00** | **100.00** | 9.44 | 98.46 | 12.25 | 94.36 | 98.90 | 2.78 |
| | ROWL | 0.01 | 99.89 | 22.57 | 88.61 | 39.54 | 80.12 | 99.68 | 50.05 |
| | NTOM (ours) | **0.00** | **100.00** | **0.12** | **99.82** | 22.97 | 91.97 | 99.97 | 2.34 |
| | ATOM (ours) | **0.00** | **100.00** | 0.13 | 99.67 | **0.09** | **99.97** | **96.08** | **63.20** |
| iSUN | MSP | 40.78 | 93.57 | 99.85 | 68.88 | 99.99 | 1.37 | 100.00 | 0.14 |
| | ODIN | 31.98 | 93.97 | 97.70 | 64.77 | 99.99 | 0.29 | 100.00 | 0.01 |
| | Mahalanobis | 19.73 | 96.25 | 98.35 | 56.95 | 98.73 | 10.21 | 100.00 | 0.01 |
| | SOFL | **0.00** | **100.00** | 0.75 | 99.70 | 56.78 | 69.82 | 99.87 | 4.39 |
| | OE | 0.01 | **100.00** | 9.50 | 98.36 | 45.45 | 76.08 | 99.76 | 1.72 |
| | ACET | 0.01 | **100.00** | 6.17 | 98.84 | 4.90 | 98.52 | 99.92 | 6.96 |
| | CCU | 0.02 | **100.00** | 9.94 | 98.32 | 17.36 | 90.54 | 99.13 | 2.56 |
| | ROWL | 0.04 | 99.87 | 24.43 | 87.68 | 44.62 | 77.58 | 99.29 | 50.24 |
| | NTOM (ours) | **0.00** | **100.00** | 0.38 | **99.77** | 30.90 | 87.40 | 99.98 | 2.26 |
| | ATOM (ours) | **0.00** | **100.00** | 0.24 | 99.59 | **0.25** | **99.94** | **95.20** | **61.70** |
| Textures | MSP | 41.91 | 92.08 | 99.33 | 61.77 | 99.45 | 2.84 | 100.00 | 0.44 |
| | ODIN | 40.48 | 89.91 | 97.36 | 52.69 | 99.29 | 2.14 | 100.00 | 0.27 |
| | Mahalanobis | 24.34 | 94.15 | 85.94 | 62.00 | 88.83 | 17.73 | 99.38 | 1.27 |
| | SOFL | 0.34 | **99.91** | 11.83 | 97.47 | 89.36 | 23.54 | 99.20 | 2.42 |
| | OE | 2.73 | 99.50 | 43.05 | 92.51 | 84.36 | 26.88 | 98.32 | 2.72 |
| | ACET | 2.55 | 99.54 | 32.55 | 94.67 | 64.57 | 58.46 | 99.40 | 5.73 |
| | CCU | 2.22 | 99.57 | 41.86 | 92.46 | 78.09 | 31.94 | 98.58 | 2.31 |
| | ROWL | 7.85 | 95.96 | 71.17 | 64.30 | 89.73 | 55.02 | 99.77 | **50.01** |
| | NTOM (ours) | 0.27 | 99.90 | **9.18** | **97.97** | 81.17 | 35.06 | 98.76 | 2.74 |
| | ATOM (ours) | 0.41 | 99.83 | 11.31 | 97.66 | **28.81** | **90.97** | **91.61** | 49.35 |
| Places365 | MSP | 36.14 | 94.37 | 99.60 | 71.71 | 99.99 | 1.03 | 100.00 | 0.14 |
| | ODIN | 26.84 | 95.01 | 96.25 | 68.40 | 99.99 | 0.32 | 100.00 | 0.01 |
| | Mahalanobis | 34.83 | 93.95 | 98.14 | 55.70 | 99.64 | 1.97 | 100.00 | 0.00 |
| | SOFL | **0.00** | **99.99** | 3.46 | 99.09 | 94.58 | 26.96 | 99.96 | 1.98 |
| | OE | 0.37 | 99.91 | 27.78 | 95.86 | 94.97 | 26.54 | 99.99 | 0.47 |
| | ACET | 0.15 | 99.96 | 19.28 | 97.06 | 49.09 | 83.63 | 99.99 | 2.65 |
| | CCU | 0.27 | 99.95 | 29.12 | 95.65 | 83.26 | 39.88 | 100.00 | 0.59 |
| | ROWL | 0.97 | 99.41 | 67.26 | 66.26 | 96.67 | 51.56 | 100.00 | **49.89** |
| | NTOM (ours) | **0.00** | **99.99** | 2.39 | **99.21** | 87.35 | 46.68 | 99.99 | 0.48 |
| | ATOM (ours) | **0.00** | **99.99** | **2.31** | 98.59 | **5.60** | **98.71** | **98.74** | 38.95 |
| CIFAR-10 | MSP | 35.45 | 94.66 | 99.79 | 72.97 | 100.00 | 1.07 | 100.00 | 0.19 |
| | ODIN | 24.15 | 95.54 | 95.45 | 70.89 | 100.00 | 0.28 | 100.00 | 0.01 |
| | Mahalanobis | 39.35 | 92.80 | 98.28 | 55.52 | 99.70 | 2.47 | 100.00 | 0.01 |
| | SOFL | 0.01 | **99.99** | 3.99 | 99.03 | 93.00 | 28.70 | 99.95 | 2.60 |
| | OE | 0.48 | 99.89 | 27.79 | 95.92 | 95.49 | 26.02 | 99.98 | 0.63 |
| | ACET | 0.21 | 99.94 | 18.32 | 97.18 | 54.71 | 80.56 | 99.98 | 3.69 |
| | CCU | 0.47 | 99.91 | 32.40 | 95.34 | 86.98 | 36.35 | 99.98 | 0.79 |
| | ROWL | 0.84 | 99.47 | 69.28 | 65.25 | 96.68 | 51.55 | 100.00 | **49.89** |
| | NTOM (ours) | **0.00** | 99.98 | 2.53 | **99.17** | 84.60 | 47.74 | 100.00 | 0.99 |
| | ATOM (ours) | **0.00** | 99.98 | **2.14** | 98.72 | **7.39** | **98.42** | **98.51** | 44.28 |

Table 14: Comparison with competitive OOD detection methods. We use SVHN as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.

| $\mathcal{D}_{out}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| **LSUN-C** | MSP | 27.34 | 96.30 | 100.00 | 71.57 | 100.00 | 13.75 | 100.00 | 13.68 |
| | ODIN | 1.89 | 99.50 | 98.94 | 71.86 | 100.00 | 0.06 | 100.00 | 0.00 |
| | Mahalanobis | 14.82 | 94.63 | 93.31 | 46.23 | 98.07 | 8.04 | 99.99 | 1.36 |
| | SOFL | 0.39 | 99.40 | 56.07 | 93.02 | 100.00 | 2.36 | 100.00 | 1.96 |
| | OE | 0.97 | 99.52 | 40.85 | 93.99 | 99.99 | 0.36 | 100.00 | 0.19 |
| | ACET | 1.76 | 99.42 | 31.46 | 95.40 | 45.54 | 90.57 | 88.09 | 70.84 |
| | CCU | 0.62 | **99.65** | 33.44 | 94.56 | 99.97 | 0.31 | 100.00 | 0.05 |
| | ROWL | 10.92 | 94.02 | 91.67 | 53.64 | 100.00 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | 0.27 | 99.59 | 20.32 | 96.31 | 99.95 | 3.12 | 100.00 | 0.36 |
| | ATOM (ours) | **0.25** | 99.53 | **16.38** | **96.75** | **0.38** | **99.49** | **17.27** | **96.49** |
| **LSUN-R** | MSP | 43.89 | 93.93 | 100.00 | 64.26 | 100.00 | 13.74 | 100.00 | 13.66 |
| | ODIN | 3.29 | 99.20 | 98.96 | 63.83 | 100.00 | 0.14 | 100.00 | 0.00 |
| | Mahalanobis | 7.43 | 97.88 | 98.71 | 39.24 | 94.59 | 16.62 | 100.00 | 0.45 |
| | SOFL | 1.67 | 99.29 | 56.41 | 90.62 | 100.00 | 0.55 | 100.00 | 0.43 |
| | OE | 0.99 | 99.43 | 51.55 | 92.25 | 99.99 | 0.15 | 100.00 | 0.02 |
| | ACET | 3.87 | 99.10 | 77.90 | 87.37 | 70.50 | **84.01** | 99.87 | 48.53 |
| | CCU | 1.53 | 99.28 | 57.03 | 90.53 | 100.00 | 0.04 | 100.00 | 0.10 |
| | ROWL | 36.03 | 81.47 | 98.72 | 50.12 | 100.00 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | **0.38** | **99.57** | 17.84 | **96.76** | 100.00 | 0.20 | 100.00 | 0.27 |
| | ATOM (ours) | 0.41 | 99.33 | **16.77** | 96.63 | 52.76 | 71.84 | 50.33 | 75.18 |
| **iSUN** | MSP | 46.18 | 93.58 | 100.00 | 62.76 | 99.99 | 13.95 | 100.00 | 13.67 |
| | ODIN | 4.45 | 99.00 | 98.90 | 62.14 | 100.00 | 0.33 | 100.00 | 0.01 |
| | Mahalanobis | 8.58 | 98.00 | 98.10 | 42.96 | 89.64 | 22.78 | 100.00 | 0.74 |
| | SOFL | 2.24 | 99.22 | 53.99 | 90.97 | 100.00 | 0.51 | 100.00 | 0.50 |
| | OE | 1.14 | 99.40 | 48.25 | 92.46 | 99.97 | 0.13 | 100.00 | 0.02 |
| | ACET | 6.16 | 98.59 | 75.36 | 87.00 | 78.59 | **79.84** | 99.63 | 47.11 |
| | CCU | 1.74 | 99.27 | 52.44 | 91.10 | 100.00 | 0.05 | 100.00 | 0.08 |
| | ROWL | 35.44 | 81.76 | 97.02 | 50.97 | 100.00 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | **0.63** | **99.59** | 16.25 | **96.90** | 99.99 | 0.32 | 100.00 | 0.38 |
| | ATOM (ours) | 0.66 | 99.34 | **15.10** | 96.79 | 52.48 | 68.44 | **51.94** | **72.08** |
| **Textures** | MSP | 64.66 | 87.64 | 100.00 | 51.85 | 100.00 | 14.14 | 100.00 | 13.72 |
| | ODIN | 52.45 | 84.81 | 99.56 | 38.20 | 99.95 | 0.56 | 100.00 | 0.07 |
| | Mahalanobis | 25.39 | 92.20 | 71.42 | 61.60 | 88.85 | 17.24 | 99.27 | 3.60 |
| | SOFL | 3.78 | 99.04 | 56.81 | 89.38 | 99.88 | 2.06 | 99.98 | 1.36 |
| | OE | 6.24 | 98.43 | 53.32 | 88.83 | 99.68 | 1.40 | 99.95 | 0.68 |
| | ACET | 11.74 | 97.96 | 54.41 | 90.52 | 64.49 | 77.66 | 94.26 | 55.24 |
| | CCU | 5.83 | 98.45 | 54.61 | 86.33 | 99.49 | 1.68 | 99.84 | 0.99 |
| | ROWL | 19.33 | 89.82 | 82.87 | 58.04 | 99.89 | 49.53 | 99.98 | 49.49 |
| | NTOM (ours) | 2.27 | 99.42 | 24.66 | 95.09 | 99.49 | 3.63 | 99.95 | 1.67 |
| | ATOM (ours) | **1.81** | **99.47** | **20.05** | **95.92** | **10.05** | **96.47** | **29.01** | **91.40** |
| **Places365** | MSP | 62.03 | 88.29 | 100.00 | 57.68 | 100.00 | 13.66 | 100.00 | 13.66 |
| | ODIN | 43.84 | 90.45 | 99.89 | 52.81 | 100.00 | 0.01 | 100.00 | 0.00 |
| | Mahalanobis | 85.77 | 65.76 | 99.47 | 22.75 | 99.79 | 1.93 | 100.00 | 0.66 |
| | SOFL | 7.73 | 97.81 | 61.66 | 88.07 | 100.00 | 0.47 | 100.00 | 0.27 |
| | OE | 11.08 | 97.00 | 67.91 | 87.39 | 100.00 | 0.03 | 100.00 | 0.01 |
| | ACET | 18.63 | 95.97 | 79.42 | 85.00 | 93.09 | 66.83 | 99.61 | 46.19 |
| | CCU | 8.49 | 97.63 | 67.68 | 85.75 | 100.00 | 0.03 | 100.00 | 0.03 |
| | ROWL | 43.76 | 77.60 | 97.67 | 50.64 | 100.00 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | 6.63 | **97.94** | 37.01 | 92.75 | 100.00 | 0.06 | 100.00 | 0.04 |
| | ATOM (ours) | **6.30** | 97.92 | **31.44** | **93.41** | **6.96** | **97.78** | **32.99** | **92.93** |
| **SVHN** | MSP | 59.15 | 90.99 | 100.00 | 41.97 | 100.00 | 13.67 | 100.00 | 13.66 |
| | ODIN | 23.96 | 95.00 | 100.00 | 19.78 | 100.00 | 0.00 | 100.00 | 0.00 |
| | Mahalanobis | 19.73 | 93.33 | 90.52 | 50.89 | 99.48 | 8.18 | 100.00 | 2.67 |
| | SOFL | 0.85 | 99.47 | 87.50 | 79.85 | 100.00 | 0.13 | 100.00 | 0.07 |
| | OE | 1.55 | 99.16 | 75.62 | 89.02 | 100.00 | 0.01 | 100.00 | 0.02 |
| | ACET | 31.50 | 94.99 | 83.04 | 85.25 | 94.49 | 69.42 | 99.81 | 54.36 |
| | CCU | 2.14 | 99.25 | 75.34 | 88.01 | 100.00 | 0.00 | 100.00 | 0.00 |
| | ROWL | 4.73 | 97.12 | 98.09 | 50.43 | 100.00 | 49.48 | 100.00 | 49.48 |
| | NTOM (ours) | 1.06 | 99.59 | 67.40 | 90.23 | 100.00 | 0.01 | 100.00 | 0.00 |
| | ATOM (ours) | **0.69** | **99.63** | **51.84** | **92.22** | **0.69** | **99.63** | **51.81** | **92.18** |

Table 15: Comparison with competitive OOD detection methods. We use CIFAR-10 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.

| $\mathcal{D}_{out}^{test}$ | Method | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ | FPR (5% FNR) ↓ | AUROC ↑ |
|---|---|---|---|---|---|---|---|---|---|
| | | Natural OOD | | Corruption OOD | | $L_\infty$ OOD | | Comp. OOD | |
| LSUN-C | MSP | 62.03 | 84.78 | 100.00 | 32.47 | 100.00 | 2.52 | 100.00 | 2.31 |
| | ODIN | 15.47 | 97.34 | 100.00 | 42.25 | 100.00 | 0.20 | 100.00 | 0.01 |
| | Mahalanobis | 47.44 | 93.47 | 98.80 | 58.23 | 98.94 | 15.07 | 99.97 | 3.01 |
| | SOFL | 17.38 | 96.66 | 100.00 | 51.59 | 100.00 | 1.10 | 100.00 | 0.58 |
| | OE | 14.75 | 97.33 | 99.91 | 54.29 | 100.00 | 1.61 | 100.00 | 0.64 |
| | ACET | 14.60 | 97.41 | 98.65 | 67.81 | 23.07 | 95.35 | 98.88 | 56.02 |
| | CCU | **12.03** | **97.84** | 99.60 | 61.24 | 100.00 | 0.86 | 100.00 | 0.50 |
| | ROWL | 88.67 | 55.35 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 20.61 | 96.58 | 95.91 | 83.28 | 100.00 | 1.31 | 100.00 | 0.25 |
| | ATOM (ours) | 21.40 | 96.31 | **79.72** | **87.67** | **21.50** | **96.26** | **79.98** | **87.11** |
| LSUN-R | MSP | 77.48 | 76.40 | 100.00 | 32.21 | 100.00 | 1.94 | 100.00 | 1.78 |
| | ODIN | 34.81 | 93.37 | 100.00 | 45.41 | 100.00 | 0.22 | 100.00 | 0.00 |
| | Mahalanobis | **14.87** | 97.06 | 99.89 | 31.14 | 94.81 | 24.18 | 100.00 | 0.37 |
| | SOFL | 50.27 | 90.28 | 99.88 | 50.12 | 100.00 | 0.11 | 100.00 | 0.20 |
| | OE | 56.25 | 84.35 | 99.96 | 41.17 | 100.00 | 0.70 | 100.00 | 0.52 |
| | ACET | 56.35 | 88.17 | 99.50 | 51.85 | 98.67 | 18.64 | 99.74 | 22.45 |
| | CCU | 38.44 | 91.83 | 99.94 | 50.62 | 100.00 | 0.59 | 100.00 | 0.47 |
| | ROWL | 88.25 | 55.57 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 37.92 | 94.31 | 99.11 | 65.00 | 100.00 | 0.36 | 100.00 | 0.06 |
| | ATOM (ours) | 17.93 | 96.94 | **95.72** | **71.51** | **31.39** | **87.38** | **95.87** | **66.15** |
| iSUN | MSP | 78.87 | 75.69 | 100.00 | 31.83 | 100.00 | 2.08 | 100.00 | 1.82 |
| | ODIN | 38.92 | 92.15 | 100.00 | 43.43 | 100.00 | 0.31 | 100.00 | 0.00 |
| | Mahalanobis | **16.46** | **96.75** | 99.76 | 33.38 | 89.71 | 28.16 | 100.00 | 0.38 |
| | SOFL | 53.51 | 89.27 | 99.96 | 48.75 | 100.00 | 0.19 | 100.00 | 0.21 |
| | OE | 61.59 | 81.51 | 99.99 | 39.94 | 100.00 | 0.81 | 100.00 | 0.54 |
| | ACET | 60.49 | 86.80 | 99.70 | 49.61 | 98.54 | 19.92 | 99.94 | 23.51 |
| | CCU | 40.97 | 90.89 | 99.98 | 49.21 | 100.00 | 0.79 | 100.00 | 0.44 |
| | ROWL | 90.42 | 54.48 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 43.66 | 93.24 | 99.51 | 61.40 | 100.00 | 0.41 | 100.00 | 0.02 |
| | ATOM (ours) | 20.09 | 96.62 | **97.05** | **68.31** | **35.70** | **85.87** | **97.13** | **63.16** |
| Textures | MSP | 85.57 | 70.08 | 100.00 | 25.93 | 100.00 | 2.63 | 100.00 | 2.28 |
| | ODIN | 83.58 | 70.71 | 100.00 | 27.30 | 100.00 | 0.11 | 100.00 | 0.01 |
| | Mahalanobis | **34.59** | 89.82 | **78.35** | 62.36 | 89.27 | 20.33 | 99.18 | 5.43 |
| | SOFL | 57.00 | 87.35 | 99.73 | 44.11 | 99.98 | 0.59 | 100.00 | 0.34 |
| | OE | 59.86 | 86.17 | 99.88 | 42.95 | 99.98 | 1.45 | 100.00 | 0.73 |
| | ACET | 62.02 | 86.26 | 99.70 | 49.02 | 83.17 | 63.61 | 99.86 | 40.58 |
| | CCU | 60.80 | 86.34 | 99.88 | 44.90 | 100.00 | 1.39 | 100.00 | 0.62 |
| | ROWL | 97.00 | 51.19 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 38.21 | **91.06** | 95.34 | 66.86 | 99.82 | 2.43 | 100.00 | 0.60 |
| | ATOM (ours) | 40.11 | 90.28 | 90.21 | **69.99** | **47.27** | **82.52** | **91.45** | **65.91** |
| Places365 | MSP | 83.65 | 73.71 | 100.00 | 32.13 | 100.00 | 1.83 | 100.00 | 1.91 |
| | ODIN | 79.19 | 76.48 | 100.00 | 39.16 | 100.00 | 0.00 | 100.00 | 0.00 |
| | Mahalanobis | 94.64 | 59.52 | 99.80 | 19.43 | 99.96 | 1.13 | 100.00 | 0.50 |
| | SOFL | 60.49 | **87.57** | 100.00 | 40.25 | 100.00 | 0.06 | 100.00 | 0.15 |
| | OE | 58.37 | 86.39 | 100.00 | 50.83 | 100.00 | 0.57 | 100.00 | 0.54 |
| | ACET | 56.26 | 86.75 | 99.66 | 57.36 | 83.60 | 72.35 | 99.83 | 44.27 |
| | CCU | **55.23** | 87.21 | 100.00 | 44.03 | 100.00 | 0.46 | 100.00 | 0.43 |
| | ROWL | 96.86 | 51.26 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 56.54 | 84.27 | 99.33 | 57.32 | 100.00 | 0.01 | 100.00 | 0.02 |
| | ATOM (ours) | 56.52 | 84.53 | **96.65** | **63.43** | **58.68** | **82.50** | **96.68** | **62.36** |
| SVHN | MSP | 80.71 | 76.00 | 100.00 | 25.69 | 100.00 | 2.47 | 100.00 | 2.29 |
| | ODIN | 88.66 | 71.65 | 100.00 | 24.17 | 100.00 | 0.00 | 100.00 | 0.00 |
| | Mahalanobis | 47.78 | 90.54 | **98.93** | 53.25 | 99.96 | 6.34 | 100.00 | 2.78 |
| | SOFL | **21.50** | 96.15 | 100.00 | 36.59 | 100.00 | 0.07 | 100.00 | 0.16 |
| | OE | 44.47 | 92.58 | 100.00 | 40.86 | 100.00 | 0.53 | 100.00 | 0.57 |
| | ACET | 55.86 | 90.36 | 100.00 | 49.51 | 70.55 | 86.86 | 99.99 | 44.93 |
| | CCU | 50.79 | 91.59 | 100.00 | 40.01 | 100.00 | 0.41 | 100.00 | 0.40 |
| | ROWL | 98.88 | 50.25 | 100.00 | 49.69 | 100.00 | 49.69 | 100.00 | 49.69 |
| | NTOM (ours) | 24.67 | **96.20** | 99.83 | 60.37 | 100.00 | 0.01 | 100.00 | 0.00 |
| | ATOM (ours) | 37.78 | 93.68 | 99.54 | **70.86** | **37.78** | **93.68** | **99.55** | **70.23** |

Table 16: Comparison with competitive OOD detection methods. We use CIFAR-100 as in-distribution dataset and use DenseNet as network architecture for all methods. We evaluate the performance on all four types of OOD inputs: (1) natural OOD, (2) corruption attacked OOD, (3) $L_\infty$ attacked OOD, and (4) compositionally attacked OOD inputs. ↑ indicates larger value is better, and ↓ indicates lower value is better. All values are percentages. **Bold** numbers are superior results.