The Learning Dynamics of Geometric Structure in Transformers

Abstract

Language models trained on various tasks exhibit a rich *geometric structure* in the representation space, such as smooth manifolds for counting characters in a line. But how these geometric structures *emerge* during training, when they become *useful* for computation, and how their formation is reflected in the model *weights* remain poorly understood. In this work, we study these learning dynamics in a small transformer trained to predict line breaks in synthetic text at a fixed line width. Specifically, we find a *phase change* that is primarily driven by the emergence of a 1D ordinal manifold for character counting, coinciding with the onset of accurate line-break prediction. This geometric structure exerts a progressive causal influence on the task. Early in training, ablating the character count subspace has no effect, but as the manifold forms and converges towards its final geometry, the same ablation increasingly degrades loss and suppresses line-break token prediction. At the weights level, we show that this phase transition exhibits the signature of *saddle escape*: low-rank updates in the attention weights and a transient negative-curvature direction in the loss landscape. Finally, we sweep the weight initialization scale α, which monotonically slows the phase transition as α decreases. More broadly, our work highlights the geometric structure as a lens for understanding how transformers acquire task-relevant representations during training.

1 Introduction

Language models exhibit striking geometric structure in their internal representations. Periodic concepts like days of the week and times of year are arranged on circles in the residual stream [Kantamneni and Tegmark, 2025, Modell et al., 2025, Karkada et al., 2026]; ordinal quantities such as the number of characters in the current line live on 1D manifolds embedded in low-dimensional subspaces [Gurnee et al., 2025]; semantic and analogical relations are visible as linear directions in word-embedding geometry [Korchinski et al., 2025]. At convergence, these geometries are well-documented and increasingly well-explained [Karkada et al., 2026]. *But when and how do they emerge during training?*

Prior work has studied learning dynamics through the loss trajectory. Grokking and hidden progress [Liu et al., 2022, Barak et al., 2023], abrupt capability onsets such as induction-head formation [Olsson et al., 2022, Park et al., 2024], and the saddle-to-saddle dynamics of deep linear networks [Saxe et al., 2014, Jacot et al., 2022, Rhee et al., 2026] characterise *when* new capabilities appear and *why* they appear discretely. On the representation side, activations of trained transformers have been mapped as concrete geometric objects [Gurnee et al., 2025, Modell et al., 2025, Kantamneni and Tegmark, 2025]. In this work, we study the learning dynamics of these geometric structures: when a representational manifold first appears, when it begins to causally influence the downstream computation it supports, and how its emergence registers in the model's weights.

(a) Cyclic template τ_m

(b) An example sequence

Figure 1: An overview of the **synthetic line-wrap dataset.** **(a)** The language is parameterized by one of $M = 32$ cyclic templates τ_m of length $K = 32$ (8 positions shown). Each template position contains a content token $c_i \in \mathcal{C}$; color denotes the token's character length $\ell(c_i) \in \{1, \ldots, 8\}$, with 12 content tokens per length class ($|\mathcal{C}| = 96$). **(b)** For each training example, we sample a template m, start offset s, and line width W, prepend `<bos>`, and then walk cyclically through τ_m from offset s. The character count cc accumulates the lengths of content tokens on the current line, with characters remaining $cr = W - cc$. At each position, the model must predict `
` iff the next content token would exceed the line width ($\ell_{\text{next}} > cr$); otherwise it predicts the next content token. After each `
`, $cc$ resets to zero. The first row shows a break after an underfilled line, the second an exact-fill break, and the dashed gray box marks a non-`
` prediction point.

We study this in a synthetic setting that isolates a single well-characterized representational geometry. Following Gurnee et al. [2025], we train a small transformer to predict line wrapping at a fixed line width — a task that requires maintaining a character count in the residual stream.

We summarize our *contributions* as follows.

- **The phase transition of the geometric structure.** We identify a sharp *phase transition* between training steps 400 and 1500 in which break-token F_1 rises from chance to ~ 0.78 and the residual stream at layer 2 organizes into the 1D ordinal manifold for character count that Gurnee et al. [2025] document at convergence.

- **Causal effect of the representational geometry.** The character count subspace's causal role acquires its final direction during the transition itself — early-training steering is *anti-causal* (patching to a larger count *decreases* break preference) and inverts in lockstep with the formation of the manifold.

- **The phase transition in weight space.** The phase transition exhibits a *saddle escape*: QK weight updates collapse to low rank during the window and the loss Hessian opens a transient negative-curvature direction that recovers afterward.

- **Initialization scale controls the timing, not the outcome.** Across four orders of magnitude, the weight initialization scale α controls only the timing of the transition, not whether the capability is acquired.

2 Problem Setting

We study the task of linebreaking in fixed-width text. Given a text with a fixed line width W, the model must not only predict the next word, but also insert line breaks so that each line stays within the fixed width. Language Models solve this task by encoding the character count of the line on a 1D manifold in the residual stream [Gurnee et al., 2025], giving us a concrete geometric object whose emergence we can study and track. We train small transformers on a *synthetic* linebreak dataset (Figure 1) that preserves the core task structure while removing the semantic and lexical complexity of natural text.

Dataset. The vocabulary $\mathcal{V}$ contains four special tokens, $\{$`<pad>`, `<bos>`, `<eos>`, `
`$\}$, and 96 content tokens $\mathcal{C}$. Each content token $c_i \in \mathcal{C}$ has a character length $\ell(c_i) \in \{1, \ldots, 8\}$, with 12 tokens

Figure 2: **Phase transition in the linebreak task. (a)** Class means $\{\mu_c^{(t,2)}\}$ at four training steps, projected onto the top 3 PCs of the final-checkpoint means (Eq. 1, $T = 24{,}000$). Color encodes character count $cc \in \{1, \ldots, 150\}$. **(b)** Eval loss $\bar{\mathcal{L}}^{(t)}$,
 negative log likelihood $\bar{\mathcal{L}}_{\texttt{
}}^{(t)}$,
-token $F_1^{(t)}$, and content-token top-1 accuracy across training. Lines show the mean over the 5 seeds; shaded bands the min-max envelope. The amber band marks the transition window $t \in [400, 1500]$.

per length class. The synthetic dataset is defined by $M = 32$ cyclic templates $\tau_m \in \mathcal{C}^K$ of length $K = 32$, drawn once at construction time and held fixed across training (Figure 1a). To generate a sequence, we sample a template m, start offset s, and line width W, then walk cyclically through τ_m from offset s. We maintain a character count cc on the current line and remaining characters $cr = W - cc$. At each position, the model predicts the next content token if its length fits, $\ell_{\text{next}} \leq cr$, and is
 otherwise; after a line break, cc resets to zero (Figure 1b). Thus the task decomposes into predicting the cyclic content stream and learning the linebreak rule. Each content token's character length is independently perturbed by ± 1 with probability 0.2, so the mapping from token identity to length becomes stochastic. Predicting
 therefore requires tracking ℓ over the current line rather than just reading ℓ_{next} off the next token's embedding.

Line widths are drawn from $W \in [20, 150]$. Twelve evenly spaced widths $\mathcal{W}_{\text{out}} \subset [20, 150]$ are held out from training and validation sets and appear only at test time, separating in-distribution performance from generalization to widths the model has never seen. We sample $|\mathcal{D}_{\text{train}}| = 100\text{k}$ training sequences (in-distribution widths only), $|\mathcal{D}_{\text{val}}| = 10\text{k}$ validation sequences (in-distribution only), and $|\mathcal{D}_{\text{test}}| = 10\text{k}$ test sequences mixing in-distribution and held-out widths. We use a fixed 2048 sequence subsample $\mathcal{D}_{\text{eval}} \subset \mathcal{D}_{\text{test}}$, drawn once for all subsequent analyses and reused across all training steps t.

Toy model. We train a small decoder-only transformer following the LLaMA 3 architecture, with two simplifications: standard multi-head attention (MHA) in place of grouped-query attention (GQA), and learned absolute positional embeddings (APEs) in place of RoPE. The embedding matrix $W_E \in \mathbb{R}^{|V| \times d}$ is weight-tied to the unembedding. The canonical configuration uses $L = 4$

86 layers, hidden dimension $d = 256$, $H = 16$ attention heads with $d_{\text{head}} = 16$, and MLP intermediate
87 dimension $4d$. [1] See Appendix A.1 for full details and model hyperparameters.

3   Phase transition in geometric structure

89 We train the toy model from Section 2 for 24,000 steps across 5 random seeds on the line-wrap dataset
90 and ask: *how does the geometry of the residual stream evolve as the model learns the linebreak task?*.

91 **Task-progress metrics.**   At every checkpoint t, we eval-
92 uate on the fixed subsample $\mathcal{D}_{\text{eval}}$ of $N = 2048$ se-
93 quences, held identical across t so that variation in any
94 reported metric reflects the model rather than the data. Let
95 $\mathcal{B} = \{i : y_i = \texttt{
}\}$ denote the break token positions
96 in $\mathcal{D}_{\text{eval}}$, $\mathcal{L}_i^{(t)} = -\log p_\theta^{(t)}(y_i \mid x_{<i})$ the per-position
97 cross-entropy loss, and $\hat{y}_i^{(t)} = \arg\max_v p_\theta^{(t)}(v \mid x_{<i})$ the
98 predicted next token. We track four task-progress metrics
99 at each checkpoint: *(i)* the eval loss $\bar{\mathcal{L}}^{(t)} = \mathbb{E}_i\left[\mathcal{L}_i^{(t)}\right]$ aver-
100 aged over all token positions in $\mathcal{D}_{\text{eval}}$; *(ii)* the $\texttt{
}$-NLL
101 $\bar{\mathcal{L}}_{\texttt{
}}^{(t)} = \mathbb{E}_{i \in \mathcal{B}}\left[\mathcal{L}_i^{(t)}\right]$ averaged only over break positions;

Figure 3: **Normalized ordinal purity** $\tilde{P}^{(t,l)}$ across training, by layer.

102 *(iii)* the $\texttt{
}$-token $F_1^{(t)}$ on $\mathcal{B}$; and *(iv)* content-token top-
103 1 accuracy on $\{i : y_i \in \mathcal{C}\}$. The accuracies are computed
104 from $\hat{y}^{(t)}$. We report the $\texttt{
}$-NLL alongside the average
105 eval loss since break tokens are rare (roughly 1 in 20 posi-
106 tions), so the average eval loss is dominated by content tokens and obscures the dynamics of the
107 break decision.

108 **Character count manifold.**   At every checkpoint t, we extract the residual stream at layer l,
109 $h_i^{(t,l)} \in \mathbb{R}^d$ at every token position in $\mathcal{D}_{\text{eval}}$ and group those positions by the character count of the
110 current line, $cc \in \{1, \ldots, W_{\max}\}$ with $W_{\max} = 150$. Averaging within each group,

$$\mu_c^{(t,l)} = \frac{1}{|\mathcal{I}_c|} \sum_{i \in \mathcal{I}_c} h_i^{(t,l)}, \qquad \mathcal{I}_c = \{i : cc_i = c\}, \tag{1}$$

111 collapses across-sequence variation (template, line width, position within the sequence) and leaves
112 only the count-conditional component of the representation. We primarily analyze layer 2 for the
113 manifold because the top three PCs of $\{\mu_c^{(T)}\}$ capture $\sim 95\%$ of variance at convergence (compared
114 to $\sim 68 - 85\%$ for other layers). To visualize how the manifold forms during training (Fig. 2a), we
115 fit a 3-component PCA on the mean-centered $\{\mu_c^{(T)}\}$ at the final checkpoint $T = 24000$ and project
116 every earlier checkpoint $\{\mu_c^{(t)}\}$ onto this fixed basis. A shared basis ensures motion across panels
117 reflects geometric change in the representation.

118 **Ordinal purity.**   We project every residual-stream activation $h_i^{(t,l)}$ onto the top $k = 6$ PCs of the
119 character count, cc manifold $\{\mu_c^{(t,l)}\}$, build a k nearest-neighbor graph in the projected space, and
120 measure, for each point, what fraction of its k neighbors have a character count within $\tau = 5$ of its
121 own:

$$P^{(t,l)} = 1 - \frac{1}{Nk} \sum_i \sum_{j \in \mathcal{N}_k(i)} \mathbf{1}\{|cc_i - cc_j| > \tau\}, \qquad \tilde{P}^{(t,l)} = \frac{P^{(t,l)} - P_0}{1 - P_0}, \tag{2}$$

122 where $N = |\mathcal{D}_{\text{eval}}|$, $\mathcal{N}_k(i)$ is the k-nearest-neighbor set of i in the projection, and $P_0 = P^{(0,l)}$ is the
123 same statistic on the untrained model. The normalization puts the random-init chance level at $\tilde{P} = 0$
124 and a perfectly count-organized neighborhood at $\tilde{P} = 1$. A high $\tilde{P}$ means that activations close in the
125 residual stream share nearly the same character count, so the count is encoded by *local* geometry —

---

[1]Token embeddings are mean-centered within each length class at initialization to remove a finite-sample bias in cc-conditioned averages at step 0. The trained model converges to the same solution; only step 0 geometry is affected.

Figure 4: **Causal effect of the count subspace. (a)** Restricted-pair logit shift $d_{\text{break}}^{(t,l)}$ (Eq. 4) from ablating the rank-3 count subspace at each layer, against a random control averaged over five draws (grey dashed). **(b)** At $l = 2$: Spearman correlation $\rho^{(t,2)}$ between target count c' and $\Delta M^{(t,2)}(c')$ for the count-subspace patch (orange, left axis) and the random control (grey dashed); effect size $\max_{c'} |\Delta M^{(t,2)}(c')|$ (purple dashed, right axis). Amber band marks the phase-transition window $t \in [400, 1500]$. **(c)** Joint trajectory at $l = 2$ of ordinal purity $\tilde{P}^{(t,2)}$ (Eq. 2) against the `
` token NLL increase. Faint lines are individual seeds; bold trajectory is the mean across 5 seeds, colored by training step (colorbar).

the defining property of a 1D ordinal manifold. A low $\tilde{P}$ means neighbors are mixed across counts: whatever structure the projected space contains is not organized by count.

Results. The two subtasks resolve on markedly different timescales (Figure 2b). Content top-1 accuracy reaches $\sim 70\%$ by step 200 and saturates above 99% by step 1500 – once the active template and offset are identified, the next content token is deterministic. The break decision is harder. `
`-$F_1^{(t)}$ stays near chance through step 200, then undergoes a sharp *phase transition* through the shaded window $t \in [400, 1500]$, climbing to $\sim 0.78$; the `
`-NLL mirrors it, dropping from ~ 3 to ~ 0.5 nats over the same window.

This behavioral phase transition is accompanied by a geometric one in layer 2. The class means $\{\mu_c^{(t,2)}\}$ collapse to a point at step 200, form a short ordinal arc by step 1k, and develop into the hooked 1D curve at convergence (Fig. 2a). Ordinal purity quantifies the same trajectory (Fig. 3): $\tilde{P}^{(t,2)}$ leaves chance inside the transition window and continues climbing to ~ 0.70 by step 24k, while adjacent layers reach at most ~ 0.32 (layer 3) or stay below 0.12 (layer 1 & 4).

The behavioral and geometric phase transitions are coupled at onset and decoupled at offset: `
`-F_1 and $\tilde{P}^{(t,2)}$ leave chance in the same window, but after step 1500 F_1 gains less than 0.1 over the remaining training steps while $\tilde{P}^{(t,2)}$ more than doubles. Behavioral performance saturates long before the geometric structure does.

4 Causal effect of the geometric structure

Count-subspace ablation. We test when the count manifold becomes causally necessary for the break decision by removing it from the residual stream and measuring the resulting change in the model's `
`-vs-content token prediction. At each checkpoint t and layer l, let $V_k^{(t,l)} \in \mathbb{R}^{d \times k}$ be the matrix whose columns are the top $k = 3$ principal components of the mean-centered class means $\{\mu_c^{(t,l)}\}$ from Eq. 1; its columns form an orthonormal basis for the *count subspace* at (t, l). We ablate this subspace at every position by applying the orthogonal projection

$$\tilde{h}_i^{(t,l)} = h_i^{(t,l)} - V_k^{(t,l)} V_k^{(t,l)\top} h_i^{(t,l)}, \tag{3}$$

and resume the forward pass on the ablated stream to obtain logits $u_i' \in \mathbb{R}^{|\mathcal{V}|}$. Because `
` tokens occupy only $\sim 5\%$ of positions, the full cross-entropy and KL divergence between baseline and ablated distributions are dominated by content tokens and obscure the break decision. Following

Figure 5: **Per-interval rank concentration of the attention weight updates.** Participation ratio $\overline{\mathrm{PR}}^{(t,l)}$ (Eq. 9) of the per-interval update ΔW at each layer, computed separately for the **(a)** QK and **(b)** OV circuits. Dashed line marks the rank cap $2\,d_{\mathrm{head}} = 32$; dotted line marks the per-head rank $d_{\mathrm{head}} = 16$. Amber band marks the phase-transition window $t \in [400, 1500]$.

Nielsen et al. [2026], we measure the intervention through the *restricted-pair logit shift*

$$d_{\mathrm{break}}^{(t,l)} = \sqrt{\mathbb{E}_{i \in \mathcal{D}_{\mathrm{eval}}}\left[\frac{1}{|\mathcal{C}|}\sum_{v \in \mathcal{C}}\left((u_{i,\texttt{
}} - u_{i,v}) - (u'_{i,\texttt{
}} - u'_{i,v})\right)^2\right]}, \qquad (4)$$

the root-mean-square change in the `
`-vs-content logprobs across all eval positions and content tokens. By construction, d_{break} is invariant to additive shifts of the logit vector and so isolates the break decision from drift in the overall logit norm. We repeat the ablation with a random rank-k orthonormal basis, averaged over five draws (grey dashed curve in Fig. 4a) as a random control.

Character count patching. To probe for directional control, we steer the count component to a target count c' and measure the change in break preference. For a position with true count c_i at layer l, we replace its count-subspace component with that of a target class mean,

$$h_i^{(t,l)}(c') = h_i^{(t,l)} + V_k^{(t,l)}V_k^{(t,l)\top}\left(\mu_{c'}^{(t,l)} - \mu_{c_i}^{(t,l)}\right), \qquad (5)$$

sweep c' over twelve evenly-spaced values in $\{1, \ldots, W_{\mathrm{max}}\}$, and resume the forward pass. Let $M(h) = u_{\texttt{
}}(h) - \frac{1}{|\mathcal{C}|}\sum_{v \in \mathcal{C}} u_v(h)$ be the `
`-vs-content logit difference as a functional of the residual stream, and let

$$\Delta M^{(t,l)}(c') = \mathbb{E}_{i \in \mathcal{D}_{\mathrm{eval}}}\left[M\big(h_i^{(t,l)}(c')\big) - M\big(h_i^{(t,l)}\big)\right] \qquad (6)$$

be the average logit shift induced by patching to c'. We summarize the intervention with two complementary scalars. The Spearman rank correlation $\rho^{(t,l)} = \mathrm{Spearman}\big(c', \Delta M^{(t,l)}(c')\big)$ reports the *direction* of control — $\rho^{(t,l)} \to +1$ means patching to larger c' monotonically raises break preference. The effect size $\max_{c'}|\Delta M^{(t,l)}(c')|$ reports its *magnitude*. We compare against a random rank-k subspace as before.

Joint trajectory of the geometry & ablation effect. We trace the joint trajectory of the character count cc manifold and its causal effect at layer $l = 2$ across training in Figure 4c. We track ordinal purity $\tilde{P}^{(t,2)}$ (Eq. 2) paired with the `
`-token negative log likelihood increase

$$\Delta \mathrm{BR}\,\mathrm{NLL}^{(t,l)} = \mathbb{E}_{i:\,y_i=\texttt{
}}[-\log p'(y_i \mid x_{<i}) + \log p(y_i \mid x_{<i})], \qquad (7)$$

induced by the rank-3 count-subspace ablation of Eq. 3.

Results. Fig. 4 probes the causal influence of the representation geometry in three ways. **(i)** The character count manifold at $l = 2$ becomes causally necessary for the break decision precisely during

Figure 6: **Hessian eigenvalues across training.** Top: **(a)** three largest $\{\lambda_k^+(t)\}_{k=1,2,3}$ and **(b)** three smallest $\{\lambda_k^-(t)\}_{k=1,2,3}$ eigenvalues of the full-parameter loss Hessian $H_t = \nabla_\theta^2 \mathcal{L}_B(\theta_t)$, estimated by Lanczos iteration on a fixed validation batch B. Bottom: training loss $\mathcal{L}_B(\theta_t)$ on the same step axis. Amber band marks the phase-transition window $t \in [400, 1500]$; dashed vertical line marks the maximum-curvature checkpoint $t \approx 500$.

the phase-transition window $t \in [400, 1500]$: $d_{\text{break}}^{(t,2)}$ rises from 1.1 at step 100 to 5.2 at step 1500, exceeding the random rank-3 control by $\sim 5\times$, and continues to grow for the rest of the training. [2] **(ii)** Before the phase transition, the count subspace is *anti-causal*: $\rho^{(t,2)} = -1.0$ from step 50 through step ~ 400 — patching to a larger c' *decreases* `
` token prediction. The manifold begins to form around step 1k (Fig. 2a), and $\rho^{(t,2)}$ rises in lockstep — flipping from -1 to $+1$ inside the transition window and stabilising by step 2k. The random control hovers near zero throughout. The geometric structure and its directional causal influence develops over the same phase transition window. **(iii)** The joint trajectory has two phases. Through step 1500, $\Delta\text{BR NLL}^{(t,2)}$ climbs to ~ 4 nats while $\tilde{P}^{(t,2)}$ improves from 0.13 to 0.31; after the phase transition, the causal effect saturates while ordinal purity continues climbing to ~ 0.75.

5   Phase transition in the weight space

We now ask what the linebreak phase transition looks like in weight space. The phase transition in Sections 3–4 is the moment a new computational capability (the break decision) and the geometric structure that implements it (the count manifold) come online together. Such discrete capability onsets are the canonical phenomenology of a *saddle escape* [Rhee et al., 2026]. Such an escape leaves two distinctive signatures: *(i)* the parameter update $\Delta\theta$ concentrates in a few singular directions and *(ii)* the Hessian of the loss transiently carries a negative-curvature direction that recovers once the escape completes. We track both across training and ask whether the phase-transition window $t \in [400, 1500]$ aligns with a saddle escape.

Attention weight updates.   We test signature *(i)* on the attention weights, the parameters that route information across positions and are the natural candidates for a circuit-forming saddle escape. For each layer l and head h, we form the effective QK and OV circuits at checkpoint t,

$$W_{\text{QK}}^{(t,l,h)} = W_Q^{(t,l,h)\top} W_K^{(t,l,h)}, \qquad W_{\text{OV}}^{(t,l,h)} = W_O^{(t,l,h)} W_V^{(t,l,h)}, \tag{8}$$

and define the per-interval update between consecutive checkpoints, $\Delta W^{(t,l,h)} = W^{(t+1,l,h)} - W^{(t,l,h)}$, separately for QK and OV. We summarise the rank profile of each update via its singular-

---

[2]Layer 1 carries an even larger d_{break} which can be due to cc in superposition — a linear probe recovers cc at $l = 1$ with $R^2 \approx 0.4$, against $R^2 \approx 0.94$ at $l = 2$ — so the rank-3 subspace ablated at $l = 1$ entangles count with other features. The 1D manifold resolves only at $l = 2$, where we anchor the causal analysis.

Figure 7: **Task-progress trajectories across initialization scales. (a)** eval loss $\bar{\mathcal{L}}^{(t)}$, **(b)** `
`-negative log likelihood $\bar{\mathcal{L}}_{\text{
}}^{(t)}$, and **(c)** `
`-$F_1^{(t)}$ across training. Color encodes α: warm tones for large α, cool tones for small α.

value participation ratio,

$$\text{PR}\big(\Delta W^{(t,l,h)}\big) \;=\; \frac{\big(\sum_j \sigma_j\big)^2}{\sum_j \sigma_j^2}, \tag{9}$$

where $\{\sigma_j\}$ are the singular values of $\Delta W^{(t,l,h)}$. PR is a soft rank: $\text{PR} = 1$ for an exactly rank-1 update, $\text{PR} = r$ for a uniform rank-r spectrum. Each $W_{\text{QK}}, W_{\text{OV}} \in \mathbb{R}^{d \times d}$ has rank at most d_{head} (dashed reference line in Figure 5). Within each layer we aggregate across heads using Frobenius-norm weights,

$$\overline{\text{PR}}^{(t,l)} \;=\; \frac{\sum_h \|\Delta W^{(t,l,h)}\|_F \cdot \text{PR}\big(\Delta W^{(t,l,h)}\big)}{\sum_h \|\Delta W^{(t,l,h)}\|_F}, \tag{10}$$

so heads with negligible updates do not dominate the layer summary. A saddle escape predicts $\overline{\text{PR}}^{(t,l)}$ to dip sharply inside the transition window $t \in [400, 1500]$ — the update concentrates into the unstable modes — and to recover toward its full-spectrum baseline once the escape completes.

Loss curvature. We test signature *(ii)* on the full-parameter loss Hessian. Let θ_t denote the parameters at checkpoint t and

$$\mathcal{L}_B(\theta) \;=\; \frac{1}{|B|} \sum_{(x,y) \in B} \text{CE}(f_\theta(x), y) \tag{11}$$

the next-token cross-entropy loss on a fixed validation batch $B = 1024$ sequences. We form the loss Hessian $H_t = \nabla_\theta^2 \mathcal{L}_B(\theta_t)$ and estimate its top and bottom three eigenvalues via Hessian-vector products and Lanczos iteration:

$$\lambda_1^+(t) \geq \lambda_2^+(t) \geq \lambda_3^+(t) \quad \text{from } H_t, \qquad \lambda_1^-(t) \leq \lambda_2^-(t) \leq \lambda_3^-(t) \quad \text{from } -H_t. \tag{12}$$

Wherever $\lambda_1^-(t) < 0$, the parameters lie at a saddle with a locally unstable descent direction. A saddle escape predicts $\lambda_1^-(t)$ to plunge below zero entering the transition window and recover to $\lambda_1^-(t) \approx 0$ once the escape completes; outside the window, all six eigenvalues should remain non-negative, locally convex along the unstable directions.

Results. **(i)** The QK participation ratio $\overline{\text{PR}}_{\text{QK}}^{(t,2)}$ collapses from ≈ 25 at step 50 to ≈ 4 at step 500 and recovers only to ≈ 6 post-transition (Fig. 5a) — the QK update at $l = 2$ concentrates into roughly four singular modes during the escape, against a rank cap of $2\,d_{\text{head}} = 32$. Layers 3 and 4 show the same dip at smaller amplitude (minimum ≈ 10); Layer 1's QK updates stay near their starting rank throughout, consistent with the count being read off in superposition. The OV updates show no comparable dip (Figure 5b): all four layers drift smoothly toward $\overline{\text{PR}} \approx d_{\text{head}}$ over the full training run. The saddle escape concentrates in QK (where each head attends), not OV (what it writes). **(ii)** The smallest Hessian eigenvalue $\lambda_1^-(t)$ plunges from ≈ -5 at step 50 to ≈ -45 at step 500 — the deepest negative-curvature direction in the trajectory — and recovers toward zero by step 24k (Fig. 6b). The top eigenvalue $\lambda_1^+(t)$ spikes from ≈ 250 to ≈ 2000 at the same checkpoint (Fig. 6a),

a transient sharpening along the unstable direction. Smaller post-transition dips in λ_1^- around step ~ 4000 are consistent with finer secondary escapes, but the dominant event coincides exactly with the transition window. At the start of the phase transition, the QK weights updates at the manifold layer concentrate to near rank-4 and the loss Hessian opens a deep transient negative direction. The linebreak *phase transition* exhibits the dynamical fingerprint of a *saddle escape*.

6 Weight initialization scale & the phase transition

If the linebreak phase transition is a saddle escape, its timing should be controlled by the weight initialization scale: deep linear network theory predicts a logarithmic dependence, $\tau \sim \log(1/\alpha^2)$ [Rhee et al., 2026]. We sweep weight initialization scale α across four orders of magnitude in order to test this.

Figure 8: **QK and OV update participation ratio across initialization scales at $l = 2$.** $\overline{\mathrm{PR}}^{(t,2)}$ (Eq. 9) of the per-interval update ΔW at the character count manifold layer, computed separately for the **(a)** QK and **(b)** OV circuits. Dashed line marks the rank cap $2\,d_{\mathrm{head}} = 32$; dotted line marks the per-head rank $d_{\mathrm{head}} = 16$. Amber band marks the canonical-α phase-transition window $t \in [400, 1500]$.

Sweep. We train a family of otherwise identical models indexed by $\alpha \in \{10^{-4}, 10^{-3}, 10^{-2}, 0.05, 0.1, 0.5, 1\}$. Every linear and embedding matrix — including the tied embedding/unembedding — is initialized as

$$W_0 \sim \mathcal{N}\big(0, (\alpha\sigma_0)^2\big) \qquad (13)$$

where σ_0 is the default initialization standard deviation. All variants share architecture, dataset, optimizer, learning-rate schedule, checkpoint schedule, and minibatch order — they are trained lockstep in a single process, three seeds per α — so only α changes across runs. We track the same task and weight-space metrics defined in Sections 3–5: the `
` negative log likelihood and `
`-F_1 trajectories (Figure 7) and the per-interval QK and OV participation ratios at $l = 2$ (Figure 8).

Results. The phase transition shifts monotonically later as α decreases. The transition window of the canonical $\alpha = 1$ run sits at $t \in [400, 1500]$; at $\alpha = 0.05$ it shifts to roughly $[1000, 2000]$, and at $\alpha = 10^{-3}$ to roughly $[1500, 2700]$. The QK participation ratio also changes shape with α. At large α ($\{0.5, 1\}$), $\overline{\mathrm{PR}}_{\mathrm{QK}}^{(t,2)}$ starts near 25 and dips sharply to ≈ 4 inside the transition window. As α shrinks, the starting value drops — ≈ 10 at $\alpha = 0.1$, ≈ 1 at $\alpha \leq 0.01$ — and the dip-and-recover collapses into a slow rise from below. Large α produces the canonical dip-and-recover signature of saddle escape. Small α initializes at the saddle itself, where ΔW_{QK} is concentrated from step 0 and the "escape" registers as a slow rise toward higher rank.

Across four orders of magnitude in α, every run reaches the same converged `
`-F_1; only the step at which it gets there changes. α *shifts the timing of the phase transition without changing whether the capability is acquired or not.*

7 Conclusion

We trace the formation of a representational manifold in a small transformer, end to end: the count subspace forms during a sharp phase transition, acquires its causal role over the same window, and leaves a saddle-escape fingerprint in the attention weights and the loss Hessian. Several open questions remain. First, how does this picture scale with model depth and width — do larger transformers show the same coupling between manifold formation and saddle escape, or does the increased representational capacity smooth the transition into a continuous process? Second, does the saddle escape correspond to the formation of a *circuit*, and if so, do other interpretable circuits form through analogous escapes? Third, how does this depend on task complexity — does a richer task induce a longer staircase of saddle escapes, each constructing a different representational object?

References

Boaz Barak, Benjamin L. Edelman, Surbhi Goel, Sham Kakade, Eran Malach, and Cyril Zhang. Hidden progress in deep learning: Sgd learns parities near the computational limit, 2023. URL https://arxiv.org/abs/2207.08799.

Wes Gurnee, Emmanuel Ameisen, Isaac Kauvar, Julius Tarng, Adam Pearce, Chris Olah, and Joshua Batson. When models manipulate manifolds: The geometry of a counting task. *Transformer Circuits Thread*, 2025. URL https://transformer-circuits.pub/2025/linebreaks/index.html.

Arthur Jacot, François Ged, Berfin Şimşek, Clément Hongler, and Franck Gabriel. Saddle-to-saddle dynamics in deep linear networks: Small initialization training, symmetry, and sparsity, 2022. URL https://arxiv.org/abs/2106.15933.

Subhash Kantamneni and Max Tegmark. Language models use trigonometry to do addition, 2025. URL https://arxiv.org/abs/2502.00873.

Dhruva Karkada, Daniel J. Korchinski, Andres Nava, Matthieu Wyart, and Yasaman Bahri. Symmetry in language statistics shapes the geometry of model representations, 2026. URL https://arxiv.org/abs/2602.15029.

Daniel J. Korchinski, Dhruva Karkada, Yasaman Bahri, and Matthieu Wyart. On the emergence of linear analogies in word embeddings, 2025. URL https://arxiv.org/abs/2505.18651.

Ziming Liu, Ouail Kitouni, Niklas Nolte, Eric J. Michaud, Max Tegmark, and Mike Williams. Towards understanding grokking: An effective theory of representation learning, 2022. URL https://arxiv.org/abs/2205.10343.

Alexander Modell, Patrick Rubin-Delanchy, and Nick Whiteley. The origins of representation manifolds in large language models, 2025. URL https://arxiv.org/abs/2505.18235.

Beatrix M. G. Nielsen, Emanuele Marconato, Luigi Gresele, Andrea Dittadi, and Simon Buchholz. Logit distance bounds representational similarity, 2026. URL https://arxiv.org/abs/2602.15438.

Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Scott Johnston, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. In-context learning and induction heads, 2022. URL https://arxiv.org/abs/2209.11895.

Core Francisco Park, Maya Okawa, Andrew Lee, Hidenori Tanaka, and Ekdeep Singh Lubana. Emergence of hidden capabilities: Exploring learning dynamics in concept space, 2024. URL https://arxiv.org/abs/2406.19370.

Mark Rhee, Dhruva Karkada, and Jamie Simon. Deep linear networks are a surprisingly useful toy model of weight-space dynamics. *Learning Mechanics*, 2026. URL https://learningmechanics.pub/deep-linear-nets.

Andrew M. Saxe, James L. McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks, 2014. URL https://arxiv.org/abs/1312.6120.

A Appendix

A.1 Toy model hyperparameters

The canonical $d{=}256$ configuration used throughout the main text is summarized in Table 1. All training runs use AdamW with a linear warmup followed by a cosine decay to $\eta_{\min}$.

Architecture	
Model family	Llama-3 style decoder-only transformer
Attention	Multi-head (no GQA)
Positional embeddings	Learned absolute (max_seq_len $= 1100$)
Embedding/unembedding	Weight-tied
Activation	SiLU
Normalization	RMSNorm (pre-norm)
Layers L	4
Hidden dimension d	256
Heads H	16
Head dimension d_{head}	16
MLP dimension d_{mlp}	1024 $(= 4d)$
Vocabulary size $|\mathcal{V}|$	100 (96 content $+$ 4 special)
Total parameters	$\sim$3.5M
Initialization	
Linear, embedding	$\mathcal{N}(0, \sigma_0^2)$ with $\sigma_0 = 0.02$
Length-class centering	Yes (Appendix **??**)
Training	
Optimizer	AdamW ($\beta_1{=}0.9$, $\beta_2{=}0.95$)
Learning rate η	3×10^{-4}
Min learning rate $\eta_{\min}$	3×10^{-5}
LR schedule	Linear warmup $\to$ cosine decay
Warmup steps	200
Weight decay	0.01
Gradient clipping	1.0
Batch size	64
Total steps	24,000
Precision	bfloat16
Seeds (canonical experiments)	5
Seeds (initialization-scale sweep)	3 per α
Data	
Templates M	32
Template length K	32
Line width range	$W \in [20, 150]$
Length jitter probability	0.2
Train / val / test sequences	100k / 10k / 10k
$|\mathcal{D}_{\text{eval}}|$	2048

Table 1: Hyperparameters for the canonical $d{=}256$ model.