ROBUST CONSTRAINED REINFORCEMENT LEARNING FOR CONTINUOUS CONTROL

ABSTRACT

Many real-world physical control systems are required to satisfy constraints upon deployment. Furthermore, real-world systems are often subject to effects such as non-stationarity, wear-and-tear, uncalibrated sensors and so on. Such effects effectively perturb the system dynamics and can cause a policy trained successfully in one domain to perform poorly when deployed to a perturbed version of the same domain. This can affect a policy's ability to maximize future rewards as well as the extent to which it satisfies constraints. We refer to this as constrained model misspecification. We present an algorithm with theoretical guarantees that mitigates this form of misspecification, and showcase its performance in multiple Mujoco tasks from the Real World Reinforcement Learning (RWRL) suite.

1 INTRODUCTION

Reinforcement Learning (RL) has had a number of recent successes in various application domains which include computer games (Silver et al., 2017; Mnih et al., 2015; Tessler et al., 2017) and robotics (Abdolmaleki et al., 2018a). As RL and deep learning continue to scale, an increasing number of real-world applications may become viable candidates to take advantage of this technology. However, the application of RL to real-world systems is often associated with a number of challenges (Dulac-Arnold et al., 2019; Dulac-Arnold et al., 2020). We will focus on the following two in this paper:

Challenge 1 - Constraint satisfaction: One such challenge is that many real-world systems have constraints that need to be satisfied upon deployment (i.e., hard constraints); or at least the number of constraint violations as defined by the system need to be reduced as much as possible (i.e., soft-constraints). This is prevalent in applications ranging from physical control systems such as autonomous driving and robotics to user facing applications such as recommender systems.

Challenge 2 - Model Misspecification (MM): In addition, many of these systems suffer from another challenge: model misspecification. We refer to the situation in which an agent is trained in one environment but deployed in a different, perturbed version of the environment as an instance of *model misspecification*. This may occur in many different applications and is well-motivated in the literature (Mankowitz et al., 2019; Derman et al., 2018; Derman & Mannor, 2019; Mankowitz et al., 2018; Iyengar, 2005; Tamar et al., 2014).

There has been much work on constrained optimization in the literature (Altman, 1999; Tessler et al., 2018; Efroni et al., 2020; Achiam et al., 2017; Bohez et al., 2019). However, to our knowledge, the effect of model misspecification on an agent's ability to satisfy constraints at test time has not yet been investigated.

Constrained Model Misspecification (CMM): We consider the scenario in which an agent is required to satisfy constraints at test time but is deployed in an environment that is different from its training environment (i.e., a perturbed version of the training environment). Deployment in a perturbed version of the environment may affect the return achieved by the agent as well as its ability to satisfy the constraints. We refer to this scenario as *constrained model misspecification*.

This problem is prevalent in many real-world applications where constraints need to be satisfied but the environment is subject to state perturbations effects such as wear-and-tear, partial observability etc., the exact nature of which may be unknown at training time. Since such perturbations can

significantly impact the agent's ability to satisfy the required constraints it is insufficient to simply ensure that constraints are satisfied in the unperturbed version of the environment. Instead, the presence of unknown environment variations needs to be factored into the training process. One area where such considerations are of particular practical relevance is sim2real transfer where the unknown sim2real gap can make it hard to ensure that constraints will be satisfied on the real system (Andrychowicz et al., 2018; Peng et al., 2018; Wulfmeier et al., 2017; Rastogi et al., 2018; Christiano et al., 2016). Of course, one could address this issue by limiting the capabilities of the system being controlled in order to ensure that constraints are never violated, for instance by limiting the amount of current in an electric motor. Our hope is that our methods can outperform these more blunt techniques, while still ensuring constraint satisfaction in the deployment domain.

Main Contributions: In this paper, we aim to bridge the two worlds of model misspecification and constraint satisfaction. We present an RL objective that enables us to optimize a policy that aims to be robust to CMM. Our contributions are as follows:

- Introducing the Robust Return Robust Constraint (R3C) and Robust Constraint (RC) RL objectives that aim to mitigate CMM as defined above. This includes the definition of a Robust Constrained Markov Decision Process (RC-MDP).

- Derive corresponding R3C and RC value functions and Bellman operators. Provide theoretical results showing that these Bellman operators are contractions. These are implemented in the policy evaluation step of actor-critic R3C algorithms.

- Empirically demonstrate the superior performance of our algorithms, compared to various baselines, on two state-of-the-art continous control RL algorithms with respect to mitigating CMM. This is shown consistently across 6 different Mujoco tasks from the Real-World RL (RWRL) suite[1].

2 BACKGROUND

2.1 MARKOV DECISION PROCESSES

A **Robust Markov Decision Process (R-MDP)** is defined as a tuple $\langle S, A, R, \gamma, \mathcal{P} \rangle$ where S is the state space, A the action space, $R : S \times A \to \mathbb{R}$ is a bounded reward function and $\gamma \in [0, 1]$ is the discount factor; $\mathcal{P}(s, a) \subseteq \mathcal{M}(S)$ is an uncertainty set where $\mathcal{M}(S)$ is the set of probability measures over next states $s' \in S$. This is interpreted as an agent selecting a state and action pair, and the next state s' is determined by a conditional measure $p(s'|s, a) \in \mathcal{P}(s, a)$ (Iyengar, 2005). We want the agent to be robust with respect to this uncertainty set. A robust policy optimizes for the robust (worst-case) expected return objective: $J_{\mathrm{R}}(\pi) = \inf_{p \in \mathcal{P}} \mathbb{E}^{p,\pi}[\sum_{t=0}^{\infty} \gamma^t r_t]$. Both the robust Bellman operator $T_{\mathrm{R}}^{\pi} : \mathcal{R}^{|S|} \to \mathcal{R}^{|S|}$ for a fixed policy and the optimal robust Bellman operator $T_{\mathrm{R}} v(s) = \max_{\pi} T_{\mathrm{R}}^{\pi} v(s)$ have previously been shown to be contractions (Iyengar, 2005). A rectangularity assumption on the uncertainty set (Iyengar, 2005) ensures that "nature" can choose a worst-case transition function independently for every state s and action a. This means that during a trajectory, at each timestep, nature can choose any transition model from the uncertainty set to reduce the performance of the agent.

A **Constrained Markov Decision Process (CMDP)** is an extension to an MDP and consists of the tuple $\langle S, A, P, R, C, \gamma \rangle$ where S, A, R and γ are defined as in the MDP above and $C : S \times A \to \mathbb{R}^K$ is a K dimensional vector representing immediate costs relating to K constraints. The solution to a CMDP is a policy $\pi : S \to \Delta_A$ which is a mapping from states to a probability distribution over actions (or a single action if the policy is deterministic). This policy aims to maximize the expected return $J_R^{\pi} = \mathbb{E}[\sum_{t=0}^{\infty} \gamma^t r_t]$ and satisfy the constraint $J_C^{\pi} = \mathbb{E}[\sum_{t=0}^{\infty} \gamma^t c_t] \leq \beta$ with respect to a pre-defined constraint threshold β. A number of approaches Tessler et al. (2018); Bohez et al. (2019) optimize the unconstrained lagrange relaxation of this objective $\max_{\lambda \geq 0} \min_{\theta} J_R^{\pi} - \lambda(J_C^{\pi} - \beta)$ by optimizing the lagrange multiplier λ and the policy parameters θ using alternating optimization.

---

[1]https://github.com/google-research/realworldrl_suite

2.2 Continuous Control RL Algorithms

We address the CMM problem by modifying two well-known continuous control algorithms by having them optimize the RC and R3C objectives.

The first algorithm is **Maximum A-Posteriori Policy Optimization (MPO)**. This is a continuous control RL algorithm that performs policy iteration using an RL form of expectation maximization (Abdolmaleki et al., 2018a;b). We use the distributional-critic version in Abdolmaleki et al. (2020), which we refer to as DMPO.

The second algorithm is **Distributed Distributional Deterministic Policy Gradient** (D4PG), which is a state-of-the-art actor-critic continuous control RL algorithm with a deterministic policy (Barth-Maron et al., 2018). It is an incremental improvement to DDPG (Lillicrap et al., 2015) with a distributional critic that is learned similarly to distributional MPO.

2.3 Robust Constrained (RC) Optimization Objective

We begin by defining a Robust Constrained MDP (RC-MDP). This combines an R-MDP and C-MDP to yield the tuple $\langle S, A, R, C, \gamma, \mathcal{P} \rangle$ where all of the variables in the tuple are defined in Section 2. We next define two optimization objectives that optimize the RC-MDP. The first variant attempts to learn a policy that is robust with respect to the return as well as constraint satisfaction - Robust Return Robust Constrained (R3C) objective. The second variant is only robust with respect to constraint satisfaction - Robust Constrained (RC) objective.

2.3.1 Robust Return Robust Constraint (R3C) Objective

The R3C objective is defined as:

$$\max_{\pi \in \Pi} \inf_{p \in P} \mathbb{E}^{p,\pi} \left[\sum_t \gamma^t r(s_t, a_t) \right] \text{ s.t. } \sup_{p' \in \mathcal{P}} \mathbb{E}^{p',\pi} \left[\sum_t \gamma^t c(s_t, a_t) \right] < \beta \tag{1}$$

Note, a couple of interesting properties about this objective: (1) it focuses on being robust with respect to the return for a pre-defined set of perturbations; (2) the objective also attempts to be robust with respect to the worst case constraint value for the perturbation set. The unconstrained lagrangian form of equation 1 is used to define an R3C value function.

Definition 1 (R3C Value Function). For a fixed λ, and using the above-mentioned rectangularity assumption (Iyengar, 2005), the robust return robust constrained value function $\mathbf{V} : S \to \mathbb{R}$ can be defined as:

$$\mathbf{V}(s) = \inf_{p \in P} \mathbb{E}^{p,\pi} \left[r(s, \pi(s)) + \gamma V(s') \right] - \lambda \left[\sup_{p' \in P} \mathbb{E}^{p',\pi} \left[c(s, \pi(s)) + \gamma V_C(s') \right] - \beta \right]$$

The β term offsets the value function, which has no effect on any policy improvement step[2]. As a result, we can drop the dependency on β and define the value function as:

$$\mathbf{V}(s) = \inf_{p \in P} \mathbb{E}^{p,\pi} \left[r(s, \pi(s)) + \gamma V(s') \right] - \lambda \left[\sup_{p' \in P} \mathbb{E}^{p',\pi} \left[c(s, \pi(s)) + \gamma V_C(s') \right] \right]$$
$$= \mathbf{r}(s, \pi(s)) + \gamma \mathbf{V}(s')$$

where $\mathbf{r}(s, \pi(s)) = r(s, \pi(s)) - \lambda c(s, \pi(s))$. The derivation can be found in the Appendix, A.2.

The next step is to define the R3C Bellman operator and show that this operator is a contraction. This is presented in Definition 2 and Theorem 1 respectively. The full derivation can be found in the Appendix, Section A.4.

---

[2] The β term is only used in the lagrange update in Equation 3

Definition 2 (R3C Bellman operator). The R3C Bellman operator is defined as: $T_{R3C}^\pi \mathbf{V}(s) = \mathbf{r}(s, \pi(s)) + \gamma \mathbf{V}(s')$.

Note that the R3C Bellman operator can be defined in terms of two separate Bellman operators: $T_{R3C}^\pi \mathbf{V}(s) = T_{inf}^\pi V(s) - \lambda T_{sup}^\pi V_C(s)$ where $T_{inf}^\pi : \mathbb{R}^d \to \mathbb{R}^d$ is the robust Bellman operator (Iyengar, 2005) and $T_{sup}^\pi : \mathbb{R}^d \to \mathbb{R}^d$ is defined as the sup Bellman operator. It has been previously shown that T_{inf}^π is a contraction with respect to the max norm (Tamar et al., 2014) and therefore converges to a fixed point. We also show that T_{sup}^π is a contraction operator in Appendix, A.3. These Bellman operators individually ensure that the value function $V(s)$ and the constraint value function $V_C(s)$ converge to a fixed point. However, it still needs to be shown that the combination of the two operators - the R3C Bellman operator - is also a contraction (Theorem 1).

Theorem 1 (R3C Bellman operator contraction). *For two arbitrary R3C value functions $\mathbf{U} : S \to \mathbb{R}^d$ and $\mathbf{V} : S \to \mathbb{R}^d$, we can show that the R3C Bellman operator $\mathcal{T}_{R3C}^\pi : \mathbb{R}^d \to \mathbb{R}^d$ is a contraction. That is $\|\mathcal{T}_{R3C}^\pi \mathbf{U}(s) - \mathcal{T}_{R3C}^\pi \mathbf{V}(s)\|_\infty \leq \gamma \|\mathbf{U} - \mathbf{V}\|_\infty$.*

As a result of the above theorem, we know that the R3C Bellman operator converges to a fixed point and that we can apply this Bellman operator in value iteration or policy iteration algorithms in the policy evaluation step. We next define the RC objective.

2.3.2 ROBUST CONSTRAINED (RC) OBJECTIVE

The RC objective focuses on being robust with respect to constraint satisfaction and is defined as:

$$\max_{\pi \in \Pi} \mathbb{E}^\pi \left[\sum_t \gamma^t r(s_t, a_t) \right] \text{ s.t. } \sup_{p \in \mathcal{P}} \mathbb{E}^{p,\pi} \left[\sum \gamma^t c(s_t, a_t) \right] < \beta \tag{2}$$

This objective differs from R3C in that it only focuses on being robust with respect to constraint satisfaction. This is especially useful in domains where perturbations are expected to have a significantly larger effect on constraint satisfaction performance compared to return performance. We next define the corresponding value function, Bellman operator and show that this operator is also a contraction.

Definition 3 (RC Value Function). For a fixed λ, and using the above-mentioned rectangularity assumption (Iyengar, 2005), the robust constrained value function $\mathbf{V} : S \to \mathbb{R}$ can be defined as:

$$\mathbf{V}(s) = \mathbb{E}^\pi \left[r(s, \pi(s)) + \gamma V(s') \right] - \lambda \left[\sup_{p \in P} \mathbb{E}^{p,\pi} \left[c(s, \pi(s)) + \gamma V_C(s') \right] \right]$$

The RC Bellman operator is defined as below.

Definition 4 (Robust Constrained Bellman operator). The Robust Constrained (RC) Bellman operator is defined as: $T_{RC}^\pi \mathbf{V}(s) = \mathbf{r}(s, \pi(s)) + \gamma \mathbf{V}(s')$.

Using similar arguments as before, it can be shown that the RC Bellman operator is a contraction. The full derivation is in the Appendix, A.5. In fact, many different combinations of sup and inf objectives yield Bellman operators that are contraction mappings. In addition, it is possible to take the mean with respect to the uncertainty set yielding a soft-robust update (Derman et al., 2018; Mankowitz et al., 2019). We do not derive all of the possible combinations of objectives in this paper, but note that the framework provides the flexibility to incorporate each of these objectives.

Theorem 2 (RC Bellman operator contraction). *For two arbitrary value functions $\mathbf{U} : S \to \mathbb{R}^d$ and $\mathbf{V} : S \to \mathbb{R}^d$, we can show that the robust constrained Bellman operator $\mathcal{T}_{RC}^\pi : \mathbb{R}^d \to \mathbb{R}^d$ is a contraction. That is $\|\mathcal{T}_{RC}^\pi \mathbf{U}(s) - \mathcal{T}_{RC}^\pi \mathbf{V}(s)\|_\infty \leq \gamma \|\mathbf{U} - \mathbf{V}\|_\infty$.*

2.4 LAGRANGE UPDATE

For both objectives, we need to learn a policy that maximizes the return. This involves performing alternating optimization on the unconstrained Lagrange relaxation of the objective. The optimization procedure alternates between updating the actor/critic parameters and the Lagrange multiplier. For both objectives we have the same gradient update for the Lagrange multiplier:

Theorem 3 (Lagrange derivative). *The gradient of the Lagrange multiplier $\lambda \geq 0$ is:*

$$\frac{\partial}{\partial \lambda} f = -\left(\sup_{p \in \mathcal{P}} \mathbb{E}^{p,\pi} \left[\sum \gamma c(s_t, a_t) \right] - \beta \right) \tag{3}$$

where f is the R3C or RC objective we wish to optimize.

This is an intuitive update in that the Lagrange multiplier is updated using the worst-case constraint violation estimate. If the worst-case estimate is larger than β, then the lagrange multiplier is increased to add more weight to constraint satisfaction and vice versa. This would arguably lead to an overall more conservative policy which would be consistent with previous work (Mankowitz et al., 2019).

3   ROBUST CONSTRAINED POLICY EVALUATION

We now describe how the R3C Bellman operator can be used to perform policy evaluation. This policy evaluation step can be incorporated into any actor-critic algorithm. Instead of optimizing the regular distributional loss (e.g. the C51 loss in Bellemare et al. (2017)), as regular D4PG and DMPO do, we optimize the worst-case distributional loss, which is the distance:

$$d\left(\mathbf{r_t} + \gamma \mathbf{V}_{\hat{\theta}}^{\pi_k}(s_{t+1}), \mathbf{V}_{\theta}^{\pi_k}(s_t) \right) ,$$

where $\mathbf{V}_{\theta}^{\pi_k}(s_t) = \inf_{p \in \mathcal{P}(s_t, \pi(s_t))} \left[V_{\theta}^{\pi_k}(s_{t+1} \sim p(\cdot|s_t, \pi(s_t))) \right] - \lambda \sup_{p' \in \mathcal{P}(s_t, \pi(s_t))} \left[V_{C,\theta}^{\pi_k}(s_{t+1} \sim p'(\cdot|s_t, \pi(s_t))) \right]$; $\mathcal{P}(s_t, \pi(s_t))$ is an uncertainty set for the current state s_t and action a_t; π_k is the current network's policy, and $\hat{\theta}$ denotes the target network parameters. The Bellman operators derived in the previous sections are repeatedly applied in this policy evaluation step depending on the optimization objective (e.g., R3C or RC). This would be utilized in the critic updates of D4PG and DMPO. Note that the action value function definition, $\mathbf{Q}_{\theta}^{\pi_k}(s_t, a_t)$, trivially follows.

4   EXPERIMENTS

The experiments were performed using domains from the Real-World Reinforcement Learning (RWRL) suite[3], namely cartpole:(balance, swingup), walker:(stand, walk, run), and quadruped:(walk, run). We define a task in our experiments as a 6-tuple $T = \langle \text{domain}, \text{domain\_variant}, \text{constraint}, \text{safety\_coefficient}, \text{threshold}, \text{perturbation} \rangle$ which refer to the domain name, the variant for that domain, the constraint being considered, the saefty coefficient value, the constraint threshold and the type of robustness perturbation being applied to the dynamics respectively. An example task would therefore be: $T = \langle \textbf{cartpole}, \textbf{swingup}, \textbf{balance\_velocity}, \textbf{0.3}, \textbf{0.115}, \textbf{pole\_length} \rangle$. In total, we have 6 different tasks on which we test our benchmark agents. The full list of tasks can be found in the Appendix, Table 8. The available constraints per domain can be found in the Appendix, Table B.1.

The baselines used in our paper can be seen in Table 1. C-ALG refers to the reward constrained, non-robust algorithms of the variants that we have adapted based on (Tessler et al., 2018; Anonymous, 2020); RC-ALG refers to the robust constraint algorithms corresponding to the Bellman operator T_{RC}^{π}; R3C-ALG refers to the robust return robust constrained algorithms corresponding to the Bellman operator T_{R3C}^{π}; SR3C-ALG refers to the soft robust (with respect to return), robust constraint algorithms and R-ALG refers to the robust return algorithms based on Mankowitz et al. (2019).

4.1   EXPERIMENTAL SETUP

For each task, the action and observation dimensions are shown in the Appendix, Table 7. The length of an episode is 1000 steps and the upper bound on reward is 1000 (Tassa et al., 2018). All the

---

[3]https://github.com/google-research/realworldrl_suite

Baseline Algorithm	Variants	Baseline Description
C-ALG	C-D4PG, C-DMPO	Constraint aware, non-robust.
RC-ALG	RC-D4PG, RC-DMPO	Robust constraint.
R3C-ALG	R3C-D4PG, R3C-DMPO	Robust return robust constraint.
R-ALG	R-D4PG, R-DMPO	Robust return.
SR3C-ALG	SR3C-D4PG	Soft robust return, robust constraint.

Table 1: The baseline algorithms used in this work.

Base	Algorithm	R	$R_{penalized}$	$\max(0, J_C^\pi - \beta)$
D4PG	C-D4PG	618.93 ± 122.07	427.218	0.192
	R-D4PG	669.48 ± 113.78	498.928	0.171
	R3C-D4PG	$\mathbf{773.48 \pm 71.13}$	**660.243**	**0.113**
	RC-D4PG	641.59 ± 134.21	500.916	0.141
	SR3C-D4PG	759.62 ± 73.10	631.383	0.128
MPO	C-MPO	539.64 ± 95.26	334.224	0.205
	R-MPO	696.68 ± 82.41	549.595	0.147
	R3C-MPO	$\mathbf{742.48 \pm 79.06}$	**635.833**	**0.107**
	RC-MPO	693.28 ± 100.69	568.196	0.125

Table 2: Performance metrics averaged over all evaluation sets for all tasks.

network architectures are the same per algorithm and approximately the same across algorithms in terms of the layers and the number of parameters. A full list of all the network architecture details can be found in the Appendix, Table 5. All runs are averaged across 3 seeds.

Metrics: We have three metrics to track overall performance, namely: **Return** R, **overshoot** $\psi_{\beta,C}$, **Penalized Return** $R_{penalized}$. The return is the sum of rewards the agent receives over the course of an episode. Constraint overshoot $\psi_{\beta,C} = \max(0, J_C^\pi - \beta)$ is defined as the different between the average long term constraint penalties over the course of an episode J_C^π and the constraint threshold β. The penalized return is defined as $R_{penalized} = R - \bar{\lambda}\psi_{\beta,C}$ where $\bar{\lambda} = 1000$ is an evaluation weight and equally trades off return with constraint overshoot $\psi_{\beta,C}$.

Constraint Experiment Setup: The *safety coefficient* is a flag in the RWRL suite (Dulac-Arnold et al., 2020) that determines how easy/difficult it is in the environment to violate constraints. The safety coefficient values range from 0.0 (easy to violate constraints) to 1.0 (hard to violate constraints). As such we selected for each task (1) a safety coefficient of 0.3; (2) a particular constraint supported by the RWRL suite and (3) a corresponding constraint threshold β, which ensures that the agent can find feasible solutions (i.e., satisfy constraints) and solve the task. The full list of thresholds per domain can be found in the Appendix, Table 4.

Robustness Experimental Setup: The robust/soft-robust agents (R3C and RC variants) are trained using a pre-defined uncertainty set consisting of 3 task perturbations (this is based on the results from Mankowitz et al. (2019)). Each perturbation is a different instantiation of the Mujoco environment. The agent is then evaluated on a set of 5 hold-out task perturbations. For example, if the task is $T = \langle \textbf{cartpole}, \textbf{swingup}, \textbf{balance\_velocity}, \textbf{0.3}, \textbf{0.115}, \textbf{pole\_length} \rangle$, then the agent will have three pre-defined pole length perturbations for training, and evaluate on three unseen pole lengths, while trying to satisfy the balance velocity constraint.

Training Procedure: All agents are always acting on the unperturbed environment. This corresponds to the default environment in the dm_control suite Tassa et al. (2018) and is referred to in the experiments as the nominal environment. When the agent acts, it generates next state realizations for the nominal environment as well as each of the perturbed environments in the training uncertainty set to generate the tuple $\langle s, a, r, [s', s'_1, s'_2 \cdots s'_N] \rangle$ where N is the number of environments in the training uncertainty set and s'_i is the next state realization corresponding to the i^{th} perturbed training environment. Since the robustness update is incorporated into the policy evaluation stage of each algorithm, the critic loss which corresponds to the TD error in each case is modified as follows:

when computing the target, the learner samples a tuple $\langle s, a, r, [s', s'_1, s'_2 \cdots s'_N] \rangle$ from the experience replay. The target action value function for each next state transition $[s', s'_1, s'_2 \cdots s'_N]$ is then computed by taking the $\inf$ (robust), average (soft-robust) or the nominal value (non-robust). In each case separate action-value functions are trained for the return $Q(s, a)$ and the constraint $Q_C(s, a)$. These value function estimates then individually return the $mean, \inf, \sup$ value, depending on the technique, and are combined to yield the target to compute $\mathbf{Q}(s, a)$.

The chosen values of the uncertainty set and evaluation set for each domain can be found in Appendix, Table 9. Note that it is common practice to manually select the pre-defined uncertainty set and the unseen test environments. Practitioners often have significant domain knowledge and can utilize this when choosing the uncertainty set (Derman & Mannor, 2019; Derman et al., 2018; Di Castro et al., 2012; Mankowitz et al., 2018; Tamar et al., 2014).

5 EXPERIMENT RESULTS

The results section is divided up into a number of sub-sections. The first sub-section analyzes the sensitivity of a fix constrained policy operating in perturbed versions of a given environment. This will help test the hypothesis that perturbing the environment does indeed have an effect on constraint satisfaction as well as return performance. Then we analyze the performance of the R3C and RC variants with respect to the baseline algorithms.

6 FIXED POLICY SENSITIVITY

In order to validate our hypothesis, we trained an RC-D4PG agent to satisfy constraints across 8 different tasks. In each case, RC-D4PG learns to solve the task and satisfy the constraints in expectation. We then perturbed each of the tasks with a supported perturbation and evaluated whether the constraint overshoot increases and the return decreases for the RC-D4PG agent. Some example graphs are shown in Figure 1 for the Cartpole (left), Quadruped (middle) and Walker (right) domains. The upper row of graphs contain the return performance (blue curve), the penalized return performance (orange curve) as a function of increased perturbations (x-axis). The vertical red dotted line indicates the nominal model on which the RC-D4PG agent was trained. The lower row of graphs contain the constraint overshoot (green curve) as a function of varying perturbations. As seen in the figures, as perturbations increase across each dimension, both the return and penalized return degrades (top row) while the constraint overshoot (bottom row) increases. This provides useful evidence for our hypothesis that constraint satisfaction does indeed suffer as a result of perturbing the environment dynamics. This was consistent among many more settings. The full performance plots can be found in the Appendix, Figures 3, 4 and 5 for Cartpole, Quadruped and Walker respectively.

Figure 1: The effect on constraint satisfaction and return as perturbations are added to Cartpole, Quadruped and Walker for a fixed RC-D4PG policy.

7 ROBUST CONSTRAINED RESULTS

As mentioned at the start of the experiments section, we compare C-ALG, RC-ALG, R3C-ALG, R-ALG and SR3C-ALG[4] across 8 tasks. The average performance across holdout sets and tasks is

---

[4]We only ran the SR3C-D4PG variant to gain intuition as to soft-robust performance.

shown in Table 2. As seen in the table, the R3C-ALG variant outperforms all of the baselines in terms of penalized return and therefore achieves lower constraint overshoot. Interestingly, the soft-robust variant yields competitive performance.

We further analyze the results for two tasks using ALG=D4PG in Figure 2, namely $T_{walker} = \langle \mathbf{walker}, \mathbf{walk}, \mathbf{joint\_velocity}, \mathbf{0.3}, \mathbf{0.1}, \mathbf{torso\_length} \rangle$ (left figure) and $T_{quadruped} = \langle \mathbf{quadruped}, \mathbf{walk}, \mathbf{balance\_velocity}, \mathbf{0.3}, \mathbf{0.115}, \mathbf{shin\_length} \rangle$ (right figure). Bar charts of the additional tasks can be found in the Appendix, Figure 6. Each graph contains, on the y-axis, the return R (marked by the transparent colors) and the penalized return $R_{penalized}$ (marked by the dark colors superimposed on top of R). The x-axis consists of the nominal model (which represents an upper bound on performance) as well as the holdout set environments in increasing order of difficulty from $test0$ to $testN$ and $N = 9$. As can be seen for T_{walker} (Figure 2 (left)), R3C-D4PG outperform the baselines, especially as the perturbations get larger. This can be seen by observing that as the perturbations increase, the penalized return for these techniques is significantly higher than that of the baselines. This implies that the amount of constraint violations is significantly lower for these algorithms resulting in robust constraint satisfaction. $T_{quadruped}$ (Figure 2 (right)) has similar performance. A comparison of D4PG and DMPO variants on the $T_{walker} = \langle \mathbf{walker}, \mathbf{walk}, \mathbf{balance\_velocity}, \mathbf{0.3}, \mathbf{0.1}, \mathbf{thigh\_length} \rangle$ can be seen in the figure (bottom row) with similar results.

Figure 2: The holdout set performance of the baseline algorithms on D4PG variants (top row) and on comparing D4PG and DMPO variants for Walker with thigh length perturbations (bottom row).

8   CONCLUSION

This papers simultaneously addresses constraint satisfaction and robustness to state perturbations, two important challenges of real-world reinforcement learning. We present two RL objectives, R3C and RC, that yield robustness to constraints under the presence of state perturbations. We develop Bellman operators to ensure that value-based RL algorithms will converge to a fixed point when optimizing these objectives. We then show that when incorporating this into the policy evaluation step of two well-known state-of-the-art continuous control RL algorithms the agent outperforms the baselines on 8 Mujoco tasks. In related work, Everett et al. (2020) considers the problem of being verifiably robust to an adversary that can perturb the state $s' \in S$ to degrade performance as measured by a Q-function. Dathathri et al. (2020) consider the problem of learning agents (in deterministic environments with known dynamics) that satisfy constraints under perturbations to states $s' \in S$. In contrast, equation 1 considers the general problem of learning agents that optimize for the return while satisfying constraints for a given RC-MDP.

REFERENCES

Abbas Abdolmaleki, Jost Tobias Springenberg, Jonas Degrave, Steven Bohez, Yuval Tassa, Dan Belov, Nicolas Heess, and Martin A. Riedmiller. Relative entropy regularized policy iteration. *CoRR*, abs/1812.02256, 2018a. URL http://arxiv.org/abs/1812.02256.

Abbas Abdolmaleki, Jost Tobias Springenberg, Yuval Tassa, Remi Munos, Nicolas Heess, and Martin Riedmiller. Maximum a posteriori policy optimisation. *arXiv preprint arXiv:1806.06920*, 2018b.

Abbas Abdolmaleki, Sandy H. Huang, Leonard Hasenclever, Michael Neunert, H. Francis Song, Martina Zambelli, Murilo F. Martins, Nicolas Heess, Raia Hadsell, and Martin Riedmiller. A distributional view on multi-objective policy optimization. *arXiv preprint arXiv:2005.07513*, 2020.

Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 22–31. JMLR. org, 2017.

Eitan Altman. *Constrained Markov decision processes*, volume 7. CRC Press, 1999.

Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Jozefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, et al. Learning dexterous in-hand manipulation. *arXiv preprint arXiv:1808.00177*, 2018.

Anonymous. Balancing rewards and constraints with meta-gradients d4pg. pp. 449–458, 2020.

Gabriel Barth-Maron, Matthew W Hoffman, David Budden, Will Dabney, Dan Horgan, Dhruva Tb, Alistair Muldal, Nicolas Heess, and Timothy Lillicrap. Distributed distributional deterministic policy gradients. *arXiv preprint arXiv:1804.08617*, 2018.

Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 449–458. JMLR. org, 2017.

Steven Bohez, Abbas Abdolmaleki, Michael Neunert, Jonas Buchli, Nicolas Heess, and Raia Hadsell. Value constrained model-free continuous control. *arXiv preprint arXiv:1902.04623*, 2019.

Paul F. Christiano, Zain Shah, Igor Mordatch, Jonas Schneider, Trevor Blackwell, Joshua Tobin, Pieter Abbeel, and Wojciech Zaremba. Transfer from simulation to real world through learning deep inverse dynamics model. *CoRR*, abs/1610.03518, 2016. URL http://arxiv.org/abs/1610.03518.

Sumanth Dathathri, Johannes Welbl, Krishnamurthy (Dj) Dvijotham, Ramana Kumar, Aditya Kanade, Jonathan Uesato, Sven Gowal, Po-Sen Huang, and Pushmeet Kohli. Scalable neural learning for verifiable consistency with temporal specifications, 2020. URL https://openreview.net/forum?id=BklC2RNKDS.

Esther Derman, Daniel J Mankowitz, Timothy A Mann, and Shie Mannor. Soft-robust actor-critic policy-gradient. *arXiv preprint arXiv:1803.04848*, 2018.

Mankowitz Daniel J Mann Timothy A Derman, Esther and Shie Mannor. A bayesian approach to robust reinforcement learning. In *Association for Uncertainty in Artificial Intelligence*, 2019.

Dotan Di Castro, Aviv Tamar, and Shie Mannor. Policy gradients with variance related risk criteria. *arXiv preprint arXiv:1206.6404*, 2012.

Gabriel Dulac-Arnold, Daniel J. Mankowitz, and Todd Hester. Challenges of real-world reinforcement learning. *CoRR*, abs/1904.12901, 2019. URL http://arxiv.org/abs/1904.12901.

Gabriel Dulac-Arnold, Nir Levine, Daniel J Mankowitz, Jerry Li, Cosmin Paduraru, Sven Gowal, and Todd Hester. An empirical investigation of the challenges of real-world reinforcement learning. *arXiv preprint arXiv:2003.11881*, 2020.

Yonathan Efroni, Shie Mannor, and Matteo Pirotta. Exploration-exploitation in constrained mdps, 2020.

Michael Everett, Bjorn Lutjens, and Jonathan P. How. Certified adversarial robustness for deep reinforcement learning, 2020.

Garud N Iyengar. Robust dynamic programming. *Mathematics of Operations Research*, 30(2): 257–280, 2005.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Daniel J Mankowitz, Timothy A Mann, Pierre-Luc Bacon, Doina Precup, and Shie Mannor. Learning robust options. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Daniel J. Mankowitz, Nir Levine, Rae Jeong, Abbas Abdolmaleki, Jost Tobias Springenberg, Timothy A. Mann, Todd Hester, and Martin A. Riedmiller. Robust reinforcement learning for continuous control with model misspecification. *CoRR*, abs/1906.07516, 2019. URL http://arxiv.org/abs/1906.07516.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Belle-mare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1–8. IEEE, 2018.

Divyam Rastogi, Ivan Koryakovskiy, and Jens Kober. Sample-efficient reinforcement learning via difference models. In *Machine Learning in Planning and Control of Robot Motion Workshop at ICRA*, 2018.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of Go without human knowledge. *Nature*, 550, 2017.

Aviv Tamar, Shie Mannor, and Huan Xu. Scaling up robust mdps using function approximation. In *International Conference on Machine Learning*, pp. 181–189, 2014.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, Timothy P. Lillicrap, and Martin A. Riedmiller. Deepmind control suite. *CoRR*, abs/1801.00690, 2018. URL http://arxiv.org/abs/1801.00690.

Chen Tessler, Shahar Givony, Tom Zahavy, Daniel J Mankowitz, and Shie Mannor. A deep hierarchical approach to lifelong learning in minecraft. In *AAAI*, volume 3, pp. 6, 2017.

Chen Tessler, Daniel J Mankowitz, and Shie Mannor. Reward constrained policy optimization. *arXiv preprint arXiv:1805.11074*, 2018.

Markus Wulfmeier, Ingmar Posner, and Pieter Abbeel. Mutual alignment transfer learning. *arXiv preprint arXiv:1707.07907*, 2017.