Increasing the Scope as You Learn:
Adaptive Bayesian Optimization in Nested Subspaces

Abstract

Recent advances have extended the scope of Bayesian optimization (BO) to expensive-to-evaluate black-box functions with dozens of dimensions, aspiring to unlock impactful applications, for example, in the life sciences, neural architecture search, and robotics. However, a closer examination reveals that the state-of-the-art methods for high-dimensional Bayesian optimization (HDBO) suffer from degrading performance as the number of dimensions increases or even risk failure if certain unverifiable assumptions are not met. This paper proposes BAxUS that leverages a novel family of nested random subspaces to adapt the space it optimizes over to the problem. This ensures high performance while removing the risk of failure, which we assert via theoretical guarantees. A comprehensive evaluation demonstrates that BAxUS achieves better results than the state-of-the-art methods for a broad set of applications.

1 Introduction

The optimization of expensive-to-evaluate black-box functions where no derivative information is available has found many applications, for example in chemical engineering [10, 26, 29, 54, 56], materials science [22, 27, 28, 30, 49, 59, 63], aerospace engineering [37, 41], hyperparameter optimization [4, 31, 36, 57], neural architecture search [34, 53], vehicle design [13, 32], hardware design [18, 46], drug discovery [48], robotics [11, 12, 39, 43, 51], and the life sciences [17, 55, 60]. Here increasing the number of dimensions (or parameters) of the optimization problem usually allows for better solutions. For example, by exposing more process parameters of a chemical reaction, we obtain a more granular control of the process; for a design task, we may optimize a larger number of design decisions jointly; in robotics, we gain access to more sophisticated control policies.

A series of breakthroughs has recently pushed the envelope of high-dimensional Bayesian optimization and facilitated a wider adoption in science and engineering. The key challenge for further scaling is the so-called curse of dimensionality. The complexity of the task of finding an optimum grows exponentially with the number of dimensions [6, 21]. Recently, methods that rely on local 'trust regions' have gained popularity. They usually achieve good performance for problems with up to a couple of dozens input parameters. However, we observe that their performance degrades for higher-dimensional problems. This is not surprising, given that trust regions have a smaller volume but still the full dimensionality of the problem. Other state-of-the-art methods suppose the existence of a low-dimensional active subspace and enjoy great scalability if they find such a space. The caveat is that its existence is usually not known for practical applications. Moreover, the user needs to 'guess' a good upper bound on its dimensionality to enjoy a good sample efficiency.

In this work, we propose a theoretically-founded approach for high-dimensional Bayesian optimization, BAxUS (**B**ayesian optimization with **A**daptive a**x**is-aligned **U**niform **S**ubspaces), that reliably achieves a high performance on a comprehensive set of applications. BAxUS utilizes a family of

nested embedded spaces to increase the dimensionality of the domain that it optimizes over as it collects more data. As a byproduct, BAxUS can leverage an active subspace, if it exists, without requiring the user to 'guess' its dimensionality. BAxUS is based on a novel random linear subspace embedding that enables a more efficient optimization and has strong theoretical guarantees. We make the following contributions:

1. We develop BAxUS that reliably achieves excellent solutions on a broad set of high-dimensional tasks, outperforming the state-of-the-art.

2. A novel family of nested random embeddings that has the following properties: a) The BAxUS embedding has a strictly higher probability of containing an optimum than the HESBO embedding proposed by Nayebi et al. [47]. b) The BAxUS embedding is the optimal embedding of the *count-sketch* type, as defined in Def. 1. c) Its probability containing an optimum converges to the one of the HESBO embedding as the input dimensionality $D \to \infty$.

3. A comprehensive evaluation on a representative collection of benchmarks that demonstrates that BAxUS outperforms the state-of-the-art methods.

The remainder of this paper is structured as follows. Section 2 states the problem and discusses related work. Section 3 presents the BAxUS algorithm and the corresponding embedding. Section 4 evaluates BAxUS on a variety of benchmarks. Lastly, we discuss our work in Section 5.

2 Background

The task is to find a minimizer

$$\boldsymbol{x}^* \in \arg\min_{\boldsymbol{x} \in \mathcal{X}} f(\boldsymbol{x}),$$

where $\mathcal{X} = [-1, +1]^D$. The objective function $f : \mathcal{X} \to \mathbb{R}$ is an expensive-to-evaluate black-box function; hence the number of function evaluations needed to find an optimizer is crucial. Evaluations may be subject to observational noise, i.e., $f(\boldsymbol{x}_i) + \varepsilon_i$, with $\varepsilon_i \sim \mathcal{N}(0, \sigma^2)$. The focus of this work is on *scalable high-dimensional Bayesian optimization*, where the *input dimensionality* D is in the hundreds, and the sampling budget may comprise a thousand or more function evaluations.

Linear embeddings. A successful approach for HDBO is to assume the existence of an *active subspace* [16], i.e., there exist a space $\mathcal{Z} \subseteq \mathbb{R}^{d_e}$, with $d_e < D$ and a function $g : \mathcal{Z} \to \mathbb{R}$, such that for all $\boldsymbol{x}$: $g(T\boldsymbol{x}) = f(\boldsymbol{x})$ where $T \in \mathbb{R}^{d_e \times D}$ is a projection matrix projecting $\boldsymbol{x}$ onto $\mathcal{Z}$ and d_e is the *effective dimensionality* of the problem. In practice, both d_e and $\mathcal{Z}$ are unknown.

REMBO (Random embedding BO) [65] and HESBO (Hashing-enhanced subspace BO) [47] try to capture this active subspace by a randomly chosen linear subspace. Therefore, they generate a random projection matrix S^T that maps from a d-dimensional subspace $\mathcal{Y} \in \mathbb{R}^d$ with $d \ll D$ (the *target space*) to $\mathcal{X}$. We call d the *target dimensionality*. For REMBO, each entry in S^T is normally distributed. REMBO uses a heuristic to determine a hyperrectangle in $\mathcal{Y}$ that it then optimizes over. Note that the bounded domain may not contain a point that maps to an optimizer of f, a risk aggravated by distortions introduced by the projection. [5, 7, 8] proposed ideas to mitigate the issue. HESBO's random projection assigns one target dimension and sign (± 1) to each input dimension. This embedding is inspired by the count-sketch algorithm [14] for estimating frequent items in data streams. The sparse projection matrix S^T is, except for the signs, binary, and each row has exactly one non-zero entry. Even though this embedding avoids REMBO's distortions, it has a lower probability of containing the optimum [38]. ALEBO [38] uses a Mahalanobis kernel and imposes linear constraints on the acquisition function to avoid projecting outside of $\mathcal{X}$.

Non-linear embeddings. Several works use autoencoders to learn non-linear spaces for optimization, trading in sample efficiency. Tripp et al. [62] change the training objective of a variational autoencoder (VAE) [35] to make the target space more suitable for optimization. They give higher weight to better-performing points when training the variational autoencoder (VAE) and show that this improves optimization. Moriconi et al. [44] incorporate the training of an autoencoder directly into the likelihood maximization of a Gaussian process (GP) surrogate. The computational cost is cubic in the number of samples and the input dimension. Lu et al. [40] and Maus et al. [42] use autoencoders to learn embeddings of highly structured input spaces such as kernels or molecules. Other approaches include partial least squares [9] or sliced inverse regression [15].

High-dimensional BO in the input space. One method to make HDBO in the input space feasible is trust regions (TRs) [21, 50, 52, 68]. The TURBO algorithm [21] optimizes over bounded TRs instead of the global space, adapting their side lengths and the center points during the optimization process. By restricting function evaluations to trust regions, TURBO addressed the problem of over-exploration; see [21] for details. Note that the TRs have full input dimensionality, which may impact TURBO's ability to scale to very large dimensions. Nonetheless, TURBO set a new state-of-the-art by scaling to dozens on input dimensions and thousands of function evaluations. Wan et al. [64] extended the idea of TRs to categorical and mixed spaces by using the Hamming distance to define the TR boundaries. SAASBO [19] uses sparse priors on the GP length scales which seems particularly valuable if the active subspace is axis-aligned. Indeed, SAASBO can outperform TURBO on certain benchmarks [19]. The cost of inference scales cubically with the number of function evaluations; thus, SAASBO is not expected to scale beyond small sampling budgets, which is confirmed by our experiments. Another line of research relies on the assumption that the input space has an additive structure [23, 33, 45, 66]. Additive GPs rely on computationally expensive sampling methods to learn a decomposition of the input variables, which limits the scalability of such methods to problems of moderate dimensionalities and sampling budgets [21, 47].

In Sect. 4 we evaluate the performances of TURBO, SAASBO, ALEBO, and HESBO. Moreover, we study the popular CMA-ES [24] and random search [3].

3 The BAxUS algorithm

Wang et al. [65] showed that the REMBO embedding contains the optimum in the target space with probability 1 if $d \geq d_e$ and there are no bounds on the target and input spaces, i.e., $\mathcal{Y} = \mathbb{R}^d$ and $\mathcal{X} = \mathbb{R}^D$. For $d < d_e$, it is generally impossible to represent an optimum in $\mathcal{X}$ for arbitrary f as S^T projects to a d-dimensional subspace in $\mathcal{X}$. We call the probability of a target space to contain the optimum the *success probability*. For $d \geq d_e$, there is a positive success probability that increases with d [38, 65]. The main problem is to set d as small as possible to avoid the detrimental effects of the curse of dimensionality but as large as necessary to achieve a high probability of $\mathcal{Y}$ to contain an optimum.

In reality, the active subspace and its dimensionality are usually unknown. The performance of methods, such as REMBO [65], HESBO [47], and ALEBO [38] depends on choosing d such that the success probability is high. Therefore, they implicitly rely on guessing the effective dimensionality d_e appropriately. We argue that choosing the target dimensionality is problematic in many practical applications. If chosen too small, the subspace cannot represent f sufficiently well. If it is chosen too large, the curse of dimensionality slows down the optimization.

The proposed algorithm, BAxUS, operates on target spaces of increasing dimensionality while preserving previous observations. Let d_{init} be the initial target dimensionality and m the total evaluation budget. BAxUS starts with a d_{init}-dimensional embedding that is increased over time until, after $m_D \leq m$ evaluations, it roughly reaches the input dimensionality D. With this strategy, we can leverage the efficiency of BO in low-dimensional spaces while guaranteeing to find an optimum in the limit. Increasing the target dimensionality is enabled by a novel embedding, which lets us carry over observations from previous, lower-dimensional target spaces into more high-dimensional target spaces. We further use a TR-based approach based on Eriksson et al. [21] to carry out optimization for high target dimensions effectively. BAxUS uses a GP surrogate [67] to model the function in the target space. Algorithm 1 gives the pseudocode for BAxUS. In Appendix D, we prove global convergence for BAxUS. We will now present the different components in detail.

3.1 The Axis-aligned Uniform Subspace Embedding

The BAxUS embedding uses a sparse projection matrix to map from $\mathcal{Y}$ to $\mathcal{X}$. The number of non-zero entries in this matrix is equal to the input dimensionality D. Another embedding with this property is the HESBO embedding [47]. Given the D and a target dimensionality d, HESBO samples a target dimension $\in \{1, \ldots, d\}$ and a sign $\in \{\pm 1\}$ for each input dimension uniformly at random. Conversely, each target dimension has a set of signed contributing input dimensions. We call the set of contributing input dimensions to a target dimension a *bin*. These relations implicitly define the embedding matrix $S \in \{0, \pm 1\}^{d \times D}$, where each column has exactly one non-zero entry [14]. In the HESBO embedding, the number of contributing input dimensions varies between 0 and D.

$$S^{\mathsf{T}} = \begin{pmatrix} -1 & 0 \\ +1 & 0 \\ 0 & +1 \\ 0 & -1 \\ 0 & -1 \end{pmatrix}$$

Figure 1: Observations are kept when increasing the target dimensionality: Example of the splitting method where $D = 5$ and $d = 2$. The first target dimension y_1 has two contributing input dimensions, x_1 and x_2; y_2 has three contributing input dimensions, x_3, x_4, and x_5. By S^{T}, a point $(0.7, 0.3)^{\mathsf{T}}$ in the target space is mapped to $(-0.7, +0.7, +0.3, -0.3, -0.3)^{\mathsf{T}}$ in the input space. Assigning the fifth input dimension to a new target dimension and copying the function values from the second target dimension does not change the observation in the input space. The new S^{T} is not shown but has one additional column with -1 in the last row, and the last row of the second column is set to 0.

The interpretation of contributing input dimensions allows for an intuitive way to increase the embedding, which is shown in Figure 1. We update the embedding matrix such that contributing input dimensions of the target dimension are re-assigned to the current bin and b new bins. We then say that we *split* the corresponding target dimension. Importantly, this type of embedding allows for retaining observations (see Figure 1) without any distortions. Assume, for example, that y_i is the dimension to be split. The contributing input dimensions are re-assigned to y_i and two new target dimensions y_j and y_k (here, $b = 2$); the observations can be retained by setting the value of the coordinate y_i to the coordinates y_j and y_k. The observations remain undistorted in the input space because an input dimension re-assigned to a new target dimension still has the same value. By doing so, the observations from the previous target dimension get carried over to the new target dimension. Algorithm 2 describes the procedure in detail.

In the BAxUS embedding, we force each bin of a target dimension to have roughly the same number of contributing input dimensions; the bin sizes differ by at most one. First, we create a random permutation of the input dimensions $1, \ldots, D$. The list of input dimensions is split into

---

Algorithm 1 BAxUS

Input: b: new bins per dimension split, D: input dimension, m_D: # evaluations by which the input dimension is reached.
Output: minimizer $\boldsymbol{x}^* \in \arg\min_{\boldsymbol{x} \in \mathcal{X}} f(\boldsymbol{x})$.
1: $d \leftarrow$ initial target dimensionality of the subspace given by Eq. (4).
2: Compute initial projection matrix $S^{\mathsf{T}} : \mathcal{Y} \rightarrow \mathcal{X}$ by BAxUS embedding for D and d.
3: Sample initial data $\mathcal{D} = \{(\boldsymbol{y}_1, f(S^{\mathsf{T}}\boldsymbol{y}_1)), \ldots\}$ and fit the GP surrogate.
4: $n \leftarrow 0$
5: **while** evaluation budget not exhausted **do**
6: $\quad L \leftarrow L_{\text{init}}$ $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad$ ▷ Initialize the trust region
7: $\quad$ Calculate fail tolerance as described in Sec. 3.4: $\tau_{\text{fail}}^s \leftarrow \max\left(1, \min\left(\tilde{\tau}_{\text{fail}}^s, d\right)\right)$
8: $\quad$ **while** $L > L_{\min}$ **and** evaluation budget not exhausted **do**
9: $\qquad$ Find $\boldsymbol{y}$ by maximizing Thompson sample in TR, evaluate $f(S^{\mathsf{T}}\boldsymbol{y})$, and add to $\mathcal{D}$.
10: $\qquad$ Re-fit the GP hyperparameters.
11: $\qquad$ Adjust trust region, see Sec. 3.2 for details.
12: $\quad$ **if** $d < D$ **then**
13: $\qquad$ $d \leftarrow \min(d \cdot (b+1), D)$.
14: $\qquad$ Increase S^{T} by Algorithm 2. $\qquad\qquad\qquad\qquad\qquad\qquad$ ▷ See Appendix E
15: $\quad$ **else**
16: $\qquad$ Re-sample initial data and discard previous observations.
17: $\quad n \leftarrow n + 1$
18: **Return** $S^{\mathsf{T}}(\arg\min_{\boldsymbol{y} \in \mathcal{D}} f(S^{\mathsf{T}}\boldsymbol{y}))$. $\qquad\qquad\qquad\qquad$ ▷ Return best point in input space

---

Figure 2: Success probabilities $p(Y^*; D, d, d_e)$ of the BAxUS and HESBO embeddings for different input dimensionalities ($D = 100$ (l), $D = 500$ (c), $D = 1000$ (r)) as a function of the target dimensionality d. The effective dimensionality is $d_e = 20$. The BAxUS embedding has a strictly higher success probability than the HESBO embedding. The improvement is enormous for input dimensionalities in the low hundreds and still substantial for 1000D tasks. Following the theoretical analysis, the difference vanishes as the input dimension D grows large.

154 $\min(d, D)$ individual bins. If d does not divide D, not all bins can have the same size. We split
155 the permutation of input dimensions such that the i-th bin has size $\lceil D/d \rceil$, if $i + d\lfloor D/d \rfloor \le D$,
156 and $\lfloor D/d \rfloor$ otherwise. The first bins have one additional element with this construction if d does
157 not divide D. We further randomly assign a sign to each input dimension. The sign of the input
158 dimensions and their assignment to target dimensions then implicitly define S^{T} (see Figure 1). We
159 now show that target spaces of the BAxUS embedding have a higher success probability than for the
160 HESBO embedding. We establish the following two definitions.

161 **Definition 1 (Count-sketch type embedding).** We say that a matrix $S \in \{0, \pm 1\}^{D \times d}$ is of the
162 *count-sketch type* if and only if each column in S has exactly one non-zero entry.

163 **Definition 2 (Success of a count-sketch type embedding).** A success of count-sketch type em-
164 bedding is the event $Y^* =$ "For any function $f : \mathcal{X} \to \mathbb{R}$ with an axis-aligned active subspace that
165 attains minima in $\mathcal{X}$, there exists a $\boldsymbol{y}^*$ in $\mathcal{Y}$ such that $S^{\mathsf{T}}\boldsymbol{y}^* \in \arg\min_{\boldsymbol{x} \in \mathcal{X}} f(\boldsymbol{x})$", where S^{T} maps
166 from the target space $\mathcal{Y}$ to the input space $\mathcal{X}$.

167 We refer to Definition 4 in Appendix C for a formal definition of a function with an axis-aligned active
168 subspace. In Lemma 1 we give the success probability of the BAxUS embedding. All proofs have
169 been deferred to Appendix C. Note that other than in the count-sketch algorithm [14], our hashing
170 function is not pairwise independent. However, this does not influence our theoretical analysis.

171 **Lemma 1 (Success probability of the BAxUS embedding).** *Let D be the input dimensionality and*
172 $d \ge d_e$ *the dimensionality of the embedding. Let $\beta_{\text{small}} = \left\lfloor \frac{D}{d} \right\rfloor$ and $\beta_{\text{large}} = \left\lceil \frac{D}{d} \right\rceil$ be the small and*
173 *large bin sizes. Then, the probability of Y^* (see Definition 2) with the BAxUS embedding is*

$$p_A(Y^*; D, d, d_e) = \frac{\sum_{i=0}^{d_e} \binom{d(1+\beta_{\text{small}})-D}{i} \binom{D-d\beta_{\text{small}}}{d_e-i} \beta_{\text{small}}^i \beta_{\text{large}}^{d_e-i}}{\binom{D}{d_e}}. \tag{1}$$

174 Figure 2 shows the success probabilities of the BAxUS and HESBO embeddings for three different
175 settings of D. The success probability of the HESBO embedding is given by $p_H(Y^*; d, d_e) =$
176 $d!/((d - d_e)! d^{d_e})$ [38]. It is independent of D but is shown for varying d-ranges on the x-axis,
177 therefore the visual discrepancy. Except for when $D \to \infty$, the HESBO embedding always has a
178 non-zero failure probability, i.e., of not containing a given optimum. The BAxUS embedding ensures
179 that the success probability is one whenever $d \ge D$. Discontinuities in the curve of the BAxUS
180 embedding occur due to the unequal bin sizes in the BAxUS embedding's success probability. The
181 difference between the two embeddings in Figure 2 is particularly large when d_e is high. For small d_e,
182 both embeddings have a high success probability for moderate d. If d_e is high, for example $d_e = 20$,
183 HESBO requires $d = 1000$ to reach a success probability of approximately 0.8, while the BAxUS
184 embedding has a success probability of 1 as soon as $d = D$. For finite D, the success probability of
185 the HESBO embedding is lower.

Corollary 1. *For $D \to \infty$, the success probability of the* BAxUS *embedding is*

$$\lim_{D \to \infty} p_A(Y^*; D, d, d_e) = \frac{d!}{(d - d_e)! d^{d_e}} \tag{2}$$

and hence matches HeSBO*'s success probability $p_H(Y^*; d, d_e)$.*

We show that the BAxUS embedding is optimal among count-sketch type embeddings.

Corollary 2. *With the same input, target, and effective dimensionalities (D, d, and d_e), no count-sketch type embedding has a higher success probability than the* BAxUS *embedding.*

3.2 Trust-region approach

Similar to TuRBO [21], BAxUS operates in TRs. TRs are hyper-rectangles in the input space; their shape is defined by their *base side length L* and the GP length scales. A TR always has volume L, but the side length for each dimension is proportional to the corresponding length scale of the GP kernel fitted to the data. The idea of this construction is that short GP length scales signify important dimensions and reduce the side length of the hyper-rectangle in that dimension. A TR is shrunk when TuRBO fails τ_{fail} consecutive times to make progress, i.e., to find a better solution. If the algorithm consecutively makes progress for $\tau_{\text{success}} = 3$ times, it expands the TR. It restarts when the base side length L of the current TR falls below a threshold $L_{\min} := 2^{-7}$. In that case, it discards all observations for the TR and initializes a new TR on new samples. TRs enable TuRBO to focus on regions of the space that are close to the incumbent, i.e., the currently best solution from the algorithm's perspective. To choose the next evaluation point, TuRBO minimizes posterior samples of the GP on a set of candidates drawn from the TR (Thompson sampling [61]).

TRs are an essential component of BAxUS as the target dimensionality grows exponentially. We use the same hyperparameter settings as TuRBO [21] with the following exceptions: First, we change the criterion for when to restart a TR. Instead of restarting a TR when it becomes too small, we increase the target dimensionality by splitting each target dimension into several new bins unless BAxUS had already reached the input dimensionality and we reset the TR base side length to the initial value. By resetting the base side length, we also avoid convergence to a particular local minimum as the TR covers a large regions of the space again. TuRBO solves this problem by allowing for multiple parallel TRs. Secondly, we change the fail tolerance τ_{fail}, such that BAxUS can roughly reach the input dimensionality in a fixed number of evaluations. The method for this is described in Section 3.4. We use the same algorithmic setup as TuRBO with the aforementioned exceptions.

3.3 Splitting strategy

Starting in a low-dimensional embedded space, BAxUS successively grows the target dimensionality to increase the probability of containing the optimum. By Corollary 2, it is optimal to keep the number of contributing input dimensions in the target bins as equal as possible. At each splitting point, BAxUS re-assigns the contributing input dimension of each target dimension to. Hence, the target dimensionality grows exponentially. The number of splits required to reach some input dimensionality D is logarithmic in D. Compared to the constant growth of the target dimensionality, BAxUS has a larger evaluation budget in each split and is less dependent on the value of D. The algorithm starts in target dimensionality d_{init}. After k splits, the target dimensionality is $d_k = d_{\text{init}}(b + 1)^k$.

3.4 Controlling the fail tolerance

As the dimensionality grows, the GP needs more data to model the objective function accurately. We partition the evaluation budget into chunks of increasing sizes such that the sizes are proportional to the target dimensionalities. Each target dimensionality then has an individual evaluation budget. Our strategy is to control the budget that BAxUS has in each target dimensionality by the fail tolerance. We choose this indirect approach as we do not want to force BAxUS to increase the current target dimensionality if it makes considerable progress. The rule we propose is based on the fail tolerance τ_{fail} required for the increasing embedding to reach the input dimensionality D, under the assumption that BAxUS always fails in making progress. We calculate the number of splits n required to reach D by

$$D \le d_{\text{init}} \cdot (b + 1)^n \Rightarrow n = \left\lfloor \log_{b+1} \frac{D}{d_{\text{init}}} \right\rfloor, \tag{3}$$

233 with $\lfloor \cdot \rceil$ indicating rounding to the nearest integer. We assign each split i a *split budget* m_i^s that is
234 proportional to d_i, such that $\sum_{i=1}^n m_i^s = m_D$, where m_D is the evaluation budget until D is reached:
235 $m_i^s = \left\lfloor -\frac{b \cdot m_D \cdot d_i}{d_{\text{init}}(1-(b+1)^{n+1})} \right\rceil$. With that budget, we set the *raw adjusted fail tolerance* in the i-th split
236 as $\tilde{\tau}_{\text{fail}}^i = \left\lfloor \frac{m_i^s}{k} \right\rceil$, with $k = \left\lfloor \log_{\frac{1}{2}} \frac{L_{\min}}{L_{\text{init}}} \right\rceil$ being the number of TR shrinkages until the TR is restarted.

237 We aim to reduce the fail tolerance to enable BAxUS to reach higher target dimensions when
238 necessary. We are not interested in having even higher fail tolerances than the TuRBO al-
239 gorithm, which could occur with this rule. Therefore, we set the fail tolerance by taking the
240 minimum of the raw adjusted fail tolerance and the TuRBO fail tolerances for single batches,
241 $\tau_{\text{fail}}^i = \max\left(1, \min\left(\tilde{\tau}_{\text{fail}}^i, d_i\right)\right)$, where d_i is the target dimension in the i-th split.

242 **Setting the initial target dimension.** If the target dimensionality is fixed, increasing the target
243 dimensionality at an exponential rate can lead to cases where none of the target dimensionalities d_k
244 are close to the input dimensionality D. For example, for a 600-dimensional problem, with $d_{\text{init}} = 1$,
245 and $b = 3$, the difference between d_k and D is at least 344. Since the final target dimensionality
246 of BAxUS is at most D, such cases are in disagreement with the exponential growth of the target
247 dimensionality: Either the final target dimensionality is much less than the input dimensionality, or
248 the last split adds only a few new dimensions. In the first case, we potentially reduce the success
249 probability. In the latter case, we assign a too large budget to the final split. Therefore, we set the
250 initial target dimensionality such that the final target dimensionality is as close to D as possible:

$$d_{\text{init}} = \underset{i \in \{1,\ldots,b\}}{\arg\min} \; \underset{n \in \mathbb{N}_+}{\min} \left| i \cdot (b+1)^n - D \right|. \tag{4}$$

251 The optimal n is given by Eq. (3).

4 Experimental evaluation

253 In this section, we evaluate the performance of BAxUS on a 388D hyperparameter optimization task,
254 124D design problem, and a collection of tasks that exhibit an active subspace. The code is available
255 at `hiddenforanonymization`.

256 **The experimental setup.** We benchmark against TuRBO [21] with one and five trust regions,
257 SAASBO [19], ALEBO [38], random search [3], CMA-ES [24], and HeSBO [47], using the
258 implementations provided by the respective authors with their settings, unless stated otherwise. For
259 CMA-ES, we use the PyCma [25] implementation. For HeSBO and ALEBO, we use the Ax
260 implementation [1]. To show the effect of different choices of d, we run HeSBO and ALEBO with
261 $d = 10$ and $d = 20$. We observed that ALEBO and SAASBO are constrained by their high runtime
262 and memory consumption. The available hardware allowed up to 100 evaluations for SAASBO, 500
263 evaluations for ALEBO. Larger sampling budgets or higher target dimensions for ALEBO resulted in
264 out-of-memory errors. We point out that limited scalability was expected for these methods, whereas
265 the other methods scaled to considerably larger budgets, as required for scalable BO. We initialize
266 each optimizer with ten initial samples and BAxUS with $b = 3$ and $m_D = 1000$ and run 20 repeated
267 trials. Plots show the mean performance with one standard error.

268 **The benchmarks.** We evaluate the selected algorithms on six benchmarks that differ considerably
269 in their characteristics. Following [65], we augment the BRANIN2 and HARTMANN6 functions
270 with additional dummy dimensions that have no influence on the function value. We use the 388D
271 SVM benchmark and the 124D soft-constraint version of the MOPTA08 benchmark proposed in [19].
272 We set a budget of 1000 evaluations for MOPTA08, BRANIN2, and HARTMANN6 and of 2000
273 evaluations for the other benchmarks. Moreover, we stopped for BRANIN2 and HARTMANN6 when
274 the simple regret dropped below .001. We also tested the algorithms on the 300D LASSO-HIGH
275 and the 1000D LASSO-HARD benchmarks from LASSOBENCH [55]. These benchmarks have an
276 effective dimensionality of 5% of the input dimensionality, i.e., the LASSO-HIGH and LASSO-
277 HARD benchmarks have 15 and 50 effective dimensions, respectively. To study the robustness to
278 observational noise, we tested on noisy variants of LASSO-HARD and LASSO-HIGH.

Figure 3: Top row: **124D MOPTA08 (l)**: BAXUS obtains the best solutions, followed by TURBO and CMA-ES. **388D SVM (c)**: BAXUS outperforms the other methods from the start. **500D BRANIN (r)**: SAASBO, BAXUS, ALEBO, and HESBO find an optimum; SAASBO and ALEBO converge fastest. Bottom row: **100D LASSO-HARD (l)** and **300D LASSO-HIGH (c)**: BAXUS outperforms the baselines. SAASBO, ALEBO, and HESBO struggle. **500D HARTMANN6 (r)**: SAASBO performs best, closely followed by BAXUS. The other methods show only slow progress or stagnate.

4.1 Experimental results

We begin with the six noise-free benchmarks. Fig. 3 summarizes the performances. On MOPTA08, a 124D vehicle design problem, SAASBO makes slightly faster initial progress than BAXUS. We suspect that this benchmark has high effective dimensionality, such that BAXUS first needs to adapt the target dimensionality to make further progress. On the 388D SVM benchmark, BAXUS adapts to the appropriate target dimensionality where it can reach good function values faster than TURBO and CMA-ES. For this benchmark, Eriksson and Jankowiak [19] reported that SAASBO learned three effective dimensions. Yet, the fact that ALEBO and HESBO seem to stagnate after a few hundred evaluations, while BAXUS, TURBO, and CMA-ES find better solutions, indicates that optimizing more of the 385 kernel length scales of the SVM benchmark allows for better solutions. On the 500D HARTMANN6, SAASBO performs best, closely followed by BAXUS. ALEBO and HESBO are competitive initially but converge to suboptimal solutions. HESBO, BAXUS, SAASBO, ALEBO all find excellent solutions on the BRANIN benchmark, with the latter algorithms converging faster.

Next, we examine the performances on the 1000D LASSO-HARD and the 300D LASSO-HIGH that exhibit active subspaces, here without observational noise. BAXUS achieves considerably better solutions than all state-of-the-art methods. We also note that TURBO and CMA-ES perform better than SAASBO and ALEBO. While one may expect BAXUS to outperform TURBO and CMA-ES on these tasks with high input dimensions, it is surprising that SAASBO, HESBO, and ALEBO are not able to benefit from the present active subspace. Here BAXUS's strategy to adaptive expand the nested subspace is superior. Another crucial observation is that performances of BAXUS vary only slightly across runs. Thus, BAXUS is robust despite the stochastic construction of the embedding.

Across the broad collection of benchmarks, BAXUS is the only method to achieve constantly high performance.

Figure 4: BAxUS outperforms the SOTA and in particular proves to be robust to noise on the **1000D LASSO-HARD (l)** and the **300D LASSO-HIGH (r)**. Note that CMA-ES performs considerably worse than on the noise-free versions of the benchmarks.

Noisy benchmarks. We evaluate the algorithms also for tasks with observational noise. Fig. 4 summarizes the results. We observe that BAxUS achieves considerably better solutions for any number of observations than the competitors. Moreover, we note that the performances of SAASBO, CMA-ES, and HESBO ($d = 20$) degrade considerably on the LASSO-HIGH task compared to the noise-free formulation of the task studied above. BAxUS's performance is equally strong as for the noise-free case and keeps making progress after 1000 observations.

BAxUS embedding ablation study. To investigate whether the proposed family of nested random subspaces contributes to the superior performance of BAxUS, we replaced the new embedding with a similar family of nested HESBO embeddings. The results show that the proposed embedding provides a significant performance gain. Due to space constraints, the results were moved to Appendix A.

5 Discussion

High-dimensional Bayesian optimization is aspiring to unlock impactful applications broadly in science and industry. However, state-of-the-art methods suffer from limited scalability or, in some cases, require practitioners to 'guess' certain hyperparameters that critically impact the performance. This paper proposes BAxUS that works out-of-the-box and achieves considerably better performance for high-dimensional problems, as the comprehensive evaluation shows. A key idea is to scale up the dimensionality of the target subspace that the algorithm optimizes over. We apply a simple strategy that we find to work well across the board. However, we expect substantial headroom in tailoring this strategy to specific applications, either using domain expertise or by a more sophisticated data-driven approach that, for example, learns a suitable target space. Moreover, future work will explore extending BAxUS to structured domains, in particular the combinatorial spaces common in materials sciences and drug discovery.

Societal impact. Bayesian optimization has recently become a popular tool for tasks in drug discovery [48], chemical engineering [10, 26, 29, 54, 56], materials science [22, 27, 28, 49, 59, 63], aerospace engineering [2, 37, 41], robotics [11, 12, 39, 43, 51], and many more. This speaks to the progress that Bayesian optimization has made in becoming a robust and reliable 'off-the-shelf solver.' However, this promise is not yet fulfilled for the newer high-dimensional Bayesian optimization field that allows optimization over hundreds of 'tunable levers.' The applications mentioned above benefit from incorporating more such levers in the optimization: it allows for more detailed modeling of an aerospace design or a more granular control of a chemical reaction, to give some examples. The evaluation shows that the performance of state-of-the-art methods degenerates drastically for such high dimensions if the application does not meet specific requirements. Adding insult to the injury, such requirements like the dimensionality of an active subspace cannot be determined beforehand.

The proposed algorithm achieves a robust performance over a broad collection of tasks and thus will become a 'goto' optimizer for practitioners in other fields. Therefore, we release the BAxUS code.

References

[1] E. Bakshy, L. Dworkin, B. Karrer, K. Kashin, B. Letham, A. Murthy, and S. Singh. Ae: A domain-agnostic platform for adaptive experimentation. In *Conference on Neural Information Processing Systems*, pages 1–8, 2018.

[2] R. Baptista and M. Poloczek. Bayesian optimization of combinatorial structures. In *International Conference on Machine Learning*, pages 462–471. PMLR, 2018.

[3] J. Bergstra and Y. Bengio. Random search for hyper-parameter optimization. *Journal of machine learning research*, 13(2), 2012.

[4] J. Bergstra, R. Bardenet, Y. Bengio, and B. Kégl. Algorithms for Hyper-Parameter Optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 24. Curran Associates, Inc., 2011.

[5] M. Binois. *Uncertainty quantification on Pareto fronts and high-dimensional strategies in Bayesian optimization, with applications in multi-objective automotive design*. PhD thesis, Ecole Nationale Supérieure des Mines de Saint-Etienne, 2015.

[6] M. Binois and N. Wycoff. A survey on high-dimensional gaussian process modeling with application to Bayesian optimization. *arXiv*, 2021.

[7] M. Binois, D. Ginsbourger, and O. Roustant. A warped kernel improving robustness in Bayesian optimization via random embeddings. In *International Conference on Learning and Intelligent Optimization (LION)*, pages 281–286. Springer, 2015.

[8] M. Binois, D. Ginsbourger, and O. Roustant. On the choice of the low-dimensional domain for global optimization via random embeddings. *Journal of global optimization*, 76(1):69–90, 2020.

[9] M. A. Bouhlel, N. Bartoli, R. G. Regis, A. Otsmane, and J. Morlier. Efficient global optimization for high-dimensional constrained problems by using the Kriging models combined with the partial least squares method. *Engineering Optimization*, 50(12):2038–2053, 2018.

[10] B. Burger, P. M. Maffettone, V. V. Gusev, C. M. Aitchison, Y. Bai, X. Wang, X. Li, B. M. Alston, B. Li, R. Clowes, et al. A mobile robotic chemist. *Nature*, 583(7815):237–241, 2020.

[11] R. Calandra, N. Gopalan, A. Seyfarth, J. Peters, and M. P. Deisenroth. Bayesian Gait Optimization for Bipedal Locomotion. In P. M. Pardalos, M. G. Resende, C. Vogiatzis, and J. L. Walteros, editors, *Learning and Intelligent Optimization*, pages 274–290, Cham, 2014. Springer International Publishing.

[12] R. Calandra, A. Seyfarth, J. Peters, and M. P. Deisenroth. Bayesian optimization for learning gaits under uncertainty. *Annals of Mathematics and Artificial Intelligence*, 76(1):5–23, 2016.

[13] A. Candelieri, R. Perego, and F. Archetti. Bayesian Optimization of Pump Operations in Water Distribution Systems. *J. of Global Optimization*, 71(1):213–235, may 2018. ISSN 0925-5001.

[14] M. Charikar, K. Chen, and M. Farach-Colton. Finding Frequent Items in Data Streams. In P. Widmayer, S. Eidenbenz, F. Triguero, R. Morales, R. Conejo, and M. Hennessy, editors, *Automata, Languages and Programming*, pages 693–703, Berlin, Heidelberg, 2002. Springer Berlin Heidelberg. ISBN 978-3-540-45465-6.

[15] J. Chen, G. Zhu, C. Yuan, and Y. Huang. Semi-supervised Embedding Learning for High-dimensional Bayesian Optimization. *arXiv preprint arXiv:2005.14601*, 2020.

[16] P. G. Constantine. *Active subspaces: Emerging ideas for dimension reduction in parameter studies*. SIAM, 2015.

[17] Z. Cosenza, R. Astudillo, P. Frazier, K. Baar, and D. E. Block. Multi-Information Source Bayesian Optimization of Culture Media for Cellular Agriculture. *Biotechnology and Bioengineering*, 2022.

[18] A. Ejjeh, L. Medvinsky, A. Councilman, H. Nehra, S. Sharma, V. Adve, L. Nardi, E. Nurvitadhi, and R. A. Rutenbar. HPVM2FPGA: Enabling True Hardware-Agnostic FPGA Programming. In *Proceedings of the 33rd IEEE International Conference on Application-specific Systems, Architectures, and Processors*, 2022.

[19] D. Eriksson and M. Jankowiak. High-dimensional Bayesian optimization with sparse axis-aligned subspaces. In C. de Campos and M. H. Maathuis, editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, volume 161 of *Proceedings of Machine Learning Research*, pages 493–503. PMLR, 27–30 Jul 2021.

[20] D. Eriksson and M. Poloczek. Scalable Constrained Bayesian Optimization. In A. Banerjee and K. Fukumizu, editors, *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, volume 130 of *Proceedings of Machine Learning Research*, pages 730–738. PMLR, 13–15 Apr 2021.

[21] D. Eriksson, M. Pearce, J. Gardner, R. D. Turner, and M. Poloczek. Scalable Global Optimization via Local Bayesian Optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 5496–5507, 2019.

[22] P. I. Frazier and J. Wang. *Bayesian Optimization for Materials Design*, pages 45–75. Springer International Publishing, Cham, 2016. ISBN 978-3-319-23871-5.

[23] J. Gardner, C. Guo, K. Weinberger, R. Garnett, and R. Grosse. Discovering and exploiting additive structure for Bayesian optimization. In *International Conference on Artificial Intelligence and Statistics*, pages 1311–1319, 2017.

[24] N. Hansen and A. Ostermeier. Adapting arbitrary normal mutation distributions in evolution strategies: the covariance matrix adaptation. In *Proceedings of IEEE International Conference on Evolutionary Computation (ICEC)*, pages 312–317, 1996.

[25] N. Hansen, Y. Akimoto, and P. Baudis. CMA-ES/pycma on Github. Zenodo, DOI:10.5281/zenodo.2559634, Feb. 2019. Last accessed: 05/09/2022. License: BSD-3-Clause.

[26] F. Hase, L. M. Roch, C. Kreisbeck, and A. Aspuru-Guzik. Phoenics: a Bayesian optimizer for chemistry. *ACS central science*, 4(9):1134–1145, 2018.

[27] F. Häse, M. Aldeghi, R. J. Hickman, L. M. Roch, and A. Aspuru-Guzik. Gryffin: An algorithm for Bayesian optimization of categorical variables informed by expert knowledge. *Applied Physics Reviews*, 8(3):031406, 2021.

[28] H. C. Herbol, W. Hu, P. Frazier, P. Clancy, and M. Poloczek. Efficient search of compositional space for hybrid organic–inorganic perovskites via Bayesian optimization. *npj Computational Materials*, 4(1):1–7, 2018.

[29] J. M. Hernández-Lobato, J. Requeima, E. O. Pyzer-Knapp, and A. Aspuru-Guzik. Parallel and Distributed Thompson Sampling for Large-scale Accelerated Exploration of Chemical Space. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1470–1479. PMLR, 06–11 Aug 2017.

[30] Z. E. Hughes, M. A. Nguyen, J. Wang, Y. Liu, M. T. Swihart, M. Poloczek, P. I. Frazier, M. R. Knecht, and T. R. Walsh. Tuning materials-binding peptide sequences toward gold-and silver-binding selectivity with Bayesian optimization. *ACS nano*, 15(11):18260–18269, 2021.

[31] C. Hvarfner, D. Stoll, A. Souza, L. Nardi, M. Lindauer, and F. Hutter. PiBO: Augmenting Acquisition Functions with User Beliefs for Bayesian Optimization. In *International Conference on Learning Representations*, 2022.

[32] D. R. Jones. Large-scale multi-disciplinary mass optimization in the auto industry. In *MOPTA 2008 Conference (20 August 2008)*, 2008.

[33] K. Kandasamy, J. Schneider, and B. Póczos. High dimensional Bayesian optimisation and bandits via additive models. In *International conference on machine learning (ICML)*, pages 295–304, 2015.

[34] K. Kandasamy, W. Neiswanger, J. Schneider, B. Poczos, and E. P. Xing. Neural Architecture Search with Bayesian Optimisation and Optimal Transport. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems (NeurIPS)*, volume 31. Curran Associates, Inc., 2018.

[35] D. P. Kingma and M. Welling. Auto-Encoding Variational Bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

[36] A. Klein, S. Falkner, S. Bartels, P. Hennig, and F. Hutter. Fast Bayesian Optimization of Machine Learning Hyperparameters on Large Datasets. In A. Singh and J. Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pages 528–536. PMLR, 20–22 Apr 2017.

[37] R. Lam, M. Poloczek, P. Frazier, and K. E. Willcox. Advances in Bayesian optimization with applications in aerospace engineering. In *2018 AIAA Non-Deterministic Approaches Conference*, page 1656, 2018.

[38] B. Letham, R. Calandra, A. Rai, and E. Bakshy. Re-Examining Linear Embeddings for High-Dimensional Bayesian Optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 1546–1558. Curran Associates, Inc., 2020.

[39] D. J. Lizotte, T. Wang, M. H. Bowling, D. Schuurmans, et al. Automatic Gait Optimization With Gaussian Process Regression. In *IJCAI*, volume 7, pages 944–949, 2007.

[40] X. Lu, J. Gonzalez, Z. Dai, and N. D. Lawrence. Structured Variationally Auto-encoded Optimization. In J. G. Dy and A. Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 3273–3281. PMLR, 2018.

[41] T. W. Lukaczyk, P. Constantine, F. Palacios, and J. J. Alonso. Active subspaces for shape optimization. In *10th AIAA multidisciplinary design optimization conference*, page 1171, 2014.

[42] N. Maus, H. T. Jones, J. S. Moore, M. J. Kusner, J. Bradshaw, and J. R. Gardner. Local latent space Bayesian optimization over structured inputs. *arXiv*, 2022.

[43] M. Mayr, F. Ahmad, K. I. Chatzilygeroudis, L. Nardi, and V. Krüger. Skill-based Multi-objective Reinforcement Learning of Industrial Robot Tasks with Planning and Knowledge Integration. *CoRR*, abs/2203.10033, 2022.

[44] R. Moriconi, M. P. Deisenroth, and K. S. Sesh Kumar. High-dimensional Bayesian optimization using low-dimensional feature spaces. *Machine Learning*, 109(9):1925–1943, Sep 2020. ISSN 1573-0565.

[45] M. Mutny and A. Krause. Efficient high dimensional Bayesian optimization with additivity and quadrature Fourier features. *Advances in Neural Information Processing Systems*, 31, 2018.

[46] L. Nardi, D. Koeplinger, and K. Olukotun. Practical design space exploration. In *2019 IEEE 27th International Symposium on Modeling, Analysis, and Simulation of Computer and Telecommunication Systems (MASCOTS)*, pages 347–358. IEEE, 2019.

[47] A. Nayebi, A. Munteanu, and M. Poloczek. A framework for Bayesian Optimization in Embedded Subspaces. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research (PMLR)*, pages 4752–4761. PMLR, 09–15 Jun 2019.

[48] D. M. Negoescu, P. I. Frazier, and W. B. Powell. The Knowledge-Gradient Algorithm for Sequencing Experiments in Drug Discovery. *INFORMS Journal on Computing*, 23(3):346–363, 2011.

[49] D. Packwood. *Bayesian optimization for materials science*. Springer.

[50] G. Pedrielli and S. H. Ng. G-STAR: A new kriging-based trust region method for global optimization. In *2016 Winter Simulation Conference (WSC)*, pages 803–814. IEEE, 2016.

[51] A. Rai, R. Antonova, S. Song, W. Martin, H. Geyer, and C. Atkeson. Bayesian optimization using domain knowledge on the ATRIAS biped. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 1771–1778. IEEE, 2018.

[52] R. G. Regis. Trust regions in Kriging-based optimization with expected improvement. *Engineering optimization*, 48(6):1037–1059, 2016.

[53] B. Ru, X. Wan, X. Dong, and M. Osborne. Interpretable Neural Architecture Search via Bayesian Optimisation with Weisfeiler-Lehman Kernels. In *International Conference on Learning Representations*, 2021.

[54] A. M. Schweidtmann, A. D. Clayton, N. Holmes, E. Bradford, R. A. Bourne, and A. A. Lapkin. Machine learning meets continuous flow chemistry: Automated optimization towards the Pareto front of multiple objectives. *Chemical Engineering Journal*, 352:277–282, 2018.

[55] K. Šehić, A. Gramfort, J. Salmon, and L. Nardi. LassoBench: A High-Dimensional Hyperparameter Optimization Benchmark Suite for Lasso. In *First Conference on Automated Machine Learning (Main Track)*, 2022.

[56] B. J. Shields, J. Stevens, J. Li, M. Parasram, F. Damani, J. I. M. Alvarado, J. M. Janey, R. P. Adams, and A. G. Doyle. Bayesian reaction optimization as a tool for chemical synthesis. *Nature*, 590(7844):89–96, 2021.

[57] J. Snoek, H. Larochelle, and R. P. Adams. Practical Bayesian Optimization of Machine Learning Algorithms. In F. Pereira, C. Burges, L. Bottou, and K. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012.

[58] F. J. Solis and R. J.-B. Wets. Minimization by Random Search Techniques. *Mathematics of Operations Research*, 6(1):19–30, 1981. ISSN 0364765X, 15265471.

[59] A. Souza, L. B. Oliveira, S. Hollatz, M. Feldman, K. Olukotun, J. M. Holton, A. E. Cohen, and L. Nardi. DeepFreak: Learning crystallography diffraction patterns with automated machine learning. *arXiv preprint arXiv:1904.11834*, 2019.

[60] L. Tallorin, J. Wang, W. E. Kim, S. Sahu, N. M. Kosa, P. Yang, M. Thompson, M. K. Gilson, P. I. Frazier, M. D. Burkart, et al. Discovering de novo peptide substrates for enzymes using machine learning. *Nature communications*, 9(1):1–10, 2018.

[61] W. R. Thompson. On the Likelihood that One Unknown Probability Exceeds Another in View of the Evidence of Two Samples. *Biometrika*, 25(3/4):285–294, 1933. ISSN 00063444.

[62] A. Tripp, E. Daxberger, and J. M. Hernández-Lobato. Sample-Efficient Optimization in the Latent Space of Deep Generative Models via Weighted Retraining. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 11259–11272. Curran Associates, Inc., 2020.

[63] T. Ueno, T. D. Rhone, Z. Hou, T. Mizoguchi, and K. Tsuda. COMBO: An efficient Bayesian optimization library for materials science. *Materials Discovery*, 4:18–21, 2016. ISSN 2352-9245.

[64] X. Wan, V. Nguyen, H. Ha, B. Ru, C. Lu, and M. A. Osborne. Think Global and Act Local: Bayesian Optimisation over High-Dimensional Categorical and Mixed Search Spaces. In M. Meila and T. Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 10663–10674. PMLR, 18–24 Jul 2021.

[65] Z. Wang, F. Hutter, M. Zoghi, D. Matheson, and N. de Feitas. Bayesian optimization in a billion dimensions via random embeddings. *Journal of Artificial Intelligence Research (JAIR)*, 55:361–387, 2016.

[66] Z. Wang, C. Gehring, P. Kohli, and S. Jegelka. Batched large-scale Bayesian optimization in high-dimensional spaces. In *International Conference on Artificial Intelligence and Statistics*, pages 745–754, 2018.

[67] C. K. Williams and C. E. Rasmussen. *Gaussian processes for machine learning*, volume 2. MIT press Cambridge, MA, 2006.

[68] J. Zhou, Z. Yang, Y. Si, L. Kang, H. Li, M. Wang, and Z. Zhang. A trust-region parallel bayesian optimization method for simulation-driven antenna design. *IEEE Transactions on Antennas and Propagation*, 69(7):3966–3981, 2020.

A Ablation study for the BAxUS embedding

We conduct an ablation study to investigate the difference between the BAxUS and HESBO embeddings. We run TuRBO of Eriksson et al. [21] in an embedded subspace with the two different embeddings. We use a version of ACKLEY10 (ten effective dimensions, i.e., $d_e = 10$), where we shift the optimum away from the origin with a uniformly random vector $\boldsymbol{\delta} \in [-32.768, 32.768]^{d_e}$ with $\delta_i \sim \mathcal{U}(-32.768, 32.768)$. The function we optimize is then

$$f_{\text{ShiftedAckley10}}(\boldsymbol{x}) = f_{\text{Ackley10}}(\boldsymbol{x} + \boldsymbol{\delta}).$$

We adjust the boundaries of the search space such that $f_{\text{ShiftedAckley10}}$ is evaluated on the domain $\mathcal{X} = [-32.768, 32.768]^{d_e}$. The reason for shifting the optimum is that the original ACKLEY function has its optimum at the origin. In that case, any count-sketch type embedding contains this optimum, even if all the important input dimensions are mapped to the same target dimension.

We add 10 dummy dimensions, such that $D = 30$ and set $d = 20$. With this problem-setting, the BAxUS and HESBO embeddings have a probability of approximately 0.27 and 0.07 to contain the optimum, respectively.

Figure 5: **Left**: the BAxUS embedding gives better optimization performance on the shifted ACKLEY10 function: TuRBO in embedded subspaces of the BAxUS and HESBO embeddings. The BAxUS embedding has a higher probability to contain the optimum. **Right**: the distribution of the final incumbents (lower the better). The horizontal bars show the median.

The left side of Figure 5 shows the incumbent mean for TuRBO in the two different embedded subspaces. The shaded regions show one standard error. TuRBO in an BAxUS embedding has significantly better optimization performance than in a HESBO embedding. The right side of Figure 5 shows the distributions of the final incumbents and their median. The BAxUS embedding leads to a significantly lower median and only rarely a similarly bad embedding as the HESBO method, when combined with TuRBO.

We perform a two-sided Wilcoxon rank-sum statistical test to check the difference between the best observed function values for the two embeddings. The difference is significant with $p \approx 0.00001$.

The performance difference between the two embeddings depends on the characteristics of the function and the different dimensionalities, the input dimensionality D, the target dimensionality d, and the effective dimensionality d_e. For problems with a few effective dimensions and many input dimensions, the BAxUS and HESBO embeddings become more similar (see Figure 2). However, by Corollary 2, the BAxUS embedding is, in expectation and in terms of success probability, always better than the HESBO embedding for arbitrary functions with an axis-aligned active subspace.

For functions with an optimum at the origin, both embeddings contain that optimum regardless of d: Even if all important input dimensions are mapped to the same target dimension, the optimum in the input space can be reached by "setting" this particular target dimension to zero.

Figure 6: TURBO in the BAXUS and HESBO embeddings on the shifted ACKLEY10 function with input dimensionality $D = 30$, target dimensionality $d = 20$, and effective dimensionality $d_e = 10$: The x-axis shows in how many different target dimensions the important input dimensions lie on average (more: better). The black lines at the bar tips give the standard error.

The distribution of important input dimensions. The success probability studied in Section 3 and above only considers the case where all the important input dimensions are mapped to different target dimensions. It might not be necessary to map all the important input dimensions to different target dimensions, but it is generally beneficial if they spread out. For example on MOPTA08 or SVM in Figure 3 (top left, top center), BAXUS makes initial progress, then seems to be in a too low embedding before the target dimensionality is increased and BAXUS makes further progress. If only the case where all d_e important input dimensions are mapped to individual target dimensions allowed to make progress, BAXUS would not make any progress until it reaches a suitable embedding.

Even though it is often possible to make progress without mapping all important input dimensions to individual target dimensions, it is undoubtedly beneficial if, for a given target dimensionality, they map to more individual target dimensions; The more the important input dimension spread out, the more the effective subspace can be covered.

Figure 6 shows a histogram of the number of individual target dimensions the $d_e = 10$ important input dimensions map to in the example from above for the BAXUS and HESBO embeddings. The bars on the very right approximately give the success probability for the HESBO and BAXUS embeddings - they correspond to a success (see Definition 2). The BAXUS embedding maps the 10 important input dimensions to 9 or 10 individual target dimensions in around 74% of the cases; in the HESBO embedding, this happens in less than half as many cases (22%).

TURBO with BAXUS embedding vs. BAXUS. We compare the simple idea of running TURBO in a BAXUS embedding with the BAXUS algorithm as described in Section 3. We run this simple approach for 11 different target dimensionalities d (2, 10, 20, 30, 40, 50, 60, 70, 80, 90, 100) on the LASSO-HARD benchmark and show the results with a sequential color map in Figure 7. Only the first $d = 2$-dimensional embedding achieves the same initial speedup as BAXUS, which is expected as BAXUS starts in a similarly low-dimensional initial embedding. However, the fixed embedding cannot explore the input space sufficiently and has the worst final solution. High-dimensional fixed embeddings have more freedom in exploring the input space; however, they suffer from slower initial optimization performance.

BAXUS has the same initial speedup as the two-dimensional fixed embedding but can explore the space further by increasing the dimensionality of its embedding.

Figure 7: BAxUS and TuRBO with BAxUS embeddings of different target dimensionalities on LASSO-HARD: We run TuRBO with the BAxUS embedding for target dimensionalities $d = 2, 10, 20, 30, \ldots, 100$ and compare to BAxUS.

Summing up, we observe that BAxUS achieves a better performance than TuRBO with a fixed embedding dimensionality.

B   Additional Lasso benchmark

In addition to the synthetic LASSO-HIGH and LASSO-HARD benchmarks studied in Section 4, we evaluate BAxUS on the LASSO-DNA benchmark from LASSOBENCH [55]. The LASSO-DNA benchmark is a biomedical classification task, taking binarized DNA sequences as input [55].

Figure 8: BAxUS and baselines on LASSO-DNA. As before, BAxUS makes considerable progress in the beginning and converges faster than TuRBO and CMA-ES.

Figure 8 shows the mean performance of BAxUS on the LASSO-DNA. Each line shows the incumbent mean; the shaded regions around the lines show one standard error. We see the same qualitative behavior as discussed in Section 4: BAxUS reaches a good initial solution faster than any other method and converges quickly.

After a worse start, TuRBO finds slightly better solutions than BAxUS.

C   Theoretical foundation for the BAxUS embedding

For reasons of clarity and comprehensibility we first recapitulate Definition 1 from Section 3.

Definition 1 (Count-sketch type embedding). We say that a matrix $S \in \{0, \pm 1\}^{D \times d}$ is of the *count-sketch type* if and only if each column in S has exactly one non-zero entry.

We state the following two definitions.

Definition 3 (Optima-preserving count-sketch type embedding). An embedding of the count-sketch type is *optima-preserving* if each target dimension contains at most one effective input dimension.

Definition 4 (Function with an (axis-aligned) active subspace). Let $\mathcal{X} = [-1, 1]^D$. A function $f : \mathcal{X} \to \mathbb{R}$ has an *active subspace*, if there exist a subspace (i.e., a space $\mathcal{Z} \subseteq \mathbb{R}^{d_e}$, with $d_e < D$ where $d_e \in \mathbb{N}_{++}$ is the effective dimensionality) and a projection matrix $S^\mathsf{T} \in \mathbb{R}^{d_e \times D}$, such that for any $\boldsymbol{x} \in \mathcal{X}$ there exists a $\boldsymbol{z} \in \mathcal{Z}$ so that $f(\boldsymbol{x}) = f(S^\mathsf{T}\boldsymbol{z})$ and d_e is the smallest integer with this property. The subspace $\mathcal{Z}$ is further called *axis-aligned* if S^T is of count-sketch type and $\mathcal{Z} = [-1, 1]^{d_e}$.

C.1 Proof of Lemma 1

We prove the success probability for the BAxUS embedding. For this, we first re-state Definition 2 from Section 3.

Definition 2 (Success of a count-sketch type embedding). A success of count-sketch type embedding is the event $Y^* =$ "For any function $f : \mathcal{X} \to \mathbb{R}$ with an axis-aligned active subspace that attains minima in $\mathcal{X}$, there exists a $\boldsymbol{y}^*$ in $\mathcal{Y}$ such that $S^\mathsf{T}\boldsymbol{y}^* \in \arg\min_{\boldsymbol{x} \in \mathcal{X}} f(\boldsymbol{x})$", where S^T maps from the target space $\mathcal{Y}$ to the input space $\mathcal{X}$.

Lemma 1 (Success probability of the BAxUS embedding). Let D be the input dimensionality and $d \geq d_e$ the dimensionality of the embedding. Let $\beta_{\text{small}} = \lfloor \frac{D}{d} \rfloor$ and $\beta_{\text{large}} = \lceil \frac{D}{d} \rceil$ be the small and large bin sizes. Then, the probability of Y^* (see Definition 2) with the BAxUS embedding is

$$p_A(Y^*; D, d, d_e) = \frac{\sum_{i=0}^{d_e} \binom{d(1+\beta_{\text{small}})-D}{i}\binom{D-d\beta_{\text{small}}}{d_e-i}\beta_{\text{small}}^i \beta_{\text{large}}^{d_e-i}}{\binom{D}{d_e}}. \tag{5}$$

Proof. The assignment of input dimensions to target dimensions and the signs of the input dimensions fully define the HESBO and BAxUS embeddings. Note that the signs do not have any effect on $p_A(Y^*; D, d, d_e)$ because they only correspond to "flipping" the input dimension in the target space and our construction ensures that the value ranges are symmetric to the origin.

An assignment is optima-preserving, if and only if it is possible to find a point in $\mathcal{Y}$ that maps to an optimum in $\mathcal{X}$ for any f. The "only if" is true because f is assumed to have an axis-aligned active subspace with d_e effective dimensions. This means that the optima in $\mathcal{X}$ only change their function values along the d_e effective dimensions. Suppose it is possible to find a point in $\mathcal{Y}$ that maps to an arbitrary optimum in $\mathcal{X}$. In that case, the assignment has to be optima-preserving because it has to be able to adjust all the d_e effective dimensions in $\mathcal{X}$ individually. However, this generally requires each effective input dimension to be mapped to a different target dimension (note that we require being able to represent the optimum for *any* f). Otherwise, there would be at least two effective input dimensions that cannot be changed independently. Therefore, the probability of Y^* is equal to the probability of an optima-preserving assignment.

As all assignments are equally likely under the construction, the probability of an assignment to be optima-preserving is equal to the number of possible optima-preserving assignments divided by the total number of assignments. There are $\binom{D}{d_e}$ ways of distributing the d_e effective dimensions across the D positions (denominator in Eq. (5)).

Let us first assume that $\beta_{\text{small}} = \beta_{\text{large}} := \beta$, i.e., all target dimensions have the same number of input dimensions and d divides D. There are $\binom{d}{d_e}$ ways of distributing the d_e effective dimensions across the d different target dimensions. Given one effective dimension, there are β ways in which this dimension can map to the target dimension. Therefore, for the case of equal bin sizes, the success probability is given by

$$p_A(Y^*; D, d, d_e) = \frac{\beta^{d_e}\binom{d}{d_e}}{\binom{D}{d_e}}. \tag{6}$$

$$D - d\beta_{\text{small}} = 2$$

small bin 1   small bin 2   small bin 3   missed

$$\boldsymbol{x}_1 \quad \boldsymbol{x}_2 \quad \boldsymbol{x}_3 \quad \boldsymbol{x}_4 \quad \boldsymbol{x}_5 \quad \boldsymbol{x}_6 \quad \boldsymbol{x}_7 \quad \boldsymbol{x}_8 \quad \boldsymbol{x}_9 \quad \boldsymbol{x}_{10} \quad \boldsymbol{x}_{11} \quad \times$$

large bin 1   large bin 2   large bin 3

$$d\beta_{\text{large}} - D = 1$$
too many

Figure 9: Example with $D = 11$ and $d = 3$. With these choices, $\beta_{\text{small}} = 3$ and $\beta_{\text{large}} = 4$. If we would only use small bins, we would miss two input dimensions (case at the top). This gives the number of large bins as each large bin has one additional input dimension, i.e., we need two large bins to cover the two missing input dimensions. If we would only use large bins, we would have one bin with one additional (fictional) input dimension. This gives the number of small bins as we need one bin with one input dimension less to achieve a correct assignment. Clearly, two large bins and one small bin cover the input dimensions correctly.

Next, we generalize Eq. (6) for cases where d does not divide D. In that case, there are two bin sizes: β_{small} and β_{large} with $\beta_{\text{large}} = \beta_{\text{small}} + 1$. There are $d\beta_{\text{large}} - D$ small bins (i.e., bins with bin size β_{small}) and $D - d\beta_{\text{small}}$ large bins: $D - d\beta_{\text{small}}$ gives the number of input dimensions that would not be covered if all bins were small. Since β_{small} and β_{large} differ by 1, this also gives the number of bins that have to be large. Conversely, if we would only have large bins, we would cover $d\beta_{\text{large}} - D$ too many input dimensions. Therefore, we need two large and one small bin (See Figure 9).

Next, we need to consider all ways of distributing the d_e effective dimensions across the the $d\beta_{\text{large}} - D$ small and $D - d\beta_{\text{small}}$ large bins (numerator in Eq. 5). Note that when we assign more effective dimensions to small or large bins than there are such bins, the binomial coefficient becomes zero and that case does not contribute to the sum. For each bin containing an effective dimensionality, there are β_{small} (or β_{large}) ways this dimension can lie in the bin (compare Figure 1). This gives the β-factors in the numerator.

It is easy to see that Eq. (5) is equivalent to the uniform formulation in Eq. (6) when d divides D. Consider the fact that $\binom{0}{0} = 1$ and $\binom{0}{x} = 0$ for all $x \in \mathbb{N}_{++}$. Then, when d divides D, $\beta_{\text{small}} = \beta_{\text{large}} = \beta$, $d(1 + \beta_{\text{small}}) - D = d$, and $D - d\beta_{\text{small}} = 0$. Therefore, the success probability for the almost-uniform case is given by

$$p_A(Y^*; D, d, d_e) = \frac{\sum_{i=0}^{d_e} \binom{d(1+\beta_{\text{small}})-D}{i}\binom{D-d\beta_{\text{small}}}{d_e-i}\beta_{\text{small}}^i \beta_{\text{large}}^{d_e-i}}{\binom{D}{d_e}}$$

$$\overset{\beta_{\text{small}}=\beta_{\text{large}}}{=} \frac{\sum_{i=0}^{d_e}\binom{d}{i}\binom{0}{d_e-i}\beta^i \beta^{d_e-i}}{\binom{D}{d_e}}$$

$$= \frac{\beta^{d_e}\sum_{i=0}^{d_e}\binom{d}{i}\binom{0}{d_e-i}}{\binom{D}{d_e}} = \frac{\beta^{d_e}\binom{d}{d_e}}{\binom{D}{d_e}},$$

where the last equality is true because the sum is zero unless $i = d_e$. $\qquad\square$

C.2 Proof of Corollary 1

We prove the equivalence of the BAXUS and the HESBO embeddings in terms for success probability.

Corollary 1. For $D \to \infty$, the success probability of the BAXUS embedding is

$$\lim_{D\to\infty} p_A(Y^*; D, d, d_e) = \frac{d!}{(d - d_e)! d^{d_e}} \tag{7}$$

and hence matches HESBO's success probability $p_H(Y^*; d, d_e)$.

Proof. The HESBO embedding is constructed by choosing a target dimension and a sign uniformly at random for each input dimension. With this construction, the HESBO embedding is independent of D. Letham et al. [38] give an expression for the HESBO success probability:

$$p_H(Y^*; d, d_e) = \frac{d!}{(d - d_e)! d^{d_e}}. \tag{8}$$

The validity of this expression can be seen by considering the probability that d_e effective input dimensions are mapped to d target dimensions without collision if $d \geq d_e$:

$$p_H(Y^*; d, d_e) = \frac{d}{d} \cdot \frac{d - 1}{d} \cdot \ldots \cdot \frac{d - d_e + 1}{d} = \prod_{i=0}^{d_e - 1} \left(1 - \frac{i}{d}\right) = \frac{d!}{(d - d_e)! d^{d_e}} \tag{9}$$

Clearly, as $D \to \infty$, the HESBO embedding has equal bin sizes; intuitively, the HESBO embedding and our formulation are equivalent in the limit.

We consider $\lim_{\beta \to \infty}$, which is equivalent to $\lim_{D \to \infty}$ as $\beta = \frac{D}{d}$ and d is fixed. We further use the uniform formulation in Eq. (6) as a starting point because all bins are of infinite size in the limit ($\lfloor \frac{D}{d} \rfloor = \lceil \frac{D}{d} \rceil$ for $D \to \infty$, $d \in \mathbb{N}_{++}$).

$$\lim_{\beta \to \infty} \frac{\beta^{d_e} \binom{d}{d_e}}{\binom{D}{d_e}} = \lim_{\beta \to \infty} \frac{\beta^{d_e} d! (D - d_e)!}{D! (d - d_e)!} \tag{10}$$

$$= \lim_{\beta \to \infty} \frac{\beta^{d_e} d! (\beta d - d_e)!}{(\beta d)! (d - d_e)!} \tag{11}$$

$$= \lim_{\beta \to \infty} \beta^{d_e} \frac{d!}{(d - d_e)!} \frac{(\beta d - d_e)!}{(\beta d)!} \tag{12}$$

$$\overset{\text{Stirling}}{=} \lim_{\beta \to \infty} \beta^{d_e} \frac{d!}{(d - d_e)!} \frac{\sqrt{2\pi(\beta d - d_e)} \left(\frac{\beta d - d_e}{e}\right)^{\beta d - d_e}}{\sqrt{2\pi \beta d} \left(\frac{\beta d}{e}\right)^{\beta d}} \tag{13}$$

$$= \lim_{\beta \to \infty} \beta^{d_e} \frac{d!}{(d - d_e)!} \sqrt{\frac{\beta d - d_e}{\beta d}} e^{d_e} \frac{(\beta d - d_e)^{\beta d - d_e}}{(\beta d)^{\beta d}} \tag{14}$$

$$= \lim_{\beta \to \infty} \beta^{d_e} \frac{d!}{(d - d_e)!} \underbrace{\sqrt{\frac{\beta d - d_e}{\beta d}}}_{\to 1} e^{d_e} \underbrace{\left(\frac{\beta d - d_e}{\beta d}\right)^{\beta d}}_{\to e^{-d_e}} \frac{1}{(\beta d - d_e)^{d_e}} \tag{15}$$

$$= \lim_{\beta \to \infty} \frac{d!}{(d - d_e)!} \underbrace{\sqrt{\frac{\beta d - d_e}{\beta d}}}_{\to 1} e^{d_e} \underbrace{\left(\frac{\beta d - d_e}{\beta d}\right)^{\beta d}}_{\to e^{-d_e}} \underbrace{\frac{\beta^{d_e}}{(\beta d - d_e)^{d_e}}}_{\to \frac{1}{d^{d_e}}} \tag{16}$$

$$= \frac{d!}{(d - d_e)! d^{d_e}} \tag{17}$$

Eq. (17) is the success probability of the HESBO embedding [38]. $\qquad \square$

C.3 Proof of Corollary 2

We prove the optimality of the BAXUS embedding in terms of success probability.

Corollary 2. With the same input, target, and effective dimensionalities (D, d, and d_e), no count-sketch type embedding has a higher success probability than the BAXUS embedding.

Proof. By Definition 1, an embedding matrix $S \in \{0, \pm 1\}^{D \times d}$ is of the count-sketch type if each row in S has exactly one non-zero entry. Such an embedding can always be interpreted as disjoint sets of signed input dimensions that are assigned to different target dimensions: For the n-th input dimension, find the column where the non-zero entry lies. The number of the respective column gives

the target dimension; the entry in the matrix itself gives the sign. Conversely, each target dimension has a set of contributing input dimensions, and we call the set of input dimensions mapping to a target dimension a "bin". The sign of the input dimensions does not influence the success probability as it does not influence the ability of an embedding to contain the optimum.

We will prove that the BAxUS embedding is optimal because every other embedding of the count-sketch type has a success probability that is lower or equal to the success probability of the BAxUS embedding. We start the proof by giving the success probability for arbitrary bin sizes.

Let β_n be the bin size of the n-th bin. By Definition 2, a success occurs if each bin contains at most one effective input dimension. The success probability for arbitrary bin sizes therefore has to consider the number of cases where each bin contains at most one effective input dimension and the number of bins containing one effective input dimensions is equal to the number of effective input dimensions d_e. In a bin of size β_i, the effective input dimension can lie in β_i different locations. Therefore, for each bin containing an effective input dimension, we have to consider all locations in which the important input dimension can lie. Bins not containing an effective dimension do not contribute to the success probability. By this reasoning, the success probability for arbitrary bin sizes is given by

$$
p_{\text{general}}(Y^*; D, d, d_e) = \frac{\overbrace{\sum_{i_1=0}^{1} \sum_{i_2=0}^{1} \cdots \sum_{i_d=0}^{1}}^{=\binom{d}{d_e}} \mathbb{1}_{(\sum_{n=1}^{d} i_n)=d_e} \prod_{n=1}^{d} \beta_n^{i_n}}{\binom{D}{d_e}},
$$
(18)

with $\beta_n > 0$, $\sum_{n=1}^{d} \beta_n = D$, and $d \geq d_e$:

First, we require $\beta_n > 0$ w.l.o.g. as bins not containing any input dimensions cannot influence the success probability. For each n from 1 to d, the value i_n indicates whether the n-th bin (or target dimension) contains an effective dimension ($i_n = 1$) or not ($i_n = 0$). The indicator variable $\mathbb{1}_{(\sum_{n=1}^{d} i_n)=d_e}$ ensures that only cases where exactly d_e bins contain an effective input dimension are considered. Note that $\sum_{i_1=0}^{1} \sum_{i_2=0}^{1} \cdots \sum_{i_d=0}^{1} \mathbb{1}_{(\sum_{n=1}^{d} i_n)=d_e} = \binom{d}{d_e}$. For each case where the d_e effective dimensions are assigned to d_e out d bins, the term $\prod_{n=1}^{d} \beta_n^{i_n}$ accounts for the locations in which the effective dimension can lie in the n-th bin. The exponent ensures that only bins actually containing an important dimension contribute to the denominator. As in Lemma 1, the numerator of Eq. (18) gives all ways of assigning d_e effective dimensions to D input dimensions. Note that for the case where $\beta_i = \beta_j$ for all $i, j \in \{1, \ldots, d\}$, Eq. (18) is equal to Eq. (6). For the case where $\beta_i \in \{\beta_s, \beta_l\}$ as defined in Section , Eq. (18) is equal to Eq. 5.

We now prove that any count sketch embedding has a success probability that is less or equal to the success probability of the BAxUS embedding. Let β_{small}, β_{large}, and $p_A(Y^*; D, d, d_e)$ as in Lemma 1. Then,

$$
p_{\text{general}}(Y^*; D, d, d_e) \leq p_A(Y^*; D, d, d_e) = \frac{\overbrace{\sum_{i=0}^{d_e} \binom{d(1+\beta_{\text{small}}) - D}{i} \binom{D - d\beta_{\text{small}}}{d_e - i}}^{=\binom{d}{d_e}} \beta_{\text{small}}^{i} \beta_{\text{large}}^{d_e - i}}{\binom{D}{d_e}}
$$
(19)

By Maclaurin's inequality, the following holds for the term $\prod_{n=1}^{d} \beta_n^{i_n}$ in the numerator of Eq. 18: $\prod_{n=1}^{d} \beta_n^{i_n} \leq \beta^{d_e}$. The numerator in Eq. (18) can also be written as $E_{d_e}(\beta_1, \ldots, \beta_d)\binom{d}{d_e}$ where $E_{d_e}(\beta_1, \ldots, \beta_d) = \frac{e_{d_e}(\beta_1, \ldots, \beta_d)}{\binom{d}{d_e}}$ is the d_e-th elementary symmetric mean and $e_{d_e}(\beta_1, \ldots, \beta_d)$ is the d_e-th elementary symmetric polynomial of $\beta_1, \ldots, \beta_d$. Then, by Maclaurin's inequality

$$
\beta^{d_e} \geq E_{d_e}(\beta_1, \ldots, \beta_d),
$$
(20)

with equality if and only if $\beta_i = \beta_j$ for $i, j \in \{1, \ldots, n\}$.

However, d does not divide D, β is no integer which is impossible. Observe that $\prod_{n=1}^{d} \beta_n^{i_n}$ is a convex function because all factors in the product are in $\mathbb{N}_{++}$. Therefore, the more the bin sizes differ from the "mean" $\beta = \frac{D}{d}$, the lower the success probability. If d does not divide D, β_{large} and β_{small} have the smallest possible difference 1. Otherwise, $\beta_{\text{small}}^{i} \beta_{\text{large}}^{d_e - i} = \beta^{d_e}$.

Therefore, the BAxUS embedding is optimal in terms of success probability. $\qquad\square$

D Consistency of BAxUS

We prove the global convergence of function values for BAxUS. The proof idea is similar to Eriksson and Poloczek [20] but relaxes the assumption of a unique global minimizer. By construction, f has an axis-aligned active subspace (see Definition 4), i.e., there exists a set of dimensions of f that do not influence the function value. Thus, an optimal solution stays optimal regardless how non-active dimensions are set. This is why we have to relax the assumption of a unique global minimizer in the input space. Instead we assume a unique global minimizer in the active subspace $\boldsymbol{z}^* \in \mathcal{Z}$ that can map to arbitrarily many minimizers in the input space.

Theorem 2 (**BAxUS convergence**). *With the following definitions:*

>   *D1. $\{\boldsymbol{x}\}_{k=1}^{\infty}$ is a decreasing sequence of incumbent function values;*

>   *D2. $\boldsymbol{x}^* \in \arg\min_{\boldsymbol{x} \in \mathcal{X}} f(\boldsymbol{x})$ is a minimizer in $\mathcal{X}$;*

and under the following assumptions:

>   *A1. D is finite;*

>   *A2. f is noiseless;*

>   *A3. The objective f has an axis-aligned active subspace and is bounded in $\mathcal{X}$, i.e., $\exists C \in \mathbb{R}_{++}$ s.t. $|f(\boldsymbol{x})| < C \; \forall \boldsymbol{x} \in \mathcal{X}$;*

>   *A4. At least one of the minimizers $\boldsymbol{x}_i^*$ lies in a continuous region with positive measure;*

>   *A5. Once BAxUS reached the input dimensionality D, the initial points $\{\boldsymbol{x}_i\}_{i=1}^{n_{\text{init}}}$ after each TR restart for BAxUS are chosen such that $\forall \delta \in \mathbb{R}_{++}$ and $\boldsymbol{x} \in \mathcal{X}$, $\exists \nu(\boldsymbol{x}, \delta) > 0$: $\mathbb{P}\left(\exists i : ||\boldsymbol{x} - \boldsymbol{x}_i||_2 \leq \delta\right) \geq \nu(\boldsymbol{x}, \delta)$, i.e., the probability that at least one point in $\{\boldsymbol{x}_i\}_{i=1}^{n_{\text{init}}}$ ends up in a ball centered at $\boldsymbol{x}$ with radius δ is at least $\nu(\boldsymbol{x}, \delta)$;*

$f(\boldsymbol{x}_k)$ converges to $f(\boldsymbol{x}^*)$ with probability 1.

Proof. We first show that BAxUS must eventually arrive at an embedding that is equivalent to the input space. By Assumption A1, the fail tolerance (i.e., the number of times BAxUS needs to fail in finding a better solution until the TR base length is shrunk) is always finite since it is always bounded by the target dimension ($\forall i \; \tau_{\text{fail}}^{i} \leq d_i$) which is at most equal to D ($\forall i \; d_i \leq D$). By the facts that BAxUS considers any sampled point an improvement only if it improves the current best solution by at least some constant $\gamma \in \mathbb{R}_{++}$ and that f is bounded (Assumption A3), BAxUS can only perform a finite number of function evaluations without increasing the target dimensionality of its embedding.

Once BAxUS reaches D, it behaves like TuRBO [21] for which Eriksson and Poloczek [20] proved global convergence assuming a unique global minimizer. For the case $d_e < D$, we notice that multiple minima in the input space occur due to non-active dimensions that do not influence the function value.

The remainder of our proof is based on the convergence theorem for global search by Solis and Wets [58] which proves convergence of function values for random search with possibly multiple minima. We note that considering the sequence of incumbent points (Definition D1) and the fact that, at each TR restart, BAxUS performs random restarts with uniform probability on $\mathcal{X}$, then BAxUS satisfies the assumptions of the theorem.

The Solis and Wets [58] theorem states that for a sequence $\{\boldsymbol{x}_k\}_{k=1}^{\infty}$ of sampling points with $\varepsilon \in \mathbb{R}_{++}$

$$\lim_{k \uparrow \infty} \mathbb{P}\left[\boldsymbol{x}_k \in R_{\varepsilon}\right] = 1,$$

where $R_\varepsilon = \{\boldsymbol{x} \in \mathcal{X} : f(\boldsymbol{x}) < \alpha + \varepsilon\}$ is the set of ε-optimal function values, $\alpha = \inf\{t : v(\boldsymbol{x} \in \mathcal{X} : f(\boldsymbol{x}) < t) > 0\}$ is the *essential infimum*, and v is the Lebesgue measure. Note that the essential infimum α is equal to the minimum if the minimizer lies in a continuous region of positive measure, i.e., $\alpha = f(\boldsymbol{x}_i^*)$. By Assumption A4 and by letting $\varepsilon \to 0$, $f(\boldsymbol{x}_k)$ converges to $f(\boldsymbol{x}_i^*)$. $\qquad\square$

E The nested family of random embeddings

We describe the method for increasing the target dimensionality under the retention of the observations. Suppose that we have collected n observations and are in target dimension d when Algorithm 2 is invoked. Algorithm 2 loops over the target dimensions $1, \ldots, d$. For each target dimension, the contributing input dimensions are randomly re-assigned to new bins of given sizes. This can, for example, be realized by, first, randomly permuting the list of contributing input dimensions, and, secondly, dividing the list into $b + 1$ chunks (bins). If the number of contributing input dimensions is less than $b + 1$ (remember that b is the number of *new* bins), then it is not possible to re-assign the contributing input dimensions to $b + 1$ bins. Therefore we re-assign the contributing input dimensions to $\hat{b} = \min(b, l_s - 1)$ bins, where l_s is the number of contributing input dimensions to the s-th target dimension. This also ensures that the target dimension never grows larger than D in the BAxUS embedding. We evenly distribute the l_s contributing input dimensions across the $\hat{b}$ bins by again using the BAxUS embedding. This gives a smaller projection matrix $\tilde{S}^\mathsf{T}$ which we finally use to update S^T:

Algorithm 2 Observation-preserving embedding increase

Input: transposed embedding matrix S^T, number of new bins per latent dimension b, observed points $Y \in [-1, 1]^{n \times d}$.
Output: updated transposed embedding matrix S^T and updated observation matrix Y
    for $s \in \{1, \ldots, d\}$ **do**
        $\boldsymbol{D}^s \leftarrow$ contributing input dimensions of s-th latent dimension of the current embedding
        $l_s \leftarrow |\boldsymbol{D}^s|$
        $\hat{b} \leftarrow \min(b, l_s - 1)$ $\triangleright$ If $l_s - 1 < b$, we can at most create $l_s - 1$ new bins.
        Copy and append s-th column of Y $\hat{b}$ times at the end of Y.
        Add $\hat{b}$ zero columns at the end of S^T.
        $\boldsymbol{\sigma} \leftarrow$ signs of dimensions $\in \boldsymbol{D}^s$.
        $\tilde{S}^\mathsf{T} \leftarrow \texttt{BAxUS-Embedding}(l_s, \hat{b} + 1)$ $\triangleright$ Re-assign input dims. equally[1], $\tilde{S}^\mathsf{T} \in \{0, \pm1\}^{l_s \times \hat{b}+1}$
        for $i \in \{1, \ldots, l_s\}, j \in \{1, \ldots, \hat{b}+1\}$ **do**
            if $\tilde{S}^\mathsf{T}_{ij} \neq 0$ **then**
                if $j > 1$ **then** $\triangleright$ Move values that fall into new bins to end of S^T.
                    $S^\mathsf{T}_{\boldsymbol{D}^s_i, \hat{d}-\hat{b}-1+j} \leftarrow \boldsymbol{\sigma}_i$ $\triangleright$ $\hat{d}$: columns of S^T
                    $S^\mathsf{T}_{\boldsymbol{D}^s_i, s} \leftarrow 0$ $\triangleright$ Set value in "old" column to zero.
    Return S^T and Y.

F Additional implementation details

We benchmark against SAASBO, TuRBO, HeSBO, Alebo, and CMA-ES:

- For SAASBO, we use the implementation from [19] (`https://github.com/martinjankowiak/saasbo`, license: none, last accessed: 05/09/2022).

- For TuRBO, we use the implementation from [21] (`https://github.com/uber-research/TuRBO`, license: Uber, last accessed: 05/09/2022).

- For HeSBO and Alebo, we use the implementation from [38] (`https://github.com/facebookresearch/alebo`, license: CC BY-NC 4.0, last accessed: 05/09/2022).

---

[1]Equally means that all $\hat{b} + 1$ bins have roughly the same number of contributing input dimensions. The number of contributing input dimensions to the different bins differ by at most 1.

832 • For the LASSO benchmarks, we use the implementation from [55] (`https://github.com/`
833   `ksehic/LassoBench`, license: `MIT` and `BSD-3-Clause`, last accessed: 05/09/2022).

834 We use `GPyTorch` to train the GP with the following setup: We place a top-hat prior one the Gaussian
835 likelihood noise, the signal variance, and the length scales of the Matérn 5/2 ARD kernel. The interval
836 for the noise is $[0.005, 0.2]$, for the signal variance $[0.05, 20]$, and for the lengthscales $[0.005, 10]$.

837 We evaluate on the synthetic BRANIN2[2] and HARTMANN6[3] functions. Since we augment the function
838 with dummy dimensions, we use the same domain for x_1 and x_2, namely $[-5, 15]^D$ for BRANIN2
839 and $[0, 1]^D$ for HARTMANN6.

840 Similar to TURBO, we sample a $\min(100d_n, 5000)$-element Sobol sequence on which we minimize
841 the posterior sample. To maximize the marginal log-likelihood of the GP, we sample 100 initial
842 hyperparameter configurations. The ten best samples are further optimized using the ADAM optimizer
843 for 50 steps.

844 We ran the experiments for approximately $7,000$ core hours on Intel Xeon Gold 6130 CPUs provided
845 by a compute cluster.

---

[2]See `https://www.sfu.ca/~ssurjano/branin.html`, last accessed: 05/09/2022
[3]See `https://www.sfu.ca/~ssurjano/hart6.html`, last accessed: 05/09/2022