DO MODELS SEE CORRUPTION AS WE SEE? AN ITEM RESPONSE THEORY BASED STUDY IN COMPUTER VISION

ABSTRACT

On a given dataset, some models perform better than others. Can we examine this performance w.r.t. different strata of the dataset rather than just focusing on an aggregate metric (such as accuracy)? Given that noise and corruption are natural in real-world settings, can we study model failure under such scenarios? For a particular corruption type, do some classes become more difficult to classify than others? To answer such fine-grained questions, in this paper, we explore the use of Item Response Theory (IRT) in computer vision tasks to gain deeper insights into the behavior of models and datasets, especially under corruption. We show that incorporating IRT can provide instance-level understanding beyond what classical metrics (such as accuracy) can provide. Our findings highlight the ability of IRT to detect changes in the distribution of the dataset when it is perturbed through corruption, using latent parameters derived from IRT models. These latent parameters can effectively suggest annotation errors, informative images, and class-level information while highlighting the robustness of different models and dataset classes under consideration.

1 INTRODUCTION

In the past two decades, remarkable advancements have been made in the field of computer vision resulting in super-human performance on various well-known benchmarks such as Imagenet (Russakovsky et al., 2015), CIFAR10/CIFAR100 (Krizhevsky et al., 2009) & MNIST(LeCun et al., 1995) courtesy of deep learning models, especially with the advent of Vision Transformers (Liu et al., 2022), (Dosovitskiy et al., 2021). However, studies have shown that classical measures of progress like accuracy are not reliable as they overestimate the capabilities of the system (Sagawa et al., 2020; Bras et al., 2020; Menon et al., 2021; Shankar et al., 2021; Patel et al., 2021). One such study, (Shankar et al., 2021) showed that model accuracy drops due to the inability to generalize to slightly "harder" images than "easy" ones, which raises the question of whether these models are uniformly better across all instances. To better understand this, consider two models, A and B. Model A is ranked higher than Model B w.r.t accuracy on the evaluation data. However, Model A classifies all easy images and fails on the 'hard' ones. In contrast, Model B classifies some 'hard' images and most of the 'easy' images but, in the aggregate, it classifies fewer images leading to lower accuracy. Thus, it is difficult to infer which model has better generalization from an accuracy-style aggregate metric alone. Thus, we argue that an instance-level analysis of evaluation data becomes necessary, especially in risk-sensitive applications.

In computer vision, researchers have tried to obtain global properties of images, including saliency, memorability, photo quality, and object importance (Liu et al., 2011; Russakovsky et al., 2015). Additionally, extrinsic anthropomorphic approaches have also been explored, such as estimating image difficulty based on the time required for human segmentation (Vijayanarasimhan & Grauman, 2009). However, in this work, we focus on assessing the difficulty of an image from the perspective of multiple models and also understand the change in the difficulty of images as they get corrupted at different severity levels. We study models and datasets from a multi-dimensional perspective. In particular, we draw upon the statistical framework of Item Response Theory (IRT) (Baker & Kim, 2004), which enables us to study model performance in relation to latent traits of samples. IRT is widely accepted in educational assessment to evaluate test items (Birnbaum, 1968). The IRT framework learns latent variables corresponding to model performance, sample difficulty,

Figure 1: This figure shows how IRT captures instance level changes as we go from Severity 1(S1) to Severity 5(S5) of corruption. Here we are considering Defocus Blur corruption on the CIFAR10 dataset. As we move from S1-S5, discriminability, and feasibility decrease, suggesting that images are getting ambiguous at higher severity levels.

and discriminability. The variable corresponding to model performance is referred to as the *ability score*. Based on the ability score, three measures are used to represent samples (questions in educational assessment, images in our context): *difficulty*, *discriminability*, and *feasibility*. *Difficulty* measures the item's hardness for the classification task. *Discriminability* measures the effectiveness of a sample in differentiating between similar models. *Feasibility* of a sample can be viewed as capturing a measure of inherent ambiguity in a sample (e.g., in educational assessment, a computer-based assessment that uses complex visual symbols may not be feasible for individuals with limited access to technology or with certain disabilities). We discuss specifics of the IRT framework used in our work in Section 2 and Figure 2.

Our key contributions and inferences in this work are summarized below:

- We estimate the difficulty of corruptions in well-known computer vision datasets using the performance of multiple models on such data, using the classical Item Response Theory framework. This is the first such effort, to the best of our knowledge.

- Using difficulty and discriminability parameters, we identify classes in these datasets that are robust and susceptible to corruption under varying difficulty. For example, we find that **Airplane** is most **robust**, and **Frog** is most **susceptible** in case of the Defocus-Blur corruption in CIFAR10.

- We observe that the detection of samples with low discriminability can aid in uncovering $\approx 30 - 40\%$ of annotation errors across CIFAR10, CIFAR100, and IMAGENET datasets.

- Our class-level analysis sheds light on the ease of distinguishability of each class. For example, in CIFAR10, we observe that **cat** and **dog** classes are the **easiest** to distinguish, whereas **ships** and **automobiles** are the **hardest**.

- Top-performing models are those that can classify a high number of difficult and discriminative samples. Unsurprisingly, we find through our studies that pretrained **Vision Transformers** are able to classify hard samples in general.

2 ITEM RESPONSE THEORY

Item Response Theory (IRT) is a widely used psychometric methodology that provides a comprehensive framework for estimating the latent traits of both items (such as exam questions) and subjects (such as test-takers). Developed as a substitute to traditional summary statistics (Edgeworth, 1888), IRT has become a widely used tool in educational testing (Birnbaum, 1968). Furthermore, its applications have extended to machine learning, with recent studies exploring its use for model and data analysis (Martínez-Plumed et al., 2016) , (Martínez-Plumed et al., 2019), (Martínez-Plumed et al., 2016), (Vania et al., 2021), evaluating test sets (Lalor et al., 2016), (Lalor & Yu, 2020), (Rodriguez et al., 2021a).

In IRT, subjects are human test-takers, and items are assessment questions. For dichotomous data, a subject's answers to a set of items are evaluated as either correct or incorrect. Given n test items $T = (T_1, T_2, ..., T_n)$ and m subjects $S = (S_1, S_2, ..., S_m)$, we create a binary response matrix $Z^{n \times m}$ where each row in the matrix represents subject $m's$ responses to all the items in the dataset, ie $z_{ij} \in [0, 1]$, where $z_{ij} = 1$ indicates a correct response and $z_{ij} = 0$ indicates an incorrect response.

2.1 IRT MODELS

We now briefly discuss existing models that are based on the Item Response Theory framework. In psychometry, IRT-Base is called a Rasch (Rasch, 1981) or a 1PL model. The 1-PL estimates a latent ability parameter θ_j for subjects and a latent difficulty parameter β_i for items. A high-performing subject will have a higher ability score. However, we can only be sure about the top-performing model being good if one keeps evaluating them on varying difficulty samples. Like our previous example, Model B should have been better in terms of accuracy. IRT handles this with ability θ and difficulty β scores. More challenging items have higher difficulty β. So, the more significant the gap between the subject skill θ_j and item difficulty β_i, the more likely the subjects will respond correctly.

Figure 2: The likelihood of the correct response is modeled as a relationship between the difficulty β_i of an item, its discriminability γ_i, its feasibility λ_i, and the subject ability θ_i.

More complex IRT models like 2PL, 3PL, and 4PL (please refer to Appendix Bfor equations) introduce additional item-specific latent parameters. We use the 4PL Model in our study, which introduces the discriminability parameter α_i and feasibility parameter λ_i. A discriminable item is challenging but can be answered by a strong subject. For example, if Model A's ability is higher than most of the items' difficulty, $(\theta_j - \beta_i)$ will be large. Discriminability multiplies this gap by γ_i, which normalizes a strong model's ability. In the context of computer vision, images with low β_i are generally easy to classify for the model. or the model is unclear about them. Feasibility captures the ambiguity of images; the 4PL model (Fig 2) imposes a cap on the probability of correctly answering an item if a significant portion of subjects has answered it incorrectly. This cap, represented by λ_i, ensures that the probability remains feasible despite many incorrect responses. Our study found that some of the low-feasibility images had annotation errors (Figure 3).

2.2 ESTIMATING PARAMETERS USING VARIATIONAL INFERENCE

We use mean field variational inference to infer IRT parameters from model responses. (Natesan et al., 2016) showed that variational inference (Jordan et al., 1998) works better than traditional methods like maximum marginal likelihood estimation (Bock & Aitkin, 1981) to calculate the latent parameters when we scale to a large dataset or a more significant number of subjects. (Lalor et al., 2019) have shown that this method effectively fits IRT models to responses on NLP datasets.

Given the data response matrix $Z^{n \times m}$, we approximate the joint probability of the parameters $p(.)$ with a variational posterior $q_\phi(.)$ with mean field assumption in Eqn 1. For each parameter, we choose the distributions mentioned in Eqn 2.

$$q_\phi(\theta, \beta, \gamma, \mu, \sigma) = q(\mu)q(\sigma)\prod_{ij} q(\theta_j)q(\beta_i)q(\gamma_i) \quad (1)$$

$$\theta_j \sim \mathcal{N}(\mu_\theta, \tau_\theta^{-1})$$
$$\beta_i \sim \mathcal{N}(\mu_\beta, \tau_\beta^{-1})$$
$$\gamma_i \sim \mathcal{N}(\mu_\gamma, \tau_\gamma^{-1})$$
$$\lambda_i \sim U[0,1]$$
$$\quad (2)$$

We fit the posterior parameters by minimizing the evidence lower bound (ELBO). Each latent z is drawn from $\mathcal{N}(\mu_\theta, \tau_\theta^{-1})$ whose parameters are also latent variables. We follow (Lalor et al., 2019) (Rodriguez et al., 2021b) for learning these latent variables.

2.3 RELIABILITY OF IRT MODELS

The IRT (Item Response Theory) test stands apart from other tests in two fundamental ways. Firstly, it recognizes that certain items are more informative than others. Secondly, it assumes that each item's degree of informativeness depends on the subject's skill level (in our case, the model's performance).

To test for the reliability of the IRT models, we compute the Kendall rank correlation between the ability score ranking and the classical ranking of the models. We also evaluate how well the IRT models predict the classical model's responses on a held-out test set. In both cases, IRT models have a high correlation. Further, Table 1 shows that the IRT model achieves high correlation even under different types of corruption.

Noises	Correlation
Elastic Transform	0.9709
Frost	0.9729
Zoom Blur	0.9698
Motion Blur	0.9776
Brightness	0.9729
Defocus Blur	0.9750
Snow	0.9735
Fog	0.9784
Spatter	0.9753

Table 1: Kendall correlation between model accuracy & ability score ranking for multiple noises (at severity level 1) on the CIFAR10 dataset.

3 EXPERIMENTAL RESULTS AND ANALYSIS

A key driving factor behind IRT is the observation that different deep learning models (equivalent to individuals with different abilities) exhibit different error patterns. For e.g., some models perform extremely well on particular strata of the dataset, whereas some perform reasonably well on all strata. IRT framework considers this phenomenon (analogous to the bandwidth-fidelity trade-off (Liu et al., 2011) in educational assessment), enabling richer comparisons between models.,

The following sections highlight the results and inferences of our study on different benchmark corrupted datasets - CIFAR10-C, and CIFAR100-C to provide a compelling use case for using Item Response Theory.

3.1 IDENTIFY ANNOTATION ERRORS?

Low feasibility and discriminable items indicate ambiguous images. Thus, we use this information to check for annotation errors in CIFAR10 and Imagenet datasets. (Northcutt et al., 2021) report annotation errors in CIFAR10 and Imagenet datasets, which we use as ground truth for validating our annotation error detection performance. We find that low discriminable and feasibile items account for $\approx 30 - 40$ percent of annotation errors in

Corruption	Susceptible Classes	Robust Classes
Defocus Blur	Frog, Truck	Airplane, Automobile
Glass Blur	Deer, Automobile	Cat, Horse
Motion Blur	Bird, Cat	Ship, Automobile
Zoom Blur	Frog, Deer	Horse, Ship
Gaussian Blur	Truck, Dog	Airplane, Horse
Elastic Transform	Automobile, Deer	Airplane, Horse
JPEG Compression	Automobile, Cat	Frog, Dog
Pixelate	Truck, Automobile	Horse, Airplane
Gaussian Noise	Cat, Ship	Airplane, Dog
Impulse Noise	Cat, Ship	Bird, Deer

Table 2: Susceptible and robust classes for various corruptions.

the dataset. This shows that IRT can help identify and remove incorrect items and enhance the model's overall performance. 3

Figure 3: Low discriminability suggests annotation errors. Left: CIFAR10, Right: Imagenet. 3.1

3.2 ANALYSIS ON CORRUPTED DATASET

We analyzed the effect of corruptions on CIFAR10-C, CIFAR100-C, and IMAGENET-C (Hendrycks & Dietterich, 2019) datasets at the instance and class level by examining the image's difficulty and discriminability scores. We sorted the images based on these scores and divided them into four categories ("easy," "medium-easy," "medium-hard," and "hard"). The robustness of a class refers to the consistency of the score achieved across different levels of corruption. Thus, we use the standard deviation of the score computed across five severity levels of corruption. We perform this operation for all of the above categories ("easy," "medium-easy," "medium-hard," and "hard") and compute the average of these standard deviation values. This becomes the robustness score for a particular class. We use this score to find the most robust (high robustness score) and most susceptible classes (low robustness score) w.r.t. a given corruption. For e.g., in the case of blur corruption on CIFAR10, 'Frog' and 'Truck' were the most susceptible, while 'Horse' and 'Ship' were the most robust. We report more such interesting results in table 2 for ten different corruptions.

The above-proposed robustness score is helpful for understanding which classes need more attention to make the model robust. For e.g., consider Fig 5, where we study the effect of brightness corruption on different classes. Here, we report the number of "easy" category images for each class for different severity levels. It can be observed that for some classes, the number of easy images decreases. For some, it remains the same, and for others, it increases. Thus, an ML practitioner could focus only on those classes that become difficult to classify as the severity of corruption increases.

3.3 DIFFICULTY AND DISCRIMINABILITY ANALYSIS

Here we perform a class-level analysis on CIFAR10, CIFAR100, and IMAGENET datasets. We used the difficulty β and discriminability γ parameters using the 4PL model Fig 2 to perform this analysis. IRT helps us analyze the model by combining discriminability and difficulty parameters. To study this, we divided the difficult and discriminable images into four segments, i.e., Easy, Med-Easy, Med-Hard, and Hard. We checked how many images in these segments a model can classify. We saw the most improvement in the high-accuracy model from correctly classifying high-difficulty images. Table 3

Models	Easy	Med_Easy	Med_Hard	Hard
Mnetv3_E1	392	281	173	157
AlexNet	1323	575	329	255
Mnetv3_E2	246	206	246	302
Mnetv3_E3	1028	633	378	335
ViTb16_E2	2283	2431	2313	2144
SwinBase_E2	2284	2428	2336	2169
R101Best	2285	2415	2252	1578
R101_E2	2287	2400	2219	1384

Table 3: Multiple models classifying varying levels of difficult samples in case of CIFAR10 Brightness noise in no particular order. E1,E2,E3 denotes intermediate checkpoints in increasing order.)

shows ViT16, a pretrained[1] model that classifies more hard samples. [2] Figure 4 shows classes with low & high difficulty and discriminable images for CIFAR10 classes. We find that in the case of CIFAR10: cat, dog, and bird are low discriminable and difficult classes. Similarly, we can see ships, trucks, and automobiles as highly discriminable and challenging classes.

Figure 4: Class level analysis on CIFAR10 based on High & Low Difficulty and Discriminable Images.

Figure 5: Exploring the Impact of Corruption on Easy Samples in CIFAR10-Brightness Corruption: Surprising Findings as Easy images persist in some classes only.

4 CONCLUSIONS

In this paper, we advocate using Item Response Theory (IRT) for evaluation in computer vision tasks instead of using the classical model accuracy. In particular, we used IRT to get a detailed and instance-level understanding of the behavior of models and datasets, particularly in the presence of noise and corruption - beyond what classical metrics such as accuracy can provide. We used the difficulty β and discriminability γ parameters of IRT to identify robust and susceptible classes w.r.t. different corruption types. We further exploited the discriminability γ parameter to detect up to 40% of the annotation errors across CIFAR10, CIFAR100, and IMAGENET datasets. We also conducted a class-level analysis, which helped shed light on the ease of distinguishability for each class. Finally, we also observed that the top-performing models could classify many difficult and discriminative samples. In summary, our findings highlight the importance of considering the impact of noise and corruption on model performance and the benefits of using IRT to analyze and improve computer vision models. We believe by incorporating IRT into computer vision tasks, researchers and practitioners can gain a more nuanced understanding of model behavior and identify potential areas for improvement in data annotation and model robustness. We hope our work can inspire further research in this area and contribute to developing more robust and reliable computer vision systems.

---

[1]Please note we have an undertrained and pretrained models

[2]Refer to Appendix A for models & dataset used.

REFERENCES

F.B. Baker and S.H. Kim. *Item Response Theory: Parameter Estimation Techniques, Second Edition*. Statistics: A Series of Textbooks and Monographs. Taylor & Francis, 2004. ISBN 9780824758257. URL https://books.google.co.in/books?id=y-Q_Q7pasJ0C.

Allan Birnbaum. Some latent trait models. *Statistical theories of mental test scores*, 1968.

R Darrell Bock and Murray Aitkin. Marginal maximum likelihood estimation of item parameters: Application of an em algorithm. *Psychometrika*, 46(4):443–459, 1981.

Ronan Le Bras, Swabha Swayamdipta, Chandra Bhagavatula, Rowan Zellers, Matthew Peters, Ashish Sabharwal, and Yejin Choi. Adversarial filters of dataset biases, 2020. URL https://openreview.net/forum?id=H1g8p1BYvS.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Francis Ysidro Edgeworth. The statistics of examinations. *Journal of the Royal Statistical Society*, 51(3):599–635, 1888.

Kaiming He, X. Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2015.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=HJz6tiCqYm.

Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, Quoc V. Le, and Hartwig Adam. Searching for mobilenetv3. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2019.

Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017.

Michael I Jordan, Zoubin Ghahramani, Tommi S Jaakkola, and Lawrence K Saul. An introduction to variational methods for graphical models. *Learning in graphical models*, pp. 105–161, 1998.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C.J. Burges, L. Bottou, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012. URL https://proceedings.neurips.cc/paper/2012/file/c399862d3b9d6b76c8436e924a68c45b-Paper.pdf.

John P Lalor and Hong Yu. Dynamic data selection for curriculum learning via ability estimation. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing*, volume 2020, pp. 545. NIH Public Access, 2020.

John P Lalor, Hao Wu, and Hong Yu. Building an evaluation scale using item response theory. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing*, volume 2016, pp. 648. NIH Public Access, 2016.

John P Lalor, Hao Wu, and Hong Yu. Learning latent parameters without human response patterns: Item response theory with artificial crowds. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing*, volume 2019, pp. 4240. NIH Public Access, 2019.

Yann LeCun, Lawrence D. Jackel, Léon Bottou, Corinna Cortes, John S. Denker, Harris Drucker, I. Ramadass Subramanian, Urs Muller, E. Sackinger, Patrice Y. Simard, and Vladimir Naumovich Vapnik. Learning algorithms for classification: A comparison on handwritten digit recognition. 1995.

Dingding Liu, Yingen Xiong, Kari Pulli, and Linda Shapiro. Estimating image segmentation difficulty. In Petra Perner (ed.), *Machine Learning and Data Mining in Pattern Recognition*, pp. 484–495, Berlin, Heidelberg, 2011. Springer Berlin Heidelberg. ISBN 978-3-642-23199-5.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 10012–10022, October 2021.

Ze Liu, Han Hu, Yutong Lin, Zhuliang Yao, Zhenda Xie, Yixuan Wei, Jia Ning, Yue Cao, Zheng Zhang, Li Dong, Furu Wei, and Baining Guo. Swin transformer v2: Scaling up capacity and resolution. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12009–12019, June 2022.

Fernando Martínez-Plumed, Ricardo BC Prudêncio, Adolfo Martínez-Usó, and José Hernández-Orallo. Making sense of item response theory in machine learning. In *ECAI 2016*, pp. 1140–1148. IOS Press, 2016.

Fernando Martínez-Plumed, Ricardo B. C. Prudêncio, Adolfo Martínez-Usó, and José Hernández-Orallo. Item response theory in ai: Analysing machine learning classifiers at the instance level. *Artificial Intelligence*, 271(C):18–42, 2019. doi: 10.1016/j.artint.2018.09.004.

Aditya Krishna Menon, Sadeep Jayasumana, Ankit Singh Rawat, Himanshu Jain, Andreas Veit, and Sanjiv Kumar. Long-tail learning via logit adjustment. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=37nvvqkCo5.

Prathiba Natesan, Ratna Nandakumar, Tom Minka, and Jonathan D Rubright. Bayesian prior choice in irt estimation using mcmc and variational bayes. *Frontiers in psychology*, 7:1422, 2016.

Curtis G Northcutt, Anish Athalye, and Jonas Mueller. Pervasive label errors in test sets destabilize machine learning benchmarks. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021. URL https://openreview.net/forum?id=XccDXrDNLek.

Kanil Patel, William H. Beluch, Bin Yang, Michael Pfeiffer, and Dan Zhang. Multi-class uncertainty calibration via mutual information maximization-based binning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=AICNpd8ke-m.

Georg Rasch. Probabilistic models for some intelligence and attainment tests. *The SAGE Encyclopedia of Research Design*, 1981.

Pedro Rodriguez, Joe Barrow, Alexander Miserlis Hoyle, John P Lalor, Robin Jia, and Jordan Boyd-Graber. Evaluation examples are not equally informative: How should that change nlp leaderboards? In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 4486–4503, 2021a.

Pedro Rodriguez, Joe Barrow, Alexander Miserlis Hoyle, John P. Lalor, Robin Jia, and Jordan L. Boyd-Graber. Evaluation examples are not equally informative: How should that change nlp leaderboards? In *Annual Meeting of the Association for Computational Linguistics*, 2021b.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115:211–252, 2015.

Shiori Sagawa, Aditi Raghunathan, Pang Wei Koh, and Percy Liang. An investigation of why overparameterization exacerbates spurious correlations. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 8346–8356. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/sagawa20a.html.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Vaishaal Shankar, Achal Dave, Rebecca Roelofs, Deva Ramanan, Benjamin Recht, and Ludwig Schmidt. Do image classifiers generalize across time? In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 9661–9669, October 2021.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, abs/1409.1556, 2014.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pp. 6105–6114. PMLR, 2019.

Clara Vania, Phu Mon Htut, William Huang, Dhara Mungra, Richard Yuanzhe Pang, Jason Phang, Haokun Liu, Kyunghyun Cho, and Samuel R Bowman. Comparing test sets with item response theory. *arXiv preprint arXiv:2106.00840*, 2021.

Sudheendra Vijayanarasimhan and Kristen Grauman. What's it going to cost you?: Predicting effort vs. informativeness for multi-label image annotations. *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2262–2269, 2009.

Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

APPENDIX

A EXPERIMENTS SETTINGS

This section talks about the models and datasets we considered for our study.

Datasets:

We experiment with CIFAR-10, CIFAR-100, and Imagenet-1K along with their corrupted counterparts, which include 19 types of algorithmically created corruptions from noise, blur, weather, and digital categories for CIFAR-10 and CIFAR-100, and 18 types of corruptions for Imagenet-1K. Each type of corruption has five severity levels resulting in 95 distinct corruptions in CIFAR-10 and CIFAR-100 and 90 in Imagenet-1K. We focused primarily on testing the reliability of IRT on various easily accessible datasets and the robustness and susceptibility of models in the presence of corrupted datasets.

Custom Test Splits - Imagenet1K and its corrupted counterpart with 18 noises do not have publicly available labeled test examples. For this, we create a new custom split by randomly sampling 50% of the validation examples as a new test set and keeping the rest for validation (25 samples per class for test and 25 samples per class for validation, for a total of 1000 classes in Imagenet-1k, this comes as 25000 samples for validation and 25000 samples for test data).

Models: For our investigation, we used various models, ranging from CNN-based to pre-trained Transformer-based models. The use of some weaker CNN-based models was justified since utilizing solely high-performing models could result in a poor IRT model fit (Martínez-Plumed et al., 2019). We use 15 deep learning models: ViTb16, ViTb32 ((Dosovitskiy et al., 2021)), Swin-Base (Liu et al., 2021), Convnext-Base, Convnext-Tiny ((Liu et al., 2022)), EfficientnetV2-Small (Tan & Le, 2019), MobilenetV2 ((Sandler et al., 2018)), MobilenetV3-Large ((Howard et al., 2019)), Alexnet (Krizhevsky et al., 2012), VGG16, VGG19 ((Simonyan & Zisserman, 2014)), Densenet121 ((Huang et al., 2017)), Resnet-18, Resnet-50, Resnet-101 ((He et al., 2015)). For all the models, we evaluate five different checkpoints—at 1%, 10%, 30%, 50%, and 70% of the maximum epochs as well as the best checkpoint on the validation set, which need not be one of the other five. This yields a total of 90 model predictions for each test example of CIFAR10 and CIFAR100.

However, with Imagenet-1K we included a few more pre-trained models' best checkpoints to achieve a satisfactory IRT model fit. We train the models using timm scripts (Wightman, 2019)

B DIFFERENT IRT MODELS

In continuation to the above section about the IRT models 2.1, here we highlight the different IRT models present.

$$p(y_{ij} = 1 | \alpha_i, \beta_i, \theta_j) = \frac{1}{1 + e^{-\alpha_i(\theta_j - \beta_i)}} \tag{3}$$

$$p(y_{ij} = 1 | \alpha_i, \beta_i, \gamma_i, \theta_j) = \gamma_i + \frac{1 - \gamma_i}{1 + e^{-\alpha_i(\theta_j - \beta_i)}} \tag{4}$$

$$p(y_{ij} = 1 | \alpha_i, \beta_i, \lambda_i, \theta_j) = \frac{\lambda_i}{1 + e^{-\alpha_i(\theta_j - \beta_i)}} \tag{5}$$

C   HARD AND EASY IMAGENET SAMPLES

Figure 6: These are the some of the hard images we got after calculating the difficulty scores β_i for the imagenet dataset.

Figure 7: These are the some of the easy images we got after calculating the difficulty scores β_i for the imagenet dataset.

D   EFFECT OF CORRUPTION ON CIFAR10

This section gives more examples mentioned in Section 3.2

Figure 8: Low discriminable class-level samples changes in CIFAR10 dataset when exposed to the JPEG Corruption. For Eg. Dog classes shows increase in low discriminable samples, airplane shows decrease in samples.

Figure 9: High discriminable class-level samples changes in CIFAR10 dataset when exposed to the JPEG Corruption. For eg. Bird samples are increasing, while frog samples are decreasing.

Figure 10: Easy and Hard class-level instance change when perturbed to Brightness Corruptions.

Figure 11: Low and High discriminable class-level instance change when perturbed to Brightness Corruptions.