GROUP EQUIVARIANT CONDITIONAL NEURAL PROCESSES

ABSTRACT

We present the group equivariant conditional neural process (EquivCNP), a meta-learning method with permutation invariance in a data set as in conventional conditional neural processes (CNPs), and it also has transformation equivariance in data space. Incorporating group equivariance, such as rotation and scaling equivariance, provides a way to consider the symmetry of real-world data. We give a decomposition theorem for permutation-invariant and group-equivariant maps, which leads us to construct EquivCNPs with an infinite-dimensional latent space to handle group symmetries. In this paper, we build architecture using Lie group convolutional layers for practical implementation. We show that EquivCNP with translation equivariance achieves comparable performance to conventional CNPs in a 1D regression task. Moreover, we demonstrate that incorporating an appropriate Lie group equivariance, EquivCNP is capable of zero-shot generalization for an image-completion task by selecting an appropriate Lie group equivariance.

1 INTRODUCTION

Data symmetry has played a significant role in the deep neural networks. In particular, a convolutional neural network, which play an important part in the recent achievements of deep neural networks, has translation equivariance that preserves the symmetry of the translation group. From the same point of view, many studies have aimed to incorporate various group symmetries into neural networks, especially convolutional operation (Cohen et al., 2019; Defferrard et al., 2019; Finzi et al., 2020). As example applications, to solve the dynamics modeling problems, some works have introduced Hamiltonian dynamics (Greydanus et al., 2019; Toth et al., 2019; Zhong et al., 2019). Similarly, Quessard et al. (2020) estimated the action of the group by assuming the symmetry in the latent space inferred by the neural network. Incorporating the data structure (symmetries) into the models as inductive bias, can reduce the model complexity and improve model generalization.

In terms of inductive bias, meta-learning, or learning to learn, provides a way to select an inductive bias from data. Meta-learning use past experiences to adapt quickly to a new task $\mathcal{T} \sim p(\mathcal{T})$ sampled from some task distribution $p(\mathcal{T})$. Especially in supervised meta-learning, a task is described as predicting a set of unlabeled data (target points) given a set of labeled data (context points). Various works have proposed the use of supervised meta-learning from different perspectives (Andrychowicz et al., 2016; Ravi & Larochelle, 2016; Finn et al., 2017; Snell et al., 2017; Santoro et al., 2016; Rusu et al., 2018). In this study, we are interested in neural processes (NPs) (Garnelo et al., 2018a;b), which are meta-learning models that have encoder-decoder architecture (Xu et al., 2019). The encoder is a permutation-invariant function on the context points that maps the contexts into a latent representation. The decoder is a function that produces the conditional predictive distribution of targets given the latent representation. The objective of NPs is to learn the encoder and the decoder, so that the predictive model generalizes well to new tasks by observing some points of the tasks. To achieve the objective, an NP is required to learn the shared information between the training tasks $\mathcal{T}, \mathcal{T}' \sim p(\mathcal{T})$: the data knowledge Lemke et al. (2015). Each task $\mathcal{T}$ is represented by one dataset, and multiple datasets are provided for training NPs to tackle a meta-task. For example, we consider a meta-task that completing the pixels that are missing in a given image. Often, images are taken by the same condition in each dataset, respectively. While the datasets contain identical subjects of images (e.g., cars or apples), the size and angle of the subjects in the image may be different; the datasets have group symmetry, such as scaling and rotation. Therefore, it is expected that pre-constraining NPs to have group equivariance improves the performance of the NPs at those datasets.

In this paper, we investigate the group equivalence of NPs. Specifically, we try to answer the following two questions, (1) can NPs represent equivariant functions? (2) can we explicitly induce the group equivariance into NPs? In order to answer the questions, we introduce a new family of NPs, EquivCNP, and show that EquivCNP is a permutation-invariant and group-equivariant function theoretically and empirically. Most relevant to EquivCNP, ConvCNP (Gordon et al., 2019) shows that using general convolution operation leads to the translation equivariance theoretically and experimentally; however it does not consider incorporation of other groups. First, we introduce the decomposition theorem for permutation-invariant and group-equivariant maps. The theorem suggests that the encoder maps the context points into a latent variable, which is a functional representation, in order to preserve the data symmetry. Thereafter, we construct EquivCNP by following the theorem. In this study, we adopt LieConv (Finzi et al., 2020) to construct EquivCNP for practical implementation. We tackle a 1D synthetic regression task (Garnelo et al., 2018a;b; Kim et al., 2019; Gordon et al., 2019) to show that EquivCNP with translation equivariance is comparable to conventional NPs. Furthermore, we design a 2D image completion task to investigate the potential of EquivCNP with several group equivariances. As a result, we demonstrate that EquivCNP enables zero-shot generalization by incorporating not translation, but scaling equivariance.

2 RELATED WORK

2.1 NEURAL NETWORKS WITH GROUP EQUIVARIANCE

Our works build upon the recent advances in group equivariant convolutional operation incorporated into deep neural networks. The first approach is group convolution introduced in (Cohen & Welling, 2016), where standard convolutional kernels are used and their transformation or the output transformation is performed with respect to the group. This group convolution induces exact equivariance, but only to the action of discrete groups. In contrast, for exact equivariance to continuous groups, some works employ harmonic analysis so as to find the basis of equivariant functions, and then parameterize convolutional kernels in the basis (Weiler & Cesa, 2019). Although this approach can be applied to any type of general data (Anderson et al., 2019; Weiler & Cesa, 2019), its implementation is costly and is limited to local application to compact, unimodular groups. To address these issues, LieConv (Finzi et al., 2020) and other works (Huang et al., 2017; Bekkers, 2019) use Lie groups. Our EquivCNP chooses LieConv to manage group equivariance for simplicity of the implementation.

There are several works that study deep neural networks using data symmetry. In some works, in order to solve machine learning problems such as sequence prediction or reinforcement learning, neural networks attempt to learn a data symmetry of physical systems from noisy observations directly (Greydanus et al., 2019; Toth et al., 2019; Zhong et al., 2019; Sanchez-Gonzalez et al., 2019). Therefore, with respect to learning the objective from the data, EquivCNP resembles these studies except that EquivCNP is not limited to domains such as physics. Furthermore, Quessard et al. (2020) let the latent space into which neural networks map data, have group equivariance, and estimated the parameters of the group equivariance. In terms of using group equivariance in the latent space, EquivCNP is similar to this study but differs from being able to use various group equivariance.

2.2 FAMILY OF NEURAL PROCESSES

NPs (Garnelo et al., 2018a;b) are deep generative models for regression functions that map an input $x_i \in \mathbb{R}^{d_x}$ into an output $y_i \in \mathbb{R}^{d_y}$. In particular, given an arbitrary number of observed data points $(x_C, y_C) \coloneqq \{(x_i, y_i)\}_{i=1}^{C}$, NPs model the conditional distribution of the target value y_T at some new, unobserved target data point x_T, where $(x_T, y_T) \coloneqq \{(x_j, y_j)\}_{j=1}^{T}$. Fundamentally, there are two NP variants: deterministic and probabilistic. Deterministic NPs (Garnelo et al., 2018a), known as conditional NPs (CNPs), model the conditional distribution as:

$$p(y_T|x_T, x_C, y_C) \coloneqq p(y_T|x_T, r_C),$$

where r represents a function that maps data sets (x_C, y_C) into a finite-dimensional vector space in a permutation-invariant way and $r_C \coloneqq r(x_C, y_C) \in \mathbb{R}^d$ is the feature vector. The function r can be implemented by DeepSets (Zaheer et al., 2017). The likelihood $p(y_T|x_T, r_C)$ is modeled by Gaussian distribution factorized across the targets (x_j, y_j) with mean and variance of prediction $\{(x_j, y_j)\}_{j=1}^{T}$ by passing inputs r_C and x_j through the MLP. The CNP is trained by maximizing the likelihood.

Probabilistic NPs include a latent variable z. The NP infers $q(z|r_C)$ given an input r_C using the reparametrization trick (Kingma & Welling, 2013) and models such a conditional distribution as:

$$p(y_T|x_T, x_C, y_C) := \int p(y_T|x_T, r_C, z)q(z|r_C)dz$$

and it is trained by maximizing an ELBO: $\mathcal{L}(\phi, \theta) = \mathbb{E}_{z \sim q_\phi(z|x_T, y_T)}[\log p_\theta(y_T|x_T)] - KL[q_\phi(z|x_T, y_T)\|p_\theta(z|x_C, y_C)]$.

NPs have various useful properties: i) Scalability: the computational cost of NPs scales as $\mathcal{O}(n + m)$ with respect to n contexts and m targets of data, ii) Flexibility: NPs can define a conditional distribution of an arbitrary number of target points, conditioning an arbitrary number of observations, iii) Permutation invariance: the encoder of NPs uses Deepsets (Zaheer et al., 2017) to make the target prediction permutation invariant. Thanks to these properties, Galashov et al. (2019) replace Gaussian processes in Bayesian optimization, contextual multi-armed bandit, and Sim2Real tasks.

While there are many NP variants (Kim et al., 2019; Louizos et al., 2019; Xu et al., 2019) to improve the performance of NPs, those do not take group equivariance into account yet. The most similar to EquivCNP, ConvCNP (Gordon et al., 2019) incorporated only translation equivariance. In contrast, EquivCNP can incorporate not only translation but also other groups such as rotation and scaling.

3 DECOMPOSITION THEOREM

In this section, we consider group convolution. We first prepare some definition and teminology. Let $\mathcal{X}$ and $\mathcal{Y} \subset \mathbb{R}$ be the input space and output space, respectively. We define as $\mathcal{Z}_M = (\mathcal{X} \times \mathcal{Y})^M$ as a collection of M input-output pairs, $\mathcal{Z}_{\leq M} = \bigcup_{m=1}^{M} \mathcal{Z}_m$ as the collection of at most M pairs, and $\mathcal{Z} = \bigcup_{m=1}^{\infty} \mathcal{Z}_m$ as the collection of finitely many pairs. Let $[n] = \{1, \ldots, n\}$ for $n \in \mathbb{N}$, and let $\mathbb{S}_n$ be the permutation group on $[n]$. The action of $\mathbb{S}_n$ on $\mathcal{Z}_n$ is defined as

$$\pi Z_n := ((\boldsymbol{x}_{\pi(1)}, \boldsymbol{y}_{\pi(1)}), \ldots, (\boldsymbol{x}_{\pi(n)}, \boldsymbol{y}_{\pi(n)})),$$

where $\pi \in \mathbb{S}_n$ and $Z_n \in \mathcal{Z}_n$. We define the multiplicity of $Z_n = ((\boldsymbol{x}_1, \boldsymbol{y}_1), \ldots, (\boldsymbol{x}_n, \boldsymbol{y}_n)) \in \mathcal{Z}_n$ by

$$\text{mult}(Z_n) := \sup\{|\{i \in [m] : \boldsymbol{x}_i = \hat{\boldsymbol{x}}\}| : \hat{\boldsymbol{x}} = \boldsymbol{x}_1, \ldots, \boldsymbol{x}_m\}$$

and the multiplicity of $\mathcal{Z}' \subseteq \mathcal{Z}$ by $\text{mult}(\mathcal{Z}') := \sup_{Z_m \in \mathcal{Z}'} \text{mult}(Z_n)$. Then, a collection $\mathcal{Z}' \subseteq \mathcal{Z}$ is said to have multiplicity K if $\text{mult}(\mathcal{Z}') = K$.

Mathematically, symmetry is described in terms of group action. The following group equivariant maps represent to preserve the symmetry in data.

Definition 1 (Group Equivariance and Invariance). *Suppose that a group G acts on sets $\mathcal{S}$ and $\mathcal{S}'$. Then, a map $\Phi : \mathcal{S} \to \mathcal{S}'$ is called G-equivariant when $\Phi(g \cdot s) = g \cdot \Phi(s)$ holds for arbitrary $g \in G$ and $s \in \mathcal{S}$. In particular, when G acts on $\mathcal{S}'$ trivially (i.e., $g \cdot s' = s'$ for $g \in G$ and $s' \in \mathcal{S}'$), the G-equivariant map is said to be G-invariant: $\Phi(g \cdot s) = \Phi(s)$.*

Then, we can derive the following theorem, which decompose a permutation-invariant and group equivariant function into two tractable functions.

Theorem 2 (Decomposition Theorem). *Let G be a group. Let $\mathcal{Z}'_{\leq M} \subseteq (\mathcal{X} \times \mathcal{Y})_{\leq M}$ be topologically closed, permutation-invariant and G-invariant with multiplicity K. For a function $\Phi : \mathcal{Z}'_{\leq M} \to C_b(\mathcal{X}, \mathcal{Y})$, the following conditions are equivalent:*

(I) Φ is continuous, permutation-invariant and G-equivariant.

(II) There exist a function space $\mathcal{H}$ and a continuous G-equivariant function $\rho : \mathcal{H} \to C_b(\mathcal{X}, \mathcal{Y})$ and a continuous G-invariant interpolating kernel $\psi : \mathcal{X}^2 \to \mathbb{R}$ such that

$$\Phi(Z) = \rho\left(\sum_{i=1}^{m} \phi_{K+1}(y_i)\, \psi_{\boldsymbol{x}_i}\right)$$

where $\phi_{K+1} : \mathcal{Y} \to \mathbb{R}^{K+1}$ is defined by $\phi_{K+1}(y) := [1, y, y^2, \ldots, y^K]^\top$.

Thanks to the Theorem 2, we can construct the permutation-invariant and group-equivariant NPs whose form of encoder and decoder is determined.

4 GROUP EQUIVARIANT CONDITIONAL NEURAL PROCESSES

In this section, we represent EquivCNP that is a permutation-invariant and group-equivariant map. First, Section 4.1 introduce the definition of group convolution, and then Section 4.2 explains LieConv (Finzi et al., 2020) used for EquivCNP to implement group convolution. Finally, we describe the architecture of proposed EquivCNP in Section 4.3.

4.1 GROUP CONVOLUTION

When $\mathcal{X}$ is a homogenous space of a group G, the lift of $x \in \mathcal{X}$ is the element of group G that transfers a fixed origin o to x : $\mathrm{Lift}(x) = \{u \in G \colon uo = x\}$. That is, each pair of coordinates and features is lifted into K elements : $\{(x_i, f_i)\}_{i=1}^{N} \to \{(u_{ik}, f_i)\}_{i=1,k=1}^{N,K}$. When the group action is transitive, the space on which it acts on is a homogenous space. More generally, however, the action is not transitive, and the total space contains an infinite number of orbits. Consider a quotient space $Q = \mathcal{X}/G$, which consists of orbits of G in $\mathcal{X}$. Then each element $q \in Q$ is a homogenous space of G. Because many equivariant maps use this information, the total space should be $G \times \mathcal{X}/G$, not G. Hence, $x \in \mathcal{X}$ is lifted to the pair (u, q), where $u \in G$ and $q \in Q$.

Group convolution is a generalization of convolution by translation, which is used in images, etc., to other groups.

Definition 3 (Group Convolution (Kondor & Trivedi, 2018; Cohen et al., 2019))**.** *Let $g, f \colon G \times Q \to \mathbb{R}$ be functions, and let $\mu(\cdot)$ be a Haar measure on G. For any $u \in G$, the convolution of f by g is defined as*

$$h(u, q) = \int_{G \times Q} g(v^{-1}u, q, q') f(v, q') d\mu(v) dq'.$$

By the definition, we can verify that the group convolution is G-equivariant. Moreover, Cohen et al. (2019) recently showed that a G-equivariant linear map is represented by group convolution when the action of a group is transitive.

4.2 LOCAL GROUP CONVOLUTION

In this study, we used LieConv as a group convolution (Finzi et al., 2020). LieConv is a convolution that can handle Lie groups in group convolutions. LieConv acts on a pair $(x_i, f_i)_{i=1}^{N}$ of coordinates $x_i \in \mathcal{X}$ and values $f_i \in V$ in vector space V. First, input data x_i is transformed (lifted) into group elements u_i and orbits q_i. Next, we define the convolution range based on the invariant (pseudo) distance in the group, and convolve it using a kernel parameterized by a neural network.

What is important for inductive bias and computational efficiency in convolution is that the range of convolutions is local; that is, if $\|u_i - u_j\| > r$, then $g_\theta(u_i, u_j) = 0$. First, we define distance in the Lie group to deal with locality in the matrix group:

$$d(u, v) := \|\log(u^{-1}v)\|_F$$

log denotes the matrix logarithm, and F denotes the Frobenius norm. Because $d(wu, wv) = \|\log(u^{-1}w^{-1}wv)\|_F = d(u, v)$ holds, this function is left-invariant and is a pseudo-distance.[1]

To further account for orbit q, we extend the distance to $d((u_i, q_i), (v_j, q_j))^2 = d(u_i, v_j)^2 + \alpha\|q_i - q_j\|^2$. It is not necessarily invariant to the transformation in q.

Based on this distance, the neighborhood is $nbhd(u) = \{v, q | d((u_i, q_i), (v_i, q_j)) < r\}$. The radius r should be adjusted appropriately from the ratio of the range of convolutions to the total input, because the appropriate value is difficult to determine depending on the group treated. Therefore, the Lie group convolution is

$$h(u, q) = \int_{v, q' \in \mathrm{nbhd(u)}} g_\theta(v^{-1}u, q, q') f(v, q') d\mu(v) dq'.$$

---

[1]Because the trigonometric inequality is not satisfied.

Figure 1: Overview of EquivCNP.

Radius r of the neighborhood corresponds to the inverse of the density channel $h^{(0)}$ in Gordon et al. (2019).

Discrete Approximation. Given a lifted input data point $\{(v_j, q_j)_{j=1}^N\}$ and a function value $f_j = f(v_j, q_j)$ at each point, we need to select a target $\{(u_i, q_i)_{i=1}^N\}$ to convolve so that we can approximate the integral of the equation. Because the convolutional range is limited by $\mathrm{nbhd}(u)$, LieConv can approximate the integrals by the Monte Carlo method :

$$h(u, q) = (g \hat{*} f)(u, q) = \frac{1}{n} \sum_{v, q' \in \mathrm{nbhd}(u,q)} g(v_j^{-1} u, q, q') f(v_j, q')$$

The classical convolutional filter kernel $g(\cdot)$ is only valid for discrete values and is not available for continuous group elements. Therefore, pointconv/Lieconv uses a multilayered neural network g_θ as a convolutional kernel. However, because neural networks are good at computation in Euclidean space, and input G is not a vector space, we let g_θ be a map in the Lie algebra $\mathfrak{g}$. Therefore, we use Lie groups in which the matrix exponential map is surjective, and logarithmic maps exist in each element of the group. That is, let $g_\theta(u) = (g \circ \exp)_\theta(\log u)$, and parameterize $\tilde{g}_\theta = (g \circ \exp)_\theta$ by MLP. We use $\tilde{g}_\theta : \mathfrak{g} \to \mathbb{R}^{c_{out} \times c_{in}}$. Therefore, the convolution of the equation is

$$h_i = \frac{1}{n_i} \sum_{j \in \mathrm{nbhd}(i)} \tilde{g}_\theta \left(\log \left(v_j^{-1} u_i \right), q_i, q_j \right) f_j.$$

Here, the input to the MLP is $a_{ij} = \mathrm{Concat}\left([\log(v_j^{-1} u_i), q_i, q_j)] \right)$.

4.3 ARCHITECTURE

EquivCNP models the same conditional distribution as well as CNPs:

$$p(\boldsymbol{Y}_T | \boldsymbol{X}_T, \mathcal{D}_C) = \prod_{n=1}^N p\left(\boldsymbol{y}_n | \Phi_{\boldsymbol{\theta}}(\mathcal{D}_C)(\boldsymbol{x}_n) \right)$$

$$= \prod_{n=1}^N \mathcal{N}\left(\boldsymbol{y}_n; \boldsymbol{\mu}_n, \boldsymbol{\Sigma}_n \right) \text{ with } (\boldsymbol{\mu}_n, \boldsymbol{\Sigma}_n) = \Phi_{\boldsymbol{\theta}}(\mathcal{D}_C)(\boldsymbol{x}_n)$$

where $\mathcal{D}_C = (\boldsymbol{X}_C, \boldsymbol{Y}_C) = \{(x_c, y_c)\}_{i=1}^C$ is the observed context data and ϕ is a EquivDeepSet. The important components of EquivCNP to be determined are $\rho, \ \phi, \ $ and ψ. The algorithm is represented in Algorithm 1.

First, we explain the form of ϕ. Because most real-world data have a single output per one input location, we treat the multiplicity of $\mathcal{D}_C$ as one, $K = 1$, and define $\phi(y) = \begin{bmatrix} 1 & y \end{bmatrix}^\top$ based on (Zaheer et al., 2017). The first dimension of output ϕ_i indicates whether the data located at x_i is observed, so that the model can distinguish between the observed data, and the unobserved data whose value is zero ($y_i = 0$).

Then, we describe the form of ψ. Following our Theorem 2, ψ is required to be stationary, non-negative, and a positive–definite kernel. For EquivCNP, we change ψ depending on whether the input

---

Algorithm 1 Group Equivariant Conditional Neural Process

Input: $\rho =$ LieConv, RBF kernel ψ, context $\{\boldsymbol{x}_i, y_i\}_{i=1}^N$, target $\{\boldsymbol{x}_j^*\}_{j=1}^M$

   lower, upper $\leftarrow$ range$((\boldsymbol{x}_i)_{i=1}^N \cup (\boldsymbol{x}_j)_{j=1}^M)$

   $(\boldsymbol{t}_k)_{k=1}^T \leftarrow$ uniform_grid(lower, upper; γ)

   $\boldsymbol{h} \leftarrow \sum_{i=1}^N \phi_{K+1}(y_i)\psi([\boldsymbol{x}_j^*, \boldsymbol{t}_k], \boldsymbol{x}_i)$

   $(\boldsymbol{\mu}_j, \boldsymbol{\Sigma}_j)^\top =$ LieConvNet$(\boldsymbol{h})(\boldsymbol{x}_j^*)$

Output: $\{(\boldsymbol{\mu}_j, \boldsymbol{\Sigma}_j)\}_{j=1}^M$

Table 1: Log-likelihood of synthetic 1-dimensional regression

Model	RBF	Matern	Periodic
Oracle GP	3.9335 ± 0.5512	3.7676 ± 0.3542	1.2194 ± 5.6685
CNP (Garnelo et al., 2018a)	-1.7468 ± 1.5415	-1.7808 ± 1.3124	-1.0034 ± 0.5174
ConvCNP (Gordon et al., 2019)	1.3271 ± 1.0324	0.8189 ± 0.9366	-0.4787 ± 0.5448
EquivCNP (ours)	1.2930 ± 1.0113	0.6616 ± 0.6728	-0.4037 ± 0.4968

data is continuous or discrete. With continuous input data (e.g. 1D regression), we use RBF kernels for ψ. An RBF kernel has a learnable bandwidth parameter and scale parameter and is optimized with EquivCNP. A functional representation $E(Z)$ is made up by multiplying the kernel ϕ with ϕ. On the other hand, when the inputs are discrete (e.g. images), we use not an RBF kernel but LieConv.

Finally, we explain the form of ρ. With our Theorem 2, because ρ needs to be a continuous group equivariant map between function spaces, we use LieConv for ρ. In this study, under the hypothesis of separability (Kaiser et al., 2017), we implemented separable LieConv in the spatial and channel directions, to improve the efficiency of computational processing. The details are given in the Appendix B. Although we want to convolve $E(Z)$ by LieConv, the current $E(Z)$ does not form to be convolved due to using the functional representation $\psi(\cdot, x)$. To address this issue, we discretize $E(Z)$ over the range of context and target points. We space the lattice points $(t_i)_{i=1}^n \subseteq \mathcal{X}$ on a uniform grid over a hypercube covering both the context and target points. Because the conventional convolution that is used in ConvCNP requires discrete lattice input space to operate on and produces discrete outputs, we need to back the outputs to continuous functions $\mathcal{X} \rightarrow \mathcal{Y}$. While ConvCNP regards the outputs as weights for evenly-spaced basis functions (i.e., RBF kernel), LieConv does not require the input location to be lattice and can produce continuous functions output directly. Note that the algorithm of EquivCNP can be the same as ConvCNP; it can also use evenly-spaced basis functions. The obtained functions are used to output the Gaussian predictive mean and the variance at the given target points. We can evaluate EquivCNP by log-likelihood using the mean and variance.

5 EXPERIMENT

To investigate the potential of EquivCNP, we constructed two questions: 1) Is EquivCNP comparable to conventional NPs such as ConvCNP? and 2) Can EquivCNP have group equivariance in addition to translation equivariance and 3) does it preserve the symmetries? To compare fairly with ConvCNP, the architecture of EquivCNP follows that of ConvCNP; details are given in the Appendix C.

5.1 1D SYNTHETIC REGRESSION TASK

To answer the first question, we tackle the 1D synthetic regression task as has been done in other papers (Garnelo et al., 2018a;b; Kim et al., 2019). At each iteration, a function f is sampled from a given function distribution, then, some of the context $\mathcal{D}_C$ and target $\mathcal{D}_T$ points are sampled from function f. In this experiment, we selected the Gaussian process with RBF kernel, Matern-$\frac{5}{2}$ and periodic kernel for the function distribution. We chose translation equivariance $T(1)$ to incorporate into EquivCNP. We compared EquivCNP with GP (as an oracle), with CNP (Garnelo et al., 2018a) as a baseline, and with ConvCNP.

Figure 2: Predictive mean and variance of ConvCNP and EquivCNP. The first two columns show the prediction of the models trained on the RBF kernel and the last two columns show the prediction of the model trained on the Matern–$\frac{5}{2}$ kernel. The target function and sampled data points are the same between the top row and bottom row except for the context. At the top row, the context is within the vertical dash line that is sampled from the same range during the training (black circle). In the bottom row, the new context located out of the training range (white circle) is appended.

Table 1 shows the log–likelihood means and standard deviations of 1000 tasks. In this task, both contexts and targets are sampled from the range $[-2, 2]$. From Table 1, we can see that EquivCNP with translation equivariance is comparable to ConvCNP throughout all GP curve datasets. That is, EquivCNP has the model capacity to learn the functions as well as ConvCNP.

We also conducted the extrapolation regression proposed in (Gordon et al., 2019) as shown in Figure 2. The first two columns show the models trained on an RBF kernel and the last two columns on a Matern–$\frac{5}{2}$ kernel. The top row shows the predictive distribution when the observation is given within the same training region; the bottom row for the observation is not only the training region but also the extrapolation region: $[-4, 4]$. As a result, EquiveCNP can generalize to the observed data whose range is not included during training. This result was expected because Gordon et al. (2019) has mentioned that translation equivariance enables the models to adapt to this setting.

5.2   2D IMAGE-COMPLETION TASK

An image-completion task aims to investigate that EquivCNP can complete the images when it is given an appropriate group equivariance. The image-completion task can be regarded as a regression task that predicts the value of y_i^* at the 2D image coordinates x_i^*, given the observed pixels $\mathcal{D}_C = \{(x_n, y_n)\}_{n=1}^N$ ($\in \mathbb{R}^3$ for the colored image input, and $\in \mathbb{R}$ for the grayscale image input). The framework of the image completion can apply not only to the images but also to other real-world applications, such as predicting spatial data (Takeuchi et al., 2018).

To evaluate the effect of EquivCNP with a specific group equivariance, we introduce a new dataset digital clock digits as shown in Figure 3. While previous works use the MNIST dataset for image completion, we consider that MNIST already contains diverse group equivariance possibly, and it is not suitable for evaluating EquivCNP with group equivariance: translation, scaling, and rotation. In this experiment, we used four kinds of group equivariance; translation group $T(2)$, the 2D rotation group $SO(2)$, the translation and rotation group $SE(2)$, and the rotation-scale group $R \times SO(2)$. The size of the images is 64×64 pixels, and the numbers are in the center with the same vertical length. For the test data, we transform the images by scaling within $[0.15, 0.5]$ and rotating within $[-90°, +90°]$. Image completion with our digits data becomes an extrapolation task in that the test data is never seen during training, though the number shapes are the same in both sets.

The log–likelihood of image completion by EquivCNP with the group equivariance is reported in Table 2. The mean and standard deviation of the log–likelihood is calculated over 1000 tasks (i.e. evaluating the digit transformed in 100 times respectively). As a result, EquivCNP with $R \times SO(2)$ performed better than other group equivarinace. On the other hand, the model with $SO(2)$ had the worst performance. This might happen because the $SO(2)$ is not able to generalize EquivCNP to

Table 2: Log-likelihood of 2D image-completion task

Group	Log–likelihood
$T(2)$	1.0998 ± 0.4115
$SO(2)$	-2.4275 ± 6.8856
$R \times SO(2)$	$\mathbf{1.8398 \pm 0.5368}$
$SE(2)$	1.1655 ± 0.5420

Figure 3: The example of training data (top) and test data (bottom).

Figure 4: Image-completion task results. The top row shows the given observation and the other rows show the mean of the conditionaldistribution predicted by EquivCNP with the specific group equivariance: $T(2)$, $SO(2)$, $R \times SO(2)$, and $SE(2)$. Two of each column shows the same image, and the difference between two columns is the percentage of context random sampling: 25% and 75%. When the size of digits is the same as that of the training set, $T(2)$ and $SE(2)$ have a good quality, but when the size of digits is smaller than that of training set, $R \times SO(2)$ has a good performance.

scaling. In fact, the log–likelihood of $SE(2)$, which is the group equivariance combining translation $T(2)$ and rotation $SO(2)$, is not improved than that of $T(2)$.

Figure 4 shows the qualitative result of image completion by EquivCNP with each group equivariance. We demonstrate that EquivCNP was able to predict digits smaller than the training digits. While $T(2)$ completes the images most clearly when the sizes of digits and the number of observations are large, other groups also complete the images. The smaller the size of digits is compared to the training digits, the worse the quality of $T(2)$ completion becomes, and $R \times SO(2)$ completes the digits more clearly. This is because the convolution region of $T(2)$ is invariant to the location, while that of $R \times SO(2)$ is adaptive to the location. As a result, for the images transformed by scaling, we can see that EquivCNP with $R \times SO(2)$ preserved scaling group equivariance.

6 DISCUSSION

We presented a new neural process, EquivCNP, that uses the group equivariant adopted from LieConv. Given a specific group equivariance, such as translation and rotation as inductive bias, EquivCNP has a good performance at regression tasks. This is because the kernel size changes depending on the specific equivariance. Real–world applications, such as robot learning tasks (e.g. using hand-eye camera) will be left as future work. We also hope EquivCNPs will help in learning group equivariance (Quessard et al., 2020) by data–driven approaches for future research.

REFERENCES

Brandon Anderson, Truong Son Hy, and Risi Kondor. Cormorant: Covariant molecular neural networks. In *Advances in Neural Information Processing Systems*, pp. 14510–14519, 2019.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in neural information processing systems*, pp. 3981–3989, 2016.

Erik J Bekkers. B-spline cnns on lie groups. *arXiv preprint arXiv:1909.12057*, 2019.

Francois Chollet. Xception: Deep learning with depthwise separable convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1251–1258, 2017.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pp. 2990–2999, 2016.

Taco S Cohen, Mario Geiger, and Maurice Weiler. A general theory of equivariant cnns on homogeneous spaces. In *Advances in Neural Information Processing Systems*, pp. 9142–9153, 2019.

Michaël Defferrard, Nathanaël Perraudin, Tomasz Kacprzak, and Raphael Sgier. Deepsphere: towards an equivariant graph-based spherical cnn. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019. URL https://arxiv.org/abs/1904.05146.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1126–1135. JMLR. org, 2017.

Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data. *arXiv preprint arXiv:2002.12880*, 2020.

Alexandre Galashov, Jonathan Schwarz, Hyunjik Kim, Marta Garnelo, David Saxton, Pushmeet Kohli, SM Eslami, and Yee Whye Teh. Meta-learning surrogate models for sequential decision making. *arXiv preprint arXiv:1903.11907*, 2019.

Marta Garnelo, Dan Rosenbaum, Chris J Maddison, Tiago Ramalho, David Saxton, Murray Shanahan, Yee Whye Teh, Danilo J Rezende, and SM Eslami. Conditional neural processes. *arXiv preprint arXiv:1807.01613*, 2018a.

Marta Garnelo, Jonathan Schwarz, Dan Rosenbaum, Fabio Viola, Danilo J Rezende, SM Eslami, and Yee Whye Teh. Neural processes. *arXiv preprint arXiv:1807.01622*, 2018b.

Jonathan Gordon, Wessel P Bruinsma, Andrew YK Foong, James Requeima, Yann Dubois, and Richard E Turner. Convolutional conditional neural processes. *arXiv preprint arXiv:1910.13556*, 2019.

Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. In *Advances in Neural Information Processing Systems*, pp. 15353–15363, 2019.

Zhiwu Huang, Chengde Wan, Thomas Probst, and Luc Van Gool. Deep learning on lie groups for skeleton-based action recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6099–6108, 2017.

Lukasz Kaiser, Aidan N Gomez, and Francois Chollet. Depthwise separable convolutions for neural machine translation. *arXiv preprint arXiv:1706.03059*, 2017.

Hyunjik Kim, Andriy Mnih, Jonathan Schwarz, Marta Garnelo, Ali Eslami, Dan Rosenbaum, Oriol Vinyals, and Yee Whye Teh. Attentive neural processes. *arXiv preprint arXiv:1901.05761*, 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Risi Kondor and Shubhendu Trivedi. On the generalization of equivariance and convolution in neural networks to the action of compact groups. *arXiv preprint arXiv:1802.03690*, 2018.

Christiane Lemke, Marcin Budka, and Bogdan Gabrys. Metalearning: a survey of trends and technologies. *Artificial intelligence review*, 44(1):117–130, 2015.

Christos Louizos, Xiahan Shi, Klamer Schutte, and Max Welling. The functional neural process. In *Advances in Neural Information Processing Systems*, pp. 8743–8754, 2019.

Robin Quessard, Thomas D Barrett, and William R Clements. Learning group structure and disentangled representations of dynamical environments. *arXiv preprint arXiv:2002.06991*, 2020.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. 2016.

Andrei A Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. *arXiv preprint arXiv:1807.05960*, 2018.

Alvaro Sanchez-Gonzalez, Victor Bapst, Kyle Cranmer, and Peter Battaglia. Hamiltonian graph networks with ode integrators. *arXiv preprint arXiv:1909.12790*, 2019.

Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *International conference on machine learning*, pp. 1842–1850, 2016.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in neural information processing systems*, pp. 4077–4087, 2017.

Koh Takeuchi, Hisashi Kashima, and Naonori Ueda. Angle-based convolution networks for extracting local spatial features. 2018.

Peter Toth, Danilo Jimenez Rezende, Andrew Jaegle, Sébastien Racanière, Aleksandar Botev, and Irina Higgins. Hamiltonian generative networks. *arXiv preprint arXiv:1909.13789*, 2019.

Maurice Weiler and Gabriele Cesa. General e (2)-equivariant steerable cnns. In *Advances in Neural Information Processing Systems*, pp. 14334–14345, 2019.

Wenxuan Wu, Zhongang Qi, and Li Fuxin. Pointconv: Deep convolutional networks on 3d point clouds. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9621–9630, 2019.

Jin Xu, Jean-Francois Ton, Hyunjik Kim, Adam R Kosiorek, and Yee Whye Teh. Metafun: Meta-learning with iterative functional updates. *arXiv preprint arXiv:1912.02738*, 2019.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *Advances in neural information processing systems*, pp. 3391–3401, 2017.

Yaofeng Desmond Zhong, Biswadip Dey, and Amit Chakraborty. Symplectic ode-net: Learning hamiltonian dynamics with control. *arXiv preprint arXiv:1909.12077*, 2019.