Control Variates for Slate Off-Policy Evaluation

Abstract

We study the problem of off-policy evaluation from batched contextual bandit data with multidimensional actions, often termed slates. The problem is common to recommender systems and user-interface optimization, and it is particularly challenging because of the combinatorially-sized action space. Swaminathan et al. (2017) have proposed the pseudoinverse (PI) estimator under the assumption that the conditional mean rewards are additive in actions. Using control variates, we consider a large class of unbiased estimators that includes as specific cases the PI estimator and (asymptotically) its self-normalized variant. By optimizing over this class, we obtain new estimators with risk improvement guarantees over both the PI and self-normalized PI estimators. Experiments with real-world recommender data as well as synthetic data validate these improvements in practice.

1 Introduction

Online services (news, music and video streaming, social media, e-commerce, app stores, etc.) serve content that often takes the form of a combinatorial, high-dimensional *slate*, where each slot on the slate can take multiple values. For example, a personalized news service can have separate slots for local news, sports, politics, etc., with multiple news items from which to select in each slot (Li et al., 2010); or a video streaming service may organize the contents of the landing homepage of a user as a multi-slot slate, where each slot can contain shows from a given category (Gomez-Uribe and Hunt, 2015). Typically, the offered content is personalized via machine learning and A/B testing. However, the number of eligible items per slot may be in the hundreds or thousands, which makes the testing and optimization of personalized *policies* a challenging task.

An alternative to A/B testing and online learning is *off-policy evaluation* (OPE). In OPE we use historical data collected by a past policy in order to evaluate a new candidate policy. This is primarily an estimation problem, often with a causality angle (Horvitz and Thompson, 1952; Robins and Rotnitzky, 1995; Dudík et al., 2011; Bottou et al., 2013; Athey and Wager, 2017; Bibaut et al., 2019; Kallus and Uehara, 2019). However, even with plentiful off-policy data, handling a combinatorial action space can be challenging: Unbiased importance sampling (IS) (Horvitz and Thompson, 1952) suffers variance on the scale of the cardinality of the action space under a uniform logging policy and deterministic target policy. To address this, Swaminathan et al. (2017) have proposed the pseudoinverse (PI) estimator, which significantly attenuates the variance and remains unbiased for decomposable reward structures. In this paper, we discuss how to further reduce this variance using a *control variates* approach (Glynn and Szechtman, 2002). We demonstrate that the self-normalized PI (wPI) estimator, which Swaminathan et al. (2017) found to be superior to PI, is asymptotically equivalent to adding a control variate. But, the choice of control variate is not optimal. We instead show how to choose optimal control variates, and even how to do so without incurring any bias. We provide strong empirical evidence based on the MSLR-WEB30K data from the Microsoft Learning to Rank Challenge (Qin and Liu, 2013) that confirms the improvement of our approach over the PI and wPI estimators.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

1.1 Related work

Much of the existing OPE work involves the use of *doubly-robust* estimators and variants, which add control variates to the standard IS estimator (Robins and Rotnitzky, 1995; Dudík et al., 2011; Thomas and Brunskill, 2016; Farajtabar et al., 2018; Bibaut et al., 2019; Kallus and Uehara, 2019; Su et al., 2020). Directly optimizing control variates for OPE has been suggested earlier (Farajtabar et al., 2018; Vlassis et al., 2019) but not for problems involving high-dimensional slates.

Combinatorial bandits and variants such as semi-bandits have been studied by Cesa-Bianchi and Lugosi (2012) and Kveton et al. (2015) and are also covered in the book of Lattimore and Szepesvári (2020). Earlier approaches to OPE for contextual combinatorial bandits have been restricted to small slate problems (Li et al., 2011) or relied on accurate parametric models of slate rewards (Chapelle and Zhang, 2009; Guo et al., 2009; Filippi et al., 2010). Li et al. (2015) and Wang et al. (2016) have suggested the use of partial matches between the logging and target actions in order to mitigate the variance explosion. Swaminathan et al. (2017) have proposed the PI estimator, a version of which we study in this paper. Under factored policies, the PI estimator is similar to an estimator proposed by Li et al. (2018) for OPE of ranking policies with user click models. Swaminathan and Joachims (2015) and Joachims et al. (2018) have developed estimators for OPE under the framework of counterfactual risk minimization and discuss approaches for offline policy optimization. Agarwal et al. (2018) have developed an OPE method for rankers, when only the relative value of two given rankers is of interest. Chen et al. (2019) have developed an approach for offline policy gradients, when slates are unordered lists of items (of random size). McInerney et al. (2020) and Lopez et al. (2020) have studied the problem of slate OPE with semi-bandit feedback (one observed reward per slot), under different assumptions on the structure of the rewards and the contextual policies. In constrast to the latter two works, and similar to Swaminathan et al. (2017) and Su et al. (2020), we study the slate OPE problem when only a single, slate-level reward is observed. Su et al. (2020) achieve variance reduction by clipping propensities, whereas we achieve variance reduction by optimizing control variates.

Applications of slate OPE in real-world problems include Sar Shalom et al. (2016) who apply OPE to a large scale real world recommender system that handles purchases from tens of millions of users, Hill et al. (2017) who present a method to optimize a message that is composed of separated widgets (slots) such as title text, offer details, image, etc, and McInerney et al. (2020) who apply OPE to a slate problem involving sequences of items such as music playlists.

2 Setup and Notation

We consider contextual slate bandits where each slate has K slots. We will use $[K]$ to denote the set $\{1, 2, \ldots, K\}$. The available actions in slot k are $[d_k] = \{1, \ldots, d_k\}$. Thus, the set of available actions has cardinality $\prod_{k=1}^{K} d_k$. The data consists of n independent and identically distributed (iid) triplets (X_i, A_i, R_i), $i = 1, \ldots, n$, representing the observed context, action taken, and resulting reward, respectively. Here, $A_i = (A_{i1}, \ldots, A_{iK})$ where $A_{ik} \in [d_k]$. We use (X, A, R) to refer to a generic draw of one of the above triplets, where $X \sim \mathbb{P}(X), A \sim \mu(\cdot \mid X), R \sim \mathbb{P}(\cdot \mid A, X)$. The distribution $\mu(a \mid x) = \mathbb{P}(A = a \mid X = x)$ is called the *logging policy* as the data can be seen as the logs generated by executing this policy. Probabilities $\mathbb{P}$, expectations $\mathbb{E}$, and (co)variances without subscripts indicating otherwise are understood to be with respect to this distribution. For any function $f(x, a, r)$ we will write $\mathbb{E}_n[f(X, A, R)] = \frac{1}{n} \sum_{i=1}^{n} f(X_i, A_i, R_i)$. We will also follow the convention that *random, data-driven* objects have the form $\hat{\cdot}_n$ (such as $\hat{w}_n$ or $\hat{\theta}_n$).

In OPE, we are given a fixed policy $\pi(a \mid x)$ and are interested in estimating its average reward $\mathbb{E}_\pi[R]$ using data collected under a logging policy $\mu(a \mid x)$. Here $\mathbb{E}_\pi$ refers to expectation under the distribution $X \sim \mathbb{P}(X), A \sim \pi(\cdot \mid X), R \sim \mathbb{P}(\cdot \mid A, X)$. The classical IS estimator for this problem is $\mathbb{E}_n\left[\frac{\pi(A|X)}{\mu(A|X)} R\right]$, which is unbiased but can suffer unacceptably large variance when A is high-dimensional and μ provides coverage of all actions, as is necessary for the identification of arbitrary policies. Generally, we cannot do much better than IS in the worst case (Wang et al., 2017), unless we impose additional assumptions about the structure of actions or rewards.

In this paper, we will focus on the case where the logging policy is *factored*, that is, μ satisfies $\mu(a \mid x) = \prod_{k=1}^{K} \mu_k(a_k \mid x)$. This generally holds if μ is given by a per-action ϵ-greedy policy or is the uniform distribution, both are common cases in practice.

We define the following slot-level density ratios and their sum

$$Y_k = \frac{\pi(A_k \mid X)}{\mu_k(A_k \mid X)}, \qquad G = 1 + \sum_{k=1}^{K} (Y_k - 1). \tag{1}$$

Using the definition of G from (1), we have the following causal identifiability result for $\mathbb{E}_\pi[R]$. (A succinct proof of this result, as well as all our novel results, can be found in Section 9 of this paper and in the Supplementary Text.)

Lemma 1 (Identifiability under additive rewards (Swaminathan et al., 2017)). *Under a factored μ, $E_\pi[R] = \mathbb{E}[GR]$ whenever $\mathbb{E}[R \mid A, X] = \sum_{k=1}^{K} \phi_k(A_k, X)$ for some (latent) functions $\phi_k(a_k, x)$.*

Motivated by this identifiability result, in this paper we focus on estimating the target parameter $\theta = \mathbb{E}[GR]$. Crucially, lemma 1 implies that under additive rewards, the variance of an estimator of θ need only suffer the size of the slot-level density ratios (namely, $\sum_{k=1}^{K} d_k^2$ for uniform exploration and deterministic evaluation) rather than the possibly astronomical size of the slate density ratio appearing in the classic IS estimator (namely, $\prod_{k=1}^{K} d_k^2$ under the same settings). Moreover, lemma 1 shows that μ need not even cover every slate combination – only marginally every action per slot. In the rest of the paper we will not assume any special structure for $\mathbb{E}[R \mid A, X]$; our estimation results on θ will hold irrespective of causal identifiability of $E_\pi[R]$. In the experiments we will show results for both additive and non-additive rewards.

In the factored policy setting, the PI and wPI estimators of Swaminathan et al. (2017) are, respectively,

$$\hat{\theta}_n^{\text{PI}} = \mathbb{E}_n[GR], \qquad \hat{\theta}_n^{\text{wPI}} = \frac{\mathbb{E}_n[GR]}{\mathbb{E}_n[G]} .$$

The PI estimator is unbiased for estimating θ by construction. While wPI may be biased, it can further reduce PI's variance.

3 A Class of Estimators

We now construct a class of unbiased estimators that includes PI and (almost) wPI. We will then propose to choose *optimal* estimators in this class and show how they can be approximated.

For any fixed tuple of weights $w = (w_1, \ldots, w_K) \in \mathbb{R}^K$, we define the estimator

$$\hat{\theta}_n^{(w)} = \mathbb{E}_n[\Gamma_w], \qquad \Gamma_w = GR - \sum_{k=1}^{K} w_k(Y_k - 1).$$

Here, each $Y_k - 1$ acts as a *control variate* (Glynn and Szechtman, 2002). We slightly overload notation and for the case $w_1 = \cdots = w_K = \beta \in \mathbb{R}$ we will write

$$\hat{\theta}_n^{(\beta)} = \mathbb{E}_n[\Gamma_\beta], \qquad \Gamma_\beta = GR - \beta(G - 1),$$

which corresponds to using a single control variate $G - 1$. Note that $\hat{\theta}_n^{\text{PI}}$ is included in the estimator class: When $\beta = 0$, we have $\Gamma_0 = GR$ and $\hat{\theta}_n^{\text{PI}} = \hat{\theta}_n^{(0)}$. We further define $V_w = \text{Var}(\Gamma_w)$. It is straightforward to show that, for any *fixed* w, the estimator $\hat{\theta}_n^{(w)}$ is unbiased (for any n) and asymptotically normal.

Lemma 2 (Unbiasedness and asymptotic normality of $\hat{\theta}_n^{(w)}$). *For any fixed w, we have*

$$\mathbb{E}[\hat{\theta}_n^{(w)}] = \mathbb{E}[\Gamma_w] = \theta,$$
$$\sqrt{n}(\hat{\theta}_n^{(w)} - \theta) \to_d \mathcal{N}(0, V_w).$$

While PI is in this class and has variance V_0, wPI is not actually a member of this class, but it is asymptotically equivalent to a member. To see this, we first need to understand the asymptotics of $\hat{\theta}_n^{(w)}$ when we plug in a *random, data-driven* w denoted $\hat{w}_n$. It turns out (by Slutsky's theorem) that, if $\hat{w}_n$ converges to some *fixed* vector w, the asymptotic behavior of $\hat{\theta}_n^{(\hat{w}_n)}$ is the same as plugging in the fixed w.

125 **Lemma 3** (Asymptotics of plug-in w). *Suppose $\hat{w}_n \to_p w$, for some fixed w. Then*

$$\sqrt{n}(\hat{\theta}_n^{(\hat{w}_n)} - \theta) \to_d \mathcal{N}(0, V_w).$$

126 We can now establish the following corollary showing that wPI is asymptotically equivalent to $\hat{\theta}_n^{(\theta)}$,
127 that is, a member of our class of estimators using $\beta = \theta$ (the unknown target estimand).
128 **Lemma 4** (Asymptotics of wPI). *We have*

$$\sqrt{n}(\hat{\theta}_n^{wPI} - \theta) \to_d \mathcal{N}(0, V_\theta).$$

4 Optimal Control Variates

130 In the previous section we showed that both PI and wPI are, or are asymptotically equivalent to,
131 members of the class of estimators $\hat{\theta}_n^{(w)}$. But the class is more general than these two, so it behooves
132 us to try to find an optimal member.

4.1 Optimal Single Control Variate

134 We first focus on the case $w_1 = \cdots = w_K = \beta$, that is, using a single control variate $G - 1$. Both PI
135 and wPI fall in this category with $\beta = 0$ and $\beta = \theta$, respectively, as we showed above. Let

$$V^\dagger = \inf_{\beta \in \mathbb{R}} V_\beta \tag{2}$$

136 represent the minimal variance in the class of single-control-variate estimators. By construction,
137 $V^\dagger \le V_0 = \mathrm{Var}(GR)$ and $V^\dagger \le V_\theta$, the right-hand sides being the (asymptotic) variance of PI and
138 wPI, respectively. Our next result derives this optimum.
139 **Lemma 5** (Optimal single control variate). *We have*

$$V^\dagger = V_{\beta^*} = V_0 - \frac{(\mathbb{E}[G^2 R] - \theta)^2}{\sum_k \mathrm{Var}(Y_k)},$$

140 *where*

$$\beta^* = \frac{\mathbb{E}[G^2 R] - \theta}{\sum_k \mathrm{Var}(Y_k)}.$$

141 Notice that generally $\beta^* \ne \theta$. That is, while wPI is asymptotically equivalent to a control-variate
142 estimate, it is not generally optimal. In the degenerate case where $R \perp\!\!\!\perp G$ (*e.g.*, constant reward) then
143 we do have $\beta^* = \theta$.

144 Our results, nonetheless, immediately suggest how to obtain this optimum asymptotically, using a
145 feasible estimator.
146 **Lemma 6** (Achieving optimal single control variate). *Compute a data-driven β as*

$$\hat{\beta}_n^* = \frac{\mathbb{E}_n[GR(G - 1)]}{\sum_k \mathbb{E}_n[(Y_k - 1)^2]}.$$

147 *Then,*

$$\sqrt{n}(\hat{\theta}_n^{(\hat{\beta}_n^*)} - \theta) \to_d \mathcal{N}(0, V^\dagger).$$

148 That is, asymptotically, $\hat{\theta}_n^{(\hat{\beta}_n^*)}$ is at least as good as either PI and wPI. The improvement is positive, in
149 general.

150 **Lemma 7.** *The improvement of $\hat{\theta}_n^{(\hat{\beta}_n^*)}$ over PI is*

$$V_0 - V^\dagger = \frac{\mathbb{E}[GR(G - 1)]^2}{\mathbb{E}[(G - 1)^2]} \ge 0,$$

151 *and the improvement over wPI is*

$$V_\theta - V^\dagger = \frac{\mathbb{E}[GR(G - 1)]^2}{\mathbb{E}[(G - 1)^2]} - 2\mathbb{E}[GR]\mathbb{E}[G^2 R] + \mathbb{E}[GR]^2(2 + \mathbb{E}[(G - 1)^2]) \ge 0.$$

 ## 4.2 Optimal Multiple Control Variates

153 We now turn our attention to optimally choosing weights on all K control variates. Let

$$V^* = \inf_{w \in \mathbb{R}^K} V_w. \tag{3}$$

154 By construction, $V^* \leq V^\dagger \leq \min(V_0, V_\theta)$, that is, it is smaller than or equal to the asymptotic
155 variances of PI, wPI, and the optimal single-control-variate estimator. Empirically, we find that the
156 first inequality can have a small gap while the second a large one; that is, optimizing control variates
157 provides substantive improvement over PI and wPI, but much of the improvement is often captured
158 by optimizing a single control variate in certain highly symmetric settings. See sections 6 and 7.

159 **Lemma 8** (Optimal multiple control variates). *We have*

$$V^* = V_{w^*} = \sum_{k=1}^{K} \frac{\mathbb{E}[GR(Y_k - 1)]^2}{\mathrm{Var}(Y_k)},$$

160 *where*

$$w_k^* = \frac{\mathbb{E}[GR(Y_k - 1)]}{\mathrm{Var}(Y_k)}.$$

161 Again, if $R \perp\!\!\!\perp Y_k$, we have $w_k = \theta$ for all k. Generally, w_k vary over k and are not equal to θ.

162 As in the single control-variate case above, we can obtain the above optimum asymptotically using a
163 feasible estimator.

164 **Lemma 9** (Achieving optimal multiple control variates). *Compute data-driven weights w_k as*

$$\hat{w}_{n,k}^* = \frac{\mathbb{E}_n[GR(Y_k - 1)]}{\mathbb{E}_n[(Y_k - 1)^2]}.$$

165 *Then,*

$$\sqrt{n}(\hat{\theta}_n^{(\hat{w}_n^*)} - \theta) \to_d \mathcal{N}(0, V^*).$$

166 **Lemma 10.** *The improvement of $\hat{\theta}_n^{(\hat{w}_n^*)}$ over PI is*

$$V_0 - V^* = \sum_k \frac{\mathbb{E}[GR(Y_k - 1)]^2}{\mathbb{E}[(Y_k - 1)^2]} \geq 0.$$

167 *The improvement over the single control variate $\hat{\theta}_n^{(\hat{\beta}_n^*)}$ is*

$$V^\dagger - V^* = \sum_k \frac{\mathbb{E}[GR(Y_k - 1)]^2}{\mathbb{E}[(Y_k - 1)^2]} - \frac{\mathbb{E}[GR(G - 1)]^2}{\mathbb{E}[(G - 1)^2]} \geq 0.$$

168 This improvement is of course no smaller than the improvement over wPI, which is no better than
169 the optimal single control variate (asymptotically). The improvement again collapses to zero in the
170 special case of constant rewards.

171 # 5 Achieving Optimality Without Suffering Bias

172 Although the above estimators have asymptotically optimal variance among control variates, they
173 may incur finite-sample bias due to the estimation of control variate weights. We can avoid this
174 using a three-way cross-fitting. The estimator we construct in this section will be *both* finite-sample
175 unbiased *and* have optimal variance asymptotically.

176 The estimator we propose is as follows:

177   1. Split the data randomly into three even folds, $\mathcal{D}_0, \mathcal{D}_1, \mathcal{D}_2$.

178   2. For $j = 0, 1, 2$, compute $\hat{w}_{n,k}^{(j)} = \frac{\mathbb{E}_{\mathcal{D}_j}[GR(Y_k - 1)]}{\mathbb{E}_{\mathcal{D}_j}[(Y_k - 1)^2]}$, where $\mathbb{E}_{\mathcal{D}_j}$ refers to the sample average
179   only over $\mathcal{D}_j$.

3. Set

$$\hat{\theta}_n^* = \mathbb{E}_n[GR] - \sum_k \sum_{j=0,1,2} \frac{|\mathcal{D}_j|}{n} \hat{w}_{n,k}^{(j+1 \mod 3)} \mathbb{E}_{\mathcal{D}_j}[Y_k - 1].$$

Lemma 11 (Unbiased estimator with optimal asymptotic variance)**.** *We have*

$$\mathbb{E}[\hat{\theta}_n^*] = \theta, \qquad \sqrt{n}(\hat{\theta}_n^* - \theta) \to_d \mathcal{N}(0, V^*).$$

6   Experiments on real data

We have benchmarked the proposed estimators on the publicly available dataset[1] MSLR-WEB30K from the Microsoft Learning to Rank Challenge (Qin and Liu, 2013). This is a labeled dataset that contains about 31k user queries, each providing up to 1251 labeled documents (the labels are relevance scores from 0 to 4). The queries form the contexts x of our OPE problem. In order to be able to provide a head-to-head comparison with the results reported by Swaminathan et al. (2017), we have closely followed the experimental protocol of the latter (with minor differences, explained next) in order to generate contextual slate bandit instances from the data. Each query-document pair in the dataset is annotated with 'title' and 'body' features. As a preprocessing step, we first use all data to train a regression tree that predicts document scores from the 'title' features of query-document pairs.[2] We then use this regressor as a standard greedy ranker to extract, for each query, the top-M predicted documents (with $M \in \{10, 50, 100\}$). Finally, we discard all queries that have less than M judged documents. (This latter step was not present in the experimental pipeline of Swaminathan et al., 2017. We include it here because it facilitates sampling with replacement, which is required in our experiments. Even for $M = 100$, the resulting dataset contains a sizable number (18k+) of unique queries, and running the PI and wPI estimators against these data attained essentially the same performance as with the unfiltered dataset.)

The above procedure defines the sets $A(x)$ of 'allowed' documents per context x. In each problem instance, we train a new predictor (using decision trees or lasso[3]) constrained on the sets $A(x)$, and use it as a greedy ranker to extract, for each query, the top-K predicted documents (with $K \in \{5, 10, 30\}$). This mapping defines a deterministic target policy $\pi(x)$ for our OPE problem: each K-size ranking defines a K-slot slate, with each slot having cardinality M. Note that each document can appear only once in the slates mapped by $\pi(x)$. The logging policy $\mu(x)$ is uniform, and it samples K documents *with replacement* from the set $A(x)$, for each context x. (In Swaminathan et al., 2017, documents were sampled without replacement by the logging policy.) To create each logged dataset, we sampled the x uniformly from the set of all non-filtered queries, up to the desired sample size (which, as in Swaminathan et al., 2017, could end up reusing some queries multiple times).

We report results for PI, wPI, and the optimal single control variate estimator $\hat{\theta}_n^{(\hat{\beta}_n^*)}$ from lemma 6, denoted PICVs. The multiple control variate estimator from lemma 9 obtained near-identical MSE as the reported PICVs, so we omit it from the plots. (The similar performance of the single vs multiple control variate estimators in this problem is owed to the symmetry between slots; for example, each having the same number of actions. In the next section we show an example where the two estimators exhibit different behavior.) We evaluate each estimator using (log) root mean square error (RMSE) as a function of sample size. We estimate MSE and standard errors of $\log(\text{RMSE})$ (the latter computed via the delta method on $\frac{\log(\text{MSE})}{2\log(10)}$) using 300 independent runs for each setting. As in Swaminathan et al. (2017), we repeat the protocol for a number of different experimental conditions, varying the values of M, K, the regression model for the target policy (tree-based or lasso), and the choice of metric.[4] We tested two metrics, NDCG (additive) and ERR (non-additive); see Swaminathan et al.

---

[1]This dataset is available for download from https://www.microsoft.com/en-us/research/project/mslr/, is distributed under Standard MSR License Agreement, and does not contain any personally identifiable information.

[2]We used sklearn.tree.DecisionTreeRegressor(criterion="mse", splitter="random", min_samples_split=4, min_samples_leaf=4), optimized using sklearn.model_selection.GridSearchCV with (main parameters) max_depth 3 and cv=3. See the provided code for more details.

[3]We used sklearn.linear_model.Lasso(fit_intercept=False, max_iter=500, tol=1e-4, normalize=False, precompute=False, copy_X=False, warm_start=False, positive=False, random_state=None, selection='random'), optimized using sklearn.model_selection.GridSearchCV with (main parameters) max_depth 3 and cv=3.

[4]For all our experiments we employed a total of about 1k quad-core machines on the cloud, each running for about two hours on average.

Figure 1: Benchmarking the proposed PICVs estimator against PI and wPI on the MSLR-WEB30K data, using a tree-based regression model for the target policy. Here we vary M, the number of available actions (documents) per slot, K, the number of slots (size of ranked lists), and the choice of metric that defines slate-level reward. Missing values for wPI (for sample size 1k) are due to excessive variance caused by the presence of outliers. See text for details.

(2017) for definitions. The version of NDCG that we used is tailored to rankings with replacements: It only differs to standard NDCG in that the denominator is the DCG of a slate that is formed by the globally most relevant document (for the given x) replicated over all K slots of the slate (capturing the fact that documents are sampled with replacement in μ). Note that this version of NDCG is additive over slots, which is a requirement for PI (and hence our cross-fitted PICV estimator) to be unbiased when the estimand is the value of the target policy. We refer to the uploaded code in the Supplementary Material for additional details.

In Fig. 1 we show the results for the NDCG and ERR metrics when using a tree-based predictor to define the target policy. (See Supplementary Text for results when using lasso.) We observe that the proposed estimator PICVs dominates both PI and wPI, in both metrics, with notable improvements for small sample sizes relative to M. We noticed that in some runs wPI would return abnormally large estimates (values up to four orders of magnitude larger than the median), especially for small sample sizes. This can happen when the denominator of wPI gets, by chance, close to zero. This in an artifact of wPI being defined as the ratio of estimates and can lead to very high variance—even higher than PI's. Our proposed PICV is not prone to such outliers and the ensuing variance, and is robust uniformly over all the sample sizes tested.

7 Experiments on synthetic data: The gap between PICV single and multi

The results on the MSLR-WEB30K data do not demonstrate any substantial differentiation between the single and multi variants of the proposed PICV estimators. This is mainly due to symmetry between slots, which need not always be the case. In this section we show results from synthetic simulations on a non-contextual slate bandit problem, using a reward model that is skewed toward the first slot of the slate and toward the target policy (which picks action 0 from each slot). This setting reveals a differential behavior of the single vs the multi PICV variants. Here we assume Bernoulli slate-level rewards, and the slate-level Bernoulli rates $p(a)$ are given by the weighted sum

$$p(a) = (0.5)^{a_1-1}\phi_1(a_1) + 0.01 \sum_{k=2}^{K} \phi_k(a_k), \tag{4}$$

where the slot-level actions are $a_k \in \{1, \ldots, d_k\}$, for $k = 1, \ldots, K$. Under this model, slot-1 actions that are closer to action 1 are conferring more impact to the slate-level reward, and hence we expect the latter to be more correlated with the target policy. This allows us to examine if there is any differential behavior between the single (PICVs) and the multi (PICVm) variants. In each simulation

Figure 2: Comparing the estimators in a small scale simulation setting, demonstrating a differentiated behavior between the single and multi variants of PICV. See text for details. Missing values for wPI are due to excessive variance caused by the presence of outliers.

experiment, we generate $T = 20$ random reward tensors $p(a) \in [0,1]^D$ using (4), where, for each a_k, the value of $\phi_k(a_k)$ is drawn from a Gaussian distribution $\mathcal{N}(0.2/K, 0.01)$. The parameters of each simulated instance are the number N of logged slates, the number of slots K, and the slot action cardinality tuple $D = [d_1, ..., d_K]$ where d_i is the number of available actions of the i-th slot. For each sampled tensor, we generate 300 datasets by drawing slates $a \sim \mu(\cdot)$ using a uniform logging policy $\mu(a)$ and drawing Bernoulli rewards from the corresponding $p(a)$. We use each dataset to evaluate a deterministic policy $\pi(a) = \mathbb{I}(a = [0, ..., 0])$ (w.l.o.g.) using each of the candidate estimators. Since we know the ground truth, we can compute the MSE of each estimator. We report (log) average root mean square error (RMSE), with standard errors (almost negligible), over the T tensors.

The results are shown in Fig. 2 and demonstrate a differentiation between PICVs and PICVm, with the multi variant obtaining lower RMSE by virtue of leveraging more control variates.

8   Conclusions and Discussion

We studied the problem of off-policy evaluation for slate bandits. We considered a class of unbiased estimators that included PI and (asymptotically) wPI, constructed using a control variate approach. This strongly suggested trying to obtain the minimal variance in this class. We showed how to do so asymptotically, and even how to do so without incurring any additional bias in finite samples. Our new estimators led to gains in both simulations and real-data experiments.

Future Work.   An interesting avenue for future research is how to meld this approach with doubly-robust (DR) style centering. Su et al. (2020) consider the DR-PI estimator given by adding to the PI estimator the (unweighted) control variate $\mathbb{E}[Gf(X, A) - \sum_{a \in \prod_{k=1}^{K}[d_k]} \pi(a \mid X) f(X, a)]$. In particular, they consider $f(x, a)$ being an estimate of $\mathbb{E}[R \mid A = a, X = x]$. But unlike the standard non-additive OPE case, it is not clear that it would be efficient to consider only this control variate (Kallus and Uehara, 2019). In particular, restricting the statistical model to have additive rewards make standard semiparametric efficiency analyses difficult, and the efficient influence function is unknown and likely has no analytic form. Again, we can consider a range of *centered* control variates, $\sum_{k=1}^{K} \left(\mathbb{E}[Y_k f_k(X, A_k)] - \mathbb{E}[\sum_{a_k \in [d_k]} \pi(a_k \mid X) f_k(X, a_k)] \right)$. Letting $f_k(x, a_k) = w_k$ recovers our estimator class $\hat{\theta}_n^{(w)}$. However, there may be benefit to using (x, a)-dependent control variates. Efficiency considerations suggest letting f_k estimate $\mathbb{E}[R \mid A_k = a_k, X = x]$, but the (sub)optimality of such in the additive-rewards model requires further investigation. A promising direction forward is to consider a parametric family, $f_k \in \mathcal{F}_k$, and optimize the choice of parameter to minimize an empirical variance estimate, in the spirit of more robust doubly robust estimation (Farajtabar et al., 2018). As long as $\mathcal{F}_k$ has nice complexity, we can obtain the best-in-class variance asymptotically. Characterizing this precisely and investigating the value of this empirically remains future work.

Societal Impacts. In general, having accurate methods for performing OPE can allow decision makers to evaluate potentially unsafe decision making policies, and decide whether they may lead to improved societal outcomes, without having to risk the potentially negative consequences of trialling such policies. Nonetheless, as discussed above, OPE with combinatorial actions is nearly hopeless without making additional assumptions. These, however, can fail to hold and lead to biased estimates, which needs to be taken into account when considering potential harms of a proposed policy. Another potential risk, which applies to OPE in general, is that the data used may not accurately reflect the diversity of the population that the policy will actually be deployed on. In this case, resulting policy value estimates may be much more accurate for individuals who are well represented in the data, compared with individuals who are not. This may bias downstream decision making towards policies that best serve those who are well represented in the data, possibly at the cost of those who are not well represented. Such biases must also be taken into account in any OPE analysis.

9 Proofs of the main results

Here we provide succinct proofs for all results, except for lemma 11 whose proof is quite involved and long and is therefore deferred to the Supplementary Material.

Proof of lemma 1. Swaminathan et al. (2017) prove this result for general policies. For completeness we give a short proof for factored μ. By construction, we have $\mathbb{E}[GR \mid A, X] = \sum_{k=1}^{K} Y_k \, \phi_k(A_k, X) + \sum_{k=1}^{K} \left(1 - K + \sum_{j \neq k} Y_j\right) \phi_k(A_k, X)$. Taking expectation over A, the last term cancels (when μ is factored) since $\mathbb{E}[Y_k \mid X] = \sum_{a_k \in [d_k]} \pi(a_k \mid X) = 1$, and the first term is $\mathbb{E}_\pi[R \mid X]$. Further taking expectation over X gives the result. $\square$

Proof of lemma 2. Since $\mathbb{E}[Y_k \mid X] = 1$, we have $\mathbb{E}[\Gamma_w \mid X] = \mathbb{E}[GR \mid X]$. Iterated expectations gives the first statement. The second statement is immediate from the central limit theorem (CLT). $\square$

Proof of lemma 3. Set $\tilde{\theta}_n = \mathbb{E}_n[\Gamma_w]$. From CLT, $\sqrt{n}(\tilde{\theta}_n - \theta) \to_d \mathcal{N}(0, V_w)$. Next, note that $\sqrt{n}(\tilde{\theta}_n - \hat{\theta}_n) = \sum_k (\hat{w}_{n,k} - w_{n,k})\sqrt{n}\mathbb{E}_n[Y_k - 1]$. Since $\sqrt{n}\mathbb{E}_n[Y_k - 1] \to_d \mathcal{N}(0, \text{Var}(Y_k))$ by CLT and $\hat{w}_{n,k} - w_{n,k} \to_p 0$ by assumption, Slutsky's theorem yields $\sqrt{n}(\tilde{\theta}_n - \hat{\theta}_n) \to_d 0$. $\square$

Proof of lemma 4. We have $\frac{\mathbb{E}_n[GR]}{\mathbb{E}_n[G]} = \mathbb{E}_n[GR] + \mathbb{E}_n[GR]\frac{1 - \mathbb{E}_n[G]}{\mathbb{E}_n[G]} = \mathbb{E}_n[GR] - \hat{\theta}_n^{\text{wPI}}\mathbb{E}_n[G - 1] = \mathbb{E}_n[GR] - \sum_k \hat{\theta}_n^{\text{wPI}}\mathbb{E}_n[Y_k - 1]$. Since $\mathbb{E}_n[GR] \to_p \theta$ and $\mathbb{E}_n[G] \to_p 1$, the continuous mapping theorem gives $\hat{\theta}_n^{\text{wPI}} \to_p \theta$. Then, invoking lemma 3 completes the proof. $\square$

Proof of lemma 5. We have $V_\beta = \text{Var}(GR) - 2\beta\mathbb{E}[GR(G - 1)] + \beta^2\mathbb{E}[(G - 1)^2]$, which is convex in β. Differentiating, setting to zero, and solving for β, we get $\beta^* = \frac{\mathbb{E}[GR(G-1)]}{\mathbb{E}[(G-1)^2]}$. For the numerator, we have $\mathbb{E}[GR(G - 1)] = \mathbb{E}[G^2R] - \mathbb{E}[GR] = \mathbb{E}[G^2R] - \theta$. For the denominator, we have $\mathbb{E}[(G - 1)^2] = \text{Var}(G) = \sum_k \text{Var}(Y_k)$. Combining yields the claim of the lemma. $\square$

Proof of lemma 6. This is direct from the weak law of large numbers and lemmas 3 and 5. $\square$

Proof of lemma 7. This follows by algebra and noting that $V^\dagger \geq \max(V_0, V_\theta)$ since both $\beta = 0$ and $\beta = \theta$ are feasible in eq. (2). $\square$

Proof of lemma 8. Let $C = (Y_1 - 1, \ldots, Y_K - 1)$. We have $V_w = \text{Var}(GR) - 2w^\intercal\mathbb{E}[GRC] + w^\intercal\mathbb{E}[CC^\intercal]w$, which is convex in w. Differentiating, setting to zero, and solving for w gives $w^* = \mathbb{E}[CC^\intercal]^{-1}\mathbb{E}[GRC]$. We have $\text{Cov}(Y_k, Y_{k'}) = 0$ whenever $k \neq k'$. Hence we can simplify and obtain the result. $\square$

Proof of lemma 9. This is direct from the weak law of large numbers and lemmas 3 and 8. $\square$

Proof of lemma 10. This follows by algebra and noting that $V^* \geq \max(V_0, V^\dagger)$ since both $w_1 = \cdots = w_K = 0$ and $w_1 = \cdots = w_K = \beta^*$ are feasible in eq. (3). $\square$

References

Agarwal, A., Wang, X., Li, C., Bendersky, M., and Najork, M. (2018). Offline comparison of ranking functions using randomized data. *arXiv preprint arXiv:1810.05252*.

Athey, S. and Wager, S. (2017). Efficient policy learning. *arXiv preprint arXiv:1702.02896*.

Bibaut, A., Malenica, I., Vlassis, N., and Van Der Laan, M. (2019). More efficient off-policy evaluation through regularized targeted learning. In *International Conference on Machine Learning*, pages 654–663. PMLR.

Bottou, L., Peters, J., Quiñonero-Candela, J., Charles, D. X., Chickering, D. M., Portugaly, E., Ray, D., Simard, P., and Snelson, E. (2013). Counterfactual reasoning and learning systems: The example of computational advertising. *Journal of Machine Learning Research*, 14(65):3207–3260.

Cesa-Bianchi, N. and Lugosi, G. (2012). Combinatorial bandits. *Journal of Computer and System Sciences*, 78(5):1404–1422.

Chapelle, O. and Zhang, Y. (2009). A dynamic bayesian network click model for web search ranking. In *Proceedings of the 18th international conference on World wide web*, pages 1–10.

Chen, M., Beutel, A., Covington, P., Jain, S., Belletti, F., and Chi, E. H. (2019). Top-k off-policy correction for a reinforce recommender system. In *Proceedings of the Twelfth ACM International Conference on Web Search and Data Mining*, pages 456–464.

Dudík, M., Langford, J., and Li, L. (2011). Doubly robust policy evaluation and learning. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, pages 1097–1104.

Farajtabar, M., Chow, Y., and Ghavamzadeh, M. (2018). More robust doubly robust off-policy evaluation. In *International Conference on Machine Learning*, pages 1447–1456. PMLR.

Filippi, S., Cappe, O., Garivier, A., and Szepesvári, C. (2010). Parametric bandits: The generalized linear case. In *NIPS*, volume 23, pages 586–594.

Glynn, P. W. and Szechtman, R. (2002). Some new perspectives on the method of control variates. In *Monte Carlo and Quasi-Monte Carlo Methods 2000*, pages 27–49. Springer.

Gomez-Uribe, C. A. and Hunt, N. (2015). The netflix recommender system: Algorithms, business value, and innovation. *ACM Transactions on Management Information Systems (TMIS)*, 6(4):1–19.

Guo, F., Liu, C., Kannan, A., Minka, T., Taylor, M., Wang, Y.-M., and Faloutsos, C. (2009). Click chain model in web search. In *Proceedings of the 18th international conference on World wide web*, pages 11–20.

Hill, D. N., Nassif, H., Liu, Y., Iyer, A., and Vishwanathan, S. (2017). An efficient bandit algorithm for realtime multivariate optimization. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1813–1821.

Horvitz, D. G. and Thompson, D. J. (1952). A generalization of sampling without replacement from a finite universe. *Journal of the American statistical Association*, 47(260):663–685.

Joachims, T., Swaminathan, A., and de Rijke, M. (2018). Deep learning with logged bandit feedback. In *International Conference on Learning Representations*.

Kallus, N. and Uehara, M. (2019). Intrinsically efficient, stable, and bounded off-policy evaluation for reinforcement learning. *arXiv preprint arXiv:1906.03735*.

Kveton, B., Wen, Z., Ashkan, A., and Szepesvari, C. (2015). Tight regret bounds for stochastic combinatorial semi-bandits. In *Artificial Intelligence and Statistics*, pages 535–543. PMLR.

Lattimore, T. and Szepesvári, C. (2020). *Bandit algorithms*. Cambridge University Press.

Li, L., Chu, W., Langford, J., and Schapire, R. E. (2010). A contextual-bandit approach to personalized news article recommendation. In *Proceedings of the 19th international conference on World wide web*, pages 661–670.

Li, L., Chu, W., Langford, J., and Wang, X. (2011). Unbiased offline evaluation of contextual-bandit-based news article recommendation algorithms. In *Proceedings of the fourth ACM international conference on Web search and data mining*, pages 297–306.

Li, L., Kim, J. Y., and Zitouni, I. (2015). Toward predicting the outcome of an A/B experiment for search relevance. In *Proceedings of the Eighth ACM International Conference on Web Search and Data Mining*, pages 37–46.

Li, S., Abbasi-Yadkori, Y., Kveton, B., Muthukrishnan, S., Vinay, V., and Wen, Z. (2018). Offline evaluation of ranking policies with click models. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1685–1694.

Lopez, R., Dhillon, I., and Jordan, M. I. (2020). Learning from extreme bandit feedback. *arXiv preprint arXiv:2009.12947*.

McInerney, J., Brost, B., Chandar, P., Mehrotra, R., and Carterette, B. (2020). Counterfactual evaluation of slate recommendations with sequential reward interactions. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1779–1788.

Qin, T. and Liu, T. (2013). Introducing LETOR 4.0 datasets. *CoRR*, abs/1306.2597.

Robins, J. M. and Rotnitzky, A. (1995). Semiparametric efficiency in multivariate regression models with missing data. *Journal of the American Statistical Association*, 90(429):122–129.

Sar Shalom, O., Koenigstein, N., Paquet, U., and Vanchinathan, H. P. (2016). Beyond collaborative filtering: The list recommendation problem. In *Proceedings of the 25th international conference on world wide web*, pages 63–72.

Su, Y., Dimakopoulou, M., Krishnamurthy, A., and Dudík, M. (2020). Doubly robust off-policy evaluation with shrinkage. In *International Conference on Machine Learning*, pages 9167–9176. PMLR.

Swaminathan, A. and Joachims, T. (2015). Counterfactual risk minimization: Learning from logged bandit feedback. In *International Conference on Machine Learning*, pages 814–823. PMLR.

Swaminathan, A., Krishnamurthy, A., Agarwal, A., Dudík, M., Langford, J., Jose, D., and Zitouni, I. (2017). Off-policy evaluation for slate recommendation. In *NIPS*.

Thomas, P. and Brunskill, E. (2016). Data-efficient off-policy policy evaluation for reinforcement learning. In *International Conference on Machine Learning*, pages 2139–2148. PMLR.

Vlassis, N., Bibaut, A., Dimakopoulou, M., and Jebara, T. (2019). On the design of estimators for bandit off-policy evaluation. In *International Conference on Machine Learning*, pages 6468–6476. PMLR.

Wang, X., Bendersky, M., Metzler, D., and Najork, M. (2016). Learning to rank with selection bias in personal search. In *Proceedings of the 39th International ACM SIGIR conference on Research and Development in Information Retrieval*, pages 115–124.

Wang, Y.-X., Agarwal, A., and Dudık, M. (2017). Optimal and adaptive off-policy evaluation in contextual bandits. In *International Conference on Machine Learning*, pages 3589–3597. PMLR.