Predicting Immune Escape with Pretrained Protein Language Model Embeddings

Abstract

Assessing the severity of new pathogenic variants requires an understanding of which mutations will escape the human immune response. Even single point mutations to an antigen can cause immune escape and infection via abrogation of antibody binding. Recent work has modeled the effect of single point mutations on proteins by leveraging the information contained in large-scale, pretrained protein language models. These models are often applied in a zero-shot setting, where the effect of each mutation is predicted based on the output of the language model with no additional training. However, this approach cannot appropriately model immune escape, which involves the interaction of two proteins—antibody and antigen—instead of one protein and requires making different predictions for the same antigenic mutation in response to different antibodies. Here, we explore several methods for predicting immune escape by building models on top of embeddings from pretrained protein language models. We evaluate our methods on a SARS-CoV-2 deep mutational scanning dataset and show that our embedding-based methods significantly outperform zero-shot methods, which have almost no predictive power. We also highlight insights gained into how best to use embeddings from pretrained protein language models to predict escape. Despite these promising results, simple statistical and machine learning baseline models that do not use pretraining perform comparably, showing that computationally expensive pretraining approaches may not be beneficial for escape prediction. Furthermore, all models perform relatively poorly, indicating that future work is necessary to improve escape prediction with or without pretrained embeddings.

1 Introduction

Pathogens are constantly evolving in their search to evade the immune system and infect host organisms [1]. In many organisms, including humans, this evolutionary battle occurs in the context of antibody-antigen interactions [2]. Antibodies are proteins produced by the immune system that are designed to bind to antigens, which are pathogenic proteins that induce an immune response. Antibodies that effectively bind to an antigen and neutralize the pathogen put evolutionary pressure on the pathogen to mutate its antigen in a process known as immune escape [3]. Predicting which mutations cause escape is crucial to identifying dangerous pathogenic variants that can cause infection and disease even in the presence of antibodies from prior infection, vaccination, or therapies [3–5].

Machine learning models have been developed that can predict the effect of protein mutations on various protein functions [4, 6–9]. Recent approaches to mutation effect prediction have leveraged

Submitted to NeurIPS 2021 AI for Science Workshop.

large protein language models that have been trained in an unsupervised manner on huge databases with hundreds of millions to billions of protein sequences [10, 11]. These models learn the underlying statistics of naturally occurring protein sequences and can predict the likelihood that a given amino acid appears at each position in a protein. These likelihoods can be used to predict the effect of a mutation in a zero-shot manner (i.e., without any additional training) by comparing the likelihood of the mutated amino acid to that of the wildtype amino acid at a given position [6, 7, 12, 13].

However, a major limitation of the zero-shot likelihood approach is that it predicts the same likelihood for a mutation regardless of the protein function in question [7]. Since proteins can have multiple functions that are affected differently by the same mutation, one likelihood cannot model the effect of a mutation on all of these functions simultaneously. Additionally, the likelihood only accounts for the protein that is mutated, which means that it ignores any interacting proteins such as antibodies.

We propose to overcome these limitations by modeling immune escape using antibody and antigen embeddings produced by a pretrained protein language model. These embeddings encode information about the protein, including aspects of 3D structure, that can inform the effect of protein mutations [14]. We build a lightweight neural model that learns to extract information from the embeddings to predict escape in an antibody-dependent manner. We develop several variants of this embedding-based approach and evaluate them on a SARS-CoV-2 deep mutational scanning dataset from [5]. We show that embeddings significantly outperform zero-shot likelihoods, which have almost no predictive power. We discuss insights gained from our experiments about how best to use embeddings from pretrained protein language models to predict escape. We also develop two statistical baseline models and a machine learning model that do not rely on the pretrained models. These models perform comparably to the embedding models, indicating that pretrained embeddings may not be beneficial for predicting escape. Furthermore, the relatively poor performance of all models demonstrates that future work is necessary to improve escape prediction with or without pretrained embeddings.

2 Methods

Our goal is to design a model that can predict the effect of antigenic single point mutations on the neutralization ability of antibodies. The input to the model is the amino acid sequences of the antibody's heavy and light chains, the amino acid sequence of the wildtype antigen, the site on the antigen that is mutated, and the new amino acid that replaces the wildtype amino acid at that site. The output of the model is an escape score, which represents the degree to which antibody neutralization is reduced by the mutated antigen. Below, we outline a several models to predict escape either using simple statistics, a machine learning model trained from scratch, or machine learning models built on top of pretrained protein language models.

2.1 Mutation Model

The mutation model computes the average escape score for each pair of (`wildtype, mutant`) amino acids and uses that average to predict escape for new antigens with the same amino acid mutation pair. This model ignores the antibody sequences and the entire antigen sequence except for the site that is mutated, and it assumes that escape depends solely on the identities of the wildtype and mutant amino acids. Since there are 20 amino acids, this model has $20 \times 20 = 400$ parameters.

2.2 Site Model

The site model computes the average escape score for each antigen site and uses that average to predict escape for new antigens with the same mutation site. Like the mutation model, this model ignores the antibody sequences and the entire antigen sequence except for the mutated site. Additionally, it ignores the identities of the wildtype and mutant amino acids. The model has one parameter for each site of the antigen.

2.3 RNN

To evaluate the benefit of using pretrained protein language models for predicting escape, we train a recurrent neural network (RNN) from scratch as a non-pretrained baseline. We specifically use a bidirectional LSTM [15] to encode the mutated antigen sequence, and we extract the output embedding from the LSTM at the mutated site and pass it through a small multilayer perceptron to predict escape.

2.4 Likelihood Model

For our likelihood model, we adopt the zero-shot mutation prediction framework of [7]. In this framework, the antigen sequence is input to a pretrained protein language model model with the mutated site replaced by a mask token, and the escape score is predicted as the model's log odds ratio of the mutated amino acid versus the wildtype amino acid at that site. The likelihood model does not require any additional training and it does not incorporate the antibody sequences.

2.5 Embedding Models

Models that use pretrained protein language model embeddings provide a more flexible way of predicting mutation effect. In these models, we train a small multilayer perceptron to use some form of protein embedding as input to predict the escape score. All of the models use an embedding of the mutated antigen, and some additionally use an embedding of the wildtype antigen and/or embeddings of the antibody heavy and light chains. The embedding variants are described below.

Antigen Mutant Sequence. The language model is given the mutated antigen sequence and computes embeddings for each amino acid. Each embedding encodes the identity of the amino acid as well as its role in the context of the antigen sequence. The amino acid embeddings are averaged to form an embedding for the full antigen sequence. We refer to this embedding as Antigen Mut Seq.

Antigen Mutant Residue. As above, embeddings are computed for each amino acid in the mutated antigen. Here, the embedding of the mutated residue is used instead of the sequence average. We refer to this embedding as Antigen Mut Res.

Antigen Difference. Antigen embeddings for both the mutated sequence and the wildtype sequence are computed, either both at the sequence level or both at the residue level. The difference between the embeddings (mutant minus wildtype) is computed. We refer to these embeddings as Antigen Seq Diff for the difference of sequence embeddings and Antigen Res Diff for the difference of residue embeddings. We also try concatenating the mutant and difference embeddings to form what we call Antigen Seq MutDiff and Antigen Res MutDiff embeddings.

Antibody. In addition to any of the antigen embedding types above, the language model computes embeddings for the heavy and light chains of the antibody. The antigen, antibody heavy chain, and antibody light chain embeddings are concatenated. We refer to these embeddings as the name of the antigen embedding + Antibody.

3 Experiments

Here, we describe the data we use to train and evaluate our model as well as the data splits, tasks, metrics, and models that we use.

3.1 Data

We use SARS-CoV-2 deep mutational scanning data from [5]. This data consists of 247 antibodies that are known to neutralize the original strain of SARS-CoV-2 by binding to the receptor binding

Figure 1: The average escape score across all amino acid mutations for each antibody and each antigen site in the receptor binding domain (RBD) in the SARS-CoV-2 deep mutational scanning data from [5]. Note: The 74 escape scores greater than 1 (max 3.6) are truncated to 1.

domain (RBD) of the spike protein. The neutralization ability of each antibody is measured for the wildtype RBD antigen as well as for all 3,819 single point mutations to the antigen (201 sites in the RBD with 19 amino acid substitutions at each site). For each antibody and each antigen mutation, an escape score is computed as a normalized measure of the reduction in antibody neutralization compared to the wildtype antigen (see Figures 1 and 4). Of the 943,293 escape scores in the dataset, 30,658 (3.2%) are non-zero, usually in the range [0, 1] with 74 outliers above 1 with a max of 3.6 (see Figure 3). The authors of [5] clustered the 247 antibodies into six groups based on their escape scores (see Figure 5).

3.2 Data Splits

The practical usefulness of an escape prediction model, as well as the difficulty of learning such a model, depends heavily on how the data is split. Below we describe the data splits we use.

Mutation. Mutations are randomly split between train and test. This assumes that for a new antibody, we already know escape scores for some but not all mutations across all antigen sites.

Site. Antigen sites are randomly split between train and test. This assumes that for a new antibody, we already know escape scores for some but not all antigen sites.

Antibody. Antibodies are randomly split between train and test. This assumes that we do not know any escape scores for a new antibody, but that antibody may have a similar pattern of escape to antibodies in the train set.

Antibody group. Antibody groups, as defined by a clustering of escape scores, are randomly split between train and test. This assumes that we do not know any escape scores for a new antibody, and no antibody in the train set has a similar pattern of escape to that antibody.

The latter two splits are more practically useful because they demonstrate the effectiveness of escape prediction for antibodies that have not undergone any experimental escape measurements. Models that are effective under these data splits could be used to guide antibody selection or design.

For all four splits, we train and test the models across all antibodies (cross-antibody setting) using five-fold cross-validation. For the mutation and site splits, we also train and test separate models for each of the 247 antibodies (per-antibody setting) since each antibody can appear in train and test.

3.3 Tasks and Metrics

For all of the models except for the likelihood model, which doesn't require training, we train the model either for a regression task, where escape scores are real values, or for a classification task, where escape scores are binarized into zero or non-zero escape. All models are evaluated with the metrics ROC-AUC (area under the receiver operating characteristic curve) and PRC-AUC (area under the precision recall curve), and regression models are additionally evaluated with the metrics MSE (mean squared error) and R^2 (coefficient of determination).

3.4 Models

Below we describe the implementation details of the models we developed. All models were built using PyTorch version 1.12.1 [16].

3.4.1 RNN

The RNN is a bidirectional LSTM with a hidden dimensionality of 100. The input to the RNN is the antigen sequence with amino acids encoded using trainable embeddings with a dimensionality of 100. The output of the RNN is an embedding for each amino acid with a dimensionality of 200 (100 for each direction of the RNN). The output embedding for the mutated amino acid is used as input to a small multilayer perceptron (see below), which makes escape predictions. The amino acid embeddings, RNN, and multilayer perceptron are trained end-to-end.

3.4.2 Protein Language Model

For the likelihood and embedding models, we use the pretrained protein language model ESM2 [14]. We specifically use the `esm2_t33_650M_UR50D` version of the model consisting of 33 layers and 650M parameters that was trained on the UniRef50 database [17]. The embeddings produced by this model have a dimensionality of 1,280 and are used as fixed input to a small multilayer perceptron (see below).

3.4.3 Multilayer Perceptron

The multilayer perceptron (MLP) model that we used with the RNN and with all of the pretrained embeddings has two hidden layers with 100 neurons in each layer and ReLU activation followed by a single output. For classification tasks, we apply a sigmoid activation to the output.

3.4.4 Training

The RNN and the embedding models were trained with mean squared error loss for regression and binary cross entropy for classification using the Adam optimizer [18]. Per-antibody models were trained for 50 epochs while cross-antibody models were trained for one epoch. The RNN model was trained on a single GPU, with training taking about 3 minutes for a cross-antibody model (one fold) and about 30 seconds for each per-antibody model. The embedding models were trained on a single

Figure 2: Classification model results with the PRC-AUC metric across data splits (x-axis) and models (color-coded bars). Error bars indicate the standard deviation across 247 antibodies for per-antibody splits and across five-fold cross-validation for cross-antibody splits.

CPU, with training taking about 1 minute for a cross-antibody model (one fold) and about 15 seconds for each per-antibody model.

4   Results

In this section, we highlight some of the key results from our experiments (see Figure 2). We only show classification model results since the regression models performed poorly. Additionally, since the relative ranking of models was similar between ROC-AUC and PRC-AUC but the differences in PRC-AUC scores were more noticeable, we only present PRC-AUC results. We show results for all data splits and for a subset of the models, leaving out embedding models whose performance was not insightful for space. The complete set of results across all settings is in Appendix C.

4.1   Mutation Model

The mutation model is a very weak model. On the mutation and site splits in the per-antibody setting, the model has essentially no predictive power, and on all four splits in the cross-antibody setting, the model performs poorly. This is to be expected since the model ignores the mutation site even though the mutation site is very informative of immune escape due to the consistent interaction of key sites with neutralizing antibodies.

4.2 Site Model

The site model is strong across most splits, with the exception of the site split where the model has no information about unseen sites. The site model is frequently competitive with the best embedding models despite containing only 201 parameters instead of 650M parameters. The site model is significantly more effective in the per-antibody mutation split than in any of the cross-antibody splits since escape is highly consistent at a given antigen site for an antibody across amino acid mutations. Even so, the fact that the model retains some predictive power across antibodies and antibody groups indicates that patterns of escape at specific sites are conserved.

4.3 RNN

The RNN model performs comparatively well across all splits. It is only outperformed by the embedding model that includes antibody embeddings, which is reasonable given that the RNN only processes the antigen sequence and has no knowledge of the antibody. Notably, the model performs on par with or better than most of the embedding models, even on the site split, despite training in just a couple of minutes with no expensive pretraining needed. This shows that existing pretraining methods and models may not be particularly beneficial for escape prediction, at least for this dataset.

4.4 Likelihood Model

The likelihood model has virtually no predictive power across all data splits. This is in contrast to examples in the literature where likelihoods achieve reasonable mutation effect prediction performance [7]. This finding demonstrates a fundamental limitation of the zero-shot prediction framework since likelihoods derived from models trained to recreate naturally occurring proteins may not be calibrated to predict the probability of antigen escape.

4.5 Embedding Models

The embedding models significantly outperform the likelihood model across all data splits. This indicates that pretrained protein language models do contain information that is useful for mutation effect prediction but require that their representations are adapted to the task rather than used in a zero-shot manner. However, the strength of the RNN model indicates that pretrained embeddings are not necessary for escape prediction. Even so, the embedding model results still provide several interesting takeaways regarding how best to use pretrained embeddings to predict escape in cases where they may be useful.

Mutant vs Difference. The Antigen Seq Diff embedding consistently outperforms the Antigen Seq Mut embedding, which indicates that the change in embedding from wildtype to mutant is more informative than the mutant embedding in isolation. The concatenation of the mutant and difference embeddings (MutDiff) does not improve performance further, indicating that the mutant embeddings do not contribute information beyond that contained in the difference embeddings.

Sequence vs Residue. The Antigen Res Mut embedding outperforms the Antigen Seq embeddings, perhaps because the sequence embeddings contain largely irrelevant information from the non-mutated residues. Interestingly, using embedding differences instead of mutant embeddings does not improve performance at the residue level (see Appendix C).

Antibody. As seen from the Antigen Res Mut + Antibody embedding, including antibody embeddings provides a benefit in all cross-antibody data splits except for the antibody group split. This indicates that the antibody embedding is useful only in cases with the same or a similar antibody but not with a very different antibody.

5   Conclusion

We presented several methods for predicting immune escape using pretrained protein language model embeddings. We performed a comprehensive set of experiments on a SARS-CoV-2 deep mutational scanning dataset and showed that embeddings from these language models are much more effective at predicting escape than zero-shot likelihoods. Notably, the Antigen Res Mut + Antibody embeddings was the top performer, indicating that escape is best modeled at the residue level with both antigen and antibody embeddings. Although these results are promising, the relatively strong performance of the site model and the RNN, neither of which rely on computationally expensive pretraining, show that pretrained protein language model embeddings may not be particularly beneficial for tasks such as escape prediction. Furthermore, the overall poor performance of all models across most splits demonstrates that significant future work is needed to make accurate and useful escape predictions. Notably, the results here are limited to a single antibody-antigen escape prediction task and dataset. The comprehensive nature of the data, which includes every possible single point mutation of the antigen for every antibody, strengthens our conclusions, but further experimentation on additional escape datasets is necessary to validate whether the conclusions drawn here generalize to other escape prediction tasks.

References

1. Rai, K. R. *et al.* Acute Infection of Viral Pathogens and Their Innate Immune Escape. *Frontiers in Microbiology* **12.** ISSN: 1664-302X. https://www.frontiersin.org/articles/10.3389/fmicb.2021.672026 (2021).

2. Kapingidza, A. B., Kowal, K. & Chruszcz, M. in *Vertebrate and Invertebrate Respiratory Proteins, Lipoproteins and other Body Fluid Proteins* (eds Hoeger, U. & Harris, J. R.) 465–497 (Springer International Publishing, Cham, 2020). ISBN: 978-3-030-41769-7. https://doi.org/10.1007/978-3-030-41769-7_19.

3. Starr, T. N. *et al.* Prospective mapping of viral mutations that escape antibodies used to treat COVID-19. *Science* **371,** 850–854. eprint: https://www.science.org/doi/pdf/10.1126/science.abf9302. https://www.science.org/doi/abs/10.1126/science.abf9302 (2021).

4. Hie, B., Zhong, E. D., Berger, B. & Bryson, B. Learning the language of viral evolution and escape. *Science* **371,** 284–288. eprint: https://www.science.org/doi/pdf/10.1126/science.abd7331. https://www.science.org/doi/abs/10.1126/science.abd7331 (2021).

5. Cao, Y. *et al.* Omicron escapes the majority of existing SARS-CoV-2 neutralizing antibodies. *Nature* **602,** 657–663. ISSN: 1476-4687. https://doi.org/10.1038/s41586-021-04385-3 (Feb. 2022).

6. Frazer, J. *et al.* Disease variant prediction with deep generative models of evolutionary data. *Nature* **599,** 91–95. ISSN: 1476-4687. https://doi.org/10.1038/s41586-021-04043-8 (Nov. 2021).

7. Meier, J. *et al.* Language models enable zero-shot prediction of the effects of mutations on protein function. *bioRxiv.* eprint: https://www.biorxiv.org/content/early/2021/11/17/2021.07.09.450648.full.pdf. https://www.biorxiv.org/content/early/2021/11/17/2021.07.09.450648 (2021).

8. Taft, J. M. *et al.* Deep mutational learning predicts ACE2 binding and antibody escape to combinatorial mutations in the SARS-CoV-2 receptor-binding domain. *Cell.* ISSN: 0092-8674. https://www.sciencedirect.com/science/article/pii/S0092867422011199 (2022).

9. Shan, S. *et al.* Deep learning guided optimization of human antibody against SARS-CoV-2 variants with broad neutralization. *Proceedings of the National Academy of Sciences* **119,** e2122954119. eprint: https://www.pnas.org/doi/pdf/10.1073/pnas.2122954119. https://www.pnas.org/doi/abs/10.1073/pnas.2122954119 (2022).

287 10. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised learning
288   to 250 million protein sequences. *Proceedings of the National Academy of Sciences* **118,**
289   e2016239118. eprint: `https://www.pnas.org/doi/pdf/10.1073/pnas.2016239118`.
290   `https://www.pnas.org/doi/abs/10.1073/pnas.2016239118` (2021).

291 11. Nijkamp, E., Ruffolo, J., Weinstein, E. N., Naik, N. & Madani, A. *ProGen2: Exploring the*
292   *Boundaries of Protein Language Models* 2022. `https://arxiv.org/abs/2206.13517`.

293 12. Riesselman, A. J., Ingraham, J. B. & Marks, D. S. Deep generative models of genetic variation
294   capture the effects of mutations. *Nature Methods* **15,** 816–822. ISSN: 1548-7105. `https:`
295   `//doi.org/10.1038/s41592-018-0138-4` (Oct. 2018).

296 13. Shin, J.-E. *et al.* Protein design and variant prediction using autoregressive generative models.
297   *Nature Communications* **12,** 2403. ISSN: 2041-1723. `https://doi.org/10.1038/s41467-`
298   `021-22732-w` (Apr. 2021).

299 14. Lin, Z. *et al.* Language models of protein sequences at the scale of evolution enable accurate
300   structure prediction. *bioRxiv.* eprint: `https://www.biorxiv.org/content/early/2022/`
301   `07/21/2022.07.20.500902.full.pdf. https://www.biorxiv.org/content/early/`
302   `2022/07/21/2022.07.20.500902` (2022).

303 15. Hochreiter, S. & Schmidhuber, J. Long Short-Term Memory. *Neural Computation* **9,** 1735–
304   1780. ISSN: 0899-7667. eprint: `https://direct.mit.edu/neco/article-pdf/9/8/`
305   `1735/813796/neco.1997.9.8.1735.pdf. https://doi.org/10.1162/neco.1997.9.`
306   `8.1735` (Nov. 1997).

307 16. Paszke, A. *et al.* in *Proceedings of the 33rd International Conference on Neural Information*
308   *Processing Systems* (Curran Associates Inc., Red Hook, NY, USA, 2019).

309 17. Suzek, B. E. *et al.* UniRef clusters: a comprehensive and scalable alternative for improving
310   sequence similarity searches. *Bioinformatics* **31,** 926–932. ISSN: 1367-4803. eprint: `https://`
311   `academic.oup.com/bioinformatics/article-pdf/31/6/926/569379/btu739.pdf.`
312   `https://doi.org/10.1093/bioinformatics/btu739` (Nov. 2014).

313 18. Kingma, D. P. & Ba, J. *Adam: A Method for Stochastic Optimization* in *3rd International*
314   *Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015,*
315   *Conference Track Proceedings* (eds Bengio, Y. & LeCun, Y.) (2015). `http://arxiv.org/`
316   `abs/1412.6980`.

A   Data and Code Availability

318 The SARS-CoV-2 deep mutational scanning data from [5] is available at `https://github.`
319 `com/jbloomlab/SARS2_RBD_Ab_escape_maps/tree/main/data/2022_Cao_Omicron`.   The
320 file `data.csv` contains the escape data for each antibody-antigen mutation combination, and the
321 file `antibodies.csv` contains the sequences for the heavy and light chains for all the antibodies.
322 The ESM2 pretrained protein language model [7] that we used is the `esm2_t33_650M_UR50D` model
323 from `https://github.com/facebookresearch/esm`. Our code will be made available.

B   Data Visualization

325 The figures in this section visualize the SARS-CoV-2 deep mutational scanning data from [5].

Figure 3: The distribution of the 30,658 non-zero escape scores in the SARS-CoV-2 deep mutational scanning data from [5]. Note: The 74 escape scores greater than 1 (max 3.6) are truncated to 1.

Figure 4: The average escape score across all antibodies and all antigen sites for each wildtype to mutant amino acid change in the SARS-CoV-2 deep mutational scanning data from [5]. Note: The 74 escape scores greater than 1 (max 3.6) are truncated to 1.

Figure 5: The average escape score across all amino acid mutations for each antibody and each antigen site in the receptor binding domain (RBD), grouped according to the antibody clusters defined by [5]. Note: The 74 escape scores greater than 1 (max 3.6) are truncated to 1.

C Complete Results

This section contains the complete set of results for all data splits, models, and tasks. The results will also be made available in tabular form along with the code.

Figure 6: Classification model results using the PRC-AUC metric.

Figure 7: Classification model results using the ROC-AUC metric.

Figure 8: Regression model results using the PRC-AUC metric.

Figure 9: Regression model results using the ROC-AUC metric.

Figure 10: Regression model results using the MSE metric.

Figure 11: Regression model results using the R^2 metric.