GENERATIVE PRETRAINING FOR BLACK-BOX OPTIMIZATION

ABSTRACT

Many problems in science and engineering involve optimizing an expensive black-box function over a high-dimensional space. For such black-box optimization (BBO) problems, we typically assume a small budget for online function evaluations, but also often have access to a fixed, offline dataset for pretraining. Prior approaches seek to utilize the offline data to approximate the function or its inverse but are not sufficiently accurate far from the data distribution. We propose BONET, a generative framework for pretraining a novel black-box optimizer using offline datasets. In BONET, we train an autoregressive model on fixed-length trajectories derived from an offline dataset. We design a sampling strategy to synthesize trajectories from offline data using a simple heuristic of rolling out monotonic transitions from low-fidelity to high-fidelity samples. Empirically, we instantiate BONET using a causally masked Transformer (Radford et al., 2019) and evaluate it on Design-Bench (Trabucco et al., 2022), where we rank the best on average, outperforming state-of-the-art baselines.

1 INTRODUCTION

Many fundamental problems in science and engineering, ranging from the discovery of drugs and materials to the design and manufacturing of hardware technology, require optimizing an expensive black-box function in a large search space (Larson et al., 2019; Shahriari et al., 2016). The key challenge here is that evaluating and optimizing such a black-box function is typically expensive, as it often requires real-world experimentation and exploration of a high-dimensional search space.

Fortunately, for many such black-box optimization (BBO) problems, we often have access to an offline dataset of function evaluations. Such an offline dataset can greatly reduce the budget for online function evaluation. This introduces us to the setting of offline BBO. A key difference exists between the offline BBO setting and its online counterpart; in offline BBO, we are **not** allowed to actively query the black-box function during optimization, unlike in online BBO where most approaches (Snoek et al., 2012; Shahriari et al., 2016) utilize iterative online solving. One natural approach for offline BBO would be to train a surrogate (forward) model that approximates the black-box function using the offline data. Once learned, we can perform gradient ascent on the input space to find the optimal point. Unfortunately, this method does not perform well in practice because the forward model can incorrectly give sub-optimal and out-of-domain points a high score (see Figure 1a). To mitigate this issue, COMs (Trabucco et al., 2021) learns a forward mapping that penalizes high scores on points outside the dataset, but this can have the opposite effect of not being able to explore high fidelity points that are far from the dataset. Further, another class of recent approaches (Kumar & Levine, 2020; Brookes et al., 2019; Fannjiang & Listgarten, 2020) propose a conditional generative approach that learns an inverse mapping function values to the points. For effective generalization, such a mapping needs to be highly multimodal for high-dimensional functions, which in itself presents a challenge for current approaches.

We propose **B**lack-box **O**ptimization **Net**works (BONET), a new generative framework for pretraining black-box optimizers on offline datasets. Instead of approximating the surrogate function (or its inverse), we seek to approximate the dynamics of online black-box optimizers using an autoregressive sequence model. Naively, this would require access to several trajectory runs of different black-box optimizers, which is expensive or even impossible in many cases. Our key observation is that we can synthesize synthetic trajectories comprised of offline points that mimic empirical charac-

Figure 1: (a) Example of offline BBO on toy 1D problem. Here, the domain ends at the red dashed line. Thus, the correct optimal value is $\mathbf{x}^*$, whereas gradient ascent on the fitted function will output out of the domain point $\bar{\mathbf{x}}$. (b) Example trajectory on the 2D-Branin function. The dotted lines denote the trajectories in our offline dataset, and the solid line refers to our model trajectory, with low-quality blue points and high-quality red points. (c) Function values of trajectories generated by a simple gaussian process (GP) based BayesOpt model on several synthetic functions.

teristics of online BBO algorithms, such as BayesOpt. While one could design many characteristic properties, we build off an empirical observation relating to the function values of the proposed points. In particular, averaged over multiple runs, online black-box optimizers (e.g., BayesOpt) tend to show improvements in the function values of the proposed points (Bijl et al., 2016), as shown in Figure 1c. While not exact, we build on this observation to develop a sorting heuristic that constructs synthetic trajectories consisting of offline points ordered monotonically based on their ascending function values. Even though such a heuristic does not apply uniformly for the trajectory runs of all combinations of black-box optimizers and functions, we show that it is simple, scalable, and quite effective in practice.

Further, we augment every offline point in our trajectories with a *regret budget*, defined as the cumulative regret of the trajectory starting at the current point until the end of the trajectory. We train BONET to generate trajectories conditioned on the regret budget of the first point of the trajectory. Thus, at test time, we can generate good candidate points by rolling out a trajectory with a low regret budget. Figure 1b shows an illustration.

We evaluate our method on several real-world tasks in the Design-Bench (Trabucco et al., 2022) dataset. These tasks are based on real-world problems such as robot morphology optimization, DNA sequence optimization, and optimizing superconducting temperature of materials, all of which requires searching over a high-dimensional search space. We achieve a normalized mean score of **0.772** and an average rank of **2.4** across all tasks, outperforming the next best baseline, which achieves a rank of 3.7.

2 PRETRAINING BLACK-BOX OPTIMIZERS VIA BONET

2.1 PROBLEM STATEMENT

Let $f : \mathcal{X} \to \mathbb{R}$ be a black-box function, where $\mathcal{X} \subseteq \mathbb{R}^d$ is an arbitrary d-dimensional domain. In black-box optimization (BBO), we are interested in finding the point $\mathbf{x}^*$ that maximizes f:

$$\mathbf{x}^* \in \arg\max_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x}) \tag{1}$$

Typically, f is expensive to evaluate and we do not assume direct access to it during training. Instead, we have access to an offline dataset of N previous function evaluations $\mathcal{D} = \{(\mathbf{x}_1, y_1), \cdots, (\mathbf{x}_N, y_N)\}$, where $y_i = f(\mathbf{x}_i)$. For evaluating a black-box optimizer post-training, we allow it to query the black-box function f for a small budget of Q queries and output the point with the best function value obtained. This protocol follows prior works in offline BBO (Trabucco et al., 2021; 2022; Kumar & Levine, 2020; Brookes et al., 2019; Fannjiang & Listgarten, 2020).

Overview of BONET We illustrate our proposed framework for offline BBO in Figure 2 and Algorithm 1 . BONET consists of 3 sequential phases: trajectory construction, autoregressive modelling,

Figure 2: Schematic for BONET. In Phase 1, we construct a trajectory dataset $\mathcal{D}_{\text{traj}}$ using SORT-SAMPLE. In Phase 2, we learn an autoregressive model for $\mathcal{D}_{\text{traj}}$. In Phase 3, we condition the model on an offline prefix sequence and unroll it further to obtain candidate proposals $\hat{\mathbf{x}}_{P+1:T}$.

roll-out evaluation. In Phase 1 (Section 2.2), we transform the offline dataset $\mathcal{D}$ into a trajectory dataset $\mathcal{D}_{\text{traj}}$. This is followed by Phase 2 (Section 2.3), where we train an autoregressive model on $\mathcal{D}_{\text{traj}}$. Finally, we evaluate the model by rolling out Q candidate points in Phase 3 (Section 2.4).

2.2 PHASE 1: CONSTRUCTING TRAJECTORIES

Our key motivation in BONET is to train a model to mimic the sequential behavior of online black-box optimizers. However, the difficulty is that we do not have the ability to generate trajectories by actively querying the black-box function during training. In BONET, we overcome this difficulty by synthesizing trajectories purely from an offline dataset based on two guiding desiderata.

Algorithm 1 **B**lack-box **O**ptimization **Net**works (BONET)

    Input Offline dataset $\mathcal{D}$, Evaluation Regret Budget $\hat{R}$, Prefix length P, Query budget Q, Trajectory length T, num_trajs, Smoothing parameter K, Temperature τ, Number of bins N_B
    Output A set of proposed candidate points $\mathbf{X}$ with the constraint $|\mathbf{X}| \leq Q$
1: ▷ **Phase** 1: SORT-SAMPLE
2: Construct bins $\{B_1, \cdots, B_{N_B}\}$ from $\mathcal{D}$, each bin covering equal y-range, as described in 2.2
3: Calculate the scores $(n_1, n_2, \cdots, n_{N_B})$ for each bin using K and τ
4: $\mathcal{D}_{\text{traj}} \leftarrow \phi$
5: **for** $i = 1, \cdots,$ num_trajs **do**
6:     Uniformly randomly sample n_i points from B_i and concatenate them to construct $\mathcal{T}$
7:     Sort $\mathcal{T}$ in the ascending order of the function value
8:     Represent $\mathcal{T}$ as $(R_1, \mathbf{x}_1, R_2, \mathbf{x}_2, \cdots, R_T, \mathbf{x}_T)$, following equation 3, and append $\mathcal{T}$ to $\mathcal{D}_{\text{traj}}$
9: **end for**
10: ▷ **Phase** 2: Training
11: Train the model g_θ to maximize the log-likelihood of $\mathcal{D}_{\text{traj}}$ using the loss in equation 4
12: ▷ **Phase** 3: Evaluation
13: Construct a trajectory $\mathcal{T}'$ from $\mathcal{D}$ following Phase 1, and delete the last $T - P$ points
14: Calculate R_t and feed $(R_t, \mathbf{x}_t)$ to g_θ sequentially, $\forall t = 1, \cdots, P$
15: Roll-out g_θ autoregressively while feeding $R_t = \hat{R}, \forall t = P+1, \cdots, T$
16: $\mathbf{X}$ is the set of last $\min(Q, T - P)$ rolled-out points.

First, the procedure for synthesizing trajectories should efficiently scale to high-dimensional data points and large offline datasets. Second, each trajectory should mimic characteristic behaviors commonly seen in online black-box optimizers. We identify one such characteristic of interest. In particular, we note that the moving average of function values of points proposed by such black-box optimizers tends to improve over the course of their runs barring local perturbations (e.g., due to

exploration). While exceptions can and do exist, this phenomena is commonly observed in practice for optimizers such as BayesOpt (Bijl et al., 2016). We also illustrate this behavior in Figure 1c for some commonly used test functions optimized via BayesOpt.

Sorted Trajectories We propose to satisfy the above desiderata in BONET by following a sorting heuristic. Specifically, given a set of T offline points, we construct a trajectory of length T by simply sorting the points in ascending order from low to high function values. We note that sorting is just a heuristic we use for constructing synthetic trajectories from the offline dataset, and this behavior may not be followed by any general optimizer over any arbitrary functions. We also perform ablations on different heuristics in Appendix C.1. Further, we note that sorting does not provide any guidance on the rate or the relative spacing between the points i.e., how fast the function values increase. This rate is important for controlling the sample budget for black-box optimization. Next, we discuss a sampling strategy for explicitly controlling this rate.

Sampling Strategies for Offline Points So far, we have proposed a simple heuristic for transitioning a set of offline points into a sorted trajectory. To obtain these offline trajectory points from the offline dataset, one default strategy is to sample uniformly at random T points from $\mathcal{D}$ and sort them. However, we found this strategy to not work well in practice. Intuitively, we might expect a large volume of the search space to consist of points with low-function values.

(a)   (b)

Figure 3: Plots showing the distribution of function values in the offline dataset $\mathcal{D}$ (left) and the trajectories in $\mathcal{D}_{\text{traj}}$ (right) for the Ant Morphology benchmark (Trabucco et al., 2022). Notice how the overall density of points with high function values is up-weighted post our re-weighting.

Thus, if our offline dataset is uniformly distributed across the domain, the probability of getting a high quality point will be very low with a uniform sampling strategy. To counter this challenge, we propose a 2 step sampling strategy based on binning followed by importance reweighting. Our formulation is motivated by a similar strategy proposed by Kumar & Levine (2020) for loss reweighting. First, we use the function values to partition the offline dataset $\mathcal{D}$ into N_B bins of equal-width, i.e., each bin covers a range of equal length. Next, for each bin, we assign a different sampling probability, such that (a) bins where the average function value is high are more likely to be sampled, and (b) bins with more points are sampled more often. The former helps minimize the budget, whereas the latter ensures diversity in trajectories. Based on these two criteria, the score s_i for a bin B_i is given as:

$$s_i = \frac{|B_i|}{|B_i| + K} \exp\left(\frac{-|\hat{y} - y_{b_i}|}{\tau}\right) \tag{2}$$

where $\hat{y}$ is the best function value in the dataset $\mathcal{D}$, $|B_i|$ refers to the number of points in the i^{th} bin, and y_{b_i} is the midpoint of the interval corresponding to the bin B_i. Here, the first term $\frac{|B_i|}{|B_i| + K}$ allows us to assign a higher weight to the larger bins with smoothing. The second term gives higher weight to the good bins using an exponential weighting scheme. More details about K and τ can be found in Appendix B. Finally, we use these scores s_i to proportionally sample n_i points from bin B_i where $n_i = T \left\lfloor \frac{s_i}{\sum_j s_j} \right\rfloor$ for $i \in \{2, \cdots, N_B\}$ and $n_1 = T - \sum_{i>1} n_i$, making the overall length of the trajectories equal to T. In Figure 3, we illustrate the shift in distribution of function values due to our sampling strategy. We refer to the combined strategy of sampling and then sorting as SORT-SAMPLE in Figure 2 and Algorithm 1.

Augmenting Trajectories With Regret Budgets Our sorted trajectories heuristically reflect rollouts of implicit black-box optimizers. However they do not provide us with information on the rate at which a trajectory approaches the optimal value. A natural choice for such a knob would be the cumulative regret. Moreover, as we shall show later, cumulative regret provides BONET a simple and effective knob to generalize outside the offline dataset during the evaluation phase.

Hence, we propose to augment each data point $\mathbf{x}_i$ in our trajectory with a Regret Budget (RB). The RB R_i at timestep i defined as the cumulative regret of the trajectory, starting at point $\mathbf{x}_i$: $R_i = \sum_{j=i}^{T}(f(\mathbf{x}^*) - f(\mathbf{x}_j))$. Intuitively, a high (low) value for R_i is likely to result in a high (low) budget for the model to explore diverse points. Note, we are only assuming knowledge of an estimate for $f(\mathbf{x}^*)$ (and not $\mathbf{x}^*$). Thus, each trajectory in our desired set $\mathcal{D}_{\text{traj}}$ can be represented as:

$$\mathcal{T} = (R_1, \mathbf{x}_1, R_2, \mathbf{x}_2, \cdots, R_T, \mathbf{x}_T) \tag{3}$$

We will refer to R_1 as Initial Regret Budget (IRB) henceforth. This will be of significance for evaluating our model in Phase 3 (Section 2.4), as we can specify a low IRB to induce the model to output points close to the optima.

2.3 PHASE 2: TRAINING AN AUTOREGRESSIVE GENERATIVE MODEL

Given our trajectory dataset, we design our BBO agent as a conditional autoregressive model and train it to maximize the likelihood of trajectories in $\mathcal{D}_{\text{traj}}$. More formally, we denote our model parameterized by θ as $g_\theta(\mathbf{x}_t | \mathbf{x}_{<t}, R_{\leq t})$, where by $k_{<t}$ we mean the set $\{k_1, \cdots, k_{t-1}\}$. Here, $\mathbf{x}_i$ are the sequence of points in a trajectory, and R_i refers to the regret budget at timestep i.

Building on recent advances in sequence modeling (Vaswani et al., 2017; Brown et al., 2020; Radford et al., 2019) , we instantiate our model with a causally masked transformer and train it to maximize the likelihood of our trajectory dataset $\mathcal{D}_{\text{traj}}$.

$$\mathcal{L}(\theta; \mathcal{D}_{\text{traj}}) = \mathop{\mathbb{E}}_{\mathcal{T} \sim \mathcal{D}_{\text{traj}}} \left[\sum_{i=1}^{T} \log g_\theta(\mathbf{x}_i | \mathbf{x}_{<i}, R_{\leq i}) \right] \tag{4}$$

In practice, we translate this loss to the mean squared error loss for a continuous $\mathcal{X}$ (equivalent to a Gaussian g_θ with fixed variance), and cross entropy loss for a discrete $\mathcal{X}$.

2.4 PHASE 3: EVALUATION ROLLOUT OF FINAL CANDIDATES

Once trained, we can use our BBO agent to directly output new points as its candidate guesses for maximizing the black-box function. We do so by rolling out evaluation trajectories from our model. Each trajectory will be subdivided into a *prefix subsequence* and a *prediction subsequence*. The prefix subsequence consists of $P < T$ points sampled from our offline dataset as before. These prefix points provide initial warm-up queries to the model. Thereafter, we rollout the prediction subsequence consisting of $T - P$ points by sampling from our autoregressive generative model.

Setting Regret Budgets One key question relates to setting the regret budget at the start of the suffix subsequence. It is not preferable to set it to R_{P+1} of the sampled trajectory, as doing so will lead to a slow rate of reaching high-quality regions similar to the one observed in the training trajectories. This will not allow the suffix to generalize beyond the offline dataset.

Alternatively, we initialize it to a low value in BONET to accelerate the trajectory towards good points following a prefix subsequence. We refer to this low value as Evaluation RB and denote it as $\hat{R}$ in Figure 2 and in Section 3. Thereafter, we keep the RB for the suffix subsequence fixed ($\hat{R}$), as the agent is expected to be already in a good region. Moreover, updating the RB here would require sequential querying to the function f, which can be prohibitive. Thus, our evaluation protocol can generate a set of candidate queries purely in an offline manner. In practice, we also find it helpful to split the Q candidates among a few (and not 1) small $\hat{R}$ values, each with a different prefix.

3 EXPERIMENTAL EVALUATION

We first empirically evaluate BONET for optimizing a synthetic 2D function, Branin, in order to analyze its working and probe the various components. Next, we perform large-scale benchmarking and experiments on Design-Bench (Trabucco et al., 2022), a suite of offline BBO tasks based on real-world problems.

3.1 Branin Task

Branin is a well-known benchmark function for evaluating optimization methods. It is a 2D function evaluated on the ranges $x_1 \in [-5, 10]$ and $x_2 \in [0, 15]$:

$$f_{br}(x_1, x_2) = a(x_2 - bx_1^2 + cx_1 - r)^2 + s(1 - t)\cos x_1 + s \qquad (5)$$

where $a = -1$, $b = \frac{5.1}{4\pi^2}$, $c = \frac{5}{\pi}$, $r = 6$, $s = -10$, and $t = \frac{1}{5\pi}$. In this square region, f_{br} has three global maximas, $(-\pi, 12.275)$, $(\pi, 2.275)$, and $(9.42478, 2.475)$; with the maximum value of -0.397887. Figure 1b shows an illustration of the function contours. For offline optimization we uniformly sample $N = 5000$ points in the domain, and remove the top 10%-ile (according to the function value) from this set to remove points close to the optima to make the task more challenging. We then construct 400 trajectories of length 64 each according to the SORT-SAMPLE strategy.

During the evaluation, we initialize four trajectories with a prefix length of 32 and unroll them for an additional 32 steps, and output the best result, thus consuming a query budget of 128. As we see in Table 1, BONET successfully generalizes beyond the best point in our offline dataset. We also report numbers for a gradient ascent baseline, which uses the offline dataset to train a forward model (a 2 layer NN) mapping $\mathbf{x}$ to y and then performs gradient ascent on $\mathbf{x}$ to infer its optima. Next, we perform ablations to understand the effect of the Evaluation RB $\hat{R}$ and prefix length P on our rolled-out trajectories.

Table 1: Best function value achieved by each method on Branin task. We report mean and standard deviation averaged over 5 runs. Gradient ascent performs poorly because on many initialization points, the trajectories escape out of the square domain.

OPTIMA	$\mathcal{D}$ (best)	BONET	Grad. Ascent
-0.398	-6.119	$\mathbf{-1.79 \pm 0.843}$	-3.953 ± 4.258

Impact of $\hat{\mathbf{R}}$ Figures 4a and 4b shows rolled-out trajectories for our model for different $\hat{R}$ values, with prefix lengths 16 and 32. We see that low $\hat{R}$ rolls out higher quality points compared to high $\hat{R}$. To verify our semantics of regret budget as a knob for controlling the rate at which the model accelerates to high-quality points, in the Figure 4c, we also plot trajectories where we update the RB values in the suffix. We stop the roll-out if RB becomes non-positive. It is evident that for smaller $\hat{R}$, the agent quickly accelerates to high-quality regions, whereas for high $\hat{R}$, it gradually shifts to high-quality points. This shows how $\hat{R}$ controls the rate of transition from low to high-quality points.

To further check whether our model has learned to generate a sequence having cumulative regret close to the initial RB R_1, we plot R_1 vs the cumulative regret of a full rolled-out sequence in Figure 5a. We observe that the curve is close to the desired ideal line $y = x$. Notice that the range of R_1 values of $\mathcal{D}_{\text{traj}}$ is quite narrow, but BONET is able to generalize well to a much wider range, allowing it to propose points even better than the dataset. During training, the model has only seen low RB values towards the end of the trajectories. However, the powerful "stitching" ability (Chen et al., 2021) of the model allows it to roll out a novel trajectory having low cumulative regret when conditioned on low unseen R_1 values. Finally, since in BBO our goal is to find the best point, we also plot the best rolled-out point across a trajectory versus $\hat{R}$ in Figure 5b while keeping the prefix sequence fixed. As expected, we observe a decreasing trend, justifying our choice of small $\hat{R}$ values.

Impact of Prefix Length Figure 5c shows the obtained best function values for different prefix lengths, averaged over multiple $\hat{R}$ values, with same query budget $Q = 32$. As expected, we see an increasing trend in the best function value. We also observe a decreasing variance, indicating that the trajectory roll-outs are more stable when augmented with history of points. Note that prefix lengths larger than 32 doesn't perform very well in practice because they have fewer than 32 shots to propose a good point in a single trajectory. Empirically, we found prefix length equal to half of the trajectory length to perform well across the experiments. We provide more details about the ablations, experimental setup, and model hyper-parameters in the Appendix B and C.

Figure 4: Rolled-out trajectories for Branin task for multiple $\hat{R}$ values (averaged over 5 runs). Figure (b) shows trajectories with prefix length 32, without updating RB (default evaluation setting). In Figure (a), we change the prefix length to 16 while in Figure (c), we update RB in the suffix.

(a) Initial RB vs Cumulative Regret   (b) Variation with $\hat{R}$ (c) Variation with Prefix length

Figure 5: Ablation studies for Branin task. All the values are averaged over 5 runs.

3.2 DESIGN-BENCH TASKS

Next, we evaluate BONET on 7 complex real-world tasks of Design-Bench (Trabucco et al., 2022)[1]. **TF-Bind-8** and **TF-Bind-10** are discrete tasks where the goal is to optimize for a DNA sequence which has maximum affinity to bind with a particular transcription factor. The sequences are of length 8 (10) for TF-Bind-8 (TF-Bind-10), where each element in the sequence is one of 4 bases. **ChEMBL** is a discrete task where the aim is to design a drug with certain qualities. **NAS** is a discrete task where we want to optimize a NN for performance on CIFAR10 (Krizhevsky et al., 2010). In **D'Kitty** and **Ant** morphology tasks, we optimize the morphology of two robots: Ant from OpenAI gym (Brockman et al., 2016) and D'Kitty from ROBEL (Ahn et al., 2019). In **Superconductor** task, the aim is to find a chemical formula for a superconducting material with high critical temperature. D'Kitty, Ant and Superconductor are continuous tasks with dimensions 56, 60, and 86 respectively. For the first four tasks, we have query access to the exact oracle function. For Superconductor, we only have an approximate oracle, which is a random forest regressor trained on a much larger hidden dataset. These tasks are considered challenging due to high dimensionality, low quality points in the offline dataset, approximate oracles in some cases, and highly sensitive landscapes with narrow optima regions (Trabucco et al., 2022).

Baselines We compare BONET with multiple canonical baselines like gradient ascent, REIN-FORCE (Sutton et al., 1999), BayesOpt (Snoek et al., 2012) and CMA-ES (Hansen, 2006). We also compare with more recent methods like MINs (Kumar & Levine, 2020), COMs (Trabucco et al., 2021) and CbAS (Brookes et al., 2019).[2] For inherently active methods like BayesOpt, since we cannot query the oracle function $f(\mathbf{x})$ during optimization (due to being in an offline setting), we follow the procedure used by Trabucco et al. (2022), and perform BayesOpt on a surrogate model $\hat{f}(\mathbf{x})$ (a feedforward NN) trained on the offline dataset. For the BayesOpt baseline, we use a Gaussian Process to quantify uncertainty and use the quasi-Expected Improvement (Wilson et al., 2017)

---

[1]We haven't included Hopper since the domain is buggy - we found that the oracle function used to evaluate the task was highly inaccurate and noisy. An expanded discussion can be found in Appendix B.7

[2]We take the baseline implementations from https://github.com/brandontrabucco/design-baselines

Table 2: **100th percentile** comparative evaluation of BONET over 7 tasks averaged over 5 runs. The error bars refer to the standard deviation across the 5 seeds. We report normalized scores with $Q = 256$ (except for NAS, where we use $Q = 128$ due to compute restrictions) and highlight the top 2 results in each column. Blue denotes the best entry in the column, and Violet denotes the second best. We observe that BONET is in the top 2 in 5 out of 7 tasks, and is also consistently able to outperform the best offline dataset point in all tasks.

BASELINE	TFBIND8	TFBIND10	SUPERCONDUCTOR	ANT	D'KITTY	CHEMBL	NAS	MEAN SCORE (↑)	MEAN RANK (↑)
$\mathcal{D}$ (best)	0.439	0.467	0.399	0.565	0.884	0.605	0.436	-	-
CbAS	0.958 ± 0.018	0.657 ± 0.017	0.45 ± 0.083	0.876 ± 0.015	0.896 ± 0.016	0.640 ± 0.005	0.683 ± 0.079	0.737 ± 0.033	5.4
GP-qEI	0.824 ± 0.086	0.635 ± 0.011	0.501 ± 0.021	0.887 ± 0.0	0.896 ± 0.0	0.633 ± 0.000	1.009 ± 0.059	0.769 ± 0.026	5.3
CMA-ES	0.933 ± 0.035	0.679 ± 0.034	0.491 ± 0.004	1.436 ± 0.928	0.725 ± 0.002	0.636 ± 0.004	0.985 ± 0.079	0.840 ± 0.156	4.0
Gradient Ascent	0.981 ± 0.015	0.659 ± 0.039	0.504 ± 0.005	0.34 ± 0.034	0.906 ± 0.017	0.647 ± 0.020	0.433 ± 0.000	0.638 ± 0.018	4.0
REINFORCE	0.959 ± 0.013	0.64 ± 0.028	0.481 ± 0.017	0.261 ± 0.042	0.474 ± 0.202	0.636 ± 0.023	-1.895 ± 0.000	0.222 ± 0.046	6.7
MINs	0.938 ± 0.047	0.659 ± 0.044	0.484 ± 0.017	0.942 ± 0.018	0.944 ± 0.009	0.653 ± 0.002	0.717 ± 0.046	0.762 ± 0.026	3.7
COMs	0.964 ± 0.02	0.654 ± 0.02	0.423 ± 0.033	0.949 ± 0.021	0.948 ± 0.006	0.648 ± 0.005	0.459 ± 0.139	0.720 ± 0.034	4.4
BONET (Ours)	0.975 ± 0.004	0.681 ± 0.035	0.437 ± 0.022	0.976 ± 0.012	0.954 ± 0.012	0.654 ± 0.019	0.724 ± 0.008	0.772 ± 0.016	2.4

Table 3: **50th percentile** evaluations on all the tasks. Similar to Table 2, we find that BONET achieves both the best average rank and the best mean score on all tasks. This shows that BONET consistently outputs good candidate points.

BASELINE	TFBIND8	TFBIND10	SUPERCONDUCTOR	ANT	D'KITTY	CHEMBL	NAS	MEAN SCORE	MEAN RANK
CbAS	0.422 ± 0.007	0.458 ± 0.001	0.111 ± 0.009	0.384 ± 0.010	0.752 ± 0.003	0.633 ± 0.000	0.292 ± 0.027	0.436 ± 0.008	5.7
GP-qEI	0.443 ± 0.004	0.494 ± 0.002	0.299 ± 0.002	0.272 ± 0.006	0.754 ± 0.004	0.633 ± 0.000	0.544 ± 0.099	0.491 ± 0.016	4.0
CMA-ES	0.543 ± 0.007	0.483 ± 0.011	0.376 ± 0.004	0.685 ± 0.018	0.637 ± 0.148	0.633 ± 0.000	0.591 ± 0.102	0.466 ± 0.020	3.4
Gradient Ascent	0.572 ± 0.024	0.470 ± 0.004	0.463 ± 0.022	0.141 ± 0.010	0.637 ± 0.148	0.633 ± 0.000	0.433 ± 0.000	0.478 ± 0.029	4.3
REINFORCE	0.450 ± 0.003	0.472 ± 0.000	0.470 ± 0.017	0.146 ± 0.009	0.307 ± 0.002	0.633 ± 0.000	-1.895 ± 0.000	0.083 ± 0.004	4.9
MINs	0.425 ± 0.011	0.471 ± 0.004	0.330 ± 0.011	0.651 ± 0.010	0.890 ± 0.003	0.633 ± 0.000	0.433 ± 0.000	0.547 ± 0.005	4.0
COMs	0.492 ± 0.009	0.472 ± 0.012	0.365 ± 0.026	0.525 ± 0.018	0.885 ± 0.002	0.633 ± 0.000	0.287 ± 0.173	0.522 ± 0.034	3.8
BONET	0.505 ± 0.055	0.496 ± 0.037	0.369 ± 0.015	0.819 ± 0.032	0.907 ± 0.020	0.630 ± 0.000	0.571 ± 0.095	0.614 ± 0.035	2.8

acquisition function for optimization, similar to prior work (Trabucco et al., 2022; 2021). MINs (Kumar & Levine, 2020) also train a forward model to optimize over the conditioning parameters. Our method does not need a separate forward model and thus, is not dependent on the quality of the fit of the forward model. We provide other variants of BayesOpt baseline in Appendix D.2.

Evaluation We allow a query budget of $Q = 256$ for all the baselines, except for NAS, where we use a reduced budget of $Q = 128$ due to compute restrictions. For BONET, across all tasks, we roll out 4 trajectories, each with a prefix and prediction subsequence length of 64 each. The prediction subsequence is initialized with one of 4 candidate low $\hat{R}$ values $0, 0.01, 0.05, 0.1$. For each $\hat{R}$, we then roll out for 64 timesteps and choose the best point. We report the mean and standard deviation over 5 trials for each of the models and tasks in Table 2. Following the procedure used by (Trabucco et al., 2021; 2022; Yu et al., 2021), the results of Table 2 are linearly normalized between the minimum and maximum values of a large hidden offline dataset. In Table 3, we also present the median function value of the the proposed output points for each method, averaged over 5 runs.

Results Overall, we obtain a mean score of 0.772 and an average rank of 2.4, which is the best among all the baselines. We also achieve the best results on three tasks. Additionally, we are among the top 2 for five out of seven tasks. We show significant improvements over generative methods such as MINs (Kumar & Levine, 2020) or CbAS (Brookes et al., 2019), and forward mapping methods such as COMs (Trabucco et al., 2021) on TF-Bind-8, TF-Bind-10, Ant and D'Kitty. We also note that while BONET is placed second in Ant, it shows a much lower standard deviation (0.012) compared to the to the best performing method CMA-ES, which has a much larger standard deviation of 0.928. We also have a lowest mean standard deviation across all tasks, suggesting that BONET is less sensitive to bad initializations compared to other methods. We report the unnormalized results, ablations and other experimental details for Design-Bench tasks in Appendix C. BONET also performs best on 50th percentile evaluation, showing that it has a better set of proposed points compared to other methods, and that the performance is not by randomly finding good points.

4 RELATED WORK

Active BBO The majority of prior work in BBO have been in the active setting, where surrogate models are allowed to query the function during training. This includes long bodies of work in

Bayesian Optimization, e.g., (Snoek et al., 2012; Swersky et al., 2013; Srinivas et al., 2010) and bandits, e.g., (Garivier et al., 2016; Riquelme et al., 2018; Joachims et al., 2018b;a; Swaminathan & Joachims, 2015; Jacq et al., 2019). Such methods usually employ surrogate models such as Gaussian Processes (Srinivas et al., 2010), Neural Processes (Garnelo et al., 2018a;b; Gordon et al., 2019; Anonymous, 2022; Singh et al., 2019) or Bayesian Neural Networks (Chang, 2021; Goan & Fookes, 2020) to approximate the black-box function, and an uncertainty-aware acquisition strategy for querying new points.

Offline BBO Recent works have made use of such datasets and shown promising results (Kumar & Levine, 2020; Trabucco et al., 2021; Brookes et al., 2019; Fannjiang & Listgarten, 2020; Fu & Levine, 2021; Yu et al., 2021). Kumar & Levine (2020) train a stochastic inverse mapping from the outputs y to inputs $\mathbf{x}$ using a generative model similar to a conditional GAN (Goodfellow et al., 2014; Mirza & Osindero, 2014; Arjovsky et al., 2017; Nowozin et al., 2016). They then optimize over y to find a good design point. Training GANs however can be difficult due to issues like mode collapse (Arjovsky et al., 2017). Other methods make use of gradient ascent to find an optimal solution. Trabucco et al. (2021) and Yu et al. (2021) train a model to be robust to outliers by regularizing the objective such that they assign low score to those points. Fu & Levine (2021) train a normalized maximum likelihood estimate of the function. We instead offer a fresh perspective based on generative sequence modelling and we show strong results in comparison to many of these prior works in Section 3.

Offline reinforcement learning (RL) While both RL and BBO are sequential decision-making problems, the key difference is that RL is stateful while BBO is not. In the offline setting (Schmidhuber, 2019; Jacq et al., 2019), both problems require models or policies that can generalize beyond the offline dataset to achieve good performance. Related to our work, autoregressive transformers have been successfully applied on trajectory data obtained from offline RL (Chen et al., 2021; Janner et al., 2021). However, there are important differences between their setting and offline BBO. For example, the data in offline BBO is not sequential in nature, unlike in offline RL where the offline data is naturally in the form of demonstrations. One of our contributions is to design a notion of 'high-to-low' sequences to BBO for autoregressive modeling and test-time generalization.

Learned optimizers Our work also bears resemblance to work on meta-learning optimizers like those of (Andrychowicz et al., 2016) and (Chen et al., 2017). However, a key difference between these learned optimizers and BONET is that they require access to gradients either during training time or during both training and evaluation time, whereas BONET has no such restriction, meaning it can work in situations where access to gradient information is not practical (for instance with non-differentiable black-box functions). Furthermore, we concentrate on the offline setting, in contrast to learned optimizer work which usually looks at an active optimization setting.

5 DISCUSSION

We presented BONET, a novel generative framework for pretraining black-box optimizers using offline data. BONET consists of a 3 phased process. In the first phase, we use a novel SORT-SAMPLE strategy to generate trajectories from offline data that use the sorting heuristic to mimic the behavior of online BBO optimizers. In phases 2 and 3, we train our model using an autoregressive transformer and use it to generate candidate points that maximize the black-box function. Experimentally, we verify that BONET is capable of solving complex high-dimensional tasks like the ones in Design-Bench, achieving an average rank of **2.4** with a mean score of **0.772**.

Limitations and Future Work BONET assumes knowledge of the approximate value of the optima $f(\mathbf{x}^*)$ to computes the regrets of points. Though we show in Appendix C.5 that different reasonable estimates of $f(\mathbf{x}^*)$ can give similar results, this is still something we would like to address in future work. We are also interested in extending BONET to an active setting where our model can quantify uncertainty and actively query the black-box function after pretraining on an offline dataset. On a practical side, we would also be interested in analyzing the properties of domains that dictate where BONET can strongly excel (e.g., D'Kitty) or struggle (e.g., Superconductor) relative to other approaches.Finally, we aim to expand our scope to a meta-task setting, where instead of a single function, our offline data consists of past evaluations from multiple black-box functions.

6 ETHICAL AND SOCIAL RESPONSIBILITY

Offline black-box optimization can play a critical role in improving efficiency and safety in many real-world settings like nuclear reactors or the pharmaceutical industry, where active optimization may prove to be computationally inefficient (requiring too many queries) or even dangerous. However, while we do not anticipate anything inherently malicious about our work, it is possible to utilize our proposed method (and other optimizers in general) in malicious settings (e.g., optimizing for drugs that have harmful effects). This is something to remember when deploying algorithms such as ours for high stake real-world applications.

7 REPRODUCIBILITY

Throughout the paper, we maintained a high standard of rigor for reproducibility. We report the detailed pseudocode of our method in Algorithm 1, and we also provide the link to our code via an anonymized link here. We provide more details on our training setup and choice of hyperparameters in Appendix B. We report results on multiple datasets in Design-Bench (Trabucco et al., 2022), each with different properties and benchmark our method over multiple baselines from different families of approaches. Our results are averaged over 5 seeds, and we also provide the standard deviations. We also conduct several ablations to evaluate sensitivity of BONET to different parameters.

REFERENCES

Michael Ahn, Henry Zhu, Kristian Hartikainen, Hugo Ponte, Abhishek Gupta, Sergey Levine, and Vikash Kumar. Robel: Robotics benchmarks for learning with low-cost robots. 2019. doi: 10.48550/ARXIV.1909.11639. URL https://arxiv.org/abs/1909.11639.

Marcin Andrychowicz, Misha Denil, Sergio Gómez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando de Freitas. Learning to learn by gradient descent by gradient descent. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/fb87582825f9d28a8d42c5e5e8b23d-Paper.pdf.

Anonymous. Neural bootstrapping attention for neural processes. In *Submitted to The Tenth International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=Z7VhFVRVqeU. under review.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 214–223. PMLR, 06–11 Aug 2017. URL https://proceedings.mlr.press/v70/arjovsky17a.html.

Hildo Bijl, Thomas B. Schön, Jan-Willem van Wingerden, and Michel Verhaegen. A sequential monte carlo approach to thompson sampling for bayesian optimization, 2016. URL https://arxiv.org/abs/1604.00169.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

David Brookes, Hahnbeom Park, and Jennifer Listgarten. Conditioning by adaptive sampling for robust design. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 773–782. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/brookes19a.html.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh,

Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.

Daniel T. Chang. Bayesian neural networks: Essentials, 2021. URL https://arxiv.org/abs/2106.13594.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *arXiv preprint arXiv:2106.01345*, 2021.

Yutian Chen, Matthew W. Hoffman, Sergio Gómez Colmenarejo, Misha Denil, Timothy P. Lillicrap, Matt Botvinick, and Nando de Freitas. Learning to learn without gradient descent by gradient descent. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 748–756. PMLR, 06–11 Aug 2017. URL https://proceedings.mlr.press/v70/chen17e.html.

Clara Fannjiang and Jennifer Listgarten. Autofocused oracles for model-based design, 2020. URL https://arxiv.org/abs/2006.08052.

Justin Fu and Sergey Levine. Offline model-based optimization via normalized maximum likelihood estimation. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=FmMKSO4e8JK.

Aurélien Garivier, Emilie Kaufmann, and Tor Lattimore. On explore-then-commit strategies. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, pp. 784–792, Red Hook, NY, USA, 2016. Curran Associates Inc. ISBN 9781510838819.

Marta Garnelo, Dan Rosenbaum, Christopher Maddison, Tiago Ramalho, David Saxton, Murray Shanahan, Yee Whye Teh, Danilo Rezende, and S. M. Ali Eslami. Conditional neural processes. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1704–1713. PMLR, 10–15 Jul 2018a. URL https://proceedings.mlr.press/v80/garnelo18a.html.

Marta Garnelo, Jonathan Schwarz, Dan Rosenbaum, Fabio Viola, Danilo J Rezende, SM Eslami, and Yee Whye Teh. Neural processes. *arXiv preprint arXiv:1807.01622*, 2018b.

Ethan Goan and Clinton Fookes. Bayesian neural networks: An introduction and survey. In *Case Studies in Applied Bayesian Data Science*, pp. 45–87. Springer International Publishing, 2020. doi: 10.1007/978-3-030-42553-1_3. URL https://doi.org/10.1007%2F978-3-030-42553-1_3.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014. URL https://proceedings.neurips.cc/paper/2014/file/5ca3e9b122f61f8f06494c97b1afccf3-Paper.pdf.

Jonathan Gordon, Wessel P Bruinsma, Andrew YK Foong, James Requeima, Yann Dubois, and Richard E Turner. Convolutional conditional neural processes. *arXiv preprint arXiv:1910.13556*, 2019.

Nikolaus Hansen. *The CMA Evolution Strategy: A Comparing Review*, pp. 75–102. Springer Berlin Heidelberg, Berlin, Heidelberg, 2006. ISBN 978-3-540-32494-2. doi: 10.1007/3-540-32494-1_4. URL https://doi.org/10.1007/3-540-32494-1_4.

Alexis Jacq, Matthieu Geist, Ana Paiva, and Olivier Pietquin. Learning from a learner. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2990–2999. PMLR, 09–15 Jun 2019. URL `https://proceedings.mlr.press/v97/jacq19a.html`.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In *Advances in Neural Information Processing Systems*, 2021.

T. Joachims, A. Swaminathan, and M. de Rijke. Deep learning with logged bandit feedback. In *International Conference on Learning Representations (ICLR)*, 2018a.

Thorsten Joachims, Adith Swaminathan, and Maarten de Rijke. Deep learning with logged bandit feedback. In *International Conference on Learning Representations*, 2018b. URL `https://openreview.net/forum?id=SJaP_-xAb`.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. Cifar-10 (canadian institute for advanced research). *URL http://www. cs. toronto. edu/kriz/cifar. html*, 5(4):1, 2010.

Aviral Kumar and Sergey Levine. Model inversion networks for model-based optimization. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 5126–5137. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/373e4c5d8edfa8b74fd4b6791d0cf6dc-Paper.pdf`.

Jeffrey Larson, Matt Menickelly, and Stefan M. Wild. Derivative-free optimization methods. *Acta Numerica*, 28:287–404, may 2019. doi: 10.1017/s0962492919000060. URL `https://doi.org/10.1017%2Fs0962492919000060`.

Mehdi Mirza and Simon Osindero. Conditional generative adversarial nets, 2014. URL `https://arxiv.org/abs/1411.1784`.

Sebastian Nowozin, Botond Cseke, and Ryota Tomioka. f-gan: Training generative neural samplers using variational divergence minimization. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL `https://proceedings.neurips.cc/paper/2016/file/cedebb6e872f539bef8c3f919874e9d7-Paper.pdf`.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.

Carlos Riquelme, George Tucker, and Jasper Snoek. Deep bayesian bandits showdown: An empirical comparison of bayesian deep networks for thompson sampling. *arXiv preprint arXiv:1802.09127*, 2018.

Juergen Schmidhuber. Reinforcement learning upside down: Don't predict rewards – just map them to actions, 2019. URL `https://arxiv.org/abs/1912.02875`.

Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P. Adams, and Nando de Freitas. Taking the human out of the loop: A review of bayesian optimization. *Proceedings of the IEEE*, 104(1): 148–175, 2016. doi: 10.1109/JPROC.2015.2494218.

Gautam Singh, Jaesik Yoon, Youngsung Son, and Sungjin Ahn. Sequential neural processes. *arXiv preprint arXiv:1906.10264*, 2019.

Jasper Snoek, Hugo Larochelle, and Ryan P. Adams. Practical bayesian optimization of machine learning algorithms, 2012. URL `https://arxiv.org/abs/1206.2944`.

Niranjan Srinivas, Andreas Krause, Sham Kakade, and Matthias W. Seeger. Gaussian Process Optimization in the Bandit Setting: No Regret and Experimental Design. In *Proceedings of the 27th International Conference on Machine Learning*, pp. 1015–1022. Omnipress, 2010.

Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In S. Solla, T. Leen, and K. Müller (eds.), *Advances in Neural Information Processing Systems*, volume 12. MIT Press, 1999. URL https://proceedings.neurips.cc/paper/1999/file/464d828b85b0bed98e80ade0a5c43b0f-Paper.pdf.

Adith Swaminathan and Thorsten Joachims. Batch learning from logged bandit feedback through counterfactual risk minimization. *Journal of Machine Learning Research*, 16(52):1731–1755, 2015. URL http://jmlr.org/papers/v16/swaminathan15a.html.

Kevin Swersky, Jasper Snoek, and Ryan P Adams. Multi-task bayesian optimization. In C.J. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL https://proceedings.neurips.cc/paper/2013/file/f33ba15effa5c10e873bf3842afb46a6-Paper.pdf.

Brandon Trabucco, Aviral Kumar, Xinyang Geng, and Sergey Levine. Conservative objective models for effective offline model-based optimization. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 10358–10368. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/trabucco21a.html.

Brandon Trabucco, Xinyang Geng, Aviral Kumar, and Sergey Levine. Design-bench: Benchmarks for data-driven offline model-based optimization. *CoRR*, abs/2202.08450, 2022. URL https://arxiv.org/abs/2202.08450.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

James T. Wilson, Riccardo Moriconi, Frank Hutter, and Marc Peter Deisenroth. The reparameterization trick for acquisition functions, 2017. URL https://arxiv.org/abs/1712.00424.

Sihyun Yu, Sungsoo Ahn, Le Song, and Jinwoo Shin. RoMA: Robust model adaptation for offline model-based optimization. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=VH0TRmnqUc.