PoRF: Pose Residual Field for Accurate Neural Surface Reconstruction

Jia-Wang Bian
Department of Engineering Science
University of Oxford

Wenjing Bian
Department of Engineering Science
University of Oxford

Victor Adrian Prisacariu
Department of Engineering Science
University of Oxford

Philip Torr
Department of Engineering Science
University of Oxford

Abstract

Neural surface reconstruction is sensitive to the camera pose noise, even if state-of-the-art pose estimators like COLMAP or ARKit are used. More importantly, existing Pose-NeRF joint optimisation methods have struggled to improve pose accuracy in challenging real-world scenarios. To overcome the challenges, we introduce the pose residual field (**PoRF**), a novel implicit representation that uses an MLP for regressing pose updates. This is more robust than the conventional pose parameter optimisation due to parameter sharing that leverages global information over the entire sequence. Furthermore, we propose an epipolar geometry loss to enhance the supervision that leverages the correspondences exported from COLMAP results without the extra computational overhead. Our method yields promising results. On the DTU dataset, we reduce the rotation error by 78% for COLMAP poses, leading to the decreased reconstruction Chamfer distance from 3.48mm to 0.85mm. On the MobileBrick dataset that contains casually captured unbounded 360-degree videos, our method refines ARKit poses and improves the reconstruction F1 score from 69.18 to 75.67, outperforming that with the dataset provided ground-truth pose (75.14). Moreover, we integrate our method into the Nerfstudio library, consistently improving performance in diverse challenging scenes. These achievements demonstrate the efficacy of our approach in refining camera poses in real-world scenarios.

1 Introduction

Object reconstruction from multi-view images is a fundamental problem in computer vision. Recently, neural surface reconstruction (NSR) methods have significantly advanced in this field Wang et al. (2021a); Wu et al. (2023). These approaches draw inspiration from implicit scene representation and volume rendering techniques that were used in neural radiance fields (NeRF) Mildenhall et al. (2020). In NSR, scene geometry is represented by using a signed distance function (SDF) field, learned by a multilayer perceptron (MLP) network trained with image-based rendering loss. Despite achieving high-quality reconstructions, these methods are sensitive to camera pose noise, a common issue in real-world applications, even when state-of-the-art pose estimation methods like COLMAP Schönberger & Frahm (2016) or ARKit are used. An example of this sensitivity is evident in Fig. 1, where the reconstruction result with the COLMAP estimated poses shows poor quantitative accuracy and visible noise on the object's surface. In this paper, we focus on refining the inaccurate camera pose to improve neural surface reconstruction.

Recent research has explored the joint optimisation of camera pose and NeRF, while they are not designed for accurate neural surface reconstruction in real-world scenes. As shown in Fig. 1, existing methods such as BARF Lin et al. (2021) and SPARF Truong et al. (2023) are hard to improve reconstruction accuracy on the DTU dataset Jensen et al. (2014) via pose refinement. We regard the challenges as stemming from independent pose representation and weak supervision. Firstly, existing methods typically optimise pose parameters for each image independently. This approach

Figure 1: Reconstruction results on the DTU dataset (*scan24*). All meshes were generated by using Voxurf Wu et al. (2023). The Chamfer Distance (mm) is reported. BARF Lin et al. (2021), SPARF Truong et al. (2023), and our method all take the COLMAP pose as the initial pose. More results are illustrated in the supplementary material.

disregards global information over the entire sequence and leads to poor accuracy. Secondly, the colour rendering loss employed in the joint optimisation process exhibits ambiguity, creating many false local minimums. To overcome these challenges, we introduce a novel implicit pose representation and a robust epipolar geometry loss into the joint optimisation framework.

The proposed implicit pose representation is named *Pose Residual Field* (PoRF), which employs an MLP network to learn the pose residuals. The MLP network takes the frame index and initial camera pose as inputs, as illustrated in Fig. 2. Notably, as the MLP parameters are shared across all frames, it is able to capture the underlying global information over the entire trajectory for boosting performance. As shown in Fig. 3, the proposed PoRF shows significantly improved accuracy and faster convergence than the conventional pose parameter optimisation approach.

Moreover, we use feature correspondences in the proposed epipolar geometry loss to enhance supervision. Although correspondences have been used in SPARF Truong et al. (2023), it depends on expensive dense matching. As shown in Fig. 3, our method demonstrates similarly excellent performance with both sparse matches by handcraft methods (SIFT Lowe (2004)) and dense matches by deep learning methods (LoFTR Sun et al. (2021)). Besides, in contrast to SPARF which fuses correspondences and NeRF-rendered depths to compute reprojection loss, our approach uses the epipolar geometry loss that solely involves poses and correspondences, without relying on the rendered depths by NeRF that can be inaccurate and limit pose accuracy. Notably, as NeRF rendering is time-consuming, SPARF is constrained in the number of correspondences it can use in each iteration, while our method allows for the utilisation of an arbitrary number of matches.

We conduct a comprehensive evaluation on both DTU Jensen et al. (2014) and MobileBrick Li et al. (2023a) datasets. Firstly, on the DTU dataset, our method takes the COLMAP pose as initialisation and reduces the rotation error by 78%. This decreases the reconstruction Chamfer Distance from 3.48mm to 0.85mm, where we use Voxurf Wu et al. (2023) for reconstruction. Secondly, on the MobileBrick dataset, our method is initialised with ARKit poses and increases the reconstruction F1 score from 69.18 to 75.67. It slightly outperforms the provided imperfect GT pose in reconstruction (75.14) and achieves state-of-the-art performance. Moreover, we integrate our method into the Nerfstudio library Tancik et al. (2023), and the resulting method outperforms the original pose optimisation method in different challenging scenes. These results demonstrate the effectiveness of our approach in refining camera poses and improving reconstruction accuracy, especially in real-world scenarios where the initial poses might not be perfect.

In summary, our contributions are as follows:

1. We introduce a novel approach that optimises camera pose within neural surface reconstruction. It utilises the proposed *Pose Residual Field* (PoRF) and a robust epipolar geometry loss, enabling accurate and efficient refinement of camera poses.

2. The proposed method demonstrates its effectiveness in refining both COLMAP and ARKit poses, resulting in high-quality reconstructions on the DTU dataset and achieving state-of-the-art performance on the MobileBrick dataset.

2 RELATED WORK

Neural surface reconstruction. Object reconstruction from multi-view images is a fundamental problem in computer vision. Traditional multi-view stereo (MVS) methods Schönberger et al. (2016); Furukawa et al. (2009) explicitly find dense correspondences across images to compute depth maps, which are fused together to obtain the final point cloud. The correspondence search and depth estimation processes are significantly boosted by the deep learning based approaches Yao et al. (2018; 2019); Zhang et al. (2020). Recently, Neural Radiance Field (NeRF) Mildenhall et al. (2020) has been proposed to implicitly reconstruct the scene geometry, and it allows for extracting object surfaces from the implicit representation. To improve performance, VolSDF Yariv et al. (2021) and NeuS Wang et al. (2021a) proposed to use an implicit SDF field for scene representation. MonoSDF Yu et al. (2022) and NeurIS Wang et al. (2022a) proposed to leverage the external monocular geometry prior. HF-NeuS Wang et al. (2022b) introduced an extra displacement network for learning surface details. NeuralWarp Darmon et al. (2022) used patch warping to guide surface optimisation. Geo-NeuS Fu et al. (2022) and RegSDF Zhang et al. (2022) proposed to leverage the sparse points generated by SfM. Neuralangelo Li et al. (2023b) proposed a coarse-to-fine method on the hash grids. Voxurf Wu et al. (2023) proposed a voxel-based representation that achieves high accuracy with efficient training.

Joint NeRF and pose optimisation. NeRFmm Wang et al. (2021b) demonstrates the possibility of jointly learning or refining camera parameters alongside the NeRF framework Mildenhall et al. (2020). BARF Lin et al. (2021) introduces a solution involving coarse-to-fine positional encoding to enhance the robustness of joint optimisation. In the case of SC-NeRF Jeong et al. (2021), both intrinsic and extrinsic camera parameters are proposed for refinement. In separate approaches, SiN-eRF Xia et al. (2022) and GARF Chng et al. (2022) suggest employing distinct activation functions within NeRF networks to facilitate pose optimisation. Nope-NeRF Bian et al. (2023) employs an external monocular depth estimation model to assist in refining camera poses. L2G Chen et al. (2023) puts forth a local-to-global scheme, wherein the image pose is computed from learned multiple local poses. Notably similar to our approach is SPARF Truong et al. (2023), which also incorporates correspondences and evaluates its performance on the challenging DTU dataset Jensen et al. (2014). However, it is tailored to sparse-view scenarios and lacks the accuracy achieved by our method when an adequate number of images is available.

3 PRELIMINARY

Volume rendering with SDF representation We adhere to the NeuS Wang et al. (2021a) methodology to optimise the neural surface reconstruction from multi-view images. The approach involves representing the scene using an implicit SDF field, which is parameterised by an MLP. To render an image pixel, a ray originates from the camera centre o and extends through the pixel along the viewing direction v, described as $\{p(t) = o + tv | t \geq 0\}$. By employing volume rendering (Max, 1995), the colour for the image pixel is computed by integrating along the ray using N discrete sampled points $\{p_i = o + t_i v | i = 1, ..., N, t_i < t_{i+1}\}$:

$$\hat{C}(r) = \sum_{i=1}^{N} T_i \alpha_i c_i, \ \ T_i = \prod_{j=1}^{i-1} (1 - \alpha_j),$$
(1)

In this equation, α_i represents the opacity value, and T_i denotes the accumulated transmittance. The primary difference between NeuS and NeRF Mildenhall et al. (2020) lies in how α_i is formulated. In NeuS, α_i is computed using the following expression:

$$\alpha_i = \max \left(\frac{\Phi_s(f(p(t_i))) - \Phi_s(f(p(t_{i+1})))}{\Phi_s(f(p(t_i)))}, 0 \right),$$ (2)

In this context, $f(x)$ is the SDF function, and $\Phi_s(x) = (1 + e^{-sx})^{-1}$ denotes the Sigmoid function, where the parameter s is automatically learned during the training process.

Neural surface reconstruction loss. In line with NeuS Wang et al. (2021a), our objective is to minimise the discrepancy between the rendered colours and the ground truth colours. To achieve this, we randomly select a batch of pixels and their corresponding rays in world space $P = \{C_k, o_k, v_k\}$ from an image in each iteration. Here, C_k represents the pixel colour, o_k is the camera centre, and v_k denotes the viewing direction. We set the point sampling size as n and the batch size as m.

The neural surface reconstruction loss function is defined as follows:

$$\mathcal{L}_{NSR} = \mathcal{L}_{colour} + \lambda \mathcal{L}_{reg}.$$ (3)

The colour loss $\mathcal{L}_{colour}$ is calculated as:

$$\mathcal{L}_{colour} = \frac{1}{m} \sum_k \left\| \hat{C}_k - C_k \right\|_1.$$ (4)

The term $\mathcal{L}_{reg}$ incorporates the Eikonal term Gropp et al. (2020) applied to the sampled points to regularise the learned SDF, which can be expressed as:

$$\mathcal{L}_{reg} = \frac{1}{nm} \sum_{k,i} (\|\nabla f(\hat{\mathbf{p}}_{k,i})\|_2 - 1)^2.$$ (5)

Here, f is the learned SDF, and $\hat{\mathbf{p}}_{k,i}$ represents the sampled points for the k-th pixel in the i-th ray. λ controls the influence of the regularisation term in the overall loss function.

Joint pose optimisation with NSR. Inspired by the previous work Wang et al. (2021b); Lin et al. (2021) that jointly optimises pose parameters with NeRF Mildenhall et al. (2020), we propose a naive joint pose optimisation with neural surface reconstruction and use Eqn. 3 as the loss function. This is denoted as the baseline method in Fig. 3, and in the next section, we present the proposed method for improving performance.

4 METHOD

Pose residual field (PoRF). We approach camera pose refinement as a regression problem using an MLP. In Fig. 2, we illustrate the process where the input to the MLP network is a 7D vector, consisting of a 1D image index (i) and a 6D initial pose (r, t). The output of the MLP is a 6D pose residual ($\Delta r, \Delta t$). This residual is combined with the initial pose to obtain the final refined pose (r', t'). In this context, rotation is represented by 3D axis angles.

To encourage small pose residual outputs at the beginning of the optimisation, we multiply the MLP output by a fixed small factor (α). This ensures an effective initialisation (the refined pose is close to the initial pose), and the correct pose residuals can be gradually learned with optimisation. Formally, the composition of the initial pose and the learned pose residual is expressed as follows:

$$\begin{cases} \hat{r} = r + \alpha \cdot \Delta r \\ \hat{t} = t + \alpha \cdot \Delta t \end{cases}$$ (6)

Figure 2: Joint optimisation pipeline. The proposed model consists of a pose residual field F_θ and a neural surface reconstruction module G_ϕ. PoRF takes the frame index and the initial camera pose as input and employs an MLP to learn the pose residual, which is composited with the initial pose to obtain the predicted pose. The output pose is used to compute the neural rendering losses with the NSR module and the epipolar geometry loss with pre-computed 2D correspondences. Parameters θ and ϕ are updated during back-propagation.

The resulting final pose $(\hat{r}, \hat{t})$ is utilised to compute the loss, and the gradients can be backpropagated to the MLP parameters during the optimisation process. In practice, we use a shallow MLP with 2 hidden layers, which we find is sufficient for object reconstruction.

Intuition on the PoRF. Our method draws inspiration from the coordinates-MLP. Similar to NeRF Mildenhall et al. (2020), in which the position and view direction of a point are taken as inputs by the MLP to learn its density and colour, our method takes the initial position (translation) and view direction (rotation) of the camera as inputs to learn the camera's pose residual. Also, our approach incorporates the frame index as an additional input, serving as a temporal coordinate.

The MLP parameters are shared across all frames, which enables our method to extract global information from the entire sequence. The inclusion of the frame index allows our method to learn local information for each frame. Overall, the utilisation of both global and local information empowers our method to effectively handle various challenges and learn accurate camera poses.

The parameter sharing in our method leads to better robustness than the conventional pose refinement method. Specifically, the previous method directly back-propagates gradients to per-frame pose parameters, so the noisy supervision and inappropriate learning rates can make certain pose parameters trapped in false local minima, causing the optimisation to diverge. In contrast, our method can leverage information from other frames to prevent certain frames from being trapped in false local minima. A quantitative comparison is illustrated in Fig. 3, where the performance of L2 (utilising PoRF) notably surpasses that of L1 (excluding PoRF).

Epipolar geometry loss. To improve the supervision, we introduce an epipolar geometry loss that makes use of feature correspondences. The correspondences can be either sparse or dense, and they can be obtained through traditional handcrafted descriptors, like SIFT Lowe (2004), or deep learning techniques, like LoFTR Sun et al. (2021). As a default option, we utilise SIFT matches, exported from COLMAP pose estimation results, to avoid introducing extra computational cost.

In each training iteration, we randomly sample n matched image pairs and calculate the Sampson distance (Eqn. 8) for the correspondences. By applying a threshold δ, we can filter out outliers and obtain m inlier correspondences. We represent the inlier rate for each pair as p_i, and the Sampson error for each inlier match as e_k. The proposed epipolar geometry loss is then defined as:

$$\mathcal{L}_{EG} = \frac{1}{n} \sum_i w_i \left(\frac{1}{m} \sum_k e_k \right). \tag{7}$$

Table 1: Absolute pose accuracy evaluation on the DTU dataset. For all methods, the COLMAP pose is used as the initial pose. The upper section presents rotation errors in degrees, while the lower section displays translation errors in millimetres (mm).

Scan	24	37	40	55	63	65	69	83	97	105	106	110	114	118	122	mean
COLMAP (Initial)	0.68	0.67	0.63	0.62	0.75	0.67	0.64	0.68	0.56	0.66	0.62	0.69	0.66	0.64	0.63	0.65
BARF Lin et al. (2021)	0.67	0.73	0.67	0.79	0.67	0.83	0.47	0.59	0.55	0.62	0.75	0.67	0.67	0.70	0.84	0.69
L2G Chen et al. (2023)	0.67	0.65	0.69	32.04	0.80	0.68	0.49	0.66	0.76	0.61	29.02	6.41	0.69	2.63	2.47	5.29
SPARF Truong et al. (2023)	0.40	0.62	0.43	0.40	0.72	0.39	0.30	0.31	0.48	0.33	0.36	0.39	0.19	0.24	0.36	0.39
Ours	**0.09**	**0.13**	**0.10**	**0.13**	**0.13**	**0.16**	**0.13**	**0.12**	**0.26**	**0.12**	**0.12**	**0.16**	**0.15**	**0.11**	**0.13**	**0.14**
COLMAP (Initial)	0.79	**1.06**	0.81	0.81	0.80	0.89	0.88	**1.07**	2.07	1.07	1.05	1.22	1.03	**0.95**	**1.02**	1.03
BARF Lin et al. (2021)	1.53	2.19	1.80	2.50	2.32	2.31	2.06	2.65	3.45	2.27	2.29	2.59	3.29	3.15	3.13	2.50
L2G Chen et al. (2023)	1.50	1.90	1.90	115	2.07	2.45	1.89	2.77	5.04	1.99	172	88.6	2.94	12.3	21.1	28.9
SPARF Truong et al. (2023)	3.66	4.76	3.89	2.22	5.68	2.57	2.32	2.96	4.88	3.21	2.94	2.85	1.96	2.23	2.65	3.25
Ours	**0.76**	1.11	**0.77**	**0.80**	**0.79**	**0.81**	**0.84**	1.08	**2.05**	**1.02**	**1.03**	**1.15**	**0.99**	0.97	1.07	**1.02**

Table 2: Reconstruction accuracy evaluation on the DTU dataset. The evaluation metric is Chamfer distance, expressed in millimetres (mm).

Method	Pose	24	37	40	55	63	65	69	83	97	105	106	110	114	118	122	mean
NeRF(Mildenhall et al., 2020)		1.83	2.39	1.79	0.66	1.79	1.44	1.50	1.20	1.96	1.27	1.44	2.61	1.04	1.13	0.99	1.54
IDR(Yariv et al., 2020)		1.63	1.87	0.63	0.48	1.04	0.79	0.77	1.33	1.16	0.76	0.67	0.90	0.42	0.51	0.53	0.90
VolSDFYariv et al. (2021)	GT	1.14	1.26	0.81	0.49	1.25	0.70	0.72	1.29	1.18	0.70	0.66	1.08	0.42	0.61	0.55	0.86
PointNeRF(Xu et al., 2022)		0.87	2.06	1.20	1.01	1.01	1.39	0.80	**1.04**	0.92	0.74	0.97	**0.76**	0.56	0.90	1.05	1.02
NeuS(Wang et al., 2021a)		0.83	0.98	0.56	0.37	1.13	**0.59**	**0.60**	1.45	0.95	0.78	**0.52**	1.43	**0.36**	**0.45**	**0.45**	0.77
Voxurf Wu et al. (2023)		**0.65**	**0.74**	**0.39**	**0.35**	0.96	0.64	0.85	1.58	1.01	**0.68**	0.60	1.11	0.37	**0.45**	0.47	**0.72**
Voxurf	COLMAP	3.60	4.36	3.62	3.00	4.44	3.52	2.64	4.11	2.85	3.86	2.98	3.86	2.76	3.26	3.34	3.48
	BARF	3.95	4.35	3.84	3.02	4.38	4.09	2.02	3.68	2.56	3.62	3.61	4.06	2.63	3.04	4.14	3.53
	SPARF	3.34	5.30	1.35	2.75	6.17	2.81	1.85	3.24	1.85	2.17	2.05	5.30	1.03	1.62	2.45	2.89
	Ours	**0.64**	**0.84**	**0.59**	**0.48**	**1.10**	**1.02**	**0.90**	**1.43**	**1.10**	**0.83**	**0.86**	**1.11**	**0.58**	**0.65**	**0.67**	**0.85**

Here, $w_i = p_i{}^2$ is the loss weight that mitigates the influence of poorly matched pairs. The computation of the Sampson distance between two points, denoted as x and x', with the fundamental matrix F obtained from the (learned) camera poses and known intrinsics, is expressed as:

$$d_{\text{Sampson}}(x, x', F) = \frac{(x'^T F x)^2}{(Fx)_1^2 + (Fx)_2^2 + (F^T x')_1^2 + (F^T x')_2^2}. \tag{8}$$

Here, subscripts 1 and 2 refer to the first and second components of the respective vectors.

Training objectives. The overall loss function in our proposed joint optimisation method combines both Eqn. 3 and Eqn. 7, as follows:

$$\mathcal{L} = \mathcal{L}_{NSR} + \beta \mathcal{L}_{EG}, \tag{9}$$

where β is a hyperparameter that controls loss weights. The first term $\mathcal{L}_{NSR}$ represents the loss related to neural surface reconstruction, which backpropagates the gradients to both PoRF and rendering network parameters. The second term $\mathcal{L}_{EG}$ represents the loss associated with the epipolar geometry loss, which backpropagates the gradients to PoRF only.

5 EXPERIMENTS

Experiment setup. We perform our experiments on both the DTU Jensen et al. (2014) and MobileBrick Li et al. (2023a) datasets. Following previous methods such as Wu et al. (2023) and Li et al. (2023a), our evaluation uses the provided 15 test scenes from DTU and 18 test scenes from MobileBrick. We assess both the accuracy of camera poses and the quality of surface reconstructions. The baseline methods for comparison includes BARF Lin et al. (2021), L2G Chen et al. (2023), and SPARF Truong et al. (2023). For a fair comparison, all methods, including ours, take the same initial pose inputs—namely, COLMAP poses on the DTU dataset and ARKit poses on the MobileBrick dataset. Here, we consider all methods to be operating in a two-stage manner, so only the pose refinement is conducted by these methods, and we utilise Voxurf Wu et al. (2023) with the refined poses for the reconstruction step for all methods.

Table 3: Absolute pose accuracy on the MobileBrick dataset. The ARKit pose serves as the initial pose for all methods. Note that the provided GT pose in this dataset is imperfect.

Metrics	Rotation Error (Deg.)					Translation Error (mm)				
Scene	ARKit	BARF	L2G	SPARF	Ours	ARKit	BARF	L2G	SPARF	Ours
aston	0.43	0.22	0.22	0.22	**0.14**	2.49	1.21	1.21	1.01	**0.70**
audi	0.64	0.46	0.52	1.10	**0.28**	3.38	2.25	2.24	4.35	**1.11**
beetles	0.49	0.52	0.57	0.17	**0.14**	1.40	1.29	2.06	**1.21**	1.23
big_ben	0.44	0.33	0.49	0.27	**0.26**	4.23	3.03	2.13	2.38	**1.82**
boat	0.61	0.24	0.38	0.26	**0.22**	1.51	0.97	1.29	1.12	**0.98**
bridge	0.44	0.22	0.18	0.32	**0.22**	1.08	1.29	1.12	1.26	**0.78**
cabin	0.61	0.34	0.32	0.30	**0.26**	1.34	1.44	1.55	1.09	**0.93**
camera	0.30	0.23	0.26	**0.17**	0.18	0.86	1.06	1.07	0.67	**0.61**
castle	0.55	4.77	4.79	4.77	**0.30**	2.42	17.1	21.1	24.12	**2.55**
colosseum	0.46	0.49	0.35	0.95	**0.28**	3.67	4.21	4.41	11.26	**3.25**
convertible	0.40	0.27	0.25	0.23	**0.13**	1.65	1.18	1.21	1.31	**0.92**
ferrari	0.43	0.20	0.20	0.23	**0.13**	1.89	1.10	1.19	0.80	**0.59**
jeep	0.34	0.24	0.22	0.28	**0.23**	0.98	1.13	1.08	0.65	**0.50**
london_bus	0.72	0.70	0.73	0.50	**0.42**	3.62	2.97	2.98	3.61	**2.63**
motorcycle	0.34	0.26	0.29	0.27	**0.20**	0.97	1.01	1.10	0.82	**0.60**
porsche	0.28	0.19	0.20	0.20	**0.15**	1.29	1.16	1.18	0.88	**0.71**
satellite	0.41	0.23	0.26	**0.15**	0.17	1.45	0.92	1.11	**0.97**	0.98
space_shuttle	0.31	0.28	0.26	0.58	**0.18**	1.45	1.81	1.76	3.43	**1.30**
mean	0.46	0.57	0.58	0.61	**0.22**	1.90	2.50	2.84	3.39	**1.23**

Table 4: Reconstruction accuracy evaluation on the MobileBrick dataset. Note that the provided GT pose in this dataset is imperfect. The results are averaged over all 18 test scenes.

Methods	Pose	$\sigma = 2.5mm$			$\sigma = 5mm$			Chamfer ↓
		Accu. (%) ↑	Rec. (%) ↑	F1 ↑	Accu. (%) ↑	Rec. (%) ↑	F1 ↑	(mm)
TSDF-Fusion Zhou et al. (2018)		42.07	22.21	28.77	73.46	42.75	53.39	13.78
BNV-Fusion Li et al. (2022)		41.77	25.96	33.27	71.20	47.09	55.11	9.60
Neural-RGBD Azinović et al. (2022)		20.61	10.66	13.67	39.62	22.06	27.66	22.78
COLMAP Schönberger & Frahm (2016)	GT	74.89	68.20	71.08	93.79	84.53	88.71	5.26
NeRF Mildenhall et al. (2020)		47.11	40.86	43.55	78.07	69.93	73.45	7.98
NeuS Wang et al. (2021a)		77.35	70.85	73.74	93.33	86.11	89.30	4.74
Voxurf Wu et al. (2023)		78.44	72.41	75.13	93.95	87.53	90.41	4.71
	ARKit	71.90	66.98	69.18	91.81	85.71	88.43	5.30
Voxurf	BARF	77.12	71.36	73.96	93.47	87.56	90.22	4.83
	SPARF	76.10	70.44	72.99	92.73	86.66	89.39	4.95
	Ours	**79.01**	**72.94**	**75.67**	**94.07**	**87.84**	**90.65**	**4.67**

Implementation details.   The hyperparameters used for training the surface reconstruction align with those utilised in NeuS Wang et al. (2021a). To calculate the proposed epipolar geometry loss, we randomly sample 20 image pairs in each iteration and distinguish inliers and outliers by using a threshold of 20 pixels. The entire framework undergoes training for 50,000 iterations, which takes 2.5 hours in one NVIDIA A40 GPU. However, it's noteworthy that convergence is achieved rapidly, typically within the first 5,000 iterations. More details are in the supplementary materials.

5.1   COMPARISONS

Results on DTU.   The pose refinement results are presented in Table 1. It shows that BARF Lin et al. (2021) and L2G Chen et al. (2023) are unable to improve the COLMAP pose on DTU, and L2G diverges in several scenes. While SPARF Truong et al. (2023) shows a slight improvement in rotation, it remains limited, and it results in worse translation. Besides, we also evaluated Nope-NeRF Bian et al. (2023), but it diverged on DTU and MobileBrick scenes due to the bad initialisation of the depth scale. Overall, our proposed method achieves a substantial reduction of 78% in rotation error and shows a minor improvement in translation error.

The reconstruction results are presented in Tab. 2, where we run Voxurf Wu et al. (2023) for reconstruction. It shows that the reconstruction with the COLMAP pose falls behind previous methods that use the GT pose. BARF Lin et al. (2021) is hard to improve performance. While SPARF Truong et al. (2023) can slightly improve performance, it is limited. When employing the refined pose by our method, the reconstruction accuracy becomes comparable to most of the previous methods that

Table 5: Novel view rendering results on the Nerfstudio dataset. We replace the pose optimisation module in the Nerfacto with our PoRF MLP, leading to consistently improved novel view rendering accuracy. Note that we do not use the proposed loss function here.

Scenes	Ours			Nerfacto		
	PSNR ↑	SSIM ↑	LPIPS ↓	PSNR	SSIM	LPIPS
Egypt	**23.08**	**0.743**	**0.245**	20.75	0.623	0.305
person	**25.87**	**0.742**	**0.261**	24.33	0.643	0.299
kitchen	**20.72**	**0.796**	**0.271**	19.60	0.73	0.298
plane	**22.44**	**0.672**	**0.356**	19.72	0.557	0.440
dozer	**21.16**	**0.760**	**0.266**	20.26	0.716	0.279
floating tree	**20.82**	**0.769**	**0.204**	20.67	0.733	0.211
aspen	**17.16**	**0.344**	**0.611**	16.48	0.292	0.657
stump	**22.62**	**0.820**	**0.194**	21.96	0.753	0.213
sculpture	**22.28**	**0.692**	**0.296**	21.74	0.652	0.315
Giannini Hall	**19.29**	**0.590**	**0.406**	17.66	0.491	0.444
mean	**21.54**	**0.693**	**0.311**	20.32	0.619	0.346

use the GT pose, although there is still a minor gap between our method and Voxurf with the GT pose, *i.e.*, 0.85mm vs. 0.72mm.

Results on MobileBrick. The pose results are summarised in Tab. 3. We initialise all baseline methods, including ours, with the ARKit pose. Note that the provided GT pose in this dataset is imperfect, which is obtained by pose refinement from human labelling. The results show that our method is closer to the GT pose than others. More importantly, our method can consistently improve pose accuracy in all scenes, while other methods cannot.

The reconstruction results are presented in Tab. 4. It shows that the refined pose by all methods can lead to an overall improvement in reconstruction performance. Compared with BARF Lin et al. (2021) and SPARF Truong et al. (2023), our method shows more significant improvement. As a result, our approach surpasses the provided GT pose in terms of reconstruction F1 score, *i.e.*, 75.67 vs 75.13, achieving state-of-the-art performance on the MobileBrick dataset.

5.2 GENERALISATION

The proposed MLP-based pose optimisation method can be readily plugged into different NeRF-like systems to improve performance. To demonstrate the universal use of our method, we integrate it into the Nerfstudio library Tancik et al. (2023), which is a modular framework for neural radiance field development. We compare our method with the recommended baseline method (Nerfacto), which integrates multiple methods into one, including pose optimisation. For a fair comparison, we replace the original pose parameter optimisation module with our proposed PoRF MLP, and we do not use the proposed loss function. Tab. 5 provides the evaluation results on the Nerfstudio dataset. The dataset comprises ten in-the-wild, 360-degree captures obtained using either a mobile phone or a mirror-less camera with a fisheye lens. The data was processed using COLMAP or the Polycam app to obtain camera poses and intrinsic parameters. It shows that our method can consistently boost novel view rendering performance in diverse scenes.

5.3 ABLATION STUDIES

We conduct extensive ablation studies on the DTU dataset Jensen et al. (2014). The pose errors during training are shown in Fig. 3, where we compare six different settings and we can draw some key observations from the ablation studies:

PoRF vs pose parameter optimisation: L2 surpasses L1 in terms of accuracy, thereby highlighting the benefits of utilising the Pose Residual Field (PoRF) in contrast to conventional pose parameter optimisation within the same baseline framework, where solely the neural rendering loss is employed. Upon the integration of the proposed epipolar geometry loss L_{EG} with the baseline approach, L4 outperforms L3, substantiating the consistency of the observed outcomes.

Figure 4: Reconstruction results on DTU (top) and MobileBrick (bottom) datasets. The initial pose denotes the COLMAP pose on DTU, and the ARKit pose on MobileBrick. We use the standard evaluation metrics, *i.e.*, Chamfer distance (mm) for DTU and F1 score for MobileBrick.

Efficacy of the epipolar geometry loss: L3 demonstrates faster convergence when compared to L1, offering substantiation of the efficacy of the proposed L_{EG} loss within the context of pose parameter optimisation. Upon incorporating the proposed Pose Residual Field (PoRF), L4 surpasses L2, thus reinforcing the same conclusion.

Ablation over correspondences: we compare handcrafted matching methods (L4 representing SIFT Lowe (2004)) with deep learning-based methods (L5 denoting LoFTR Sun et al. (2021)). On average, SIFT yields 488 matches per image pair, while LoFTR generates a notably higher count of 5394 matches. The results indicate that both methods achieve remarkably similar levels of accuracy and convergence. It's worth noting that the SIFT matches are derived from COLMAP results, so their utilisation does not entail additional computational overhead.

Figure 3: Pose errors during training on the DTU dataset. The results are averaged over 15 test scenes. Baseline (B) denotes the naive joint optimisation of NSR and pose parameters.

Ablation over scene representations: We substitute the SDF-based representation (L4) with the NeRF representation Mildenhall et al. (2020), denoted as L6. This adaptation yields comparable performance, highlighting the versatility of our method across various implicit representations.

6 CONCLUSION

This paper introduces the concept of the Pose Residual Field (**PoRF**) and integrates it with an epipolar geometry loss to facilitate the joint optimisation of camera pose and neural surface reconstruction. Our approach leverages the initial camera pose estimation from COLMAP or ARKit and employs these newly proposed components to achieve high accuracy and rapid convergence. By incorporating our refined pose in conjunction with Voxurf, a cutting-edge surface reconstruction technique, we achieve state-of-the-art reconstruction performance on the MobileBrick dataset. Furthermore, when evaluated on the DTU dataset, our method exhibits comparable accuracy to previous approaches that rely on ground-truth pose information.

ACKNOWLEDGEMENT

The authors gratefully acknowledge the financial support provided by Apple. This work is also supported by the UKRI grant: Turing AI Fellowship EP/W002981/1 and EPSRC/MURI grant: EP/N019474/1. We also thank the Royal Academy of Engineering and FiveAI.

REFERENCES

Dejan Azinović, Ricardo Martin-Brualla, Dan B Goldman, Matthias Nießner, and Justus Thies. Neural rgb-d surface reconstruction. In *CVPR*, pp. 6290–6301, June 2022.

Wenjing Bian, Zirui Wang, Kejie Li, Jia-Wang Bian, and Victor Adrian Prisacariu. Nope-nerf: Optimising neural radiance field with no pose prior. In *CVPR*, pp. 4160–4169, 2023.

Yue Chen, Xingyu Chen, Xuan Wang, Qi Zhang, Yu Guo, Ying Shan, and Fei Wang. Local-to-global registration for bundle-adjusting neural radiance fields. In *CVPR*, pp. 8264–8273, 2023.

Shin-Fang Chng, Sameera Ramasinghe, Jamie Sherrah, and Simon Lucey. Garf: gaussian activated radiance fields for high fidelity reconstruction and pose estimation. *arXiv e-prints*, pp. arXiv–2204, 2022.

François Darmon, Bénédicte Bascle, Jean-Clément Devaux, Pascal Monasse, and Mathieu Aubry. Improving neural implicit surfaces geometry with patch warping. In *CVPR*, pp. 6260–6269, 2022.

Qiancheng Fu, Qingshan Xu, Yew Soon Ong, and Wenbing Tao. Geo-neus: Geometry-consistent neural implicit surfaces learning for multi-view reconstruction. *NeurIPS*, 35:3403–3416, 2022.

Yasutaka Furukawa, Brian Curless, Steven M Seitz, and Richard Szeliski. Reconstructing building interiors from images. In *ICCV*, pp. 80–87. IEEE, 2009.

Amos Gropp, Lior Yariv, Niv Haim, Matan Atzmon, and Yaron Lipman. Implicit geometric regularization for learning shapes. *arXiv preprint arXiv:2002.10099*, 2020.

Rasmus Jensen, Anders Dahl, George Vogiatzis, Engil Tola, and Henrik Aanæs. Large scale multi-view stereopsis evaluation. In *CVPR*, pp. 406–413, 2014. doi: 10.1109/CVPR.2014.59.

Yoonwoo Jeong, Seokjun Ahn, Christopher Choy, Anima Anandkumar, Minsu Cho, and Jaesik Park. Self-calibrating neural radiance fields. In *ICCV*, pp. 5846–5854, 2021.

Kejie Li, Yansong Tang, Victor Adrian Prisacariu, and Philip HS Torr. Bnv-fusion: Dense 3d reconstruction using bi-level neural volume fusion. In *CVPR*, 2022.

Kejie Li, Jia-Wang Bian, Robert Castle, Philip HS Torr, and Victor Adrian Prisacariu. Mobilebrick: Building lego for 3d reconstruction on mobile devices. In *CVPR*, pp. 4892–4901, 2023a.

Zhaoshuo Li, Thomas Müller, Alex Evans, Russell H Taylor, Mathias Unberath, Ming-Yu Liu, and Chen-Hsuan Lin. Neuralangelo: High-fidelity neural surface reconstruction. In *CVPR*, 2023b.

Chen-Hsuan Lin, Wei-Chiu Ma, Antonio Torralba, and Simon Lucey. Barf: Bundle-adjusting neural radiance fields. In *ICCV*, pp. 5741–5751, 2021.

David G Lowe. Distinctive image features from scale-invariant keypoints. *IJCV*, 60:91–110, 2004.

Nelson Max. Optical models for direct volume rendering. *IEEE TVCG*, 1995.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *ECCV*, pp. 405–421. Springer, 2020.

Johannes Lutz Schönberger and Jan-Michael Frahm. Structure-from-motion revisited. *CVPR*, 2016.

Johannes Lutz Schönberger, Enliang Zheng, Marc Pollefeys, and Jan-Michael Frahm. Pixelwise view selection for unstructured multi-view stereo. In *ECCV*, 2016.

Jiaming Sun, Zehong Shen, Yuang Wang, Hujun Bao, and Xiaowei Zhou. LoFTR: Detector-free local feature matching with transformers. *CVPR*, 2021.

Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH 2023 Conference Proceedings*, pp. 1–12, 2023.

Prune Truong, Marie-Julie Rakotosaona, Fabian Manhardt, and Federico Tombari. Sparf: Neural radiance fields from sparse and noisy poses. In *CVPR*, pp. 4190–4200, 2023.

Jiepeng Wang, Peng Wang, Xiaoxiao Long, Christian Theobalt, Taku Komura, Lingjie Liu, and Wenping Wang. Neuris: Neural reconstruction of indoor scenes using normal priors. In *ECCV*, pp. 139–155. Springer, 2022a.

Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. Neus: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. In *NeurIPS*, 2021a.

Yiqun Wang, Ivan Skorokhodov, and Peter Wonka. Hf-neus: Improved surface reconstruction using high-frequency details. *NeurIPS*, 35:1966–1978, 2022b.

Zirui Wang, Shangzhe Wu, Weidi Xie, Min Chen, and Victor Adrian Prisacariu. NeRF−−: Neural radiance fields without known camera parameters. *arXiv preprint arXiv:2102.07064*, 2021b.

Tong Wu, Jiaqi Wang, Xingang Pan, Xudong Xu, Christian Theobalt, Ziwei Liu, and Dahua Lin. Voxurf: Voxel-based efficient and accurate neural surface reconstruction. In *ICLR*, 2023.

Yitong Xia, Hao Tang, Radu Timofte, and Luc Van Gool. Sinerf: Sinusoidal neural radiance fields for joint pose estimation and scene reconstruction. *arXiv preprint arXiv:2210.04553*, 2022.

Qiangeng Xu, Zexiang Xu, Julien Philip, Sai Bi, Zhixin Shu, Kalyan Sunkavalli, and Ulrich Neumann. Point-nerf: Point-based neural radiance fields. In *CVPR*, pp. 5438–5448, 2022.

Yao Yao, Zixin Luo, Shiwei Li, Tian Fang, and Long Quan. Mvsnet: Depth inference for unstructured multi-view stereo. In *ECCV*, pp. 767–783, 2018.

Yao Yao, Zixin Luo, Shiwei Li, Tianwei Shen, Tian Fang, and Long Quan. Recurrent mvsnet for high-resolution multi-view stereo depth inference. In *CVPR*, pp. 5525–5534, 2019.

Lior Yariv, Yoni Kasten, Dror Moran, Meirav Galun, Matan Atzmon, Basri Ronen, and Yaron Lipman. Multiview neural surface reconstruction by disentangling geometry and appearance. *NeurIPS*, 33, 2020.

Lior Yariv, Jiatao Gu, Yoni Kasten, and Yaron Lipman. Volume rendering of neural implicit surfaces. In *Thirty-Fifth Conference on Neural Information Processing Systems*, 2021.

Zehao Yu, Songyou Peng, Michael Niemeyer, Torsten Sattler, and Andreas Geiger. Monosdf: Exploring monocular geometric cues for neural implicit surface reconstruction. *NeurIPS*, 2022.

Jingyang Zhang, Yao Yao, Shiwei Li, Zixin Luo, and Tian Fang. Visibility-aware multi-view stereo network. *BMVC*, 2020.

Jingyang Zhang, Yao Yao, Shiwei Li, Tian Fang, David McKinnon, Yanghai Tsin, and Long Quan. Critical regularizations for neural surface reconstruction in the wild. In *CVPR*, pp. 6270–6279, 2022.

Qian-Yi Zhou, Jaesik Park, and Vladlen Koltun. Open3D: A modern library for 3D data processing. *arXiv:1801.09847*, 2018.