EquiMod: An Equivariance Module to Improve Self-Supervised Learning

Abstract

Self-supervised visual representation methods are closing the gap with supervised learning performance. These methods rely on maximizing the similarity between embeddings of related synthetic inputs created through data augmentations. This can be seen as a task that encourages embeddings to leave out factors modified by these augmentations, i.e. to be invariant to them. However, this only considers one side of the trade-off in the choice of the augmentations: they need to strongly modify the images to avoid simple solution shortcut learning (e.g. using only color histograms), but on the other hand, augmentations-related information may be lacking in the representations for some downstream tasks (e.g. color is important for birds and flower classification). Few recent works proposed to mitigate the problem of using only an invariance task by exploring some form of equivariance to augmentations. This has been performed by learning additional embeddings space(s), where some augmentation(s) cause embeddings to differ, yet in a non-controlled way. In this work, we introduce *EquiMod* a generic equivariance module that structures the learned latent space, in the sense that our module learns to predict the displacement in the embedding space caused by the augmentations. We show that applying that module to state-of-the-art invariance models, such as SimCLR and BYOL, increases the performances on CIFAR10 and ImageNet datasets. Moreover, while our model could collapse to a trivial equivariance, i.e. invariance, we observe that it instead automatically learns to keep some augmentations-related information beneficial to the representations.

1 Introduction

Using relevant and general representation is central for achieving good performances on downstream tasks, for instance when learning object recognition from for high-dimensional data like images. Historically, feature engineering was the usual way of building representations, but we can currently rely on deep learning solutions to automate and improve this process of representation learning. Still, it is challenging as it requires learning a structured latent space while controlling the precise amount of features to put in representations: too little information will lead to not interesting representations, yet too many non-pertinent features will make it harder for the model to generalize. Recent works have focused on Self-Supervised Learning (SSL), i.e. determining a supervisory signal from the data with a pretext task. It has the advantages of not biasing the learned representation toward a downstream goal, as well as not requiring human labeling, allowing the use of plentiful raw data especially for domains lacking annotations. In addition, deep representation learning encourages network reuse via transfer learning, allowing for better data efficiency and lowering the computational cost of training for downstream tasks compared to the usual end-to-end fashion.

The performances of recent approaches in SSL of visual representation are progressively closing the gap with the supervised baseline (Caron et al., 2020; Chen et al., 2020a;b; Chen & He, 2021; Bardes et al., 2021; Grill et al., 2020; He et al., 2020; Misra & Maaten, 2020; Zbontar et al., 2021). Even if these SSL methods are diverse (see Liu (2021) for a review, and Szegedy et al. (2013) for a unification of existing works), they are mainly siamese networks performing an instance discrimination task. Their underlying mechanism is to maximize the similarity between the embedding of related synthetic inputs, a.k.a. views, created through data augmentations that share the same concepts, while using various tricks to avoid a collapse towards a constant solution (Jing et al., 2021;

Hua et al., 2021). This induces that the latent space learns an invariance to the transformations used, which causes representations to lack of augmentations-related information.

Even if these models are self-supervised, they rely on human expert knowledge to find these relevant invariances. For instance, as most downstream tasks in computer vision require object recognition, existing augmentations do not degrade the categories of objects in images. More precisely, the choice of the transformations was driven by some form of supervision, as it was done by experimentally searching for the set of augmentations giving the highest object recognition performance on the ImageNet dataset (Chen et al., 2020a). For instance, it has been found that color jitter is the most efficient augmentation on ImageNet. One possible explanation is that color histograms are an easy-to-learn shortcut solution (Geirhos et al., 2020), which is not removed by cropping augmentations (Chen et al., 2020a). Indeed, as there are many objects in the categories of ImageNet, and as an object category does not change when its color does, the loss of color information is worth removing the shortcut. However, while this is true for objects, it is known that color is an essential feature for some categories, such as flowers or birds (Xiao et al., 2020).

Thus, for a given downstream task, we can separate augmentations into two groups: the ones for which the representations benefit from insensitivity (or invariance) and the ones for which sensitivity (or variance) is beneficial (Dangovski et al., 2021). Indeed, there is a trade-off in the choice of the augmentations: they require to significantly modify the images to avoid simple solution shortcut learning (e.g. relying just on color histograms), yet some downstream tasks may need augmentations-related in the representations (e.g. need of color for birds or flower classification). Theoretically, this trade-off limits the generalization of such representation learning methods relying on invariance. Recently, some works have explored different ways of including sensitivity to augmentations and successfully improved augmentations-invariant SSL methods by using tasks forcing sensitivity while keeping an invariance objective in parallel. Dangovski et al. (2021) impose a sensitivity to rotations, an augmentation that is not beneficial for the invariance task, while we focus in this paper on sensitivity to transformations used for invariance. Xiao et al. (2020) propose to learn as many tasks as there is augmentations by learning multiple latent spaces, each one being invariant to all but one transformation, however, it does not control the way augmentations-related information is conserved. One can see this as an implicit way of learning variance to each possible augmentation. Contrary to these works that to not control the way augmentations-related information is conserved, here we propose to explore sensitivity by introducing an equivariance module that structures its latent space by learning to predict the displacement in the embedding space caused by augmentations in the pixel space.

The contributions of this article are the following:

- We introduce a generic equivariance module *EquiMod* to mitigate the invariance to augmentations in recent self-supervised visual representation learning;
- We show that using *EquiMod* with state-of-the-art invariance models, such as SimCLR and BYOL, boosts the performances on CIFAR10 and ImageNet datasets;
- We study the robustness of *EquiMod* to architectural variations of its sub-components;
- We observe that our model automatically learns a specific level of equivariance for each augmentation.

Sec. 2 will present our EquiMod module as well as the implementation details, while in Sec. 3 we will describe the experimental setup used to study our model and present the results obtained. The Sec. 4 will position our work w.r.t. related work. Finally, in Sec. 5 we will discuss our current results and possible future works.

2 EQUIMOD

2.1 NOTIONS OF INVARIANCE AND EQUIVARIANCE

As in Dangovski et al. (2021), we relate the notions of augmentations sensitivity and insensitivity to the mathematical concepts of invariance and equivariance. Let $\mathcal{T}$ be a distribution of possible transformations, and f denotes a projection from the input space to a latent space. That latent space is said to be invariant to $\mathcal{T}$ if for any given input x the Eq. 1 is respected.

$$\forall t \in \mathcal{T} \qquad f(t(\boldsymbol{x})) = f(\boldsymbol{x}) \tag{1}$$

Misra & Maaten (2020) used this definition of invariance to design a pretext task for representation learning. This formulation reflects that the embedding of a non-augmented input sample $\boldsymbol{x}$ will not change if the input is transformed by any of the transformations in $\mathcal{T}$. However, more recent works (Bardes et al., 2021; Chen et al., 2020a; Chen & He, 2021; Grill et al., 2020; Zbontar et al., 2021) focused on another formulation of invariance defined by the following Eq. 2.

$$\forall t \in \mathcal{T}, \ \forall t' \in \mathcal{T} \qquad f(t(\boldsymbol{x})) = f(t'(\boldsymbol{x})) \tag{2}$$

With this definition, the embedding produced by an augmented sample $\boldsymbol{x}$ is independent of the transformation used. Still, note that Eq. 1 implies Eq. 2, and that if the identity function is part of $\mathcal{T}$, which is the case with recent approaches, then both definitions are indeed equivalent.

While insensitivity to augmentation is reflected by invariance, sensitivity can be obtained by achieving variance, i.e. replacing the equality by an inequality in Eq. 1 or Eq. 2. Yet, this is not an interesting property, as any injective function will satisfy this constraint. In this paper, we propose to use equivariance as a way to achieve variance to augmentations for structuring our latent space. Eq. 3 gives the definition of equivariance used in the following work.

$$\forall t \in \mathcal{T}, \ \exists u_t \qquad f(t(\boldsymbol{x})) = u_t(f(\boldsymbol{x})) \tag{3}$$

With u_t being a transformation in the latent space parameterized by the transformation t, it can be seen as the counterpart of the transformation t but in the embedding space. With this definition, the embeddings from different augmentations will be different, and thus encode somehow information related to the augmentations. Yet, if u_t is always the identity then this definition of equivariance becomes the same as invariance Eq.1. Indeed, one can see invariance as a trivial specific case of equivariance. In the following, we only target non-trivial equivariance where u_t produces some displacement in the latent space. See Fig. 1 for a visual comparison of invariance and equivariance.

2.2 METHOD

EquiMod[1] (see Fig. 2) is a generic equivariance module that captures some augmentations-related information originally suppressed by the learned invariance. The main idea relies on equivariance, in the sense that our module learns to predict the displacement in the embedding space caused by the augmentations. This way by having non-null displacement, we ensure embeddings to contain augmentations-related information. Our model acts as a supplement to existing invariance models (Bardes et al., 2021; Chen et al., 2020a; Chen & He, 2021; Grill et al., 2020; Zbontar et al., 2021). We first introduce a formalization for these existing methods (see Bardes et al. (2021) for an in-depth explanation of this unification), before introducing how our approach adds on top.

Let t and t' denote two augmentations sampled from the augmentations distribution $\mathcal{T}$. For a given input image $\boldsymbol{x}$, two views are defined as $\boldsymbol{v}_i := t(\boldsymbol{x})$ and $\boldsymbol{v}_j := t'(\boldsymbol{x})$. Following previous works, we note f_θ an encoder parameterized by θ producing representations from images, and g_ϕ a projection head parameterized by ϕ, which projects representations in an embedding space. This way, the representations are defined as $\boldsymbol{h}_i := f_\theta(\boldsymbol{v}_i)$ as well as $\boldsymbol{h}_j := f_\theta(\boldsymbol{v}_j)$, and the embeddings as $\boldsymbol{z}_i := g_\phi(\boldsymbol{h}_i)$ as well as $\boldsymbol{z}_j := g_\phi(\boldsymbol{h}_j)$. Then, the model learns to maximize the similarity between $\boldsymbol{z}_i$ and $\boldsymbol{z}_j$, while using diverse tricks to maintain a high entropy for the embeddings, preventing collapse to constant representations.

To extend those preceding works, we introduce a second latent space to learn our equivariance task. For this purpose, we first define a second projection head $g'_{\phi'}$ parameterized by ϕ' whose objective is to project representations in our latent space. Using this projection head we note $\boldsymbol{z}'_i := g'_{\phi'}(\boldsymbol{h}_i)$ and $\boldsymbol{z}'_j := g'_{\phi'}(\boldsymbol{h}_j)$, the embeddings of the views $\boldsymbol{v}_i$ and $\boldsymbol{v}_j$ in this latent space we introduce. Moreover, the way we have defined equivariance in Eq 3 requires us to produce the embedding of the non-augmented image $\boldsymbol{x}$, thus we note the representation $\boldsymbol{h}_o := f_\theta(\boldsymbol{x})$, which is used to create

---

[1]Code will be made publicly available on GitHub

Figure 1: On the left, invariance described by Eq. 1, on the right, equivariance considered in this paper and described by Eq. 3.

Figure 2: The model learns similar embeddings for an augmented view (z_i') and the prediction of the displacement in the embedding space caused by that augmentations ($\hat{z}_i'$), see Sec. 2 for notation details.

the embedding $z_o' := g_{\phi'}'(h_o)$ for the given image x. Next, as mentioned in Sec.2.1, to learn an equivariant latent space one needs to determine a transformation u_t for any given t, this can be done either by fixing it or by learning it. In this work, we learn the transformation u_t. To this end, we define u_ψ a projection parameterized by the learnable parameters ψ, referenced later as the equivariance predictor (implementation details about how t influences u_ψ are given below in Sec. 2.3). The goal of this predictor is to produce $\hat{z}_i'$ from a given z_o' and t (resp. $\hat{z}_j'$ for z_o' and t'). One can see $\hat{z}_i'$ as an alternative way to obtain z_i' using the equivariance property defined by Eq. 3. Instead of computing the embedding of the augmented view $v_i := t(x)$, we apply t via u_ψ on the embedding z_o' of the original image x.

Still, as $g_{\phi'}'$ and u_ψ are initialized with random values, that equivariance property between z_i' and $\hat{z}_i'$ has to be learned. For this purpose, we denote $(z_i', \hat{z}_i')$ as a positive pair (resp. $(z_j', \hat{z}_j')$), and design our equivariance task so that our model learns to maximize the similarity between those positive pairs. One issue with this formulation is that it allows collapse solutions, e.g. every z' being a constant. To avoid such simple solutions, we consider negative pairs (as in Chen et al. (2020a); He et al. (2020)) to repulse embedding from other embedding coming from views of different images and use the Normalized Temperature-scaled cross entropy (NT-Xent) loss to learn from positive and negative pairs, and define our equivariance loss for a pair (i, j) as Eq. 4:

$$\ell_{i,j}^{EquiMod} = -\log \frac{\exp(\text{sim}(z_i', \hat{z}_i')/\tau')}{\sum_{k=1}^{2N} \mathbb{1}_{[k \neq i \wedge k \neq j]} \exp(\text{sim}(z_i', z_k')/\tau')} \tag{4}$$

where τ' is a temperature parameter, $\text{sim}(a, b)$ is the cosine similarity defined as $a^\top b/(\|a\|\|b\|)$, and $\mathbb{1}_{[k \neq i \wedge k \neq j]}$ is the indicator function evaluated to 1 (0 otherwise) when $k \neq i$ and $k \neq j$. This way, we exclude from negative pairs the views of a same image, note that such pairs are usually positive in invariance methods. While we could consider these pairs as negative and still be in accordance with 3, we found that not using them as negative nor as positive lead to slightly better results. One hypothesis is that repulsing views that can be very close in the pixel space (e.g. if the sampled augmentations modify weakly the original image) could induce training instability. One can notice that $g_{\phi'}'$ and u_ψ are learned simultaneously, thus they can influence each other during the training phase. We finally define the total loss of the model as

$$\mathcal{L} = \mathcal{L}_{Invariance} + \lambda \mathcal{L}_{EquiMod}$$

with $\mathcal{L}_{EquiMod}$ being the loss Eq. 4 applied to all pairs of a batch and $\mathcal{L}_{Invariance}$ being the loss of the invariance baseline. λ is an hyperparameter that ponder the equivariant term of the loss.

2.3 IMPLEMENTATION DETAILS

2.3.1 ARCHITECTURES

We have tested our module on 3 baselines, SimCLR Chen et al. (2020a), BYOL Grill et al. (2020), and Barlow Twins Zbontar et al. (2021). Here are the details of each part of the architecture, including the baseline ones and our equivariance module:

- *Encoder*: we follow existing works and use a convolutional neural network for the encoder f_θ, more specifically deep residual architectures from He et al. (2016).

- *Invariance projection head*: for the projection head g_ϕ (and potential predictor as in Sim-Siam and BYOL Chen & He (2021); Grill et al. (2020)), we have used the same experimental setup as the ones of the original papers, except for SimCLR where we used a 3 layers projection head as in Chen & He (2021).

- *Equivariance projection head*: the setup of our projection head $g'_{\phi'}$ is a 3 layers Multi-Layer Perceptron (MLP), where each Fully-Connected (FC) layer is followed by a Batch Normalization (BN) and a ReLU activation, except the last layer which is only followed by a BN and no ReLU. Hidden FC have 2048 neurons each.

- *Equivariant predictor*: the predictor u_ψ is a FC followed by a BN. To feed u_ψ with t, we concatenate an encoding representing t with the input embedding (details of how augmentations are encoded are presented in Sec.2.3.2). This way, the input dimension of the predictor is the dimension of the latent space plus the dimension of the encoding of augmentations, while the output dimension is the same as the latent space.

2.3.2 ENCODING OF THE AUGMENTATIONS

To encode augmentations we first represent them by a vector containing their application (or not) and their parameters. To construct this vector, since each of the augmentations are applied with some probabilities (except crop which is always performed), we first define an element for each augmentation (thus cropping apart) valued to 1 when the augmentation is performed and valued to 0 otherwise. While this is enough to describe horizontal flip, grayscale and solarize, other augmentations require additional elements to be fully represented:

- *Resized Crop* (4 elements): x and y coordinates of the top-left pixel of the crop as well as width and height of the crop.

- *Color Jitter* (8 elements): the jitter factors for brightness, saturation, contrast and hue $(1, 1, 1, 0$ if color jitter is not applied), as well as the order of application of the jitter. More precisely, to encode the order of modification, we use the following mapping $\{0 :$ brightness, $1 :$ contrast, $2 :$ saturation, $3 :$ hue$\}$ and index the operations regarding their order. For instance an encoding with "$1, 3, 2, 0$" would mean that contrast jitter is first applied, then hue, followed by contrast, and finally brightness $(0, 1, 2, 3$ if color jitter is not applied).

- *Gaussian Blur* (1 element): the value of sigma used (0 if blur is not applied).

This way, while using all the augmentations mentioned, one finds a vector of 18 dimensions. Still, we do not use this vector directly, but rather use a FC followed with a BN to project it in a 128 dimensional space. Those layers are learned jointly with the rest of the model, and raw input vectors are normalized with experimental mean and std.

3 EXPERIMENTS

3.1 EXPERIMENTAL SETTINGS

In our experimentations, we tested our method on ImageNet (IN) (Deng et al., 2009) and CIFAR10 (Krizhevsky et al., 2009). As mentioned before, we have used our module as a complement to SimCLR, BYOL and Barlow Twins, 3 state-of-the-art invariance methods with quite different ideas, in order to test the genericity of our module. As in previous works, while training on ImageNet we used a ResNet50 without the last FC, but while training on CIFAR10 we used the CIFAR variant of ResNet18 (He et al., 2016). For all our experimentations we used the LARS You et al. (2017) optimizer, yet, biases and BN parameters were excluded from both weight decay and LARS adaptation as in Grill et al. (2020)).

3.1.1 SIMCLR

The model is trained for 800 epochs with 10 warm-up epochs and a cosine decay learning rate schedule. We have used a batch size of 4096 for ImageNet and 512 for CIFAR10, while using an

initial learning rate of 2.4 for ImageNet (where we use 4.8 for SimCLR without EquiMod, as in the original paper) and 4.0 for CIFAR10. For the optimizer, we fix the momentum to 0.9 and the weight decay to $1e^{-6}$. Both the invariant and equivariant latent space dimensions have been set to 128. Finally, we use $\tau' = 0.2$ for our loss, but $\tau = 0.2$ on ImageNet $\tau = 0.5$ with CIFAR10 for the loss of SimCLR (we refer reader to the orignial paper for more information about the loss of SimCLR (Chen et al., 2020a)).

3.1.2 BYOL

The model learns for only 100 epochs[2] (800 on CIFAR10) with 10 warm-up epochs and a cosine decay learning rate schedule. The batch size used is 4096 for ImageNet and 512 for CIFAR10. We have been using a initial learning rate of 4.8 for ImageNet (where we use 3.2 for BYOL without EquiMod, as in the original paper) while using 2.0 for CIFAR10. Momentum of the optimizer is set to 0.9 and weight decay to $1.5e^{-6}$ on ImageNet, but $1e^{-6}$ on CIFAR10. The invariant space have 256 dimensions while we keep our equivariant latent space to 128. Last, we use $\tau' = 0.2$ for our loss, and $\tau_{\text{base}} = 0.996$ for the momentum encoder of BYOL with a cosine schedule as in the original paper (once again, we refer reader to the paper for more details (Grill et al., 2020)).

3.1.3 BARLOW TWINS

We tested our method with Barlow Twins only on CIFAR10 with the following setup: 800 epochs with 10 warm-up epochs and a cosine decay learning rate schedule, a batch size of 512, an initial learning rate of 1.2, a momentum of 0.9 and weight decay of $1.5e^{-6}$. Both the invariant and equivariant latent space have 128 dimensions, while we use $\tau' = 0.2$ for our loss and $\lambda_{\text{Barlow Twins}} = 0.005$ for the loss of Barlow Twins (as in the paper (Grill et al., 2020)).

3.2 RESULTS

3.2.1 LINEAR EVALUATION

After training on either ImageNet or CIFAR10, we evaluate the quality of the learned representation using the usual linear evaluation. To this end, we train a linear classifier on top of the frozen representation, using the Stochastic Gradient Descent (SGD) for 90 epochs with a batch size of 256, a nesterov momentum of 0.9, no weight decay, an initial learning rate of 0.2 and a cosine decay learning rate schedule.

Results of this linear evaluation are presented in Table 1. Across all baselines and datasets tested, EquiMod increases the performances of the baselines used, which supports the genericity of our approach. Moreover, this confirms our idea that adding an equivariance task helps to extract more pertinent information than with just an invariance task to improves representations. Note that for ImageNet, on BYOL we trained for 100 epochs as in Dangovski et al. (2021), still, with 100 epochs we observe a performance gain with our addition. We may expect a better final performance if learning was performed over 1000 epochs, which was not possible due to computational ressource limitations. On CIFAR10, we achieve the second best performance after E-SSL, yet, contrary to us, they tested their model on an improved hyperparameter settings of SimCLR.

3.2.2 EQUIVARIANCE MEASUREMENT

The way our model is formulated could lead to the learning of invariance rather than equivariance. Indeed, learning an invariant latent space as well as the function identity for u_ψ is an admissible solution. Therefore, to verify that our model is really learning equivariance, we define the two metrics of equivariance Eq.5 and Eq.6. The first one evaluate the absolute displacement toward z'_i caused by the predictor u_ψ. One can see this as how much does applying the augmentation t to z'_o in the latent space via u_ψ makes the resulting embedding $\hat{z}'_i$ more similar to z'_i. This way, if our model is learning invariance, we should observe an absolute displacement of 0, as u_ψ would be the identity. On the contrary, if it is learning equivariance, we should observe a positive value, meaning that the u_ψ plays its role of predicting the displacement in the embedding space caused by

---

[2]We only perform 100 epoch (instead of 1000) as in Dangovski et al. (2021) due to limited computational resources

Method	ImageNet		CIFAR10	
	Top-1	Top-5	Top-1	Top-5
PIRL (Misra & Maaten, 2020)	63.6	-	-	-
E-SimCLR (Dangovski et al., 2021)	68.3‡	-	94.1	-
E-SimSiam (Dangovski et al., 2021)	68.6‡	-	94.2	-
SimCLR (Chen et al., 2020a)	69.3	89.0	-	-
SimSiam (Chen & He, 2021)	71.3	-	-	-
SwAV (w/o multi-crop) (Caron et al., 2020)	71.8	-	-	-
Barlow Twins (Zbontar et al., 2021)	73.2	91.0	-	-
VICReg (Bardes et al., 2021)	73.2	91.1	-	-
BYOL (Grill et al., 2020)	74.3	91.6	-	-
SimCLR∗	71.57	90.48	90.96	99.73
SimCLR∗ + EquiMod	**72.30**	**90.84**	**92.79**	**99.78**
BYOL∗	62.09‡	84.01‡	90.44	99.62
BYOL∗ + EquiMod	**65.55‡**	**86.74‡**	**91.57**	**99.71**
Barlow Twins∗	-	-	86.94	99.61
Barlow Twins∗ + EquiMod	-	-	**88.87**	**99.71**

Table 1: **Linear Evaluation**; top-1 and top-5 accuracies (in %) under linear evaluation on ImageNet and CIFAR10 (symbols ∗ denote our re-implementations, and ‡ denote only 100 epochs training).

the augmentations. Still, a small displacement do not mean poor equivariance, for instance, if z'_o is very similar to z'_i, room for displacement is already very small. This is why we also introduce the second metric, which evaluate the relative displacement toward z'_i caused by u_ψ. It reflects by which factor does applying the augmentation t to z'_o in the latent space via u_ψ makes the resulting embedding $\hat{z}'_i$ less dissimilar to z'_i. Thus, if the model is learning invariance, we should see no reduction nor augmentation of the dissimilarity, thus the factor should remain to 1. However, a model achieving equivariance would exhibit a positive factor.

$$\text{sim}(z'_i, \hat{z}'_i) - \text{sim}(z'_i, z'_o) \qquad (5) \qquad\qquad \frac{1 - \text{sim}(z'_i, z'_o)}{1 - \text{sim}(z'_i, \hat{z}'_i)} \qquad (6)$$

The Fig. 4 shows the absolute equivariance measured for each augmentation. Note that this is performed on a model already trained with the usual augmentation policy containing all the augmentations. If an augmentation induces a large displacement, it means the embedding is highly sensitive to the given augmentation. What we can see from Fig. 4, is that regardless of the dataset used, the model achieves poor sensitivity to horizontal flip and grayscale. However, on ImageNet, we observe a high sensitivity to color jitter as well as medium sensitivity to crop and gaussian blur. On CIFAR10 we observe a strong sensitivity to crop and a medium sensitivity to color jitter. Therefore, we can conclude that our model truly learns an equivariance structure, and moreover, that the learned equivariance is more sensitive to some augmentation such as crop or color jitter.

Figure 3: Absolute equivariance measure for each augmentation.

Figure 4: Relative equivariance measure for each augmentation.

3.2.3 INFLUENCE OF THE ARCHITECTURES

We study how architectural variations can influence our model. More precisely, we explore the impact of the architecture of the $g'_{\phi'}$, u_ψ as well as the learned projection of t mentioned Sec. 2.3.2. To this end, we train models for each architectural variation on CIFAR10, and report the the top-1 accuracies under linear evaluation, the results are reported in Table 2. What we observe in Table 2a, is that the projection head of the equivariant latent space benefits from having more layers, yet this effect seems to plateau at some point. These results are in line with existing works (Chen et al., 2020a). While testing various architecture for the equivariant predictor Table 2b, we note only small performance variations, indicating that u_ψ is robust to architectural changes. Finally, looking at Table 2c, we observe that removing the projection of t only lead to a small drop of performance. On the contrary, complex architectures (two last lines) lead to a bigger drop of accuracy. Furthermore, while testing different output dimensions (lines 2 to 4), we note that using the same dimension for the output and for the equivariant latent space lead to highest results.

Layers in $g'_{\phi'}$	Top-1
None	88.46
1	91.58
2	92.58
3 †	92.79

(a) **Equivariance projection head**

Layers in u_ψ	Top-1
1 †	92.79
2 (H: 16-d)	92.67
2 (H: 128-d)	92.59
2 (H: 2048-d)	92.70

(b) **Equivariant predictor**

Layers in the projection of t	Top-1
None	92.50
1 (O: 16-d)	92.57
1 (O: 128-d) †	92.79
1 (O: 2048-d)	92.50
2 (H: 16-d; O: 128-d)	92.47
2 (H: 128-d; O: 128-d)	92.13
2 (H: 2048-d; O: 128-d)	92.05

(c) **Augmentation projector**

Table 2: Top-1 accuracies (in %) under linear evaluation on CIFAR10 for some architectural variations of our module. H stands for hidden layer, O for output layer, † denotes default setup.

4 RELATED WORK

Recent methods of SSL visual representation learn a latent space where embeddings of augmentations from a same image are learned to be similar. Yet, this task admits simple constant solutions. To avoid such collapse, recent methods implement diverse tricks to maintain a high entropy for the embeddings. Grill et al. (2020) rely on a momentum encoder as well as an architectural asymmetry, Chen & He (2021) rely on a stop gradient operation, Zbontar et al. (2021) rely on a redundancy reduction loss term, Bardes et al. (2021) rely on a variance term as well as a covariance term in the loss, Chen et al. (2020a) use negative pairs repulsing sample in a batch. In this work, our task also admits collapse solutions, thus we make use of the same negative pairs as in Chen et al. (2020a) to avoid such collapse. Most recent methods are creating pairs of augmentations to maximize the similarity between those pairs. However, our addition does not rely on pairs of augmentations, and only need a source image and an augmentation. This is similar to Misra & Maaten (2020) which requires to have a source image and an augmentation, however, they use these pairs to learn an invariance task while we use them to learn an equivariance task.

Our approach is part of a line of recent works, which try to perform additional tasks of sensitivity to augmentation while learning an invariance task. This is the case of E-SSL (Dangovski et al., 2021), which simultaneously learns to predict rotations applied to the input image while learning an invariance pretext task. This way, their model learn to be sensitive to the rotation transformation, usually not used for invariance. Where this can be considered as a form of equivariance (a rotation in input space produces a predictable displacement in the prediction space) this is far from the equivariance we explore in this paper. Indeed, E-SSL sensitivity task can be seen as learning an instance-invariant pretext task, where for any given input, the output represents only the augmentation (rotation) used. However, we explore equivariance sensitive both to image and to augmentations. Moreover, we only consider sensitivity to the augmentations used for invariance. In LooC (Xiao et al., 2020), authors propose to use as many different projection heads as there is augmentations, and learn each of these projection heads to be invariant to all but one augmentations. This way the projection heads can

implicitly learn to be sensitive to an augmentation. Still, they do not control how this sensitivity occurs, where we explicitly define an equivariance structure for the augmentations-related information. Note that a work have tried to tackle the trade-off from the other side, by trying to reduce the shortcut learning occurring, instead of adding sensitivity to augmentations. Robinson et al. (2021) shows that shortcut learning occurring in invariant SSL is partly due to the formulation of the loss function and proposes a method to reduce shortcut learning in contrastive learning.

Some other works have also successfully used equivariance with representation learning. For instance, Jayaraman & Grauman (2015) uses the same definition of equivariance than us, and successfully learns an equivariant latent space tied to ego-motion. Still, their objective is to learn embodied representations as well as using the learned equivariant space, in comparison we only use equivariance as a pretext task to learn representations. Moreover, we do not learn equivariance on the representations, but rather on a non-linear projection of the representations. Lenc & Vedaldi (2015) learns an equivariant predictor on top of representations to measure their equivariance, however, to learn that equivariance, they require the use of strong regularizations.

5 CONCLUSION AND PERSPECTIVES

Recent self-supervised visual representation methods rely on learning a pretext task of invariance to augmentations. This encourages the leaned embeddings to discard information related to transformations. However, this does not fully consider the underlying dilemma that occurs in the choice of the augmentations: strong modifications of image are required to remove some possible shortcut solutions, while information manipulated by the augmentation could be useful to some downstream tasks. In this paper, we have introduced EquiMod, a generic equivariance module that can complements existing invariance approaches. The goal of our module is to let the network learn an appropriate form of sensitivity to augmentations. It is done through equivariance via a module that predict the displacement in the embedding space caused by the augmentations. Our method is part of a research trend that preforms sensitivity to augmentations. Nonetheless, compared to other existing works, we perform sensitivity to augmentations also used for invariance, therefore reducing the trade-off, while defining a stringer structure in our latent space via equivariance.

When testing EquiMod across multiple invariance baselines models and datasets, we always observed an improvement under linear evaluation. This shows that our model is able to capture more pertinent information than with just an invariance task. In addition, we also studied the robustness of our model through architectural variations of its components, and observed a strong robustness, which is a non negligible advantage as training such methods is computationally expensive, and so does the hyperparameters exploration. When exploring the sensitivity to the various augmentations, we noticed that the latent space effectively learns to be equivariant to almost all augmentations, which shows that it captures most of the augmentations-related information.

For future works, we plan on testing our module on more baselines models or even as a standalone. As EquiMod always improved the results in our tests, it suggests that EquiMod could improve performances on many more baselines and datasets. Then, since E-SSL adds sensitivity to rotation, yet still do not consider sensitivity to augmentations used for invariance, it would be interesting to study if combining EquiMod and E-SSL can improve even further the performances. Another research axis is to perform an in depth study of the generalization and robustness capacity of our model. To this end, we want to explore its capacity for transferability and few-shot learning, both on usual object recognition datasets, but also on more challenging datasets containing flowers and birds as in Xiao et al. (2020). Since the trade-off theoretically limits the generalization on the learned representation, and since we reduce the effect of the trade-off, we hope that EquiMod may show advanced generalization and robustness properties. On a more distant horizon, the equivariant structure learned by our latent space, may open some interesting perspectives, related to world model learning and planning.

REFERENCES

Adrien Bardes, Jean Ponce, and Yann LeCun. Vicreg: Variance-invariance-covariance regularization for self-supervised learning. *arXiv preprint arXiv:2105.04906*, 2021.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *arXiv preprint arXiv:2006.09882*, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020a.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey Hinton. Big self-supervised models are strong semi-supervised learners. *arXiv preprint arXiv:2006.10029*, 2020b.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15750–15758, 2021.

Rumen Dangovski, Li Jing, Charlotte Loh, Seungwook Han, Akash Srivastava, Brian Cheung, Pulkit Agrawal, and Marin Soljačić. Equivariant Contrastive Learning. *arXiv preprint arXiv:2111.00899*, 2021.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A. Wichmann. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020. Publisher: Nature Publishing Group.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, and Mohammad Gheshlaghi Azar. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Tianyu Hua, Wenxiao Wang, Zihui Xue, Sucheng Ren, Yue Wang, and Hang Zhao. On feature decorrelation in self-supervised learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9598–9608, 2021.

Dinesh Jayaraman and Kristen Grauman. Learning image representations tied to ego-motion. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1413–1421, 2015.

Li Jing, Pascal Vincent, Yann LeCun, and Yuandong Tian. Understanding dimensional collapse in contrastive self-supervised learning. *arXiv preprint arXiv:2110.09348*, 2021.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Karel Lenc and Andrea Vedaldi. Understanding image representations by measuring their equivariance and equivalence. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 991–999, 2015.

Ran Liu. Understand and Improve Contrastive Learning Methods for Visual Representation: A Review. *arXiv preprint arXiv:2106.03259*, 2021.

Ishan Misra and Laurens van der Maaten. Self-supervised learning of pretext-invariant representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6707–6717, 2020.

Joshua Robinson, Li Sun, Ke Yu, Kayhan Batmanghelich, Stefanie Jegelka, and Suvrit Sra. Can contrastive learning avoid shortcut solutions? *Advances in neural information processing systems*, 34:4974–4986, 2021.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Tete Xiao, Xiaolong Wang, Alexei A. Efros, and Trevor Darrell. What should not be contrastive in contrastive learning. *arXiv preprint arXiv:2008.05659*, 2020.

Yang You, Igor Gitman, and Boris Ginsburg. Large batch training of convolutional networks. *arXiv preprint arXiv:1708.03888*, 2017.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. *arXiv preprint arXiv:2103.03230*, 2021.