Stealthy Terrain-Aware Multi-Agent Active Search

Abstract: Stealthy multi-agent active search is the problem of making efficient sequential data-collection decisions to identify an unknown number of sparsely located targets while adapting to new sensing information and concealing the search agents' location from the targets. This problem is applicable to reconnaissance tasks wherein the safety of the search agents can be compromised as the targets may be adversarial. Prior work usually focuses either on adversarial search, where the information leakage to the targets is ignored or evasion strategies where efficient search is ignored. We present the Stealthy Terrain-Aware Reconnaissance (STAR) algorithm, a multi-objective parallelized Thompson sampling-based algorithm that relies on a strong topographical prior to reason over changing visibility risk over the course of the search. The STAR algorithm outperforms existing state-of-the-art multi-agent active search methods on both rate of recovery of targets as well as minimising risk even when subject to noisy observations, communication failures and an unknown number of targets.

Keywords: Reconnaissance, Adversarial Search, Multi-robot, Active Learning

1 Introduction

Search and reconnaissance efforts have historically been a human endeavour, however several factors can impede effective search by human teams. The search region could be too vast to mobilise enough human resources to effectively search and the personal safety of human searchers could be at risk. While human operators can remotely control a small number of robotic platforms, they cannot efficiently coordinate larger teams [1]. Consistent communication between the agents may not be possible either due to adversarial attacks or environmental factors. Finally, these operations are time-critical, hence decentralized multi-robot teams capable of efficient asynchronous adversarial search with active learning are crucial as data-collection decisions need to be made online on the basis of runtime observations.

In prior work, the problem of adversarial search is often referred to as the pursuer-evader problem [2, 3]. Several approaches seek to maximise the worst-case performance of the pursuer and imbibe the evader with extraordinary abilities like complete knowledge, infinite travel speed, and infinite compute. However, these solutions are often prohibitively expensive to compute [4] in real-time or too conservative to be applicable in the real-world settings [5].

We model the problem as one of stealthy target detection [6], with multiple pursuers and immobile evaders that may be placed on the map adversarially. This is in contrast to target tracking [7, 8] where the targets can move. Target detection with static targets is a realistic choice as, in the reconnaissance task, it is not uncommon that the search is being carried out for well-concealed static objects like pieces of infrastructure or environmental features as this knowledge can be of strategic importance; and, in search and rescue missions, stranded people could be immobile or mobile, but until they are

(a) Desert mountainous landscape in our Unity-based simulation environment. Two full-size ground vehicles are also pictured.

(b) Top-down view of the terrain showing average visibility as a colour gradient from deep blue to bright yellow.

(c) Top-down view of the terrain showing the costmap and the search region as a red polygon.

Figure 1: Terrain can inform search and evasion strategies. The grid size in Fig. 1b is $60m \times 60m$. This region's dimensions are $2305.5m \times 1837.5m$ representing a total area of $4.236km^2$. In the costmap in Fig. 1c the area inside the red polygon is $2.48km^2$. Magenta is non-traversable. Black to blue to red indicate increasing topography-aware visibility risk. The green cross is the goal location provided to the OMPL [9] path planner and the green path is the path computed to the goal location while minimizing the visibility risk.

detected for the first time they can be treated as immobile and the problem formulation remains the same.

The core idea of our approach is simple, during search and reconnaissance missions, a strong prior on the number of targets or their locations is usually not available, however, satellite imagery and by extension topographical information of the search region may be available. If the agent were to search for sparsely located targets in the map shown in Fig. 1b, the intuition is that it would be beneficial to search in better hiding places.

We present the Stealthy Terrain-Aware Reconnaissance (STAR) algorithm, a multi-objective optimisation algorithm that follows the Myopic Posterior Sampling (MPS) framework [10, 11, 12, 13] which has been shown to be near optimal for adaptive goal-oriented tasks [14] such as in the multi-agent asynchronous active search problem we have here. In MPS, we select the optimal action by optimising a reward based on a single sample (known as the Thompson Sample) taken from the current belief, this allows for a calculated randomness in the search decisions made by various agents even if communication or hardware failures prevent coordination. As more observations are made, the agents learn to take better actions that bring them closer to their search objective.

We ablate the performance of STAR against existing methods in simulation varying the map type, reliability of communication, number of search agents and whether or not targets are placed adversarially in simulation. In all cases, STAR outperforms existing methods. We have designed STAR to be deployable on ground-based robotic platforms described in [citation omitted to preserve double blind] in a search region that is $4km^2$ in size. In the supplementary material we have also attached a demo video showcasing our ground platforms and search behaviour of STAR in the realistic simulator. Our motivation for only presenting simulation results in this paper is to ablate and assess the performance of the STAR algorithm against the state of the art from an algorithmic standpoint as physical runs cannot usually be conducted in quantities that show statistical significance.

To the best of our knowledge, STAR is the state-of-the-art in search efficiency for adversarial multi-agent active search that is robust to communication failures and operates without any human direction or manual subdivision of the search region.

2 Related Work

In pursuer-evader problems the primary objective of the search agent(s) is to trap or track the evader with theoretical guarantees for a worst-case evader [15, 16, 17, 18]. However, these approaches don't consider the inverse adversarial problem of minimizing information leakage to the adversary (as it already has complete knowledge). Some approaches attempt to use approximate algorithms and relax the requirement for guarantees [19], however none of these approaches can be extended to have an unknown number of evaders.

Probabilistic search methods seek to improve expected or average case performance. Bayesian learning provides an effective way to model the probabilistic world, inculcate prior information and adapt to information over the course of the search [20, 21]. However, these approaches often rely on perfect observation models (no noise, no false positives) and their examination of optimal behaviour is usually confined to single pursuer or single evader cases [22, 23]. In a similar vein, prior work has attempted to model the problem using Partially Observable Markov Decision Processes (POMDPs) [24] in an effort to identify optimal policies, however beyond one pursuer, the optimal solution becomes intractable. An excellent survey on adversarial search by Chung et. al. [25] covers an overview of the field and open research questions.

Decentralised adversarial multi-agent active search that is robust to communication failure is an actively researched field. Given the success of the POMDP formulation mentioned earlier in the single-agent case, researchers have attempted to apply reinforcement learning to the problem [6, 26]; however, these approaches are extremely sample inefficient and prone to overfit to the environment they are trained on. In our formulation with known topography, it is not clear if these RL methods will generalize to different topographies.

Terrain-aware path planning with adversarial targets is well-studied in the context of military operations [27, 28, 29] and in the context of stealth-based video games [30, 31]. However, these approaches focus on path planning but not on a competing search objective.

Adversarial search has some implementations on real-hardware [32, 33, 34, 35] and there are approaches that attempt to validate their results in simulation [22, 36, 37]. However, these approaches are usually single-agent. If they are multi-agent then they rely on strong coordination between agents. GUTS [13] is a non-adversarial active search algorithm that has been shown to outperform state-of-the-art algorithms on recovery rate of targets and has been deployed on physical hardware. It is the state-of-the-art for robust multi-agent active search.

3 Problem Formulation

We model the search region as a grid with a cell size of 60m x 60m. Fig 1c shows an overhead view of the costmap for one of the maps we test on. Due to the ubiquity of satellite imagery, it is reasonable to assume such approximate map information of the search region to be available. Some parts of the map may be different during deployment on physical systems, but our on-robot sensing and mapping system can recognize changes and dynamically update the prior map. For our experiments, however, we assume the map to be fixed.

We model the stealthy active search problem as follows:

- We give the same search region to all robots, for example, see red polygon in Fig. 1c.
- The targets are sparsely placed and static. They need to be located as fast as possible with high certainty.
- The robots must minimise their exposure to the targets which are considered hostile.
- Each robot must plan its next data collection action on-board, i.e., no central planner exists.
- The robots may communicate their locations and observations with each other; however, the algorithm's performance should improve with increasing number of search agents anywhere in the spectrum of total absence of communication to perfect communication.

Formally, we represent the locations of targets in our 2D grid representation using a sparse matrix $\mathbf{B} \in \mathbb{R}^{M_1 \times M_2}$. Let $\beta \in \mathbb{R}^M$ be the flattened version of matrix $\mathbf{B}$, where $M = M_1 M_2$. This vector is sparsely populated, with 1 at locations corresponding to targets and 0 elsewhere. We model the uncertainty in our observations by

$$\mathbf{y}_t^j = clip(\mathbf{X}_t^j \beta \pm \mathbf{b}_t^j, 0, 1) \tag{1}$$

where, $\mathbf{X}_t^j \in \mathbb{R}^{Q \times M}$ describes the sensing matrix such that each row in $\mathbf{X}_t^j$ is a one-hot vector indicating one of the grid cells in view of the robot j at timestep t, and Q is the total number of grid cells

| (a) | (b) | (c) | (d) |

Figure 2: A simple illustration of the maximum extent of the (a) robot viewable region given its coordinates and direction of facing, and (b) the target's viewable region given its coordinates. The black cells represent obstructed cells.

Figure 3: Depth Elevation Map (DEM) of (c) a natural mountainous search region, and (d) a grid of perpendicular corridors. The brighter the region, the greater the elevation.

the robot can view. $\mathbf{y}_t^j \in \mathbb{R}^{Q \times 1}$ is the resultant observation including the additive terrain-aware noise vector $\mathbf{b}_t^j \in \mathbb{R}^{Q \times 1}$. Going forward, we assume that these quantities are defined on a per-robot basis and drop the superscript j for ease of notation. The topography-aware noise $\mathbf{b}_t$ has two components; firstly, it encodes the intuition that observation uncertainty increases with distance to the robots; secondly, it encodes the intuition that observation uncertainty increases with occlusions in the line of sight from the robot. We model it as follows:

$$\mathbf{b}_t = \mathbf{n}_t / \mathbf{v}_t \tag{2}$$

here, $/$ denotes element wise division, $\mathbf{n}_t \sim \mathcal{N}^+(0, \Sigma_t)$ with diagonal elements of the noise covariance matrix Σ_t monotonically increasing with the square of the distance of the observed cell from the robot. $\mathbf{v}_t \in \mathbb{R}^{Q \times 1}$ where each entry represents the square of the fractional visibility (accounting for occlusions) of each of the Q cells visible in $\mathbf{X}_t$. The noise is sampled from a positive half-Gaussian distribution $\mathcal{N}^+(0, \Sigma_t)$ and is added for cells without targets and subtracted for cells with targets. The observation $\mathbf{y}_t$ is clipped to be within 0 and 1. Similarly, we have an observation model for the targets albeit with some relaxations, namely, only accounting for occlusions but no depth-aware noise. Fig. 2 shows simple examples of the modelled viewable regions of the robots and targets.

Let the robot trajectory for robot j until timestep t be denoted $\mathbf{L}_t^j \in \mathbb{R}^M$ such that each entry in $\mathbf{L}_t^j$ is the integer count of the number of times robot j has visited that cell in the whole space M. We define a penalty function $\mathscr{P}(\mathbf{L}_t^j)$, which penalizes the robot for showing itself to any of the targets.

$$\mathscr{P}(\mathbf{L}_t^j) = \sum_q^{Q'} \sum_k \mathbf{X}_k \mathbf{L}_t^j \tag{3}$$

Similar to above, $\mathbf{X}_k \in \mathbb{R}^{Q' \times M}$ is the sensing matrix for the k^{th} target, note that it is not dependent on the timestep t as targets are static. The second summation is to reduce the value to a single real number. The stealth penalty can be thought of as a scaled discretized representation of the time spent in the viewable region of the target(s).

Let $\mathbf{D}_t^j$ be the set of observations available to robot j at timestep t. $\mathbf{D}_t^j$ comprises of $(\mathbf{X}_t, \mathbf{y}_t)$ pairs collected by robot j as well as those communicated to robot j by other robots. Let the total number of sensing actions by all agents be T. Our main objective is to sequentially optimize the next sensing action $\mathbf{X}_{t+1}$ based on $\mathbf{D}_t^j$ at each timestep t to recover the sparse signal β with as few measurements T as possible while minimizing the stealth penalty over all robots $\sum_j \mathscr{P}(\mathbf{L}_t^j)$. Each robot optimizes this objective based on its own partial dataset $\mathbf{D}_t^j$ in a decentralized manner.

4 STAR: Stealthy Terrain-Aware Reconnaissance

This section presents the STAR algorithm. Each robot j asynchronously estimates the posterior distribution over target locations based on its partial dataset $\mathbf{D}_t^j$. During the action selection stage, each robot generates a sample from this posterior and simultaneously optimizes a reward function

148 and a stealth penalty for this sampled set of target locations. The reward function represents potential
149 information gain for the sensing action in consideration, while the stealth penalty represents the
150 potential information leakage based on the partial dataset $\mathbf{D}_t^j$ available.

4.1 Calculating Posterior

152 Each robot assumes a zero-mean gaussian prior per entry of the vector β s.t. $p_0(\beta_m) = \mathcal{N}(0,\gamma_m)$.
153 The variances $\Gamma = diag([\gamma_1...\gamma_M])$ are hidden variables which are estimated using data. We follow
154 Tipping [38] and Wipf and Rao [39] and use a conjugate inverse gamma prior on γ_m to enforce
155 sparsity s.t. $p(\gamma_m) = IG(a_m,b_m) = \frac{b_m^{a_m}}{\Gamma(a_m)}\gamma_m^{(-a_m-1)}e^{-(b_m/\gamma_m)} \forall m \in \{1...M\}$. The salient feature of the
156 inverse gamma distribution $IG(.)$ is that it selects a small number of variances γ_m to be significantly
157 greater than zero, while the rest will be nearly zero, this enforces sparsity. We estimate the posterior
158 distribution on β given data $\mathbf{D}_t^j$ for robot j using Expectation Maximisation [40]. We can write
159 analytic expressions for the E-step (estimating $\hat{\beta} = p(\beta|\mathbf{D}_t^j,\Gamma) = N(\mu,\mathbf{V})$) and M-step (computing
160 $\max_\Gamma p(\mathbf{D}_t^j|\beta,\Gamma)$) respectively:

$$\mathbf{V} = (\Gamma^{-1} + \mathbf{X}^T\Sigma\mathbf{X})^{-1}; \mu = \mathbf{V}\mathbf{X}^T\Sigma\mathbf{y} \quad (4) \qquad \gamma_m = ([\mathbf{V}]_{mm} + [\mu]_m^2 + 2b_m)/(1 + 2a_m) \quad (5)$$

162 where $\mathbf{X}$ and $\mathbf{y}$ are created by vertically stacking all measurements $(\mathbf{X}_t,\mathbf{y}_t)$ in $\mathbf{D}_t^j$, and Σ is a diagonal
163 matrix composed of their corresponding terrain-aware noise variances.

164 Each robot estimates $p(\beta|\mathbf{D}_t^j) = N(\mu,\mathbf{V})$ on-board using its partial dataset $\mathbf{D}_t^j$. We set the values
165 of $a_m = 0.1$ and $b_m = 1$ as these were found to be effective in Ghods et al. [11]. Finally, agent j
166 samples from the posterior $\tilde{\beta} \sim p(\beta|\mathbf{D}_t^j)$.

4.2 Choosing Next Sensing Action

168 Each robot chooses the next sensing action $\mathbf{X}_{t+1}$ by assuming that the sampled set of target locations
169 $\tilde{\beta}$ is correct. Specifically, let $\hat{\beta}(\mathbf{D}_t^j \cup (\mathbf{X}_{t+1},\mathbf{y}_{t+1}))$ be our expected estimate of the parameter β using
170 all available measurements $\mathbf{D}_t^j$ and the next candidate measurement $(\mathbf{X}_{t+1},\mathbf{y}_{t+1})$. Then, following
171 Bakshi et al. [13] the reward function is defined as:

$$\mathcal{R}(\tilde{\beta},\mathbf{D}_t^j,\mathbf{X}_t) = -||\tilde{\beta} - \hat{\beta}(\mathbf{D}_t^j \cup (\mathbf{X}_t,\mathbf{y}_t))||_2^2 - \lambda \times I(\tilde{\beta},\hat{\beta}) \quad (6)$$

172 Where, $\lambda (= 0.01)$ is a hyperparameter that reduces the reward for a search location if the estimated
173 $\hat{\beta}$ does not have high likelihood entries in common with the sample at the current step $\tilde{\beta}$. Let $\hat{k}$ and
174 $\tilde{k}$ be the number of non-zero entries in $\hat{\beta}$ and $\tilde{\beta}$, then the indicator function $I(.)$ is defined as:

$$I(\tilde{\beta},\hat{\beta}) = \begin{cases} 0, \text{if any matches between top } \frac{\hat{k}}{2} \text{ entries in } \hat{\beta} \text{ and top } \frac{\tilde{k}}{2} \text{ entries in } \tilde{\beta} \\ 1, \text{otherwise} \end{cases}$$

175 The reward function is stochastic due to the sampling of $\tilde{\beta}$ and this ensures that the search actions
176 selected by the robots are diverse. This reward function was shown to improve search recovery rate
177 in robotic search and rescue missions over existing methods [13] .

179 This reward function needs to be balanced against the stealth penalty term that was defined in Eqn.
180 3 except that instead of the robot trajectory till time step t we calculate the penalty for the next
181 possible goal location of the robot j which we denote as $\mathbf{l}_t^j$. $\mathbf{l}_t^j \in \mathbb{R}^M$ is a one hot vector indicating
182 the location of the robot corresponding to the potential measurement $\mathbf{X}_t^j$ in the reward defined in Eqn.
183 6. However, we don't know the ground truth locations of the targets, we only have the posterior $\hat{\beta}$.
184 We use the folded normal distribution to determine a separate posterior mean $\hat{\mu}_{vis} \in \mathbb{R}^M$ for visibility
185 risk that accounts for the mean and variance of the posterior $\hat{\beta}$ as defined in Eqn. 7 and the penalty
186 function is defined in Eqn. 8:

$$\hat{\mu}_{vis}^i = \sqrt{\frac{2\mathbf{V}_{ii}}{\pi}}exp\left(\frac{-\hat{\mu}_i^2}{2\mathbf{V}_{ii}}\right) + \hat{\mu}_i\left(1 - 2\phi\left(\frac{-\hat{\mu}_i}{\sqrt{\mathbf{V}_{ii}}}\right)\right) \qquad \mathcal{P}(\mathbf{l}_t^j) = \sum_i^M \hat{\mu}_{vis}^i \sum_q^{Q'} \mathbf{X}_i\mathbf{l}_t^j \quad (8)$$

$$(7)$$

(a) We generate the view-shed of the agent in all directions if it were located at the red dot. White indicates visibility to the agent, and black indicates invisibility.

(b) We impose viewing limits ($200m-300m$), discretize the viewshed to the $60m \times 60m$ cell size grid, and superimpose this viewshed on the topographical map.

(c) Search Efficiency vs. Number of Agents: We see that search efficiency improves with an increasing number of search agents for all algorithms except RSI, which is an information-greedy method.

(d) Visibility Risk vs. Number of Agents: STAR is a clear winner here. Its terrain-awareness informs search and path planning to optimize recovery rate and visibility risk simultaneously.

Figure 4: (Left) Representative examples of extent of field-of-view of ground-based agents. (Right) Performance of STAR algorithm in the grid of corridors map.

(a) Non-Adversarial (b) Comm. Breakdown (c) Adversarial (d) Comm. Breakdown

(e) Non-Adversarial (f) Comm. Breakdown (g) Adversarial (h) Comm. Breakdown

Figure 5: Simplified Simulator Results. Top row shows the graphs of number of decision steps per agent to locate all targets against number of agents. Bottom row shows the stealth penalty incurred by the search team against number of agents. STAR outperforms existing state-of-the-art methods on both metrics (lower is better) regardless of how targets are placed, and even when there is total communication breakdown.

where, in Eqn. 7 $\mathbf{V}$ and μ are the variance and mean of the posterior defined in Eqn. 4, ϕ is the error function $\phi(z) = \frac{2}{\sqrt{\pi}} \int_0^z e^{-t^2} dt$ and i indexes into the M length vector. In Eqn. 8, $\hat{\mu}_{vis}^i$ behaves as a weighting scalar for each location i in the map where a threat may be located. When the posterior variance for a location i is close to zero then $\hat{\mu}_{vis}^i$ will tend to the posterior mean μ^i, and when the variance is high but the mean is zero (as it is at the beginning of the run) the weighting factor will still be non-zero as it will be governed by the variance. The overall optimisation objective can then be thought of as two competing objectives as follows:

$$\mathbf{X}_t, \mathbf{l}_t = \arg\max_{\tilde{\mathbf{X}}, \tilde{\mathbf{l}}} \left(\mathscr{R}(\beta^*, \mathbf{D}_t^j, \tilde{\mathbf{X}}) - \gamma \mathscr{P}(\tilde{\mathbf{l}}) \right) \text{ from (6) and (8)} \tag{9}$$

where, γ is a hyperparameter controls the tradeoff between goal selection to satisfy the stealth penalty and the reward term. We found that the best value for γ is 1 combined with normalising both the reward and stealth penalty terms between 0 and 1.

5 Experiments and Results

Our experiments demonstrate the superior search efficiency of our proposed algorithm STAR compared to existing search methods: GUTS, RSI, coverage-based search and random search. The GUTS algorithm [13] is a parallelized Thompson sampling based algorithm that prioritises recovery

(a) 1-Robot Search Perf.	(b) 1-Robot Stealth Perf.	(c) 2-Robot Search Perf.	(d) 2-Robot Stealth Perf.
(e) 1-Robot Search Perf.	(f) 1-Robot Stealth Perf.	(g) 2-Robot Search Perf.	(h) 2-Robot Stealth Perf.

Figure 6: Realistic Simulation Results. Top row shows the performance adversarially placed targets. Bottom Row with targets placed uniformly at random. STAR displays greater search efficiency and lower stealth penalty incurred regardless of target placement strategy. In (b) RSI is able to have a lower stealth penalty than STAR as it fails to locate the targets in most runs. The end of the line indicates the end of the runtime budget, and hence the stealth penalty at the end of each curve is the final stealth penalty for that run.

rate in multi-agent active search missions with realistically modelled noise. It has been optimised to run on real robots and to the best of our knowledge it is the state-of-the-art in decentralised multi-agent active search methods. Region Sensing Index (RSI) [41] is an active search algorithm that locates sparse targets while taking into account realistic sensing constraints based on greedy maximisation of information gain. The coverage baseline myopically chooses the next waypoint in an unvisited part of the search region while the random search policy randomly selects a cell to visit.

5.1 Testing Setup

Each search run is initialized by specifying the same search region for each robot (see Fig. 1c). All robots start at the same location. We evaluate the various search algorithms under two target sampling paradigms: uniform and adversarial. In uniform sampling the targets are placed uniformly at random in the search region. In adversarial sampling the targets are placed stealthily, i.e., they are placed in locations with a lower average visibility within the search region. We control for the locations of the targets using these two paradigms. We utilize two possible maps, a mountainous desert landscape (See Fig. 1a and Fig. 3-a) and a grid of corridors (see Fig. 3-b). There are always 5 targets (K) but this is not known apriori. We run experiments with a varying number of search agents (J) which may or may not be able to communicate with each other to showcase the robustness of STAR.

5.2 Evaluation Metrics

Our primary evaluation metric is the recovery rate, which is defined as the fraction of targets the search method has located against the number of search decisions made within the time budget. Our secondary metric is the stealth penalty incurred by the team of search agents.

We evaluate the algorithm on the basis of decision steps, i.e. one search decision is one time step. This is equivalent to assessing an algorithm's sample complexity while abstracting away environment/hardware specific factors like terrain conditions or particular compute specifications that might affect wall clock time. That being said, when evaluating in the realistic simulator each algorithm is given the same runtime budget of 1 hr and 15 min as indicated in Sec. 5.4.

The stealth penalty is a scaled discretized representation of the time spent in the viewable region of the target(s). Eqn. 3 describes the stealth penalty as the dot product between the viewable region of the targets and the path(s) taken by the robot(s). Given the cell size of the grid and speed of the robots, we may calculate time spent by the agents in view of the targets using the stealth penalty.

Similar to above, however, we choose to abstract away physical quantities like speed and report performance on the stealth penalty directly.

5.3 Simple Simulator Results

Our simple simulator accurately simulates the robots' sensing and trajectory planning while using a very simple physics model for robot traversal in order to speed up simulation time. Fig. 4 shows the performance the results in the simple simulator on the grid of corridors (Fig. 3-b) with adversarially placed targets. STAR wins out on both metrics, maximising recovery rate of targets and minimising risk. Fig. 5 shows the results on the simple simulator for the mountainous desert landscape (Fig. 3-a) and ablates it against communication failures and non-adversarial target placement. Across the board, STAR (marked in red) outperforms existing methods. When communication failures exist, coverage based planners suffer the most as their search efficiency relies on coordination. RSI remains unaffected as it is an information greedy algorithm and more agents doesn't translate to greater efficiency either. GUTS, the current state-of-the-art in decentralised multi-agent active search, performs fairly well on recovery targets but clearly loses out on the stealth metric to STAR.

5.4 Realistic Simulator Results

We have also designed STAR such that it can run in real-time on the multi-robot team presented in [citation redacted in deference to double blind review]. To this end we simulate field tests in a natural unstructured environment with a search area of $\sim 2.5km^2$ with a realistic physics model and present those results here. We compare the search efficiency of STAR, with GUTS, RSI, random search and coverage-based search in Fig. 6. We plot results varying team size and target placement strategy with five targets. Results are aggregated across 10-12 runs for each line on the graph. We can see that STAR outperforms our baselines: GUTS, RSI, coverage-based search and random search on the recovery rate (odd columns) as well as in terms of the stealth penalty (even columns) regardless if the targets are placed adversarially or uniformly.

5.5 Discussion

Despite optimising to reduce the stealth penalty, a competing objective, STAR still outperforms the other algorithms on recovery rate, including GUTS, the the previous best algorithm in terms of search efficiency. This indicates that the terrain-aware stealth penalty term improves the discriminatory power of the reward function.

The results shown in this work demonstrate that fully autonomous robots can effectively search in complicated natural terrains in a time efficient manner. We believe the algorithm presented here paves the way for more ubiquitous application of autonomous robotics in multi-agent search for disaster response and reconnaissance and will save human effort and human lives with greater adoption.

6 Limitations

This work tackles a gap in current literature wherein, prior work ignores the information leakage aspect when solving adversarial search and ignores the efficient search when designing stealth algorithms. However, we do not tackle the case for moving targets and this limits the applicability of the STAR algorithm.

We utilize Depth Elevation Maps since our primary use case is open outdoor environments. In the current formulation this is useful as we assume the search space is 2-D, however this limits the applications as it would likely fail in caves, cliff overhangs, or other 3-D structures that breakdown the 2-D assumption.

We assume a symmetric sensing model for the targets and the agents, while this is conservative, it can be improved by incorporating a directionality to the assumed target sensing model, possibly by incorporating a movement model. Another limitation is that, if the target had a less powerful sensing model than the agents, it is possible to complete a search with zero-risk?

References

[1] F. Greenwood, E. L. Nelson, and P. G. Greenough. Flying into the hurricane: a case study of uav use in damage assessment during the 2017 hurricanes in texas and florida. *PLoS one*, 15 (2):e0227808–e0227808, 2020. ISSN 1932-6203. doi:10.1371/journal.pone.0227808.

[2] R. Nowakowski and P. Winkler. Vertex-to-vertex pursuit in a graph. *Discrete Mathematics*, 43 (2):235–239, 1983. ISSN 0012-365X. doi:https://doi.org/10.1016/0012-365X(83)90160-7.

[3] M. Aigner and M. Fromme. A game of cops and robbers. *Discrete Applied Mathematics*, 8(1): 1–12, 1984. ISSN 0166-218X. doi:https://doi.org/10.1016/0166-218X(84)90073-8.

[4] A. S. Goldstein and E. M. Reingold. The complexity of pursuit on a graph. *Theor. Comput. Sci.*, 143:93–112, 1995.

[5] V. Isler, S. Kannan, and S. Khanna. Randomized pursuit-evasion with local visibility. *SIAM j. discrete math.*, 20(1):26–41, 2006.

[6] J. Buermann and J. Zhang. Multi-robot adversarial patrolling strategies via lattice paths. *Artificial Intelligence*, 311:103769, 2022. ISSN 0004-3702.

[7] L. Zhou, V. Tzoumas, G. J. Pappas, and P. Tokekar. Resilient active target tracking with multiple robots. *IEEE Robotics and Automation Letters*, 4(1):129–136, 2019.

[8] L. Zhou and V. Kumar. Robust multi-robot active target tracking against sensing and communication attacks. In *2022 American Control Conference (ACC)*, pages 4443–4450, 2022. doi:10.23919/ACC53348.2022.9867575.

[9] I. A. Şucan, M. Moll, and L. E. Kavraki. The Open Motion Planning Library. *IEEE Robotics & Automation Magazine*, 19(4):72–82, December 2012. doi:10.1109/MRA.2012.2205651.

[10] K. Kandasamy, A. Krishnamurthy, J. Schneider, and B. Poczos. Parallelised bayesian optimisation via thompson sampling. In A. Storkey and F. Perez-Cruz, editors, *Proceedings of the Twenty-First International Conference on Artificial Intelligence and Statistics*, volume 84 of *Proceedings of Machine Learning Research*, pages 133–142. PMLR, 09–11 Apr 2018.

[11] R. Ghods, W. J. Durkin, and J. Schneider. Multi-Agent active search using realistic Depth-Aware noise model. *CoRR*, abs/2011.04825, 2020.

[12] R. Ghods, A. Banerjee, and J. Schneider. Decentralized multi-agent active search for sparse signals. In C. de Campos and M. H. Maathuis, editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, volume 161 of *Proceedings of Machine Learning Research*, pages 696–706. PMLR, 27–30 Jul 2021.

[13] N. A. Bakshi, T. Gupta, R. Ghods, and J. Schneider. Guts: Generalized uncertainty-aware thompson sampling for multi-agent active search. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2023. To appear.

[14] K. Kandasamy, W. Neiswanger, R. Zhang, A. Krishnamurthy, J. Schneider, and B. Poczos. Myopic posterior sampling for adaptive goal oriented design of experiments. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pages 3222–3232. PMLR, 2019.

[15] G. Hollinger, A. Kehagias, and S. Singh. Gsst: Anytime guaranteed search. *Auton. Robots*, 29 (1):99–118, jul 2010. ISSN 0929-5593. doi:10.1007/s10514-010-9189-9.

[16] G. Hollinger, S. Singh, and A. Kehagias. Improving the efficiency of clearing with multi-agent teams. *The International Journal of Robotics Research*, 29(8):1088–1105, 2010. doi:10.1177/0278364910369949.

[17] A. Kehagias, G. Hollinger, and S. Singh. A graph search algorithm for indoor pursuit/evasion. *Mathematical and Computer Modelling*, 50(9):1305–1317, 2009. ISSN 0895-7177. doi:https://doi.org/10.1016/j.mcm.2009.06.011.

[18] A. Kleiner and A. Kolling. Guaranteed search with large teams of unmanned aerial vehicles. In *2013 IEEE International Conference on Robotics and Automation*, pages 2977–2983, 2013. doi:10.1109/ICRA.2013.6630990.

[19] R. J. Marcotte, A. Haggenmiller, G. Ferrer, and E. Olson. Probabilistic multi-robot search for an adversarial target.

[20] D. Assaf and S. Zamir. Optimal Sequential Search: A Bayesian Approach. *The Annals of Statistics*, 13(3):1213 – 1221, 1985.

[21] F. Bourgault, A. Göktogan, T. Furukawa, and H. F. Durrant-Whyte. Coordinated search for a lost target in a bayesian world. *Advanced Robotics*, 18(10):979–1000, 2004.

[22] E.-M. Wong, F. Bourgault, and T. Furukawa. Multi-vehicle bayesian search for multiple lost targets. In *Proceedings of the 2005 IEEE International Conference on Robotics and Automation*, pages 3169–3174, 2005. doi:10.1109/ROBOT.2005.1570598.

[23] G. Kimeldorf and F. H. Smith. Binomial searching for a random number of multinomially hidden objects. *Management Science*, 25(11):1115–1126, 1979.

[24] N. Roy, G. Gordon, and S. Thrun. Finding approximate pomdp solutions through belief compression. *J. Artif. Int. Res.*, 23(1):1–40, jan 2005. ISSN 1076-9757.

[25] T. H. Chung, G. A. Hollinger, and V. Isler. Search and pursuit-evasion in mobile robotics: A survey. *Auton. Robots*, 31(4):299–316, 2011.

[26] B. Baker, I. Kanitscheider, T. Markov, Y. Wu, G. Powell, B. McGrew, and I. Mordatch. Emergent tool use from multi-agent autocurricula. In *International Conference on Learning Representations*, 2020.

[27] A. Teng, D. DeMenthon, and L. Davis. Stealth terrain navigation. *Systems, Man and Cybernetics, IEEE Transactions on*, 23:96 – 110, 02 1993. doi:10.1109/21.214770.

[28] A. Tews, G. Sukhatme, and M. Mataric. A multi-robot approach to stealthy navigation in the presence of an observer. In *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA '04. 2004*, volume 3, pages 2379–2385 Vol.3, 2004. doi:10.1109/ROBOT.2004.1307417.

[29] B. McCue and National Defense University Press. *U-boats in the bay of Biscay: An essay in operations analysis*. National Defense University Press, 1990.

[30] W. Al Enezi and C. Verbrugge. Skeleton-based multi-agent opponent search. In *2021 IEEE Conference on Games (CoG)*, pages 1–8. IEEE, 2021.

[31] D. Isla. Third eye crime: building a stealth game around occupancy maps. In *Proceedings of the Ninth AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, page 206. AAAI Press, 2013.

[32] R. Vidal, O. Shakernia, H. Kim, D. Shim, and S. Sastry. Probabilistic pursuit-evasion games: theory, implementation, and experimental evaluation. *IEEE Transactions on Robotics and Automation*, 18(5):662–669, 2002. doi:10.1109/TRA.2002.804040.

[33] J. Tisdale, Z. Kim, and J. K. Hedrick. Autonomous uav path planning and estimation. *IEEE Robotics Automation Magazine*, 16(2):35–42, 2009. doi:10.1109/MRA.2009.932529.

[34] B. P. Gerkey, S. Thrun, and G. Gordon. Parallel stochastic hill- climbing with small teams. In L. E. Parker, F. E. Schneider, and A. C. Schultz, editors, *Multi-Robot Systems. From Swarms to Intelligent Automata Volume III*, pages 65–77, Dordrecht, 2005. Springer Netherlands. ISBN 978-1-4020-3389-6.

[35] M. Vieira, R. Govindan, and G. Sukhatme. Scalable and practical pursuit-evasion with networked robots. *Intelligent Service Robotics*, 2:247–263, 10 2009. doi:10.1007/s11370-009-0050-y.

[36] G. Hollinger, S. Singh, J. Djugash, and A. Kehagias. Efficient multi-robot search for a moving target. *Int. J. Rob. Res.*, 28(2):201–219, 2009.

[37] J. Buermann and J. Zhang. Multi-robot adversarial patrolling strategies via lattice paths. *Artificial Intelligence*, 311:103769, 2022. ISSN 0004-3702. doi:https://doi.org/10.1016/j.artint.2022.103769.

[38] M. E. Tipping. Sparse bayesian learning and the relevance vector machine. 1, 2001. ISSN 1532-4435.

[39] D. Wipf and B. Rao. Sparse bayesian learning for basis selection. *IEEE Transactions on Signal Processing*, 52(8):2153–2164, 2004. doi:10.1109/TSP.2004.831016.

[40] T. Moon. The expectation-maximization algorithm. *IEEE Signal Processing Magazine*, 13(6): 47–60, 1996. doi:10.1109/79.543975.

[41] Y. Ma, R. Garnett, and J. Schneider. Active search for sparse signals with region sensing. *Proceedings of the AAAI Conference on Artificial Intelligence*, 31(1), Feb. 2017.

[42] J. Wang, G. Robinson, and K. White. Generating viewsheds without using sightlines. 66, 01 2000.

[43] S. D. Roth. Ray casting for modeling solids. *Computer Graphics and Image Processing*, 18 (2):109–144, 1982. ISSN 0146-664X. doi:https://doi.org/10.1016/0146-664X(82)90169-1.

[44] M. F. Goodchild and J. Lee. Coverage problems and visibility regions on topographic surfaces. *Annals of Operations Research*, 18(1):175–186, Dec 1989. ISSN 1572-9338. doi:10.1007/BF02097802.

[45] M. R. Travis, G. H. Elsner, W. D. Iverson, and C. G. Johnson. Viewit: computation of seen areas, slope, and aspect for land-use planning. 1975.

[46] P. Fisher. First experiments in viewshed uncertainty: The accuracy of the viewshed area. *Photogrammetric Engineering Remote Sensing*, 57, 01 1991.

[47] P. F. Fisher. Extending the applicability of viewsheds in landscape planning. *Photogrammetric Engineering and Remote Sensing*, 52:1297–1302, 1996.

[48] P. E. Hart, N. J. Nilsson, and B. Raphael. A formal basis for the heuristic determination of minimum cost paths. *IEEE Transactions on Systems Science and Cybernetics*, 4(2):100–107, 1968.