CAD-bench: Benchmarking Language Models on Functional CAD Generation

Dhruv Saini [1]

Abstract

Language-model agents are increasingly able to operate computer-aided design (CAD) toolchains, but current evaluations often measure only executable code, rendered appearance, or coarse geometric similarity. These proxies can miss the properties that matter for reliable artifact-producing agents in engineering settings: exact dimensions, mating interfaces, standards-like details, and functional behavior of assemblies. We introduce CAD-bench, an execution-based benchmark for evaluating language-model CAD agents. CAD-bench contains 17 tasks across four difficulty tiers, ranging from basic solids to threaded mating pairs and functional gear trains. Each submission is executed, exported as geometry, and evaluated with task-specific checks, including dimensional and pose verification, reference-geometry gates, thread-profile analysis, and Blender-based rigid-body simulation. The benchmark supports both one-shot CAD-code generation and agent harnesses that produce final STEP artifacts in an executable environment. Initial results show that CAD-bench is not saturated by current systems. The strongest standalone model reaches 59.9% overall, while functional tasks remain near zero for most standalone runs. Agent harnesses perform better than one-shot generation, but still fail frequently on interfaces, standards-like details, and mechanisms. CAD-bench therefore exposes a gap between producing runnable CAD artifacts and producing CAD artifacts that satisfy mechanically meaningful task requirements, a distinction that is central to evaluating agents intended to operate in real engineering workflows.

[1]Independent Researcher. Correspondence to: Dhruv Saini <dhruv9saini@gmail.com>.

Accepted to the Second Workshop on Agents in the Wild: Safety, Security, and Beyond (AIWILD), ICML 2026, Seoul, South Korea.

1. Introduction

Computer-aided design (CAD) is a central representation for physical product development. CAD artifacts encode not only visible shape, but also dimensions, constraints, features, interfaces, and assemblies that downstream engineering tools use for simulation, inspection, and manufacturing. As language-model agents become more capable of writing code, operating tools, and iterating on execution feedback, CAD generation is becoming a natural target for agentic automation.

Evaluation remains a bottleneck. A generated CAD artifact can compile, render, and resemble a target object while still failing the engineering task. Common errors include shifted poses, incorrect hole placement, missing mating features, invalid thread profiles, gear collisions, or assemblies that cannot transmit motion. These errors determine whether the artifact can be edited, assembled, manufactured, or used. They also illustrate a broader issue for real-world agent evaluation: an agent can succeed at producing an executable intermediate artifact while failing the task-level requirements that motivated the workflow.

Prior CAD-generation benchmarks have established important foundations. SketchGraphs represents CAD sketches as geometric constraint graphs (Seff et al., 2020). CAD-as-Language and DeepCAD model CAD sketches or construction histories as serialized design programs (Ganin et al., 2021; Wu et al., 2021). Fusion 360 Gallery provides human-authored design sequences and a programmatic reconstruction environment (Willis et al., 2021). More recent systems move toward natural-language CAD generation, executable CAD code, or geometric validation. Text2CAD studies text-to-parametric-CAD generation from natural-language prompts (Khan et al., 2024). CADPrompt pairs natural-language CAD prompts with expert CAD code and uses a visual verification loop (Alrashedy et al., 2024). CAD-Coder and Text-to-CadQuery target text-to-CAD-code generation with executable feedback or geometric rewards (Guan et al., 2025; Xie and Ju, 2025). CadEval, CADSmith, and CAD Arena provide related evaluation settings based on rendering, geometry, validity, or programmatic measurement (Epoch AI, 2026; Barkley et al., 2026; CAD Arena, 2026). These benchmarks and systems show that executable geometric feedback is valuable. CAD-bench targets a complementary

question: whether a submitted CAD artifact satisfies mechanically meaningful task requirements, including dimensions, interfaces, threads, and functional assembly behavior.

CAD-bench evaluates complete harnesses rather than a single modeling API or decoding format. A harness receives a task prompt and must produce either CAD code or a STEP artifact. The benchmark then executes the submission, exports geometry where needed, and applies task-specific evaluators. The release includes 17 tasks across four tiers: basic solids, feature-rich parts, standards-like mechanical components, and functional assemblies. The hardest tasks require not only shape synthesis but also interface compatibility and rigid-body function.

The central claim of CAD-bench is that build success is not a sufficient CAD metric. For example, in the reported agent rows, the right-angle gearbox builds in 96.9% of attempts but averages only 4.0% on the full functional score. CAD-bench is designed to distinguish artifacts that merely execute from artifacts that satisfy the dimensional, interface, and functional constraints of the task. This distinction is especially important for language-model agents operating toolchains in engineering environments, where syntactic success can mask task-level functional failure.

Contributions. This paper makes four contributions.

- We introduce CAD-bench, a 17-task executable benchmark for language-model CAD agents, spanning primitive solids, feature-rich parts, standards-like components, threaded mating pairs, and functional transmissions.

- We define a harness protocol that supports both one-shot CAD-code generation and agent-produced STEP submissions, allowing model-only and tool-using systems to be evaluated through a shared artifact interface.

- We develop a task-specific scoring stack that combines build success, dimensional and pose checks, reference-geometry gates, thread-profile analysis, and Blender-based rigid-body simulation.

- We report complete baseline sweeps for standalone models and agent harnesses, together with scorer-validation cases, aggregation-sensitivity checks, repeated-run diagnostics, and reproducibility artifacts.

2. Related Work

CAD-bench builds on CAD generation, engineering-document understanding, and executable agent benchmarks.

CAD generation and CAD code benchmarks. Prior work has developed structured representations and datasets for CAD generation. SketchGraphs represents CAD sketches as geometric constraint graphs (Seff et al., 2020). CAD-as-Language and DeepCAD model CAD sketches or construction histories as serialized design programs (Ganin et al., 2021; Wu et al., 2021). Fusion 360 Gallery provides human-authored design sequences and a programmatic reconstruction environment (Willis et al., 2021).

Recent systems move closer to natural-language CAD generation and executable CAD code. Text2CAD studies text-to-parametric-CAD generation from natural-language prompts (Khan et al., 2024). CADPrompt pairs natural-language CAD prompts with expert CAD code and uses visual verification (Alrashedy et al., 2024). CAD-Coder and Text-to-CadQuery target text-to-CAD-code generation with executable feedback and geometric rewards (Guan et al., 2025; Xie and Ju, 2025).

Several recent benchmarks also emphasize geometric validation. CadEval evaluates text-to-CAD systems using rendering success, Chamfer and Hausdorff distances, and volume or consistency checks (Epoch AI, 2026). CADSmith uses execution repair with programmatic OpenCASCADE measurements and visual judging to refine CadQuery code (Barkley et al., 2026). CAD Arena provides a public comparison grid for prompt-based CAD generation, with reported validity based on executable STL production (CAD Arena, 2026).

These works establish CAD as a structured generation problem and show that executable geometric feedback matters. CAD-bench differs by scoring submitted artifacts against task-level mechanical requirements, including mating interfaces, thread observables, exact pose, and rigid-body function, rather than construction-sequence, rendering, or point-cloud similarity.

Engineering-document understanding. Doris et al. (2024) introduce DesignQA for evaluating multimodal understanding of engineering documentation. That work is complementary to CAD-bench: understanding drawings and manuals is part of the input side of engineering intelligence, while CAD-bench evaluates output-side artifact generation in a runnable CAD environment.

Executable benchmarks for agents. Recent work has shown the value of realistic, environment-grounded evaluation for agents. AgentBench benchmarks agents across multiple interactive environments (Liu et al., 2023). GAIA studies general assistant tasks that require multi-step tool use and reasoning (Mialon et al., 2023). VisualWebArena and OSWorld evaluate agents in realistic web, desktop, and multimodal environments (Koh et al., 2024; Xie et al., 2024). In software engineering, SWE-bench evaluates repository-level issue resolution, while MLE-bench evaluates machine-

learning engineering tasks (Jimenez et al., 2023; Chan et al., 2024). RE-Bench and PaperBench extend this perspective to open-ended research engineering and research replication (Wijk et al., 2024; Starace et al., 2025). CAD-bench adopts the same benchmark philosophy for CAD: models should be evaluated in the artifact-producing environment itself, and agent outputs should be judged by whether the resulting artifacts satisfy task-level requirements.

Benchmark methodology. BetterBench emphasizes best practices such as transparent reporting, replicability, and careful benchmark lifecycle management (Reuel et al., 2024). LiveBench highlights the importance of contamination-resistant evaluation and benchmark refreshes (White et al., 2024). CAD-bench follows these principles through executable scoring, explicit artifact traces, and a design that makes future task refreshes and extensions straightforward.

3. Motivation: Why CAD Agents Need Executable Functional Benchmarks

CAD evaluation requires stronger checks than syntactic validity or visual plausibility. A model can generate valid Python, export a watertight mesh, or render an object with the correct silhouette while still producing the wrong dimensions, pose, feature placement, mating geometry, or assembly behavior. In mechanical design, these local errors are often decisive.

Surface-level geometric similarity is also incomplete. Many CAD tasks are defined by constrained interfaces rather than by global shape alone. A screw head with an incorrect socket, a thread that cannot mate, a gear train that collides, or a gearbox that fails to transmit motion may remain visually plausible under coarse rendering or point-cloud metrics. Such artifacts may look close to a reference but fail the engineering role specified by the prompt.

CAD agents also operate in executable tool environments, where they must synthesize parametric programs, reason over APIs and exchange formats, and satisfy exact toolchain semantics. This makes CAD a useful setting for evaluating agents that act through real software systems: the artifact can be executed, inspected, and scored, but task success depends on engineering observables rather than on execution alone. CAD-bench is therefore designed around task-specific observables rather than visual complexity alone. Visually simple tasks may require exact conventions or mating constraints, while visually complex tasks may be straightforward once decomposed into deterministic features.

Table 1. CAD-bench task taxonomy. Difficulty is authored for benchmark design; as shown later, model difficulty is not strictly monotone in the same order.

Difficulty	Count	Example tasks	Main capability stress
Easy	3	cube, box, ring spacer	pose, units, simple solids
Medium	4	L-bracket, extrusion segment, slotted plate, hex nut blank	feature placement, boolean modeling, conventions
Hard	6	flange, bolted ring, stepped block, large slotted plate, spur gear, M3 socket-head screw	denser geometry, standards-like structure, gears, threads
Functional	4	gearbox, custom threaded pair, compound gearbox, right-angle compound gearbox	assembly reasoning, interface compatibility, rigid-body functionality

4. Benchmark Design and Artifact Construction

4.1. Scope and task taxonomy

CAD-bench contains 17 tasks divided into four difficulty levels: easy, medium, hard, and functional. Table 1 summarizes the task structure.

The benchmark intentionally mixes single-part and multi-part tasks. The early tasks test whether a model can synthesize basic parametric geometry. Middle tasks add feature density and standards-like details. The final tasks require reasoning about interfaces and physical behavior rather than about isolated solids alone.

4.2. Task packaging

Each task is stored as a prompt, metadata, expected values, and evaluator configuration. In the repository, tasks are specified through files such as `prompt.txt`, `task.toml`, and optional reference assets used for reproducibility. The public task format includes reference programs in `gold.py`, but those are benchmark-side reference implementations rather than the definition of the task itself. The expected metadata includes task ID, difficulty, evaluator, and task-specific expected values. Public task payloads can be loaded from a local mirror or from a Hugging Face repository.

This packaging supports two important use cases: exact reproduction of published harness runs and evaluation of custom harnesses against the same task set and scoring logic.

The tasks are synthetic but engineering-grounded: they specify concrete dimensions, poses, mating interfaces, thread conventions, and gearbox behavior that a CAD artifact must satisfy. This construction is intended to make the benchmark sound as an evaluation artifact: the prompts define real CAD outcomes, the metadata records the expected observables, and the evaluators test submitted artifacts rather than checking whether a model reproduced a particular text program.

4.3. Runtime and submission modes

The benchmark runtime supports two submission styles. In one-shot mode, code-oriented harnesses return CAD code inside a structured XML block, with the built-in implementation using Build123D (build123d contributors, 2026). In step-based agent mode, an interactive harness writes the final CAD artifact to a designated STEP path inside the evaluation environment. In both cases, the runtime executes the submission in a containerized workspace and converts the result into a common scoring pipeline.

We report complete standalone model runs separately from complete agent runs. The agent interface remains part of the benchmark runtime, but agent rows are not mixed into the standalone model table because they use interactive tool feedback and a different wall-clock budget.

4.4. Scoring and verification

Each task returns normalized metrics including `build_success`, `task_score`, `overall_score`, and a benchmark-facing reward:

$$\text{reward} = 0.05 \cdot \text{build\_success} + 0.95 \cdot \text{overall\_score} \tag{1}$$

At the benchmark level, CAD-bench first averages task `overall_score` within each difficulty bucket. Missing benchmark tasks are inserted as explicit zero-score rows for result aggregation. The final score is the category-weighted mean

$$S = \frac{1S_{\text{easy}} + 2S_{\text{medium}} + 3S_{\text{hard}} + 4S_{\text{functional}}}{1 + 2 + 3 + 4}. \tag{2}$$

This means a zero on a difficulty bucket remains part of the denominator rather than silently dropping that category from the leaderboard. The 1:2:3:4 weighting is a benchmark-design choice rather than a statistical estimate of task importance. It prevents the 13 static tasks from dominating the four functional tasks, while still reporting every bucket separately. We do not use any aggregation rule for statistically significant pairwise model-ranking claims; Section 7 reports a small aggregation-sensitivity check.

The task evaluators are designed to match engineering reality. The benchmark uses:

- mesh- and part-level dimensional checks,

- pose and placement metrics,

- reference-geometry gates that downweight large deviations from the authored solution,

- thread-specific profile and pitch metrics for the custom threaded-pair task, and

- Blender-based rigid-body simulation for gearbox tasks.

Reference-geometry gates are used only as coarse sanity gates on selected tasks. They compare boolean volume differences between the submitted artifact and the reference artifact, then multiply the task score by a smooth penalty when the submitted shape has large missing or extra volume. The task-specific metrics remain responsible for dimensions, poses, threads, and function. This design allows ordinary alternative CAD construction histories, but intentionally reduces credit for artifacts that satisfy a few scalar checks while omitting major geometry.

This combination is central to the benchmark. A large part of CAD-bench's value is that it measures the difference between "the program ran" and "the artifact solved the task."

4.5. Scorer validation and ablations

Because CAD-bench uses task-specific evaluators, the release includes explicit scorer-calibration cases in `metadata/cad-bench-scorer-validation.json`. These cases cover reference submissions, independently authored valid submissions, minor defects, major defects, and nonbuild submissions across representative easy, hard-static, standards-like, threaded-pair, and functional tasks. Table 2 summarizes the main cases.

The validation cases serve two purposes. First, they test invariance to implementation details by giving full credit to independently authored valid artifacts that are not copies of the corresponding `gold.py` programs. Second, they test sensitivity to engineering-relevant defects. Several defective artifacts build successfully but receive low full scores, which demonstrates why build success alone is an inadequate CAD metric. Generic geometry proxies also over-credit local-but-incomplete artifacts, such as a screw without a socket or a flange without bolt holes. For gearbox tasks, the decisive signal is rigid-body behavior: a rigid bridge with plausible axle holes builds and may have the approximately correct bounding box, but receives zero because it cannot transmit the required motion.

Worked M3 example. The M3 socket-head screw evaluator illustrates the scoring pattern. It first checks pose and dimensions: top of head at $z = 0$, full body in $z \leq 0$, head diameter and height, under-head length, and major

Table 2. Representative scorer-calibration cases. Full is the CAD-bench `overall_score`. Build is a build-success-only ablation. Proxy is the available generic geometry proxy where one exists; gearbox rows are dominated by functional simulation rather than a generic geometry proxy.

Task	Case	Full	Build	Proxy
Cube	independent valid cube	1.000	1.000	1.000
Cube	correct cube shifted off the required pose	0.000	1.000	0.000
Flange	independently constructed valid flange	1.000	1.000	1.000
Flange	bolt circle 1 mm too small	0.800	1.000	0.800
Flange	missing all four bolt holes	0.176	1.000	0.341
M3 screw	independently authored equivalent	1.000	1.000	1.000
M3 screw	threaded screw with missing socket	0.629	1.000	0.723
M3 screw	plain unthreaded shank	0.273	1.000	0.435
Gearbox	reference functional gear pair	0.962	1.000	–
Gearbox	rigid bridge between axle holes	0.000	1.000	–
Gearbox	reference gear pair shifted off axles	0.000	1.000	–
Threaded pair	reference mating threaded pair	0.974	1.000	–
Threaded pair	plausible unthreaded bolt and nut	0.406	1.000	–
Compound gearbox	rigid three-axle bridge	0.000	1.000	–
Right-angle gearbox	intersecting reference-like assembly	0.000	1.000	–

diameter. It then checks contact geometry: socket depth, across-flats estimate, open radius at multiple depths, and six-fold harmonic signal. Finally it checks task-specific thread observables: helical signal, pitch, handedness, and approximate turns-to-seat. The final score is a weighted mean over generic pose, generic dimensions, generic contact, task thread, and task insertion modules. This is why the independently authored equivalent fixture receives full credit, a threaded screw without a socket receives partial credit, and an unthreaded cylinder receives only low residual credit despite building.

5. Experimental Protocol

5.1. Model and harness matrix

The benchmark is intended to support a mixed portfolio of closed and open providers. The result artifact contains 19 complete standalone model sweeps and 32 complete agent rows satisfying the validity criteria in Appendix B.3. Table 3 summarizes these rows, while Appendix B records the exact run identifiers and full row-level results. The standalone model set covers OpenAI, DeepSeek, Gemini, Vercel AI Gateway, and free OpenRouter rows.

The experiments focus on completed full-benchmark runs, meaning sweeps that cover all 17 tasks and reach model output plus benchmark scoring. This choice avoids mixing partially completed campaigns with full evaluations. Provider quota failures, API outages, malformed transport responses, harness setup failures, and upload failures are retained in the provenance artifacts for accounting but excluded from model-quality comparisons because they do not measure the model's CAD capability.

Table 3. Summary of complete CAD-bench baselines. Scores are category-weighted using Eq. (2). Full per-row results and run identifiers are reported in Appendix B.

Setting	Rows	Best overall	Mean easy	Mean hard	Mean fu
Standalone models	19	0.599	0.930	0.585	0.0
Agent harnesses	32	0.677	0.906	0.761	0.1

5.2. Reporting protocol

For each completed run, we report benchmark score, per-difficulty aggregates, wall-clock time, and estimated cost when the harness exposes enough usage and pricing data. When multiple complete runs exist for the same provider, model, access mode, and reasoning level, all complete rows in the result artifact are reported, and the exact run identifiers are recorded in Appendix B. We do not claim statistically significant pairwise rankings.

This choice reflects the state of the experimental log rather than a limitation of the benchmark. CAD-bench stores the artifacts needed for repeated-run reporting, and larger campaigns can replace unreplicated full-sweep rows with repeated-run aggregates.

6. Results: What CAD-bench Reveals

6.1. Overall performance

Table 3 summarizes the complete full-benchmark evaluations in the result artifact. Full leaderboards, run identifiers, wall-clock times, and cost estimates are reported in Appendix B; the main text focuses on aggregate conclusions because many configurations have only one complete sweep.

Three conclusions emerge from the completed rows.

First, CAD-bench is not saturated. The best standalone model reaches 0.599 overall, and the best agent harness reaches 0.677. These scores leave substantial headroom despite high performance on many easy and static tasks.

Second, static geometry is substantially easier than functional CAD. Completed standalone runs average 0.585 on hard-static tasks but only 0.037 on functional tasks. Agent harnesses improve both categories, but the same pattern remains: they average 0.761 on hard-static tasks and 0.141 on functional tasks.

Third, the benchmark distinguishes model and harness settings. Agent harnesses generally outperform standalone one-shot generation, consistent with the hypothesis that execution feedback helps repair dimensional, geometric, and interface errors. However, agent success is uneven, and functional assemblies remain difficult even when submissions build successfully.

The difficulty claim is not based only on the names of the

tiers. Under the same reported artifacts, replacing CAD-bench's full score with weaker proxies would make the benchmark look easier. Reported agent submissions build the right-angle gearbox in 96.9% of attempts but average only 4.0% full score, and standalone submissions build the gearbox task in 63.2% of attempts but average only 6.7% full score. Thus the functional tasks are not merely harder by author label. They expose failures that build success and coarse geometry checks systematically miss.

Because only one complete standalone web-enabled row is available, these results should not be interpreted as a matched web-versus-offline comparison.

6.2. Per-difficulty behavior

Across the 19 reported standalone model sweeps, the mean score by difficulty is 0.930 on easy, 0.753 on medium, 0.585 on hard, and 0.037 on functional tasks. Across the 32 reported agent sweeps, the corresponding means are 0.906, 0.849, 0.761, and 0.141. The large drop on functional tasks is expected. The remaining drop from medium to hard indicates that standards-like details, dense feature placement, and gear/thread structure still matter after simple part synthesis is solved.

In CAD-bench, difficulty labels are benchmark-design labels, not claims about a strict monotone model ordering. Several hard tasks are still static, deterministic solids with many dimensions but little ambiguity, while some lower-level tasks are sensitive to conventions such as exact orientation, alignment, or hole placement. The results therefore reinforce the point that CAD evaluation must be task-specific rather than purely complexity-labeled.

7. Discussion and Limitations

CAD-bench is an evaluation artifact rather than primarily a final model leaderboard. Its main claim is that executable CAD scoring exposes failures that build success, rendering validity, and coarse geometry proxies miss. The reported rows are useful diagnostic baselines, but many configurations have only one full sweep. We therefore avoid statistically significant pairwise model-ranking claims. Repeated-run statistics in Appendix B.2 support the static-versus-functional difficulty contrast for seven standalone configurations, and promoted leaderboard rows require repeated full sweeps under a declared aggregation rule.

The aggregation rule is not driving the main benchmark story. Under the complete result payload, the top standalone row is unchanged under the weighted score, equal bucket averaging, and task-count weighting: Gemini 3.1 Pro offline scores 0.599, 0.727, and 0.709 respectively. For agent rows, weighted and equal-bucket aggregation both put Codex GPT-5.4 mini medium web first, at 0.677 and 0.781; task-count

weighting instead puts Pi GPT-5.4 high offline first at 0.772. The qualitative conclusion is stable: easy/static CAD is much stronger than functional CAD, while fine-grained row ordering remains diagnostic until repeated runs are available.

The benchmark is also small. Seventeen tasks are enough for a high-information initial release that covers primitives, feature placement, standards-like details, threaded interfaces, and simulated mechanisms, but they are not enough to claim broad CAD-agent competence. CAD-bench is therefore versioned. Appendix A describes the lifecycle: immutable public task bundles, private refresh tasks with canary hashes, contamination monitoring, and repeated-run promotion for leaderboard rows.

Task-specific scorers encode engineering assumptions. This is necessary for CAD: a threaded pair, socket-head screw, or gearbox cannot be judged by build success alone. It also creates a risk that a valid alternative solution could miss an authored observable. The scorer-validation cases in Table 2 partially address this by giving full credit to independently authored valid artifacts and low credit to controlled defects, but they are not exhaustive. The intended use of CAD-bench is therefore comparative and diagnostic: inspect per-task traces, scorer components, and validation cases, not only the aggregate score.

8. Conclusion

CAD-bench is an executable benchmark for CAD generation that emphasizes artifact correctness over surface plausibility. CAD-bench v0 shows that models and agent harnesses can often produce runnable CAD, but still fail on standards-like details, mating interfaces, and functional assemblies. The benchmark's main contribution is the scoring interface and reproducible artifact protocol: it separates easy geometry from mechanically meaningful CAD behavior and gives future systems a concrete target for improving assemblies and interfaces that actually work. For language-model agents operating in engineering environments, this distinction is central: a successful agent must not only produce executable artifacts, but artifacts whose task-level mechanical behavior can be verified.

Table 4. Per-task mean `overall_score` and build success across the complete reported rows. Standalone means use 19 model sweeps; agent means use 32 agent sweeps. This table is computed from the 867 task rows in the released result artifact, not from the difficulty aggregates alone.

Difficulty	Task	Standalone score	Standalone build	Agent score	Agent build
Easy	cube	0.895	0.947	0.938	0.969
Easy	box	0.947	1.000	0.844	0.844
Easy	ring spacer	0.947	1.000	0.938	0.938
Medium	L-bracket	0.632	0.842	0.906	0.969
Medium	extrusion	0.868	0.947	0.875	0.875
Medium	slotted plate	0.672	0.947	0.864	0.969
Medium	hex nut blank	0.842	0.895	0.750	0.906
Hard	flange	0.746	0.842	0.906	0.969
Hard	bolted ring	0.789	0.789	0.947	1.000
Hard	stepped block	0.812	0.947	1.000	1.000
Hard	large slotted plate	0.718	0.842	0.853	1.000
Hard	spur gear	0.237	0.526	0.345	0.844
Hard	M3 socket screw	0.207	0.526	0.512	0.875
Functional	gearbox	0.067	0.632	0.316	0.844
Functional	threaded pair	0.012	0.211	0.071	0.938
Functional	compound gearbox	0.069	0.632	0.138	0.719
Functional	right-angle gearbox	0.000	0.158	0.040	0.969

References

Kamel Alrashedy, Pradyumna Tambwekar, Zulfiqar Zaidi, Megan Langwasser, Wei Xu, and Matthew Gombolay. Generating CAD Code with Vision-Language Models for 3D Designs. arXiv:2410.05340, 2024. URL: https://arxiv.org/abs/2410.05340.

Jesse Barkley, Rumi Loghmani, and Amir Barati Farimani. CADSmith: Multi-Agent CAD Generation with Programmatic Geometric Validation. arXiv:2603.26512, 2026. URL: https://arxiv.org/abs/2603.26512.

build123d contributors. build123d documentation. 2026. URL: https://build123d.readthedocs.io/en/stable/index.html.

CAD Arena. CAD Arena: Open Benchmark for AI-Generated Parametric CAD. 2026. URL: https://cadarena.dev/.

Jun Shern Chan, Neil Chowdhury, Oliver Jaffe, James Aung, Dane Sherburn, Evan Mays, Giulio Starace, Kevin Liu, Leon Maksin, Tejal Patwardhan, Lilian Weng, and Aleksander Mądry. MLE-bench: Evaluating Machine Learning Agents on Machine Learning Engineering. arXiv:2410.07095, 2024. URL: https://arxiv.org/abs/2410.07095.

Anna C. Doris, Daniele Grandi, Ryan Tomich, Md Ferdous Alam, Mohammadmehdi Ataei, Hyunmin Cheong, and Faez Ahmed. DesignQA: A Multimodal Benchmark for Evaluating Large Language Models' Understanding of Engineering Documentation. arXiv:2404.07917, 2024. URL: https://arxiv.org/abs/2404.07917.

Epoch AI. CadEval. 2026. URL: https://epoch.ai/benchmarks/cad-eval.

Yaroslav Ganin, Sergey Bartunov, Yujia Li, Ethan Keller, and Stefano Saliceti. Computer-Aided Design as Language. arXiv:2105.02769, 2021. URL: https://arxiv.org/abs/2105.02769.

Yandong Guan, Xilin Wang, Xingxi Ming, Jing Zhang, Dong Xu, and Qian Yu. CAD-Coder: Text-to-CAD Generation with Chain-of-Thought and Geometric Reward. arXiv:2505.19713, 2025. URL: https://arxiv.org/abs/2505.19713.

Mohammad Sadil Khan, Sankalp Sinha, Talha Uddin Sheikh, Didier Stricker, Sk Aziz Ali, and Muhammad Zeshan Afzal. Text2CAD: Generating Sequential CAD Models from Beginner-to-Expert Level Text Prompts. In *Advances in Neural Information Processing Systems*, volume 37, 2024. URL: https://openreview.net/forum?id=5k9XeHIK3L.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can Language Models Resolve Real-World GitHub Issues? arXiv:2310.06770, 2023. URL: https://arxiv.org/abs/2310.06770.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. VisualWebArena: Evaluating Multimodal Agents on Realistic Visual Web Tasks. arXiv:2401.13649, 2024. URL: https://arxiv.org/abs/2401.13649.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. AgentBench: Evaluating LLMs as Agents. arXiv:2308.03688, 2023. URL: https://arxiv.org/abs/2308.03688.

Gregoire Mialon, Clementine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. GAIA: a benchmark for General AI Assistants. arXiv:2311.12983, 2023. URL: https://arxiv.org/abs/2311.12983.

Anka Reuel, Amelia Hardy, Chandler Smith, Max Lamparth, Malcolm Hardy, and Mykel J. Kochenderfer. BetterBench: Assessing AI Benchmarks, Uncovering Issues, and Establishing Best Practices. arXiv:2411.12990, 2024. URL: https://arxiv.org/abs/2411.12990.

Ari Seff, Yaniv Ovadia, Wenda Zhou, and Ryan P. Adams. SketchGraphs: A Large-Scale Dataset for Modeling Relational Geometry in Computer-Aided Design. arXiv:2007.08506, 2020. URL: https://arxiv.org/abs/2007.08506.

Giulio Starace, Oliver Jaffe, Dane Sherburn, James Aung, Jun Shern Chan, Leon Maksin, Rachel Dias, Evan Mays, Benjamin Kinsella, Wyatt Thompson, Johannes Heidecke, Amelia Glaese, and Tejal Patwardhan. Paper-Bench: Evaluating AI's Ability to Replicate AI Research. arXiv:2504.01848, 2025. URL: https://arxiv.org/abs/2504.01848.

Colin White, Samuel Dooley, Manley Roberts, Arka Pal, Ben Feuer, Siddhartha Jain, Ravid Shwartz-Ziv, Neel Jain, Khalid Saifullah, Siddartha Naidu, Chinmay Hegde, Yann LeCun, Tom Goldstein, Willie Neiswanger, and Micah Goldblum. LiveBench: A Challenging, Contamination-Free LLM Benchmark. arXiv:2406.19314, 2024. URL: https://arxiv.org/abs/2406.19314.

Haoyang Xie and Feng Ju. Text-to-CadQuery: A New Paradigm for CAD Generation with Scalable Large Model Capabilities. arXiv:2505.06507, 2025. URL: https://arxiv.org/abs/2505.06507.

Karl D. D. Willis, Yewen Pu, Jieliang Luo, Hang Chu, Tao Du, Joseph G. Lambourne, Armando Solar-Lezama, and Wojciech Matusik. Fusion 360 Gallery: A Dataset and Environment for Programmatic CAD Construction from Human Design Sequences. *ACM Transactions on Graphics*, 40(4), 2021. URL: https://arxiv.org/abs/2010.02392.

Hjalmar Wijk, Tao Lin, Joel Becker, Sami Jawhar, Neev Parikh, Thomas Broadley, Lawrence Chan, Michael Chen, Josh Clymer, Jai Dhyani, Elena Ericheva, Katharyn Garcia, Brian Goodrich, Nikola Jurkovic, Megan Kinniment, Aron Lajko, Seraphina Nix, Lucas Sato, William Saunders, Maksym Taran, Ben West, and Elizabeth Barnes. RE-Bench: Evaluating frontier AI R&D capabilities of language model agents against human experts. arXiv:2411.15114, 2024. URL: https://arxiv.org/abs/2411.15114.

Rundi Wu, Chang Xiao, and Changxi Zheng. DeepCAD: A Deep Generative Network for Computer-Aided Design Models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021. URL: https://arxiv.org/abs/2105.09492.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments. arXiv:2404.07972, 2024. URL: https://arxiv.org/abs/2404.07972.

A. Benchmark lifecycle and broader impacts

The artifact is designed to support a versioned benchmark lifecycle rather than a single frozen leaderboard. CAD-bench v0 is a public, reproducible task set with exact run artifacts. The benchmark lifecycle uses four controls.

- **Frozen public splits.** Published task bundles are immutable and identified by manifest hashes and dataset revisions.

- **Private refresh tasks.** New functional and standards-like tasks can be staged privately, with salted bundle-hash canaries exported before evaluation to establish that the tasks existed before result collection.

- **Versioned leaderboards.** Rows are reported against an explicit task-set version; old rows are not silently mixed with refreshed tasks.

- **Repeated-run promotion.** A configuration moves from diagnostic reporting to a primary leaderboard row only after independent full sweeps are available with a declared aggregation rule.

The release files reflect this lifecycle: task manifests record per-file hashes, the release pins the task dataset revision, and the source artifact contains a canary-export command for private or unreleased tasks. The v0 rows are diagnostic rows, so the empirical claims are framed around benchmark behavior and failure modes rather than statistically significant pairwise model rankings.

CAD agents could provide several benefits: lowering the barrier to prototyping, supporting accessibility-focused device customization, improving engineering education, and reducing repetitive modeling work in low-volume manufacturing workflows.

The same capabilities also create risks. More capable CAD generation could accelerate the design of unsafe hardware, restricted components, or deceptive engineering artifacts. It may also encourage overtrust in automatically generated mechanical designs that have not received appropriate engineering review. Transparent, function-aware benchmarking is one mitigation: it makes it harder to confuse runnable CAD code with mechanically correct design.

B. Reproducibility and Reporting Details

B.1. Raw complete result rows

Tables 5–7 record the exact complete rows summarized in Table 3. Scores are reported as percentages for readability. The run column is the run identifier corresponding to the stored report artifact. Partial runs and infrastructure-failed rows are excluded from model-quality comparisons.

Table 5. Raw complete standalone model rows.

Rank	Harness	Overall	Easy	Med.	Hard	Func.	Min.	Cost	Run
1	gemini/gemini-3.1-pro-preview-offline-none	59.9	100.0	96.8	70.8	23.2	25.4	5.8625	gemini__gemini-3.1-pro-preview-offline-none_ 20260428T194054Z_2313253
2	openai/gpt-5.4-pro-web-med	53.9	100.0	96.8	78.5	2.5	325.7	37.0405	openai__gpt-5.4-pro-web-med_20260423T122643Z_ 1626647
3	vercel/alibaba/qwen-3.6-max-preview-offline-none	52.8	100.0	96.8	76.2	1.5	42.8	3.2293	vercel__alibaba__qwen-3.6-max-preview-offline-none_20260430T003706Z_2473332
4	gemini/gemini-3-flash-preview-offline-none	52.6	100.0	96.8	77.4	0.0	21.1	1.3596	gemini__gemini-3-flash-preview-offline-none_ 20260428T121645Z_2280737
5	openrouter/tencent/hy3-preview:free-offline-none	51.1	100.0	96.8	60.8	8.7	51.4	–	openrouter__tencent__hy3-preview_free-offline-none_20260428T035110Z_2240039
6	openai/gpt-5.3-codex-spark-offline-med	50.4	100.0	96.8	70.0	0.0	6.1	4.9685	openai__gpt-5.3-codex-spark-offline-med_ 20260427T023421Z_2115684
7	vercel/alibaba/qwen3.6-27b-offline-none	50.0	100.0	96.8	68.9	0.0	58.6	1.5128	vercel__alibaba__qwen3.6-27b-offline-none_ 20260430T003707Z_2473345
8	openai/gpt-5.3-codex-spark-offline-xhigh	48.9	100.0	96.8	65.0	0.0	6.0	5.4877	openai__gpt-5.3-codex-spark-offline-xhigh_ 20260427T024838Z_2122296
9	openai/gpt-5.5-offline-med	48.7	100.0	71.8	65.0	12.0	9.8	8.6697	openai_codex__gpt-5.5-offline-med_ 20260426T055852Z_2010916
10	openai/gpt-5.5-offline-low	47.5	100.0	71.8	76.3	0.6	10.1	9.7384	openai_codex__gpt-5.5-offline-low_ 20260426T054800Z_2000292
11	deepseek/deepseek-v4-pro-offline-none	47.5	100.0	59.4	68.0	12.9	55.7	3.6274	deepseek__deepseek-v4-pro-offline-none_ 20260426T042645Z_1958729
12	openai/gpt-5.5-offline-high	45.6	66.7	71.8	82.1	0.0	8.9	7.8075	openai_codex__gpt-5.5-offline-high_ 20260426T061252Z_2019625
13	openai/gpt-5.5-offline-xhigh	45.6	100.0	71.8	59.3	8.7	9.9	9.2523	openai_codex__gpt-5.5-offline-xhigh_ 20260426T062226Z_2023449
14	openai/gpt-5.3-codex-spark-offline-high	40.4	100.0	96.8	36.9	0.0	6.1	5.2469	openai__gpt-5.3-codex-spark-offline-high_ 20260427T024046Z_2118961
15	deepseek/deepseek-v4-flash-offline-none	39.5	100.0	64.3	55.5	0.0	18.1	0.2778	deepseek__deepseek-v4-flash-offline-none_ 20260426T052907Z_1985868
16	gemini/gemini-3.1-flash-lite-preview-offline-none	34.2	100.0	75.0	30.8	0.0	19.2	0.1993	gemini__gemini-3.1-flash-lite-preview-offline-none_20260428T050032Z_2249465
17	openai/gpt-5.3-codex-spark-offline-low	33.9	100.0	71.8	31.7	0.0	5.8	4.2688	openai__gpt-5.3-codex-spark-offline-low_ 20260427T022715Z_2111735
18	openrouter/inclusionai/ling-2.6-1t:free-offline-none	13.9	33.3	2.7	33.3	0.0	12.8	–	openrouter__inclusionai__ling-2.6-1t_free-offline-none_20260428T033043Z_2234914
19	gemini/gemma-3-27b-it-offline_nodocs-none	8.1	66.7	0.0	4.6	0.0	3.7	–	gemini__gemma-3-27b-it-offline_nodocs-none_ 20260430T022138Z_2493048

B.2. Repeated-run statistical check

The result set reports complete full 17-task sweeps for every row, but many configurations have only one independent sweep. Those rows are therefore not used for pairwise model-ranking significance claims. To test the main qualitative difficulty claim under repeated sampling, the source artifact includes 47 complete local reports, with repeated full-sweep statistics for seven standalone configurations, summarized in metadata/cad-bench-repeat-stats.json. Additional attempted repeats across the reported standalone and agent matrix were excluded when provider quota, authentication, unavailable-model, or timeout failures prevented a complete 17-task report.

Across six openai/gpt-5.3-codex-spark-offline-med sweeps, the benchmark score is 0.471 with bootstrap 95% CI $[0.453, 0.490]$. The easy bucket is stable at 1.000, medium is 0.973 with CI $[0.968, 0.984]$, hard is 0.572 with CI $[0.507, 0.643]$, and functional is 0.011 with CI $[0.000, 0.033]$. A paired exact two-sided sign-flip test over full-sweep difficulty aggregates gives $p = 0.03125$ for hard score minus functional score, with mean difference 0.561 and bootstrap 95% CI $[0.486, 0.641]$.

Across the four six-sweep openai/gpt-5.5-offline-* repeated checks, benchmark means are 0.477 for low with CI $[0.455, 0.492]$, 0.444 for medium with CI $[0.391, 0.503]$, 0.505 for high with CI $[0.454, 0.563]$, and 0.573 for xhigh with CI $[0.528, 0.612]$. Their hard-minus-functional mean differences are 0.701, 0.483, 0.695, and 0.694, respectively, and each exact sign-flip test gives $p = 0.03125$. The xhigh row has the strongest repeated GPT-5.5 mean here, but these runs still support only a within-configuration static-versus-functional difficulty contrast, not a statistically significant model-ranking claim.

Across six openrouter/tencent/hy3-preview:free-offline- sweeps, the benchmark score is 0.518 with CI $[0.471, 0.557]$; easy is 1.000, medium is 0.823 with CI $[0.729, 0.917]$, hard is 0.664 with CI $[0.585, 0.737]$, and functional is 0.135 with CI $[0.095, 0.176]$. The hard-minus-functional sign-flip test gives $p = 0.03125$, mean difference 0.529, and CI $[0.472, 0.594]$. Across five openrouter/inclusionai/ling-2.6-1t:free-offline-non sweeps, the benchmark score is 0.154 with CI $[0.080, 0.236]$; hard-minus-functional remains positive at 0.227 with CI $[0.084, 0.407]$, but the exact sign-flip test is $p = 0.125$ at $n = 5$. These repeated-run checks support the paper's main diagnostic claim that functional CAD remains much harder than static CAD for multiple standalone harnesses, while leaving the model-level ranking tables as diagnostic baselines rather than statistically significant pairwise comparisons.

Table 6. Raw complete agent rows.

Rank	Agent	Harness	Overall	Easy	Med.	Hard	Func.	Min.	Cost	Run
1	Codex	codex/gpt-5.4-mini-web-med	67.7	100.0	96.8	78.7	36.8	234.0	2.4446	codex__gpt-5.4-mini-web-med_20260420T000623Z_676664
2	Pi	pi/gpt-5.4-offline-high	67.1	100.0	96.8	82.9	32.1	618.8	4.6416	pi__gpt-5.4-offline-high_20260422T092300Z_1340452
3	Codex	codex/gpt-5.4-offline-high	65.3	66.7	71.8	83.6	47.9	245.2	8.2311	codex__gpt-5.4-offline-high_20260419T190624Z_603644
4	Pi	pi/gpt-5.4-offline-xhigh	64.7	100.0	96.8	88.0	22.3	418.3	4.8298	pi__gpt-5.4-offline-xhigh_20260421T075050Z_1041869
5	Pi	pi/gpt-5.4-web-high	64.6	100.0	96.8	82.9	25.9	281.6	4.5650	pi__gpt-5.4-web-high_20260422T092300Z_1340450
6	Pi	pi/gpt-5.4-mini-web-xhigh	61.0	100.0	100.0	84.5	14.2	240.2	2.4442	pi__gpt-5.4-mini-web-xhigh_20260422T092301Z_1340454
7	Pi	pi/gpt-5.4-mini-offline-high	60.3	100.0	75.0	80.3	28.0	169.0	3.5843	pi__gpt-5.4-mini-offline-high_20260422T151655Z_1441926
8	Pi	pi/gpt-5.4-offline-med	59.9	100.0	96.8	76.2	19.3	304.2	1.9074	pi__gpt-5.4-offline-med_20260421T075052Z_1041872
9	Codex	codex/gpt-5.4-web-low	59.1	100.0	96.8	79.4	14.8	279.8	6.3453	codex__gpt-5.4-web-low_20260419T190502Z_603630
10	Codex	codex/gpt-5.4-web-med	59.1	100.0	71.8	78.0	28.2	260.7	5.7144	codex__gpt-5.4-web-med_20260419T190540Z_603629
11	Pi	pi/gpt-5.4-mini-offline-xhigh	59.0	100.0	96.8	83.5	11.4	282.4	3.4776	pi__gpt-5.4-mini-offline-xhigh_20260422T121627Z_1402824
12	Codex	codex/gpt-5.4-mini-offline-med	57.8	100.0	96.8	52.5	31.7	157.2	3.3316	codex__gpt-5.4-mini-offline-med_20260420T004107Z_683812
13	Codex	codex/gpt-5.4-web-xhigh	56.9	100.0	96.8	89.7	1.7	396.2	12.7137	codex__gpt-5.4-web-xhigh_20260421T075051Z_1041874
14	Codex	codex/gpt-5.4-mini-offline-xhigh	56.9	100.0	96.8	77.8	10.5	120.9	4.0830	codex__gpt-5.4-mini-offline-xhigh_20260422T205507Z_1497871
15	Pi	pi/gpt-5.4-web-xhigh	56.0	100.0	71.8	82.9	16.9	419.3	4.7572	pi__gpt-5.4-web-xhigh_20260421T075052Z_1041870
16	Pi	pi/gpt-5.4-mini-web-med	54.5	100.0	96.8	81.8	1.5	191.2	1.6381	pi__gpt-5.4-mini-web-med_20260422T092300Z_1340457

The repeated-run artifact also includes the `metadata/cad-bench-repeat-check.json` two-run sanity record for traceability. Repeated-sweep reports use the following format:

- number of independent full sweeps per configuration,

- central estimate (mean or median),

- uncertainty interval (e.g., standard deviation or bootstrap 95% CI),

- policy for selecting primary leaderboard rows when multiple repetitions exist.

The analysis therefore avoids pairwise significance claims and uses the complete sweeps as baseline diagnostics.

B.3. Run validity criteria

A run is eligible for a complete-results table if it satisfies all of the following conditions:

- it uses a standalone model harness or an agent harness,

- it attempts the full 17-task benchmark under one fixed provider, model, access mode, and reasoning setting,

- each task reaches model-output capture, STEP export when applicable, and benchmark scoring, and

- failures, if any, are model-output or scored-artifact failures rather than provider quota, API outage, harness setup, or artifact-upload failures.

Provider and infrastructure failures are retained in the experiment logs for auditability, but they are not assigned model-quality scores because they do not evaluate the submitted model on CAD generation.

B.4. Compute and environment reporting

The benchmark runtime uses Dockerized environments, Python 3.11, NumPy, trimesh, and Blender for the functional simulation tasks, together with Build123D in the code-oriented reference and harness pipeline. The reported local runs used the following environment:

- host hardware: Intel Core i5-7300U CPU, 15 GiB RAM, CPU-only scoring except for Blender's local simulation/rendering stack,

- software versions: Docker 29.4.0, Blender 5.1.1, uv 0.11.7, project Python 3.11 environment from `uv.lock`,

- standalone model wall-clock range in the reported rows: 3.7–325.7 minutes,

- agent wall-clock range in the reported rows: 65.1–618.8 minutes,

- failed-run accounting: provider quota failures are kept in logs but excluded from model-quality comparisons.

B.5. Code, data, and asset availability

The benchmark runtime, scoring code, and harness interface are available in the source artifact. Public task payloads and result artifacts include every complete run reported in this manuscript.

Table 7. Raw complete agent rows, continued.

Rank	Agent	Harness	Overall	Easy	Med.	Hard	Func.	Min.	Cost	Run
17	Pi	pi/gpt-5.4-mini-web-high	54.0	100.0	96.8	75.7	4.7	130.5	2.5139	pi__gpt-5.4-mini-web-high_20260422T183318Z_ 1468372
18	Codex	codex/gpt-5.4-mini-web-high	53.8	100.0	96.8	78.3	2.3	389.9	3.6274	codex__gpt-5.4-mini-web-high_20260420T235625Z_ 845623
19	Codex	codex/gpt-5.4-offline-xhigh	53.5	33.3	71.8	76.2	32.3	289.6	11.4765	codex__gpt-5.4-offline-xhigh_20260419T190535Z_ 603631
20	Pi	pi/gpt-5.4-offline-low	53.3	100.0	75.0	84.4	7.6	171.2	1.5744	pi__gpt-5.4-offline-low_20260419T061026Z_383966
21	Pi	pi/gpt-5.4-web-med	53.0	100.0	71.8	80.1	11.6	366.2	2.1871	pi__gpt-5.4-web-med_20260421T075053Z_1041868
22	Pi	pi/gpt-5.4-web-low	52.6	100.0	96.8	76.2	0.9	65.1	1.1919	pi__gpt-5.4-web-low_20260422T205357Z_1497569
23	Codex	codex/gpt-5.4-web-high	52.1	66.7	96.8	80.1	5.0	300.5	7.9083	codex__gpt-5.4-web-high_20260419T190546Z_603612
24	Codex	codex/gpt-5.4-mini-offline-high	51.3	100.0	96.8	71.1	1.5	169.1	4.4820	codex__gpt-5.4-mini-offline-high_ 20260420T004018Z_683339
25	Codex	codex/gpt-5.4-mini-web-xhigh	51.1	100.0	71.8	86.9	1.6	416.0	5.9764	codex__gpt-5.4-mini-web-xhigh_20260421T075051Z_ 1041875
26	Pi	pi/gpt-5.4-mini-offline-med	49.7	100.0	96.8	64.5	2.4	241.8	2.4102	pi__gpt-5.4-mini-offline-med_20260422T094713Z_ 1351194
27	Pi	pi/gpt-5.4-mini-web-low	48.1	100.0	75.0	77.1	0.0	189.4	0.5317	pi__gpt-5.4-mini-web-low_20260419T064631Z_ 413438
28	Codex	codex/gpt-5.4-mini-offline-low	48.1	100.0	100.0	57.5	2.2	111.3	1.6688	codex__gpt-5.4-mini-offline-low_ 20260420T014421Z_709021
29	Codex	codex/gpt-5.4-offline-low	46.8	33.3	46.8	88.4	18.9	181.1	4.4749	codex__gpt-5.4-offline-low_20260419T190806Z_ 603646
30	Pi	pi/gpt-5.4-mini-offline-low	37.9	100.0	71.8	38.5	4.9	132.1	0.5499	pi__gpt-5.4-mini-offline-low_20260422T100629Z_ 1359611
31	Codex	codex/gpt-5.4-offline-med	36.2	33.3	46.8	61.6	12.6	260.4	8.0969	codex__gpt-5.4-offline-med_20260419T190604Z_ 603645
32	Codex	codex/gpt-5.4-mini-web-low	32.9	66.7	50.0	54.1	0.0	246.5	1.8227	codex__gpt-5.4-mini-web-low_20260420T000933Z_ 677450

The artifact includes a no-API smoke path for package integrity and scorer calibration. Full model sweeps require provider credentials, but scorer validation and artifact consistency do not.

The release pointers are:

- task dataset revision: `20ad0b586b70ac2c5e6fe2b501386cf26a887137`,

- result artifact: `results/cad-bench-reported-results.json`,

- scorer validation artifact: `results/cad-bench-scorer-validation.json`,

- run artifact bundles: `provenance/<run-id>/report.json`.

The artifact includes Croissant metadata with Responsible AI fields describing intended use, limitations, task authoring, and safety-relevant non-use cases.

B.6. Licenses and upstream assets

Table 8 documents the main upstream software and data assets used by the benchmark runtime and dataset.

The benchmark tasks and authored fixtures are synthetic benchmark assets rather than redistributed proprietary CAD files.

Table 8. Primary upstream software assets used by CAD-bench.

Asset	License / terms	Role in benchmark
Build123D	Apache-2.0	reference implementation and code-harness dependency, not the benchmark definition itself
Blender	GNU GPL	rigid-body simulation and rendering for functional gearbox evaluation
NumPy	BSD-style license	numeric processing in evaluators and utilities
trimesh	MIT	mesh conversion and geometric analysis
Repository code	MIT	benchmark runtime, harnesses, and scoring stack
Public task dataset	MIT	hosted task prompts, metadata, reference programs, and authored benchmark assets
Authored CAD fixtures	MIT	synthetic task-side fixtures, including the M3 socket-head screw equivalent fixture
Closed model APIs	provider terms	external inference services used for benchmarked models