DELTA: DEBIASED FULLY TEST-TIME ADAPTATION

ABSTRACT

Fully test-time adaptation aims at adapting a pre-trained model to the test stream during real-time inference, which is urgently required when the test distribution differs from the training distribution. Several efforts have been devoted to improving adaptation performance. However, we find that two unfavorable biases are concealed in the prevalent adaptation methodologies like test-time batch normalization (BN) and self-learning. First, we reveal that the normalization statistics in test-time BN are inherently biased in favor of currently received test samples. Second, we show that during test-time adaptation, the parameter update is biased towards some dominant classes. In addition to the extensively studied IID test stream, we further observe that the biases can be exacerbated in more complicated test environments, such as non-IID or class-imbalanced data. In this paper, we provide a plug-in solution called DELTA for debiased fully test-time adaptation, which consists of two components: (i) Test-time batch renormalization (TBR), introduced to alleviate the bias in normalization statistics. (ii) Dynamic online re-weighting (DOT), designed to address the class bias within optimization. We investigate various test-time adaptation methods on three commonly used datasets and four scenarios. Previous approaches only work well in certain scenarios while failing in others; DELTA can help them deal with all scenarios simultaneously, leading to new state-of-the-art test-time adaptation performance.

1 INTRODUCTION

Models suffer from performance degradation when test and training distributions are mismatched (Quinonero-Candela et al., 2008). Numerous studies have been conducted to narrow the performance gap based on a variety of hypotheses/settings. Unsupervised domain adaptation methods (Ganin et al., 2016) necessitate simultaneous access to labeled training data and unlabeled target data, limiting their applications. Source-free domain adaptation approaches (Liang et al., 2020) only need a trained model and do not require original training data when performing adaptation. Nonetheless, in a more difficult and realistic setting, known as fully test-time adaptation (Wang et al., 2021), the model must perform online adaptation to the test stream in real-time inference. The model is adapted in a single pass on the test stream using a pre-trained model and continuously arriving test data (rather than a prepared target set). Offline iterative training or extra heavy computational burdens beyond normal inference do not meet the requirements.

There have been several studies aimed at fully test-time adaptation. Test-time BN (Nado et al., 2020) / BN adapt (Schneider et al., 2020) directly uses the normalization statistics derived from test samples instead of those inherited from the training data, which is found to be beneficial in reducing the performance gap. Entropy-minimization-based methods, such as TENT (Wang et al., 2021), further optimize model parameters during inference. Contrastive learning (Chen et al., 2022), data augmentation (Wang et al., 2022a) and uncertainty-aware optimization (Niu et al., 2022) have been introduced to enhance adaptation performance. Efforts have also been made to address test-time adaptation in more complex test environments, like LAME (Boudiaf et al., 2022).

Despite the achieved progress, we find that there are non-negligible biases hidden in the popular methods. First, we take a closer look at the normalization statistics within inference (Section 3.2). We observe that the statistics used in BN adapt are far from the actual population statistics, due to the small sample size of test mini-batches. Second, we reveal that there is a category bias during model updating using the prevalent entropy minimization principle or pseudo-labeling (Section 3.3). We notice that the model predictions are extremely imbalanced on the mismatched distribution,

IID

non-IID

CI

CI & non-IID

test stream of batches   different classes

Figure 1: IID / non-IID: the test stream which is independently / non-independently sampled from a class-balanced distribution; CI / CI & non-IID: independently / non-independently drawn from a class-imbalanced distribution.

Table 1: Comparison of fully test-time adaptation methods against the pre-trained model on CIFAR100-C. DELTA achieves improvement in all scenarios.

Scenario	TENT	LAME	DELTA (Ours)
IID	⬆	⬇	⬆
non-IID	⬇	⬆	⬆
CI	⬆	⬇	⬆
CI & non-IID	⬇	⬆	⬆

which is exacerbated by the self-learning-based adaptation methods. Besides the most common IID scenario considered in existing studies, following Boudiaf et al. (2022), we investigate other three test scenarios as illustrated in Figure 1 (please see details in Section 3.1) and find that the more intricate test streams, like non-IID or class-imbalanced (CI) data, would lead to more severe biases. These biases limit the usefulness of existing test-time adaptation strategies.

To address the aforementioned biases, we propose a powerful method named DELTA. Specifically, to handle the bias in normalization statistics, we introduce test-time batch renormalization (TBR) (Section 3.2), which uses the test-time moving averaged statistics to rectify the normalized features and considers normalization during gradient optimization. By taking advantage of the observed test samples, the calibrated normalization is less biased. We further propose dynamic online re-weighting (DOT) (Section 3.3) to tackle the category bias, which is derived from cost-sensitive learning. To balance adaptation, DOT assigns low/high weights to the dominant/underrepresented categories. The weight mapping function is based on a momentum-updated class-frequency vector that takes into account multiple sources of category bias, including the pre-trained model, the test stream, and the adaptation methods. TBR can be applied directly to the common BN-based pre-trained models and does not interfere with the training process (corresponding to the fully test-time adaptation setting), and DOT can be easily combined with other adaptation approaches as well.

The existing test-time adaptation methods behave differently across the four scenarios, as we observe. While DELTA performs well in all four scenarios at the same time without any prior knowledge of the test data, which is important for real-world applications. Table 1 compares our method to others on CIFAR100-C (Hendrycks & Dietterich, 2019) across various scenarios.

The major contributions of our work are as follows. **(i)** We expose biases in commonly used test-time adaptation methods, which ultimately harm adaptation performance. **(ii)** We demonstrate that the biases will be even more severe in complex test environments, causing the adaptation methods to fail completely. **(iii)** To achieve debiased fully test-time adaptation, we propose DELTA which comprises two components: TBR and DOT, to mitigate biases in normalization statistics and optimization. **(iv)** We evaluate DELTA on three datasets and four scenarios, and find that it can consistently improve the performance of popular test-time adaptation methods on all scenarios, yielding new state-of-the-art results.

2 RELATED WORK

Unsupervised domain adaptation (UDA). In reality, the test distribution is frequently inconsistent with the training distribution, resulting in performance degradation. UDA aims to alleviate degradation with the collected unlabeled samples from the target distribution. One popular approach is to align the statistical moments across different distributions (Gretton et al., 2006; Zellinger et al., 2017; Long et al., 2017). Another line of studies adopts adversarial training to achieve adaptation (Ganin et al., 2016; Long et al., 2018). UDA has been developed for a variety of tasks including object classification (Saito et al., 2017)/detection (Li et al., 2021) and semantic segmentation (Hoffman et al., 2018).

Source-free domain adaptation (SFDA). SFDA deals with domain gap with only the trained model and the prepared unlabeled target data. To be more widely used, SFDA methods should be built on a common source model trained by a standard pipeline. SHOT (Liang et al., 2020) freezes the source model's classifier and optimizes the feature extractor via entropy minimization, diversity regularization, and pseudo-labeling. While SHOT incorporates weight normalization, 1D BN, and

label-smoothing into common backbones and training pipelines, its application may be limited. USFDA (Kundu et al., 2020) utilizes synthesized samples to achieve compact decision boundaries. NRC (Yang et al., 2021b) encourages label consistency among local target features with the same network architecture as SHOT. GSFDA (Yang et al., 2021a) further expects the adapted model performs well not only on target data but also on source data.

Fully test-time adaptation (FTTA). FTTA is a more difficult and realistic setting. In the same way that SFDA does not provide the source training data, only the trained model is provided. Unlike SFDA, FTTA cannot access the entire target dataset; however, the methods should be capable of doing online adaptation on the test stream and providing instant predictions for the arrived test samples. BN adapt (Nado et al., 2020; Schneider et al., 2020) replaces the normalization statistics estimated during training with those derived from the test mini-batch. On top of it, TENT (Wang et al., 2021) optimizes the affine parameters in BN through entropy minimization during test. EATA (Niu et al., 2022) and CoTTA (Wang et al., 2022a) study long-term test-time adaptation in continually changing environments. ETA (Niu et al., 2022) excludes unreliable and redundant samples from the optimization. AdaContrast (Chen et al., 2022) resorts to contrastive learning to promote feature learning along with a pseudo label refinement mechanism. Both AdaContrast and CoTTA utilize heavy data augmentation during test, which will increase inference latency. Besides, AdaContrast modifies the model architecture as in SHOT. Different from them, LAME (Boudiaf et al., 2022) is a relatively "conservative" method, which does not rectify the model's parameters but only the model's output.

Class-imbalanced learning. Training with class-imbalanced data has attracted widespread attention (Liu et al., 2019). Cost-sensitive learning (Elkan, 2001) and resampling (Wang et al., 2020) are the classical strategies to handle this problem. Ren et al. (2018) designs a meta-learning paradigm to assign weights to samples. Class-balanced loss (Cui et al., 2019) uses the effective number of samples when performing re-weighting. Decoupled training (Kang et al., 2020b) learns the feature extractor and the classifier separately. Menon et al. (2021) propose logit adjustment from a statistical perspective. Other techniques such as weight balancing (Alshammari et al., 2022; Zhao et al., 2020), contrastive learning (Kang et al., 2020a), knowledge distillation (He et al., 2021), *etc.* have also been applied to solve this problem.

3 DELTA: DEBIASED FULLY TEST-TIME ADAPTATION

3.1 PROBLEM DEFINITION

Assume that we have the training data $\mathcal{D}^{\text{train}} = \{(x_i, y_i)\}_{i=1}^{N^{\text{train}}} \sim P^{\text{train}}(x, y)$, where $x \in \mathcal{X}$ is the input and $y \in \mathcal{Y} = \{1, 2, \cdots, K\}$ is the target label; $f_{\{\theta_0, a_0\}}$ denotes the model with parameters θ_0 and normalization statistics a_0 learned or estimated on $\mathcal{D}^{\text{train}}$. Without loss of generality, we denote the test stream as $\mathcal{D}^{\text{test}} = \{(x_j, y_j)\}_{j=1}^{N^{\text{test}}} \sim P^{\text{test}}(x, y)$, where $\{y_j\}$ are not available actually, the subscript j also indicates the sample position within the test stream. When $P^{\text{test}}(x, y) \neq P^{\text{train}}(x, y)$ (the input/output space $\mathcal{X}/\mathcal{Y}$ is consistent between training and test data), $f_{\{\theta_0, a_0\}}$ may perform poorly on $\mathcal{D}^{\text{test}}$. Under fully test-time adaptation scheme (Wang et al., 2021), during inference step $t \geq 1$, the model $f_{\{\theta_{t-1}, a_{t-1}\}}$ receives a mini-batch of test data $\{x_{m_t+b}\}_{b=1}^{B}$ with B batch size (m_t is the number of test samples observed before inference step t), and then elevates itself to $f_{\{\theta_t, a_t\}}$ based on current test mini-batch and outputs the real-time predictions $\{p_{m_t+b}\}_{b=1}^{B}$ ($p \in \mathbb{R}^K$). Finally, the evaluation metric is calculated based on the online predictions from each inference step. Fully test-time adaptation emphasizes performing adaptation during real-time inference entirely, *i.e.*, the training process cannot be interrupted, the training data is no longer available during test, and the adaptation should be accomplished in a single pass over the test stream.

The most common hypothesis is that $\mathcal{D}^{\text{test}}$ is independently sampled from $P^{\text{test}}(x, y)$. However, in real environment, the assumption does not always hold, *e.g.*, samples of some classes may appear more frequently in a certain period of time, leading to another hypothesis: $\mathcal{D}^{\text{test}}$ is non-independently drawn from $P^{\text{test}}(x, y)$ (Boudiaf et al., 2022). By decomposing the joint distributions, we have $P^{\text{train}}(x|y) \, P^{\text{train}}(y) \neq P^{\text{test}}(x|y) \, P^{\text{test}}(y)$, implying there are two possible factors causing the distribution shift: $P^{\text{train}}(x|y) \neq P^{\text{test}}(x|y)$ and $P^{\text{train}}(y) \neq P^{\text{test}}(y)$. Most studies only considered scenarios with the former factor while ignoring the latter one, *e.g.*, a corrupted test set with the same class distribution as during training. We investigate and eliminate biases within fully test-time adaptation under the four scenarios below, taking into account the various latent sampling strategies

and distribution shift types. For convenience, we denote the test stream drawn independently/non-independently from P^{test} with $P^{\text{train}}(x|y) \neq P^{\text{test}}(x|y)$ and $P^{\text{train}}(y) = P^{\text{test}}(y)$ as IID scenario / non-IID scenario; denote the test stream sampled independently/non-independently from P^{test} with both $P^{\text{train}}(x|y) \neq P^{\text{test}}(x|y)$ and $P^{\text{train}}(y) \neq P^{\text{test}}(y)$ as CI scenario / CI & non-IID scenario, as shown in Figure 1.

3.2 A CLOSER LOOK AT NORMALIZATION STATISTICS

We revisit BN (Ioffe & Szegedy, 2015) briefly. Let $v \in \mathbb{R}^{B \times C \times S \times S'}$ be a mini-batch of features with C channels, height S and width S'. BN normalizes v with the normalization statistics $\mu, \sigma \in \mathbb{R}^C$: $v^* = \frac{v-\mu}{\sigma}, v^\star = \gamma \cdot v^* + \beta$, where $\gamma, \beta \in \mathbb{R}^C$ are the learnable affine parameters, $\{\gamma, \beta\} \subset \theta$. We mainly focus on the first part $v \rightarrow v^*$. In BN, during training, μ, σ are set to the empirical mean μ^{batch} and standard deviation σ^{batch} calculated for each channel c: $\mu^{\text{batch}}[c] = \frac{1}{BSS'} \sum_{b,s,s'} v[b, c, s, s']$, $\sigma^{\text{batch}}[c] = \sqrt{\frac{1}{BSS'} \sum_{b,s,s'} (v[b, c, s, s'] - \mu^{\text{batch}}[c])^2 + \epsilon}$. During inference, μ, σ are set to μ^{ema}, σ^{ema} which are the exponential-moving-average (EMA) estimates over training process (a_0 is formed by the EMA statistics of all BN modules). However, when $P^{\text{test}}(x, y) \neq P^{\text{train}}(x, y)$, studies found that replacing $\mu^{\text{ema}}, \sigma^{\text{ema}}$ with the statistics of the test mini-batch: $\hat{\mu}^{\text{batch}}, \hat{\sigma}^{\text{batch}}$ can improve model accuracy (Nado et al., 2020) (for clarify, statistics estimated on test samples are denoted with 'ˆ'). The method is also marked as "BN adapt" (Schneider et al., 2020).

Diagnosis I: Normalization statistics are biased towards current test mini-batch. We conduct experiments on CIFAR100-C with $B = 128$. From Figure 2 we can see that the statistics $\hat{\mu}^{\text{batch}}, \hat{\sigma}^{\text{batch}}$ used in BN adapt are biased: they are far from the ideal global values and fluctuate dramatically during adaptation. More seriously, the bias can be aggravated on non-IID test streams. In Table 2, though BN adapt and TENT can improve accuracy compared to Source (test with the fixed pre-trained model $f_{\{\theta_0, a_0\}}$) in the IID scenario, they suffer from degradation in the non-IID cases ($\rho = 0.1$, which will be explained in Section 4 and Appendix A.1). Overall, we can see that the biased statistics severely impede test-time adaptation because they are derived solely from the current small mini-batch.

(a) μ, IID data   (b) μ, non-IID data

(c) σ, IID data   (d) σ, non-IID data

Figure 2: Normalization statistics in different scenarios on CIFAR100-C.

Treatment I: Test-time batch renormalization (TBR) is a simple and powerful tool to relieve the above bias. It is natural to simply employ the test-time moving averages $\hat{\mu}^{\text{ema}}, \hat{\sigma}^{\text{ema}}$ to perform normalization during adaptation, referring to as TEMA, where $\hat{\mu}_t^{\text{ema}} = \alpha \hat{\mu}_{t-1}^{\text{ema}} + (1 - \alpha) \hat{\mu}_t^{\text{batch}}, \hat{\sigma}_t^{\text{ema}} = \alpha \hat{\sigma}_{t-1}^{\text{ema}} + (1 - \alpha) \hat{\sigma}_t^{\text{batch}}, \alpha$ is a smoothing coefficient and $\hat{\mu}_0^{\text{ema}}, \hat{\sigma}_0^{\text{ema}}$ are defined as $\hat{\mu}_1^{\text{batch}}, \hat{\sigma}_1^{\text{batch}}$. TEMA can consistently improve BN adapt: the normalization statistics in Figure 2 become more stable and accurate, and the test accuracy in Table 2 is improved as well.

However, for TENT which involves parameters update, TEMA can destroy the trained model as shown in Table 2. As discussed in Ioffe & Szegedy (2015), simply employing the moving averages would neutralize the effects of gradient optimization and normalization, as the gradient descent optimization does not consider the normalization, leading to unlimited growth of model parameters. Thus, we introduce batch renormalization (Ioffe, 2017) into test-time adaptation, leading to TBR, which is formulated by

$$v^* = \frac{v - \hat{\mu}^{\text{batch}}}{\hat{\sigma}^{\text{batch}}} \cdot r + d, \quad \text{where} \quad r = \frac{sg(\hat{\sigma}^{\text{batch}})}{\hat{\sigma}^{\text{ema}}}, \quad d = \frac{sg(\hat{\mu}^{\text{batch}}) - \hat{\mu}^{\text{ema}}}{\hat{\sigma}^{\text{ema}}}, \quad (1)$$

$sg(\cdot)$ stands for the operation of stopping gradient. Different from BN adapt, we use the test-time moving averages to rectify the normalization (through r and d). Different from the TEMA, TBR is well compatible with gradient-based adaptation methods (e.g., TENT) and can improve them as summarised in Table 2. For BN adapt, TEMA is equal to TBR. Different from the original batch renormalization used in the training phase, TBR is employed in the inference phase which uses the

Table 2: Average accuracy (%) of 15 corrupted sets on CIFAR100-C.

Method	IID	non-IID
Source	53.5	53.5
BN adapt	64.4	26.6
BN adapt+TEMA	64.9	62.8
TENT	68.7	23.1
TENT+TEMA	23.0	25.0
TENT+TBR	**68.9**	**63.1**

Table 3: Variance (Var), Range (R) of per-class number of predictions, and accuracy (Acc, %) on Gauss data.

Method	IID			non-IID		
	Var	R	Acc	Var	R	Acc
Source	25051.5	956	27.0	25051.5	956	27.0
BN adapt+TEMA	346.3	118	58.0	428.9	147	56.0
TENT+TBR	1243.5	266	62.1	3401.6	520	55.8
TENT+TBR+DOT	432.8	137	**64.0**	795.5	236	**59.6**

(a) **:, IID, Source** (b) **Gauss, IID, :** (c) **Gauss, :, TENT+TBR** (d) **Gauss, :, TENT+TBR+DOT**

Figure 3: Per-class number of predictions under combinations of [*data, scenario, method*]. (a): counts of Source on clean and Gauss data; (b): counts of various methods on IID Gauss data; (c) / (d): counts of TENT+TBR / TENT+TBR+DOT on IID and non-IID Gauss data.

statistics and moving averages derived from test batches. Besides, as the adaptation starts with a trained model $f_{\{\theta_0, a_0\}}$, TBR discards the warm-up and truncation operation to r and d, thus does not introduce additional hyper-parameters. TBR can be applied directly to a common pre-trained model with BN without requiring the model to be trained with such calibrated normalization.

3.3 A CLOSER LOOK AT TEST-TIME PARAMETER OPTIMIZATION

Building on BN adapt, TENT (Wang et al., 2021) further optimizes the affine parameters γ, β through entropy minimization and demonstrates that test-time parameter optimization can yield better results compared to employing BN adapt alone. We further take a closer look at this procedure.

Diagnosis II: the test-time optimization is biased towards dominant classes. We evaluate the model on the IID and non-IID ($\rho = 0.1$) gaussian noise corrupted test data (Gauss) of CIFAR100-C. We also test the model on the original clean test set of CIFAR100 for comparison. Figure 3 depicts the per-class number of predictions, while Table 3 shows the corresponding variance, range (maximum subtract minimum), and accuracy. We draw the following five conclusions.

- Predictions are naturally imbalanced, even for a model trained on class-balanced data and tested on a class-balanced test set with $P^{\text{test}}(x, y) = P^{\text{train}}(x, y)$: the "clean" curve in Figure 3a with variance 68.8 and range 46. This phenomenon is also studied in Wang et al. (2022b).
- Predictions becomes more imbalanced when $P^{\text{test}}(x, y) \neq P^{\text{train}}(x, y)$: the ranges are 46 and 956 on the clean and corrupted test set respectively.
- BN adapt+TEMA improves accuracy (from 27.0% to 58.0%) and alleviates the prediction imbalance at the same time (the range dropped from 956 to 118).
- Though accuracy is further improved with TENT+TBR (from 58.0% to 62.1%), the predictions become more imbalanced inversely (the range changed from 118 to 266). TENT focuses on data with low entropy, while samples of some classes may have relatively lower entropy intrinsically, thus TENT would aggravate the prediction imbalance.
- On non-IID test streams, not only the model accuracy drops, but also the predictions become more imbalanced (range 266 / range 520 on the IID stream / non-IID stream for TENT+TBR), as the model may be absolutely dominated by some classes over a period of time in non-IID scenario.

The imbalanced data is harmful during the normal training phase, resulting in biased models and poor overall accuracy (Liu et al., 2019). Our main motivation is that the test-time adaptation methods also involve gradient-based optimization which is built on the model predictions; however, the predictions are actually imbalanced, particularly for non-IID or CI streams and the low-entropy-

---

Algorithm 1: Dynamic **O**nline reweigh**T**ing (DOT)

Input: inference step $t := 0$; test stream samples $\{x_j\}$; pre-trained model $f_{\{\theta_0,a_0\}}$; class-frequency
   vector z_0; loss function $\mathcal{L}$; smooth coefficient λ.

1 **while** *the test mini-batch* $\{x_{m_t+b}\}_{b=1}^{B}$ *arrives* **do**
2     $t = t + 1$
3     $\{p_{m_t+b}\}_{b=1}^{B}, f_{\{\theta_{t-1},a_t\}} \leftarrow \text{Forward}(\{x_{m_t+b}\}_{b=1}^{B}, f_{\{\theta_{t-1},a_{t-1}\}})$ // `output predictions`
4   **for** $b = 1$ **to** B **do**
5        $k_{m_t+b}^{*} = \arg\max_{k\in[1,K]} p_{m_t+b}[k]$ // `predicted label`
6        $w_{m_t+b} = 1/z_{t-1}[k_{m_t+b}^{*}]$ // `assign sample weight`
7     $\bar{w}_{m_t+b} = B \cdot w_{m_t+b}/\sum_{b'=1}^{B} w_{m_t+b'},\ b = 1,2,\cdots,B$ // `normalize sample weight`
8     $l = \frac{1}{B}\sum_{b=1}^{B}\bar{w}_{m_t+b} \cdot \mathcal{L}(p_{m_t+b})$ // `combine sample weight with loss`
9     $f_{\{\theta_t,a_t\}} \leftarrow \text{Backward \& Update}(l, f_{\{\theta_{t-1},a_t\}})$ // `update θ`
10     $z_t \leftarrow \lambda z_{t-1} + \frac{(1-\lambda)}{B}\sum_{b=1}^{B} p_{m_t+b}$ // `update z`

---

emphasized adaptation methods. Therefore, we argue that the test-time optimization is biased towards some dominant classes actually, resulting in inferior performance. A vicious circle is formed by skewed optimization and imbalanced predictions.

Treatment II: Dynamic online re-weighting (DOT) can alleviate the class bias. Many methods have been developed to deal with class imbalance during the training phase, but they face several challenges when it comes to fully test-time adaptation: (i) Network architectures are immutable. (ii) Because test sample class frequencies are dynamic and agnostic, the common constraint of making the output distribution uniform Liang et al. (2020) is no longer reasonable. (iii) Inference and adaptation must occur in real-time when test mini-batch arrived (only a single pass through test data, no iterative learning).

Given these constraints, we propose DOT to combat the class bias, as presented in Algorithm 1. DOT is mainly derived from class-wise re-weighting (Cui et al., 2019). To tackle the dynamically changing and unknown class frequencies, we use a momentum-updated class-frequency vector $z \in \mathbb{R}^K$ instead (L10), which is initiated with $z[k] = \frac{1}{K}$, $k = 1, 2, \cdots, K$. For each inference step, we assign weights to each test sample based on its pseudo label and the current z (L5, 6). Specifically, when $z[k]$ is relatively large, during the subsequent adaptation, DOT will reduce the contributions of the k^{th} class samples (pseudo label) and emphasize others. It is worth noting that DOT can alleviate the class bias caused by the pre-trained model (*e.g.*, inter-class similarity), test stream (*e.g.*, class-imbalanced scenario) or adaptation methods (*e.g.*, TENT) simultaneously.

DOT is a general idea to tackle the class bias and can be combined with other test-time adaptation techniques. Some components in Algorithm 1 have multiple options. For the "Forward $(\cdot)$" function (L3), the discussed BN adapt and TBR can be incorporated. For the loss function $\mathcal{L}(\cdot)$ (L8), studies usually employ the entropy minimization loss: $\mathcal{L}(p_b) = -\sum_{k=1}^{K} p_b[k]\log p_b[k]$ or the cross-entropy loss with pseudo labels: $\mathcal{L}(p_b) = -\mathbb{I}_{p_b[k_b^*]\geq\tau} \cdot \log p_b[k_b^*]$ (commonly, only samples with high prediction confidence are utilized, τ is a pre-defined threshold). Similarly, for entropy minimization, Ent-W (Niu et al., 2022) also discard the high-entropy samples and emphasizes the low-entropy ones: $\mathcal{L}(p_b) = -\mathbb{I}_{H_b<\tau} \cdot e^{\tau-H_b} \cdot \sum_{k=1}^{K} p_b[k]\log p_b[k]$, where H_b is the entropy of sample x_b.

4 EXPERIMENTS

Datasets and models. We conduct experiments on common datasets CIFAR100-C, ImageNet-C Hendrycks & Dietterich (2019), and ImageNet-R Hendrycks et al. (2021). CIFAR100-C / ImageNet-C contains 15 corruption types, each with 5 severity levels; we use the highest level unless otherwise specified. ImageNet-R contains various styles (*e.g.*, paintings) of ImageNet categories. Following Wang et al. (2022a); Niu et al. (2022), for evaluations on CIFAR100-C, we adopt the trained ResNeXt-29 (Xie et al., 2017) model from Hendrycks et al. (2020) as $f_{\{\theta_0,a_0\}}$; for ImageNet-C / -R, we use the trained ResNet-50 model from Torchvision. The models are trained on the corresponding original training data. Details and examples are provided in Appendix A.1

Metrics. Unless otherwise specified, for the class-balanced data, we report the classification accuracy (%); for the class-imbalanced data, we report the mean accuracy over classes (%) (Liu et al., 2019); results are averaged over 15 different corruption types for CIFAR100-C and ImageNet-C in the main text, please see detailed performance on each corruption type in Appendix A.4, A.5.

Implementation details. Following Wang et al. (2021; 2022a); Niu et al. (2022), unless otherwise specified, we use Adam optimizer with learning rate of 1e-3, batch size of 200 for CIFAR100-C and SGD optimizer with learning rate of 2.5e-4, batch size of 64 for ImageNet-C/-R. For DELTA, the smoothing coefficient α in TBR is set to 0.95, λ in DOT is set to 0.95 for ImageNet-C/-R and 0.9 for CIFAR100-C. For other methods, the hyper-parameters are set according to corresponding papers and listed in Appendix A.2. The code will be available online.

Baselines. We adopt the following SOTA methods as baselines: pseudo label (PL) (Lee et al., 2013), test-time augmentation (TTA) (Ashukha et al., 2020), BN adaptation (BN adapt) (Schneider et al., 2020; Nado et al., 2020), test-time entropy minimization (TENT) (Wang et al., 2021), marginal entropy minimization with one test point (MEMO) (Zhang et al., 2021), efficient test-time adaptation (ETA) (Niu et al., 2022), entropy-based weighting (Ent-W) (Niu et al., 2022), laplacian adjusted maximum-likelihood estimation (LAME) (Boudiaf et al., 2022), continual test-time adaptation (CoTTA/CoTTA*: w/wo resetting) (Wang et al., 2022a). We combine DELTA with PL, TENT, and Ent-W in this work.

Table 4: Accuracy in IID scenarios.

Method	CIFAR100-C	ImageNet-C
Source	53.5	18.0
TTA	–	17.7
BN adapt	64.6	31.5
MEMO	–	23.9
ETA	69.5	48.0
LAME	50.7	17.2
CoTTA	65.5	34.4
CoTTA*	67.5	35.1
PL	68.2	40.2
+DELTA	68.7 (+0.5)	41.8 (+1.6)
TENT	69.0	42.7
+DELTA	69.6 (+0.6)	45.1 (+2.4)
Ent-W	69.6	44.6
+DELTA	**70.2** (+0.6)	**49.9** (+5.3)

Evaluation on IID test streams. The results on CIFAR100-C are reported in Table 4. As can be seen, the proposed DELTA consistently improves the previous adaptation approaches PL (gain 0.5%), TENT (gain 0.6%), and Ent-W (gain 0.6%), achieving new state-of-the-art performance. The results also indicate that current test-time adaptation methods indeed suffer from biases, and the debiasing mechanism can help them obtain superior performance. Then we evaluate the methods on the more challenging dataset ImageNet-C. Consistent with the results on CIFAR100-C, DELTA remarkably improves the existing methods. As the adaptation batch size (64) is too small compared to the class number (1,000) on ImageNet-C, the previous methods undergo more severe biases than on CIFAR100-C. Consequently, DELTA achieves greater gains on ImageNet-C: 1.6% gain over PL, 2.4% gain over TENT, and 5.3% gain over Ent-W.

Evaluation on non-IID test streams. To simulate non-IID streams, following Yurochkin et al. (2019), we arrange the samples via the Dirichlet distribution with a concentration factor $\rho > 0$ (the smaller ρ is, the more concentrated the same-class samples will be, which is detailed in Appendix A.1). We test models with $\rho \in \{1.0, 0.5, 0.1\}$. The experimental results are provided in Table 5. The representative test-time adaptation methods suffer from performance deterioration in the non-IID scenario, especially on data sampled with small ρ. DELTA successfully helps models adapt to environments across different concentration factors. It is worth noting that DELTA's non-IID-stream results are close to the IID results, e.g., TENT+DELTA achieves 69.6% and 67.8% accuracy on the IID and non-IID ($\rho = 0.5$) test streams from CIFAR100-C.

Table 5: Accuracy in non-IID scenarios with different ρ.

Method	CIFAR100-C			ImageNet-C		
	1.0	0.5	0.1	1.0	0.5	0.1
Source	53.5	53.5	53.5	18.0	18.0	18.0
BN adapt	52.4	49.5	35.4	21.6	19.3	12.1
ETA	54.9	50.9	34.6	27.1	22.8	10.0
LAME	60.5	61.6	65.1	22.0	22.7	24.7
CoTTA	53.3	50.4	36.5	23.2	20.5	12.7
CoTTA*	53.5	50.5	36.1	23.1	21.0	12.9
PL	54.3	50.6	34.9	25.6	22.6	13.1
+DELTA	67.6	67.0	65.4	40.5	39.9	37.2
	+13.3	+16.4	+30.5	+14.9	+17.3	+24.1
TENT	54.1	50.2	33.6	25.7	22.2	12.1
+DELTA	68.6	67.8	**66.3**	43.7	43.1	40.2
	+14.5	+17.6	+32.7	+18.0	+20.9	+28.1
Ent-W	54.8	51.0	34.4	16.8	12.9	4.4
+DELTA	**69.0**	**68.2**	**66.3**	**48.3**	**47.5**	**43.3**
	+14.2	+17.2	+31.9	+31.5	+34.6	+38.9

Evaluation on CI and CI&non-IID test streams.
Following Cui et al. (2019), we resample the test samples with an imbalance factor π (the smaller π is, the more imbalanced the test data will be, which is detailed in Appendix A.1). We test models with $\pi \in \{0.1, 0.05\}$. Table 6 summarizes the results in the CI, CI&non-IID scenarios, with the following observations: **(i)** Under class-imbalanced scenario, the biases are aggravated, but not as

Table 6: Accuracy in CI, CI&non-IID ($\rho = 0.5$) scenarios with different π.

| Method | CI | | | | CI & non-IID | | | |
| | CIFAR100-C | | ImageNet-C | | CIFAR100-C | | ImageNet-C | |
	0.1	0.05	0.1	0.05	0.1	0.05	0.1	0.05
Source	53.3	53.3	17.9	17.9	53.3	53.3	17.9	17.9
BN adapt	64.3	63.6	31.5	31.4	49.9	49.0	20.1	20.2
ETA	68.2	67.7	47.5	47.0	51.1	50.2	21.8	20.9
LAME	50.7	50.5	17.2	17.2	60.3	59.2	21.7	21.5
CoTTA	65.1	64.3	34.1	34.0	50.7	49.6	21.6	21.6
CoTTA*	66.8	66.0	33.5	34.4	50.8	49.7	21.7	21.8
PL	67.2	66.8	39.4	39.0	50.6	49.9	23.0	22.8
+DELTA	67.5	67.2	40.9	40.5	66.6	65.5	38.8	38.2
	+0.3	+0.4	+1.5	+1.5	+16.0	+15.6	+15.8	+15.4
TENT	67.6	67.3	42.1	41.8	50.2	49.3	22.4	22.2
+DELTA	68.3	68.1	44.4	44.0	67.8	66.4	42.2	41.5
	+0.7	+0.8	+2.3	+2.2	+17.6	+17.1	+19.8	+19.3
Ent-W	68.2	67.7	40.7	38.9	51.1	50.2	10.8	10.7
+DELTA	**69.1**	**68.6**	**48.4**	**47.5**	**67.9**	**67.0**	**45.3**	**44.5**
	+0.9	+0.9	+7.7	+8.6	+16.8	+16.8	+34.5	+33.8

Table 7: Results on in-distribution test set of CIFAR100.

Method	Accuracy
Source	78.9
BN adapt	76.1
TENT	78.7
+DELTA	78.8 (+0.1)
Ent-W	78.8
+DELTA	**79.0** (+0.2)

Figure 4: Across architecture.

severe as under non-IID data. This is primarily because the imbalanced test data has little effect on the normalization statistics. DELTA works well on the imbalanced test stream. **(ii)** The hybrid CI&non-IID scenario can be more difficult than the individual scenarios. DELTA can also boost baselines in the hybrid scenario. **(iii)** Though the low-entropy-emphasized method Ent-W improves TENT in IID scenario (Table 4), it can be inferior to TENT in CI or non-IID scenarios (the results on ImageNet-C in Table 5,6). The reason is that Ent-W leads to a side effect — amplifying the biases, which would neutralize or even overwhelm its benefits. DELTA eliminates Ent-W's side effects while retaining its benefits, so Ent-W+DELTA always significantly outperforms TENT+DELTA.

Evaluation on the real-world out-of-distribution dataset ImageNet-R. We find the ImageNet-R is class-imbalanced inherently. Thus, in addition to the overall accuracy used in its previous benchmark, we also report the mean accuracy over classes in Table 8. DELTA also leads to consistent improvement on the realistic distribution-shift dataset, which consists of mixed variants such as cartoon, art, painting, sculpture, sketch, toy, *etc.*

Evaluation on in-distribution test data, *i.e.*, $P^{\text{test}}(x, y) = P^{\text{train}}(x, y)$. A qualified test-time adaptation method should not degenerate on an in-distribution dataset. According to Table 7, (i) DELTA continues to improve performance, albeit slightly; (ii) most adaptation methods can produce comparable results to Source, and the combination with DELTA even outperforms Source on in-distribution data.

Table 8: Results on ImageNet-R.

Method	Acc	Mean Acc
Source	36.2	38.4
TTA	38.7	-
MEMO	41.2	-
BN adapt	39.7	42.1
ETA	46.4	48.6
TENT	42.6	44.8
+DELTA	43.1 (+0.5)	45.3 (+0.5)
Ent-W	46.6	48.5
+DELTA	**46.9** (+0.3)	**48.9** (+0.4)

Evaluation with different architectures. Figure 4 indicates that DELTA can help improve previous test-time adaptation methods with different model architectures. More analyses (*e.g.*, evaluations with small batch size, different severity levels) are provided in Appendix A.3.

Contribution of each component of DELTA. DELTA consists of two debiasing tools: TBR and DOT. In Table 9, we analyze their contributions on the basis of TENT with four scenarios and two datasets. Row #1 indicates the results of TENT. Applying either TBR or DOT alone on TENT brings gain in most scenarios and datasets. While, we find that TBR achieves less improvement when the test stream is IID and the batch size is large (*e.g.*, performing adaptation with TBR alone on the IID data of CIFAR100-C with batch size of 200 does not improve TENT). However, when the batch size is relatively small (*e.g.*, ImageNet-C, batch size of 64), the benefits of TBR will become apparent. More importantly, TBR is extremely effective and necessary for non-IID scenarios. DOT can consistently promote TENT or TENT+TBR in all scenarios, especially when the class number is large (the class bias is more severe). These results demonstrate that while both the normalization statistics bias and the class bias are detrimental, TBR and DOT can effectively alleviate them.

Table 9: Ablation on the effectiveness of each component (on top of TENT) measured by accuracy (%) in various scenarios: IID, non-IID ($\rho = 0.5$), CI ($\pi = 0.1$), CI & non-IID ($\rho = 0.5$, $\pi = 0.05$).

#	TBR	DOT	CIFAR100-C				ImageNet-C			
			IID	non-IID	CI	CI&non-IID	IID	non-IID	CI	CI&non-IID
1			69.0	50.2	67.6	49.3	42.7	22.2	42.1	22.2
2	✓		68.9	66.7	67.8	65.5	43.5	40.9	42.7	39.3
3		✓	69.4	51.1	68.0	50.1	44.4	23.9	43.9	24.4
4	✓	✓	**69.6**	**67.8**	**68.3**	**66.4**	**45.1**	**43.1**	**44.4**	**41.5**

Table 10: Ablation on different techniques for class imbalance (on top of Ent-W+TBR) measured by accuracy (%) on various scenarios: IID, non-IID ($\rho = 0.5$), CI ($\pi = 0.1$), CI & non-IID ($\rho = 0.5$, $\pi = 0.05$).

Method	CIFAR100-C				ImageNet-C			
	IID	non-IID	CI	CI&non-IID	IID	non-IID	CI	CI&non-IID
Div-W (0.05)	67.4	67.6	66.7	66.4	48.9	45.4	47.8	40.7
Div-W (0.1)	69.3	68.1	68.2	66.9	48.4	43.1	47.5	39.6
Div-W (0.2)	69.8	67.5	68.7	66.5	46.1	40.3	46.1	37.6
Div-W (0.4)	69.7	67.3	68.5	66.2	43.5	37.1	43.3	35.2
LA	70.0	66.4	69.0	65.5	42.4	27.9	42.2	27.8
Sample-drop	**70.2**	68.1	68.8	66.7	49.5	46.9	48.2	42.5
DOT	**70.2**	**68.2**	**69.1**	**67.0**	**49.9**	**47.5**	**48.4**	**44.5**

Figure 5: Impacts of α and λ on CIFAR100-C (non-IID data with $\rho = 0.5$).

Comparing DOT with other techniques for class imbalance. On the basis of Ent-W+TBR, Table 10 compares DOT against the following strategies for solving class imbalance. *Diversity-based weight (Div-W)* (Niu et al., 2022) computes the cosine similarity between the arrived test samples' prediction and a moving average one like z, then only employs the samples with low similarity to update model. Although the method is proposed to reduce redundancy, we find it can resist class bias too. The method relies on a pre-defined similarity threshold to determine whether to use a sample. We report the results of Div-W with varying thresholds (shown in parentheses). We observe that the threshold is very sensitive and the optimal value varies greatly across datasets. *Logit adjustment (LA)* (Menon et al., 2021) shows strong performance when training on imbalanced data. Following Wang et al. (2022b), we can perform LA with the estimated class-frequency vector z in test-time adaptation tasks. While we find that LA does not show satisfactory results here. We speculate that this is because the estimated class distribution is not accurate under the one-pass adaptation and small batch size, while LA requires a high-quality class distribution. We further propose another strategy called *Sample-drop*. It records the (pseudo) categories of the test samples that have been employed, then Sample-drop will directly discard a newly arrived test sample (*i.e.*, not use the sample to update the model) if its pseudo category belongs to the majority classes among the counts. This simple strategy is valid but inferior to DOT, as it completely drops too many useful samples.

Impacts of α in TBR and λ in DOT. Similar to most exponential-moving-average-based methods, when the smoothing coefficient α (or λ) is too small, the adaptation may be unstable; and when α (or λ) is too large, the adaptation would be slow. Figure 5 provides the ablation studies of α (above) and λ (below) on the non-IID ($\rho = 0.5$) test stream of CIFAR100-C. We find that TBR and DOT perform reasonably well under a wide range of α and λ.

5 CONCLUSION

In this paper, we expose the biases in test-time adaptation methods and propose DELTA to mitigate them. First, the normalization statistics used in BN adapt are heavily influenced by the current test mini-batch, which can be one-sided and highly fluctuant. We introduce TBR to mitigate the bias using the (approximate) global statistics. Second, the optimization is highly skewed towards dominant classes, leaving other classes underrepresented. DOT corrects this bias by re-balancing the contributions of each class in an online manner. The combination of these two powerful tools results in our plug-in debiasing method DELTA, which outperforms various existing methods in different scenarios (IID, non-IID, CI, and CI & non-IID) at the same time.

REFERENCES

Shaden Alshammari, Yu-Xiong Wang, Deva Ramanan, and Shu Kong. Long-tailed recognition via weight balancing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6897–6907, 2022.

Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BJxI5gHKDr.

Malik Boudiaf, Romain Mueller, Ismail Ben Ayed, and Luca Bertinetto. Parameter-free online test-time adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8344–8353, 2022.

Dian Chen, Dequan Wang, Trevor Darrell, and Sayna Ebrahimi. Contrastive test-time adaptation. In *CVPR*, 2022.

Yin Cui, Menglin Jia, Tsung-Yi Lin, Yang Song, and Serge Belongie. Class-balanced loss based on effective number of samples. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9268–9277, 2019.

Charles Elkan. The foundations of cost-sensitive learning. In *International joint conference on artificial intelligence*, volume 17, pp. 973–978. Lawrence Erlbaum Associates Ltd, 2001.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The journal of machine learning research*, 17(1):2096–2030, 2016.

Arthur Gretton, Karsten Borgwardt, Malte Rasch, Bernhard Schölkopf, and Alex Smola. A kernel method for the two-sample-problem. In B. Schölkopf, J. Platt, and T. Hoffman (eds.), *Advances in Neural Information Processing Systems*, volume 19. MIT Press, 2006. URL https://proceedings.neurips.cc/paper/2006/file/e9fb2eda3d9c55a0d89c98d6c54b5b3e-Paper.pdf.

Yin-Yin He, Jianxin Wu, and Xiu-Shen Wei. Distilling virtual examples for long-tailed recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 235–244, 2021.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=HJz6tiCqYm.

Dan Hendrycks, Norman Mu, Ekin D. Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. AugMix: A simple data processing method to improve robustness and uncertainty. *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8340–8349, 2021.

Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alexei Efros, and Trevor Darrell. Cycada: Cycle-consistent adversarial domain adaptation. In *International conference on machine learning*, pp. 1989–1998. Pmlr, 2018.

Sergey Ioffe. Batch renormalization: Towards reducing minibatch dependence in batch-normalized models. *Advances in neural information processing systems*, 30, 2017.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Bingyi Kang, Yu Li, Sa Xie, Zehuan Yuan, and Jiashi Feng. Exploring balanced feature spaces for representation learning. In *International Conference on Learning Representations*, 2020a.

Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2020b. URL https://openreview.net/forum?id=r1gRTCVFvB.

Jogendra Nath Kundu, Naveen Venkat, Rahul M V, and R. Venkatesh Babu. Universal source-free domain adaptation. June 2020.

Dong-Hyun Lee et al. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In *Workshop on challenges in representation learning, ICML*, volume 3, pp. 896, 2013.

Lei Li, Ke Gao, Juan Cao, Ziyao Huang, Yepeng Weng, Xiaoyue Mi, Zhengze Yu, Xiaoya Li, and Boyang Xia. Progressive domain expansion network for single domain generalization. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 224–233, 2021.

Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International Conference on Machine Learning*, pp. 6028–6039. PMLR, 2020.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X Yu. Large-scale long-tailed recognition in an open world. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2537–2546, 2019.

Mingsheng Long, Han Zhu, Jianmin Wang, and Michael I Jordan. Deep transfer learning with joint adaptation networks. In *International conference on machine learning*, pp. 2208–2217. PMLR, 2017.

Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I Jordan. Conditional adversarial domain adaptation. *Advances in neural information processing systems*, 31, 2018.

Aditya Krishna Menon, Sadeep Jayasumana, Ankit Singh Rawat, Himanshu Jain, Andreas Veit, and Sanjiv Kumar. Long-tail learning via logit adjustment. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=37nvvqkCo5.

Zachary Nado, Shreyas Padhy, D Sculley, Alexander D'Amour, Balaji Lakshminarayanan, and Jasper Snoek. Evaluating prediction-time batch normalization for robustness under covariate shift. *arXiv preprint arXiv:2006.10963*, 2020.

Shuaicheng Niu, Jiaxiang Wu, Yifan Zhang, Yaofo Chen, Shijian Zheng, Peilin Zhao, and Mingkui Tan. Efficient test-time model adaptation without forgetting. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 16888–16905. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/niu22a.html.

Joaquin Quinonero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D Lawrence. *Dataset shift in machine learning*. Mit Press, 2008.

Mengye Ren, Wenyuan Zeng, Bin Yang, and Raquel Urtasun. Learning to reweight examples for robust deep learning. In *International conference on machine learning*, pp. 4334–4343. PMLR, 2018.

Kuniaki Saito, Yoshitaka Ushiku, and Tatsuya Harada. Asymmetric tri-training for unsupervised domain adaptation. In *International Conference on Machine Learning*, pp. 2988–2997. PMLR, 2017.

Steffen Schneider, Evgenia Rusak, Luisa Eck, Oliver Bringmann, Wieland Brendel, and Matthias Bethge. Improving robustness against common corruptions by covariate shift adaptation. *Advances in Neural Information Processing Systems*, 33:11539–11551, 2020.

Dequan Wang, Evan Shelhamer, Shaoteng Liu, Bruno Olshausen, and Trevor Darrell. Tent: Fully test-time adaptation by entropy minimization. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=uXl3bZLkr3c.

Qin Wang, Olga Fink, Luc Van Gool, and Dengxin Dai. Continual test-time domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7201–7211, 2022a.

Tao Wang, Yu Li, Bingyi Kang, Junnan Li, Junhao Liew, Sheng Tang, Steven Hoi, and Jiashi Feng. The devil is in classification: A simple framework for long-tail instance segmentation. In *European conference on computer vision*, pp. 728–744. Springer, 2020.

Xudong Wang, Zhirong Wu, Long Lian, and Stella X Yu. Debiased learning from naturally imbalanced pseudo-labels. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14647–14657, 2022b.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1492–1500, 2017.

Shiqi Yang, Yaxing Wang, Joost van de Weijer, Luis Herranz, and Shangling Jui. Generalized source-free domain adaptation. In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 8958–8967, 2021a. doi: 10.1109/ICCV48922.2021.00885.

Shiqi Yang, Yaxing Wang, Joost van de weijer, Luis Herranz, and SHANGLING JUI. Exploiting the intrinsic neighborhood structure for source-free domain adaptation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021b. URL https://openreview.net/forum?id=ueGDv64HmO.

Mikhail Yurochkin, Mayank Agarwal, Soumya Ghosh, Kristjan Greenewald, Nghia Hoang, and Yasaman Khazaeni. Bayesian nonparametric federated learning of neural networks. In *International Conference on Machine Learning*, pp. 7252–7261. PMLR, 2019.

Werner Zellinger, Thomas Grubinger, Edwin Lughofer, Thomas Natschläger, and Susanne Saminger-Platz. Central moment discrepancy (CMD) for domain-invariant representation learning. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=SkB-_mcel.

M. Zhang, S. Levine, and C. Finn. MEMO: Test time robustness via adaptation and augmentation. 2021.

Bowen Zhao, Xi Xiao, Guojun Gan, Bin Zhang, and Shu-Tao Xia. Maintaining discrimination and fairness in class incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13208–13217, 2020.

Art	Cartoon	Deviantart	Graffiti	Graphic
Misc	Origami	Painting	Sculpture	Sketch
Sticker		Tattoo	Toy	Videogame

Figure 6: Different renditions of class n01694178 (African chameleon) from ImageNet-R.

A APPENDIX

A.1 DATASETS

Examples of ImageNet-R and ImageNet-C are shown in Figure 6 and Figure 7 respectively. ImageNet-R Hendrycks et al. (2021) holds a variety of renditions (*sketches, graphics, paintings, plastic objects, cartoons, graffiti, origami, patterns, deviantart, plush objects, sculptures, art, tattoos, toys, embroidery, video game*) of 200 ImageNet classes, resulting in 30,000 images. CIFAR100-C and ImageNet-C are established in Hendrycks & Dietterich (2019). CIFAR100-C contains 10,000 images with 15 corruption types: *Gaussian Noise (abbr. Gauss), Shot Noise (Shot), Impulse Noise (Impul), Defocus Blur (Defoc), Frosted Glass Blur (Glass), Motion Blur (Motion), Zoom Blur (Zoom), Snow, Frost, Fog, Brightness (Brit), Contrast (Contr), Elastic, Pixelate (Pixel), JPEG*. There are 50,000 images for each corruption type in ImageNet-C, others are the same as CIFAR100-C.

To simulate non-IID scenarios, for each class, we sample $q_k \sim Dir_J(\rho)$, $q_k \in \mathbb{R}^J$ and allocate a $q_{k,j}$ proportion of the k^{th} class samples to piece j, then the J pieces are concatenated to form a test stream in our experiments (J is set to 10 for all experiments); $\rho > 0$ is a concentration factor, when ρ is small, samples belong to the same category will concentrate in test stream.

To simulate CI scenarios, we re-sample data points with an exponential decay in frequencies across different classes. We control the degree of imbalance through an imbalance factor π, which is defined as the ratio between sample sizes of the least frequent class and the most frequent class.

For CI & non-IID scenarios, we mimic the class-imbalanced test set first, then perform the non-IID sampling process.

A.2 IMPLEMENTATIONS

We summarize the implementation details of the compared methods here, including BN adapt, PL, TENT, LAME, ETA, Ent-W, and CoTTA (CoTTA*). Unless otherwise specified, the optimizer, learning rate, and batch size are the same as those described in the main paper. For BN adapt, we follow the operation in Nado et al. (2020) and the official code of TENT (https://github.com/DequanWang/tent), *i.e.*, using the test-time normalization statistics completely. Though one can introduce a hyper-parameter to adjust the trade-off between current statistics and those inherited from the trained model (a_0) (Schneider et al., 2020), we find this strategy does not lead to significant improvement and its effect varies from dataset to dataset. For PL and TENT, besides the normalization statistics, we update the affine parameters in BN modules. The confidence threshold in PL is set to 0.4, which can produce acceptable results in most cases. We adopt/modify the

Figure 7: Different corruption types of class n01694178 (African chameleon) from ImageNet-C.

official implementation `https://github.com/DequanWang/tent` to produce the results of TENT/PL. For LAME, we use the k-NN affinity matrix with 5 nearest neighbors following Boudiaf et al. (2022) and the official implementation `https://github.com/fiveai/LAME`. For ETA, the entropy constant threshold is set to $0.4 \times \ln K$ (K is the number of task classes), and the similarity threshold is set to 0.4/0.05 for CIFAR/ImageNet experiments following the authors' suggestion and official implementation `https://github.com/mr-eggplant/EATA`. For Ent-W, the entropy constant threshold is set to 0.4 or 0.5 times $\ln K$. For CoTTA, the used random augmentations include color jitter, random affine, gaussian blur, random horizontal flip, and gaussian noise. 32 augmentations are employed in this method. The learning rate is set to 0.01 for ImageNet experiments following official implementation `https://github.com/qinenergy/cotta`. The restoration probability is set to 0.01 for CIFAR experiments and 0.001 for ImageNet experiments. The augmentation threshold is set to 0.72 for CIFAR experiments and 0.1 for ImageNet experiments. The exponential-moving-average factor is set to 0.999 for all experiments. CoTTA optimizes all learnable parameters during adaptation.

A.3 ADDITIONAL ANALYSIS

Fully test-time adaptation with small (test) batch size. In the main paper, we report results with the default batch size following previous studies. Here, we study test-time adaptation with a much smaller batch size. The small batch size brings two serious challenges: the normalization statistics can be inaccurate and fluctuate dramatically; the gradient-based optimization can be noisy. Previous study (Niu et al., 2022) employs a sliding window with L samples in total (including $L - B$ previous samples, assuming $L > B$, $L\%B = 0$ here) to perform adaptation. However, this strategy significantly increases the computational cost: $\frac{L}{B} \times$ forward and backward, *e.g.,* $64\times$ when $B = 1, L = 64$. We employ another strategy, called "fast-inference and slow-update". When the samples arrive, infer them instantly with the current model but do not perform adaptation; the model is updated with the recent L samples every $\frac{L}{B}$ mini-batches. Thus, this strategy only needs $2\times$ forward and $1\times$ backward. Note that the two strategies both need to cache some recent test samples, which may be a bit against the "online adaptation". We evaluate TENT and DELTA on the IID test stream of CIFAR100-C with batch sizes 128, 16, 8, and 1. The results are listed in Table 11. We find that TENT suffers from severe performance degeneration when the batch size is small, which is due to TENT always using the normalization statistics derived from the test mini-batches, thus

it is still affected by the small batch size during "fast-inference". With the assistance of DELTA, the performance degradation can be significantly alleviated: it only drops by 0.7% (from 69.8% to 69.1%) when $B = 1$.

Table 11: Results (classification accuracy, %) with different batch sizes on IID test stream of CIFAR100-C.

Method	128	16	8	1
Source	53.5	53.5	53.5	53.5
TENT	68.7	64.9	59.9	1.6
TENT+DELTA	**69.8**	**69.4**	**69.0**	**69.1**

The initialization of TBR's normalization statistics. As described in Section 3.2, TBR keeps the moving normalization statistics $\hat{\mu}^{\text{ema}}$, $\hat{\sigma}^{\text{ema}}$, we usually have two ways to initialize them: using the statistics $\hat{\mu}_1^{\text{batch}}$, $\hat{\sigma}_1^{\text{batch}}$ derived from the first test mini-batch (First); using the statistics μ^{ema}, σ^{ema} inherited from the trained model (Inherit). In the main paper, we use the "First" initialization strategy. However, it is worth noting that "First" is not reasonable for too small batch size. We perform TENT+DELTA with the above two initialization strategies and different batch sizes on the IID test stream of CIFAR100-C. Figure 8 summaries the results, we can see that when the batch size is too small, using the inherited normalization statistics as initialization is better; when the batch size is acceptable (just > 8 for CIFAR100-C), using the "First" initialization strategy is superior.

Figure 8: Comparison of two TBR initialization strategies on top of TENT+DELTA in IID scenario on CIFAR100-C.

Performance under different severity levels on CIFAR100-C and ImageNet-C. In the main paper, for CIFAR100-C and ImageNet-C, we report the results with the highest severity level 5 following previous studies. Here, we investigate DELTA on top of TENT with different severity levels on CIFAR100-C (IID scenario). Figure 9 presents the results. We observe that (i) as the corruption level increases, the model accuracy decreases; (ii) DELTA works well under all severity levels.

Figure 9: Comparison under different severity levels on CIFAR100-C.

Influence of random seeds. As fully test-time adaptation is established based on a pre-trained model, *i.e.*, does not need random initialization; methods like PL, TENT, Ent-W, and our DELTA

also do not bring random initialization. As a result, the adaptation results are always the same on one fixed test stream. However, the random seeds can affect sample order in our experiments. We study the influence of random seeds on Gauss and Shot data (IID scenario) of ImageNet-C with seeds {2020, 2021, 2022, 2023}. The results of TENT and DELTA are summarized in Table 12, from which one can see the methods are not greatly affected by the sample order *within the same scenario*. For fair comparison, all methods are investigated under the same sample order for each specific scenario in our experiments.

Table 12: Influence of random seeds. Classification accuracies (%) are reported on two kinds of corrupted data (IID) of ImageNet-C under four random seeds (2020, 2021, 2022, and 2023).

Data	TENT				TENT+DELTA			
	2020	2021	2022	2023	2020	2021	2022	2023
Gauss	28.672	28.434	28.774	28.796	31.186	30.916	31.270	31.208
Shot	30.536	30.496	30.370	30.458	33.146	33.140	33.124	32.994

A.4 RESULTS OF EACH CORRUPTION TYPE ON CIFAR100-C.

Table 2 has compared the usages of different normalization statistics, we further provide the detailed results of all corruption types in Table 13.

Table 14 presents the results of all corruption types under different batch sizes and the two initialization strategies for normalization statistics in TBR, the averaged results have been illustrated in Table 11 and Figure 8 respectively.

Table 15 summarises the detailed performance on IID test stream with different severity levels.

Table 16 compares the test-time adaptation methods in IID scenario; Table 17 for non-IID test stream ($\rho = 1.0$), Table 18 for non-IID test stream ($\rho = 0.5$), Table 19 for non-IID test stream ($\rho = 0.1$); Table 20, 21 for CI data with $\pi = 0.1$, $\pi = 0.05$; Table 22 / Table 23 for CI & non-IID test data with $\rho = 0.5$ and $\pi = 0.1$ / $\pi = 0.05$.

A.5 RESULTS OF EACH CORRUPTION TYPE ON IMAGENET-C.

Table 24 compares the test-time adaptation methods in IID scenario and Table 25 further compares them with different model architectures; Table 26, Table 27, and Table 28 for non-IID test streams with $\rho = 1.0$, $\rho = 0.5$ and $\rho = 0.1$, respectively; Table 29, 30 for CI data with $\pi = 0.1$, $\pi = 0.05$; Table 31 / Table 32 for CI & non-IID test data with $\rho = 0.5$ and $\pi = 0.1$ / $\pi = 0.05$.

Table 13: Comparison of the normalization statistics on IID and non-IID test streams of CIFAR100-C with $B = 128$ in terms of classification accuracy (%).

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
IID scenario																
BN adapt	57.6	59.0	56.9	72.3	58.0	70.3	71.8	64.8	64.8	58.1	73.3	69.7	64.0	66.7	58.4	64.4
BN adapt+TEMA	58.0	59.7	57.1	72.5	58.6	70.3	72.5	65.3	65.5	58.3	74.1	70.2	64.4	67.0	59.2	64.9
TENT	62.4	64.7	67.3	74.3	62.5	72.4	74.2	69.4	67.6	66.8	75.6	71.8	66.9	71.3	62.6	68.7
TENT+TEMA	19.4	14.9	16.4	31.9	14.8	25.0	28.9	24.3	25.0	19.3	31.1	24.3	25.5	26.0	18.2	23.0
TENT+TBR	62.1	64.7	67.7	74.6	62.0	72.6	74.0	69.7	67.9	67.8	76.2	71.6	67.1	71.8	63.3	68.9
non-IID scenario																
BN adapt	24.1	24.7	23.4	30.2	23.2	29.9	29.8	26.6	27.2	24.2	30.0	28.6	25.7	27.8	23.8	26.6
BN adapt+TEMA	56.0	57.8	55.2	70.7	56.7	68.6	70.2	63.2	63.6	56.6	71.7	67.8	62.2	64.8	57.2	62.8
TENT	21.2	22.7	21.9	26.6	20.0	25.5	26.6	23.0	22.2	21.7	26.3	21.6	21.7	24.7	20.3	23.1
TENT+TEMA	18.0	17.3	15.2	34.2	18.6	26.3	36.6	18.9	27.2	24.6	36.2	25.8	26.5	28.6	20.4	25.0
TENT+TBR	55.8	60.0	58.8	70.7	57.2	67.4	69.7	64.4	62.8	60.2	71.5	64.0	60.9	67.1	56.4	63.1

Table 14: Comparison of different batch sizes and the initialization strategies for TBR's normalization statistics on IID test stream of CIFAR100-C in terms of classification accuracy (%).

Method	Init	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	–	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
TENT, B=128	–	62.4	64.7	67.3	74.3	62.5	72.4	74.2	69.4	67.6	66.8	75.6	71.8	66.9	71.3	62.6	68.7
TENT, B=16	–	58.7	61.0	63.8	70.8	58.7	68.8	70.3	65.8	64.1	63.3	72.2	66.9	62.7	67.6	59.4	64.9
TENT, B=8	–	54.0	56.1	58.6	65.9	53.0	64.1	65.4	61.0	58.6	57.8	67.1	62.9	58.1	62.8	53.8	59.9
TENT, B=1	–	1.5	1.5	1.6	1.6	1.6	1.8	1.7	1.8	1.6	1.5	1.6	1.6	1.5	1.8	1.6	1.6
TENT+DELTA, B=128	Inherit	62.4	63.9	69.0	75.3	63.2	73.2	74.8	69.8	69.2	66.6	76.0	71.3	67.4	69.7	64.3	69.1
TENT+DELTA, B=128	First	64.0	66.0	69.1	75.3	63.3	73.0	74.6	70.3	69.4	68.1	76.7	72.9	67.6	72.3	64.6	69.8
TENT+DELTA, B=16	Inherit	62.3	64.0	69.1	75.2	63.1	73.3	74.8	69.6	69.3	66.7	76.0	70.8	67.3	69.7	64.3	69.0
TENT+DELTA, B=16	First	63.5	65.5	68.2	74.8	63.2	72.7	74.6	70.2	69.3	67.7	76.2	72.4	67.5	71.9	63.9	69.4
TENT+DELTA, B=8	Inherit	62.4	64.0	69.0	75.2	63.1	73.3	74.8	69.7	69.4	66.6	75.9	71.2	67.3	69.6	64.2	69.0
TENT+DELTA, B=8	First	63.1	65.1	67.1	74.8	62.4	72.6	74.3	69.9	69.2	67.2	75.7	71.2	67.0	71.6	63.0	68.9
TENT+DELTA, B=1	Inherit	62.2	64.0	68.9	75.3	63.1	73.2	74.7	69.7	69.4	66.6	76.1	71.6	67.4	69.6	64.4	69.1
TENT+DELTA, B=1	First	60.0	62.0	64.4	71.4	59.5	69.0	71.4	65.6	65.7	62.9	72.6	64.0	63.6	68.6	59.8	65.4

Table 15: Classification accuracy (%) on IID test stream of CIFAR100-C with different severity levels ($B = 128$).

Method	Level	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	1	64.2	70.9	77.6	78.9	54.4	77.0	76.8	76.5	74.2	78.4	78.7	78.2	74.4	76.5	70.5	73.8
	2	49.3	63.6	75.3	78.1	56.6	75.1	76.6	69.9	69.7	76.1	77.7	75.2	75.0	72.3	65.8	70.4
	3	36.5	47.2	73.1	76.8	60.6	72.3	75.4	69.6	62.1	72.3	76.6	71.9	73.7	69.1	64.1	66.8
	4	31.2	40.6	68.0	75.2	39.5	72.4	74.0	65.2	61.1	65.8	74.9	65.7	68.9	52.3	62.5	61.2
	5	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
TENT	1	73.8	75.8	77.2	77.9	69.4	76.6	77.1	76.3	75.8	78.0	77.9	77.3	73.3	76.3	71.3	75.6
	2	70.2	73.7	76.0	77.9	69.6	75.6	76.8	73.4	74.0	76.2	77.8	75.2	74.8	76.0	68.5	74.4
	3	66.7	70.0	74.5	77.4	68.7	73.7	76.4	72.1	71.4	74.9	77.3	74.4	73.9	75.6	66.3	72.9
	4	64.4	68.3	70.9	76.3	62.6	74.2	75.3	70.5	70.4	72.2	76.9	74.1	70.5	74.3	65.2	71.1
	5	62.4	64.7	67.3	74.3	62.5	72.4	74.2	69.4	67.6	66.8	75.6	71.8	66.9	71.3	62.6	68.7
TENT+DELTA	1	74.4	76.1	78.0	78.7	70.3	77.2	77.7	77.1	76.6	78.6	78.5	78.3	74.5	77.1	72.0	76.3
	2	70.9	74.7	76.4	78.4	70.3	75.8	77.4	74.5	74.8	76.9	78.4	76.9	75.4	77.0	69.8	75.2
	3	67.8	70.2	75.3	77.9	69.8	74.5	76.8	73.1	72.5	75.6	78.1	76.6	74.8	76.5	67.6	73.8
	4	65.6	69.2	72.5	76.9	63.4	74.9	76.0	71.0	71.3	73.2	77.9	75.8	71.3	75.1	66.4	72.0
	5	64.0	66.0	69.1	75.3	63.3	73.0	74.6	70.3	69.4	68.1	76.7	72.9	67.6	72.3	64.6	69.8

Table 16: Classification accuracy (%) on IID test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
BN adapt	57.9	59.3	57.3	72.4	58.2	70.3	72.1	65.1	65.0	58.5	73.5	69.7	64.3	67.1	58.8	64.6
ETA	63.2	65.3	66.9	75.1	63.2	73.1	74.9	70.0	69.7	66.9	76.5	73.6	67.7	72.0	64.0	69.5
LAME	24.1	29.0	59.2	69.0	42.8	67.0	68.9	58.3	50.7	46.5	67.6	39.2	60.3	21.4	56.7	50.7
CoTTA	60.0	61.8	60.1	72.6	60.2	70.5	72.3	64.8	65.5	56.7	73.6	69.9	64.3	68.4	62.6	65.5
CoTTA*	60.0	62.2	60.8	73.2	62.3	71.9	73.7	67.0	67.9	59.8	75.4	72.9	67.5	72.0	66.6	67.5
PL	61.8	64.5	65.0	74.6	62.0	72.1	74.2	68.9	68.4	64.8	75.5	72.0	66.8	70.8	61.9	68.2
PL+DELTA	62.8	64.8	66.3	74.3	62.7	72.7	74.6	69.4	68.5	65.7	75.5	72.8	66.8	71.3	62.7	68.7
TENT	62.8	65.4	66.3	74.8	62.3	72.8	74.6	69.6	68.6	66.8	76.1	72.3	67.3	71.6	63.5	69.0
TENT+TBR	62.5	64.9	67.0	74.8	62.1	72.9	74.3	69.8	68.3	66.8	76.6	72.0	67.1	71.9	63.0	68.9
TENT+DOT	63.6	65.7	66.9	75.1	63.0	73.1	74.8	69.8	69.0	67.1	76.2	73.2	67.6	71.8	63.8	69.4
TENT+DELTA	63.5	65.7	67.8	75.1	63.3	73.1	74.7	70.3	69.3	67.4	76.8	72.8	67.8	72.3	63.6	69.6
Ent-W	63.5	65.5	67.2	75.1	63.2	73.1	74.8	70.1	69.8	67.1	76.6	73.5	67.7	72.0	64.1	69.6
Ent-W+TBR+Div-W(0.05)	60.3	63.5	63.8	73.5	60.8	71.8	73.7	68.6	66.2	63.8	74.9	71.8	66.7	69.9	61.7	67.4
Ent-W+TBR+Div-W(0.1)	63.5	65.3	67.0	75.2	62.7	72.8	74.7	70.0	69.4	66.7	76.1	73.2	67.1	71.7	63.8	69.3
Ent-W+TBR+Div-W(0.2)	63.8	65.6	68.1	75.3	63.1	73.4	75.0	70.7	70.0	67.4	77.0	73.5	67.3	72.5	64.1	69.7
Ent-W+TBR+Div-W(0.4)	63.6	65.4	68.2	75.3	63.1	73.3	75.0	70.8	69.9	67.3	76.9	73.6	67.1	72.6	64.0	69.7
Ent-W+TBR+LA	64.0	65.9	68.4	75.4	63.5	73.6	75.1	71.0	70.2	67.6	77.0	73.8	67.6	72.8	64.5	70.0
Ent-W+TBR+Sample-drop	64.1	66.2	68.6	75.8	63.8	73.5	75.5	70.9	70.2	67.7	77.0	73.9	68.2	72.8	64.4	70.2
Ent-W+DELTA	64.2	66.1	68.5	75.6	63.6	73.5	75.2	71.2	70.3	68.0	77.1	74.0	68.0	72.8	64.7	70.2

Table 17: Classification accuracy (%) on non-IID ($\rho = 1.0$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
BN adapt	47.2	47.8	46.2	59.5	47.2	57.4	58.8	52.2	53.2	46.7	59.9	57.4	51.9	54.4	46.9	52.4
ETA	50.1	51.2	52.6	60.3	49.4	58.7	60.2	55.2	54.7	51.2	61.0	58.0	53.2	56.8	50.1	54.9
LAME	28.0	34.2	68.6	80.1	52.1	78.6	80.7	70.5	61.1	57.4	79.3	49.2	73.3	26.1	68.7	60.5
CoTTA	49.1	51.2	49.7	57.7	49.3	56.8	58.6	52.8	53.6	46.6	60.0	53.6	52.6	57.3	50.9	53.3
CoTTA*	49.1	51.3	49.5	57.4	49.8	56.6	58.4	53.1	54.1	46.9	59.1	54.2	53.3	57.1	52.8	53.5
PL	49.9	50.5	51.5	60.0	48.3	58.2	60.4	54.2	54.6	50.4	60.7	57.4	53.0	56.5	49.2	54.3
PL+DELTA	61.3	62.9	64.4	73.9	61.8	71.7	74.0	68.1	68.0	63.9	74.9	71.2	66.2	70.1	62.2	67.6
TENT	49.3	50.7	52.6	59.9	48.7	57.8	59.5	53.8	53.5	50.7	60.2	56.8	52.7	56.1	49.4	54.1
TENT+DELTA	62.3	64.4	66.7	74.5	62.6	72.0	74.3	68.9	68.5	65.8	75.6	72.0	66.8	71.4	63.4	68.6
Ent-W	50.0	51.3	52.9	60.3	49.3	58.9	60.3	54.9	54.9	51.1	61.0	57.8	53.1	56.7	50.0	54.8
Ent-W+DELTA	62.7	64.9	67.4	74.6	62.7	72.6	74.4	69.6	69.2	66.1	75.7	72.4	66.8	71.7	64.2	69.0

Table 18: Classification accuracy (%) on non-IID ($\rho = 0.5$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
BN adapt	43.8	45.2	43.9	56.2	44.5	54.7	55.5	49.1	50.0	43.9	57.0	54.2	48.7	51.2	45.0	49.5
ETA	45.8	47.5	48.9	56.4	45.3	54.5	55.8	51.2	51.2	48.1	57.4	53.8	49.4	53.1	45.9	50.9
LAME	28.5	34.8	69.7	80.8	53.5	79.6	81.8	71.9	62.7	58.6	81.1	50.6	74.5	26.9	69.5	61.6
CoTTA	46.9	48.3	46.5	55.1	46.6	54.2	55.2	49.3	50.6	43.4	56.9	50.8	49.3	54.2	48.3	50.4
CoTTA*	46.9	48.4	46.5	54.5	47.2	53.8	54.4	50.0	51.2	43.9	56.1	51.5	50.3	53.9	49.4	50.5
PL	45.4	47.0	47.8	56.0	45.5	54.5	55.7	50.8	51.3	47.2	57.1	52.6	49.4	52.7	45.9	50.6
PL+DELTA	61.3	62.5	63.2	73.1	61.3	70.8	73.6	68.0	67.0	63.3	74.5	70.0	65.7	69.7	61.2	67.0
TENT	44.8	46.7	48.4	55.9	45.5	54.0	55.2	50.0	50.1	47.3	56.6	52.2	48.4	52.6	45.6	50.2
TENT+TBR	59.7	62.4	64.6	73.3	60.7	70.7	72.9	67.3	66.6	64.2	74.2	68.9	65.0	69.5	61.0	66.7
TENT+DOT	45.9	47.5	49.3	56.8	46.4	54.8	55.8	50.8	51.1	48.2	57.4	53.6	49.6	53.0	46.4	51.1
TENT+DELTA	61.3	63.5	65.5	73.9	62.2	71.5	73.8	68.3	67.5	65.6	74.8	70.8	66.1	70.4	62.0	67.8
Ent-W	45.8	47.5	49.0	56.3	45.5	54.5	55.6	51.6	51.1	48.3	57.2	53.8	49.3	53.0	45.9	51.0
Ent-W+TBR+Div-W(0.05)	61.5	64.0	64.1	73.8	60.7	71.7	73.5	67.6	68.2	64.2	74.8	71.0	66.4	70.3	62.2	67.6
Ent-W+TBR+Div-W(0.1)	62.4	63.9	65.7	74.3	61.9	71.8	73.8	68.3	68.5	65.0	75.0	71.1	66.2	70.5	62.4	68.1
Ent-W+TBR+Div-W(0.2)	61.0	63.5	65.5	73.6	60.8	71.2	72.9	68.0	67.9	65.1	74.5	70.7	65.7	70.2	62.2	67.5
Ent-W+TBR+Div-W(0.4)	60.5	63.4	65.2	73.4	60.3	71.2	72.9	67.6	67.9	65.0	74.4	70.6	65.3	69.9	61.8	67.3
Ent-W+TBR+LA	60.0	62.8	64.2	72.3	59.5	69.9	71.7	66.8	66.8	63.9	73.3	69.4	64.7	69.1	61.0	66.4
Ent-W+TBR+Sample-drop	61.9	64.2	65.6	74.2	61.8	71.7	73.8	68.3	68.4	65.5	74.9	71.4	66.2	70.7	62.7	68.1
Ent-W+DELTA	61.9	64.2	66.0	74.3	61.9	71.9	73.9	68.3	68.5	65.9	74.9	71.5	66.4	70.9	62.9	68.2

Table 19: Classification accuracy (%) on non-IID ($\rho = 0.1$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	27.0	32.0	60.6	70.7	45.9	69.2	71.2	60.5	54.2	49.7	70.5	44.9	62.8	25.3	58.8	53.5
BN adapt	31.5	32.8	31.4	40.4	31.0	39.3	40.0	35.3	35.7	31.5	40.7	38.0	34.5	36.7	31.7	35.4
ETA	31.2	32.2	32.6	38.4	30.4	37.7	38.4	34.6	34.7	32.2	39.4	36.3	33.2	36.3	31.2	34.6
LAME	30.3	36.9	73.2	84.3	57.2	83.3	85.0	76.7	66.4	63.1	84.7	54.3	79.2	28.6	73.9	65.1
CoTTA	33.7	34.8	34.1	39.5	33.2	39.3	40.1	36.3	36.8	31.8	39.9	36.8	35.8	39.6	35.3	36.5
CoTTA*	33.7	35.0	33.7	39.0	33.2	38.7	39.4	35.8	36.6	31.8	39.1	36.1	35.6	38.8	35.5	36.1
PL	32.2	32.0	32.5	39.2	30.7	37.8	39.2	35.0	35.0	32.1	39.5	36.8	33.5	36.9	31.2	34.9
PL+DELTA	59.2	61.0	61.6	72.0	58.8	70.1	72.2	66.2	65.2	61.6	72.8	69.2	63.5	67.4	59.6	65.4
TENT	29.9	31.1	32.1	37.8	30.0	36.6	37.6	33.6	33.3	31.4	38.1	34.4	32.0	36.0	30.1	33.6
TENT+DELTA	60.3	62.7	63.1	72.7	60.2	70.7	72.1	66.7	65.9	63.4	73.6	69.8	64.5	68.5	60.2	66.3
Ent-W	31.0	32.1	32.7	38.3	30.1	37.7	38.5	34.5	34.5	32.0	39.3	36.0	32.9	36.2	30.6	34.4
Ent-W+DELTA	60.2	62.3	63.5	72.3	59.6	70.0	72.3	67.3	66.3	63.2	73.7	70.3	64.2	69.2	60.5	66.3

Table 20: Classification accuracy (%) on CI ($\pi = 0.1$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	26.2	31.7	60.1	70.3	45.7	69.5	71.2	60.1	53.9	49.7	69.7	45.1	62.5	25.6	58.9	53.3
BN adapt	58.0	58.8	56.7	71.6	58.3	69.6	71.5	64.9	65.1	58.6	72.9	68.7	64.4	66.3	58.5	64.3
ETA	62.6	63.7	65.2	73.6	62.9	71.6	73.8	68.6	68.9	65.6	75.2	72.1	65.9	70.7	62.7	68.2
LAME	23.5	28.6	59.4	68.8	43.3	67.1	68.8	58.2	50.9	46.6	67.1	39.4	60.4	21.6	56.7	50.7
CoTTA	59.8	61.3	59.7	71.8	59.8	69.6	71.6	64.4	65.3	56.5	73.1	68.5	64.2	68.2	62.5	65.1
CoTTA*	59.8	61.9	60.1	72.0	61.7	70.9	72.6	66.2	67.4	59.1	74.5	71.3	67.3	71.5	66.3	66.8
PL	61.7	62.3	62.8	73.1	61.7	71.1	73.6	67.2	68.1	63.7	74.3	71.3	65.5	69.7	61.3	67.2
PL+DELTA	62.4	63.0	63.2	73.4	61.3	71.9	73.5	67.2	68.3	64.0	75.0	71.5	65.6	70.1	62.2	67.5
TENT	61.7	63.3	63.9	73.0	62.3	71.4	73.1	67.6	68.1	65.1	74.9	71.4	65.5	70.7	62.5	67.6
TENT+TBR	61.6	63.8	64.4	73.3	62.2	71.5	73.6	68.0	68.0	64.9	74.8	71.4	65.5	71.0	63.0	67.8
TENT+DOT	62.4	63.6	64.7	73.1	62.6	71.6	73.7	68.0	68.6	65.3	74.7	71.8	66.1	70.7	63.0	68.0
TENT+DELTA	62.5	64.3	65.3	73.8	62.4	71.3	73.6	68.3	69.0	66.1	75.1	71.6	66.2	71.1	63.9	68.3
Ent-W	62.5	63.8	65.2	73.6	62.9	71.7	73.7	68.5	68.9	65.5	75.3	72.0	66.3	70.7	62.9	68.2
Ent-W+TBR+Div-W(0.05)	61.1	62.0	62.6	73.0	60.8	71.1	73.1	66.9	66.9	63.4	74.1	70.2	65.6	68.6	60.5	66.7
Ent-W+TBR+Div-W(0.1)	62.5	63.5	64.8	73.7	62.8	72.0	74.2	68.5	68.7	65.5	75.2	71.7	66.7	70.7	62.4	68.2
Ent-W+TBR+Div-W(0.2)	63.3	64.1	66.2	73.9	63.2	72.0	73.8	68.9	69.5	65.8	75.7	72.5	66.8	71.2	62.9	68.7
Ent-W+TBR+Div-W(0.4)	62.7	63.7	65.7	73.5	62.9	71.8	74.2	68.3	69.5	65.5	75.6	73.1	66.5	70.9	62.9	68.5
Ent-W+TBR+LA	63.6	64.6	66.4	74.2	63.7	72.1	74.2	69.0	70.1	66.0	76.0	73.3	67.2	71.8	63.4	69.0
Ent-W+TBR+Sample-drop	63.3	64.6	65.8	73.8	63.6	72.2	74.0	69.5	69.7	66.4	75.6	72.5	67.0	71.5	63.1	68.8
Ent-W+DELTA	63.9	64.8	66.4	74.1	63.7	72.2	74.4	69.2	70.5	66.2	75.6	73.3	67.0	71.6	63.3	69.1

Table 21: Classification accuracy (%) on CI ($\pi = 0.05$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	26.2	31.8	60.5	70.5	46.4	68.9	70.6	59.8	53.7	50.3	70.4	44.9	61.8	24.7	58.2	53.3
BN adapt	56.7	58.0	55.5	71.4	57.5	69.5	71.1	64.7	64.1	57.5	72.5	69.0	63.1	66.2	58.0	63.6
ETA	61.3	63.2	64.6	73.6	61.5	72.2	73.3	68.1	67.7	65.0	74.4	71.4	65.6	70.2	62.8	67.7
LAME	23.2	28.9	59.0	67.9	43.8	66.7	67.8	58.2	50.5	47.1	67.7	39.8	59.7	20.6	56.9	50.5
CoTTA	58.4	60.6	58.8	71.6	58.2	69.4	71.2	63.5	64.2	55.6	72.5	68.6	62.4	67.9	61.0	64.3
CoTTA*	58.4	60.9	59.1	72.0	59.9	70.9	71.8	65.2	66.5	58.6	73.9	71.0	65.7	70.5	65.2	66.0
PL	60.4	62.1	62.9	72.8	60.8	71.4	72.7	67.7	67.1	62.6	73.5	71.3	65.4	69.4	61.4	66.8
PL+DELTA	61.0	63.1	62.8	73.2	61.8	71.6	73.2	67.9	67.6	63.5	74.2	71.4	65.3	69.6	62.0	67.2
TENT	61.0	63.4	64.0	73.3	60.6	71.7	73.2	68.7	66.9	64.9	73.9	71.0	65.1	70.0	62.0	67.3
TENT+DELTA	61.7	64.8	65.6	73.5	62.1	71.2	73.4	69.0	68.6	65.4	74.6	71.1	66.1	70.6	63.1	68.1
Ent-W	61.4	63.2	64.7	73.7	61.5	72.1	73.2	68.4	67.8	64.9	74.4	71.3	65.6	70.1	62.7	67.7
Ent-W+DELTA	62.8	64.4	65.6	74.4	62.5	72.3	74.1	69.1	68.9	66.2	75.5	73.0	66.1	71.7	63.0	68.6

Table 22: Classification accuracy (%) on CI&non-IID ($\rho = 0.5$, $\pi = 0.1$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	26.2	31.7	60.1	70.3	45.7	69.5	71.2	60.1	53.9	49.7	69.7	45.1	62.5	25.6	58.9	53.3
BN adapt	44.9	45.6	44.7	56.1	44.8	54.4	56.4	49.4	50.8	44.3	56.5	53.4	49.2	51.7	46.0	49.9
ETA	46.5	47.0	48.6	56.2	46.1	55.1	56.5	51.4	51.9	47.1	56.7	53.5	49.3	53.4	46.7	51.1
LAME	27.2	34.0	68.5	80.0	52.5	78.9	80.5	70.3	60.5	56.6	78.2	49.9	72.7	26.4	68.6	60.3
CoTTA	47.0	48.3	47.5	55.0	47.0	54.6	55.5	49.7	51.6	44.0	55.9	50.3	50.5	55.2	49.0	50.7
CoTTA*	47.0	48.3	47.6	54.7	48.0	54.1	54.7	49.7	51.7	45.1	55.2	50.1	50.6	54.7	50.6	50.8
PL	46.0	45.9	47.7	56.0	45.8	55.4	56.4	50.7	50.7	46.4	56.3	53.5	48.8	53.2	46.8	50.6
PL+DELTA	60.3	62.1	62.9	72.6	60.9	70.9	72.4	66.6	67.4	62.2	73.5	69.9	65.6	69.3	62.5	66.6
TENT	46.3	46.1	47.6	55.8	45.2	54.7	55.6	49.8	50.5	47.4	56.7	51.3	48.6	52.4	45.2	50.2
TENT+DELTA	62.5	63.7	64.9	73.5	62.2	70.8	72.1	67.6	68.0	65.7	75.0	70.5	66.6	69.9	63.4	67.8
Ent-W	46.7	46.9	48.7	56.1	46.1	55.0	56.3	51.2	51.9	47.7	57.1	53.5	49.2	53.2	46.6	51.1
Ent-W+DELTA	62.4	63.9	65.0	73.5	61.9	71.4	73.5	68.1	68.8	65.4	74.7	70.7	66.2	70.4	63.3	67.9

Table 23: Classification accuracy (%) on CI&non-IID ($\rho = 0.5$, $\pi = 0.05$) test stream of CIFAR100-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	26.2	31.8	60.5	70.5	46.4	68.9	70.6	59.8	53.7	50.3	70.4	44.9	61.8	24.7	58.2	53.3
BN adapt	43.0	45.0	42.3	55.4	44.0	54.2	54.9	49.1	49.4	43.8	56.2	53.1	48.5	51.3	44.3	49.0
ETA	45.4	46.4	46.8	56.2	45.3	54.7	54.8	50.7	50.1	46.5	56.4	52.2	48.8	53.0	45.5	50.2
LAME	27.1	33.3	67.6	78.7	51.7	77.1	78.9	68.5	59.7	56.0	77.5	49.3	70.1	25.1	66.6	59.2
CoTTA	46.5	47.3	45.3	54.5	45.5	53.7	55.0	48.6	49.9	42.4	56.0	49.0	49.1	53.5	47.2	49.6
CoTTA*	46.5	47.8	45.5	54.1	46.2	53.4	54.2	48.8	50.6	43.5	54.2	49.4	49.6	52.8	48.7	49.7
PL	44.3	45.8	46.4	55.8	45.2	54.2	54.8	50.7	49.3	45.8	56.5	52.4	49.1	52.0	45.5	49.9
PL+DELTA	59.3	61.1	62.2	71.6	59.4	70.3	70.8	66.3	65.5	61.4	74.0	69.0	64.5	67.5	59.8	65.5
TENT	44.7	46.7	45.7	55.3	44.6	53.8	53.7	50.0	48.6	46.1	55.5	50.0	48.9	52.0	44.6	49.3
TENT+TBR	58.8	61.6	62.5	72.2	58.6	70.3	70.9	67.0	64.8	62.5	73.5	68.1	63.4	68.5	59.4	65.5
TENT+DOT	45.2	47.1	46.7	55.6	45.4	54.3	54.3	50.9	49.7	47.3	56.1	51.7	49.2	52.9	45.5	50.1
TENT+DELTA	60.3	62.3	63.7	72.9	60.3	70.3	71.3	67.8	66.2	64.1	74.2	68.7	64.3	69.1	60.7	66.4
Ent-W	45.6	46.4	47.0	56.0	45.4	54.9	54.9	50.7	50.1	46.8	56.3	52.2	48.6	53.1	45.1	50.2
Ent-W+TBR+Div-W(0.05)	60.9	62.3	62.9	73.0	59.5	70.7	72.0	67.0	66.2	62.4	74.5	69.8	64.9	69.0	60.7	66.4
Ent-W+TBR+Div-W(0.1)	61.2	62.8	64.5	73.5	59.9	71.3	71.8	67.4	66.4	63.7	74.5	70.6	65.2	69.5	61.0	66.9
Ent-W+TBR+Div-W(0.2)	60.4	62.4	63.6	73.5	59.4	70.7	72.0	67.1	65.8	63.4	74.4	70.1	64.5	69.5	60.4	66.5
Ent-W+TBR+Div-W(0.4)	59.7	62.3	63.3	72.9	59.4	70.6	71.9	67.0	65.8	63.1	74.3	69.6	63.9	69.4	60.3	66.2
Ent-W+TBR+LA	59.2	61.6	62.3	71.9	58.9	69.5	71.3	65.7	65.1	62.8	73.2	69.0	63.3	68.2	60.0	65.5
Ent-W+TBR+Sample-drop	60.9	62.6	63.7	73.2	60.0	70.6	72.0	66.9	66.6	64.1	74.9	69.4	64.6	69.9	61.1	66.7
Ent-W+DELTA	61.2	62.9	64.0	73.7	60.4	71.1	72.3	67.4	67.0	64.2	74.7	70.2	64.7	69.8	61.0	67.0

Table 24: Classification accuracy (%) on IID test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.2	2.9	1.9	17.9	9.8	14.8	22.5	16.9	23.3	24.4	58.9	5.4	17.0	20.6	31.6	18.0
TTA	4.1	4.9	4.5	12.5	8.2	12.9	25.8	14.0	19.1	21.3	53.0	12.4	14.6	24.6	33.6	17.7
BN adapt	15.2	15.8	15.8	15.0	15.3	26.4	38.8	34.3	33.1	47.8	65.3	16.8	43.9	48.9	39.7	31.5
MEMO	7.5	8.7	9.0	19.7	13.0	20.7	27.6	25.3	28.8	32.1	61.0	11.0	23.8	33.0	37.5	23.9
ETA	35.6	37.5	36.2	33.7	33.1	47.7	52.5	51.9	45.8	60.0	67.8	44.7	57.8	60.9	55.2	48.0
LAME	1.6	2.4	1.3	17.6	9.1	13.9	21.9	15.6	22.5	22.8	58.6	5.2	15.2	19.9	31.1	17.2
CoTTA	17.6	18.0	17.4	15.6	18.2	31.2	43.6	36.6	35.1	53.0	66.5	19.5	46.3	54.9	42.6	34.4
CoTTA*	17.6	22.1	24.3	19.8	22.7	29.7	38.1	36.0	37.2	45.2	60.1	26.4	46.6	53.4	46.8	35.1
PL	26.2	26.2	27.0	25.2	24.3	37.2	46.5	43.3	39.5	55.0	66.7	30.2	51.2	55.7	49.1	40.2
PL+DELTA	27.7	29.4	28.5	27.0	26.1	38.1	47.9	44.1	40.7	55.9	67.4	34.1	52.9	56.6	50.3	41.8
TENT	28.7	30.5	30.1	28.0	27.2	41.4	49.4	47.2	41.2	57.4	67.4	26.5	55.4	58.5	52.5	42.7
TENT+TBR	29.5	31.4	30.9	28.8	28.0	41.9	50.3	47.7	41.8	58.3	68.1	26.9	55.4	59.3	53.3	43.5
TENT+DOT	30.5	32.3	31.6	29.6	29.3	42.5	49.9	47.8	42.2	57.5	67.5	37.5	55.4	58.8	52.9	44.4
TENT+DELTA	31.2	33.1	32.1	30.5	30.2	42.9	50.9	48.2	43.0	58.5	68.1	37.9	56.2	59.5	53.6	45.1
Ent-W	34.5	29.0	33.1	29.6	26.3	47.4	52.2	51.9	45.6	59.9	67.8	17.8	57.8	60.9	55.0	44.6
Ent-W+TBR+Div-W(0.05)	36.1	37.9	37.8	34.4	33.5	49.1	53.3	53.2	46.7	60.9	68.5	45.1	58.9	61.7	56.0	48.9
Ent-W+TBR+Div-W(0.1)	35.3	37.3	36.3	33.6	32.2	49.1	53.4	53.1	46.6	61.0	68.4	43.1	58.7	61.7	55.9	48.4
Ent-W+TBR+Div-W(0.2)	32.5	35.4	33.5	26.7	25.8	48.9	53.0	52.9	46.2	60.9	68.4	31.1	58.7	61.7	56.0	46.1
Ent-W+TBR+Div-W(0.4)	28.7	32.8	31.7	20.3	19.3	48.9	53.0	52.7	46.2	60.8	68.4	13.9	58.7	61.7	56.0	43.5
Ent-W+TBR+LA	26.7	22.4	29.6	20.3	20.0	49.2	53.4	52.9	46.7	60.7	68.0	10.1	58.8	61.5	56.0	42.4
Ent-W+TBR+Sample-drop	37.0	38.9	38.2	35.8	35.4	49.6	53.8	53.3	47.4	61.0	68.5	46.4	59.1	62.0	56.4	49.5
Ent-W+DELTA	38.1	39.6	39.0	36.3	36.5	49.9	54.0	53.5	47.6	61.1	68.4	46.9	59.2	61.9	56.6	49.9

Table 25: Classification accuracy (%) on IID test stream of ImageNet-C with different architectures.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
ResNet18																
Source	1.2	1.8	1.0	11.4	8.7	11.2	17.6	10.9	16.5	14.3	51.3	3.4	16.8	23.1	29.6	14.6
TENT	22.3	24.7	22.2	20.3	21.1	32.2	41.1	37.8	33.7	49.0	59.2	19.5	46.9	50.6	45.8	35.1
TENT+DELTA	24.5	26.8	24.4	22.6	23.7	34.0	42.7	38.9	35.4	50.2	60.3	27.5	48.5	51.9	47.0	37.2
Ent-W	27.1	30.7	24.3	22.3	17.5	37.6	44.2	42.5	37.8	51.5	59.9	5.5	49.5	52.9	48.5	36.8
Ent-W+DELTA	31.7	33.8	32.0	29.0	30.3	40.2	46.1	44.2	39.7	53.1	60.9	36.9	51.5	54.7	49.8	42.3
ResNet50																
Source	2.2	2.9	1.9	17.9	9.8	14.8	22.5	16.9	23.3	24.4	58.9	5.4	17.0	20.6	31.6	18.0
TENT	28.7	30.5	30.1	28.0	27.2	41.4	49.4	47.2	41.2	57.3	67.4	26.7	54.6	58.5	52.5	42.7
TENT+DELTA	31.2	33.1	32.1	30.5	30.2	42.9	50.9	48.2	43.0	58.5	68.1	37.9	56.2	59.5	53.6	45.1
Ent-W	34.5	29.0	33.1	29.6	26.3	47.4	52.2	51.9	45.6	59.9	67.8	17.8	57.8	60.9	55.0	44.6
Ent-W+DELTA	38.1	39.6	39.0	36.3	36.5	49.9	54.0	53.5	47.6	61.1	68.4	46.9	59.2	61.9	56.6	49.9
ResNet101																
Source	3.5	4.3	3.5	21.9	13.1	19.2	26.5	21.0	26.7	28.1	61.4	7.2	24.3	35.0	42.3	22.5
TENT	32.6	34.0	33.2	32.2	32.4	45.1	53.0	50.8	45.0	59.6	69.1	33.8	58.6	61.1	55.8	46.4
TENT+DELTA	35.1	37.4	35.6	34.9	35.1	46.8	54.6	51.8	46.7	60.7	69.8	42.6	60.1	62.3	57.2	48.7
Ent-W	36.1	20.8	37.3	33.6	31.7	50.3	55.6	54.9	46.8	62.4	69.8	19.7	61.1	63.2	58.2	46.8
Ent-W+DELTA	40.9	43.0	41.9	39.8	40.1	53.1	57.4	56.5	50.8	63.4	70.2	50.6	62.3	64.2	59.8	53.0
ResNet152																
Source	3.6	4.4	3.3	22.1	11.9	24.8	25.5	22.1	28.9	27.7	63.1	5.2	24.9	27.1	42.2	22.5
TENT	34.0	36.8	35.3	34.1	34.0	46.9	54.0	52.4	47.0	61.3	70.7	35.5	59.9	62.4	57.2	48.1
TENT+DELTA	36.6	39.2	37.7	36.7	36.3	48.7	55.6	54.0	48.4	62.4	71.2	44.0	61.3	63.3	58.4	50.2
Ent-W	38.7	33.4	34.6	36.6	33.2	52.9	57.4	56.9	46.5	64.2	71.0	29.3	62.7	64.8	60.0	49.5
Ent-W+DELTA	42.6	45.4	44.5	42.0	42.2	55.5	58.9	58.5	52.7	65.5	71.4	51.9	63.7	65.8	61.2	54.8
WideResNet50																
TENT	34.5	37.2	34.7	30.6	31.6	45.2	52.0	51.1	45.8	60.5	69.9	38.4	58.3	61.7	54.9	47.1
TENT+DELTA	36.7	39.6	37.2	33.5	34.6	47.4	54.5	53.0	47.6	62.2	71.2	44.1	60.3	63.4	56.9	49.5
Ent-W	34.0	37.1	33.6	25.0	27.7	51.0	54.7	55.5	49.9	62.8	70.4	24.9	60.7	63.9	57.6	47.3
Ent-W+DELTA	41.1	44.9	42.9	38.6	39.3	53.4	57.3	57.6	51.8	64.7	71.4	52.0	62.4	65.7	59.8	53.5
ResNeXt50																
TENT	33.3	36.2	34.2	32.3	30.9	45.5	52.2	51.1	45.9	59.6	69.3	39.0	57.1	61.5	53.8	46.8
TENT+DELTA	35.3	38.5	36.1	34.5	33.5	46.6	53.7	52.1	47.0	60.5	69.9	43.9	58.4	62.4	55.0	48.5
Ent-W	31.4	37.5	34.7	34.0	25.2	51.0	54.6	55.1	49.1	62.2	70.0	49.1	60.3	64.3	57.1	49.0
Ent-W+DELTA	40.7	43.6	42.0	39.5	39.1	53.1	56.7	56.6	51.1	63.2	70.4	50.7	61.5	64.9	58.2	52.8

Table 26: Classification accuracy (%) on non-IID ($\rho = 1.0$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.2	2.9	1.9	17.9	9.8	14.8	22.5	16.9	23.3	24.4	58.9	5.4	17.0	20.6	31.6	18.0
BN adapt	10.6	10.9	10.9	10.2	10.3	17.5	25.8	23.5	23.1	33.0	46.5	11.3	30.2	33.3	27.0	21.6
ETA	17.0	19.2	18.2	14.1	12.0	25.9	31.1	30.9	26.8	38.6	46.1	18.9	36.0	38.7	33.5	27.1
LAME	1.8	2.7	1.5	22.4	11.3	17.2	28.4	19.8	28.4	29.8	74.4	5.9	20.0	25.6	40.4	22.0
CoTTA	12.2	12.5	12.8	9.5	11.2	19.7	28.4	24.7	23.9	35.9	47.4	12.8	31.1	37.0	28.4	23.2
CoTTA*	12.2	14.9	16.2	12.3	14.2	18.9	24.2	24.4	25.2	30.0	41.5	15.3	30.8	35.5	31.2	23.1
PL	15.9	15.6	16.4	14.4	13.9	23.1	29.8	28.1	26.2	37.3	47.2	12.8	34.2	37.2	32.2	25.6
PL+DELTA	26.3	27.4	27.1	25.5	25.1	37.4	46.5	43.0	39.8	54.8	66.6	32.7	51.4	55.6	48.6	40.5
TENT	16.1	16.8	16.8	15.1	14.1	23.3	30.2	28.8	24.9	37.5	46.7	9.3	34.9	37.8	33.0	25.7
TENT+DELTA	29.6	31.7	30.4	29.1	28.6	41.5	49.8	47.0	42.1	57.6	67.5	35.7	54.9	58.5	52.0	43.7
Ent-W	4.2	2.8	3.1	2.9	3.6	11.3	20.2	20.0	12.5	34.4	44.7	1.7	32.0	37.1	21.5	16.8
Ent-W+DELTA	35.6	37.9	36.0	34.4	34.4	47.9	52.8	51.9	46.5	60.1	67.8	44.2	57.9	60.8	55.4	48.3

Table 27: Classification accuracy (%) on non-IID ($\rho = 0.5$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.2	2.9	1.9	17.9	9.8	14.8	22.5	16.9	23.3	24.4	58.9	5.4	17.0	20.6	31.6	18.0
BN adapt	9.6	9.9	9.8	8.8	9.1	15.8	22.8	21.0	20.8	29.5	41.9	10.3	26.7	29.5	24.2	19.3
ETA	13.9	15.5	13.3	11.1	10.3	21.4	26.2	26.1	22.9	33.4	40.5	13.4	30.9	33.2	29.3	22.8
LAME	1.9	2.8	1.6	23.6	11.7	17.8	29.4	20.4	29.4	30.5	76.1	6.2	20.8	26.4	41.5	22.7
CoTTA	10.8	11.0	11.0	7.8	10.4	17.4	25.0	22.0	21.6	32.0	42.6	9.9	27.9	32.5	25.8	20.5
CoTTA*	10.8	13.3	14.3	11.0	12.9	17.1	22.0	21.8	22.8	27.6	38.0	14.8	27.8	32.6	28.0	21.0
PL	14.2	13.4	14.5	12.5	11.5	20.0	26.3	24.9	23.4	33.2	42.4	11.1	30.5	33.1	28.5	22.6
PL+DELTA	25.6	27.3	26.2	25.2	24.6	36.0	45.7	42.9	39.3	54.4	66.5	31.0	50.6	55.0	47.9	39.9
TENT	13.9	14.6	14.5	12.6	11.7	19.0	26.1	25.2	21.5	33.2	41.6	6.5	30.5	33.1	28.9	22.2
TENT+TBR	27.3	28.5	28.2	26.0	25.4	38.9	48.5	46.0	39.6	57.1	67.3	18.5	53.6	57.6	51.2	40.9
TENT+DOT	15.5	16.5	15.9	14.2	14.0	20.9	27.1	25.9	23.5	33.7	41.8	15.2	31.4	33.5	29.5	23.9
TENT+DELTA	29.1	30.9	29.7	28.2	27.8	40.3	49.0	46.7	41.5	57.3	67.3	33.9	54.4	58.1	51.6	43.1
Ent-W	2.9	2.5	3.5	1.4	1.0	7.1	11.9	15.1	8.5	27.7	37.0	1.3	22.2	31.1	20.1	12.9
Ent-W+TBR+Div-W(0.05)	32.4	34.6	33.3	27.2	28.3	45.2	51.3	50.5	44.3	59.3	67.4	36.0	57.0	60.1	54.3	45.4
Ent-W+TBR+Div-W(0.1)	30.1	33.4	31.1	25.5	21.7	44.8	51.1	50.4	43.4	59.3	67.4	16.3	56.9	60.2	54.3	43.1
Ent-W+TBR+Div-W(0.2)	23.7	30.5	26.5	19.7	12.2	44.3	51.1	50.5	41.1	59.4	67.4	7.0	56.8	60.2	54.2	40.3
Ent-W+TBR+Div-W(0.4)	17.1	15.3	22.2	11.2	4.8	43.7	51.1	50.2	36.5	59.5	67.4	6.1	56.7	60.3	54.2	37.1
Ent-W+TBR+LA	10.9	7.2	14.3	5.1	5.0	35.0	39.9	39.3	23.2	46.8	53.6	4.1	44.6	47.2	42.4	27.9
Ent-W+TBR+Sample-drop	33.7	36.4	35.1	31.9	30.8	46.7	52.2	51.2	45.6	60.0	67.6	40.4	57.3	60.6	54.7	46.9
Ent-W+DELTA	34.9	37.5	35.8	32.7	32.3	46.7	52.3	51.5	46.0	59.7	67.3	42.8	57.3	60.4	54.9	47.5

Table 28: Classification accuracy (%) on non-IID ($\rho = 0.1$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.2	2.9	1.9	17.9	9.8	14.8	22.5	16.9	23.3	24.4	58.9	5.4	17.0	20.6	31.6	18.0
BN adapt	6.3	6.4	6.2	5.6	5.6	9.8	13.9	13.6	13.4	18.4	26.1	6.4	16.5	18.1	15.0	12.1
ETA	4.6	5.2	5.1	2.3	2.8	7.0	12.3	11.6	10.9	17.5	22.5	2.3	14.5	17.1	14.4	10.0
LAME	1.9	2.9	1.6	26.2	12.8	19.8	32.7	22.8	32.5	33.8	80.0	6.6	22.5	29.0	45.5	24.7
CoTTA	7.1	7.0	7.1	5.0	6.2	10.5	15.0	14.1	13.7	19.3	26.5	6.4	17.1	19.6	15.8	12.7
CoTTA*	7.1	8.2	8.7	6.3	7.3	10.3	13.4	14.3	14.5	17.9	23.7	7.9	16.9	19.4	17.3	12.9
PL	7.7	7.6	8.3	6.4	6.1	10.8	15.4	15.0	14.0	20.0	25.9	5.0	17.5	19.4	17.0	13.1
PL+DELTA	23.4	24.6	24.0	22.0	21.5	33.3	43.4	40.0	37.3	52.2	65.0	26.1	47.8	52.5	45.4	37.2
TENT	7.4	7.8	7.8	6.2	5.9	8.9	14.7	12.5	11.6	19.0	24.5	3.0	16.8	18.5	16.5	12.1
TENT+DELTA	26.7	28.2	27.3	25.0	24.8	37.1	46.6	43.6	39.6	55.1	65.7	27.2	51.6	55.6	49.0	40.2
Ent-W	1.5	0.6	1.4	1.1	0.8	2.3	4.6	4.4	3.1	8.4	15.5	0.5	7.0	9.7	5.7	4.4
Ent-W+DELTA	30.4	33.1	31.4	26.8	28.1	42.2	48.9	48.2	42.6	56.9	65.4	31.5	54.4	57.8	51.5	43.3

Table 29: Classification accuracy (%) on CI ($\pi = 0.1$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.4	3.0	1.9	17.8	9.7	14.7	22.4	16.5	23.1	24.2	58.9	5.5	16.9	20.4	31.5	17.9
BN adapt	15.0	15.8	15.4	14.7	15.1	25.6	39.1	34.4	33.2	47.8	65.1	17.5	44.4	48.8	39.8	31.5
ETA	34.6	36.7	35.7	33.1	32.5	46.5	51.9	51.3	45.4	59.5	67.6	44.8	57.3	60.9	55.1	47.5
LAME	1.8	2.5	1.5	17.5	9.0	13.9	21.8	15.1	22.3	22.6	58.5	5.3	14.9	19.8	30.9	17.2
CoTTA	17.1	17.8	17.5	15.9	16.7	30.2	43.2	36.8	35.7	51.9	66.4	17.7	47.1	54.0	42.8	34.1
CoTTA*	17.1	22.0	24.1	19.0	22.2	28.0	35.7	35.2	35.8	42.8	57.8	22.9	44.8	50.4	45.3	33.5
PL	24.9	24.8	25.9	24.3	23.4	36.2	45.7	42.3	39.5	54.6	66.5	28.6	49.9	55.5	48.5	39.4
PL+DELTA	26.4	27.7	27.0	26.3	24.9	37.5	46.9	43.3	40.2	55.3	66.8	33.3	52.1	56.5	49.8	40.9
TENT	27.8	29.3	29.2	28.1	26.6	40.8	48.7	46.5	41.0	57.2	67.3	25.7	53.6	58.2	51.9	42.1
TENT+TBR	28.5	30.1	29.7	28.7	27.3	41.3	49.9	47.0	41.7	57.6	67.9	25.1	54.5	59.0	52.9	42.7
TENT+DOT	29.8	31.6	30.9	29.4	28.8	41.7	49.4	47.0	42.1	57.3	67.3	36.8	54.9	58.6	52.4	43.9
TENT+DELTA	30.7	32.5	31.3	30.3	29.3	42.0	50.5	47.5	42.9	57.8	67.7	36.4	55.7	59.2	53.1	44.4
Ent-W	23.2	21.7	29.4	19.1	19.6	46.7	51.7	51.0	39.0	58.9	67.5	10.1	57.2	60.5	54.9	40.7
Ent-W+TBR+Div-W(0.05)	34.1	37.4	36.4	32.5	32.9	47.7	52.9	52.1	45.7	60.0	67.9	42.6	57.8	61.7	55.7	47.8
Ent-W+TBR+Div-W(0.1)	34.5	36.1	35.9	32.4	32.0	48.0	52.9	52.1	45.8	59.8	68.0	40.2	57.9	61.5	55.7	47.5
Ent-W+TBR+Div-W(0.2)	32.5	34.1	35.3	30.0	29.7	47.6	52.7	51.9	45.5	59.7	68.0	30.2	57.9	61.5	55.7	46.1
Ent-W+TBR+Div-W(0.4)	29.2	27.5	34.3	27.4	25.1	47.8	52.8	51.8	44.7	59.5	68.0	6.1	58.0	61.4	55.8	43.3
Ent-W+TBR+LA	24.8	23.5	34.6	25.1	20.4	48.2	52.9	52.2	45.0	59.7	67.3	4.2	58.0	61.3	55.8	42.2
Ent-W+TBR+Sample-drop	36.1	37.8	37.3	33.7	33.2	47.3	52.9	52.1	46.0	59.7	68.0	43.7	57.9	61.5	55.5	48.2
Ent-W+DELTA	36.6	38.6	37.8	34.9	34.4	47.7	52.6	51.9	46.1	59.5	67.4	44.6	57.9	60.9	55.4	48.4

Table 30: Classification accuracy (%) on CI ($\pi = 0.05$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.2	2.9	1.9	18.0	10.0	14.6	22.5	16.6	23.1	24.4	58.4	5.5	16.9	20.6	31.5	17.9
BN adapt	15.1	15.2	15.6	14.9	15.8	25.6	39.0	34.6	33.2	47.8	64.7	17.2	44.1	48.2	39.9	31.4
ETA	34.2	36.1	35.0	32.0	32.0	46.1	52.0	50.6	45.0	59.4	67.3	43.4	57.0	60.3	54.5	47.0
LAME	1.6	2.4	1.4	17.7	9.1	13.9	21.9	15.4	22.3	22.7	58.0	5.2	15.1	19.8	30.9	17.2
CoTTA	17.3	17.4	17.8	15.4	17.1	29.8	43.1	37.5	35.4	51.9	65.8	19.3	46.8	53.3	42.5	34.0
CoTTA*	17.3	21.6	23.8	19.9	22.9	29.3	37.4	35.7	36.6	44.5	59.0	24.2	45.5	51.8	45.9	34.4
PL	24.2	24.6	25.8	24.7	23.5	36.2	45.8	42.7	38.9	54.3	65.9	27.0	49.0	55.0	48.0	39.0
PL+DELTA	26.1	27.3	27.1	25.8	25.3	36.2	46.8	43.2	39.9	54.8	66.4	32.6	51.1	55.4	48.8	40.5
TENT	27.1	29.0	28.8	27.7	27.1	40.3	49.1	46.4	40.7	57.1	66.6	24.8	53.1	57.8	51.3	41.8
TENT+DELTA	30.1	32.3	31.2	29.6	29.6	41.4	50.0	47.4	42.4	57.6	67.2	35.3	55.1	58.5	52.6	44.0
Ent-W	17.2	13.4	25.6	15.8	12.1	45.9	51.0	50.4	44.6	59.3	66.9	10.0	56.5	60.0	54.1	38.9
Ent-W+DELTA	35.7	38.2	37.1	34.1	33.8	46.5	51.7	51.1	45.6	58.4	66.0	43.5	57.0	59.3	54.5	47.5

Table 31: Classification accuracy (%) on CI&non-IID ($\rho = 0.5, \pi = 0.1$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.4	3.0	1.9	17.8	9.7	14.7	22.4	16.5	23.1	24.2	58.9	5.5	16.9	20.4	31.5	17.9
BN adapt	9.7	10.1	10.1	9.3	9.5	16.1	24.2	21.7	21.4	30.8	43.5	11.2	27.0	30.9	25.7	20.1
ETA	11.9	12.7	12.7	8.6	7.3	18.8	27.1	25.9	22.8	34.0	41.9	7.9	30.7	34.9	30.3	21.8
LAME	2.0	2.8	1.5	22.4	11.4	17.1	27.5	19.4	28.0	29.5	73.1	6.0	19.8	24.9	40.0	21.7
CoTTA	11.4	11.6	11.7	9.8	10.4	17.9	26.4	22.9	22.6	33.3	44.4	11.6	28.6	33.8	27.3	21.6
CoTTA*	11.4	13.9	14.9	11.7	13.3	17.9	22.8	22.7	23.5	29.2	39.4	14.6	28.2	33.1	29.6	21.7
PL	14.4	12.5	14.0	12.6	11.8	20.2	27.2	25.3	24.1	34.1	43.9	10.7	29.8	34.2	29.8	23.0
PL+DELTA	24.8	25.5	25.4	23.6	23.0	34.9	44.8	41.0	38.8	53.2	65.9	29.6	49.7	54.1	47.3	38.8
TENT	12.9	13.9	14.3	12.8	11.7	18.5	27.0	25.0	21.7	34.1	42.9	6.6	30.1	34.5	30.1	22.4
TENT+DELTA	28.3	30.1	29.1	27.5	27.2	39.3	48.3	45.2	41.2	56.3	66.8	31.0	53.6	57.2	51.2	42.2
Ent-W	1.6	1.6	2.4	2.3	1.3	5.6	12.9	13.5	11.1	16.7	40.4	1.1	16.8	17.4	16.6	10.8
Ent-W+DELTA	32.2	35.0	34.1	30.5	29.4	44.8	50.7	49.5	44.5	58.1	66.6	36.6	55.7	58.4	53.7	45.3

Table 32: Classification accuracy (%) on CI&non-IID ($\rho = 0.5, \pi = 0.05$) test stream of ImageNet-C.

Method	Gauss	Shot	Impul	Defoc	Glass	Motion	Zoom	Snow	Frost	Fog	Brit	Contr	Elastic	Pixel	JPEG	Avg
Source	2.2	2.9	1.9	18.0	10.0	14.6	22.5	16.6	23.1	24.4	58.4	5.5	16.9	20.6	31.5	17.9
BN adapt	9.8	9.9	10.5	9.6	9.5	15.8	23.8	22.1	21.8	31.4	43.9	11.2	26.9	30.6	25.8	20.2
ETA	9.1	11.2	12.5	3.9	7.8	18.2	26.3	25.6	22.4	34.4	41.9	6.4	30.7	33.7	29.7	20.9
LAME	1.8	2.7	1.6	21.9	11.5	16.9	27.3	19.3	28.3	29.3	71.4	5.8	20.2	24.6	39.1	21.5
CoTTA	11.3	11.4	12.1	8.9	10.0	17.9	26.3	23.4	23.0	33.9	44.6	10.1	29.0	34.1	27.6	21.6
CoTTA*	11.3	13.6	14.9	12.1	13.4	17.8	23.1	23.3	23.5	29.1	40.0	13.9	28.4	33.1	29.8	21.8
PL	13.3	11.2	14.7	12.4	12.4	19.6	27.1	25.7	24.2	34.7	44.4	8.4	29.7	34.0	30.0	22.8
PL+DELTA	23.8	25.0	25.1	23.4	22.6	33.6	44.3	41.2	38.7	53.1	65.4	27.9	48.9	53.6	46.6	38.2
TENT	12.6	13.6	14.3	12.6	11.4	17.2	26.6	25.2	21.7	34.6	43.0	6.0	29.6	34.2	30.3	22.2
TENT+TBR	24.7	26.6	26.9	24.8	24.7	37.1	47.0	44.4	39.0	55.5	66.2	15.5	51.0	56.3	50.0	39.3
TENT+DOT	15.4	16.6	16.4	14.6	14.5	20.1	27.7	26.5	24.1	35.4	43.3	13.6	31.4	35.2	31.3	24.4
TENT+DELTA	27.5	29.4	28.9	26.3	27.2	38.4	47.7	45.3	40.8	56.0	66.4	29.1	52.7	56.8	50.5	41.5
Ent-W	0.9	1.5	3.6	0.8	1.4	5.9	11.7	10.8	8.9	23.0	36.2	0.5	18.0	23.5	13.9	10.7
Ent-W+TBR+Div-W(0.05)	27.0	28.5	29.4	21.3	23.3	40.1	48.5	48.1	42.1	57.3	66.1	13.4	54.4	58.3	52.6	40.7
Ent-W+TBR+Div-W(0.1)	24.3	28.8	28.8	16.5	22.0	40.0	48.6	48.1	41.5	57.1	66.2	6.9	54.7	58.5	52.5	39.6
Ent-W+TBR+Div-W(0.2)	20.6	22.6	24.4	9.4	15.0	39.9	49.2	48.5	42.4	57.2	66.4	3.2	54.7	58.7	52.5	37.6
Ent-W+TBR+Div-W(0.4)	12.5	10.7	15.0	7.4	13.4	41.0	49.3	48.5	37.9	57.1	66.4	2.1	54.9	58.6	52.7	35.2
Ent-W+TBR+LA	7.5	7.6	13.0	3.6	6.4	33.8	39.7	39.3	30.4	46.3	54.1	1.7	44.3	47.3	42.7	27.8
Ent-W+TBR+Sample-drop	27.9	32.2	30.9	24.3	27.0	40.8	48.9	48.2	41.9	56.4	65.8	29.3	54.0	58.0	52.2	42.5
Ent-W+DELTA	30.8	34.4	33.0	28.7	29.3	42.8	49.7	49.1	43.9	57.2	65.3	36.7	54.9	58.6	52.7	44.5