Bridging the Gap: Unifying the Training and Evaluation of Neural Network Binary Classifiers

Abstract

While neural network binary classifiers are often evaluated on metrics such as Accuracy and F_1-Score, they are commonly trained with a cross-entropy objective. How can this training-evaluation gap be addressed? While specific techniques have been adopted to optimize certain confusion matrix based metrics, it is challenging or impossible in some cases to generalize the techniques to other metrics. Adversarial learning approaches have also been proposed to optimize networks via confusion matrix based metrics, but they tend to be much slower than common training methods. In this work, we propose a unifying approach to training neural network binary classifiers that combines a differentiable approximation of the Heaviside function with a probabilistic view of the typical confusion matrix values using soft sets. Our theoretical analysis shows the benefit of using our method to optimize for a given evaluation metric, such as F_1-Score, with soft sets, and our extensive experiments show the effectiveness of our approach in several domains.

1 Introduction

Neural network binary classifiers output a probability $p \in [0, 1]$ which is often used at training time to optimize model parameters using the binary cross-entropy (BCE) loss. The network's output p can also be translated to a binary value $\{0, 1\}$ indicating set membership to the negative or positive class. To determine set membership, the Heaviside step function H is commonly used with a threshold τ, where $p \geq \tau$ are considered positive classification outcomes. This notion of set membership is often used in evaluation metrics for binary classifiers.

It is a common assumption that optimizing a network via the desired evaluation metric is preferable to optimizing a surrogate objective [10, 26, 15, 30]. However, the Heaviside step function used to compute confusion matrix set membership in terms of true positives, false positives, false negatives, and true negatives, has a gradient with properties not conducive to optimization via gradient descent. The Heaviside function's gradient is not defined at the threshold τ and is zero everywhere else. Therefore the Heaviside function cannot be used to effectively backpropagate errors and train a neural network by optimizing metrics composed of confusion matrix set values, such as F_1-Score.

To address the gap between training and evaluating neural network binary classifiers, we propose a method to make confusion-matrix based evaluation metrics usable for backpropagation. Specifically, we propose the use of a differentiable approximation of the Heaviside step function along with confusion matrix values computed using the notion of soft set membership. A desired evaluation metric can then be made differentiable by calculating it over the soft-set confusion matrix, rather than using the traditional confusion matrix values.

Our main contributions are: 1) a novel method for training neural network binary classifiers that allows for the optimization of confusion-matrix based evaluation metrics with soft sets (Sec. 3); 2) a

theoretical analysis of our method (Sec. 4); and 3) the application of our approach to various domains with varying levels of class imbalance, showing its flexibility and superior performance compared to several baseline methods (Sec. 5). We provide an open-source implementation of our method for reproducibility.[1]

2 Preliminaries

In binary classification via neural networks, a step function is required to transform the network's output to a binary value. A common choice is the Heaviside step function with a threshold value τ:

$$H(p, \tau) = \begin{cases} 1 & p \geq \tau \\ 0 & p < \tau \end{cases} \tag{1}$$

Confusion matrix set membership is then computed for a prediction p and ground truth label y via:

$$tp(p, y, \tau) = \begin{cases} H(p, \tau) & y = 1 \\ 0 & \text{otherwise} \end{cases} \qquad fn(p, y, \tau) = \begin{cases} 1 - H(p, \tau) & y = 1 \\ 0 & \text{otherwise} \end{cases}$$

$$fp(p, y, \tau) = \begin{cases} H(p, \tau) & y = 0 \\ 0 & \text{otherwise} \end{cases} \qquad tn(p, y, \tau) = \begin{cases} 1 - H(p, \tau) & y = 0 \\ 0 & \text{otherwise} \end{cases} \tag{2}$$

Consider a set of predictions $p \in [0, 1]$, ground truth labels $y \in \{0, 1\}$ and threshold value $\tau \in (0, 1)$, e.g., $\{(p_1, y_1, \tau), (p_2, y_2, \tau), ..., (p_n, y_n, \tau)\}$. For n samples, the cardinality of each confusion matrix set is then computed as:

$$|TP| = \sum_{i=1}^{n} tp(p_i, y_i, \tau) \quad |FN| = \sum_{i=1}^{n} fn(p_i, y_i, \tau) \quad |FP| = \sum_{i=1}^{n} fp(p_i, y_i, \tau) \quad |TN| = \sum_{i=1}^{n} tn(p_i, y_i, \tau)$$

Common classification metrics are based on these cardinalities. For example, Precision $= |TP|/(|TP| + |FP|)$ is the proportion of positive predictions that are true positive results. Recall $= |TP|/(|TP| + |FN|)$ indicates the proportion of positive examples that are correctly identified. These two metrics represent a trade-off between classifier objectives; it is generally undesirable to optimize or evaluate for one while ignoring the other [14]. This makes summary evaluation metrics that balance between these trade-offs popular. Commonly used metrics include:

$$\text{Accuracy} = \frac{|TP| + |TN|}{|TP| + |TN| + |FP| + |FN|} \qquad F_1\text{-Score} = \frac{2}{\text{precision}^{-1} + \text{recall}^{-1}} \tag{3}$$

Accuracy is the rate of correct predictions to all predictions. F_1-Score is a specific instance of F_β-Score, which is the weighted harmonic mean of precision and recall: $F_\beta\text{-Score} = (1 + \beta^2) \cdot (\text{precision} \cdot \text{recall})/(\beta^2 \cdot \text{precision} + \text{recall})$. The value β indicates that recall is considered β times more important than precision.

Some metrics like F_β-Score are usually computed at a specific threshold τ whereas others are computed over a range of τ values. For example, the area under the receiver operating characteristic curve (AUROC) is a commonly used ranking performance measure defined in terms of the true positive rate (TPR) and false positive rate (FPR), each a function of τ: $\int_{\infty}^{-\infty} \text{TPR}(\tau)\text{FPR}'(\tau) \, d\tau$.

While metrics that rely on confusion matrix set values are commonly used for evaluation, as shown in Fig. 1 (right), it is difficult to use them as a loss during training. These metrics rely on the Heaviside step function, the derivative of which is undefined at the threshold τ and zero everywhere else. This means that these metrics do not have a derivative useful to backpropagate errors through the network.

When a binary classification neural network is trained on a loss function that is different from the evaluation metric, such as BCE, the network parameters are unlikely to be optimal for the desired evaluation metric. As shown in our theoretical analysis and experimental results, when the goal is to balance various confusion matrix set values, e.g., with F_1-Score, performance is improved by using our proposed method to optimize F_1-Score.

Figure 1: The proposed method. Binary classifiers are typically trained with the BCE loss and then evaluated on a confusion-matrix based metric. We propose to bridge this gap between training and evaluation by optimizing model parameters based on a metric that is computed over a soft-set confusion matrix, which is differentiable. This is done using a differentiable approximation of the Heaviside step function.

3 Method

We propose a method (Fig. 1) that aims to better unify the training and evaluation steps of binary neural network classifiers whose performance is measured with metrics based on the confusion matrix. Our method has two main steps. First, the Heaviside step function, H, is approximated with a function $\mathcal{H}$ useful for optimization via gradient descent. Then, $\mathcal{H}$ is used to compute a soft version of set membership in the confusion matrix. With the soft-set confusion matrix values, we can then compute desired confusion-matrix based metrics, such as F_1-score, using their standard formula. This appraoch makes the metrics end-to-end differentiable so that they can be used as a training loss.

3.1 Heaviside Approximation

A useful Heaviside approximation, $\mathcal{H}$, has a non-zero gradient: $\mathcal{H}'(p, \tau) \neq 0$, $\forall \tau$. Also, it ensures that for a single example, the classifier predicts positive and negative probabilities which sum to 1. Like H, the approximation should meet the properties of a cumulative distribution function (CDF) which ensures it is right-continuous, non-decreasing, with outputs in $[0, 1]$ following:

$$\lim_{p \to 0} \mathcal{H}(p, \tau) = 0 \quad \forall \tau \qquad \qquad \lim_{p \to 1} \mathcal{H}(p, \tau) = 1 \quad \forall \tau \tag{4}$$

Sigmoid approximation: One approximation method for H, proposed by [20], is the sigmoid function $s_0(k; p) = (1 + e^{-kp})^{-1}$. We reparameterize s_0 to account for τ, so that it can be used for varying thresholds: $\mathcal{H}^s(k, p, \tau) = (1 + e^{-k(p-\tau)})^{-1}$. A challenge with the sigmoid approximation is that as k increases, the sigmoid function better approximates the Heaviside function, but the derivative is close to zero over a larger range of valid inputs. Another challenge is that when τ is close to 0 or 1, $\mathcal{H}^s$ does not approach H as the input approaches 0 or 1. These limitations as well as the hyperparameters k and τ are further discussed in the Supplementary Material (Sec. 2).

Linear approximation: An alternative approximation of H is a five-point linearly interpolated function (Fig. 1, left). This approximation $\mathcal{H}^l$, is defined over $[0, 1]$ and is parameterized by a given threshold τ and a slope parameter δ, which define three linear segments with slopes m_1, m_2, and m_3. The slope of each line segment is:

$$m_1 = \frac{\delta}{\tau - \frac{\tau_m}{2}} \qquad \qquad m_2 = \frac{1 - 2\delta}{\tau_m} \qquad \qquad m_3 = \frac{\delta}{1 - \tau - \frac{\tau_m}{2}}$$

with $\tau_m = \min\{\tau, 1 - \tau\}$ in order to ensure a gradient suitable for backpropagation. The linear Heaviside approximation is thus given by:

$$\mathcal{H}^l = \begin{cases} p \cdot m_1 & \text{if } p < \tau - \frac{\tau_m}{2} \\ p \cdot m_3 + (1 - \delta - m_3(\tau + \frac{\tau_m}{2})) & \text{if } p > \tau + \frac{\tau_m}{2} \\ p \cdot m_2 + (0.5 - m_2\tau) & \text{otherwise} \end{cases} \tag{5}$$

Considering the threshold τ in the formulation of $\mathcal{H}^l$ ensures $\mathcal{H}^l(p = \tau, \tau) = 0.5$ while maintaining the limits in Eq. (4). See the Supplementary Material, Sec. 2.2, for the derivation of Eq. (5).

---

[1]Source code will be made public upon acceptance.

Recently, a similar linear function was implemented as an activation function to enforce meaningful logical outputs in logical neural networks [27]. However, rather than using the linear function for activation within the larger model architecture, we use it in the training objective of a classifier.

3.2 Soft Sets

We use soft sets, a generalization of fuzzy sets [22], to compose differentiable versions of confusion-matrix based evaluation metrics useful for backpropagation. A soft set μ in U, the initial universal set, is defined by the membership function $\mu : U \to [0, 1]$. For $x \in U$, the set membership function $\mu(x)$ specifies a degree of belonging for x to set u.

We use the notion of soft sets to compute confusion-matrix based metrics with a Heaviside approximation in place of the typically used strict sets. Soft set membership corresponds to the degree to which a sample tuple (p, y, τ) belongs to a confusion matrix set. We define the soft confusion matrix set membership functions for prediction and ground truth examples (p, y) relative to τ as:

$$
tp_s(p, y, \tau) = \begin{cases} \mathcal{H}(p, \tau) & y = 1 \\ 0 & \text{otherwise} \end{cases} \qquad fn_s(p, y, \tau) = \begin{cases} 1 - \mathcal{H}(p, \tau) & y = 1 \\ 0 & \text{otherwise} \end{cases}
$$
$$
fp_s(p, y, \tau) = \begin{cases} \mathcal{H}(p, \tau) & y = 0 \\ 0 & \text{otherwise} \end{cases} \qquad tn_s(p, y, \tau) = \begin{cases} 1 - \mathcal{H}(p, \tau) & y = 0 \\ 0 & \text{otherwise} \end{cases}
\tag{6}
$$

After computing per-sample soft set values, specific metrics can be approximated by summing over the relevant elements of the confusion matrix. For instance, we approximate precision as $|TP_s|/(|TP_s| + |FP_s|)$, where $|TP_s| = \sum_{i=1}^{n} tp_s(p_i, y_i, \tau)$ and $|FP_s| = \sum_{i=1}^{n} fp_s(p_i, y_i, \tau)$ for n samples. In practice, this summation occurs at training time over mini-batches while optimizing via gradient descent. Because gradient descent and its variants expect a small but representative sample of the broader data [4], the proposed method also expects a representative sample.

Decomposability: Metrics based on confusion matrix set values are considered non-decomposable. Non-decomposable metrics cannot be calculated per datapoint and are not additive across subsets of data [16]. We acknowledge that our optimization method of mini-batch stochastic gradient descent (SGD) does not provide an unbiased estimator on non-decomposable metrics. However, this is common in neural network training [13]. In practice, we find that large enough mini-batches provide a representative sample for confusion matrix based metrics, allowing the use of mini-batch SGD in our approach. Moreover, our method does not limit maximum batch size for training, unlike the adversarial approach to optimize F_1-Score proposed by [11].

Metrics and losses: Any metric composed of confusion matrix set values (TP, FP, FN, TN) can be approximated using our proposed method and used as a training loss. In our experiments, we train and evaluate on Accuracy, F_1-Score, AUROC, and F_β-Score [28]. We chose these metrics to show the flexibility of our approach. Accuracy, F_1-Score and F_β-Score may be selected based on class imbalance and resulting tradeoffs. AUROC illustrates that our method can be used when computation over a range of thresholds, τ, is required.

4 Theoretical Grounding

In this section, we first show the Lipschitz continuity of a variety of soft-set based metrics under the proposed Heaviside function approximations. This indicates that when such metrics are used as the loss in a neural network, the difference between successive losses is bounded across iterations of stochastic gradient descent. We then show, under certain assumptions, that metrics computed over the soft-set confusion matrix values are asymptotically similar to the true metric.

4.1 Lipschitz Continuity of Metrics Based on Soft-Set Confusion Matrix Values

A function f is considered Lipschitz continuous if there exists some constant K such that for all x_1, x_2 in the domain, $|f(x_1) - f(x_2)| \leq K|x_1 - x_2|$. Lipschitz continuous functions are always themselves continuous.

Theorem 4.1. *The linear Heaviside approximation $\mathcal{H}^l$ is Lipschitz continuous with Lipschitz constant* $M = \max\{m_1, m_2, m_3\}$.

143 $\mathcal{H}^l$ is continuous because each piecewise linear component is continuous and $\mathcal{H}^l$ is defined to be
144 continuous at the two points $p = \tau \pm \frac{\tau_m}{2}$. Also, by construction, the slope of any secant line is
145 positive and bounded by $M = \max\{m_1, m_2, m_3\}$. Thus, $\mathcal{H}^l$ is Lipschitz continuous with Lipschitz
146 constant M. Please see the full proof in Sec. 1.1 of the Supplementary Material. Note that the $\mathcal{H}^s$ is
147 also Lipschitz continuous [29].

148 **Theorem 4.2.** *Every entry of the soft-sets confusion matrix based on the Heaviside approximations*
149 *is Lipschitz continuous in the output of a neural network.*

150 The proof of Theorem 4.2 is in the Supplementary Material (Sec. 1.1).

151 The value of a Lipschitz continuous loss function composed of soft-set confusion matrix values
152 is Lipschitz continuous. This is because compositions of Lipschitz continuous functions are also
153 Lipschitz continuous. Following [8], we note that the confusion-matrix based metrics Accuracy,
154 Balanced Accuracy, F_β, Jaccard, and G-Mean are all Lipschitz continuous. These metrics are also
155 Lipschitz continuous under our proposed method computed via soft sets.

156 Lipschitz continuity of the loss function in a neural network optimized via stochastic gradient descent
157 indicates convergence without extreme variations in losses throughout training. Let K be the Lipschitz
158 constant for the objective function $\ell(w)$ on network weights w. Because of Lipschitz continuity,
159 when updating $w_{i+1} \to w_i - \alpha_i \ell'(w_i)$ using stochastic gradient descent with a learning rate α_i, a
160 small local change in the weights $|w_{i+1} - w_i| = \alpha_i |\ell'(w_i)|$ corresponds to a small local change in
161 the value of the objective function of $|\ell(w_{i+1}) - \ell(w_i)| \leq K\alpha_i |\ell'(w_i)|$.

4.2 Approximation of Confusion-Matrix Based Metrics with Soft Sets

163 We provide a statistical analysis showing that in the limit, as the number of examples goes to infinity,
164 F_1-Score calculated with soft sets approximates the expected true F_1-score under a set of assumptions.
165 Similar proofs for Accuracy and AUROC are provided in the Supplementary Material (Sec. 1.2).

166 Consider a dataset of size n with $\{x_1, ..., x_n\}$ examples and $\{y_1, ..., y_n\}$ labels. Suppose a network
167 outputs a probability p_i that the label $y_i = 1$. In this section, since the specific outputs p_i are unknown
168 and may change across iterations, we assume p_i is a random variable. When calculating F_1-Score,
169 p_i is passed through the Heaviside function H, which generates an output $\hat{y}_i^H = H(p_i, \tau)$, where
170 $\hat{y}_i^H \in \{0, 1\}$. The F_1-Score can be expressed as:

$$F_1 = \frac{\sum_{i=1}^n y_i \hat{y}_i^H}{\sum_{i=1}^n y_i \hat{y}_i^H + \frac{1}{2}\sum_{i=1}^n ((1-y_i)\hat{y}_i^H + y_i(1-\hat{y}_i^H))} = \frac{2\sum_{i=1}^n y_i \hat{y}_i^H}{\sum_{i=1}^n (y_i + \hat{y}_i^H)} \tag{7}$$

171 To calculate F_1-Score with soft sets (F_1^s), p_i is passed through the Heaviside approximation $\mathcal{H}$, which
172 generates an output $\hat{y}_i^{\mathcal{H}} = \mathcal{H}(p_i, \tau)$, where $\hat{y}_i^{\mathcal{H}} \in [0, 1]$. F_1-Score with soft-sets can be expressed as:

$$F_1^s = \frac{2\sum_{i=1}^n y_i \hat{y}_i^{\mathcal{H}}}{\sum_{i=1}^n (y_i + \hat{y}_i^{\mathcal{H}})} \tag{8}$$

173 Consider a network trained on a dataset with rn positive and $(1-r)n$ negative elements, where
174 $r \in [0, 1]$ is some constant. Suppose this classifier correctly classifies any positive example as a true
175 positive with probability u and any negative example as a false positive with probability v. Also,
176 assume that all classifications are independent. Because F_1-Score is calculated with discrete $\hat{y}_i^H$,
177 assume that the classifier will classify examples as a random variable $\hat{y}_i^H \sim \text{Bernoulli}(uy_i + v(1-y_i))$.
178 Thus, $\hat{y}_i^H \sim \text{Bernoulli}(u)$ if $y_i = 1$, and $\hat{y}_i^H \sim \text{Bernoulli}(v)$ if $y_i = 0$.

179 Since F_1^s can take on continuous values in $[0, 1]$, we consider that $\hat{y}_i^{\mathcal{H}}$ is a random variable drawn
180 from a Beta distribution, which has support $[0, 1]$. In particular, assume $\hat{y}_i^{\mathcal{H}} \sim \text{Beta}(\alpha_u y_i + \alpha_v(1 -$
181 $y_i), \beta_u y_i + \beta_v(1-y_i))$. Hence, $\hat{y}_i^{\mathcal{H}} \sim \text{Beta}(\alpha_u, \beta_u)$ if $y_i = 1$, and $\hat{y}_i^{\mathcal{H}} \sim \text{Beta}(\alpha_v, \beta_v)$ if $y_i = 0$.
182 Let $\frac{\alpha_u}{\alpha_u + \beta_u} = u$ and $\frac{\alpha_v}{\alpha_v + \beta_v} = v$, so for any i, $\mathbb{E}\left[\hat{y}_i^{\mathcal{H}}\right] = u$ if $y_i = 1$, and $\mathbb{E}\left[\hat{y}_i^{\mathcal{H}}\right] = v$ if $y_i = 0$.

183 Under the above assumptions, both F_1 and F_1^s have the same average classification correctness: for
184 any given i, $\mathbb{E}\left[\hat{y}_i^H\right] = \mathbb{E}\left[\hat{y}_i^{\mathcal{H}}\right]$. Also, there exists some $\alpha_u, \beta_u, \alpha_v, \beta_v$ such that the distributions of
185 $\hat{y}_i^H = H(p_i, \tau)$ and $\hat{y}_i^{\mathcal{H}} = \mathcal{H}(p_i, \tau)$ can both hold simultaneously under the same network for all i.

186 If we let $U \sim \text{Binomial}(nr, u)$ and $V \sim \text{Binomial}(n(1-r), v)$ be the independent random variables
187 denoting the number of true positives and false positives in a sequence of n independent predictions,

then F_1 from Eq. (7) becomes:

$$F_1 = \frac{2\sum_{i=1}^{n} y_i \hat{y}_i^H}{\sum_{i=1}^{n}(y_i + \hat{y}_i^H)} = 2\left(\frac{\sum_{i=1}^{n} y_i \hat{y}_i^H}{nr + \sum_{i=1}^{n} \hat{y}_i^H}\right) = 2\left(\frac{U}{nr + U + V}\right) = 2\left(\frac{U/n}{r + U/n + V/n}\right) \quad (9)$$

By the Strong Law of Large Numbers, $\frac{1}{nr}U \xrightarrow{\text{a.s.}} u$ and $\frac{1}{n(1-r)}V \xrightarrow{\text{a.s.}} v$ both converge with probability 1 as $n \to \infty$. Hence, $\frac{U}{n} \xrightarrow{\text{a.s.}} ru$ and $\frac{V}{n} \xrightarrow{\text{a.s.}} (1-r)v$. We therefore have, from the Continuous Mapping Theorem, that as $n \to \infty$:

$$F_1 = 2\left(\frac{U/n}{r + U/n + V/n}\right) \xrightarrow{\text{a.s.}} 2\left(\frac{ru}{r + ru + (1-r)v}\right) = \frac{2ru}{r + ru + v - rv} \quad (10)$$

For F_1^s, let $U^s = \sum_{y_i=1} \hat{y}_i^{\mathcal{H}}$ and $V^s = \sum_{y_i=0} \hat{y}_i^{\mathcal{H}}$ be the independent random variables denoting the total amount of true positives and false positives in the soft set case. Then, F_1^s from Eq. (8) becomes:

$$F_1^s = \frac{2\sum_{i=1}^{n} y_i \hat{y}_i^{\mathcal{H}}}{\sum_{i=1}^{n}(y_i + \hat{y}_i^{\mathcal{H}})} = 2\left(\frac{\sum_{i=1}^{n} y_i \hat{y}_i^{\mathcal{H}}}{nr + \sum_{i=1}^{n} \hat{y}_i^{\mathcal{H}}}\right) = 2\left(\frac{U^s}{nr + U^s + V^s}\right) = 2\left(\frac{U^s/n}{r + U^s/n + V^s/n}\right) \quad (11)$$

Since U^s is the sum of nr i.i.d. random variables distributed as $\text{Beta}(\alpha_u, \beta_u)$, which has mean $\frac{\alpha_u}{\alpha_u + \beta_u}$, by the Strong Law of Large Numbers, $\frac{1}{nr}U^s \xrightarrow{\text{a.s.}} \frac{\alpha_u}{\alpha_u + \beta_u} = u$. Similarly, $\frac{1}{n(1-r)}V^s \xrightarrow{\text{a.s.}} \frac{\alpha_v}{\alpha_v + \beta_v} = v$ also converges with probability 1 as $n \to \infty$. Hence, $\frac{U^s}{n} \xrightarrow{\text{a.s.}} ru$ and $\frac{V^s}{n} \xrightarrow{\text{a.s.}} (1-r)v$. We therefore have, from the Continuous Mapping Theorem, that as $n \to \infty$,

$$F_1^s = 2\left(\frac{U^s/n}{r + U^s/n + V^s/n}\right) \xrightarrow{\text{a.s.}} 2\left(\frac{ru}{r + ru + (1-r)v}\right) = \frac{2ru}{r + ru + v - rv} \quad (12)$$

Thus, F_1 and F_1^s both converge almost surely to the same value as $n \to \infty$. Since $0 \le \frac{2ru}{r+ru+v-rv} \le 1$ is bounded, $\mathbb{E}[F_1], \mathbb{E}[F_1^s] \to \frac{2ru}{r+ru+v-rv}$ by the Bounded Convergence Theorem. This means that the F_1^s value is an asymptotically unbiased estimator for the expected true F_1-Score, and we expect average F_1-Score values to converge to F_1^s as $n \to \infty$, under our setup. However, the F_1-Score computed from soft sets is not an unbiased estimator for the expected true F_1-Score for finite n.

The proof of almost sure convergence generalizes for any metric that is a continuous function in the ratio of each entry of the confusion matrix to n, as shown in the Supplementary Material (Sec. 1.2). This suggests that optimizing over the desired evaluation metric using our proposed method (e.g., F_1-Score computed with soft sets) is justified, as the loss should follow our true final loss closely for a large enough n. However, note that some metrics may be poor indicators of true classifier performance, such as Accuracy when data is imbalanced [14]. In such cases, it may not be desirable to optimize for such metrics using our method, as further discussed in the next section.

5   Experiments

This section presents three experiments to (1) evaluate the performance of our approach against several baselines on tabular data, (2) evaluate our approach on higher-dimensional image data, and (3) evaluate the ability of our method to balance precision and recall during training.

Datasets: Experiments were conducted on five publicly available datasets in a variety of domains and were chosen for their varying levels of class imbalance as explained later. All datasets were minimally pre-processed and split into separate train, test, and validation sets. See Sec. 4.1 of the Supplementary Material for details.

Architecture and training: Our experiments aim to fairly evaluate our method using different confusion-matrix based objective functions. Therefore, the same network architecture and training scheme was used unless otherwise noted. Performance was evaluated over 10 repeated trials to control for the effects of random weight initialization. We report the mean of results evaluated over threshold values $T = \{0.1, 0.2, ..., 0.9\}$ for metrics that require a threshold choice at evaluation. The details of the network architecture and training scheme are in Sec. 4.2 of the Supplementary Material.

Table 1: Losses (rows): F_1, Accuracy (Acc), and AUROC (ROC) via the proposed method (*) using the linear approximation; F_1-Score† via adversarial approach [11] and AUROC‡ via WMW statistic [33]. Bold indicates performance better than or equal to the BCE baseline.

		CocktailParty ($\mu \pm \sigma$)			Adult ($\mu \pm \sigma$)		
	Loss	F_1-Score	Accuracy	AUROC	F_1-Score	Accuracy	AUROC
(1)	F_1*	**0.75 ± 0.01**	**0.85 ± 0.01**	**0.82 ± 0.01**	**0.63 ± 0.02**	0.78 ± 0.04	**0.78 ± 0.02**
(2)	F_1†	0.30 ± 0.06	0.76 ± 0.01	0.60 ± 0.02	0.16 ± 0.02	0.78 ± 0.00	0.55 ± 0.01
(3)	Accuracy*	**0.70 ± 0.02**	**0.85 ± 0.01**	**0.78 ± 0.01**	0.35 ± 0.04	**0.81 ± 0.01**	0.61 ± 0.02
(4)	AUROC*	0.51 ± 0.01	0.41 ± 0.01	0.57 ± 0.00	**0.42 ± 0.01**	0.32 ± 0.02	0.55 ± 0.01
(5)	AUROC‡	0.01 ± 0.03	0.70 ± 0.03	0.50 ± 0.00	0.00 ± 0.00	0.76 ± 0.00	0.50 ± 0.00
(6)	BCE	0.70 ± 0.02	0.85 ± 0.01	0.78 ± 0.01	0.26 ± 0.06	0.80 ± 0.01	0.58 ± 0.02

		Mammography ($\mu \pm \sigma$)			Kaggle ($\mu \pm \sigma$)		
	Loss	F_1-Score	Accuracy	AUROC	F_1-Score	Accuracy	AUROC
(1)	F_1*	**0.63 ± 0.04**	0.98 ± 0.00	**0.78 ± 0.03**	**0.83 ± 0.02**	**1.00 ± 0.00**	**0.90 ± 0.02**
(2)	F_1†	0.46 ± 0.08	0.98 ± 0.00	0.66 ± 0.04	**0.76 ± 0.06**	**1.00 ± 0.00**	**0.83 ± 0.04**
(3)	Accuracy*	0.00 ± 0.00	0.97 ± 0.00	0.50 ± 0.00	**0.62 ± 0.33**	**1.00 ± 0.00**	**0.78 ± 0.15**
(4)	AUROC*	0.11 ± 0.01	0.18 ± 0.04	0.57 ± 0.02	0.06 ± 0.01	0.11 ± 0.00	0.55 ± 0.00
(5)	AUROC‡	0.00 ± 0.01	0.88 ± 0.12	0.50 ± 0.00	0.00 ± 0.00	0.93 ± 0.15	0.50 ± 0.00
(6)	BCE	0.56 ± 0.11	0.99 ± 0.00	0.71 ± 0.06	0.50 ± 0.33	1.00 ± 0.00	0.73 ± 0.16

Baselines: We trained networks using the typical BCE loss as well as two existing approaches for optimizing specific confusion matrix metrics: an adversarial approach for F_1-score [11], and using an approximation of the Wilcoxon-Mann-Whitney (WMW) statistic for AUROC [33]. Also, the Supplementary Material provides comparisons with other, less related methods for binary classification.

5.1 Experiments on Tabular Data

We evaluate our proposed approach using four tabular datasets with different levels of class imbalance. The CocktailParty dataset has a 30.29% positive class balance making it the most class-balanced dataset of those considered in this experiment. Salary classification data in the Adult dataset has a 23.93% positive class balance. Classifications of microcalcifications in the Mammography dataset is heavily skewed with a 2.32% positive class balance. Lastly, the Kaggle Credit Card Fraud Detection dataset has the most extreme class balance with only a 0.17% positive class balance.

We compare baseline methods against the performance of neural networks trained using our method to optimize F_1-Score, Accuracy, and AUROC. We instantiated our method using the Heaviside approximations and soft sets. Results using the linear approximation are presented in Table 1. See the Supplementary Material, Sec. 5, for results using the sigmoid approximation, which were comparable.

F_1 *computed with soft sets.* Our method of optimizing F_1 over the soft-set confusion matrix outperforms baselines when evaluated on F_1-Score for all datasets. In Table 1, line (1) has a higher F_1-Score than lines (2) and (6). Additionally, even when evaluated on the other metrics (Accuracy and AUROC), networks trained using our method on F_1 perform similarly or better than BCE.

Accuracy computed with soft sets. Our method of optimizing Accuracy over the soft-set confusion matrix has comparable performance to the BCE baseline when evaluated on Accuracy for all datasets. In Table 1, line (3) has comparable Accuracy to line (6). Note that Accuracy can reward prediction of only the dominant-class in imbalanced datasets [14], potentially resulting in no positive predictions and an F_1-Score of 0, as in line (3) of Table 1 for the Mammography and Kaggle datasets.

AUROC computed with soft sets. Neither optimizing AUROC using our method nor optimizing AUROC via the WCW statistic [33] consistently outperform traditional BCE. In Table 1, lines (4) and (5) have lower F_1-Score, Accuracy, and AUROC than line (6). This may be due in part to the AUROC metric's challenge with scale assumptions [12]. Moreover, AUROC is not linear-fractional [18], unlike F_β-Score and Accuracy. Therefore, AUROC has no unbiased estimator of gradient direction [1], which may also contribute to lackluster performance.

Note that in comparison to [11], the adversarial approach F_1† did not perform as well in our experiments. The difference could be due to different datasets, and because we used a PyTorch

Table 2: Losses (rows): F_1 and Accuracy and via the proposed method. Bold indicates performance better than or equal to BCE baseline.

| | Loss | CIFAR-10-Transportation ($\mu \pm \sigma$) | | CIFAR-10-Frog ($\mu \pm \sigma$) | |
		F_1-Score	Accuracy	F_1-Score	Accuracy
(1)	F_1*	$\mathbf{0.91 \pm 0.00}$	$\mathbf{0.93 \pm 0.00}$	$\mathbf{0.73 \pm 0.01}$	$\mathbf{0.95 \pm 0.00}$
(2)	Accuracy$*$	$\mathbf{0.92 \pm 0.00}$	$\mathbf{0.93 \pm 0.00}$	$\mathbf{0.74 \pm 0.01}$	$\mathbf{0.95 \pm 0.00}$
(3)	BCE	0.88 ± 0.01	0.91 ± 0.00	0.59 ± 0.04	0.94 ± 0.00

Table 3: **Mammography** ($\mu \pm \sigma$) dataset: F_β ($\beta = \{1, 2, 3\}$) loss using the proposed method, to balance between precision and recall while maximizing F_1-Score.

	Loss	F_1-Score	F_2-Score	F_3-Score	Precision	Recall
(1)	F_1*	0.61 ± 0.06	0.57 ± 0.06	0.56 ± 0.06	0.70 ± 0.06	0.55 ± 0.07
(2)	F_2*	0.63 ± 0.04	0.67 ± 0.04	0.69 ± 0.04	0.57 ± 0.05	0.71 ± 0.04
(3)	F_3*	0.57 ± 0.03	0.69 ± 0.02	0.75 ± 0.02	0.44 ± 0.04	0.81 ± 0.03

implementation provided by the author while [11] utilized Julia and Flux ML. Training networks for the tabular datasets on F_1-Score using our method on a CPU took a median time of 2.3 ± 0.16 minutes whereas the adversarial approach on CPU took a median time of 70 ± 118 minutes.

5.2 Experiments on Image Data

We conducted experiments similar to the those in Sec. 5.1 with higher dimensional data using two different binary image datasets created from the CIFAR-10 dataset [19]. The CIFAR-10-Transportation and CIFAR-10-Frog datasets had a 40% and 10% positive class balance, respectively.

We focused on Accuracy and F_1-Score, given the limitations with AUROC found in earlier experiments. We also excluded the adversarial approach to optimize F_1-Score [11] due to long runtime on tabular data. Otherwise, we use the same set up from Sec. 5.1.

Overall, our findings with image data in Table 2 are consistent with tabular results from Sec. 5.1. Our method of optimizing F_1-Score over the soft-set confusion matrix performed better than traditional BCE for both datasets when evaluated on both F_1-Score and Accuracy. In Table 2, line (1) has higher scores than line (3). Results from our method of optimizing Accuracy over the soft-set confusion matrix (line (2) in Table 2) are better than the results for BCE (line (3) in Table 2).

5.3 Balancing Between Precision and Recall

Our method also allows training-time optimization that balances between precision and recall using F_β-Score. This approach to training is particularly useful in real-world scenarios where there is a high cost associated with missed detections. This type of metric is difficult to optimize effectively for using a typical BCE loss because BCE is not aware of any preference towards precision or recall.

Results in Table 3 show that using the proposed method to optimize F_β-Score is an effective way of maintaining maximum classifier performance while balancing between precision and recall at a ratio appropriate for a given task. Increasing values of β correspond to an increased preference toward recall with small loss of total performance measured by F_1-Score. Similar results on optimizing for F_β-Score with additional datasets are provided in Sec. 6.2 of the Supplementary Material.

6 Related work

Our work is inspired by research on the direct optimization of evaluation metrics for binary classification. This includes plug-in methods that empirically estimate a threshold for a classifier on a metric. For example, [23] demonstrated the applicability of plug-in classifiers to optimize F_1-Score with linear models. For metrics based on linear combinations of confusion matrix set cardinalities, [18] identified an optimal plug-in classifier with a metric-dependent threshold. Also, [17] explored the Precision@K metric for linear models in the context of ranking. Our approach is not a competitor

to plug-in methods, but rather an approach to train a neural network classifier on a differentiable approximation of a metric based on the confusion matrix. As such, it could be used in conjunction with a plug-in method, if desired.

Works such as [16, 6] optimized specific metrics like Precision@K and F_1-Score in online learning, which is characterized by the sequential availability of data. Our work does not address online learning, but batch learning methods. Additionally, other work has focused on optimizing AUROC [33, 15], F-score [9, 34], and AUPRC in the context of ranking [10]. Rather than focusing on a single specific metric, we provide a flexible method for optimizing a neural network using approximations of varied metrics based on the confusion matrix. For example, our experiments in Sec. 5.3 show how tradeoffs between precision and recall can be made by adjusting the β parameter of the F_β-score during training with our method.

In the field of computer vision, differentiable surrogate losses have been proposed for the F_1-Score [7, 5], Jaccard Index [2, 25, 26], and Dice score [24, 31, 21, 3]. However, since these methods are applied to difficult problems in computer vision, they incorporate a particular surrogate, such as a surrogate for the F_1-Score, into a larger composition of losses. In our experiments, we instead focus on evaluating the impact of individual losses approximating a desired evaluation metric. We also evaluate the theoretical merits of optimizing a differentiable surrogate for confusion-matrix based metrics using an approximation of the Heaviside step function and soft-set confusion matrix values.

Recently, adversarial approaches have emerged as another related area of research. Wang et al. [32] used a structured support vector machine and reported performance on Precision@K as well as F_1-Score. Fathony and Kolter [11], which we compare against, improved performance via a marginalization technique that ensured polynomial time convergence. The authors evaluated their adversarial approach on Accuracy and F_1-Score, among other metrics, while reporting performance relative to BCE [11]. Downsides of the latter approach are that it is limited to a small batch size, on the order of 25 samples, and has cubic runtime complexity. Our approach does not limit batch sizes and has a worst-case runtime complexity equivalent to the runtime complexity of the confusion-matrix based metric being used as a loss.

7 Broader impact and ethics

Our work was motivated by the potentially wide ranging impact that more flexible and robust binary classifiers could have across application domains such as social group dynamics, sociology, and economics, which we explored in our experiments. Improving the tools used in these areas of research has the potential to positively impact human quality of life, but are still susceptible to data bias. These tools should be used with care when building safe and responsible artificial intelligence systems.

8 Conclusion

We proposed a novel method to optimize for confusion-matrix based metrics by using a Heaviside function approximation and soft-set membership. Our method addresses the common training-evaluation gap when working with binary neural network classifiers: these networks are typically trained with BCE loss, but evaluated using a confusion-matrix based metric, such as F_1-Score.

Our theoretical analyses showed that soft-set confusion matrix based metrics, such as F_1^s, are Lipschitz continuous and are likely to converge in expectation to the true metric's expectation. Additionally, our experiments showed the feasibility of using our method to optimize confusion-matrix based metrics. While many factors play into final classifier performance, such as balance of samples in the dataset, the desired evaluation metric, the approximation of H, and network hyperparameters, we found that in many cases, final classifier performance can be improved by bridging the training-evaluation gap using our method. In fact, optimizing model parameters for F_1 with soft sets resulted in better evaluation results with F_1-Score and better or comparable evaluation results with Accuracy and AUROC. Our approach also outperformed other methods that directly optimize for a specific metric. For example, Fathony and Kolter's [11] adversarial approach applied to F_1-Score had much longer training time and resulted in worse performance than our approach. In the future, we are interested in further studying how our method can be applied to multi-class classification problems.

References

[1] Han Bao and Masashi Sugiyama. Calibrated surrogate maximization of linear-fractional utility in binary classification. In *International Conference on Artificial Intelligence and Statistics*, 2020.

[2] Maxim Berman, Amal Rannen Triki, and Matthew B Blaschko. The lovász-softmax loss: A tractable surrogate for the optimization of the intersection-over-union measure in neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4413–4421, 2018.

[3] Jeroen Bertels, Tom Eelbode, Maxim Berman, Dirk Vandermeulen, Frederik Maes, Raf Biss-chops, and Matthew B Blaschko. Optimizing the dice score and jaccard index for medical image segmentation: Theory and practice. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, 2019.

[4] Léon Bottou. Stochastic gradient descent tricks. In *Neural networks: Tricks of the trade*, pages 421–436. Springer, 2012.

[5] Ilker Bozcan, Jonas Le Fevre, Huy X Pham, and Erdal Kayacan. Gridnet: Image-agnostic conditional anomaly detection for indoor surveillance. *IEEE Robotics and Automation Letters*, 6(2):1638–1645, 2021.

[6] Róbert Busa-Fekete, Balázs Szörényi, Krzysztof Dembczynski, and Eyke Hüllermeier. Online f-measure optimization. In *NeurIPS*, pages 595–603, 2015.

[7] Rail Chamidullin, Milan Šulc, Jiří Matas, and Lukáš Picek. A deep learning method for visual recognition of snake species. 2021.

[8] Krzysztof Dembczyński, Wojciech Kotłowski, Oluwasanmi Koyejo, and Nagarajan Natarajan. Consistency analysis for binary classification revisited. In *International Conference on Machine Learning*, pages 961–969. PMLR, 2017.

[9] Krzysztof J Dembczynski, Willem Waegeman, Weiwei Cheng, and Eyke Hüllermeier. An exact algorithm for f-measure maximization. In *NeurIPS*, 2011.

[10] Elad Eban, Mariano Schain, Alan Mackey, Ariel Gordon, Ryan Rifkin, and Gal Elidan. Scalable Learning of Non-Decomposable Objectives. In *AISTATS*, 2017.

[11] Rizal Fathony and Zico Kolter. Ap-perf: Incorporating generic performance metrics in differen-tiable learning. In *AISTATS*, pages 4130–4140, 2020.

[12] Peter Flach and Meelis Kull. Precision-recall-gain curves: Pr analysis done right. In *NeurIPS*, pages 838–846, 2015.

[13] Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT press Cambridge, 2016.

[14] Haibo He and Edwardo A Garcia. Learning from imbalanced data. *TKDE*, 21(9):1263–1284, 2009.

[15] Alan Herschtal and Bhavani Raskutti. Optimising area under the roc curve using gradient descent. In *ICML*, page 49, 2004.

[16] Purushottam Kar, Harikrishna Narasimhan, and Prateek Jain. Online and stochastic gradient methods for non-decomposable loss functions. In *NeurIPS*, pages 694–702, 2014.

[17] Purushottam Kar, Harikrishna Narasimhan, and Prateek Jain. Surrogate functions for maximiz-ing precision at the top. In *ICML*, pages 189–198, 2015.

[18] Oluwasanmi O Koyejo, Nagarajan Natarajan, Pradeep K Ravikumar, and Inderjit S Dhillon. Consistent binary classification with generalized performance metrics. In *NeurIPS*, pages 2744–2752, 2014.

[19] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[20] Nikolay Kyurkchiev and Svetoslav Markov. Sigmoid functions: some approximation and modelling aspects. *LAP LAMBERT Academic Publishing, Saarbrucken*, 2015.

[21] Fausto Milletari, Nassir Navab, and Seyed-Ahmad Ahmadi. V-net: Fully convolutional neural networks for volumetric medical image segmentation. In *2016 fourth international conference on 3D vision (3DV)*, 2016.

[22] Dmitriy Molodtsov. Soft set theory—first results. *CAMWA*, 1999.

[23] Harikrishna Narasimhan, Rohit Vaish, and Shivani Agarwal. On the statistical consistency of plug-in classifiers for non-decomposable performance measures. In *NeurIPS*, pages 1493–1501, 2014.

[24] Marcus Nordström, Han Bao, Fredrik Löfman, Henrik Hult, Atsuto Maki, and Masashi Sugiyama. Calibrated surrogate maximization of dice. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 269–278. Springer, 2020.

[25] Md Atiqur Rahman and Yang Wang. Optimizing intersection-over-union in deep neural networks for image segmentation. In *International symposium on visual computing*, pages 234–244. Springer, 2016.

[26] Hamid Rezatofighi, Nathan Tsoi, JunYoung Gwak, Amir Sadeghian, Ian Reid, and Silvio Savarese. Generalized intersection over union: A metric and a loss for bounding box regression. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019.

[27] Ryan Riegel, Alexander Gray, Francois Luus, Naweed Khan, Ndivhuwo Makondo, Ismail Yunus Akhalwaya, Haifeng Qian, Ronald Fagin, Francisco Barahona, Udit Sharma, et al. Logical neural networks. *arXiv preprint arXiv:2006.13155*, 2020.

[28] C. J. Van Rijsbergen. *Information Retrieval*. Butterworth-Heinemann, USA, 2nd edition, 1979.

[29] Yuzhang Shang, Bin Duan, Ziliang Zong, Liqiang Nie, and Yan Yan. Lipschitz continuity guided knowledge distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10675–10684, 2021.

[30] Yang Song, Alexander Schwing, Raquel Urtasun, et al. Training deep neural networks via direct loss minimization. In *ICML*, pages 2169–2177, 2016.

[31] Carole H Sudre, Wenqi Li, Tom Vercauteren, Sebastien Ourselin, and M Jorge Cardoso. Generalised dice overlap as a deep learning loss function for highly unbalanced segmentations. In *Deep learning in medical image analysis and multimodal learning for clinical decision support*, pages 240–248. Springer, 2017.

[32] Hong Wang, Wei Xing, Kaiser Asif, and Brian Ziebart. Adversarial prediction games for multivariate losses. In *NeurIPS*, pages 2728–2736, 2015.

[33] Lian Yan, Robert H Dodier, Michael Mozer, and Richard H Wolniewicz. Optimizing classifier performance via an approximation to the wilcoxon-mann-whitney statistic. In *ICML*, 2003.

[34] Ming-Jie Zhao, Narayanan Edakunni, Adam Pocock, and Gavin Brown. Beyond fano's inequality: bounds on the optimal f-score, ber, and cost-sensitive risk and their implications. *JMLR*, 2013.