# Understanding the Evolution of Linear Regions in Deep Reinforcement Learning

## Abstract

Policies produced by deep reinforcement learning are typically characterised by their learning curves, but they remain poorly understood in many other respects. ReLU-based policies result in a partitioning of the input space into piecewise linear regions. We seek to understand how observed region counts and their densities evolve during deep reinforcement learning using empirical results that span a range of continuous control tasks and policy network dimensions. Intuitively, we may expect that during training, the region density increases in the areas that are frequently visited by the policy, thereby affording fine-grained control. We use recent theoretical and empirical results for the linear regions induced by neural networks in supervised learning settings for grounding and comparison of our results. Empirically, we find that the region density increases only moderately throughout training, as measured along fixed trajectories coming from the final policy. However, the trajectories themselves also increase in length during training, and thus the region densities decrease as seen from the perspective of the current trajectory. We further provide other empirically-driven observations regarding the number of visited regions with respect to the number of neurons, changing trajectory lengths during training, and the impact of network depth on region density.

## 1 Introduction

Deep reinforcement learning (RL) utilizes neural networks to represent the policy and to train this network to optimize an objective, typically the expected value of time-discounted future rewards. Deep RL algorithms have been successfully applied to diverse applications including robotics, challenging games, and an increasing number of real-world decision-and-control problems [François-Lavet et al., 2018]. For a given choice of task, RL algorithm, and policy network configuration, the performance is commonly characterised via the learning curves, which provide insight into both the final performance and the efficiency of the learning. However, little has been done to understand, in detail, the structure of the state-to-action mappings induced by the control policies and how this evolves over time.

In this work, we aim to further understand deep feed-forward neural network policies that use rectified linear activation functions (rectifier linear units or ReLUs). ReLUs [Nair and Hinton, 2010] are among the most popular choices of activation functions due to their practical successes [Montúfar et al., 2014]. For RL, these activations induce a piecewise linear mapping from states to actions, where the input space, i.e, the state space, is divided into distinct *linear regions*, where within each region, the actions are a linear function of the states. Note that the regions are formally an affine function of the input, due to the constant-valued bias terms. For simplicity and convenience, these

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: Schematic illustration of a trajectory traversing the piecewise linear regions in the policy state space.

are more commonly described as linear regions. Figure 1 provides a schematic illustration of these regions, along with a policy trajectory.

The number of distinct regions into which the input space is divided is a natural measure of network expressivity. Learned functions with many linear regions have the capacity to build complex and flexible decision boundaries. Thus, the problem of counting the number of linear regions has been extensively studied in recent literature [Montúfar et al., 2014, Raghu et al., 2017, Hanin and Rolnick, 2019a, Serra et al., 2018]. While the maximum number of regions is exponential with respect to network depth [Montúfar et al., 2014], recent work has demonstrated that the number of regions is instead typically proportional to the number neurons [Hanin and Rolnick, 2019a].

For RL, we are interested in the local granularity (density) of linear regions along trajectories arising from the policy. Fine-grained regions afford fine-grained control, and thus we may hypothesize that region density *increases* in regions frequently visited by the policy, in order to afford better control. Recent work in supervised-learning of image classification is inconsistent with regard to findings about the region density seen in the vicinity of data points, with some reporting a decrease [Novak et al., 2018] to provide better generalization and robustness to perturbation, and others not [Hanin and Rolnick, 2019a]. For the RL setting, we note that counting regions visited along an episode trajectory arguably provides a meaningful and task-grounded measurement in contrast to line-segments and ellipses that pass through randomly sampled points sampled from training data, which have been used in the prior works mentioned above.

To the best of our knowledge, our work is the first to investigate the structure and evolution of linear regions of ReLU-based deep RL policies in detail. We seek to answer several basic empirical questions :

**Q1** Do findings for network expressivity, originally developed in supervised learning settings, apply to RL policies? How are the region densities affected by the policy network configuration? Do deeper policy networks result in finer-grained regions and hence an increased expressivity?

**Q2** How do the linear regions of a policy evolve during training? Do we see a significantly greater density of regions emerge along the areas of the state space frequently visited by the episodic trajectories, thereby allowing for finer-grained control? Do random-action trajectories see different densities?

The key results can be summarized as follows, for policies trained using proximal policy optimization [Schulman et al., 2017], and evaluated on four different continuous control tasks. Q1: There is a general alignment with recent theoretical and empirical results for supervised learning settings. Region density is principally proportional to the number of neurons, with an additional small observed increase in density for deeper networks. Q2: Only a moderate increase of density is observed during training, as measured along fixed final-policy trajectories. Therefore, the complexity of a final learned policy does *not* come principally from increased density on-and-around the optimal trajectories, which is a potentially surprising result. In contrast, as measured along the evolving current-policy trajectories, a decrease in region density is observed during training. Across all settings, we also observe that the region-transition count, as observed during fixed time-duration episodes, grows during training before converging to a plateau. However, the trajectory length, as measured in the

input space, also grows towards a plateau, although not at the same rate, and this leads to variations in the mean region densities as observed along current trajectories during training.

## 2   Related Work

Understanding the expressivity of a neural network is fundamental to better understanding its operation. Several works study exprressivity of deep neural networks with piecewise linear activations by counting their linear regions [Arora et al., 2016, Bianchini and Scarselli, 2014]. On the theoretical side, Pascanu et al. [2013] show that in the asymptotic limit of many hidden layers, deep ReLU networks are capable of separating their input space into exponentially more linear regions compared with shallow networks, despite using the same number of computational units. Following this, Montúfar et al. [2014] also explore the complexity of functions computable by deep feed-forward neural networks with ReLU and maxout activations, and provide tighter upper and lower bounds for the maximal number of linear regions. They show that the number of linear regions is polynomial in the network width and exponential with respect to the network depth. Furthermore, Raghu et al. [2017] improve the upper bound for ReLU networks by introducing a new set of expressivity measures and showing that expressivity grows exponentially with network depth for ReLU and tanh activated neural networks. Serra et al. [2018] generalizes these results by providing even tighter upper and lower bounds for the number of regions for ReLU networks and show that the maximal number of regions grows exponentially with depth when input dimension is sufficiently large.

More recent work that touches on expressivity of depth shows that the effect of depth on the expressivity of neural networks is likely far below that of the theoretical maximum proposed by prior literature. Hanin and Rolnick [2019b] study the importance of depth on expressivity of neural networks in practice. They show that the average number of linear regions for ReLU networks at initialization is bounded by the number of neurons raised to the input dimension, and is independent of network depth. They also empirically show that this bound remains tight during training. Similarly, Hanin and Rolnick [2019a] find that the average distance to the boundary of the linear regions depends only on the number of neurons and not on the network depth – both at initialization and during training for supervised-learning tasks on ReLU networks. This strongly suggests that deeper networks do not necessarily learn more complex functions in comparison to shallow networks. Prior to this, a number of works have shown that the strength of deep learning may arise in part from a good match between deep architectures and current training procedures [Mhaskar and Poggio, 2016, Mhaskar et al., 2016, Zhang et al., 2021]. Notably, Ba and Caruana [2013] show that, once deep networks are trained to perform a task successfully, their behavior can often be replicated by shallow networks, suggesting that the advantages of depth may be linked to easier learning.

Another line of work studies function complexity in terms of robustness to perturbations to the input. Sokolić et al. [2017] theoretically studies the input-output Jacobian, a measure of robustness, relates to generalization. Similarly, Zahavy et al. [2016b] propose a sensitivity measure in terms of adversarial robustness, and provides theoretical and experimental insights on how it relates to generalization. Novak et al. [2018] also study robustness and sensitivity using the input-output Jacobian and number of transitions along trajectories in the input space as measures of robustness. They show that neural networks trained for image classification tasks are more robust to input perturbations in the vicinity of the training data manifold, due to training points lying in regions of lower density. Several other recent works have also focused on proposing tight generalization bounds for neural networks [Bartlett et al., 2017, Dziugaite and Roy, 2017, Neyshabur et al., 2017].

There are a number of works that touch on understanding deep neural networks by finding general principles and patterns during training. Arpit et al. [2017] empirically show that deep networks prioritize learning simple patterns of the data during training. Xu et al. [2019] find a similar phenomenon in the case of 2-layer networks with Sigmoid activations. Rahaman et al. [2019] study deep ReLU activated networks through the lens of Fourier analysis and show that while deep neural networks can approximate arbitrary functions, they favour low frequency ones and thus, they exhibit a bias towards smooth functions. Samek et al. [2017] present two approaches in explaining predictions of deep learning models in a classification task, with the first method computing the sensitivity of the prediction with respect to input perturbations and the second method that meaningfully decomposes the decision in terms of input variables.

While deep RL methods are widely used and extensively studied, few works focus on understanding the policy structure in detail. Zahavy et al. [2016a] propose a visualization method to interpret the agent's actions by describing the Markov Decision Process as a directed graph on a t-SNE map. They then suggest ways to interpret, debug and optimize deep neural network policies using the proposed visualization maps. Rupprecht et al. [2019] train a generative model over the state space of Atari games to visualize states which minimize or maximize given action probabilities. Luo et al. [2018] adapt three visualization techniques to the domain of image-based RL using convolutional neural networks in order to understand the decision making process of the RL agent.

# 3 Piecewise Linear Regions

Throughout this work, we consider RL policies based on *ReLU networks*. A ReLU network is a ReLU-activated feed-forward neural network, or a multi-layer perceptron (MLP) which can be formulated as a scalar function $f : \mathbb{R}^d \to \mathbb{R}^o$ defined by a neural network with $L$ hidden layers of width $d_1, ..., d_L$ and a $o$-dimensional output. Assuming the output to be 1-dimensional, and following the notation of Rahaman et al. [2019], we have:

$$f(\mathbf{x}) = (T^{(L+1)} \circ \sigma \circ T^{(L)} \circ ... \circ \sigma \circ T^{(1)})(\mathbf{x}),$$ (1)

where $T^{(k)} : \mathbb{R}^{d_{k-1}} \to \mathbb{R}^{d_k}$ computes the weighted sum $T^{(k)}(\mathbf{x}) = W^{(k)}\mathbf{x} + \mathbf{b}^{(k)}$ for some weight matrix $W^{(k)}$ and bias vector $\mathbf{b}^{(k)}$. Here, $\sigma(\mathbf{u}) = \max(0, \mathbf{u})$ denotes the ReLU activation function acting element-wise on a vector $\mathbf{u} = (u_1, ..., u_n)$.

Given the ReLU network $f$ from Equation 1, again following Rahaman et al. [2019], piecewise linearity can be explicit written by

$$f(\mathbf{x}) = \sum_{r \in R} 1_{P_r}(\mathbf{x})(W_r\mathbf{x} + \mathbf{b}_r)$$ (2)

where $r$ is an index for the linear regions $P_r$ and $1_{P_r}$ is the indicator function on $P_r$. The $1 \times d$ matrix $W_r$ is given by:

$$W_r = W^{(L+1)}W_r^{(L)}...W_r^{(1)}$$ (3)

where $W_r^{(k)}$ is obtained from the original weight $W^{(k)}$ by setting its $j^{\text{th}}$ column to zero whenever neuron $j$ of layer $k-1$ is inactive.

# 4 Counting Linear Regions in RL Policies

To answer the key questions posed in the introduction, we need a method for counting the regions encountered during the episodic trajectories taken during RL. For each input $\mathbf{x}$, we encode each neuron of the policy network with a binary code of $0$ if its pre-activation is negative, and with a binary code $1$ otherwise. The linear region of the input $\mathbf{x}$ can thus be uniquely identified by a concatenation of binary codes of all the neurons in the network called an *activation pattern*. Figure 2 illustrates the activation pattern construction for a 2D input space.

Figure 1 provides a schematic illustration of the linear regions for a 2D state space, together with an example trajectory that consists of sequential states encountered by the policy, connected with straight-line segments. As seen in the figure, regions can be revisited, which leads to a distinction between the number of transitions between regions and the number of unique regions visited along a trajectory. We compute both of these metrics along episodic trajectories, as enabled by keeping a list of the regions already visited at any point in time when processing a given episode trajectory. Our region-counting method also includes regions that are crossed by the straight-line segments between successive trajectory states, although the policy itself does not explicitly encounter these regions due to the discrete-time nature of typical RL environments.

Figure 2: An overview of a policy network and the binary labeling scheme of the linear regions.

Figure 3: State space visualization with current ($\tau$) and fixed trajectories ($\tau^*$) of a ReLU-activated policy network with depth 2 and width 8 trained on a 2D toy environment during training. The first row, plots a fixed trajectory sampled from the final policy over the state space. The second row plots a trajectory sampled from the current policy. Columns indicate the number of training epochs. Epoch $= 0$ corresponds to the policy at initialization and Epoch $= 100$ corresponds to the fully-trained policy. In this toy environment, an agent starts at the origin indicated with a blue dot and the goal is to move the agent to reach a target state located at $x = 100$. States are the position $x$ (horizontal axis) and velocity $\dot{x}$ (vertical axis) of the agent, and action is the acceleration.

To represent the $k$-th line segment of the episodic trajectories in the input space, we develop a parameterized line segment given by $s(u) = (1-u)s_{k-1} + us_k$, where $u \in [0, 1]$ and $s_{k-1}, s_k \in \mathbb{R}^d$ denote the endpoints of the line segment. We then calculate the exact number of the linear regions by considering the hidden layers of the policy network one at a time, starting from input towards the output, and observe how each region can be split by the neurons. Starting with the first layer, we consider neurons one by one, and identify the point in the domain of $u$, if any, that induces a change in the binary labeling for that neuron. Each such point subdivides the domain of $u$ into two new regions where the pre-activation will be zero for one of them in the next layer. By maintaining a list of these regions and the linear functions defined over them, and whether their pre-activation vanishes in the next layer, we proceed to the neurons of the next layer. This process repeats for each of the regions resulting from the previous layer. We record the activation patterns of all the final regions, to track state visits during all segments of episode trajectories. In the end, for each trajectory $\tau$, we compute the total region transitions, $R_T(\tau)$, as well as the number of unique visited regions, $R_U(\tau)$, where $R_T(\tau) + 1 \geq R_U(\tau)$. We further compute the trajectory length in the input space, $L(\tau)$. This allows us to compute normalized region densities according to $\rho(\tau) = R_T(\tau)/(NL(\tau))$ where $N$ is the total number of neurons in the policy network, in accordance with Hanin and Rolnick [2019a].

We use the above metrics along two types of trajectories. First, we consider a fixed trajectory, $\tau^*$ as sampled from the final fully-trained policy. Second, we consider *current* trajectories, $\tau$, as sampled from the current policy during training. Both of these trajectories offer informative views of the evolution of the policy. The former offers a direct picture of the linear-region density along a meaningful, fixed region of the state space, i.e., that of the final optimized policy. The latter offers a view of what the policy trajectories actually encounter during training. In order to better

understand the evolution of $\tau$, we also track its length, $L(\tau)$, given that the density is determined by the region-transition count as well as the length of the trajectory. Figure 3 shows the evolution of linear regions and the types of trajectories $\tau^*$ and $\tau$ for a simple 2D toy environment, and a ReLU-activated policy network of depth 2 and width 8.

## 5 Experimental Results

We conduct our experiments on four continuous control tasks including HalfCheetah-v2, Walker-v2, Ant-v2, and Swimmer-v2 environments from the OpenAI gym benchmark suits [Brockman et al., 2016]. We use the Stable-Baselines3 implementations of the PPO algorithm [Schulman et al., 2017] in all of our experiments throughout this work. We run each experiment with 5 different random seeds and the results show the mean and the standard deviation across the random seeds. The policy network architecture used is an MLP with ReLU activations in all hidden layers.

We train 18 policy network configurations, as listed in supplementary material, and having $N \in \{32, 48, 64, 96, 128, 192\}$ neurons, widths $w \in \{8, 16, 32, 64\}$, and depths $d \in \{1, 2, 3, 4\}$. We use a fixed value function network structure of $(64, 64)$ in all of our experiments. These network configurations are chosen such that the network is fully-capable of learning the task and achieves near state-of-the-art cumulative reward on the particular task it is trained on. This allows us to study the evolution of linear regions disentangled from properties such as trainability, which is outside the scope of this work. The table showing the range of the mean cumulative reward per task, across all network configurations can be found in the supplementary material.

We adopt the network initialization and hyperparameters of PPO from StableBaselines3 [Raffin et al., 2021] and train our policy networks on 2M samples (i.e. 2M timesteps in the environment). This initialization scheme also matches the best-practice recommendations for on-policy RL, e.g., [Andrychowicz et al., 2020], although it differs from that used in Hanin and Rolnick [2019a] for theoretical and empirical linear region analysis. An anonymized version of our code is available in supplemental material and will be made public upon acceptance, under an MIT license.

In what follows, we focus on the results for the HalfCheetah-v2 environment as a representative example. Similar results for the other environments are provided in the supplemental material.

### 5.1 Evolution of the Density of Linear Regions during Training

We begin by examining the number of transitions encountered as we sweep along the fixed final-policy trajectory, $R_T(\tau^*)$, as shown in Figure 4(a). For clarity, we present results for only three policy network configurations. The complete set of results is available in the supplementary material. This plot shows a moderate and gradual increase of 50% in the number of region transitions observed in fixed-duration RL episodes during training, with larger policy networks having more regions. Computing the region density requires dividing by number of neurons, $N$, and the trajectory length, $L(\tau^*)$, which is constant for the fixed final trajectory, $\tau^*$. The result is given in Figure 4(b) which shows the mean and standard deviation of the normalized region densities across policy networks with the same depth. This shows a result that is consistent across all policy network dimensions to within $\pm 30\%$, and reflects an identical moderate-and-gradual increase during training, regardless of the policy network configuration. Thus, in response to **Q2**, RL policies trained with PPO see a moderate increase in region density along the parts of the state space that are frequently visited by the policy. We later discuss the observed impact of policy-network depth (§5.2).

We next examine the number of transitions encountered as we sweep along the evolving set of current-policy trajectories, $R_T(\tau)$, shown in Figure 4(c). These begin near zero and then rapidly increase as the policy succeeds at exploration. Again, for clarity, we show a representative sample of three policy network dimensions here and the complete set of results are available in the supplementary material. The corresponding region densities are shown in Figure 4(d), together with the fixed-region densities which are repeated from Figure 4(b) (see the bottom dashed curve). We speculate that the observed densities are higher early on due to the unstructured nature of early exploration and the form of network initialization, and then decrease over time as the trajectory lengths begin to increase, as shown in Figure 4(e).

We compute the number of repeat visits to regions as $R_T - R_U$, i.e., the region transition count minus the unique region count. In Figure 4(f), we track this for the current trajectory during training. We

(a) Transition count, fixed trajectory $\tau^*$

(b) Region density, fixed trajectory $\tau^*$

(c) Transition count, current trajectory $\tau$

(d) Region density, $\tau^*$ and $\tau$

(e) Trajectory length, current trajectory $\tau$

(f) Repeat visits to regions, current trajectory $\tau$

(g) Density for random lines through the origin

(h) Density for random-action trajectories

Figure 4: Evolution of the number of transitions, linear region densities, and length of trajectories for HalfChee-tah, during training. Results for the rest of the environments are provided in the supplementary material. The ranges indicate the standard error across 5 random seeds. $[n_1, ..., n_d]$ in the legend corresponds to a network architecture with depth $d$ and $n_i$ neurons in each layer. Summary results are grouped by network depth, $d$.

speculate that repeat visits are high early in training because of limited exploration. Repeat visits remain later in training because of the cyclic nature of the learned locomotion for HalfCheetah.

## 5.2 Impact of Policy Network Structure on Expressivity

Our normalized density computation assumes that the number of transitions scales linearly with the number of neurons, $N$. However, we empirically observe that there remains a moderate dependence on the network depth, as seen in Figure 4(b), with deeper networks resulting in moderately denser regions in the learned policies. We further examine the policy network expressivity using random infinite lines. Following Hanin and Rolnick [2019a], for each policy network, we sample 100 random lines by randomly sampling 100 points from the final trajectory $\tau^*$, and connecting each randomly sampled point to the origin of the policy input space. Figure 4(g) shows the mean and standard deviation of the normalized number of transitions, $R_T/N$, as computed along these infinite lines in random directions passing through the origin, across the 100 random lines, over the 5 random seeds of each network configuration. These produce approximately uniform results throughout training, showing no overall changes in mean density in various directions. These results are also consistent with the findings of Hanin and Rolnick [2019a] as they show normalized region densities are close to 1 at initialization and remain roughly constant during training. We repeated the same experiment with 100 random lines through the mean point instead of the origin, by connecting each randomly sampled point to the mean of the 100 sampled points. The difference between the density over lines through the origin and through the mean point is negligible.

To further examine the behavior of the policy network on areas that it does not focus on exploring during training, we compute the region density along random trajectories created by taking random actions in the environment. For each policy network, we sample 10 such random trajectories $\tau^R$ and compute the normalized region density over these. Figure 4(h) shows the mean and standard deviation of this metric across the 10 random trajectories, over the 5 random seeds of each network configuration. This shows a very moderate decrease during training, with fairly consistent densities for all policy network configurations. We speculate that the slight decrease in density over time arises from the trained policy no longer visiting the same regions as the random-action policy. Comparing the results of random trajectories with fixed and current (Figure 4(b) and Figure 4(d)), we can see that the normalized region density over random-action trajectories and a fixed final trajectory are within the same range. Also, although this metric is higher over current trajectories early on during training, it eventually decreases and converges to the same range of region densities as the fixed trajectory.

In Figure 5, we visualize the regions of a policy network with trained on HalfCheetah in the 17-dimensional input space through three data points randomly sampled from the final fixed trajectory as well as through three points sampled from a random-action trajectory. Similarly, we do not observe any significant difference between the granularity of regions on a plane over points of the fixed trajectory compared with the granularity of regions on a plane over points of a random-action trajectory.

## 6 Conclusions

The structure of ReLU-based reinforcement learning policies remains poorly understood. In this work, we have explored a key property of such policies, the density of linear regions observed along policy trajectories, as a proxy for the complexity of functions they can learn. We performed a set of experiments to see how this evolves during training and whether and how changes in depth, and width of the policy network affect it. The hypothesis that the final policy trajectory sees an increase in region density is supported to a limited degree, as we observe a moderate increase in density during training, i.e., 50%. This result is consistent across tasks and across policy networks of different configurations. When observed from the vantage point of the evolving current trajectory, the region density is high to begin with, due to the limited length of early trajectories, and then decreases asymptotically towards the observed final density. For the tasks we consider, trajectory lengths are observed to grow and asymptotically approach a plateau during training. Overall, the surprising implication, for our experimental setting, is that the complexity of RL policies appears to be captured by fine-tuning during learning, rather than a significant growth in the complexity of the functions observed along trajectories of the final policy.

The key properties of linear regions as demonstrated for supervised learning of image classifiers, e.g., [Hanin and Rolnick, 2019a], are shown to generally also hold true for reinforcement learning policies. In particular, their expressivity is well modeled as being proportional to the number of neurons, and largely independent of their width and depth, for ranges of these parameters where good policies can

Figure 5: Linear regions that intersect e 2D plane through the input space for a network of depth 2 and width 32 trained on HalfCheetah-v2. Black dots indicate three points from the input space on which the plane is defined. In the first row, the three points are randomly sampled from the final trajectory trajectory $\tau^*$ whereas in the second row, the three points are randomly sampled from a random-action trajectory $\tau^R$.

still be learned. The number of regions observed for randomly oriented line segments through the origin of the input space is also in line with earlier theoretical and empirical results, and does not change significantly during training.

Our work comes with a number of limitations. All the tasks are locomotion-based and thus eventually produce cyclic trajectories. This could mean that the results may not generalize to other types of tasks. For example, some tasks may not result in transition counts that grow, as generally observed in our experiments. Currently, we compute only the mean region density for a trajectory; it may be useful to further understand the distribution of observed densities across trajectories. We note that it is common practice in RL to apply input (observation) normalization based on a rolling average of observations seen so far [Andrychowicz et al., 2020], and thus our results also employ this strategy. Applying RL without this normalization may impact both the performance of the RL algorithm and the resulting evolution of transition counts and region-density.

We leave a number of questions to future work, including understanding the behavior of observed linear regions in the contexts of other RL algorithms, behavior cloning, and more. Lastly, we believe that exploring possible connections with the lottery-ticket hypothesis [Frankle and Carbin, 2018] will be worthwhile.

As foundational research related to reinforcement learning, this work could be used to develop improved reinforcement learning policy structures and algorithms, with many possible applications, both good and bad in terms of societal impact.

# References

Marcin Andrychowicz, Anton Raichuk, Piotr Stańczyk, Manu Orsini, Sertan Girgin, Raphael Marinier, Léonard Hussenot, Matthieu Geist, Olivier Pietquin, Marcin Michalski, et al. What matters in on-policy reinforcement learning? a large-scale empirical study. *arXiv preprint arXiv:2006.05990*, 2020.

Raman Arora, Amitabh Basu, Poorya Mianjy, and Anirbit Mukherjee. Understanding deep neural networks with rectified linear units. *arXiv preprint arXiv:1611.01491*, 2016.

Devansh Arpit, Stanisław Jastrzębski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, et al. A closer look at memorization in deep networks. In *International Conference on Machine Learning*, pages 233–242. PMLR, 2017.

Lei Jimmy Ba and Rich Caruana. Do deep nets really need to be deep? *arXiv preprint arXiv:1312.6184*, 2013.

Peter L Bartlett, Dylan J Foster, and Matus J Telgarsky. Spectrally-normalized margin bounds for neural networks. *Advances in neural information processing systems*, 30, 2017.

Monica Bianchini and Franco Scarselli. On the complexity of neural network classifiers: A comparison between shallow and deep architectures. *IEEE transactions on neural networks and learning systems*, 25(8):1553–1565, 2014.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Gintare Karolina Dziugaite and Daniel M Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. *arXiv preprint arXiv:1703.11008*, 2017.

Vincent François-Lavet, Peter Henderson, Riashat Islam, Marc G Bellemare, and Joelle Pineau. An introduction to deep reinforcement learning. *arXiv preprint arXiv:1811.12560*, 2018.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv preprint arXiv:1803.03635*, 2018.

Boris Hanin and David Rolnick. Complexity of linear regions in deep networks. In *International Conference on Machine Learning*, pages 2596–2604. PMLR, 2019a.

Boris Hanin and David Rolnick. Deep relu networks have surprisingly few activation patterns. *Advances in neural information processing systems*, 32, 2019b.

Jieliang Luo, Sam Green, Peter Feghali, George Legrady, and Cetin Kaya Koç. Visual diagnostics for deep reinforcement learning policy development. *arXiv preprint arXiv:1809.06781*, 2018.

Hrushikesh Mhaskar, Qianli Liao, and Tomaso Poggio. Learning functions: when is deep better than shallow. *arXiv preprint arXiv:1603.00988*, 2016.

Hrushikesh N Mhaskar and Tomaso Poggio. Deep vs. shallow networks: An approximation theory perspective. *Analysis and Applications*, 14(06):829–848, 2016.

Guido Montúfar, Razvan Pascanu, Kyunghyun Cho, and Yoshua Bengio. On the number of linear regions of deep neural networks. *arXiv preprint arXiv:1402.1869*, 2014.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Icml*, 2010.

Behnam Neyshabur, Srinadh Bhojanapalli, David McAllester, and Nati Srebro. Exploring generalization in deep learning. *Advances in neural information processing systems*, 30, 2017.

Roman Novak, Yasaman Bahri, Daniel A Abolafia, Jeffrey Pennington, and Jascha Sohl-Dickstein. Sensitivity and generalization in neural networks: an empirical study. *arXiv preprint arXiv:1802.08760*, 2018.

Razvan Pascanu, Guido Montufar, and Yoshua Bengio. On the number of response regions of deep feed forward networks with piece-wise linear activations. *arXiv preprint arXiv:1312.6098*, 2013.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 2021.

Maithra Raghu, Ben Poole, Jon Kleinberg, Surya Ganguli, and Jascha Sohl-Dickstein. On the expressive power of deep neural networks. In *international conference on machine learning*, pages 2847–2854. PMLR, 2017.

Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of neural networks. In *International Conference on Machine Learning*, pages 5301–5310. PMLR, 2019.

Christian Rupprecht, Cyril Ibrahim, and Christopher J Pal. Finding and visualizing weaknesses of deep reinforcement learning agents. *arXiv preprint arXiv:1904.01318*, 2019.

Wojciech Samek, Thomas Wiegand, and Klaus-Robert Müller. Explainable artificial intelligence: Understanding, visualizing and interpreting deep learning models. *arXiv preprint arXiv:1708.08296*, 2017.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Thiago Serra, Christian Tjandraatmadja, and Srikumar Ramalingam. Bounding and counting linear regions of deep neural networks. In *International Conference on Machine Learning*, pages 4558–4566. PMLR, 2018.

Jure Sokolić, Raja Giryes, Guillermo Sapiro, and Miguel RD Rodrigues. Robust large margin deep neural networks. *IEEE Transactions on Signal Processing*, 65(16):4265–4280, 2017.

Zhi-Qin John Xu, Yaoyu Zhang, and Yanyang Xiao. Training behavior of deep neural network in frequency domain. In *International Conference on Neural Information Processing*, pages 264–274. Springer, 2019.

Tom Zahavy, Nir Ben-Zrihem, and Shie Mannor. Graying the black box: Understanding dqns. In *International Conference on Machine Learning*, pages 1899–1908. PMLR, 2016a.

Tom Zahavy, Bingyi Kang, Alex Sivak, Jiashi Feng, Huan Xu, and Shie Mannor. Ensemble robustness and generalization of stochastic deep learning algorithms. *arXiv preprint arXiv:1602.02389*, 2016b.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning (still) requires rethinking generalization. *Communications of the ACM*, 64(3):107–115, 2021.