Unsupervised Learning of Neurosymbolic Encoders

Abstract

We present a framework for the unsupervised learning of neurosymbolic encoders, which are encoders obtained by composing neural networks with symbolic programs from a domain-specific language. Our framework naturally incorporates symbolic expert knowledge into the learning process, which leads to more interpretable and factorized latent representations compared to fully neural encoders. We integrate modern program synthesis techniques with the variational autoencoding (VAE) framework, in order to learn a neurosymbolic encoder in conjunction with a standard decoder. The programmatic descriptions from our encoders can benefit many analysis workflows, such as in behavior modeling where interpreting agent actions and movements is important. We evaluate our method on learning latent representations for real-world trajectory data from animal biology and sports analytics. We show that our approach offers significantly better separation than standard VAEs and leads to practical gains on downstream analysis tasks, such as for behavior classification.

1 Introduction

Advances in unsupervised learning have enabled the discovery of latent structures in data from a variety of domains, such as image data (Dupont, 2018), sound recordings (Calhoun et al., 2019), and tracking data (Luxem et al., 2020). For instance, a common approach is to use encoder-decoder frameworks, such as variational autoencoders (VAEs) (Kingma & Welling, 2014), to identify a low-dimensional latent representation from the raw data that could contain disentangled factors of variation (Dupont, 2018) or semantically meaningful clusters (Luxem et al., 2020). Such approaches typically employ complex mappings based on neural networks, and explaining how the model assigns inputs to latent representations can be challenging (Zhang et al., 2020).

In this paper, we introduce *unsupervised neurosymbolic representation learning*, which allows part of a representation to be computed using symbolic *encoder programs* written in a predefined domain-specific language (DSL). (The rest of the representation is computed using a neural network.) The use of such neurosymbolic encoders can offer two key benefits over purely neural approach. First, since a DSL reflects structured domain knowledge, neurosymbolic encoders can often produce representations that are human-interpretable (Verma et al., 2018; Shah et al., 2020). Second, as observed in studies that used hand-crafted programmatic encoders (Zhan et al., 2020), these representations can potentially be more factorized or well-separated (and semantically meaningful) than purely neural representations.

Our learning algorithm is grounded in the VAE framework (Kingma & Welling, 2014; Mnih & Gregor, 2014) and aims to discover a neurosymbolic encoder coupled with a standard neural decoder.[1] A key challenge here is that the space of programs in a DSL is combinatorial. We tackle this problem by assuming programs to be differentiable and by tightly integrating standard VAE training with modern program synthesis methods (Chaudhuri et al., 2021; Shah et al., 2020). We further show how to incorporate ideas from adversarial information factorization (Creswell et al., 2017) and enforcing capacity constraints (Burgess et al., 2017; Dupont, 2018) in order to mitigate issues such as posterior and index collapse in the learned representation.

Programmatic descriptions from neurosymbolic encoders are especially useful in behavior analysis (Segalin et al., 2020; Sun et al., 2021b), where domain experts routinely interpret clusters of behaviors as part of an

---

[1]Some prior work have studied the complementary problem of learning (neuro-)symbolic decoders (e.g,. Ellis et al. (2018); Feinman & Lake (2020)). See Section 5 for more discussion.

analysis workflow. Accordingly, our experimental evaluation focuses on this setting. By integrating domain knowledge using program synthesis, we demonstrate that our clusters are inherently interpretable and better aligned with human-annotated labels across multiple behavior analysis datasets. To validate the end-to-end practicality for analysis workflows, we integrate our automatically learned programs into a state-of-the-art behavior analysis framework, Task Programming (Sun et al., 2021b), that typically relies on expert-crafted programs, and demonstrate competitive performance using our automatically synthesized programs.

To summarize, our contributions are:

- We propose a neurosymbolic approach to representation learning, in which part of the latent representation is produced by an interpretable encoder program, while the rest is computed using a neural network.

- We realize the approach via a learning algorithm that combines VAE training and program synthesis.

- We show that our approach can significantly outperform purely neural encoders in extracting semantically meaningful representations of behavior, as measured by standard unsupervised metrics.

- We further explore the flexibility of our approach, by showing that performance can be robust across different DSL designs by domain experts.

- We showcase the practicality of our approach on downstream tasks, by incorporating our approach into a state-of-the-art self-supervised learning approach for behavior analysis (Sun et al., 2021b).

2 Background

2.1 Variational Autoencoders

We build on VAEs (Kingma & Welling, 2014; Mnih & Gregor, 2014), a latent variable modeling framework shown to learn effective latent representations (also called encodings/embeddings) (Higgins et al., 2016; Zhao et al., 2017; Yingzhen & Mandt, 2018) and can capture the generative process (Oord et al., 2017; Vahdat & Kautz, 2020; Zhan et al., 2020). VAEs introduce a latent variable $\mathbf{z}$, an encoder q_ϕ, a decoder p_θ, and a prior distribution p on $\mathbf{z}$. ϕ and θ are the parameters of the q and p respectively, often instantiated with neural networks. The learning objective is to maximize the evidence lower bound (ELBO) of the data log-likelihood:

$$\text{ELBO} := \quad \mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})} \big[\log p_\theta(\mathbf{x}|\mathbf{z}) \big] - D_{KL}\big(q_\phi(\mathbf{z}|\mathbf{x}) || p(\mathbf{z}) \big) \leq \quad \log p(\mathbf{x}). \tag{1}$$

The first term in Eq. 1 is the log-density assigned to the data, while the second term is the KL-divergence between the prior and approximate posterior of $\mathbf{z}$. Latent representations $\mathbf{z}$ are often continuous and modeled with a Gaussian prior, but $\mathbf{z}$ can be modeled to contain discrete dimensions as well (Kingma et al., 2014; Hu et al., 2017; Dupont, 2018). Our experiments are focused on behavioral tracking data in the form of trajectories, and so in practice we utilize a trajectory variant of VAEs (Co-Reyes et al., 2018; Zhan et al., 2020; Sun et al., 2021b), described in Section 3.4.

One challenge with VAEs (and deep encoder-decoder models in general) is that while the model is expressive, it is often difficult to interpret what is encoded in the latent representation $\mathbf{z}$. Common approaches include taking traversals in the latent space and visualizing the resulting generations (Burgess et al., 2017), or post-processing the latent variables using techniques such as clustering (Luxem et al., 2020). Such techniques are post-hoc and thus cannot guide (in an interpretable way) the encoder to be biased towards a family of structures. Some recent work have studied how to impose structure in the form of graphical models or dynamics in the latent space (Johnson et al., 2016; Deng et al., 2017), and our work can be thought of as a first step towards imposing structure in the form of symbolic knowledge encoded in a domain specific programming language.

2.2 Synthesis of Differentiable Programs

Our approach utilizes recent work on the synthesis of differentiable programs (Chaudhuri et al., 2021; Shah et al., 2020; Valkov et al., 2018), where one learns both the discrete structure of the symbolic program

Figure 1: **Learning Neurosymbolic Encoders: Sketch of Algorithm 1** (Section 3.1). The symbolic encoder is initially fully neural. We alternate between VAE training with the program architecture fixed (Step 1), and supervised program learning to increase the depth of the program by 1 (Step 2). Once we reach a symbolic program, we train the model one last time to learn all the parameters. The color (in terms of lightness) of the symbolic encoder corresponds to the encoder becoming more symbolic over time.

(analogous to the architecture of a neural network) as well as the differentiable parameters within that structure. Our formulation closely follows that of Shah et al. (2020). We use a domain-specific programming language (DSL), generated with a context-free grammar (see Figure 2 for an example). A program is represented as a pair (α, ψ), where α is a discrete program architecture and ψ are its real-valued parameters. We denote $\mathcal{P}$ as the space of symbolic programs (i.e. programs with complete architectures). The semantics of a program (α, ψ) is given by a function $[\![\alpha]\!](x, \psi)$ that is guaranteed to be differentiable in both x and ψ.

Like Shah et al. (2020), we pose the problem of learning differentiable programs as search through a directed program graph $\mathcal{G}$. The graph $\mathcal{G}$ models the top-down construction of program architectures α through the repeated firing of rules of the DSL grammar, starting with an *empty* architecture (represented by the "start" nonterminal of the grammar). The *leaf nodes* of $\mathcal{G}$ represent programs with *complete* architectures (no nonterminals). Thus, $\mathcal{P}$ is the set of programs in the leaf nodes of $\mathcal{G}$. The other nodes in $\mathcal{G}$ contain programs with *partial* architectures (has at least one nonterminal). We interpret a program in a non-leaf node as being neurosymbolic, by viewing its nonterminals as representing neural networks with free parameters. The root node in $\mathcal{G}$ is the empty architecture α_0, interpreted as a fully neural program. An edge (α, α') exists in $\mathcal{G}$ if one can obtain α' from α by applying a rule in the DSL that replaces a nonterminal in α.

Program synthesis in this problem setting equates to searching through $\mathcal{G}$ to find the optimal complete program architecture, and then learning corresponding parameters ψ, i.e., to find the optimal (α, ψ) that minimizes a combination of standard training loss (e.g., classification error) and structural loss (preferring "simpler" α's). Shah et al. (2020) evaluate multiple strategies for solving this problem and finds *informed search using admissible neural heuristics* to be the most efficient strategy (see appendix). Consequently, we adopt this algorithm for our program synthesis task.

3 Neurosymbolic Encoders

The structure of our neurosymbolic encoder is shown in the right diagram of Figure 1. The latent representation $\mathbf{z} = [\mathbf{z}_\phi, \mathbf{z}_{(\alpha, \psi)}]$ is partitioned into neurally encoded $\mathbf{z}_\phi$ and programmatically encoded $\mathbf{z}_{(\alpha, \psi)}$. This approach boasts several advantages:

- The symbolic component of the latent representation is programmatically interpretable.

- The neural component can encode any residual information not captured by the program, which maintains the model's capacity compared to deep encoders.

- By incorporating a modular design, we can leverage state-of-the-art learning algorithms for both differentiable encoder-decoder training and program synthesis.

We denote q_ϕ and $q_{(\alpha, \psi)}$ as the neural and symbolic encoders respectively (see Figure 1), where $\mathbf{z}_\phi \sim q_\phi(\cdot|\mathbf{x})$ and $\mathbf{z}_{(\alpha, \psi)} \sim q_{(\alpha, \psi)}(\cdot|\mathbf{x})$. q_ϕ is instantiated with a neural network, but $q_{(\alpha, \psi)}$ is a differentiable program with

architecture α and parameters ψ in some program space $\mathcal{P}$ defined by a DSL. Given an unlabeled training set of $\mathbf{x}$'s, the VAE learning objective in Eq. 1 then becomes:

$$
\max_{\phi,(\alpha,\psi),\theta} \quad \mathbb{E}_{q_\phi(\mathbf{z}_\phi|\mathbf{x})q_{(\alpha,\psi)}(\mathbf{z}_{(\alpha,\psi)}|\mathbf{x})} \Big[\underbrace{\log p_\theta(\mathbf{x}|\mathbf{z}_\phi, \mathbf{z}_{(\alpha,\psi)})}_{\text{reconstruction loss}} \Big]
$$
$$
- \underbrace{D_{KL}\big(q_\phi(\mathbf{z}_\phi|\mathbf{x})||p(\mathbf{z}_\phi)\big)}_{\text{regularization for neural latent}} - \underbrace{D_{KL}\big(q_{(\alpha,\psi)}(\mathbf{z}_{(\alpha,\psi)}|\mathbf{x})||p(\mathbf{z}_{(\alpha,\psi)})\big)}_{\text{regularization for symbolic latent}}.
\tag{2}
$$

Compared to the standard VAE objective in Eq. 1 for a single neural encoder, Eq. 2 has separate KL-divergence terms for the neural and programmatic encoders.

3.1 Learning Algorithm

The challenge with solving for Eq. 2 is that while (ϕ, ψ, θ) can be optimized via back-propagation with α fixed, optimizing for α is a discrete optimization problem. Since it is difficult to jointly optimize over both continuous and discrete spaces, we take an iterative, alternating optimization approach. We start with a fully neural program (one with empty architecture α_0 as described in Section 2.2) trained using standard differentiable optimization (Figure 1, Step 1). We then gradually make it more symbolic (Figure 1, Step 2) by finding a program that is a child of the current program in $\mathcal{G}$ (more symbolic by construction of $\mathcal{G}$) that outputs as similar to the current latent representations as possible:

$$
\min_{\alpha':(\alpha,\alpha')\in\mathcal{G}, \ \psi'} \quad \mathcal{L}_{\text{supervised}}\big(q_{(\alpha,\psi)}(\mathbf{x}), q_{(\alpha',\psi')}(\mathbf{x})\big),
\tag{3}
$$

which can be viewed as a form of distillation (from less symbolic to more symbolic programs) via matching the input/output behavior. We solve Eq. 3 by enumerating over all child programs and selecting the best one, which is similar to iteratively-deepened depth-first search in Shah et al. (2020) (see appendix). We alternate between optimizing Eq. 2 and Eq. 3 until we obtain a complete program. Algorithm 1 outlines this procedure and is guaranteed to terminate if $\mathcal{G}$ is finite by specifying a maximum program depth.

We chose this optimization procedure for two reasons. First, it maximally leverages state-of-the-art tools in both differentiable latent variable modeling (VAE-style training) and supervised program synthesis (for distillation), leading to tractable algorithm design. Second, this procedure never makes a drastic change to the program architecture, leading to relatively stable learning behavior across iterations.

Algorithm 1 Learning a neurosymbolic encoder	**Algorithm 2** Learning a neurosymbolic encoder with k programs
1: **Input**: program space $\mathcal{P}$, program graph $\mathcal{G}$	
2: initialize $\phi, \psi, \theta, \alpha = \alpha_0$ (empty architecture)	1: **Input**: program space $\mathcal{P}$, program graph $\mathcal{G}$, k
3: **while** α is not complete **do**	2: **for** $i = 1..k$ **do**
4: $\quad \phi, \psi, \theta \leftarrow$ optimize Eq. 2 with α fixed	3: $\quad$ fix programs $\{q_{(\alpha_1,\psi_1)}, \dots, q_{(\alpha_{i-1},\psi_{i-1})}\}$
5: $\quad (\alpha, \psi) \leftarrow$ optimize Eq. 3	4: $\quad$ execute Algorithm 1 to learn $q_{(\alpha_i,\psi_i)}$
6: **end while**	5: $\quad$ remove $q_{(\alpha_i,\psi_i)}$ from $\mathcal{P}$ to avoid redundancies
7: $\phi, \psi, \theta \leftarrow$ optimize Eq. 2 with complete α	6: **end for**
8: **Return**: encoder $\{q_\phi, q_{(\alpha,\psi)}\}$	7: **Return**: encoder $\{q_\phi, q_{(\alpha_1,\psi_1)}, \dots, q_{(\alpha_k,\psi_k)}\}$

3.2 Learning Multiple Programs

The interpretability of latent representations induced by symbolic encoders $q_{(\alpha,\psi)}$ ultimately depends on the DSL. For instance, a program that encodes to one of ten classes may not be very interpretable if it involves a matrix multiplication within the program. Instead, we learn *binary* programs that encode sequences into one of two classes (using binary cross-entropy for $\mathcal{L}_{\text{supervised}}$, a uniform prior on $\mathbf{z}_{(\alpha,\psi)}$, and Gumbel-Softmax (Jang et al., 2017) to sample from the posterior). Figures 4a & 4b depict learned binary programs that encode mice trajectories and their interpretations.

To encode more than two classes, we simply learn multiple binary programs by extending Eq. 2 to sum over $\mathcal{L}_{\text{supervised}}$ for k symbolic programs $\{q_{(\alpha_1,\psi_1)}, \dots, q_{(\alpha_k,\psi_k)}\}$ and corresponding latent representations $\{\mathbf{z}_{(\alpha_1,\psi_1)}, \dots, \mathbf{z}_{(\alpha_k,\psi_k)}\}$. This results in 2^k classes and a solution space that now scales exponentially (e.g.

$|\mathcal{P}|^k$ if using exhaustive enumeration). Algorithm 2 outlines our greedy solution that reuses Algorithm 1 by iteratively learning one symbolic program at a time. We leave the exploration of more sophisticated search methods as future work.

3.3 Dealing with Posterior and Index Collapse

Deep latent variable models, especially those with discrete latent variables, are notoriously prone to both posterior (Bowman et al., 2015; Chen et al., 2016b; Oord et al., 2017) and index (Kaiser et al., 2018) collapse. Since our algorithms optimize for such models repeatedly, they can be susceptible to these failure modes. Below, we summarize two strategies that we found to work well in our setting.[2]

Adversarial information factorization. Creswell et al. (2017) introduces an adversarial network A_ω that aims to predict $\mathbf{z}_{(\alpha,\psi)}$ from $\mathbf{z}_\phi$. Maximizing this adversarial loss can prevent index collapse, where all data is encoded into one class, as doing so would would not fool the adversary:

$$\max_{\phi,(\alpha,\psi),\theta} \quad \mathbb{E}_{q_\phi(\mathbf{z}_\phi|\mathbf{x})q_{(\alpha,\psi)}(\mathbf{z}_{(\alpha,\psi)}|\mathbf{x})} \Big[\log p_\theta(\mathbf{x}|\mathbf{z}_\phi, \mathbf{z}_{(\alpha,\psi)}) + \underbrace{\min_\omega \mathcal{L}_{\text{adv}}\big(A_\omega(\mathbf{z}_\phi), \mathbf{z}_{(\alpha,\psi)}\big)}_{\text{adversary}} \Big]$$
$$- D_{KL}\big(q_\phi(\mathbf{z}_\phi|\mathbf{x})||p(\mathbf{z}_\phi)\big) - D_{KL}\big(q_{(\alpha,\psi)}(\mathbf{z}_{(\alpha,\psi)}|\mathbf{x})||p(\mathbf{z}_{(\alpha,\psi)})\big) \tag{4}$$

Channel capacity constraint. (Burgess et al., 2017; Dupont, 2018) forces the KL-divergence terms to match capacities C_ϕ and $C_{(\alpha,\psi)}$. Since the KL-divergence is an upper bound on the mutual information between latent variables and the data (Kim & Mnih, 2018; Dupont, 2018), this encourages the latent variables to encode information and aims to prevent posterior collapse.

$$\max_{\phi,(\alpha,\psi),\theta} \quad \mathbb{E}_{q_\phi(\mathbf{z}_\phi|\mathbf{x})q_{(\alpha,\psi)}(\mathbf{z}_{(\alpha,\psi)}|\mathbf{x})} \Big[\log p_\theta(\mathbf{x}|\mathbf{z}_\phi, \mathbf{z}_{(\alpha,\psi)})\Big]$$
$$- \gamma_\phi |D_{KL}\big(q_\phi(\mathbf{z}_\phi|\mathbf{x})||p(\mathbf{z}_\phi)\big) - C_\phi| - \gamma_{(\alpha,\psi)}|D_{KL}\big(q_{(\alpha,\psi)}(\mathbf{z}_{(\alpha,\psi)}|\mathbf{x})||p(\mathbf{z}_{(\alpha,\psi)})\big) - C_{(\alpha,\psi)}| \tag{5}$$

In our algorithms, we augment our initial objective in Eq. 2 with Eq. 4 and Eq. 5.

3.4 Instantiation for Sequential Domains

The objective in Eq. 2 describes a general problem that is applicable to any domain. In our experiments, we focus on the sequential domain of trajectory data. Trajectory data is often used in scientific applications where interpretability is desirable, such as behavior discovery (Luxem et al., 2020; Hsu & Yttri, 2020). The ability to easily explain the learned latent representation using programs can help domain experts better understand the structure in their data. Additionally, trajectory data is often low dimensional for each timestamp, which helps experts encode domain knowledge into the DSL more easily (Shah et al., 2020; Sun et al., 2021b; Zhan et al., 2020).

In this domain, $\mathbf{x}$ is a trajectory of length T: $\mathbf{x} = \{x_1, \ldots, x_T\}$. We then factorize the log-density in Eq. 2 as a product of conditional probabilities:

$$\log p_\theta(\mathbf{x}|\mathbf{z}_\phi, \mathbf{z}_{(\alpha,\psi)}) = \sum_{t=1}^{T} \log p_\theta(x_t|x_{<t}, \mathbf{z}_\phi, \mathbf{z}_{(\alpha,\psi)}). \tag{6}$$

When q_ϕ and p_θ are instantiated with recurrent neural networks (RNN), the model is more commonly known as a trajectory-VAE (TVAE) Co-Reyes et al. (2018).

As symbolic encoder $q_{(\alpha,\psi)}$ maps sequences to vectors, we adopt a DSL (Figure 2) previously used for sequence classification (Shah et al., 2020). Our DSL is purely functional and contains both basic algebraic operations and parameterized library functions. Domain experts can easily augment the DSL with their own functions, such as selection functions that select subsets of features that they deem potentially important. We ensure that all programs in our DSL are differentiable, utilizing a smooth approximation of the nondifferentiable **if-then-else** construct (Shah et al., 2020). Figures 4a & 4b depict example programs in our DSL (full details in the appendix).

---

[2]There are many approaches available for tackling both these issues, but we emphasize that these contributions are orthogonal to ours; as techniques for preventing posterior and index collapse improve, so will the robustness of our algorithm.

$$\alpha \quad ::= \quad x \mid \oplus(\alpha_1, \ldots, \alpha_k) \mid \oplus_\theta(\alpha_1, \ldots, \alpha_k)$$
$$\textbf{if } \alpha_1 \textbf{ then } \alpha_2 \textbf{ else } \alpha_3 \mid \textbf{sel}_S \ x \mid \textbf{mapaverage } (\textbf{fun } x_1.\alpha_1) \ x$$

Figure 2: Our DSL for sequential domains, similar to the one used in Shah et al. (2020). x, $\oplus$, and $\oplus_\theta$ represent inputs, basic algebraic operations, and parameterized library functions, respectively. **fun** $x.e(x)$ represents a function that evaluates an expression $e(x)$ over the input x. **sel**$_S$ selects a subset S of the dimensions of the input x. **mapaverage** g x applies the function g to every element of the sequence x and returns the average of the results. We employ a different approximation of the **if-then-else** construct.

4 Experiments

We take a multi-faceted approach to evaluate our unsupervised learning approach using synthetic data and real-world data from animal behavior and sports analytics. We also show the end-to-end practicality of our programs by applying them to a downstream behavior classification framework. Our research questions are:

- **Q1: Are the clusters created with our programs meaningful?** (Section 4.2). We evaluate this aspect both qualitatively and quantitatively by comparing with the truth generative process on synthetic datasets, as well as by comparing to human annotated labels on real-world datasets.

- **Q2: How sensitive is our approach to different DSL choices?** (Section 4.3). We compare programs learned in our framework from three different DSLs designed by three domain experts for studying animal behavior.

- **Q3: Are the programs useful for downstream tasks?** (Section 4.4). Ultimately, the practicality of these methods must be validated by their usefulness in downstream tasks such as those used in scientific analyses. We apply our unsupervised programs to a behavior classification framework called task programming Sun et al. (2021b). This framework uses hand-crafted programs for self-supervision, which we replace with our automatically learned programs.

4.1 Experimental Setup

4.1.1 Datasets

We summarize the datasets used in our experiments, and provide full details in the appendix.

Synthetic. We generate synthetic trajectories by sampling initial positions and velocities from a Gaussian distribution and introducing 2 ground-truth factors of variation as large external forces in the positive/negative x/y directions that affect velocity, totaling to 4 discrete classes. Velocities are fixed for the entire trajectory, but we also sample small Gaussian noise at each timestep. We generate 10k/2k/2k trajectories of length 25 for train/validation/test. Figure 3a shows 50 trajectories from the training set. We evaluate qualitatively whether or not our algorithm can learn programs that reflect the ground-truth factors of variation.

CalMS21. Our primary real-world dataset is the CalMS21 dataset (Sun et al., 2021a), containing trajectories of socially interacting mice captured for neuroscience experiments. Each frame contains 7 tracked keypoints for each of two mice. The dataset has one set of unlabeled tracking data, which we use to train our neurosymbolic encoder, and another set annotated for 4 behaviors, which we use to evaluate our programs. Specifically, our evaluation uses labels from the test split of the CalMS21 classification task. We have 231k/52k/262k trajectories of length 21 for train/val/test. The features in our DSL are selected by a domain expert based on the attributes from (Segalin et al., 2020).

Basketball. We use the same basketball dataset as in (Shah et al., 2020; Zhan et al., 2020) that tracks professional basketball players. Each trajectory is of length 25 over 8 seconds and contains the xy-positions of 10 players. We split trajectories by grouping offensive and defensive players (5 each), effectively doubling the dataset size. We evaluate our algorithm and the baselines with respect to the labels of offensive/defensive players. Our DSL includes additional domain features like player speed and distance-to-basket. In total, we have 177k/31k/27k trajectories for train/val/test.

4.1.2 Quantitative Evaluation Setup

The quantitative evaluations are used to compare our neurosymbolic encoders with baseline unsupervised learning methods on the real-world datasets.

Baselines. We compare our model containing a neurosymbolic encoder against other approaches based on VAEs. In particular, we compare against JointVAE (Dupont, 2018), which also has both discrete and continuous latent representations, and can be viewed as a fully neural version of our neurosymbolic encoder. Other baselines include VAE, VAE with K-means loss used in (Ma et al., 2019; Luxem et al., 2020), and Beta-VAE (Burgess et al., 2017). These models have a fully neural encoder and learn continuous latent representations, which we can then use to produce clusters with K-means clustering (Lloyd, 1982). We additionally compare against VQ-VAEs (Oord et al., 2017), which produce discrete latent clusters. We use the TVAE version of all baselines (details included in the appendix).

Metrics. Unlike in the synthetic setting, we do not have ground truth programs in the real-world datasets. We thus evaluate our programs quantitatively using (1) standard cluster metrics relative to human-defined labels, and (2) average precision for behavior classification when integrating our programs into downstream tasks. For cluster metrics, we use Purity (Schütze et al., 2008), Normalized Mutual Information (NMI) (Zhang et al., 2006), and Rand Index (RI) (Rand, 1971). We report the median of three runs. More details, including the standard deviation and the ELBO, are in the appendix.

4.2 Q1: Are the clusters created with our programs meaningful?

(a) 50 synthetic trajectories   (b) learned programs   (c) $\mathbf{z}_\phi$, 0 programs   (d) $\mathbf{z}_\phi$, 1 program   (e) $\mathbf{z}_\phi$, 2 programs

Figure 3: **Synthetic dataset experiments.** **(a)** Trajectories in synthetic training set. Initial/final positions are indicated in green/blue. Red lines delineate ground-truth classes, based on final positions. **(b)** $k = 2$ learned binary programs using our algorithm. The first program (top) thresholds the final x-position while the second program (bottom) thresholds the final y-position. **(c, d, e)** Neural latent variables reduced to 2 dimensions. Top/bottom rows are colored by final x/y-positions respectively (green/yellow is positive/negative). **(c)** Clusters in TVAE neural latent space correspond to 4 ground-truth classes. **(d)** After learning the first program, the neural latent space contains clusters only based on the final y-position. **(e)** After learning the second program, all 4 ground-truth classes have been extracted as programs and the remaining neural latent space contains no clear clustering.

Synthetic dataset experiments. Our synthetic dataset consists of trajectory data with 4 ground truth classes, corresponding to positive/negative x/y directions. We visualize the neural latent space in 2 dimensions of a TVAE with 0, 1, and 2 learned programs in Figure 3bcd. The initial TVAE latent space contains 4 clusters corresponding to the 4 ground-truth classes in Figure 3c. After our algorithm learns the first program that thresholds the final x-position, the resulting latent space in Figure 3d captures the other factor of variation as 2 clusters corresponding to the final y-positions. Lastly, when our algorithm learns a second program that thresholds the final y-position, the resulting latent space in Figure 3e no longer contains any clear clustering, as we've successfully extracted the 4 ground-truth classes with our 2 programs.

Real-world datasets experiments. We compare clusters produced by our neurosymbolic encoder with fully neural autoencoding baselines (Table 1), measured against human-annotated behaviors. For CalMS21,

$$\mathbb{1}_{[>-7]} \left[\begin{array}{l} \textbf{mapaverage } (\textbf{fun } x_t. \\ \quad \textbf{multiply } (ResidentSpeedAffine_{[-6.3];-8.3}(x_t), \\ \quad NoseTailDistAffine_{[.04];-9.1}(x_t)) \ x \end{array} \right]$$

(a) **Program learned using CalMS21 DSL 1**, resulting NMI 0.428. Since speed is positive, the first term is always negative. One cluster thus generally consists of trajectories where the mice are further apart, such that the second term is positive, and the negative product is less than the threshold. The other cluster generally occurs when the mice are close together, the second term is negative, and the product will be positive.

$$\mathbb{1}_{[>-5.7]} \left[\begin{array}{l} \textbf{mapaverage } (\textbf{fun } x_t. \\ \quad \textbf{add } (ResidentAxisRatioAffine_{[-8.0];-7.1}(x_t), \\ \quad BoundingBoxIOUAffine_{[-16.6];5.9}(x_t)) \ x \end{array} \right]$$

(b) **Program learned using CalMS21 DSL 2**, resulting NMI 0.320. The axis ratio is the ratio of major axis length and minor axis length of an ellipse fitted to the mouse keypoints. The second term measures the bounding box overlap between mice, and is zero when the mice are far apart. It follows that one cluster generally contains trajectories when the mice has larger bounding box overlaps or if the resident axis ratio is large. The other cluster thus contains trajectories where the mice bounding boxes do not overlap, and resident body is compact.

Figure 4: Learned programs on CalMS21. The subscripts represents the learned weights (in brackets) and biases (after the brackets) for the affine transformation followed by the bias.

Model	CalMS21			Basketball		
	Purity	NMI	RI	Purity	NMI	RI
Random assignment	.597	.000	.536	.500	.000	.500
TVAE	.598	.089	.564	.501	.001	.500
TVAE+KMeans loss	.605	.118	.573	.501	.001	.500
JointVAE	.597	.019	.537	.560	.034	.507
VQ-TVAE	.601	.124	.588	.572	.016	.511
Beta-TVAE	.616	.115	.589	.565	.013	.509
Ours (1 program)	.706	.423	.694	.596	.027	.518
Ours (2 programs)	.725	.320	.648	.561	.033	.507
Ours (3 programs)	.756	.314	.633	.584	.022	.514

Table 1: **Evaluating clusters from baseline and our neurosymbolic encoders on human-annotated labels.** Median purity, NMI, and RI on CalMS21 and Basketball compared to human-annotated labels (3 runs). Experiment hyperparameters are included in the appendix.

we observe that our method consistently outperforms the baselines in all three cluster metrics. We note that purity increases as the number of programs (thus clusters) increase, while NMI and RI decrease. This implies our method with two clusters best correspond to CalMS21 behaviors, but the other clusters found by our method may still be useful for domain experts. For Basketball, our method improves slightly with respect to purity, but is overall comparable with the baselines.

Qualitative interpretation of our clusters. We further study the programs and clusters produced by our algorithm for the CalMS21 dataset, through a qualitative study with a domain expert in behavioral neuroscience. In the single program case, the domain expert classified the discovered clusters as when the mice are interacting and when there are no interaction. They noted that this is based on distance between the mice, which is consistent with our program (Figure 4a) using distance between nose of resident and tail of intruder. For two programs, there are a total of four clusters, with two clusters each corresponding to no interaction and interaction. For the interaction clusters, the domain expert was further able to identify sniff tail behavior as one of the clusters. In this case, the programs found were based on intruder head body angle, resident nose and intruder tail distance, and resident nose and intruder nose distance. The domain expert found the three program case to be more difficult to interpret, but was able to identify clusters corresponding to sniff tail, resident exploration, interaction facing the same direction (ex: mounting), and interaction facing opposite directions (ex: face-to-face sniffing).

Model	CalMS21 (DSL 1)			CalMS21 (DSL 2)			CalMS21 (DSL 3)		
	Purity	NMI	RI	Purity	NMI	RI	Purity	NMI	RI
Ours (1 program)	.706	.423	.694	.689	.364	.681	.649	.325	.616
Ours (2 programs)	.725	.320	.648	.715	.359	.673	.664	.324	.634

Table 2: **Effect of varying DSLs on CalMS21 for neurosymbolic encoders.** Median purity, NMI, and RI on CalMS21 of our algorithms with DSLs selected by three domain experts compared to human-annotated labels (3 runs). DSL1 corresponds to Table 1.

Model	CalMS21			Basketball		
	Purity	NMI	RI	Purity	NMI	RI
TVAE	.598	.089	.564	.501	.001	.500
TVAE (w/ features)	.597	.103	.570	.565	.012	.508
VQ-TVAE	.601	.124	.588	.571	.016	.511
VQ-TVAE (w/ features)	.608	.114	.601	.525	.002	.501
Beta-TVAE	.616	.115	.589	.566	.013	.509
Beta-TVAE (w/ features)	.612	.096	.571	.563	.011	.508

Table 3: **Effect of encoding DSL features into baselines.** Median purity, NMI, and RI on CalMS21 and Basketball compared to human-annotated labels (3 runs) for baseline with trajectory inputs only, and baseline with trajectory features added.

4.3 Q2: How sensitive is our approach to the DSL?

Choice of DSL. To study the effect of DSL choices, we worked with three domain experts to construct three different DSLs used to learn our programmatic representations. These DSLs contained 8 to 10 different behavioral features for studying mouse social behavior on CalMS21, in addition to common sequential operations (Figure 2). A full list of features selected by domain experts are in the appendix.

While there is some variability, our approach consistently outperforms the baselines that contain fully neural encoders for all three DSLs (Table 2). Comparing some learned programs from two DSLs (Figures 4a, 4b), both contain a term that correlates with whether the mice are interacting (distance and bounding box overlap), and another term that correlates with resident speed (mice tends to be more stretched when they are moving quickly).

DSL features as input. Lastly, we experiment with using the same DSL features introduced by domain experts as additional features for input trajectories instead (Table 3). For both CalMS21 and Basketball, the baselines using the additional features have comparable performance to using input trajectory data alone. In contrast, by using the features more explicitly as part of the DSL in our neurosymbolic encoders, we are able to produce clusters with a better separation between behavior classes based on cluster metrics (see Table 1).

4.4 Q3: Are the programs useful for downstream tasks?

We apply our programs to frame-level behavior classification (Segalin et al., 2020; Eyjolfsdottir et al., 2016; Burgos-Artizzu et al., 2012), where the goal is to automatically quantify behavior based on expert annotations. We are motivated by the observation that manual behavior annotation is time-consuming and expensive (Anderson & Perona, 2014), often being a bottleneck in the analysis workflow. Our unsupervised programs have the potential to reduce annotation effort and help accelerate behavioral studies, through the task programming framework. Task programming Sun et al. (2021b) uses hand-crafted programs as self-supervision to improve behavior classification data efficiency; however, hand designing programs still requires human effort. Here, we show that unsupervised programs learned using our neurosymbolic encoders performs comparably to expert-designed programs.

We integrate the learned programs from our neurosymbolic encoder into the task programming framework (i.e., use them as a source of self-supervision instead of the expert-crafted programs), and compare to the classification performance using expert programs (Figure 5). Using only one program found using our approach, we are able to achieve comparable performance to 10 expert-written programs on the behavior

Figure 5: **Applying symbolic encoders for self-supervision.** "Features" is baseline w/o self-supervision. "TREBA" is a self-supervised approach in the Task Programming paradigm (Sun et al., 2021b), using either expert-crafted programs or our symbolic encoders as the weak-supervision rules. The shaded region is std dev over 9 repeats. The std dev for our approach (not shown) is comparable.

classification task studied in Sun et al. (2021b). Importantly, we note that we automatically learned the self-supervision tasks from a DSL, instead of hand-crafting them as in Sun et al. (2021b). This demonstrates that programs found by our approach can be applied effectively to downstream behavior analysis tasks such as task programming.

5 Other Related Work

Interpretable latent variable models. Latent representations, especially those that are human-interpretable, can help us understand the structure of data. These models may learn disentangled factors (Higgins et al., 2016; Chen et al., 2016a; Ma et al., 2020) or semantically meaningful clusters (Ma et al., 2019) using unsupervised learning approaches. These approaches are often grounded in the VAE framework (Kingma & Welling, 2014). Some of these approaches, such as JointVAE (Dupont, 2018), Discrete VAE (Rolfe, 2016), Guided-VAE (Ding et al., 2020), and VQ-VAE (Oord et al., 2017), learn discrete latent representations (in particular, JointVAE learns a combined discrete-continuous representation, just like our approach). However, these approaches use fully neural encoders. To our knowledge, our work is the first to propose neurosymbolic encoders, where the symbolic component produces a symbolic program that produces an low-dimensional encoding of the input data.

Neurosymbolic programming. Neurosymbolic programming (Chaudhuri et al., 2021) has seen much activity in the recent past. Existing approaches here are often trained in a supervised fashion (Gulwani, 2011; Wang et al., 2017; Shah et al., 2020; Cui & Zhu, 2021), or within a (generative) policy learning context with an explicit reward function (Chen et al., 2018; Verma et al., 2018; 2019; Bastani et al., 2018; Inala et al., 2020; Feinman & Lake, 2020; Trivedi et al., 2021). Prior work on unsupervised program synthesis has mostly addressed generative modeling, i.e., the synthesis of programs that can generate the training data (Tian et al., 2018; Ellis et al., 2018; Feinman & Lake, 2020). This task is analogous to learning a symbolic decoder rather than a symbolic encoder. Studying how to incorporate such methods into our framework can be an interesting future direction.

Representation learning for behavior analysis. Representation learning has been applied to a variety of downstream tasks for behavior analysis, such as discovering behavior motifs (Berman et al., 2014; Singh et al., 2021), identifying internal states (Calhoun et al., 2019), and improving sample-efficiency (Sun et al., 2021b). Studies in this area have used methods such as VAE (Kingma & Welling, 2014), AR-HMM (Wiltschko et al., 2015), forecasting or predicting future behaviors (Liang et al., 2020; Gao et al., 2020), and Umap (McInnes et al., 2018) to better understand the latent structure of behavior. Similar to a few other representation learning methods (Luxem et al., 2020; Sun et al., 2021b), we also use an encoder-decoder setup on trajectory data. However, our work learns a neurosymbolic encoder whereas existing works in this area have fully neural encoders. Our work can aid behavior analysis by learning more interpretable latent representations and can be applied to downstream tasks, such as behavior classification.

6 Conclusion

We present a novel approach for unsupervised learning of neurosymbolic encoders. Our approach integrates the VAE framework with program synthesis and results in a learned representation with both neural and symbolic components. Experiments on trajectory data from behavior analysis demonstrate that our programmatic descriptions of the latent space result in more meaningful clusters relative to human-defined behaviors, compared to purely neural encoders. Additionally, we show the practicality of our approach by applying our learned programs to achieve comparable performance to expert-constructed tasks in a self-supervised learning approach for behavior classification.

Based on our work, there are many future directions to explore for neurosymbolic encoders. One direction is to extend this work to other domains such as image and text data, in order to learn interpretable symbolic latent representations. Neurosymbolic encoders on images would require a DSL for pixel data as well as architecture changes, such as using convolutional VAEs. Another direction is to improve upon our greedy approach in Algorithm 2 for finding the optimal set of symbolic programs, e.g. by performing local coordinate ascent in program space, similar to algorithms for large-scale neighborhood search (Ahuja et al., 2002). Lastly, while practically-oriented extensions of VAEs such as our own have yielded great practical benefit, they often lead to sub-optimal results from a pure likelihood (or ELBO) perspective. One final direction is to rigorously formulate a learning objective from the ground up that formally encapsulates practically-oriented extensions of VAEs.

References

Ravindra K Ahuja, Özlem Ergun, James B Orlin, and Abraham P Punnen. A survey of very large-scale neighborhood search techniques. *Discrete Applied Mathematics*, 123(1-3):75–102, 2002.

David J Anderson and Pietro Perona. Toward a science of computational ethology. *Neuron*, 84(1):18–31, 2014.

Osbert Bastani, Yewen Pu, and Armando Solar-Lezama. Verifiable reinforcement learning via policy extraction. In *Advances in Neural Information Processing Systems*, 2018.

Gordon J Berman, Daniel M Choi, William Bialek, and Joshua W Shaevitz. Mapping the stereotyped behaviour of freely moving fruit flies. *Journal of The Royal Society Interface*, 11(99):20140672, 2014.

Samuel R. Bowman, Luke Vilnis, Oriol Vinyals, Andrew M. Dai, Rafal Józefowicz, and Samy Bengio. Generating sentences from a continuous space. *arXiv preprint arXiv:1511.06349*, 2015.

Christopher P. Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in β-vae. In *Neural Information Processing Systems Disentanglement Workshop*, 2017.

Xavier P Burgos-Artizzu, Piotr Dollár, Dayu Lin, David J Anderson, and Pietro Perona. Social behavior recognition in continuous video. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1322–1329. IEEE, 2012.

Adam J Calhoun, Jonathan W Pillow, and Mala Murthy. Unsupervised identification of the internal states that shape natural behavior. *Nature neuroscience*, 22(12):2040–2049, 2019.

Swarat Chaudhuri, Kevin Ellis, Oleksandr Polozov, Rishabh Singh, Armando Solar-Lezama, Yisong Yue, et al. Neurosymbolic programming. *Foundations and Trends® in Programming Languages*, 7(3):158–243, 2021.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. *arXiv preprint arXiv:1606.03657*, 2016a.

Xi Chen, Diederik P Kingma, Tim Salimans, Yan Duan, Prafulla Dhariwal, John Schulman, Ilya Sutskever, and Pieter Abbeel. Variational lossy autoencoder. *arXiv preprint arXiv:1611.02731*, 2016b.

Xinyun Chen, Chang Liu, and Dawn Song. Towards synthesizing complex programs from input-output examples. In *International Conference on Learning Representations*, 2018.

John Co-Reyes, YuXuan Liu, Abhishek Gupta, Benjamin Eysenbach, Pieter Abbeel, and Sergey Levine. Self-consistent trajectory autoencoder: Hierarchical reinforcement learning with trajectory embeddings. In *International Conference on Machine Learning*, 2018.

Antonia Creswell, Yumnah Mohamied, Biswa Sengupta, and Anil A Bharath. Adversarial information factorization. *arXiv preprint arXiv:1711.05175*, 2017.

Guofeng Cui and He Zhu. Differentiable synthesis of program architectures. *Advances in Neural Information Processing Systems*, 34:11123–11135, 2021.

Zhiwei Deng, Rajitha Navarathna, Peter Carr, Stephan Mandt, Yisong Yue, Iain Matthews, and Greg Mori. Factorized variational autoencoders for modeling audience reactions to movies. In *IEEE conference on computer vision and pattern recognition*, 2017.

Zheng Ding, Yifan Xu, Weijian Xu, Gaurav Parmar, Yang Yang, Max Welling, and Zhuowen Tu. Guided variational autoencoder for disentanglement learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7920–7929, 2020.

Emilien Dupont. Learning disentangled joint continuous and discrete representations. In *Neural Information Processing Systems*, 2018.

Kevin Ellis, Daniel Ritchie, Armando Solar-Lezama, and Joshua B Tenenbaum. Learning to infer graphics programs from hand-drawn images. In *Advances in Neural Information Processing Systems*, 2018.

Eyrun Eyjolfsdottir, Kristin Branson, Yisong Yue, and Pietro Perona. Learning recurrent representations for hierarchical behavior modeling. *arXiv preprint arXiv:1611.00094*, 2016.

Reuben Feinman and Brenden M Lake. Learning task-general representations with generative neuro-symbolic modeling. In *International Conference on Learning Representations*, 2020.

Jiyang Gao, Chen Sun, Hang Zhao, Yi Shen, Dragomir Anguelov, Congcong Li, and Cordelia Schmid. Vectornet: Encoding hd maps and agent dynamics from vectorized representation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11525–11533, 2020.

Sumit Gulwani. Automating string processing in spreadsheets using input-output examples. *ACM Sigplan Notices*, 46(1):317–330, 2011.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2016.

Alexander I Hsu and Eric A Yttri. B-soid: An open source unsupervised algorithm for discovery of spontaneous behaviors. *bioRxiv*, pp. 770271, 2020.

Zhiting Hu, Zichao Yang, Xiaodan Liang, Ruslan Salakhutdinov, and Eric P Xing. Toward controlled generation of text. In *International Conference on Machine Learning*, 2017.

Jeevana Priya Inala, Osbert Bastani, Zenna Tavares, and Armando Solar-Lezama. Synthesizing programmatic policies that inductively generalize. In *International Conference on Learning Representations*, 2020.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2017.

Matthew J Johnson, David Duvenaud, Alexander B Wiltschko, Sandeep R Datta, and Ryan P Adams. Composing graphical models with neural networks for structured representations and fast inference. In *Advances in Neural Information Processing Systems*, 2016.

Lukasz Kaiser, Samy Bengio, Aurko Roy, Ashish Vaswani, Niki Parmar, Jakob Uszkoreit, and Noam Shazeer. Fast decoding in sequence models using discrete latent variables. In *International Conference on Machine Learning*, 2018.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014.

Diederik P Kingma, Danilo J Rezende, Shakir Mohamed, and Max Welling. Semi-supervised learning with deep generative models. *arXiv preprint arXiv:1406.5298*, 2014.

Ming Liang, Bin Yang, Rui Hu, Yun Chen, Renjie Liao, Song Feng, and Raquel Urtasun. Learning lane graph representations for motion forecasting. In *European Conference on Computer Vision*, pp. 541–556. Springer, 2020.

Stuart Lloyd. Least squares quantization in pcm. *IEEE transactions on information theory*, 28(2):129–137, 1982.

Kevin Luxem, Falko Fuhrmann, Johannes Kürsch, Stefan Remy, and Pavol Bauer. Identifying behavioral structure from deep variational embeddings of animal motion. *bioRxiv*, 2020.

Jianxin Ma, Chang Zhou, Hongxia Yang, Peng Cui, Xin Wang, and Wenwu Zhu. Disentangled self-supervision in sequential recommenders. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 483–491, 2020.

Qianli Ma, Jiawei Zheng, Sen Li, and Gary W Cottrell. Learning representations for time series clustering. *Advances in neural information processing systems*, 32:3781–3791, 2019.

Leland McInnes, John Healy, and James Melville. Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

Andriy Mnih and Karol Gregor. Neural variational inference and learning in belief networks. In *International Conference on Machine Learning*, 2014.

Aaron van den Oord, Oriol Vinyals, and Koray Kavukcuoglu. Neural discrete representation learning. In *Advances in Neural Information Processing Systems*, 2017.

William M Rand. Objective criteria for the evaluation of clustering methods. *Journal of the American Statistical association*, 66(336):846–850, 1971.

Jason Tyler Rolfe. Discrete variational autoencoders. *arXiv preprint arXiv:1609.02200*, 2016.

Hinrich Schütze, Christopher D Manning, and Prabhakar Raghavan. *Introduction to information retrieval*, volume 39. Cambridge University Press Cambridge, 2008.

Cristina Segalin, Jalani Williams, Tomomi Karigo, May Hui, Moriel Zelikowsky, Jennifer J Sun, Pietro Perona, David J Anderson, and Ann Kennedy. The mouse action recognition system (mars): a software pipeline for automated analysis of social behaviors in mice. *bioRxiv*, 2020.

Ameesh Shah, Eric Zhan, Jennifer J Sun, Abhinav Verma, Yisong Yue, and Swarat Chaudhuri. Learning differentiable programs with admissible neural heuristics. In *Neural Information Processing Systems*, 2020.

Satpreet H Singh, Steven M Peterson, Rajesh PN Rao, and Bingni W Brunton. Mining naturalistic human behaviors in long-term video and neural recordings. *Journal of Neuroscience Methods*, 2021.

Jennifer J Sun, Tomomi Karigo, Dipam Chakraborty, Sharada P Mohanty, David J Anderson, Pietro Perona, Yisong Yue, and Ann Kennedy. The multi-agent behavior dataset: Mouse dyadic social interactions. *arXiv preprint arXiv:2104.02710*, 2021a.

Jennifer J Sun, Ann Kennedy, Eric Zhan, David J Anderson, Yisong Yue, and Pietro Perona. Task programming: Learning data efficient behavior representations. In *Conference on Computer Vision and Pattern Recognition*, 2021b.

Yonglong Tian, Andrew Luo, Xingyuan Sun, Kevin Ellis, William T Freeman, Joshua B Tenenbaum, and Jiajun Wu. Learning to infer and execute 3d shape programs. In *International Conference on Learning Representations*, 2018.

Dweep Trivedi, Jesse Zhang, Shao-Hua Sun, and Joseph J Lim. Learning to synthesize programs as interpretable and generalizable policies. *Advances in neural information processing systems*, 34:25146–25163, 2021.

Arash Vahdat and Jan Kautz. Nvae: A deep hierarchical variational autoencoder. In *Advances in Neural Information Processing Systems*, 2020.

Lazar Valkov, Dipak Chaudhari, Akash Srivastava, Charles Sutton, and Swarat Chaudhuri. Houdini: Lifelong learning as program synthesis. In *Advances in neural information processing systems*, 2018.

Abhinav Verma, Vijayaraghavan Murali, Rishabh Singh, Pushmeet Kohli, and Swarat Chaudhuri. Programmatically interpretable reinforcement learning. In *International Conference on Machine Learning*, 2018.

Abhinav Verma, Hoang M Le, Yisong Yue, and Swarat Chaudhuri. Imitation-projected programmatic reinforcement learning. In *Advances in Neural Information Processing Systems*, 2019.

Xinyu Wang, Isil Dillig, and Rishabh Singh. Program synthesis using abstraction refinement. *Proceedings of the ACM on Programming Languages*, 2017.

Alexander B Wiltschko, Matthew J Johnson, Giuliano Iurilli, Ralph E Peterson, Jesse M Katon, Stan L Pashkovski, Victoria E Abraira, Ryan P Adams, and Sandeep Robert Datta. Mapping sub-second structure in mouse behavior. *Neuron*, 88(6):1121–1135, 2015.

Li Yingzhen and Stephan Mandt. Disentangled sequential autoencoder. In *International Conference on Machine Learning*, 2018.

Eric Zhan, Albert Tseng, Yisong Yue, Adith Swaminathan, and Matthew Hausknecht. Learning calibratable policies using programmatic style-consistency. In *International Conference on Machine Learning*, 2020.

Hui Zhang, Tu Bao Ho, Yang Zhang, and M-S Lin. Unsupervised feature extraction for time series clustering using orthogonal wavelet transform. *Informatica*, 30(3), 2006.

Yu Zhang, Peter Tiňo, Aleš Leonardis, and Ke Tang. A survey on neural network interpretability. *arXiv preprint arXiv:2012.14261*, 2020.

Shengjia Zhao, Jiaming Song, and Stefano Ermon. Learning hierarchical features from generative models. In *International Conference on Machine Learning*, 2017.