Deconfounding Transformers via Weight Masking: Addressing Gender Confounding Shift in Dementia Detection

Abstract

Deep neural language models (NLMs) are often described as "black-box" systems due to their opaque inference procedures. This presents a challenge in understanding the information they capture, and how it is encoded within transformer networks, raising the possibility that encoded biases may remain undetected. This work addresses confounding bias learned during model fine-tuning, when a pretrained NLM is adapted to downstream domains and tasks. We extend the previous deconfounding methods by proposing the Extended Confounding Filter and the Dual Filter. These methods aim to isolate and augment weights within the transformer network that are associated with confounding variables through distinct training phases. We evaluate these methods on two dementia datasets that contain language of patients with cognitive impairment and healthy controls in the first-person narratives. We aim to demonstrate the applicability of the proposed methods in the domain of dementia detection as a means to correct for gender-related disparities in class distribution at training time. Our results show that transformer models can overfit to the subpopulation distribution in the training data. By disrupting the weights associated with known confounders, we show that fairer models can be achieved with reduced prediction bias towards specific subgroups. Moreover, our findings highlight resilience of the model against weights deletion and show a trade-off between model performance in dementia detection and the reduction of disparities across gender groups.

1 Introduction

Transformer-based models (Vaswani et al., 2017) have achieved significant success across various language and vision tasks, leading to numerous applications. In particular, bidirectional encoder models based on the self-attention mechanism, such as BERT (Devlin et al., 2019) and its variants (Liu et al., 2019; Sanh et al., 2020; Lee et al., 2020; Qian et al., 2022), have demonstrated impressive performance gains on NLP benchmarks and domain-specific tasks due to their ability to learn rich dense representations from text. As the popularity of these models increases, it is important to ensure that their outputs are not biased towards (or against) certain groups at the point of deployment. However, in practice, most transformer models are optimized for and evaluated on a task of interest, without considering biases inherent in the data that may be embedded into the model (Baldini et al., 2022; Bolukbasi et al., 2016; Hutchinson et al., 2020; Webster et al., 2021; de Vassimon Manela et al., 2021). If left unaddressed, such biases can propagate and cause the model to learn spurious correlations in downstream tasks. Efforts have been made to mitigate these data-derived biases. One approach involves task-agnostic methods that enforce the learning of fair representations (Kaneko and Bollegala, 2021; Cheng et al., 2021; Guo et al., 2022), while another focuses on reducing discrimination in specific tasks using annotated data (Shen et al., 2021; Ravfogel et al., 2022; Gira et al., 2022; Zhu et al., 2023).

Confounding bias is a particular type of bias that arises when the relationship between the anticipated signal and the outcome is distorted by the presence of extraneous factors, known as confounders. This results in discrepancies in model performance across different confounder strata. In the context of text classification, a confounder can be considered as an extraneous variable that influences both the language provided to a classifier, and the distribution of the class labels of interest (Landeiro and Culotta, 2018). In this study, we focus on task-specific methods to mitigate the effects of confounding bias. Specifically, we investigate confounding shift in binary classification, where positive examples are unevenly distributed across different subgroups, and these subgroup-specific

class distributions differ at the point of evaluation or deployment. This can lead to errors when a model uses language indicating a subgroup, rather than the outcome of interest, as a basis for prediction. Inspired by the Confounding Filter (Wang et al., 2019), we propose two novel techniques: the Extended Confounding Filter (ECF) and Dual Filter (DF), and evaluate them on two dementia datasets that have been widely used in research (Li et al., 2022; Farzana and Parde, 2023) to study the effects of Alzheimer's disease dementia on language. Our main contributions are as follows:

- We identified under-explored gender confounding bias in health-related speech dataset.

- We extended the Confounding Filter method to the Transformers architecture and demonstrated improvements in task performance.

- We introduced the Dual Filter as a simple yet effective weight masking algorithm that identifies and ablates parameters associated with the confounding bias in the entire model's network (vs. individual layers).

2 Related Work

Our work focuses on bias mitigation through weight masking, which requires isolating and erasing the influence of model weights that represent information about a confounding variable. As such, our work relates to prior efforts to access information encoded within transformer networks. One line of research exhibits weights isolation through disentangled learning (Zhang et al., 2021; Colombo et al., 2021). These methods require special loss functions to restrict information overlap between targets and sensitive attributes. Adapter sub-networks gate and control access to information from protected features (Hauzenberger et al., 2023; Masoudian et al., 2024). Without defining additional training objectives, Liu et al. (2024) propose a gradient integration method to pinpoint neurons that cause gaps in output logit distributions among demographic groups. Lee et al. (2019); Sun et al. (2024) developed different weight importance ranking algorithms that can be used to locate redundant weights to prune network connectivity. These ranking algorithms track either neuron activation or loss output by masking certain weights within a layer, and assign an importance score to each entry given a calibrated dataset. While most of these methods focus on pretrained models (some

exceptions provide the baseline models for our experiments), our work targets bias learned during finetuning toward a specific task. Compared to prior efforts, the method we employ for identifying the weights can be applied within a naive training procedure, requiring no additional training components or objective formulation, yet still produces significant bias mitigation across various distribution shifts in the data.

3 Methods

3.1 Confounding Filter

Deep learning models often recognize false signals from confounding factors, leading to sub-optimal performance in many real-world cases (Szegedy et al., 2013; Nguyen et al., 2015; Wang et al., 2017b,a). To address this issue, the Confounding Filter (Wang et al., 2019) was proposed to address confounding biases in models trained on electroencephalogram and medical imaging data. The Confounding Filter method is straightforward and model-agnostic, designed to mitigate the impact of confounding factors. In this approach, a deep learning model is denoted as having two components: $g(\cdot; \theta)$, a representation learning network, and $f(\cdot; \phi)$, a classification network. The algorithm first optimizes the entire network by solving the following objective:

$$\hat{\theta}, \hat{\phi} = \arg\min_{\theta, \phi} \mathcal{L}(y, f(g(X); \theta); \phi)$$

where $\mathcal{L}$ denotes the loss function to be minimized.

In the second phase, assuming we have access to the confounder label m in the dataset, the algorithm localizes weights that are reactive to the confounding variable. This is achieved through tuning $f(\cdot; \phi)$ towards m while keeping $g(\cdot; \theta)$ fixed. During the second phase, updates in $\hat{\phi}$ are tracked and normalized after each batch. The sum of normalized updates is denoted as $\pi = \frac{1}{b}\sum_{i=1}^{b}|\Delta\phi_i|$ where b is the number of total batches in the second phase of training. The importance of each element in π is determined by their magnitude. A threshold function is then employed to get the mask:

$$M_i = \begin{cases} 0 & \text{if } \pi_i > \tau \\ 1 & \text{otherwise} \end{cases}$$

Here, τ is the k^{th} percentile in π, where k is a hyperparameter. The element-wise product $\hat{\phi}' = \hat{\phi} \otimes M$ results in the confounder-mitigated network $f(g(X); \hat{\theta}); \hat{\phi}')$.

Figure 1: **(a)** Illustration of the Extended Confounding Filter (**ECF**) Probing framework for weights identification. **(b)** Illustration of the Dual Filter (**DF**) procedure to find weights to mask.

3.2 Extended Confounding Filter

While the original Confounding Filter algorithm has shown improvements over the baseline in some neural network architectures (Wang et al., 2019), its adaptation to transformer networks remains unexplored. Transformer-based language models (LMs) learn to generate distributional semantic representations (Vaswani et al., 2017) through the attention mechanism and positional encoding. By fine-tuning a pretrained LM, semantic information pertinent to a task of interest is dynamically stored across the transformer network layers.

Our hypothesis is that fixing $g(\cdot; \theta)$ when training for the confounder variable may not effectively capture the most confounder-associated weights within the transformer network. To test this hypothesis, we sequentially unfroze each layer in the transformer network, starting from the classification head down to the embedding layer and observed its impact on the prediction. This is different from the original Confounder Filter method, where only the classification head is trainable in the encoder model. We refer it as Extended Confounding Filter (ECF) in the paper.

The illustration of how ECF works is shown in Figure 2. Matrices $W_Q, W_K, W_V, W_O, W_1, W_2$ are tracked in a single transformer block, while W_{emb} and W_{cls} represent the token embedding matrix and classification weight matrix in a sequence classification model, respectively. Similarly to the Confounding Filter, we start by training a classification model towards the primary label Y_p (Phase 1) and then continue training the model towards classifying the confounder label Y_c with layers sequentially unfreeze (Phase 2).

By sequentially unfreezing different numbers of layers, we allow varying amounts of the model's parameter spaces to react to the information introduced during Phase 2. (Figure. 1a) This sequential

Figure 2: Tracked weights in the transformer network

probing scheme follows the idea from Confounding Filter but provides more flexibility as you can partition the classification network $f(x)$ and representation learning network $g(x)$ at different points. The change in parameter $\Delta \phi_i$ is normalized within the matrix and recorded after each training batch. Following the Confounding Filter methodology, we restrict $\Delta \phi_i$ to each W in this probing procedure, and the threshold τ is calculated for each individual weight matrix. The probing step size is by layer. Masking matrices, derived from the threshold function, are applied to the tracked weight matrix from Phase 1 fine-tuning. We later evaluate the effectiveness of this method in mitigating confounding bias against the probing depth on a real world dataset.

3.3 Dual Filter

Next, we further lift the restriction on Phase 2 training from the ECF method that the masking be performed locally, ignoring the dynamics and interaction the LM might have during finetuning. We propose Dual Filter, a method that tracks the weight change from two separate models starting from the same checkpoint, one for the primary outcome and the other for the confounder. After obtaining change matrices π from both models, we utilize set operations to isolate weights that are most reactive to the confounder label during finetuning. Specifically, we choose the top $k\%$ most changed weights from the primary model f and the

confounder model g, and take the intersection or the difference from these two weight sets to generate the mask matrices (Figure 1b). One could apply either the intersection set mask, the difference set mask, or the joint set of the two masks (which is equivalent to the top $k\%$ most changed weights from the confounder model), depending on the dataset or tasks. We formally describe the proposed algorithm in Algorithm 1.

Algorithm 1 Dual Filter for weights masking

Input: pretrained LM: $f_0(x)$, $g_0(x)$; dataset: $\mathcal{D}(x, y_p, y_c)$; threshold: k
Output: Confounder-adjusted model $f(x; \theta')$
  1: Train $f_0(x; \theta) \mapsto y_p$, obtain weights change Δ_p and finetuned model $f(x; \hat{\theta})$.
  2: Train $g_0(x; \phi) \mapsto y_c$, obtain weights change Δ_c and finetuned model $g(x; \hat{\phi})$.
  3:
$$\Delta_{p,k} = \underset{p \subseteq \Delta_p, |p|=k}{\arg\max} \sum_{p_i \in \Delta_p} p_i$$
$$\Delta_{c,k} = \underset{c \subseteq \Delta_c, |c|=k}{\arg\max} \sum_{c_i \in \Delta_c} c_i$$
  4: $M_I \leftarrow \Delta_{p,k} \cap \Delta_{c,k}$, $M_D \leftarrow \Delta_{c,k} \setminus \Delta_{p,k}$
  5: Pick mask $M \in \{M_I, M_D, M_I \cup M_D\}$
  6:
$$\theta' \leftarrow \hat{\theta}_i = 0 \quad \forall i \in M$$

3.4 Other Baselines

We include two baseline adapter models, CON-GATER (Masoudian et al., 2024) and MODDIFFY (Hauzenberger et al., 2023) using their publicly available code[1,2], both of which address biases learned during fine-tuning. These methods append additional bias-mitigate modules into a network and learn their weights through a joint loss function. We run these two methods using their default configurations with a range of hyperparameters to investigate their fairness-performance trade-offs. See hyperparameters experimented in Table A2.

4 Evaluations

Confounding Shift One fundamental assumption in machine learning is the test dataset and training dataset are from the same distribution. However this assumption is often violated in real world applications resulting in distribution shifts. One specific form of distribution shift is sub-population shift

(Cao et al., 2019; Cai et al., 2021). A model optimized on a distribution shifted training set tends to learn spurious correlations with the majority class and may lead to poor performance on data with a different from the training data class distribution (Yang et al., 2023).

While the sub-population shifts are determined by the product of group attributes and the label, and the group attributes are not independent of the label, it is a special type of dataset shift referred to as *Confounding Shift* (Landeiro and Culotta, 2018). Formally, confounding shift exists when two conditions are met: (i) a confounding variable Y_c exists that impacts both X and Y_p through distributions $P(X|Y_c)$ and $P(Y_p|Y_c)$ through the backdoor path in a causal graph (Pearl, 2009); (ii) a subpopulation distribution $P_{train}(Y_p|Y_c)$ is different from $P_{test}(Y_p|Y_c)$ (Landeiro and Culotta, 2018).

To quantitatively assess the degree of confounding shift, we use a framework proposed by Ding et al. (2024) in our experiments. This allows us to perturb the target variable and confounding variable distributions in both training and test splits to different degrees through sampling from the original dataset. Under this framework, we consider a dataset with a binary target and binary confounder, the joint distribution $P(Y_p, Y_c)$ governed by the following quantity: $P(Y_c = 1), P(Y_p = 1), P(Y_p = 1|Y_c = 1), P(Y_p = 1|Y_c = 0)$. Next Ding et al. (2024) introduced a positive auxiliary variable $\alpha = \frac{P(Y_p=1|Y_c=1)}{P(Y_p=1|Y_c=0)}$, which serves as a knob for controlling the degree of subpopulation shift. By setting different α values, we control the source of the positive examples. If we hold $P(Y_c = 1)$ and $P(Y_p = 1)$ constant, we can vary α_{train} and α_{test} to create a mixture of datasets with various degrees of shift for model evaluation. Details are described in Section 5.2.

Fairness The concept of fairness in machine learning addresses the goal of ensuring that models operate without bias and equitably across different demographic groups. A widely accepted notion of group fairness, which focuses on equity at the population level, is statistical parity (Dwork et al., 2011). In problems with a binary outcome Y and a binary group variable G, statistical parity is defined as the absolute difference or ratio between $P(\hat{y} = 1|g = 1)$ and $P(\hat{y} = 1|g = 0)$. Smaller values of statistical parity indicate greater equality in the model's outputs across the two groups. In addition to statistical parity, other fairness met-

---

[1]https://github.com/ShawMask/DebiasingConGater
[2]https://github.com/CPJKU/ModularizedDebiasing

rics consider ground truth labels and compare the true positive rates between groups (Romano et al., 2020; Hardt et al., 2016). These metrics assess the model's ability to make accurate predictions without discriminating against any group.

In our context, the test set attributes vary due to different data distributions associated with parameter α, rendering comparisons of statistical parity across different α values infeasible. Therefore, we evaluate $P(\hat{y} = 1|G, y = 0)$, which describes the predicted probability for dementia among healthy participants, and is equivalent to the false positive rate (FPR). We calculate the absolute difference of FPR between the subgroups. This metric helps us assess fairness by examining the model's behavior across different α values.

5 Dementia Detection Case Study

In recent years, transformers have demonstrated promising performance in dementia detection using patient spoken data (Hernandez-Dominguez et al., 2018; Cohen and Pakhomov, 2020; Luz et al., 2020; Guo et al., 2021; Li et al., 2022). However, these models are susceptible to bias due to the small size of publicly available datasets utilized in most studies. Within this context, confounding by gender is an unexplored potential source of bias that could lead to erroneous predictions if the confounding effects are not addressed. The underlying hypothesis is that the language used by male and female participants performing the same task may vary, and the model learns these differences to make dementia predictions, regardless of the participants' true cognitive status.

5.1 Dataset

DementiaBank (DB) The benchmark dataset used for our experiments is the Pittsburgh Corpus from DementiaBank (Becker et al., 1994; MacWhinney, 2007) This corpus is a widely used resource in the fields of computational linguistics and dementia studies. It provides detailed speech and language data from elderly participants with dementia as well as healthy controls. Notably, the Pittsburgh Corpus includes responses to the *Cookie Theft* picture description task from the Boston Diagnostic Aphasia Examination (Goodglass and Kaplan, 1983). The dataset comprises 548 examples collected from longitudinal records of 290 participants. To ensure the transcripts accurately reflect the diagnosis label, we selected the last transcript

for each patient as input for our model.

Carolinas Conversation Collection (CCC) Different from DB, CCC (Pope and Davis, 2011) curates corpus from English conversations rather than neuropsychological tasks. It contains 646 recorded interviews of 48 elderly cognitively normal individuals with non-dementia related conditions, and 284 individuals with dementia. Each individual could participate in multiple interviews with different interviewers. The target focus of the conversational interviews is on eliciting autobiographical narrative pertaining to health and wellness. This data has been used frequently in NLP research with a focus on psycholinguistics (Nasreen et al., 2021; Li et al., 2022; Farzana and Parde, 2023). In this study we use data from 70 interviewees with available gender information which encompasses 395 transcripts in total.

5.2 Experiments

We start by examining whether a text classification model will recognize gender confounding bias from such picture description data. We fine-tuned a BERT-base model (Devlin et al., 2019) on the full dataset and evaluated the model's performance on the task of recognizing each gender [3]. We ran the experiments using 5-fold cross validation with 3 repeats on both the original dataset, and a perfectly balanced dataset created by down-sampling the more prevalent category. Mann-Whitney-Wilcoxon test were performed between male and female and the result is shown in Table 1 - performance discrepancies were observed among male and female examples across multiple runs. This result shows that there exists confounding by gender in the dementia detection task which is independent of the gender distribution in the dataset. It provides insights that the gender of the speaker influences the language they use to complete the Cookie Theft picture description task or the phone interviews, and confound the dementia signals during model fine-tuning. Hereby, we further investigate this confounding by gender effects in dementia detection and evaluate our proposed deconfounding methods.

Dataset Perturbation As described in Section 4 , we manipulated the conditional distribution of dementia by gender in our dataset through random sampling, creating a series of datasets with varying

---

[3]Both dataset provides labels only for two genders: male and female

Figure 3: ECF filtering with 15% masking rate across different confounding shifts from two dataset.

dataset	setup	abs mean diff	p-value
DB	Original	0.055	< .001
	Balanced	0.068	< .001
CCC	Original	0.152	0.002
	Balanced	0.102	0.007

Table 1: Two sided Mann-Whitney-Wilcoxon test results of male and female dementia prediction performance (AUPRC) across different setups.

levels of confounding shift. In our experiments, dementia cases and female participants are coded as 1, respectively. We fixed $P(\text{gender} = 1) = 0.5$ and $P(\text{dementia} = 1) = 0.5$ in both the training and test sets to ensure fair comparisons across different configurations. This way, the dataset is balanced with respect to both dementia and gender. Then we adjusted the value of $\alpha = \frac{P(\text{dementia}|\text{female})}{P(\text{dementia}|\text{male})}$ to create an imbalance in the source of dementia cases (sub-population shift). If $\alpha > 1$, more dementia cases are drawn from females, while $\alpha < 1$ indicates the opposite. The further α is from 1, the more severe the imbalance. To evaluate the model's robustness to confounding shifts, the model is trained on one α_{train} value and tested on its reciprocal value $\alpha_{\text{test}} = \frac{1}{\alpha_{\text{train}}}$, simulating an extreme shift in the test set compared to the distribution the model was exposed to during training. The selection of $\frac{1}{\alpha_{\text{train}}}$ is entirely arbitrary and is intended solely to calibrate the magnitude of the shift and establish the testbed for evaluation. Models are trained for 20 epochs on 480 training examples, validated on 120 examples and evaluated on 150 examples for each configuration. Among them, training set and validation set are sampled from α while test set is sourced from $\frac{1}{\alpha}$. The best checkpoint is selected based on AUPRC achieved on the validation dataset with early stopping to prevent overfitting.

Extended Confounding Filter On creating a series of datasets with different α_{train} values, we probed each layer in the model in response to the shift. The encoder model we used for dementia de-

tection is BERT-base, with 12 encoder layers and 12 attention heads in each layer. Once we obtain the dementia finetuned model $f(x)$ in the first Phase, we take a snapshot of the parameters and only make some parts of it trainable towards the gender label in the second Phase. The trainable layer starts from $\{cls\}$, and 1 layer is added to the trainable set each time sequentially. Eventually the trainable set becomes $\{cls, layer12, layer11, ..., layer1, emb\}$ and spans the whole network. Then for each trainable set, f_d is trained towards gender prediction. We ranked weights that changed in each layer and picked top 15% of the weights that changed the most in each layer to mask (Figure 1a). Then we evaluated the masked models.

Dual Filter In the Dual Filter approach, we track the global weights change throughout the model's architecture. The classification head is exempt from tracking as it is training towards two different tasks and the weights in the classification head are assumed to have the most significant change compared to the rest of network. We first obtain two lists of weights change matrices from $f(x)$ and $g(x)$, using the same approach as Extended CF. Then we rank and select the top $k\%$ weights by their locations in the network. A sequence of k values are tested, ranging from 0 to 60 and step size of 1. Then three kinds of set $(M_I, M_D, M_I \cap M_D)$ are calculated and applied to $f(x)$ to create the masked model. Note when training toward gender in both Extended CF and Dual Filter, we select only non-dementia cases to let the model learn from texts that are representative of the gender differences. Consequently, only healthy cases are used in the evaluation as well.

6 Results

6.1 Extended Confounding Filter

Figure 3 demonstrates the Extended Confounding Filter results, the red dotted line shows the per-

formance of the intact model and models whose weights are eliminated cumulatively layer-by-layer from left to right until the embedding layer is reached (the right most bar). The orange bar represents the idea of the original Confounding Filter, where only the classification head is trained in the second phase and then masked. From results of both dataset we observe a "ladder" effect by confounding shift - a model trained and tested on the same distribution ($\alpha = 1$) reaches the highest performance among all the configurations, while the degree of confounding shift correlates with the model's performance (i.e. the model performance drops as α_{train} shifts away from 1). Another observation is that the model demonstrates some resilience in its ability to detect dementia to removing gender associated weights from upper layers in the network. No significant performance drops are observed until weights are removed from lower layers. In some cases, dropping gender-associated weights from certain layers help boost AUPRC on average comparing to the intact model and their patterns need to be further studied.

6.2 Dual Filter

Figure 4: AUPRC comparisons on ECF and DF for different α_{train} configurations. The x-axis represents the % of ablated weights through the whole network.

In Figure 4, we visualize the dementia prediction performance change on the DB dataset as we apply three different types of mask to the original model and gradually increase the masking ratio. The results from ECF with 15% layer-specific masking ratio are added for comparison. The plot shows the relation between how many weight entries are ablated within the whole network against dementia detection performance in terms of AUPRC. The rows indicate three types of masks that are generated by Dual Filter and the columns indicate the specific α_{train} configurations that control the dis-

tribution shift.

Next, we show the absolute False Positive Rate difference (i.e. $|P(\hat{y} = 1|g = 1, y = 0) - P(\hat{y} = 1|g = 0, y = 0)|$) calculated under both ECF and DF methods. The Figure 5 shows the FPR measurements change as the ablation ratios increase for all three types of masks. The mask type is indicated by row while the columns represents different α_{train}. Similar trends are also present in CCC dataset. (Section A.4)

Figure 5: Absolute False Positive Rate (FPR) difference on ECF and DF for different α_{train} configurations

6.3 Comparisons with other methods

We train on data with the configuration of $\alpha_{train} = 3$, where a confounding shift is present. That means the dementia cases for training are sourced three times more from the female cohort than the male cohort. We then test on samples from the configuration of $\alpha_{test} = \frac{1}{3}$. We evaluate the results on ECF, DF and other baselines using the AUPRC-FPR curve (Figure 6), in which the upper-left points represent an ideal classifier, with both high accuracy and fairness. From our experiments, we observe

Figure 6: AUPRC-FPR curves among different methods for DB (left) and CCC (right)

that on the CCC dataset, ECF achieves the best performance in terms of the trade-off compared to DF variants. In contrast, on the DB dataset, the performance of DF(all) and DF(difference) is consistent with that of ECF. In both datasets, our proposed methods outperform the two adapter-based baseline methods, as well as the naive Confounding Fil-

ters. This demonstrates that the proposed masking procedure effectively handles confounding shifts. Among the DF variants, the intersection masking procedure consistently outperforms the other masking techniques across both datasets. Compared to the naive Confounding Filter, the proposed methods exhibit a better trade-off curve and in general achieve significantly higher AUPRC performance at the same level of FPR disparity. Additionally, the fact that the weight masking approach produces a more fine-grained trade-off trajectory compared to loss-optimization approaches, which often converge to a few optimal points given the dataset. This flexibility enhances the method's applicability across a wider range of use cases in practice.

7 Discussion

ECF probes each layer and the associated masked weights in a cumulative manner. Figure 3 shows the results of simply applying Confounding Filter (orange patch) on the classification layer of the transformer is insufficient to address the confounding bias. Propagating masks layer-by-layer helps improve or retain the dementia classification performance from Confounding Filter until several layers deep into the network. We observe the resilience of weights ablation in the BERT model on dementia prediction performance which is consistent with similar resilience on capturing linguistic features reported in other work (Li et al., 2024). The token embedding appears to be a critical factor in dementia detection. We experimentally discovered that deleting even a small proportion of the embedding weights causes a drastic change in the model's dementia detection ability. Further work is needed to explore its exact role.

The grid of Figure 4 provides an overview of the performance change in dementia against the ablation ratios in the whole model, for both ECF and DF. The results show that the different behaviors from the three types of masks. For $M_I \cup M_D$ filter, the model illustrates resistance against the weight deletion more consistently. Comparing to ECF, masking weights inside $M_I \cup M_D$ shows less resilience at the start but the performance curves cross over right after the point where 12% weights are removed and then becomes more robust to weight deletion as compared to ECF. As for M_D, some resilience can be observed at the start of the masking but the performance degradation becomes more extensive after a certain point. However, the impact of M_I mask turned out to be different. Ablating weights in M_I first results in a sharp decrease in performance and then gradually stabilizes when more weights get deleted. Those results suggest the entanglement of weights responsive for dementia detection and gender detection from two change matrices, especially those weight entries that have changed the most. We present the details of the analysis of entanglement in Section A.6. We also observe the ECF method in general preserves better dementia detection capability if weights are only removed from top half layers in the BERT base model (layer 6-12). Figure 5 shows that both methods improve output equity. We further investigate the trade-offs in Figure 6 and compare the performance of our proposed methods to baselines in the presence of a confounding shift ($\alpha_{train} = 3$). We consistently observed that both ECF and DF outperform naive CF and two other baseline methods, suggesting that the proposed approaches offer distinct advantages, particularly in confounding shift scenarios. It is important to note, however, that unlike the confounding filter and our variants, the two adapter-based methods were not specifically designed to address confounding bias. Both ECF and DF provide a broad selection of models along the trade-off curve, with DF being more computationally efficient as it requires training only once.

8 Conclusion

In this paper, we address confounding bias learned during model fine-tuning and propose two model-agnostic methods for filtering confounding-associated weights in transformers. We apply these methods to dementia detection tasks, demonstrating their utility in clinical practice. Our findings indicate unaddressed confounding shifts degrade model performance even when the overall label and group distributions are balanced. Experimental results compare the identification of gender-associated weights both layer-wise and across the entire model. Both methods effectively retain their performance on dementia detection while reducing gender bias. We observed non-monotonic responses across layers, suggesting further investigation is needed to understand the inner workings of even small transformer models. Lastly, we note that ensuring fairness and maintaining model performance often involves trade-offs, and real-world decisions should consider multiple factors, including bias tolerance and use case specifics.

9 Limitations

Dataset The experiments of our proposed methods are only conducted on two relatively small datasets; therefore, generalizability to other datasets will need to be further investigated. In addition, given the small data size, manifesting different levels of confounding shift requires repetitive sampling to meet the desired subgroup distribution. Thus the resultant dataset contains a significant amount of duplicates that may reduce the strength of the findings and would need to be replicated in larger datasets.

Methods In ECF methods, even though the approach we take is the most straightfoward and allows the model to absorb unidirectional effects, we ignore the possibility of other combinations of layer freezing inside the network and leave it to be explored in future work.

Experiments While we acknowledge BERT-base as a good starting point of investigation, we did not include other encoder models in this work. Also, while we briefly discussed some other weight importance measurements to isolate weights that impact certain outputs, we didn't include and compare them with our current approach for deconfounding mainly due to the publicly available code for other prior work not being model-agnostic.

References

Ioana Baldini, Dennis Wei, Karthikeyan Natesan Ramamurthy, Mikhail Yurochkin, and Moninder Singh. 2022. Your fairness may vary: Pretrained language model fairness in toxic text classification. *Preprint*, arXiv:2108.01250.

JT Becker, F Boller, OL Lopez, J Saxton, and KL McGonigle. 1994. The natural history of alzheimer's disease: Description of study cohort and accuracy of diagnosis. *Archives of Neurology*, 51(6):585–594.

Tolga Bolukbasi, Kai-Wei Chang, James Zou, Venkatesh Saligrama, and Adam Kalai. 2016. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *Preprint*, arXiv:1607.06520.

Tianle Cai, Ruiqi Gao, Jason D. Lee, and Qi Lei. 2021. A theory of label propagation for subpopulation shift. *Preprint*, arXiv:2102.11203.

Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Arechiga, and Tengyu Ma. 2019. Learning imbalanced datasets with label-distribution-aware margin loss. In *Advances in Neural Information Processing Systems*.

Pengyu Cheng, Weituo Hao, Siyang Yuan, Shijing Si, and Lawrence Carin. 2021. Fairfil: Contrastive neural debiasing method for pretrained text encoders. In *International Conference on Learning Representations*.

Trevor Cohen and Serguei Pakhomov. 2020. A tale of two perplexities: Sensitivity of neural language models to lexical retrieval deficits in dementia of the alzheimer's type. *Preprint*, arXiv:2005.03593.

Pierre Colombo, Pablo Piantanida, and Chloé Clavel. 2021. A novel estimator of mutual information for learning to disentangle textual representations. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 6539–6550, Online. Association for Computational Linguistics.

Daniel de Vassimon Manela, David Errington, Thomas Fisher, Boris van Breugel, and Pasquale Minervini. 2021. Stereotype and skew: Quantifying gender bias in pre-trained and fine-tuned language models. *Preprint*, arXiv:2101.09688.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Xiruo Ding, Zhecheng Sheng, Meliha Yetişgen, Serguei Pakhomov, and Trevor Cohen. 2024. Backdoor adjustment of confounding by provenance for robust text classification of multi-institutional clinical notes. In *AMIA ... Annual Symposium proceedings. AMIA Symposium*, pages 923–932.

Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Rich Zemel. 2011. Fairness through awareness. *Preprint*, arXiv:1104.3913.

Shahla Farzana and Natalie Parde. 2023. Towards domain-agnostic and domain-adaptive dementia detection from spoken language. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11965–11978, Toronto, Canada. Association for Computational Linguistics.

Michael Gira, Ruisu Zhang, and Kangwook Lee. 2022. Debiasing pre-trained language models via efficient fine-tuning. In *Proceedings of the Second Workshop on Language Technology for Equality, Diversity and Inclusion*, pages 59–69, Dublin, Ireland. Association for Computational Linguistics.

Harold Goodglass and Edith Kaplan. 1983. *Boston Diagnostic Aphasia Examination Booklet*. Lea & Febiger, Philadelphia.

Yue Guo, Changye Li, Carol Roan, Serguei Pakhomov, and Trevor Cohen. 2021. Crossing the "cookie theft" corpus chasm: Applying what bert learns from outside data to the adress challenge dementia detection task. *Frontiers in Computer Science*, 3.

Yue Guo, Yi Yang, and Ahmed Abbasi. 2022. Auto-debias: Debiasing masked language models with automated biased prompts. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL 2022)*. Association for Computational Linguistics.

Moritz Hardt, Eric Price, and Nathan Srebro. 2016. Equality of opportunity in supervised learning. *Preprint*, arXiv:1610.02413.

Lukas Hauzenberger, Shahed Masoudian, Deepak Kumar, Markus Schedl, and Navid Rekabsaz. 2023. Modular and on-demand bias mitigation with attribute-removal subnetworks. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 6192–6214, Toronto, Canada. Association for Computational Linguistics.

Luis Hernandez-Dominguez, Samuel Ratté, Basilio A. Sierra, and Jesus A. Roche-Berges. 2018. Computer-based evaluation of alzheimer's disease and mild cognitive impairment using lexical and syntactic information. *Journal of Alzheimer's Disease*, 63(2):709–719.

Ben Hutchinson, Vinodkumar Prabhakaran, Emily Denton, Kellie Webster, Yu Zhong, and Stephen Denuyl. 2020. Social biases in nlp models as barriers for persons with disabilities. *Preprint*, arXiv:2005.00813.

Masahiro Kaneko and Danushka Bollegala. 2021. Debiasing pre-trained contextualised embeddings. *Preprint*, arXiv:2101.09523.

Virgile Landeiro and Aron Culotta. 2018. Robust text classification under confounding shift. *J. Artif. Int. Res.*, 63(1):391–419.

Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. 2020. Biobert: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240.

Namhoon Lee, Thalaiyasingam Ajanthan, and Philip H. S. Torr. 2019. Snip: Single-shot network pruning based on connection sensitivity. *Preprint*, arXiv:1810.02340.

Changye Li, David Knopman, Weizhe Xu, Trevor Cohen, and Serguei Pakhomov. 2022. GPT-D: Inducing dementia-related linguistic anomalies by deliberate degradation of artificial neural language models. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1866–1877, Dublin, Ireland. Association for Computational Linguistics.

Changye Li, Zhecheng Sheng, Trevor Cohen, and Serguei Pakhomov. 2024. Too big to fail: Larger language models are disproportionately resilient to induction of dementia-related linguistic anomalies. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 6363–6377, Bangkok, Thailand and virtual meeting. Association for Computational Linguistics.

Yan Liu, Yu Liu, Xiaokang Chen, Pin-Yu Chen, Daoguang Zan, Min-Yen Kan, and Tsung-Yi Ho. 2024. The devil is in the neurons: Interpreting and mitigating social biases in language models. In *The Twelfth International Conference on Learning Representations*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *Preprint*, arXiv:1907.11692.

Saturnino Luz, Fasih Haider, Sofia de la Fuente, Davida Fromm, and Brian MacWhinney. 2020. Alzheimer's dementia recognition through spontaneous speech: The ADReSS Challenge. In *Proceedings of INTERSPEECH 2020*, Shanghai, China.

Brian MacWhinney. 2007. The talkbank project. In *Creating and Digitizing Language Corpora*, pages 163–180. Palgrave Macmillan, London.

Shahed Masoudian, Cornelia Volaucnik, Markus Schedl, and Navid Rekabsaz. 2024. Effective controllable bias mitigation for classification and retrieval using gate adapters. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2434–2453, St. Julian's, Malta. Association for Computational Linguistics.

Shamila Nasreen, Julian Hough, and Matthew Purver. 2021. Rare-class dialogue act tagging for Alzheimer's disease diagnosis. In *Proceedings of the 22nd Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 290–300, Singapore and Online. Association for Computational Linguistics.

Anh Nguyen, Jason Yosinski, and Jeff Clune. 2015. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*.

Judea Pearl. 2009. *Causality*, 2nd edition. Cambridge University Press, Cambridge, UK.

Charlene Pope and Boyd H. Davis. 2011. Finding a balance: The carolinas conversation collection. *Corpus Linguistics and Linguistic Theory*, 7(1):143–161.

Rebecca Qian, Candace Ross, Jude Fernandes, Eric Smith, Douwe Kiela, and Adina Williams. 2022. Perturbation augmentation for fairer nlp. *Preprint*, arXiv:2205.12586.

Shauli Ravfogel, Michael Twiton, Yoav Goldberg, and Ryan Cotterell. 2022. Linear adversarial concept erasure. *Preprint*, arXiv:2201.12091.

Yaniv Romano, Stephen Bates, and Emmanuel J. Candès. 2020. Achieving equalized odds by resampling sensitive attributes. *Preprint*, arXiv:2006.04292.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2020. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *Preprint*, arXiv:1910.01108.

Aili Shen, Xudong Han, Trevor Cohn, Timothy Baldwin, and Lea Frermann. 2021. Contrastive learning for fair representations. *Preprint*, arXiv:2109.10645.

Mingjie Sun, Zhuang Liu, Anna Bair, and J. Zico Kolter. 2024. A simple and effective pruning approach for large language models. *Preprint*, arXiv:2306.11695.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. 2013. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30.

Haohan Wang, Akshay Meghawat, Louis-Philippe Morency, and Eric P Xing. 2017a. Select-additive learning: Improving generalization in multimodal sentiment analysis. In *IEEE International Conference on Multimedia and Expo*.

Haohan Wang, Bhiksha Raj, and Eric P Xing. 2017b. On the origin of deep learning. *arXiv preprint arXiv:1702.07800*.

Haohan Wang, Zhenglin Wu, and Eric P. Xing. 2019. Removing confounding factors associated weights in deep neural networks improves the prediction accuracy for healthcare applications. In *Pacific Symposium on Biocomputing. Pacific Symposium on Biocomputing*, volume 24, pages 54–65.

Kellie Webster, Xuezhi Wang, Ian Tenney, Alex Beutel, Emily Pitler, Ellie Pavlick, Jilin Chen, Ed Chi, and Slav Petrov. 2021. Measuring and reducing gendered correlations in pre-trained models. *Preprint*, arXiv:2010.06032.

Boyi Wei, Kaixuan Huang, Yangsibo Huang, Tinghao Xie, Xiangyu Qi, Mengzhou Xia, Prateek Mittal, Mengdi Wang, and Peter Henderson. 2024. Assessing the brittleness of safety alignment via pruning and low-rank modifications. *Preprint*, arXiv:2402.05162.

Yuzhe Yang, Haoran Zhang, Dina Katabi, and Marzyeh Ghassemi. 2023. Change is hard: A closer look at subpopulation shift. *Preprint*, arXiv:2302.12254.

Xiongyi Zhang, Jan-Willem van de Meent, and Byron Wallace. 2021. Disentangling representations of text by masking transformers. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 778–791, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Beier Zhu, Yulei Niu, Saeil Lee, Minhoe Hur, and Hanwang Zhang. 2023. Debiased fine-tuning for vision-language models by prompt regularization. *Preprint*, arXiv:2301.12429.

A Appendix

A.1 Gender bias in dementia detection

Figure A1: Performance discrepancy between male and female in two datasets, all with BERT-base model for prediction. **Top**: AUPRC results from DB, **Bottom**: AUPRC results from CCC.

A.2 Dataset Statistics

A.3 Relationship of three types of masks in Dual Filter

The relationships between the ablation ratio of the three types of masks and the choice of k are shown in Figure A2. As we tune k to increase the coverage of active parameters in the model, the size of M_D first grows then reaches its peak at around $k = 40$ and then falls back to zero, while the size of M_I keeps increasing.

DB Dataset		
Gender	Label	Count
Female	0	57
Female	1	126
Male	0	41
Male	1	66

CCC Dataset		
Gender	Label	Count
Female	0	220
Female	1	103
Male	0	42
Male	1	29

Table A1: DB and CCC Datasets gender-label counts

Figure A2: Ablation ratio by each mask against the total masking ratio

Figure A3: Relationship between AUPRC and weights ablation on CCC dataset.

Figure A4: Relationship between AUPRC and weights ablation on CCC dataset.

Methods	Hyparam	Values	Note
CONGATER	ω	0.2, 0.4, 0.6, 0.8, 1.0	gate sensitivity
MODDIFFY	fixmask_pct	0.1, 0.3, 0.5, 0.7, 0.9	weight mask cutoffs

Table A2: Hyperparameters used in baseline experiments

A.4 CF vs ECF on CCC dataset

A.5 Baseline Methods Hyperparameters

A.6 Entanglement Analysis

While the aim of this work is to eliminate gender confounding effects from the model's dementia detection capability, there is a possibility that the weights associated with dementia and gender become entangled during the learning process (i.e., same weights responsible for both - gender and dementia encoding). To investigate this, we record the change matrices for all layers in the network during the Dual Filter training process. We then conduct an analysis of the similarity between the change matrices from the fine-tuned dementia model and those from the fine-tuned gender model. For similarity measurements, we utilize the Jaccard Index to quantify the similarity between the two input matrices, which is defined as:

$$J(U, V) = \frac{|U \cap V|}{|U \cup V|}$$

To prepare the input, 85% percentiles of the two change matrices are calculated and then the percentile values are used to binarize each of the matrices. Figure A5 demonstrates the barplot from six of the tracked weight matrices at each layer, with the configuration of α_{train} equals to 1. From the plot we can observe that at lower encoder layers, the similarity between dementia model and gender model concentrates on the attention block, especially W_V and W_O. As we move up to the upper layer, the FFN block starts to display more similarity and jumps up at 12^{th} layer. Similar patterns are also observed in other α_{train} configurations. This result indicates the fine-tuned model stores information dynamically through the whole network and shift the storage at different layers. This finding also aligns with other work (Wei et al., 2024) where weights entanglement are assessed with a larger model and different tasks.

Figure A5: Jaccard Index for each of the tracked matrix
in Dual Filter