Provable Benefits of Representation Learning in Linear Bandits

Abstract

We study how representation learning can improve the efficiency of bandit problems. We study the setting where we play T linear bandits with dimension d concurrently, and these T bandit tasks share a common $k(\ll d)$ dimensional linear representation. For the finite-action setting, we present a new algorithm which achieves $\widetilde{O}(T\sqrt{kN} + \sqrt{dkNT})$ regret, where N is the number of rounds we play for each bandit. When T is sufficiently large, our algorithm significantly outperforms the naive algorithm (playing T bandits independently) that achieves $\widetilde{O}(T\sqrt{dN})$ regret. We also provide an $\Omega(T\sqrt{kN} + \sqrt{dkNT})$ regret lower bound, showing that our algorithm is minimax-optimal up to poly-logarithmic factors. Furthermore, we extend our algorithm to the infinite-action setting and obtain a corresponding regret bound which demonstrates the benefit of representation learning in certain regimes. We also present experiments on synthetic and real-world data to illustrate our theoretical findings and demonstrate the effectiveness of our proposed algorithms.

1 Introduction

This paper investigates the benefit of using representation learning for sequential decision-making problems. Representation learning learns a joint low-dimensional embedding (feature extractor) from different but related tasks, and then uses a simple function (often a linear one) on top of the embedding (Baxter, 2000; Caruana, 1997). The mechanism behind is that since the tasks are related, we can extract the common information more efficiently than treating each task independently.

Empirically, representation learning has become a popular approach for improving the efficiency across various machine learning tasks (Bengio et al., 2013). In particular, recently, representation learning has become increasingly more popular in sequential decision-making problems (Teh et al., 2017; Taylor & Stone, 2009; Lazaric & Restelli, 2011; Rusu et al., 2015; Liu et al., 2016; Parisotto et al., 2015; Higgins et al., 2017; Hessel et al., 2019; Arora et al., 2020; D'Eramo et al., 2020). For example, many sequential decision-making tasks share the same environment but have different reward functions. Thus a natural approach is to learn a succinct representation that describes the environment and then make decisions for different tasks on top of the learned representation.

While representation learning is already widely applied in sequential decision-making problems empirically, its theoretical foundation is still limited. One important problem remains open:

When does representation learning *provably* improves the efficiency of sequential decision-making problems?

In this paper, we take a step to characterize the benefit of representation learning in sequential decision-making problems. We tackle the above problem in the linear bandits setting, one of the most fundamental and popular settings in sequential decision-making problems. This model is widely used in applications as such clinical treatment, manufacturing process, job scheduling, recommendation systems, etc (Dani et al., 2008; Chu et al., 2011). In this paper. we study the multi-task version of linear bandits, which naturally models the scenario where one needs to deal with multiple different but closely related sequential decision-making problems concurrently.

We will mostly focus on the finite-action setting. Specifically, we have T tasks, each of which is governed by an unknown linear coefficient $\boldsymbol{\theta}_t \in \mathbb{R}^d$. At the n-th round, for each task $t \in [T]$, the

player chooses an action $a_{n,t}$ that belongs to a finite set, and receive a reward $r_{n,t}$ with expectation $\mathbb{E}\, r_{n,t} = \langle \boldsymbol{\theta}_t, \boldsymbol{x}_{n,t,a_{n,t}} \rangle$ where $\boldsymbol{x}_{n,t,a_{n,t}}$ represents the context of action $a_{n,t}$. For this problem, a straightforward approach is to treat each task independently, which leads to $\widetilde{O}(T\sqrt{dN})$[1] total regret. Can we do better?

Clearly, if the tasks are independent, then by the classical $\Omega(\sqrt{dN})$ per task lower bound for linear bandit, it is impossible to do better. We investigate how representation learning can help if the tasks are related. Our main assumption is the existence of an unknown *linear feature extractor* $\boldsymbol{B} \in \mathbb{R}^{d \times k}$ with $k \ll d$ and a set of linear coefficients $\{\boldsymbol{w}_t\}_{t=1}^{T}$ such that $\boldsymbol{\theta}_t = \boldsymbol{B}\boldsymbol{w}_t$. Under this assumption, the tasks are closely related as $\boldsymbol{B}$ is a *shared* linear feature extractor that maps the raw contexts $\boldsymbol{x}_{n,t,a} \in \mathbb{R}^d$ to a low-dimensional embedding $\boldsymbol{B}^\top \boldsymbol{x}_{n,t,a} \in \mathbb{R}^k$. Typically, k is small compared to other parameters d, N, T. Problems with similar assumptions have been studied in the supervised learning setting (Ando & Zhang, 2005). However, to our knowledge, this formulation has not been studied in the bandits settings.

Our Contributions We give the first rigorous characterization on the benefit of representation learning for multi-task linear bandits. Our contributions are summarized below.

- We design a new algorithm for the aforementioned problem. Theoretically, we show our algorithm incurs $\widetilde{O}(\sqrt{dkTN} + T\sqrt{kN})$ total regret in N rounds for all T tasks. Therefore, our algorithm outperforms the naive approach with $O(T\sqrt{dN})$ regret. To our knowledge, this is the first theoretical result demonstrating the benefit of representation learning for bandits problems.

- To complement our upper bound, we also provide an $\Omega(\sqrt{dkTN} + T\sqrt{kN})$ lower bound, showing our regret bound is tight up to polylogarithmic factors.

- We further design a new algorithm for the infinite-action setting, which has a regret $\widetilde{O}(d^{1.5}k\sqrt{TN} + kT\sqrt{N})$, which outperforms the naive approach with $O(Td\sqrt{N})$ regret in the regime where $T = \widetilde{\Omega}(dk^2)$.

- We provide simulations and an experiment on MNIST dataset to illustrate the effectiveness of our algorithms and the benefits of representation learning.

Organization This paper is organized as follows. In Section 2, we discuss related works. In Section 3, we introduce necessary notations, formally set up our problem, and describe our assumptions. In Section 4, we present our main algorithm for finite-action setting and its performance guarantee. In Section 5, we describe our algorithm and its theoretical guarantee for the infinite-action setting. In Section 6, we provide simulation studies and real-world experiments to validate the effectiveness of our approach. We conclude in Section 7 and defer all proofs to appendix.

2 RELATED WORK

Here we mainly focus on related theoretical results. We refer readers to Bengio et al. (2013) for empirical results of using representation learning.

For supervised learning, there is a long line of works on multi-task learning and representation learning with various assumptions (Baxter, 2000; Ando & Zhang, 2005; Ben-David & Schuller, 2003; Maurer, 2006; Cavallanti et al., 2010; Maurer et al., 2016; Du et al., 2020; Tripuraneni et al., 2020). All these results assumed the existence of a common representation shared among all tasks. However, this assumption alone is not sufficient. For example, Maurer et al. (2016) further assumed every task is i.i.d. drawn from an underlying distribution. Recently, Du et al. (2020) replaced the i.i.d. assumption with a deterministic assumption on the input distribution. Finally, it is worth mentioning that Tripuraneni et al. (2020) gave the method-of-moments estimator and built the confidence ball for the feature extractor, which inspired our algorithm for the infinite-action setting.

The benefit of representation learning has been studied in sequential decision-making problems, especially in reinforcement learning domains. D'Eramo et al. (2020) showed that representation learning can improve the rate of approximate value iteration algorithm. Arora et al. (2020) proved

---

[1] $\widetilde{O}(\cdot)$ omits logarithmic factors.

that representation learning can reduce the sample complexity of imitation learning. Both works require a probabilistic assumption similar to that in (Maurer et al., 2016) and the statistical rates are of similar forms as those in (Maurer et al., 2016).

We remark that representation learning is also closely connected to meta-learning (Schaul & Schmidhuber, 2010). Raghu et al. (2019) empirically suggested that the effectiveness of meta-learning is due to its ability to learn a useful representation. There is a line of works analyzed the theoretical properties of meta-learning (Denevi et al., 2019; Finn et al., 2019; Khodak et al., 2019; Lee et al., 2019; Bertinetto et al., 2018). We also note that there are analyses for other representation learning schemes (Arora et al., 2019; McNamara & Balcan, 2017; Galanti et al., 2016; Alquier et al., 2016; Denevi et al., 2018).

Linear bandits (stochastic linear bandits / linearly parameterized bandits / contextual linear bandits) have been studied in recent years (Auer, 2002; Dani et al., 2008; Rusmevichientong & Tsitsiklis, 2010; Abbasi-Yadkori et al., 2011; Chu et al., 2011; Li et al., 2019a;b). The studies are divided into two branches according to whether the action set is finite or infinite. For the finite-action setting, $\widetilde{\Theta}(\sqrt{dN})$ has been shown to be the near-optimal regret bound (Chu et al., 2011; Li et al., 2019a), and for the infinite-action setting, $\widetilde{\Theta}(d\sqrt{N})$ regret bound has been shown to be near-optimal (Dani et al., 2008; Rusmevichientong & Tsitsiklis, 2010; Li et al., 2019b).

Jun et al. (2019) studied the bilinear bandit with low-rank structure. In their setting, the player chooses two actions $\boldsymbol{x}, \boldsymbol{y}$ and receives the stochastic reward with mean $\boldsymbol{x}^\top \boldsymbol{\Theta} \boldsymbol{y}$, where $\boldsymbol{\Theta}$ is an unknown bilinear form with low rank. Their proposed algorithm shares some similarity as our algorithm for the infinite-action setting in that they added an exploration stage to extract the low-rank structure of Θ. Their setting is further generalized and studied by Lu et al. (2020).

Some previous work proposed multi-task bandits with different settings. Deshmukh et al. (2017) proposed a setting under the contextual bandits framework. They assumed similarities among arms. Soare et al. (2018) proposed a setting where tasks were played one by one sequentially and the coefficients of the tasks were near in ℓ_2 distance. In our setting, the tasks are played simultaneously and the coefficients share a common linear feature extractor.

3 PRELIMINARIES

Notations. Matrices are upright bold letters. For any positive integer n, we use $[n]$ to denote the set of integers $\{1, 2, \cdots, n\}$. For any vector $\boldsymbol{x}$, we use $\|\boldsymbol{x}\|$ to denote its ℓ_2 norm. For matrix $\boldsymbol{A}$, we use $\|\boldsymbol{A}\|$ to denote the 2-norm of $\boldsymbol{A}$, $\|\boldsymbol{A}\|_F$ to denote the Frobenius norm, and $\|\boldsymbol{A}\|_{\max} = \max_{i,j} |\boldsymbol{A}_{ij}|$ to denote the max-norm. For two expressions α, β, we denote $\alpha \lesssim \beta$ if there is a numeric constant $c > 0$ such that $\alpha \leq c\beta$. We denote $\alpha \gtrsim \beta$ if $\beta \lesssim \alpha$.

Problem Setup. Let d be the ambient dimension and $k(\leq d)$ be the representation dimension. In total, we have T tasks and we play each task concurrently for N rounds. Each task $t \in [T]$ has an unknown vector $\boldsymbol{\theta}_t \in \mathbb{R}^d$. At each round $n \in [N]$, the player chooses action $\boldsymbol{a}_{n,t} \in \mathcal{A}_{n,t}$ for each task $t \in [T]$ where $\mathcal{A}_{n,t}$ is the action set at round n for the task t.

After the player commits to a batch of actions $\{\boldsymbol{a}_{n,t}\}_{t \in [T]}$, it receives a batch of rewards $\{r_{n,t}\}_{t \in [T]}$, where we assume $r_{n,t} = \langle \boldsymbol{a}_{n,t}, \boldsymbol{\theta}_t \rangle + \varepsilon_{n,t}$. Here we assume the noise $\varepsilon_{n,t}$ are independent 1-sub-Gaussian random variables, which is a standard assumption in the literature.

In this paper, we use total expected regret to measure the performance of our algorithm. When we have N rounds and T tasks, it is defined as $R^{N,T} = \sum_{n=1}^N \sum_{t=1}^T \max_{\boldsymbol{a} \in \mathcal{A}_{n,t}} \langle \boldsymbol{a}, \boldsymbol{\theta}_t \rangle - \langle \boldsymbol{a}_{n,t}, \boldsymbol{\theta}_t \rangle$. When the action set is finite, we assume that all $\mathcal{A}_{n,t}$ have the same size K, i.e. $|\mathcal{A}_{n,t}| \equiv K$. Furthermore, we write $\mathcal{A}_{n,t} = \{\boldsymbol{x}_{n,t,1}, \ldots, \boldsymbol{x}_{n,t,K}\}$. Besides, we interchangeably use the number $a_{n,t} \in [K]$ and the vector $\boldsymbol{a}_{n,t} = \boldsymbol{x}_{n,t,a_{n,t}} \in \mathbb{R}^d$ to refer to the same action.

Assumptions. Our main assumption is the existence of a common linear feature extractor.

Assumption 1 (Common Feature Extractor)**.** There exists a linear feature extractor $\boldsymbol{B} \in \mathbb{R}^{d \times k}$ and a set of linear coefficients $\{\boldsymbol{w}_t\}_{t=1}^T$ such that the expected reward of the t-th task at the n-th round satisfies $\mathbb{E}[r_{t,n}] = \langle \boldsymbol{w}_t, \boldsymbol{B}^\top \boldsymbol{x}_{n,t,a_{n,t}} \rangle$.

Algorithm 1: MLinGreedy: Multi-task Linear Bandit with Finite Actions

1: Let $M = \lceil \log_2 \log_2 N \rceil, \mathcal{G}_0 = 0, \mathcal{G}_M = N, \mathcal{G}_m = N^{1-2^{-m}}$ for $1 \le m \le M-1$, let $\widehat{\boldsymbol{\theta}}_{0,t} \leftarrow \mathbf{0}$;
2: **for** $m \leftarrow 1, \dots, M$ **do**
3:      **for** $n \leftarrow \mathcal{G}_{m-1} + 1, \dots, \mathcal{G}_m$ **do**
4:          For each task $t \in [T]$: choose action $a_{n,t} = \arg\max_{a \in [K]} \boldsymbol{x}_{n,t,a}^\top \widehat{\boldsymbol{\theta}}_{m,t}$;
5:      Compute $\widehat{\boldsymbol{B}}\widehat{\boldsymbol{W}} \leftarrow \arg\min_{\boldsymbol{B} \in \mathbb{R}^{d \times k}, \boldsymbol{W} \in \mathbb{R}^{k \times T}} \sum_{n=\mathcal{G}_{m-1}+1}^{\mathcal{G}_m} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t,a_{n,t}}^\top \boldsymbol{B} \boldsymbol{w}_t - r_{n,t}]^2$;
6:      For each task $t \in [T]$: let $\widehat{\boldsymbol{\theta}}_{m,t} = \widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t$;

For simplicity, we let $\boldsymbol{W} = [w_1, \dots, w_T]$. Assumption 1 implies that $\boldsymbol{\Theta} \triangleq [\boldsymbol{\theta}_1, \dots, \boldsymbol{\theta}_T] = \boldsymbol{B}\boldsymbol{W}$. Note this assumption is in a sense necessary to guarantee the effectiveness of representation learning, because without it one cannot hope representation learning can help.

In this paper, we mostly focus on the finite-action setting. We put the following assumption on action sets.

Assumption 2. Marginally, for every $n \in [N], t \in [T], a \in [K]$, the contexts satisfy $\boldsymbol{x}_{n,t,a} \sim \mathcal{N}(\mathbf{0}, \Sigma_t)$ such that $\lambda_{\max}(\Sigma_t) \le O(1/d)$ and $\lambda_{\min}(\Sigma_t) \ge \Omega(1/d)$.

In this assumption, we have an unknown covariance matrix Σ_t for at each task. In each round the actions of the t-th task are samples from a Gaussian distribution with covariance Σ_t. This is a prototypical setting for theoretical development on linear bandits with finite actions (See e.g., Han et al. (2020)). At a population level, each one of the K actions is equally good but being able to select different actions based on the realized contexts allows the player to gain more reward.

We will also study the infinite-action setting. We first state our assumption about the action sets.

Assumption 3 (Ellipsoid Action Set). We assume $\mathcal{A}_{n,t} = \mathcal{A}_t = \{x^\top \boldsymbol{Q}_t^{-1} x \le 1 : x \in \mathbb{R}^d\}$ is an ellipsoid with $\lambda_{\min}(\boldsymbol{Q}_t) \ge \lambda_0 = \Omega(1)$.

The first assumption states that each action set is an ellipsoid which covers all directions. This is a standard assumption, e.g., see Rusmevichientong & Tsitsiklis (2010).

In this setting, we will also need to put some additional assumptions on the underlying parameters $\boldsymbol{B}$ and $\boldsymbol{W}$.

Assumption 4 (Diverse Source Tasks). We assume that $\lambda_{\min}(\frac{1}{T}\boldsymbol{W}\boldsymbol{W}^\top) \ge \frac{\nu}{k}$, where $\nu = \Omega(1)$.

This assumption roughly states that the underlying linear coefficients $\{\boldsymbol{w}_t\}_{t=1}^T$ equally spans all directions in $\mathbb{R}^k$. This is a common assumption in representation learning literature that enables us to learn the linear feature extractor (Du et al., 2020; Tripuraneni et al., 2020). For example, the assumption holds with high probability when $\boldsymbol{w}_i$ is uniformly chosen from the sphere $\mathbb{S}^{k-1}$.

Assumption 5. We assume $\|\boldsymbol{w}_t\| \ge \omega = \Omega(1)$.

This is a normalization assumption on the linear coefficients.

4 MAIN RESULTS FOR FINITE-ACTION SETTING

In this section focus on the finite-action setting. The pseudo-code is listed in Algorithm 1. Our algorithm uses a doubling schedule rule (Gao et al., 2019; Simchi-Levi & Xu, 2019; Han et al., 2020; Ruan et al., 2020). We only update our estimation of $\boldsymbol{\theta}$ after an epoch is finished, and we only use samples collected within the epoch. In Line 5, we solve an empirical ℓ_2-risk minimization problem on the data collected in the last epoch to estimate the feature extractor $\boldsymbol{B}$ and linear predictors $\boldsymbol{W}$, similar to Du et al. (2020). Given estimated feature extractor $\widehat{\boldsymbol{B}}$ and linear predictors $\widehat{\boldsymbol{W}}$, we compute our estimated linear coefficients of task t as $\widehat{\boldsymbol{\theta}}_t \triangleq \widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t$ in Line 6. For choosing actions, for each task, we use a greedy rule, i.e., we choose the action that maximizes the inner product with our estimated $\boldsymbol{\theta}$ (cf. Line 4).

The following theorem gives an upper bound on the regret of Algorithm 1.

Theorem 1 (Regret of Algorithm 1). *Suppose $K, T \leq \text{poly}(d)$ and $N \geq d^2$. Under Assumption 1 and Assumption 2, the expected regret of Algorithm 1 is upper bounded by*

$$\mathbb{E}[R^{N,T}] = \widetilde{O}(T\sqrt{kN} + \sqrt{dkNT}).$$

There are two terms in Theorem 1, and we interpret them separately. The first term $\widetilde{O}(T\sqrt{kN})$ represents the regret for playing T independent linear bandits *with dimension k* for N rounds. This is the regret we need to pay even if we know the optimal feature extractor, with which we can reduce the original problem to playing T independent linear bandits with dimension k (recall $\boldsymbol{w}_t$ are different for different tasks). The second term $\widetilde{O}(\sqrt{dkNT})$ represents the price we need to pay to learn the feature extractor $\boldsymbol{B}$. Notably, this term shows we are using data across all tasks to learn $\boldsymbol{B}$ as this term scales with $\sqrt{NT}$.

Now comparing with the naive strategy that plays T independent d-dimensional linear bandits with regret $\widetilde{O}(T\sqrt{dN})$, our upper bound is smaller as long as $T = \Omega(k)$. Furthermore, when T is large, our bound is significantly stronger than $\widetilde{O}(T\sqrt{dN})$, especially when $k \ll d$. To our knowledge, this is the first formal theoretical result showing the advantage of representation learning for bandit problems. We remark that requiring $T = \Omega(k)$ is necessary. One needs at least k tasks to recover the span of $\boldsymbol{W}$, so only in this regime representation learning can help.

Our result also puts a technical requirement on the scaling $K, T \leq \text{poly}(d)$ and $N \geq d^2$. These are conditions that are often required in linear bandits literature. The first condition ensures that K and T are not too large, so we need not characterize $\log(KT)$ factors in regret bound. If they are too large, e.g. $K, T \geq \Omega(e^d)$, then we would have $\log KT = O(d)$ and we could no longer omit the logarithmic factors in regret bounds. The second condition ensures one can at least learn the linear coefficients up to an constant error. See more discussions in (Han et al., 2020, Section 2.5).

While Algorithm 1 is a straightforward algorithm, the proof of Theorem 1 requires a combination of representation learning and linear bandit techniques. First, we prove the in-sample guarantee of representation learning, as done in Lemma 2. Second, we exploit Assumption 2 to show that the learned parameters could extrapolate well on new contexts, as shown in Lemma 4. The regret analysis then follows naturally. We defer the proof of Theorem 1 to Appendix A.

The following theorem shows that Algorithm 1 is minimax optimal up to logarithmic factors.

Theorem 2 (Lower Bound for Finite-Action Setting). *Let $\mathcal{A}$ denote an algorithm and $\mathcal{I}$ denote a finite-actioned multi-task linear bandit instance that satisfies Assumption 1 and Assumption 2. Then for any $N, T, d, k \in \mathbb{Z}^+$ with $k \leq d$, $k \leq T$, we have*

$$\inf_{\mathcal{A}} \sup_{\mathcal{I}} \mathbb{E}[R^{N,T}_{\mathcal{A},\mathcal{I}}] = \Omega\left(T\sqrt{kN} + \sqrt{dkNT}\right). \tag{1}$$

Theorem 2 has the exactly same two terms as in Theorem 1. This confirms our intuition that the two prices to pay are real: 1) playing T independent k-dimensional linear bandits and 2) learning the $d \times k$-dimensional feature extractor. We defer the proof of Theorem 2 to Appendix B. At a high level, we separately prove the two terms in the lower bound. The first term is established by the straightforward observation that our multi-task linear bandit problem is at least as hard as solving T independent k-dimensional linear bandits. The second term is established by the observation that multi-task linear bandit can be seen as solving k independent d-dimensional linear bandits, each has NT/k rounds. Note that the observation would directly imply the regret lower bound $k\sqrt{d(NT/k)} = \sqrt{dkNT}$, which is exactly the second term. To our knowledge, this lower bound is also the first one of its kind for multi-task sequential decision-making problems. We believe our proof framework can be used in proving lower bounds for other related problems.

5 EXTENSION TO INFINITE-ACTION SETTING

In this section we present and analyze an algorithm for the infinite-action setting. Pseudo-code is listed in Algorithm 2. Our algorithm has three stages, and we explain each step below.

Stage 1: Estimating Linear Feature Extractor with Method-of-Moments. The goal of the first stage is to estimate the linear feature extractor $\boldsymbol{B}$. Our main idea to view this problem as a low-rank estimation problem for which we use an method-of-moments estimator. In more detail, we

---

Algorithm 2: $\mathsf{E^2TC}$: Explore-Explore-Then-Commit

Input: N: total number of rounds , N_1: number of rounds for stage 1 , N_2: number of rounds for stage 2

1: *Stage 1: Estimating Linear Feature Extractor with Method-of-Moments*;
2: **for** $\forall t \in [T], n \in [N_1]$ **do**
3:     Play $x_{n,t} \sim \mathrm{Unif}(\lambda_0 \cdot \mathbb{S}^{d-1})$ and receive reward $r_{n,t}$;
4: Compute $\widehat{\mathbf{M}} \leftarrow \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} r_{n,t}^2 x_{n,t} x_{n,t}^\top$;
5: Let $\widehat{\mathbf{B}} \mathbf{D} \widehat{\mathbf{B}}^\top \leftarrow$ top-k singular value decomposition of $\widehat{\mathbf{M}}$. Denote $\widehat{\boldsymbol{b}}_i$ the i-th column of $\widehat{\mathbf{B}}$;
6: *Stage 2: Estimating Optimal Actions on Low-dimensional Space* ;
7: **for** $\forall t \in [T], i \in [k]$ **do**
8:     Play $v_{t,i} \triangleq \sqrt{\lambda_0} \hat{\boldsymbol{b}}_i$ for N_2/k times and receive rewards $\{r_{n,t}\}_{n=N_1+(i-1)N_2/k+1}^{N_1+iN_2/k}$;
9: **for** $\forall t \in [T]$ **do**
10:     Estimate $\widehat{\boldsymbol{w}}_t \leftarrow \arg\min_{\boldsymbol{w} \in \mathbb{R}^k} \frac{1}{2N_2} \sum_{n=N_1+1}^{N_1+N_2} [\langle x_{n,t}, \widehat{\mathbf{B}} \boldsymbol{w}\rangle - r_{n,t}]^2$;
11:     Let $\widehat{\boldsymbol{\theta}}_t = \widehat{\mathbf{B}} \widehat{\boldsymbol{w}}_t$;
12: *Stage 3: Committing to Near-optimal Actions*;
13: **for** $\forall t \in [T], n = N_1 + N_2 + 1, \ldots, N$ **do**
14:     Play $\boldsymbol{a}_{n,t} \leftarrow \arg\max_{\boldsymbol{a} \in \mathcal{A}_t} \langle a, \widehat{\boldsymbol{\theta}}_t \rangle$ and receive reward $r_{n,t}$;

---

first sample each $x_{n,t} \sim \mathrm{Unif}[\lambda_0 \cdot \mathbb{S}^d]$ for N_1 times. We can use this sampling scheme because the action set is an ellipsoid. Note this sampling scheme has a sufficient coverage on all directions, which help us estimate $\mathbf{B}$. Next, we compute the empirical weighted covariance matrix $\widehat{\mathbf{M}} = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} r_{n,t}^2 \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top$. To proceed, we compute the singular value decomposition of $\widehat{\mathbf{B}}$ and keep its top-k column space as our estimated linear feature extractor $\widehat{\mathbf{B}}$, which is a sufficiently accurate estimator (cf. Theorem 5).

Stage 2: Estimating Optimal Actions on Low-dimensional Space. In the second stage, we use our estimated linear feature extractor to refine our search space for the optimal actions. Specifically, we denote $\widehat{\mathbf{B}} = [\widehat{\boldsymbol{b}}_1, \ldots, \widehat{\boldsymbol{b}}_k]$ and for $i \in [k]$ and $t \in [T]$, we let $v_{t,i} = \sqrt{\lambda_0} \widehat{\boldsymbol{b}}_i$. Under Assumption 3, we know $\boldsymbol{v}_{t,i} \in \mathcal{A}_t$ for all $i \in [k]$. Therefore, we can choose $\boldsymbol{v}_{t,i}$ to explore. Technically, our choice of actions $\boldsymbol{v}_{t,i}$ also guarantees a sufficient cover in the sense that $\lambda_{\min}\left(\sum_{i=1}^{k} \widehat{\mathbf{B}}^\top \boldsymbol{v}_{t,i} \boldsymbol{v}_{t,i}^\top \widehat{\mathbf{B}}\right) \geq \lambda_0$. In particular, this coverage is on a *low-dimensional space* instead of the original ambient space.

The second stage has N_2 rounds and on the t-th task, we just play each $\boldsymbol{v}_{t,i}$ for N_2/k rounds. After that, we use linear regression to estimate $\boldsymbol{w}_t$ for each task. Given the estimation $\widehat{\boldsymbol{w}}_t$, we can obtain an estimation to the true linear coefficient $\widehat{\boldsymbol{\theta}}_t \triangleq \widehat{\mathbf{B}} \widehat{\boldsymbol{w}}_t$.

Stage 3: Committing to Near-optimal Actions. After the second stage, we have an estimation $\widehat{\boldsymbol{\theta}}_t$ for each task. For the remaining $(N - N_1 - N_2)$ rounds, we just commit to the optimal action indicated by our estimations. Specifically, we play the action $\boldsymbol{a}_{n,t} \leftarrow \arg\max_{\boldsymbol{a} \in \mathcal{A}_t} \langle \boldsymbol{a}_t, \widehat{\boldsymbol{\theta}}_t \rangle$ for round $n = N_1 + N_2 + 1, \ldots, N$.

The following theorem characterizes the regret of our algorithm.

Theorem 3 (Regret of Algorithm 2). *If we choose $N_1 = c_1 d^{1.5} k \sqrt{\frac{N}{T}}$ and $N_2 = c_2 k \sqrt{N}$ for some constants $c_1, c_2 > 0$. The regret of Algorithm 2 is upper bounded by*

$$\mathbb{E}[R^{N,T}] = \widetilde{O}(d^{1.5} k \sqrt{TN} + kT\sqrt{N}).$$

The first term represents the regret incurred by estimating the linear feature extractor. Notably, the term scales with $\sqrt{TN}$, which means we utilize all TN data here. The first term scales with $d^{1.5}k$, which we conjecture is unavoidable at least by our algorithm. The second term represents playing T independent k-dimensional infinite-action linear bandits.

Notice that if one uses a standard algorithm, e.g. the PEGE algorithm (Rusmevichientong & Tsitsiklis, 2010), to play T tasks independently, one can achieve an $\widetilde{O}(dT\sqrt{N})$ regret. Comparing with

Figure 1: Comparisons of Algorithm 1 with the naive algorithm for $d = 30$ on synthetic data.

Figure 2: Comparisons of Algorithm 1 with the naive algorithm for $d = 20$ on synthetic data.

this bound, our bound's second term is always smaller and the first is smaller when $T = \widetilde{\Omega}(dk^2)$. This demonstrates that more tasks indeed help us learn the representation and reduce the regret.

We complement our upper bound with a lower bound below. This theorem suggests our second term is tight but there is still a gap in the first term. We leave it as an open problem to design new algorithm to match the lower bound or to prove a stronger lower bound.

Theorem 4 (Lower Bound for Infinite-Action Setting). *Let $\mathcal{A}$ denote an algorithm and $\mathcal{I}$ denote an infinite-action multi-task linear bandit instance that satisfies Assumption 1, Assumption 3, Assumption 4, Assumption 5. Then for any $N, T, d, k \in \mathbb{Z}^+$ with $k \le d$, $k \le T$, we have*

$$\inf_{\mathcal{A}} \sup_{\mathcal{I}} \mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N,T}] = \Omega\left(d\sqrt{kNT} + kT\sqrt{N}\right). \tag{2}$$

6 EXPERIMENTS

In this section, we use synthetic data and MNIST data to illustrate our theoretical findings and demonstrate the effectiveness of our Algorithm for the finite-action setting. We also have simulation studies for the infinite-action setting, which we defer to Appendix F.

6.1 SYNTHETIC DATA

Setup. The linear feature extractor $\boldsymbol{B}$ is uniformly drawn from the set of $d \times k$ matrices with orthonormal columns.[2] Each linear coefficient $\boldsymbol{w}_t$ is uniformly chosen from the k-dimensional sphere. The noises are i.i.d. Gaussian: $\varepsilon_{n,t,a} = \mathcal{N}(0,1)$ for every $n \in [N], t \in [T], a \in [K]$. We fix $K = 5$ and $N = 10000$ for all simulations on finite-action setting. We vary k, d and T to compare Algorithm 1 and the naive algorithm which plays T tasks independently.

Results and Discussions. We present the simulation results in Figure 1 and Figure 2. We emphasize that the y-axis in our figures corresponds to the regret per task, which is defined as $R^{N,T}/T$. We fix $K = 5, N = 10000$. These simulations verify our theoretical findings. First, as the number of tasks

---

[2]We uniformly (under the Haar measure) choose a random element from the orthogonal group $O(d)$ and uniformly choose k of its columns to generate $\boldsymbol{B}$.

Figure 3: Comparisons of Algorithm 1 with the naive algorithm for $T = 10$ on MNIST .

Figure 4: Comparisons of Algorithm 1 with the naive algorithm for $T = 45$ on MNIST.

increases, the advantage of our algorithm increases compared to the naive algorithm. Secondly, we notice that as k becomes larger (relative to d), the advantage of our algorithm becomes smaller. This can be explained by our theorem that as k increases, our algorithm pays more regret, whereas the naive algorithm's regret does not depend on k.

6.2 FINITE-ACTION LINEAR BANDITS FOR MNIST

Setup. We create a linear bandits problem on MNIST data (LeCun et al., 2010) to illustrate the effectiveness of our algorithm on real-world data. We fix $K = 2$ and create $T = \binom{10}{2}$ tasks and each task is parameterized by a pair (i, j), where $0 \leq i < j \leq 9$. We use $\mathcal{D}_i$ to denote the set of MNIST images with digit i. At each round $n \in [N]$, for each task (i, j), we randomly choose one picture from $\mathcal{D}_i$ and one from $\mathcal{D}_j$, then we present those two pictures to the algorithm and assign the picture with larger digit with reward 1 and the other with reward 0. The algorithm is now required to select an image (action). We again compare our algorithm with the naive algorithm.

Results and Discussions. The experimental results are displayed in Figure 3 for $T = 10$ (done by constructing tasks with the first five digits) and Figure 4 for $T = 45$. We observe for both $T = 10$ and $T = 45$, our algorithm significantly outperforms the naive algorithm for all k. Interestingly, unlike our simulations, we find the advantage of our algorithm does not decrease as we increase k. We believe the reason is the optimal predictor is not exactly linear, and we need to develop an agnostic theory to explain this phenomenon, which we leave as a future work.

7 CONCLUSION

We initiate the study on the benefits of representation learning in bandits. We proposed new algorithms and demonstrated that in the multi-task linear bandits, if all tasks share a common linear feature extractor, then representation learning provably reduces the regret. We demonstrated empirical results to corroborate our theory. An interesting future direction is to generalize our results to general reward function classes (Li et al., 2017; Agrawal et al., 2019).

REFERENCES

Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pp. 2312–2320, 2011.

Shipra Agrawal, Vashist Avadhanula, Vineet Goyal, and Assaf Zeevi. Mnl-bandit: A dynamic learning approach to assortment selection. *Operations Research*, 67(5):1453–1485, 2019.

Pierre Alquier, The Tien Mai, and Massimiliano Pontil. Regret bounds for lifelong learning. *arXiv preprint arXiv:1610.08628*, 2016.

Rie Kubota Ando and Tong Zhang. A framework for learning predictive structures from multiple tasks and unlabeled data. *Journal of Machine Learning Research*, 6(Nov):1817–1853, 2005.

Sanjeev Arora, Hrishikesh Khandeparkar, Mikhail Khodak, Orestis Plevrakis, and Nikunj Saunshi. A theoretical analysis of contrastive unsupervised representation learning. In *Proceedings of the 36th International Conference on Machine Learning*, 2019.

Sanjeev Arora, Simon S Du, Sham Kakade, Yuping Luo, and Nikunj Saunshi. Provable representation learning for imitation learning via bi-level optimization. *arXiv preprint arXiv:2002.10544*, 2020.

Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

Jonathan Baxter. A model of inductive bias learning. *Journal of artificial intelligence research*, 12: 149–198, 2000.

Shai Ben-David and Reba Schuller. Exploiting task relatedness for multiple task learning. In *Learning Theory and Kernel Machines*, pp. 567–580. Springer, 2003.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Luca Bertinetto, Joao F Henriques, Philip HS Torr, and Andrea Vedaldi. Meta-learning with differentiable closed-form solvers. *arXiv preprint arXiv:1805.08136*, 2018.

Rajendra Bhatia. *Matrix analysis*, volume 169. Springer Science & Business Media, 2013.

Rich Caruana. Multitask learning. *Machine learning*, 28(1):41–75, 1997.

Giovanni Cavallanti, Nicolo Cesa-Bianchi, and Claudio Gentile. Linear algorithms for online multitask classification. *Journal of Machine Learning Research*, 11(Oct):2901–2934, 2010.

Wei Chu, Lihong Li, Lev Reyzin, and Robert Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pp. 208–214, 2011.

Varsha Dani, Thomas P. Hayes, and Sham M. Kakade. Stochastic linear optimization under bandit feedback. In *COLT*, 2008.

Giulia Denevi, Carlo Ciliberto, Dimitris Stamos, and Massimiliano Pontil. Incremental learning-to-learn with statistical guarantees. *arXiv preprint arXiv:1803.08089*, 2018.

Giulia Denevi, Carlo Ciliberto, Riccardo Grazzi, and Massimiliano Pontil. Learning-to-learn stochastic gradient descent with biased regularization. In *Proceedings of the 36th International Conference on Machine Learning*, 2019.

Carlo D'Eramo, Davide Tateo, Andrea Bonarini, Marcello Restelli, and Jan Peters. Sharing knowledge in multi-task deep reinforcement learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rkgpv2VFvr.

Aniket Anand Deshmukh, Urun Dogan, and Clay Scott. Multi-task learning for contextual bandits. In *Advances in neural information processing systems*, pp. 4848–4856, 2017.

Simon S Du, Wei Hu, Sham M Kakade, Jason D Lee, and Qi Lei. Few-shot learning via learning the representation, provably. *arXiv preprint arXiv:2002.09434*, 2020.

Kai Wang Fang. *Symmetric multivariate and related distributions*. CRC Press, 2018.

Chelsea Finn, Aravind Rajeswaran, Sham Kakade, and Sergey Levine. Online meta-learning. In *Proceedings of the 36th International Conference on Machine Learning*, 2019.

Tomer Galanti, Lior Wolf, and Tamir Hazan. A theoretical framework for deep transfer learning. *Information and Inference: A Journal of the IMA*, 5(2):159–209, 2016.

Zijun Gao, Yanjun Han, Zhimei Ren, and Zhengqing Zhou. Batched multi-armed bandits problem. In *Advances in Neural Information Processing Systems*, pp. 503–513, 2019.

Yanjun Han, Zhengqing Zhou, Zhengyuan Zhou, Jose Blanchet, Peter W Glynn, and Yinyu Ye. Sequential batch learning in finite-action linear contextual bandits. *arXiv preprint arXiv:2004.06321*, 2020.

Matteo Hessel, Hubert Soyer, Lasse Espeholt, Wojciech Czarnecki, Simon Schmitt, and Hado van Hasselt. Multi-task deep reinforcement learning with popart. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 3796–3803, 2019.

Irina Higgins, Arka Pal, Andrei Rusu, Loic Matthey, Christopher Burgess, Alexander Pritzel, Matthew Botvinick, Charles Blundell, and Alexander Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1480–1490. JMLR. org, 2017.

Kwang-Sung Jun, Rebecca Willett, Stephen Wright, and Robert Nowak. Bilinear bandits with low-rank structure. In *International Conference on Machine Learning*, pp. 3163–3172, 2019.

Mikhail Khodak, Maria-Florina Balcan, and Ameet Talwalkar. Adaptive gradient-based meta-learning methods. *arXiv preprint arXiv:1906.02717*, 2019.

Alessandro Lazaric and Marcello Restelli. Transfer from multiple mdps. In *Advances in Neural Information Processing Systems*, pp. 1746–1754, 2011.

Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 10657–10665, 2019.

Lihong Li, Yu Lu, and Dengyong Zhou. Provably optimal algorithms for generalized linear contextual bandits. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2071–2080. JMLR.org, 2017.

Yingkai Li, Yining Wang, and Yuan Zhou. Nearly minimax-optimal regret for linearly parameterized bandits. In *Conference on Learning Theory*, pp. 2173–2174, 2019a.

Yingkai Li, Yining Wang, and Yuan Zhou. Tight regret bounds for infinite-armed linear contextual bandits. *arXiv preprint arXiv:1905.01435*, 2019b.

Lydia T Liu, Urun Dogan, and Katja Hofmann. Decoding multitask dqn in the world of minecraft. In *The 13th European Workshop on Reinforcement Learning (EWRL) 2016*, 2016.

Yangyi Lu, Amirhossein Meisami, and Ambuj Tewari. Low-rank generalized linear bandit problems. *arXiv preprint arXiv:2006.02948*, 2020.

Andreas Maurer. Bounds for linear multi-task learning. *Journal of Machine Learning Research*, 7 (Jan):117–139, 2006.

Andreas Maurer, Massimiliano Pontil, and Bernardino Romera-Paredes. The benefit of multitask representation learning. *The Journal of Machine Learning Research*, 17(1):2853–2884, 2016.

Daniel McNamara and Maria-Florina Balcan. Risk bounds for transferring representations with and without fine-tuning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2373–2381. JMLR. org, 2017.

Emilio Parisotto, Jimmy Lei Ba, and Ruslan Salakhutdinov. Actor-mimic: Deep multitask and transfer reinforcement learning. *arXiv preprint arXiv:1511.06342*, 2015.

Aniruddh Raghu, Maithra Raghu, Samy Bengio, and Oriol Vinyals. Rapid learning or feature reuse? towards understanding the effectiveness of maml. *arXiv preprint arXiv:1909.09157*, 2019.

Yufei Ruan, Jiaqi Yang, and Yuan Zhou. Linear bandits with limited adaptivity and learning distributional optimal design. *arXiv preprint arXiv:2007.01980*, 2020.

Paat Rusmevichientong and John N Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

Andrei A Rusu, Sergio Gomez Colmenarejo, Caglar Gulcehre, Guillaume Desjardins, James Kirkpatrick, Razvan Pascanu, Volodymyr Mnih, Koray Kavukcuoglu, and Raia Hadsell. Policy distillation. *arXiv preprint arXiv:1511.06295*, 2015.

Tom Schaul and Jürgen Schmidhuber. Metalearning. *Scholarpedia*, 5(6):4650, 2010.

David Simchi-Levi and Yunzong Xu. Phase transitions and cyclic phenomena in bandits with switching constraints. In *Advances in Neural Information Processing Systems*, pp. 7523–7532, 2019.

Marta Soare, Ouais Alsharif, Alessandro Lazaric, and Joelle Pineau. Multi-task linear bandits. 2018.

Matthew E Taylor and Peter Stone. Transfer learning for reinforcement learning domains: A survey. *Journal of Machine Learning Research*, 10(Jul):1633–1685, 2009.

Yee Teh, Victor Bapst, Wojciech M Czarnecki, John Quan, James Kirkpatrick, Raia Hadsell, Nicolas Heess, and Razvan Pascanu. Distral: Robust multitask reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 4496–4506, 2017.

Nilesh Tripuraneni, Chi Jin, and Michael I Jordan. Provable meta-learning of linear representations. *arXiv preprint arXiv:2002.11684*, 2020.

Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*, volume 47. Cambridge university press, 2018.

Zirui Wang, Zihang Dai, Barnabás Póczos, and Jaime Carbonell. Characterizing and avoiding negative transfer. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 11293–11302, 2019.

A PROOF OF THEOREM 1

Lemma 1 (General Hoeffding's inequality, Vershynin (2018), Theorem 2.6.2). *Let $X_1, \ldots, X_n$ be independent random variables such that $\mathbb{E}[X_i] = 0$ and X_i is σ_i-sub-Gaussian. Then there exists a constant $c > 0$, such that for any $\delta > 0$, we have*

$$\Pr\left[\left|\sum_{i=1}^{n} X_i\right| \geq c\sqrt{\sum_{i=1}^{n} \sigma_i^2 \log(1/\delta)}\right] \leq \delta. \tag{3}$$

Lemma 2. *Let T be the number of tasks and N be the number of samples. For every $(n, t) \in [N] \times [T]$, let $\boldsymbol{x}_{n,t} \in \mathbb{R}^d$ be a fixed vector and let $y_{n,t} = \boldsymbol{x}_{n,t}^\top \boldsymbol{\theta}_t + \varepsilon_{n,t}$, where $\boldsymbol{\theta}_t \in \mathbb{R}^d$ is a vector and $\varepsilon_{n,t}$ is an independent 1-sub-Gaussian variable. Let*

$$\widehat{\boldsymbol{B}}\widehat{\boldsymbol{W}} = \operatorname*{arg\,min}_{\widehat{\boldsymbol{B}} \in \mathbb{R}^{d \times k}, \widehat{\boldsymbol{W}} \in \mathbb{R}^{k \times T}} \sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - y_{n,t}]^2, \tag{4}$$

where $\widehat{\boldsymbol{W}} = (\widehat{\boldsymbol{w}}_1 \quad \cdots \quad \widehat{\boldsymbol{w}}_T)$. Then with probability $1 - \delta$, we have

$$\sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{B}\boldsymbol{w}_t)]^2 \lesssim (dk + kT)\log(NTdk) + \log(1/\delta).$$

Proof. By (4), we have

$$\sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - y_{n,t}]^2 \leq \sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top \boldsymbol{B}\boldsymbol{w}_t - y_{n,t}]^2.$$

Since $y_{n,t} = \boldsymbol{x}_{n,t}^\top \boldsymbol{B}\boldsymbol{w}_t + \varepsilon_{n,t}$, we have

$$\sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{B}\boldsymbol{w}_t) + \varepsilon_{n,t}]^2 \leq \sum_{n=1}^{N} \sum_{t=1}^{T} \varepsilon_{n,t}^2,$$

which implies

$$\sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{B}\boldsymbol{w}_t)]^2 \leq \sum_{n=1}^{N} \sum_{t=1}^{T} 2\varepsilon_{n,t}\boldsymbol{x}_{n,t}^\top (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{B}\boldsymbol{w}_t). \tag{5}$$

Next we bound the right-hand side of (5) via a uniform concentration argument. We let

$$\mathcal{B} = \{\boldsymbol{B}' \in \mathbb{R}^{d \times k} : \|\boldsymbol{B}'\|_{\max} \leq 1\}, \qquad \mathcal{W} = \{\boldsymbol{W}' \in \mathbb{R}^{k \times T} : \|\boldsymbol{W}'\|_{\max} \leq 1\}.$$

For any fixed matrices $\boldsymbol{B}' \in \mathcal{B}, \boldsymbol{W}' \in \mathcal{W}$, we write $\boldsymbol{W}' = (\boldsymbol{w}'_1 \quad \cdots \quad \boldsymbol{w}'_T)$ and define

$$\eta_{n,t}(\boldsymbol{B}', \boldsymbol{W}') = 2\varepsilon_{n,t}\boldsymbol{x}_{n,t}^\top (\boldsymbol{B}'\boldsymbol{w}'_t - \boldsymbol{B}\boldsymbol{w}_t).$$

Note that $\eta_{n,t}(\boldsymbol{B}', \boldsymbol{W}')$ is an independent sub-Gaussian variable with sub-Gaussian norm $2\boldsymbol{x}_{n,t}^\top (\boldsymbol{B}'\boldsymbol{w}'_t - \boldsymbol{B}\boldsymbol{w}_t)$. By the general Hoeffding's inequality (Lemma 1), with probability $1 - \delta$, we have

$$\sum_{n=1}^{N} \sum_{t=1}^{T} \eta_{n,t}(\boldsymbol{B}', \boldsymbol{W}') \lesssim \sqrt{f(\boldsymbol{B}', \boldsymbol{W}')\log(1/\delta)}, \tag{6}$$

$$\text{where } f(\boldsymbol{B}', \boldsymbol{W}') = \sum_{n=1}^{N} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t}^\top (\boldsymbol{B}'\boldsymbol{w}'_t - \boldsymbol{B}\boldsymbol{w}_t)]^2.$$

Next we apply the ϵ-net. Let $\mathcal{B}' = \mathcal{N}(\mathcal{B}, \|\cdot\|_{\max}, \epsilon), \mathcal{W}' = \mathcal{N}(\mathcal{W}, \|\cdot\|_{\max}, \epsilon)$. Applying an union bound over $\mathcal{B}' \times \mathcal{W}'$ for (6), we have

$$\Pr\left[\forall (\boldsymbol{B}', \boldsymbol{W}') \in \mathcal{B}' \times \mathcal{W}' : \sum_{n=1}^{N} \sum_{t=1}^{T} \eta_{n,t} \lesssim \sqrt{f(\boldsymbol{B}', \boldsymbol{W}')\log(1/\delta)}\right] \geq 1 - \delta|\mathcal{B}' \times \mathcal{W}'|.$$

Since $f(\boldsymbol{B}', \boldsymbol{W}')$ is $(3NTdk)$-Lipschitz with respect to $\|\cdot\|_{\max}$, we have

$$\Pr\left[\forall (\boldsymbol{B}', \boldsymbol{W}') \in \mathcal{B} \times \mathcal{W} : \sum_{n=1}^{N} \sum_{t=1}^{T} \eta_{n,t} \lesssim \sqrt{f(\boldsymbol{B}', \boldsymbol{W}') \log(1/\delta)} + 24NTdk\epsilon\right] \geq 1 - \delta|\mathcal{B}' \times \mathcal{W}'|.$$

Note that $|\mathcal{B}'| = O((1/\epsilon)^{dk})$ and $|\mathcal{W}'| = O((1/\epsilon)^{kT})$. Let $\delta = \delta_0/|\mathcal{B}' \times \mathcal{W}'|$ and $\epsilon = (24NTdk)^{-1}$. We have

$$\Pr\left[\forall (\boldsymbol{B}', \boldsymbol{W}') \in \mathcal{B} \times \mathcal{W} : \sum_{n=1}^{N} \sum_{t=1}^{T} \eta_{n,t} \lesssim \sqrt{f(\boldsymbol{B}', \boldsymbol{W}')[(dk + kT)\log(NTdk) + \log(1/\delta_0)]}\right] \geq 1 - \delta_0. \tag{7}$$

Now we assume that the above event holds. Combining (5) and (7), we have

$$\Pr\left[\sqrt{f(\widehat{\boldsymbol{B}}, \widehat{\boldsymbol{W}})} \lesssim \sqrt{(dk + kT)\log(NTdk) + \log(1/\delta_0)}\right]$$

$$= \Pr\left[f(\widehat{\boldsymbol{B}}, \widehat{\boldsymbol{W}}) \lesssim \sqrt{f(\widehat{\boldsymbol{B}}, \widehat{\boldsymbol{W}})[(dk + kT)\log(NTdk) + \log(1/\delta_0)]}\right]$$

$$\geq 1 - \delta_0,$$

which proves our lemma. $\qquad\square$

Lemma 3. *With probability* $1 - O((NT)^{-2})$, *for every* $m \in [M], t \in [T]$, *we have*

$$\lambda_{\min}\left(\sum_{n=\mathcal{G}_{m-1}+1}^{\mathcal{G}_m} \boldsymbol{x}_{n,t,a_{n,t}} \boldsymbol{x}_{n,t,a_{n,t}}^\top\right) \gtrsim \frac{\mathcal{G}_m - \mathcal{G}_{m-1}}{d}.$$

Proof. The proof can be done by following the proof of Lemma 4 in (Han et al., 2020). $\qquad\square$

Lemma 4. *For each* $m \in [M]$, *with probability* $1 - O((NT^{-2}))$, *we have*

$$\left\|\widehat{\boldsymbol{B}}\widehat{\boldsymbol{W}} - \boldsymbol{BW}\right\|_F^2 \lesssim \frac{(dk + kT)\log(NTdk) + \log(1/\delta)}{(\mathcal{G}_m - \mathcal{G}_{m-1})/d}.$$

Proof. By Lemma 2, with probability $1 - O((NT)^{-2})$, we have

$$\sum_{n=\mathcal{G}_{m-1}}^{\mathcal{G}_m} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t,a_{n,t}}^\top (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{Bw}_t)]^2 \lesssim (dk + kT)\log(NTdk). \tag{8}$$

By Lemma 3, with probability $1 - O((NT)^{-2})$, we have

$$\sum_{n=\mathcal{G}_{m-1}}^{\mathcal{G}_m} \sum_{t=1}^{T} [\boldsymbol{x}_{n,t,a_{n,t}}^\top (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{Bw}_t)]^2$$

$$= \sum_{t=1}^{T} (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{Bw}_t)^\top \left(\sum_{n=\mathcal{G}_{m-1}}^{\mathcal{G}_m} \boldsymbol{x}_{n,t,a_{n,t}} \boldsymbol{x}_{n,t,a_{n,t}}^\top\right) (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{Bw}_t)$$

$$\gtrsim \sum_{t=1}^{T} (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{Bw}_t)^\top \frac{\mathcal{G}_m - \mathcal{G}_{m-1}}{d} (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - \boldsymbol{Bw}_t)$$

$$= \frac{\mathcal{G}_m - \mathcal{G}_{m-1}}{d} \left\|\widehat{\boldsymbol{B}}\widehat{\boldsymbol{W}} - \boldsymbol{BW}\right\|_F^2. \tag{9}$$

We conclude by combining (9) with (8). $\qquad\square$

Let

$$R_m = \sum_{n=1}^{N} \sum_{t=1}^{T} \max_{a \in [K]} \langle \boldsymbol{x}_{n,t,a}, \boldsymbol{\theta}_t \rangle - \langle \boldsymbol{x}_{n,t,a_{n,t}}, \boldsymbol{\theta}_t \rangle$$

be the regret incurred in the m-th epoch. We have the following lemma.

Lemma 5. *We have*

$$\mathbb{E}[R_m] \lesssim (\sqrt{NTdk} + T\sqrt{kN})\sqrt{\log(NTdk)\log(NKT)}.$$

Proof. At round n, for task t, we have

$$\max_{a \in [K]} \boldsymbol{\theta}_t^\top (\boldsymbol{x}_{n,t,a} - \boldsymbol{x}_{n,t,a_{n,t}}) \leq \max_{a \in [K]} \{\boldsymbol{\theta}_t^\top (\boldsymbol{x}_{n,t,a} - \boldsymbol{x}_{n,t,a_{n,t}}) + \widehat{\boldsymbol{\theta}}_t^\top (\boldsymbol{x}_{n,t,a_{n,t}} - \boldsymbol{x}_{n,t,a})\}$$

$$= \max_{a \in [K]} (\boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t)^\top \boldsymbol{x}_{n,t,a} + (\widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t)^\top \boldsymbol{x}_{n,t,a_{n,t}}$$

$$\leq 2 \max_{a \in [K]} \left|(\boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t)^\top \boldsymbol{x}_{n,t,a}\right|.$$

By Assumption 2 and a union bound over K actions, we have with probability $1 - (NKT)^{-2}$,

$$\max_{a \in [K]} \left|(\boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t)^\top \boldsymbol{x}_{n,t,a}\right| \lesssim \left\|\boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\right\| \sqrt{\frac{\log(NKT)}{d}}.$$

Therefore, the regret incurred in the m-th epoch is

$$\mathbb{E}[R_m] \lesssim \sum_{n=\mathcal{G}_{m-1}+1}^{\mathcal{G}_m} \sum_{t=1}^{T} \max_{a \in [K]} \boldsymbol{\theta}_t^\top (\boldsymbol{x}_{n,t,a} - \boldsymbol{x}_{n,t,a_{n,t}})$$

$$\lesssim \mathcal{G}_m \sum_{t=1}^{T} \left\|\boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\right\| \sqrt{\frac{\log(NKT)}{d}} \leq \mathcal{G}_m \sqrt{T} \left\|\widehat{\boldsymbol{\Theta}} - \boldsymbol{\Theta}\right\|_F \sqrt{\frac{\log(NKT)}{d}}$$

$$\leq \mathcal{G}_m \sqrt{T} \sqrt{\frac{(dk + kT)\log(NTdk)}{\mathcal{G}_{m-1}/d}} \sqrt{\frac{\log(NKT)}{d}}$$

$$\leq \sqrt{NT(dk + kT)\log(NTdk)\log(NKT)}$$

$$\lesssim (\sqrt{NTdk} + T\sqrt{kN})\sqrt{\log(NTdk)\log(NKT)}. \qquad \square$$

Proof of Theorem 1. The regret is bounded by

$$\mathbb{E}[R^{N,T}] = \sum_{m=1}^{M} \mathbb{E}[R_m] \lesssim M(\sqrt{NTdk} + T\sqrt{kN})\sqrt{\log(NTdk)\log(NKT)}$$

$$= (\sqrt{NTdk} + T\sqrt{kN})\sqrt{\log(NTdk)\log(NKT)} \log\log N. \qquad \square$$

B   PROOF OF THEOREM 2

In this appendix, we assume that $\Sigma_t = \boldsymbol{I}$ in Assumption 2 and that all noises are gaussian, i.e. $\varepsilon_{n,t} \sim \mathcal{N}(0, 1)$ for all $n \in [N], t \in [T]$.

For each task $t \in [T]$, we denote the regret incurred on task t as

$$R^{N,(t)} = \sum_{n=1}^{N} \max_{a \in [K]} \langle \boldsymbol{x}_{n,t,a}, \boldsymbol{\theta}_t \rangle - \langle \boldsymbol{x}_{n,t,a_{n,t}}, \boldsymbol{\theta}_t \rangle.$$

We divide Theorem 2 into the following two lemmas.

Lemma 6. *Under the setting of Theorem 2, we have* $\inf_{\mathcal{A}} \sup_{\mathcal{I}} \mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N;T}] \geq \Omega(T\sqrt{kN})$.

Lemma 7. *Under the setting of Theorem 2, we have* $\inf_{\mathcal{A}} \sup_{\mathcal{I}} \mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N;T}] \geq \Omega(\sqrt{dkNT})$.

Proof of Theorem 2. We combine Lemma 6 and Lemma 7. $\qquad \square$

Our proofs to the lemmas will be based on the lower bounds for the (single-task) linear bandit setting, which corresponds to the $T = 1$ case in our multi-task setting. For this single-task setting, we assume $k = d$ and $\boldsymbol{B} = \boldsymbol{I}_d$. We write the regret as $R^N = R^{N,1}$ and call algorithms for the single-task setting as single-task algorithms.

Lemma 8 (Han et al. (2020), Theorem 2). *Assume $N \geq d^2$ and $d \geq 2$. Let $\mathcal{N}(\mu, \Sigma)$ be the multivariate normal distribution with mean μ and covariance matrix Σ. There is a constant $C > 0$, such that for any single-task algorithm $\mathcal{S}$, we have*

$$\sup_{\|\boldsymbol{w}\| \leq 1} \mathbb{E}[R^N_{\mathcal{S}, \mathcal{I}}] \geq C\sqrt{dN},$$

where $\mathcal{I}$ is the instance with hidden linear coefficients $\boldsymbol{w}$.

Next we use it to prove Lemma 6 and Lemma 7. The main idea to prove Lemma 6 is to note that we can treat our setting as T independent k-dimensional linear bandits.

Proof of Lemma 6. Suppose there is an algorithm $\mathcal{A}$ that achieves $\sup_{\mathcal{I}} \mathbb{E}[R^{N,T}_{\mathcal{A}, \mathcal{I}}] \leq CT\sqrt{kN}$. Then we have

$$\sup_{\|\boldsymbol{w}_t\| \leq 1} \mathbb{E}\left[\sum_{t=1}^{T} R^{N,(t)}_{\mathcal{A}, \mathcal{I}}\right] \leq \sup_{\mathcal{I}} \mathbb{E}[R^{N,T}_{\mathcal{A}, \mathcal{I}}] \leq CT\sqrt{kN}.$$

Therefore, there exists $t \in [T]$ such that

$$\sup_{\mathcal{I}} \mathbb{E}[R^{N,(t)}_{\mathcal{A}, \mathcal{I}}] \leq \frac{1}{T}CT\sqrt{kN} = C\sqrt{kN},$$

which contradicts Lemma 8. $\qquad \square$

Proof of Lemma 7. Suppose there is an algorithm $\mathcal{A}$ that achieves $\sup_{\mathcal{I}} \mathbb{E}[R^{N,T}_{\mathcal{A}, \mathcal{I}}] \leq C\sqrt{dkNT}$. We complete the proof separately, based on whether $k \leq \frac{d}{2}$ or not. Note that when $k > \frac{d}{2}$, the lower bound in Lemma 6 becomes $\Omega(T\sqrt{kN}) = \Omega(T\sqrt{dN})$. Since $T \geq k$, we have $\sqrt{dkTN} \lesssim T\sqrt{dN}$. Thus we conclude by Lemma 6.

In the remaining, we assume $k \leq \frac{d}{2}$. Without loss of generality, we assume that d is even and that $2k$ divides T. For $i = 1, \ldots, k$, we denote the regret of group i as

$$R^{N,((i))}_{\mathcal{A}, \mathcal{I}} = \sum_{t=(i-1)T/k+1}^{iT/k} R^{N,(t)}_{\mathcal{A}, \mathcal{I}}.$$

We consider instances such that tasks from the same group share the same hidden linear coefficients $\boldsymbol{\theta}_t$. Since there are k groups, we have

$$\sup_{\|\boldsymbol{\theta}_t\| \leq 1} \mathbb{E}\left[\sum_{i=1}^{k} R^{N,((i))}_{\mathcal{A}, \mathcal{I}}\right] \leq \sup_{\mathcal{I}} \mathbb{E}[R^{N,T}_{\mathcal{A}, \mathcal{I}}] \leq C\sqrt{dkNT}. \tag{10}$$

Therefore, there exists a group $i \in [k]$ such that

$$\sup_{\mathcal{I}_i} \mathbb{E}[R^{N,((i))}_{\mathcal{A}, \mathcal{I}}] \leq \frac{1}{k}C\sqrt{dkNT} = C\sqrt{\frac{dNT}{k}}, \tag{11}$$

which means that the regret incurred in group i is less than $C\sqrt{dNT/k}$. Since the tasks in group i share the same hidden linear coefficients, they could be regarded as one large linear bandit problem. Since there are T/k tasks in group i, the large linear bandit is played for $N \cdot T/k$ rounds. By Lemma 8, the algorithm $\mathcal{A}$ must have incurred $C\sqrt{dNT/k}$ regret on group i, which contradicts with (11). $\qquad \square$

C   METHOD-OF-MOMENTS ESTIMATOR UNDER BANDIT SETTING

The following theorem shows the guarantee of the method-of-moments (MoM) estimator we used to find the linear feature extractor $\boldsymbol{B}$. In this appendix, for a matrix $\boldsymbol{B}$ with orthogonal columns, we write $\boldsymbol{B}_\perp$ to denote its orthogonal complement matrix (a matrix whose columns are the orthogonal complement of those of $\boldsymbol{B}$).

Theorem 5 (MoM Estimator). *Assume $N_1 T \gtrsim \text{polylog}(N_1, T) \cdot \frac{d^{1.5}k}{\lambda_0 \nu}$. We have with probability at least $1 - (N_1 T)^{-100}$,*

$$\left\| \widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B} \right\| \lesssim \widetilde{O}\left(\frac{d^{1.5}k}{\lambda_0 \nu \sqrt{N_1 T}} \right). \tag{12}$$

The theorem guarantees that our estimated $\widehat{\boldsymbol{B}}$ is close to the underlying $\boldsymbol{B}$ in the operator norm so long as the values N_1 and T are sufficiently large. We add a remark that our theorem is similar to Theorem 3 in Tripuraneni et al. (2020). The key differences are: (i) we use a uniform distribution to find the feature extractor, while they assumed the input distribution is standard d-dimensional Gaussian; (ii) the SNR (signal-to-noise ratio) in our linear bandit setting is worse than that in their supervised learning setting, and thus we get an extra d factor in our theorem.

In the sequel, we prove the theorem.

Lemma 9 (Hoeffding). *Let $\varepsilon_1, \ldots, \varepsilon_N$ be i.i.d. 1-sub-Gaussian random variables. We have*

$$\Pr\left[\left| \frac{1}{N} \sum_{i=1}^N (\varepsilon_i - \mathbb{E}\, \varepsilon_i) \right| \geq t \right] \leq 2 e^{-\frac{t^2}{2N}}.$$

Lemma 10 (Matrix Bernstein's inequality, Vershynin (2018), Theorem 5.4.1). *Let $\boldsymbol{X}_1, \ldots, \boldsymbol{X}_m \in \mathbb{R}^{d \times d}$ be independent, mean zero, symmetric random matrices that $\|\boldsymbol{X}_i\| \leq M$ almost surely for all $i \in [m]$. Let $\sigma^2 = \left\| \sum_{i=1}^m \mathbb{E}\, \boldsymbol{X}_i^2 \right\|$. We have*

$$\Pr\left[\left\| \sum_{i=1}^m \boldsymbol{X}_i \right\| \geq \delta \right] \leq 2d \exp\left(-\frac{\delta^2/2}{\sigma^2 + M\delta/3} \right).$$

Equivalently, with probability at least $1 - \delta$, we have

$$\left\| \sum_{i=1}^m \boldsymbol{X}_i \right\| \lesssim \sqrt{\sigma^2 \log(d/\delta)} + M \log(d/\delta).$$

Lemma 11 (Moments of Uniform Distribution on Sphere). *Let $\boldsymbol{x} \sim \text{Unif}(\mathbb{S}^{d-1})$ be a uniformly chosen unit vector. We have $\mathbb{E}\, x_1^6 = \frac{15}{d(d+2)(d+4)}$, $\mathbb{E}\, x_1^4 = \frac{3}{d(d+2)}$, $\mathbb{E}\, x_1^2 = \frac{1}{d}$. Moreover, we have $\mathbb{E}\, x_1^4 x_2^2 = \frac{3}{d(d+2)(d+4)}$.*

Proof. We need to recall the fact that when $\boldsymbol{x} \sim \text{Unif}(\mathbb{S}^{d-1})$, its coordinate x_i follows the Beta distribution: $\frac{x_1+1}{2} \sim \text{Beta}(\frac{d-1}{2}, \frac{d-1}{2})$. Then we prove the lemma by noting the moments of the Beta distribution (Fang, 2018). $\square$

Corollary 6 (Uniform Distribution on Sphere). *Let $x \sim \text{Unif}(\mathbb{S}^{d-1})$ be a uniformly chosen unit vector. We have the following statements.*

(a) $\mathbb{E}\, \langle \boldsymbol{x}, \boldsymbol{\theta} \rangle^2 \boldsymbol{x}\boldsymbol{x}^\top = \frac{2\boldsymbol{\theta}\boldsymbol{\theta}^\top + \boldsymbol{I}}{d(d+2)}$.
(b) $\mathbb{E}\, \langle \boldsymbol{x}, \boldsymbol{\theta} \rangle^4 \boldsymbol{x}\boldsymbol{x}^\top = \frac{12\boldsymbol{\theta}\boldsymbol{\theta}^\top + 3\boldsymbol{I}}{d(d+2)(d+4)}$.

Proof. Let $\boldsymbol{e}_1 = (1, 0, \ldots, 0) \in \mathbb{R}^d$ be the unit vector. For (a), note that

$$(\mathbb{E}\, \langle \boldsymbol{x}, \boldsymbol{e}_1 \rangle^2 \boldsymbol{x}\boldsymbol{x}^\top)_{ij} = \mathbb{E}\, x_1^2 x_i x_j = \begin{cases} 0, & i, j \neq 1 \text{ and } i \neq j, \\ 0, & i = 1 \neq j \text{ or } j = 1 \neq i, \\ \frac{1}{d(d+2)}, & i = j \neq 1, \\ \frac{3}{d(d+2)}, & i = j = 1. \end{cases}$$

Therefore, we have $\mathbb{E}[\langle \boldsymbol{x}, \boldsymbol{e}_1 \rangle^2 \boldsymbol{x}\boldsymbol{x}^\top] = \frac{1}{d(d+2)}(2\boldsymbol{e}_1\boldsymbol{e}_1^\top + \boldsymbol{I})$. By the isotropy (rotation invariance) of uniform distribution, we have

$$\mathbb{E} \langle \boldsymbol{x}, \boldsymbol{\theta} \rangle^2 \boldsymbol{x}\boldsymbol{x}^\top = \frac{1}{d(d+2)}(2\boldsymbol{\theta}\boldsymbol{\theta}^\top + \boldsymbol{I}).$$

For (b), note that

$$(\mathbb{E} \langle \boldsymbol{x}, \boldsymbol{e}_1 \rangle^4 \boldsymbol{x}\boldsymbol{x}^\top)_{ij} = \mathbb{E} x_1^4 x_i x_j = \begin{cases} 0, & i, j \neq 1 \text{ and } i \neq j, \\ 0, & i = 1 \neq j \text{ or } j = 1 \neq i, \\ \frac{3}{d(d+2)(d+4)}, & i = j \neq 1, \\ \frac{15}{d(d+2)(d+4)}, & i = j = 1. \end{cases}$$

Therefore, we have $\mathbb{E} \langle \boldsymbol{x}, \boldsymbol{e}_1 \rangle^4 \boldsymbol{x}\boldsymbol{x}^\top = \frac{1}{d(d+2)(d+4)}(12\boldsymbol{e}_1\boldsymbol{e}_1^\top + 3\boldsymbol{I})$. By the isotropy, we have

$$\mathbb{E} \langle \boldsymbol{x}, \boldsymbol{\theta} \rangle^4 \boldsymbol{x}\boldsymbol{x}^\top = \frac{1}{d(d+2)(d+4)}(12\boldsymbol{\theta}\boldsymbol{\theta}^\top + 3\boldsymbol{I}). \qquad \square$$

Let $\boldsymbol{A}_{n,t} = r_{n,t}^2 x_{n,t} x_{n,t}^\top$, $\boldsymbol{M} = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} \boldsymbol{A}_{n,t}$. We decompose $\boldsymbol{M}$ into three terms $\boldsymbol{M} = \boldsymbol{M}_1 + \boldsymbol{M}_2 + \boldsymbol{M}_3$, where

$$\boldsymbol{M}_1 = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} \langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle^2 \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top,$$

$$\boldsymbol{M}_2 = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} 2\varepsilon_{n,t} \langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top,$$

$$\boldsymbol{M}_3 = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} \varepsilon_{n,t}^2 \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top.$$

Let $\boldsymbol{A}_{1nt} = \frac{1}{N_1 T} \langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle^2 \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top$. Next we analyze each error $\|\boldsymbol{M}_i - \mathbb{E} \boldsymbol{M}_i\|$.

Lemma 12. *With probability at least* $1 - \frac{1}{N_1^3 T^3}$*, we have*

$$\|\boldsymbol{M}_1 - \mathbb{E} \boldsymbol{M}_1\| \lesssim \sqrt{\frac{\log(dN_1 T)}{d^3 N_1 T}} + \frac{\log(dN_1 T)}{N_1 T}.$$

Proof. We have

$$\mathbb{E} \boldsymbol{A}_{1nt}^2 = \frac{1}{N_1^2 T^2} \mathbb{E} \langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle^4 \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top = \frac{12\boldsymbol{\theta}_t\boldsymbol{\theta}_t^\top + 3\boldsymbol{I}}{d(d+2)(d+4)N_1^2 T^2}.$$

Using Lemma 10 with $m = N_1 T, M = \frac{1}{N_1 T}, \sigma^2 \lesssim m \cdot \frac{1}{d^3 N_1^2 T^2} = \frac{1}{d^3 N_1 T}$, we have with probability at least $1 - \frac{1}{N_1^3 T^3}$,

$$\|\boldsymbol{M}_1 - \mathbb{E} \boldsymbol{M}_1\| \lesssim \sqrt{\frac{\log(dN_1 T)}{d^3 N_1 T}} + \frac{\log(dN_1 T)}{N_1 T}. \qquad \square$$

Next we analyze the errors of $\boldsymbol{M}_2$ and $\boldsymbol{M}_3$. Since these errors contain the unbounded sub-Gaussian terms $\varepsilon_{n,t}$, we need to cut their tails before applying the matrix Bernstein inequality. Define $\varepsilon'_{n,t} = \varepsilon_{n,t} \mathbb{I}\{|\varepsilon_{n,t}| \leq R\}$. We have

$$\begin{aligned} \left|\mathbb{E} \varepsilon_{n,t} - \mathbb{E} \varepsilon'_{n,t}\right| &\leq \mathbb{E} |\varepsilon_{n,t}| \mathbb{I}\{|\varepsilon_{n,t}| > R\} \\ &= R \cdot \Pr[|\varepsilon_{n,t}| > R] + \int_R^{+\infty} \Pr[|\varepsilon_{n,t}| > x] \, dx \\ &\leq 2Re^{-\frac{R^2}{2}} + \int_R^{+\infty} 2e^{-\frac{x^2}{2}} \, dx \\ &\leq 2(R + \frac{1}{R})e^{-\frac{R^2}{2}}. \end{aligned}$$

Let $\varepsilon_{n,t}'' = \varepsilon_{n,t}^2 \, \mathbb{I}\{|\varepsilon_{n,t}| \le R\}$. We have

$$
\begin{aligned}
\left| \mathbb{E}\, \varepsilon_{n,t}^2 - \mathbb{E}\, \varepsilon_{n,t}'' \right| &\le \mathbb{E}\, \varepsilon_{n,t}^2 \, \mathbb{I}\{\varepsilon_{n,t}^2 > R^2\} \\
&= R^2 \cdot \Pr\left[\varepsilon_{n,t}^2 > R^2\right] + \int_{R^2}^{+\infty} \Pr\left(\varepsilon_{n,t}^2 > x\right) \mathrm{d}d\,x \\
&\le 2R^2 e^{-\frac{R^2}{2}} + \int_{R^2}^{+\infty} 2 e^{-\frac{x}{2}} \, \mathrm{d}d\,x \\
&\le (2R^2 + 4) e^{-\frac{R^2}{2}}.
\end{aligned}
$$

Define

$$
\boldsymbol{M}_2' = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} 2\varepsilon_{n,t}' \langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top,
$$

$$
\boldsymbol{M}_3'' = \frac{1}{N_1 T} \sum_{n=1}^{N_1} \sum_{t=1}^{T} \varepsilon_{n,t}'' \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top.
$$

Lemma 13. *With probability at least $1 - (N_1 T)^{-3}$, we have*

$$
\|\boldsymbol{M}_2' - \mathbb{E}\, \boldsymbol{M}_2'\| \lesssim \sqrt{\frac{\log(d N_1 T)}{d^2 N_1 T}} + \frac{R \log(d N_1 T)}{N_1 T}.
$$

Proof. Let $\boldsymbol{A}_{2nt} = \frac{1}{N_1 T} 2\varepsilon_{n,t}' \langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top$. We find that

$$
\mathbb{E}\, \boldsymbol{A}_{2nt}^2 = \frac{4\,\mathbb{E}\,(\varepsilon_{n,t}')^2}{N_1^2 T^2} \mathbb{E}\,\langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle^2 \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top = \frac{4\,\mathbb{E}\,(\varepsilon_{n,t}')^2}{N_1^2 T^2} \frac{2\boldsymbol{\theta}_t \boldsymbol{\theta}_t^\top + \boldsymbol{I}}{d(d+2)}.
$$

We conclude by using [Lemma 10](#) with $m = N_1 T, M = \frac{R}{N_1 T}, \sigma^2 \lesssim m \cdot \frac{1}{d^2 N_1^2 T^2} = \frac{1}{d^2 N_1 T}$. $\qquad \square$

Lemma 14. *With probability at least $1 - (N_1 T)^{-3}$, we have*

$$
\|\boldsymbol{M}_3'' - \mathbb{E}\, \boldsymbol{M}_3''\| \lesssim \sqrt{\frac{\log(d N_1 T)}{d N_1 T}} + \frac{R^2 \log(d N_1 T)}{N_1 T}.
$$

Proof. Let $\boldsymbol{A}_{3nt} = \frac{1}{N_1 T} \varepsilon_{n,t}'' \boldsymbol{x}_{n,t} \boldsymbol{x}_{n,t}^\top$. We find that

$$
\mathbb{E}\, \boldsymbol{A}_{3nt}^2 = \frac{\mathbb{E}\,(\varepsilon_{n,t}'')^2}{N_1^2 T^2} \mathbb{E}\,\boldsymbol{x}_{n,t} x_{n,t}^\top = \frac{\mathbb{E}\,(\varepsilon_{n,t}'')^2}{N_1^2 T^2} \frac{\boldsymbol{I}}{d}.
$$

We conclude by using [Lemma 10](#) with $m = N_1 T, M = \frac{R^2}{N_1 T}, \sigma^2 \lesssim m \cdot \frac{1}{d N_1^2 T^2} = \frac{1}{d N_1 T}$. $\qquad \square$

Lemma 15. *With probability at least $1 - (N_1 T)^{-2}$, we have*

$$
\|\boldsymbol{M} - \mathbb{E}\, \boldsymbol{M}\| \lesssim \sqrt{\frac{\log(d N_1 T)}{d N_1 T}} + \frac{\log^2(d N_1 T)}{N_1 T}.
$$

Proof. Let $R = \sqrt{8 \log(N_1 T)}$. With probability at least $1 - (N_1 T)^{-3}$, we have $|\varepsilon_{n,t}| \le R$ for every $n \in [N_1]$ and $t \in [T]$. Note that in this case, we have $\boldsymbol{M}_2 = \boldsymbol{M}_2'$ and $\boldsymbol{M}_3 = \boldsymbol{M}_3''$. Using a union bound over [Lemma 12](#), [Lemma 13](#), and [Lemma 14](#), we have with probability at least $1 - (N_1 T)^{-2}$,

$$
\begin{aligned}
\|\boldsymbol{M} - \mathbb{E}\, \boldsymbol{M}\| &\le \|\boldsymbol{M}_1 - \mathbb{E}\, \boldsymbol{M}_1\| + \|\boldsymbol{M}_2 - \mathbb{E}\, \boldsymbol{M}_2\| + \|\boldsymbol{M}_3 - \mathbb{E}\, \boldsymbol{M}_3\| \\
&= \|\boldsymbol{M}_1 - \mathbb{E}\, \boldsymbol{M}_1| + \|\boldsymbol{M}_2' - \mathbb{E}\, \boldsymbol{M}_2\| + \|\boldsymbol{M}_3'' - \mathbb{E}\, \boldsymbol{M}_3\| \\
&\le \|\boldsymbol{M}_1 - \mathbb{E}\, \boldsymbol{M}_1\| + \|\boldsymbol{M}_2' - \mathbb{E}\, \boldsymbol{M}_2'\| + \|\mathbb{E}\, \boldsymbol{M}_2' - \mathbb{E}\, \boldsymbol{M}_2\| \\
&\quad + \|\boldsymbol{M}_3'' - \mathbb{E}\, \boldsymbol{M}_3''\| + \|\mathbb{E}\, \boldsymbol{M}_3'' - \mathbb{E}\, \boldsymbol{M}_3\| \\
&\lesssim \sqrt{\frac{\log(d N_1 T)}{d N_1 T}} + \frac{\log^2(d N_1 T)}{N_1 T}. \qquad \square
\end{aligned}
$$

Proof of Theorem 5. We note that $\sigma_{k+1}(\boldsymbol{M}) - \sigma_{k+1}(\mathbb{E}\,\boldsymbol{M}) \leq \|\mathbf{E}\|$. Under Assumption 3, we have

$$\mathbb{E}\,\boldsymbol{M}_1 = \frac{2\lambda_0}{d(d+2)T}\boldsymbol{\theta}\boldsymbol{\theta}^\top + c_1\mathbf{I}, \quad \mathbb{E}\,\boldsymbol{M}_2 = 0, \quad \mathbb{E}\,\boldsymbol{M}_3 = c_3\mathbf{I},$$

where $c_1, c_3 \in \mathbb{R}$ are constants. Since

$$\sigma_k(\frac{1}{T}\boldsymbol{\theta}\boldsymbol{\theta}^\top) - \sigma_{k+1}(\frac{1}{T}\boldsymbol{\theta}\boldsymbol{\theta}^\top) = \sigma_k(\frac{1}{T}\mathbf{W}\mathbf{W}^\top) = \frac{\nu}{k},$$

we have

$$\sigma_k(\mathbb{E}\,\boldsymbol{M}) - \sigma_{k+1}(\mathbb{E}\,\boldsymbol{M}) \asymp \frac{\lambda_0\nu}{d^2k}.$$

Assume $N_1 T \gtrsim \mathrm{polylog}(N_1, T) \cdot dk$ so that $\|\mathbf{E}\| \leq \frac{\lambda_0\nu}{d^2k}$. Together with Davis-Kahan sin $\boldsymbol{\theta}$ theorem, we have with probability at least $1 - (N_1 T)^{-100}$,

$$\|\widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\| \lesssim \frac{\|\widehat{\boldsymbol{B}}_\perp^\top \mathbf{E}\boldsymbol{B}\|}{\sigma_k(\mathbb{E}\,\boldsymbol{M}) - \sigma_{k+1}(\mathbb{E}\,\boldsymbol{M}) - \|\mathbf{E}\|} \tag{13}$$

$$\leq \frac{\|\mathbf{E}\|}{\sigma_k(\mathbb{E}\,\boldsymbol{M}) - \sigma_{k+1}(\mathbb{E}\,\boldsymbol{M}) - \|\mathbf{E}\|} \lesssim \frac{\|\mathbf{E}\|}{\lambda_0\nu/d^2k}$$

$$\lesssim \frac{d^2k}{\lambda_0\nu}\left(\sqrt{\frac{\log(dN_1T)}{dN_1T}} + \frac{\log^2(dN_1T)}{N_1T}\right) \lesssim \frac{d^{1.5}k}{\sqrt{N_1T}} \cdot \mathrm{polylog}(d, N, T),$$

where (13) uses the Davis-Kahan sin $\boldsymbol{\theta}$ theorem (Bhatia, 2013, Section VII.3). $\qquad\square$

D PROOF OF THEOREM 3

Our proof is similar to the proof of Theorem 3.1 of Rusmevichientong & Tsitsiklis (2010).

Lemma 16 (Rusmevichientong & Tsitsiklis (2010), Lemma 3.5). *For two vectors $\boldsymbol{u}, \boldsymbol{v} \in \mathbb{R}^d$, we have*

$$\left\|\frac{\boldsymbol{u}}{\|\boldsymbol{u}\|} - \frac{\boldsymbol{v}}{\|\boldsymbol{v}\|}\right\| \leq \frac{2\|\boldsymbol{u} - \boldsymbol{v}\|}{\max\{\|\boldsymbol{u}\|, \|\boldsymbol{v}\|\}}.$$

Lemma 17. *Let $x_t = \arg\max_{x \in \mathcal{A}_t}\langle x, \hat{\boldsymbol{\theta}}_t\rangle$. We have*

$$\max_{x \in \mathcal{A}_t}\langle x, \boldsymbol{\theta}_t\rangle - \langle x_t, \boldsymbol{\theta}_t\rangle \leq J\frac{\|\boldsymbol{\theta}_t - \hat{\boldsymbol{\theta}}_t\|^2}{\|\boldsymbol{\theta}_t\|}.$$

Proof. For $\boldsymbol{\theta} \in \mathbb{R}^d$, we define $f_t(\boldsymbol{\theta}) = \max_{\boldsymbol{a} \in \mathcal{A}_t}\langle \boldsymbol{a}, \boldsymbol{\theta}\rangle$. Let $\boldsymbol{x}_t^* = \arg\max_{\boldsymbol{x} \in \mathcal{A}_t}\langle \boldsymbol{x}, \boldsymbol{\theta}_t\rangle$. Then we have

$$\max_{\boldsymbol{x} \in \mathcal{A}_t}\langle \boldsymbol{x}, \boldsymbol{\theta}_t\rangle - \langle \boldsymbol{x}_t, \boldsymbol{\theta}_t\rangle = \langle \boldsymbol{x}_t^* - \boldsymbol{x}_t, \boldsymbol{\theta}_t\rangle = \langle \boldsymbol{x}_t^*, \boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\rangle + \langle \boldsymbol{x}_t^* - \boldsymbol{x}_t, \widehat{\boldsymbol{\theta}}_t\rangle + \langle \boldsymbol{x}_t, \widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t\rangle$$

$$\leq \langle \boldsymbol{x}_t^*, \boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\rangle + \langle \boldsymbol{x}_t, \widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t\rangle = \langle \boldsymbol{x}_t^* - \boldsymbol{x}_t, \boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\rangle$$

$$= \langle f_t(\boldsymbol{\theta}_t) - f_t(\widehat{\boldsymbol{\theta}}_t), \boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\rangle = \langle f_t(\frac{\boldsymbol{\theta}_t}{\|\boldsymbol{\theta}_t\|}) - f_t(\frac{\widehat{\boldsymbol{\theta}}_t}{\|\widehat{\boldsymbol{\theta}}_t\|}), \boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\rangle$$

$$\leq \|f_t(\frac{\boldsymbol{\theta}_t}{\|\boldsymbol{\theta}_t\|}) - f_t(\frac{\widehat{\boldsymbol{\theta}}_t}{\|\widehat{\boldsymbol{\theta}}_t\|})\| \cdot \|\boldsymbol{\theta}_t - \widehat{\boldsymbol{\theta}}_t\| \leq J\|\frac{\boldsymbol{\theta}_t}{\|\boldsymbol{\theta}_t\|} - \frac{\hat{\boldsymbol{\theta}}_t}{\|\hat{\boldsymbol{\theta}}_t\|}\| \cdot \|\boldsymbol{\theta}_t - \hat{\boldsymbol{\theta}}_t\| \tag{14}$$

$$\leq 2J\frac{\|\boldsymbol{\theta}_t - \hat{\boldsymbol{\theta}}_t\|^2}{\|\boldsymbol{\theta}_t\|}, \tag{15}$$

where the first inequality in (14) uses Cauchy and (15) uses Lemma 16. $\qquad\square$

Lemma 18. *For each task $t \in [T]$, we have $\mathbb{E}\|\widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t\|^2 \lesssim \frac{k^2}{\lambda_1^2 N_2} + \|\widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\|^2$.*

Proof. We define $\boldsymbol{\theta}_t' = \widehat{\boldsymbol{B}}\widehat{\boldsymbol{B}}^\top \boldsymbol{\theta}_t$. Note that $\boldsymbol{\theta}_t = \boldsymbol{\theta}_t' + \widehat{\boldsymbol{B}}_\perp \widehat{\boldsymbol{B}}_\perp^\top$. We have

$$\widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t = \widehat{\boldsymbol{B}}\widehat{\boldsymbol{w}}_t - (\widehat{\boldsymbol{B}}\widehat{\boldsymbol{B}}^\top \boldsymbol{\theta}_t + \widehat{\boldsymbol{B}}_\perp \widehat{\boldsymbol{B}}_\perp^\top)\boldsymbol{\theta}_t$$
$$= \widehat{\boldsymbol{B}}(\widehat{\boldsymbol{w}}_t - \widehat{\boldsymbol{B}}^\top \boldsymbol{\theta}_t) - \widehat{\boldsymbol{B}}_\perp \widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\boldsymbol{w}_t.$$

Note that $\widehat{\boldsymbol{B}}$ is perpendicular to $\widehat{\boldsymbol{B}}_\perp$ and that $\|\widehat{\boldsymbol{B}}\| = \|\widehat{\boldsymbol{B}}_\perp\| = 1$. We have

$$\|\widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t\|^2 = \|\widehat{\boldsymbol{B}}(\widehat{\boldsymbol{w}}_t - \widehat{\boldsymbol{B}}^\top \boldsymbol{\theta}_t)\|^2 + \|\widehat{\boldsymbol{B}}_\perp \widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\boldsymbol{w}_t\|^2 \le \|\widehat{\boldsymbol{w}}_t - \widehat{\boldsymbol{B}}^\top \boldsymbol{\theta}_t\|^2 + \|\widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\|^2.$$

Let $v_i = \sqrt{\lambda_0}\hat{b}_i$. The OLS estimator is given by

$$\hat{w}_t = \left(\sum_{n=N_1+1}^{N_1+N_2+1} \widehat{\boldsymbol{B}}^\top \boldsymbol{v}_i \boldsymbol{v}_i^\top \widehat{\boldsymbol{B}}\right)^{-1} \sum_{n=N_1+1}^{N_1+N_2} \widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t} r_{n,t}$$
$$= \left(\sum_{n=N_1+1}^{N_1+N_2+1} \widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t}\boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\right)^{-1} \sum_{n=N_1+1}^{N_1+N_2} \widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t}(\boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\boldsymbol{w}_t' + \varepsilon_{n,t})$$
$$= w_t' + \left(\sum_{n=N_1+1}^{N_1+N_2+1} \widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t}\boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\right)^{-1} \sum_{n=N_1+1}^{N_1+N_2} \widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t}\varepsilon_{n,t}.$$

Write $\boldsymbol{A} = \sum_{n=N_1+1}^{N_1+N_2+1} \widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t}\boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}$.

$$\mathbb{E}\|\widehat{\boldsymbol{w}}_t - \boldsymbol{w}_t'\|^2 = \sum_{n=N_1+1}^{N_1+N_2} \boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\boldsymbol{A}^{-2}\widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t} \, \mathbb{E}\,\varepsilon_{n,t}^2$$
$$\le \sum_{n=N_1+1}^{N_1+N_2} \boldsymbol{x}_{n,t}^\top \widehat{\boldsymbol{B}}\boldsymbol{A}^{-2}\widehat{\boldsymbol{B}}^\top \boldsymbol{x}_{n,t} \le N_2\|\boldsymbol{A}^{-2}\| \le N_2(\frac{k}{\lambda_0 N_2})^2 = \frac{k^2}{\lambda_0^2 N_2}.$$

Putting together, we have

$$\mathbb{E}\|\widehat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t\|^2 \le \frac{k^2}{\lambda_0^2 N_2} + \|\widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\|^2. \qquad \square$$

*Proof of [Theorem 3](). Note that $J = O(1)$ under our assumptions, as indicated by [Rusmevichientong & Tsitsiklis](2010). So we have

$$\mathbb{E}[R^{N,T}] \le TN_1 + TN_2 + T(N - N_1 - N_2)J\frac{\mathbb{E}\|\hat{\boldsymbol{\theta}}_t - \boldsymbol{\theta}_t\|^2}{\|\boldsymbol{\theta}_t\|}$$
$$\le TN_1 + TN_2 + TNJ\frac{\|\widehat{\boldsymbol{B}}_\perp^\top \boldsymbol{B}\|^2 + k^2/(\lambda_1^2 N_2)}{\omega}$$
$$\lesssim TN_1 + TN_2 + TN \cdot \frac{d^3 k^2}{N_1 T}\log^3(NT) + TN\frac{k^2}{N_2}$$
$$\le TN_1 + \frac{Nd^3 k^2}{N_1}\log^3(NT) + TN_2 + TN\frac{k^2}{N_2}$$
$$\le d^{1.5}k\sqrt{NT}\log^3(NT) + kT\sqrt{N}. \qquad \square$$

E   PROOF OF [THEOREM 4]()

In this appendix, we assume all action sets are spherical, i.e. $\mathcal{A}_{n,t} \equiv \mathbb{S}^{d-1}$ for $n \in [N], t \in [T]$. Note that these action sets meet [Assumption 3]().

For each task $t \in [T]$, we use $R^{N,(t)} = \sum_{n=1}^{N}[\max_{\boldsymbol{x} \in \mathcal{A}_{n,t}} \langle \boldsymbol{x}, \boldsymbol{\theta}_t \rangle - \mathbb{E}\langle \boldsymbol{x}_{n,t}, \boldsymbol{\theta}_t \rangle]$ to denote the regret incurred on task t.

Lemma 19. *Under the setting of [Theorem 4](), we have $\inf_{\mathcal{A}} \sup_{\mathcal{I}} \mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N,T}] \ge CkT\sqrt{N}$, where* $C = 0.0001$.

Lemma 20. *Under the setting of [Theorem 4](), we have $\inf_{\mathcal{A}} \sup_{\mathcal{I}} \mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N,T}] \geq Cd\sqrt{kTN}$, where $C = 0.0001$.*

Proof of [Theorem 4](). We combine [Lemma 19]() and [Lemma 20](). □

The proofs in this appendix would largely follow the proofs in [Appendix B](), yet this appendix is much longer, because we need to construct instances that satisfies [Assumption 3](), [Assumption 4](), and [Assumption 5]().

Our proofs to the lemmas are based on the lower bounds for the (single-task) linearly parameterized bandit setting, which corresponds to the $T = 1$ case in our setting. For this single-task setting, we assume $k = d$ and $\boldsymbol{B} = \boldsymbol{I}_d$. (This setting need not meet [Assumption 4]() and [Assumption 5]()). We write the regret as $R^N = R^{N,1}$ and call algorithms for the single-task setting as single-task algorithms.

We invoke the following lower bound for the single-task setting.

Lemma 21. *Assume $N \geq d^2$ and $d \geq 2$. Let $\mathcal{N}(\mu, \Sigma)$ be the multivariate normal distribution with mean μ and covariance matrix Σ. For any single-task algorithm, we have*

$$\mathbb{E}_{\boldsymbol{w} \sim \mathcal{N}(0, \boldsymbol{I}_d/d)}[R^N \cdot \mathbb{I}\{0.09 \leq \|\boldsymbol{w}\| \leq 3\}] \geq 0.006d\sqrt{N}. \tag{16}$$

The lemma can be proved by following the proof of Theorem 2.1 of [Rusmevichientong & Tsitsiklis]() ([2010]()). Next we use it to prove [Lemma 19]() and [Lemma 20](). The main idea to prove [Lemma 19]() is to note that we can treat our setting as T independent k-dimensional linear bandits.

Let μ_d be the conditional probability measure whose density function is given by

$$f(x) = \begin{cases} \frac{g(x)}{\Pr_X[0.09 \leq \|X\| \leq 3]}, & 0.09 \leq \|x\| \leq 3, \\ 0, & \text{otherwise}, \end{cases}$$

where $X \sim \mathcal{N}(0, \boldsymbol{I}_d/d)$ is the multivariate gaussian vector and $g(x)$ is the probability density function of X. Then [(16)]() implies

$$\mathbb{E}_{w \sim \mu_d}[R^N] \geq 0.006d\sqrt{N}. \tag{17}$$

Proof of [Lemma 19](). Without loss of generality, we assume $2k$ divides T. Suppose, for contradiction, that there is an algorithm $\mathcal{A}'$, such that for every instance $\mathcal{I}$, it incurs regret $\mathbb{E}[R_{\mathcal{A}',\mathcal{I}}^{N,T}] \leq CTk\sqrt{N}$. We replace the condition $\|w_t\| \leq 1$ by $\|w_t\| \leq 3$ in our setting. Note that $\mathcal{A}'$ implies an algorithm $\mathcal{A}$ that incurs regret $\mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N,T}] \leq 3CTk\sqrt{N}$.

We construct the following instances $\mathcal{I} = (\boldsymbol{B}, \boldsymbol{W})$, where $\boldsymbol{B} = \begin{pmatrix} \boldsymbol{I}_k & 0 \end{pmatrix}^\top$ and $\boldsymbol{W} = \begin{pmatrix} \boldsymbol{w}_1 & \cdots & \boldsymbol{w}_T \end{pmatrix}$ as follows. Let

$$\boldsymbol{w}_1 = \cdots \boldsymbol{w}_{T/2k} = \boldsymbol{e}_1, \boldsymbol{w}_{T/2k+1} = \cdots = \boldsymbol{w}_{T/k} = \boldsymbol{e}_2, \ldots, \boldsymbol{w}_{(k-1)T/2k+1} = \cdots = \boldsymbol{w}_{T/2} = \boldsymbol{e}_k,$$

where $\boldsymbol{e}_1, \ldots, \boldsymbol{e}_k \in \mathbb{R}^k$ is the standard basis. Let

$$\boldsymbol{w}_{T/2+1}, \ldots, \boldsymbol{w}_T \sim \mu_d$$

be i.i.d. drawn. Thanks to the first $\frac{T}{2}$ tasks, the instance $\mathcal{I}$ always satisfies [Assumption 4](). Note that $\|\boldsymbol{w}_t\| \geq 0.09$, so the instance also satisfies [Assumption 5](). Then we have

$$\mathbb{E}_{\boldsymbol{w}_{T/2+1}, \ldots, \boldsymbol{w}_T \sim \mu_d}[R_{\mathcal{A},\mathcal{I}}^{N,T}] \leq 3CTk\sqrt{N}.$$

Thus

$$\sum_{t=T/2+1}^{T} \mathbb{E}_{\boldsymbol{w}_{T/2+1}, \ldots, \boldsymbol{w}_T \sim \mu_d}[R_{\mathcal{A},\mathcal{I}}^{N,(t)}] \leq \mathbb{E}_{\boldsymbol{w}_{T/2+1}, \ldots, \boldsymbol{w}_T \sim \mu_d}[R_{\mathcal{A},\mathcal{I}}^{N,T}] \leq 3CTk\sqrt{N}.$$

Therefore, we can find $t \in [T/2 + 1, T]$ such that

$$\mathbb{E}_{\boldsymbol{w}_{T/2+1},\ldots,\boldsymbol{w}_T \sim \mu_d}[R_{\mathcal{A},\mathcal{I}}^{N,(t)}] \leq \frac{3CT}{T/2} k\sqrt{N} = 6Ck\sqrt{N}.$$

We note that the expectation operator $\mathbb{E}_{\boldsymbol{w}_{T/2+1},\ldots,\boldsymbol{w}_T \sim \mu_d}$ is over all randomness on tasks $\tau \neq t$ and its parameter w_τ. So there is a realization of the randomness on other tasks $\tau \neq t$ that satisfies

$$\mathbb{E}_{\boldsymbol{w}_t \sim \mu_d}[R_{\mathcal{A},\mathcal{I}}^{N,(t)} \mid \boldsymbol{w}_\tau, \varepsilon_\tau, \tau \neq t] \leq 6Ck\sqrt{N}.$$

Based on the realization $\boldsymbol{w}_\tau, \varepsilon_\tau$, we design a single-task algorithm $\mathcal{S}$, which plays task t and simulates other tasks $\tau \neq t$ with $\boldsymbol{w}_\tau, \varepsilon_\tau$. The algorithm achieves

$$\mathbb{E}_{\boldsymbol{w} \sim \mu_d}[R_{\mathcal{S},\mathcal{I}}^{N}] = \mathbb{E}_{\boldsymbol{w}_t \sim \mu_d}[R_{\mathcal{A},\mathcal{I}}^{N,(t)} \mid \boldsymbol{w}_\tau, \varepsilon_\tau, \tau \neq t] \leq 6Ck\sqrt{N},$$

which contradicts to (17) because $C = 0.0001$. $\qquad\square$

Proof of Lemma 20. Without loss of generality, we assume that d is even and that $2k$ divides T. Suppose, for contradiction, that there is an algorithm $\mathcal{A}'$, such that for every instance $\mathcal{I}$, it incurs regret $\mathbb{E}[R_{\mathcal{A}',\mathcal{I}}^{N,T}] \leq Cd\sqrt{kTN}$. We replace the condition $\|\boldsymbol{w}_t\| \leq 1$ by $\|\boldsymbol{w}_t\| \leq 3$ in our setting. Note that $\mathcal{A}'$ implies an algorithm $\mathcal{A}$ that incurs regret $\mathbb{E}[R_{\mathcal{A},\mathcal{I}}^{N,T}] \leq 3Cd\sqrt{kTN}$.

We prove the lemma separately, based on whether $k \geq \frac{d}{2}$ or not.

1. Consider $k \leq \frac{d}{2}$. We generate k vectors $\psi_1, \ldots, \psi_k$ so that $\psi_i \sim \mu_{d-i+1}$. For every dimension i, we consider a map

$$c_i : \mathbb{R}^{d \times i} \to \mathbb{R}^{d \times (d-i+1)},$$
$$(x_1, \ldots, x_i) \mapsto (y_1, \ldots, y_{d-i+1}),$$

so that when $\{x_1, \ldots, x_i\}$ are orthogonal, the set $\{y_1, \ldots, y_{d-i+1}\}$ is the orthonormal basis of the orthogonal complement $\text{span}\{x_1, \ldots, x_i\}^\perp$ of $\mathbb{R}^d$. Note that c_i can be computed efficiently, e.g. by Gram-Schmidt process.

We define $\phi_1 = \psi_1$ and $\phi_i = c_{i-1}(\phi_1, \ldots, \phi_{i-1}) \cdot \psi_i$ for $i \geq 2$. We observe that $\{\phi_1, \ldots, \phi_k\}$ are orthogonal. Next we define our instance $\mathcal{I} = (\boldsymbol{B}, \mathbf{W})$, where $\boldsymbol{B} = (b_1 \quad \cdots \quad b_k)$ and $b_i = \frac{\phi_i}{\|\phi_i\|}$. For $\boldsymbol{W} = (w_1 \quad \cdots \quad w_T)$, we let

$$w_1 = \cdots = w_{T/k} = \|\phi_1\| \cdot \boldsymbol{e}_1,$$
$$w_{T/k+1} = \cdots = w_{2T/k} = \|\phi_2\| \cdot \boldsymbol{e}_2,$$
$$\vdots$$
$$w_{(k-1)T/k+1} = \cdots = w_T = \|\phi_k\| \cdot \boldsymbol{e}_k,$$

where $\{\boldsymbol{e}_1, \ldots, \boldsymbol{e}_k\} \subseteq \mathbb{R}^k$ is the standard basis. Note that the instance $\mathcal{I}$ always satisfies Assumption 4 and Assumption 5 by our choice of $\boldsymbol{w}_t$. Note that we have divided the tasks into k groups, so that each group share the same vector $\boldsymbol{w}_t$. For $i = 1, \ldots, k$, we denote the regret of group i as

$$R_{\mathcal{A},\mathcal{I}}^{N,((i))} = \sum_{t=(i-1)T/k+1}^{iT/k} R_{\mathcal{A},\mathcal{I}}^{N,(t)}.$$

For the algorithm $\mathcal{A}$, it incurs regret

$$\mathbb{E}_{\phi_1,\ldots,\phi_k}[R_{\mathcal{A},\mathcal{I}}^{N,((i))}] \leq 3Cd\sqrt{kNT}.$$

So there is a group $i \in [k]$, such that

$$\mathbb{E}_{\phi_1,\ldots,\phi_k}[R_{\mathcal{A},\mathcal{I}}^{N,((i))}] \leq \frac{1}{k} 3Cd\sqrt{kNT} = 3Cd\sqrt{\frac{NT}{k}}.$$

Similar to the proof of Lemma 19, we can fix the randomness for groups $j \neq i$ to obtain a realization, such that

$$\mathbb{E}_{\phi_i | \phi_{j(j \neq i)}} [R_{\mathcal{A},\mathcal{I}}^{N,((i))} \mid \phi_j, \varepsilon_j, j \neq i] \leq \frac{1}{k} 3Cd\sqrt{kNT} = 3Cd\sqrt{\frac{NT}{k}}.$$

Here we note that ϕ_i could depend on ϕ_ι for $\iota \geq i+1$. Now we let $\psi_i' \sim \mu_{d-k+1}$ and let

$$\phi_i' = A\psi_i', \qquad A = c_{k-1}(\phi_1, \ldots, \phi_{i-1}, \phi_{i+1}, \ldots, \phi_k). \tag{18}$$

Note that ϕ_i' and $\phi_i \mid \phi_{j(j \neq i)}$ are identical, so we have

$$\mathbb{E}_{\phi_i = \phi_i'} [R_{\mathcal{A},\mathcal{I}}^{N,((i))} \mid \phi_j, \varepsilon_j, j \neq i] \leq \frac{1}{k} 3Cd\sqrt{kNT} = 3Cd\sqrt{\frac{NT}{k}}. \tag{19}$$

We complete the proof by showing that (19) implies a single-task algorithm $\mathcal{S}$ that plays a $(d-k+1)$-dimensional linear bandit for $\frac{NT}{k}$ times. Let $w = \psi_i'$. Then w is independently drawn from μ_{d-k+1}. Next we design the algorithm $\mathcal{S}$, which runs $\mathcal{A}$ by playing the tasks $t \in \mathcal{T} = \{(i-1)T/k + 1, \ldots, iT/k\}$ and simulates other tasks $\tau \notin \mathcal{T}$. Note that playing the task $t \in \mathcal{T}$ is the same as playing the single-task bandit defined by w, because we have $\boldsymbol{\theta}_t = \boldsymbol{B}w_t = \phi_i = A\psi_i'$ and the matrix A is known (as in (18)) after we fix the randomness on other tasks. Since $|\mathcal{T}| = \frac{T}{k}$ and $\mathcal{A}$ is played for N times, $\mathcal{S}$ can play the single-task bandit specified by w for $\frac{NT}{k}$ times. As a result, we have

$$\mathbb{E}_{\boldsymbol{w} \sim \mu_{d-k+1}} [R_{\mathcal{S},\mathcal{I}}^N(\mathcal{I})] = \mathbb{E}_{\phi_i = \phi_i'} [R_{\mathcal{A},\mathcal{I}}^{N,((i))} \mid \phi_j, \varepsilon_j, j \neq i]$$

$$\leq 3Cd\sqrt{\frac{NT}{k}}$$

$$\leq 6C(d-k+1)\sqrt{\frac{NT}{k}},$$

which contradicts to (17) because $C = 0.0001$.

2. Consider $k > \frac{d}{2}$. In this case, the lower bound in Lemma 19 becomes $\Omega(Tk\sqrt{N}) = \Omega(Td\sqrt{N})$. Since $T \geq k$, we have $d\sqrt{kTN} \lesssim Td\sqrt{N}$. Thus we conclude by Lemma 19. □

F EXPERIMENTS FOR INFINITE-ARM SETTING

Setup In all experiments, we set $d = 10, N = 10^4$ and the action $\mathcal{A}_t = \mathbb{S}^{d-1}$. The parameters are generated as follows. We consider $k = 2, 3$ in our experiments. The noise $\varepsilon_{n,t} \sim \mathcal{N}(0, 1)$ are i.i.d. Gaussian random variables. To verify our theoretical results, we consider a hyper-parameter $c \in \{0.5, 1, 1.5, 2\}$. For each c, we run $\mathsf{E}^2\mathsf{TC}$ with $N_1 = d^c k \sqrt{\frac{N}{T}}$ and $N_2 = k\sqrt{N}$.

Results and Discussions We present the simulation results in Figure 5 and Figure 6. We emphasize that the y-axis in our figures corresponds to the regret per task, which is defined as $\frac{\text{Reg}_{N,T}}{T}$.

Our main observation is that only when the number of tasks T is large and we choose the right scaling $N_1 = d^{1.5} k \sqrt{\frac{N}{T}}$, our method can outperform the PEGE algorithm. We discuss several implications of our results. First, representation learning does help, especially when there are many tasks available for us to learn the representation, as we see in all figures that the regret per task of $\mathsf{E}^2\mathsf{TC}$ decreases as T increases. Second, the help of representation learning is bounded. In the figures, we see that the curves of $\mathsf{E}^2\mathsf{TC}$ bends to a horizontal line as T increases, which suggests a lower bound on the regret per task. Meanwhile, we also proved an $\Omega(k\sqrt{N})$ lower bound on the regret per task in Theorem 4. Third, representation learning may have adverse effect without enough task. In our figures, this was established by noting that our algorithm cannot outperform PEGE when T is small. This corresponds to the "negative transfer" phenomenon observed in previous work (Wang et al., 2019). Fourth, the correct hyper-parameter $c = 1.5$ is crucial. For hyper-parameter other than $c = 1.5$, the figures show that our algorithm would require much more tasks to outperform PEGE. Lastly, by comparing the two figures, we notice that our algorithm has bigger advantage when k is smaller, which corroborates the scaling with respect to k in our regret upper bound. In contrast, PEGE does not benefit from a smaller k.

Figure 5: Comparisons of E^2TC with PEGE for $k = 3$.

Figure 6: Comparisons of E^2TC with PEGE for $k = 2$.