MULTIMODALQA: COMPLEX QUESTION ANSWERING OVER TEXT, TABLES AND IMAGES

ABSTRACT

When answering complex questions, people can seamlessly combine information from visual, textual and tabular sources. While interest in models that reason over multiple pieces of evidence has surged in recent years, there has been relatively little work on question answering models that reason *across* multiple modalities. In this paper, we present MULTIMODALQA (MMQA): a challenging question answering dataset that requires joint reasoning over text, tables and images. We create MMQA using a new framework for generating complex multi-modal questions at scale, harvesting tables from Wikipedia, and attaching images and text paragraphs using entities that appear in each table. We then define a formal language that allows us to take questions that can be answered from a single modality, and combine them to generate *cross-modal* questions. Last, crowdsourcing workers take these automatically generated questions and rephrase them into more fluent language. We create 26,878 questions through this procedure, and empirically demonstrate the necessity of a multi-modal multi-hop approach to solve our task: our multi-hop model, *ImplicitDecomp*, achieves an average F_1 of 51.1 over cross-modal questions, substantially outperforming a strong baseline that achieves 42.9 F_1, but still lags significantly behind human performance, which is at 85.2 F_1.

1 INTRODUCTION

When presented with complex questions, people often do not know in advance what source(s) of information are relevant for answering it. In general scenarios, these sources can encompass multiple modalities, be it paragraphs of text, structured tables, images or combinations of those. For instance, a user might ponder *"When was the famous painting with two touching fingers completed?"*, if she cannot remember the exact name of the painting. Answering this question is made possible by integrating information across both the textual and visual modalities.

Recently, there has been substantial interest in question answering (QA) models that reason over multiple pieces of evidence (*multi-hop* questions (Yang et al., 2018; Talmor & Berant, 2018; Welbl et al., 2017)). In most prior work, the question is phrased in natural language and the answer is in a context, which may be a paragraph (Rajpurkar, 2016), a table (Pasupat & Liang, 2015), or an image (Antol et al., 2015). However, there has been relatively little work on answering questions that require integrating information *across* modalities. Hannan et al. (2020) created MANYMODALQA: a dataset where the context for each question includes information from multiple modalities. However, the answer to each question can be derived from a *single modality* only, and no *cross-modality reasoning* is needed. Thus, the task is focused on identifying the relevant modality. Recently, Chen et al. (2020) presented HYBRIDQA, a dataset that requires reasoning over tabular and textual data. While HYBRIDQA necessitates cross-modality reasoning, it does not require visual inference, limiting the types of questions that can be represented.

In this work, we present *MMQA*, the first large-scale (26,878 examples) QA dataset that requires integrating information across free text, semi-structured tables, and images, where 40% of the questions require cross-modality reasoning. Figure 1 shows an example cross-modal question: *"Which B.Piazza title came earlier: the movie S. Stallon's son starred in, or the movie with half of a lady's face on the poster?"*. Answering this question entails (i) decomposing the question into a sequence of simpler questions, (ii) determining the modalities for the simpler questions and answering them, i.e., information on the poster is in an image, the information on *"S. Stallon's son"* is in free

Figure 1: Example of a *MMQA* question, answer and context. In green are the text modality question and answer, and in red the image modality. The table is used to perform the year comparison.

text, and the years of the movies are in the table, (iii) combining the information from the simpler questions to compute the answer: *"Tell Me that you love me, Junie Moon"*.

Our methodology for creating *MMQA* involves three high-level steps. (a) *Context construction*: we harvest tables from Wikipedia, and connect each table to images and paragraphs that appear in existing Reading Comprehension (RC) datasets (Kwiatkowski et al., 2019; Clark et al., 2019; Yang et al., 2018); (b) *Question generation*: Following past work (Talmor & Berant (2018)), we use the linked structure of the context to automatically generate questions that require multiple reasoning operations (composition, conjunction, comparison) across modalities in pseudo-language ; (c) *Paraphrasing*: we use crowdsourcing workers to paraphrase the pseudo-language questions into more fluent English.

To tackle *MMQA*, we introduce *ImplicitDecomp*, a new model that predicts a program that specifies the required reasoning steps over different modalities, and executes the program with dedicated text, table, and image models. *ImplicitDecomp* performs multi-hop multimodal reasoning without the need for an explicit decomposition of the question.

We empirically evaluate *MMQA* by comparing *ImplicitDecomp* to strong baselines that do not perform cross-modal reasoning and to human performance. We find that on multimodal questions, *ImplicitDecomp* improves F_1 from $42.9 \rightarrow 51.1$ over a single-hop approach. Humans are able to reach 85.2 F_1, significantly outperforming our best model. Because automatic evaluation is non-trivial, we also manually analyze human performance and find humans correctly answer 91.6% of the questions in *MMQA*. Finally, our dataset can be used in an open-domain setup over all of Wikipedia. In this setup, the F_1 of humans is 76.3.

To summarize, our key contributions are:

- *MMQA*: a dataset with 26,878 questions and answers, 40% of which require cross-modal reasoning.
- A methodology for generating multimodal questions over text, tables and images at scale.
- *ImplicitDecomp*, A model for implicitly decomposing multimodal questions, which improves on a single-hop model by 8.2 absolute F_1 points on questions requiring cross-modal reasoning.

2 DATASET GENERATION

Our goal is to develop a method that allows generating complex questions over multiple modalities at scale. An overview of the methodology is captured in Figure 2. We first select a Wikipedia table as an anchor, to which we add images and texts paragraphs and obtain a *context*. Single modality questions are generated based on these contexts, and used to automatically create multimodal, multi-hop questions. AMT workers rephrase the questions into natural language, and finally distractor paragraphs and images are selected for each question. We now elaborate on the 6 steps of the process.

Figure 2: *MMQA* dataset generation process.

2.1 Wikipedia tables as anchors The 01-01-2020 English Wikipedia dump contains roughly $3M$ tables. We extracted all tables and selected those that meet the following criteria: (a) The tables contain 10-25 rows (b) At least 3 images are associated with the table. This results in a total of $700k$ tables. (see supp. material for more information). These tables are the anchors of our contexts, which we enrich with images and text for multimodal question generation. A key element of the tables are Wikipedia Entities (*WikiEntities*) that appear in them, i.e., concepts linked to other Wikipedia entries. We use them to connect different modalities, bridge questions, and solve ambiguities (details below).

2.2 Connecting Images and Text to Tables *Images.* We consider two cases: (a) in-table images and (b) images from pages of linked *WikiEntities*. In the former, the images are featured inside the table cells. In the latter, the table contains a column of *WikiEntities* that potentially have images, e.g. a table describing the filmography of an actor often contains a column of film names, which may have posters in their respective pages. To associate entities with their representative image, we map entities and their profile images in their Wikipedia pages. Overall, we obtain 48,885 images, with 671 in-table images and 48,214 *WikiEntities* images. *Text.* We build on texts from contexts appearing in existing Reading Comprehension datasets. We elaborate on this process next.

2.3 Generating Single-Modality Questions *Tables.* We generate pseudo-language table questions in the following form *"In [table title] of [Wikipedia page title] which cells in [column X] have the [value Y] in [column Z]?"*. We additionally support numeric computations over columns classified as dates or numbers, such as min and max values, e.g., *"In [Doubles] of [WCT Tournament of Champions], what was the MOST RECENT [Year](s) where the [Location] was [Forest Hills]"*.

Images. We use crowdsourcing to generate single-modality questions about images. We generated two types of image questions, based on the images we retrieved from the previous step: (i) questions over a single image, (ii) questions over a list of images.

When generating single-image questions, we show Amazon Mechanical Turk (AMT) crowd workers an image alongside its *WikiEntity*, and ask them to phrase a question about the image with the entity being the focus of the question. E.g, if the entity is *"Roger Federer"*, a potential question is *"What's the hair color of Roger Federer?"*. For questions to have meaning in an open-domain setting, we primed AMT workers to ask questions that correspond to "stable" features, i.e., features that are unlikely to change in different images and are thus appropriate in an open-domain setting.

For questions with a list of images, we use images that appear in the same column of a table. To generate these questions, AMT workers were given the images and asked to phrase a binary question about a distinctive feature of the entities that a subset of the images share. E.g., given a list of statues, the worker could ask *"Which of the statues features a horse?"* This process results in 2,268 single image questions and 2,223 list image questions that are later used to create multimodal questions.

Text. To obtain questions answerable over text paragraphs we build on existing Reading Comprehension datasets: *Natural Questions (NQ)* (Kwiatkowski et al., 2019) consists of about $300K$ questions issued to the Google search engine. This dataset mostly contains simple questions where a single paragraph suffices to answer each question. *BoolQ* (Clark et al., 2019) contains $15,942$ yes/no questions, gathered using the same pipeline as NQ. *HotpotQA* (Yang et al., 2018) contains $112K$ training questions, where crowd workers were shown pairs of related Wikipedia paragraphs and were asked to author questions that require multi-hop reasoning over the paragraphs.

To use questions from the above datasets as building blocks for multi-hop multimodal questions, we unified them into a corpus that consists of triples of (i) a text question, (ii) an answer and (iii) 1-2 gold paragraphs from Wikipedia. We link a question to a table, by matching *WikiEntities* in the table to entities in the text of the question (see supplementary material for further details). Overall, we retrieved 6,593 questions from NQ, 1,095 from BoolQ and 4,045 from HotpotQA.

Type	Q&A	%
TextQ	*The Carlsberg Group brews which type of beer that was originally made by Norbertine monks? Grimbergen*	28.9
TableQ	*Does the German state Baden-Wurttemberg or Thuringia have more residents? Baden-Württemberg*	21.5
Compose(TableQ,TextQ)	*Who caught the last pass in the game that Buffalo Bills played on December 4 1994? former teammate Mark Clayton*	12.3
ImageQ	*What weapon is the statue in Nottingham holding? bow*	8.4
Compose(TextQ,TableQ)	*On what date did the original artist who sang Sweet Child of Mine have a concert at US Bank Stadium? July 30, 2017*	5.5
Compose(TableQ,ImageListQ)	*The Athletes of the Men's wheelchair Tokyo Marathon in 2018 wore what to cover their heads? helmet*	4.5
Compose(ImageQ,TableQ)	*In what year was Toru Iwatani's video game whose cover shows Pac-Man wearing a hat released? 1984*	3.9
Compare(Compose(TableQ,ImageQ),TableQ)	*Which manufacturer has fewer wins at the First Data 500: Buick or the brand with a cross for a logo? Buick*	3.0
Intersect(TableQ,TextQ)	*Who was the artist for Damon Fox in 2006 who also sings "You got the moves like Jagger"? Christina Aguilera*	2.5
Compose(ImageQ,TextQ)	*Did Gary Oldman take part in the movie whose poster features two men holding handguns, and which had Mark L. Smith as a writer? no*	2.4
Intersect(ImageListQ,TableQ)	*What covers of the Chandler Canterbury films from 2009 has more than one person? Powder Blue Balls Out, Gary the Tennis Coach, After.Life*	2.0
Compare(TableQ,Compose(TableQ,TextQ))	*Did Chelsea or club that sings You'll Never Walk Alone rank higher in Deloitte Football Money League 2007? Chelsea*	1.9
ImageListQ	*What is the common name of the bush warbler in Thailand that has an orange stripe above its eye? Chestnut-crowned bush warbler*	1.3
Compose(TextQ,ImageListQ)	*On the poster for the movie based on the book "Act like a Lady, Think Like a Man," how many people are there in total? nine*	1.0
Compare(Compose(TableQ,ImageQ), Compose(TableQ,TextQ))	*Which commercial did Ryan Stiles appear in first: an ad for a company whose logo features a bird, or and ad for America's largest pizza chain? Pizza Hut*	0.8
Intersect(ImageListQ,TextQ)	*Which gray haired driver at the Motor Trend 500 of 1969 has won the most indy 500? A.J.Foyt, Al Unser*	0.2

Table 1: All 16 compositional templates in *MMQA* with an example and their relative frequency.

2.4 Generating multimodal complex questions We present an automatic method for creating at scale multimodeal compositional questions (i,e., questions that require answering a sequence of sub-questions to conclude the final answer). Our first step is to introduce a formal language that allows to combine questions answerable from a single modality. Below we introduce the logical operations that allow to generate such pseudo-language (PL) questions, while keeping a formal representation of how they were constructed. In Table 1, we illustrate this process with all 16 different compositional templates used for question generation. We now describe our logical operations.

Logical Operations Functions in our formal language take arguments and return a PL partial question, as well as answers that can be a list of one or more strings, or a list of one or more *WikiEntities*. All operations have access to the full context. In addition, we prepend a prefix containing the Wikipedia table name and page title—e.g. *"In the Filmography of Brad Pitt,"*—to all our PL questions to support an open-domain QA setup. Our set of logical operations are:

1. **TABLEQ**: Returns a question from the table questions generated in §2.3, as well as a list of *WikiEntities* or a list of strings as answers.
2. **TEXTQ**: Returns a text corpus question (see §2.3) and a list of *WikiEntities* or strings as answers.
3. **IMAGEQ**: Returns a question about a single image associated with a *WikiEntity* and a single token answer from a fixed vocabulary (see §2.3).
4. **IMAGELISTQ**: Returns a question about a list of images and a list of *WikiEntities* corresponding to the images that answer the question (see §2.3).
5. **COMPOSE**($\cdot, \cdot$): Takes a PL question containing *a single WikiEntity* as a first argument, and a PL question that produces that *WikiEntity* as the output answer as its second argument. E.g., COMPOSE(*"Where was Barack Obama born?"*,*"Who was the 44th president of the USA?"*). The function replaces the *WikiEntity* in the first-argument PL question with the second-argument PL question and returns the resulting PL question (*"Where was the 44th president of the USA born?"*).
6. **INTERSECT**($\cdot, \cdot$): Takes two PL questions that return lists of more than one *WikiEntity*, and returns their intersection as the answer. The resulting PL question is of the form *"PL$_1$ and PL$_2$"* omitting PL$_2$'s first word (*"Who was born in Hawaii and is the parent of Sasha Obama?"*).
7. **COMPARE**($\cdot, \cdot$): Takes two PL questions each returning one *WikiEntity* that can be linked to one cell in the table, denoted by Ans$_1$, Ans$_2$. We first choose a numeric or date column in the table, if such exists. We then compare the values of this column corresponding to the rows of Ans$_1$ and Ans$_2$. Depending on the comparison outcome, output one of (Ans$_1$, Ans$_2$) as the operation answer.

The PL question created is of the form *"What has compare-op numeric-column-name, PL_1 or PL_2?"* omitting PL_1 and PL_2's first word. E.g. *"What has most recent creation year, the rocket of Appolo program, or the rocket of Gemini program?"*

2.5 Paraphrasing using AMT We used English-speaking AMT workers to paraphrase automatically-generated PL questions into natural language (NL). Each question was paraphrased by 1 worker and validated by 1-3 other workers. To avoid annotator biases (Geva et al., 2019), the number of annotators who worked on both the training and evaluation set was kept to a minimum. We also deployed a feedback mechanism, where workers receive a bonus if a baseline model correctly answered the question after their first paraphrasing attempt, but incorrectly after they refined the paraphrase. See supp. material for print-screens of the AMT annotator interface.

To generate diversity, workers got a bonus if the normalized edit distance of a paraphrase compared to the PL question was higher than 0.7. A total of 113 workers were involved, and 26,878 examples were produced with an average cost of 0.3$ per question. We split the dataset into 22,069 training, 1,921 development (dev.), 2,888 test-set examples. Context components in the dev. and test sets are disjoint, and were constructed from a disjoint set of single-modality questions.

A shortcoming of our method for automatically generating examples is that the question distribution does not come from a "natural" source. We argue that developing models that are capable of performing reasoning over multiple modalities is an important direction and *MMQA* provides an opportunity to develop and evaluate such models. Moreover, this method allows to control the compositional questions created, proving effective in creating a cheap and scalable dataset.

2.6 Adding distractors to the context *Images.* Questions from the IMAGELISTQ operator require reasoning over a list of images from the same column, and hence do not require additional distractors. For IMAGEQ questions (single-image), we randomly add images that are associated with the *WikiEntities* that appear in the table, setting a maximum of 15 distractors per question.

Text. We used DPR (Karpukhin et al., 2020), a neural information retrieval model, to retrieve distractors for all questions. Each context includes exactly 10 paragraphs, where 1-2 are gold paragraphs and the rest are distractors. Specifically, we encode the first 2 paragraphs of each Wikipedia article with the DPR encoder, and use as distractors the paragraphs with the highest dot product between their encoding and the question encoding. We do not allow: (a) an overlap between the distractors in the training and evaluation sets, (b) distractors originating from the gold article, (c) distractors containing an exact match to the gold answer.

To summarize, each of our examples contains a question, an answer, the formal representation of the PL question (ignored by our models), and all distractors and gold context for all modalities. This renders *MMQA* useful for both open-domain multimodal QA, as well as context-dependant QA.

3 DATASET ANALYSIS

To present the diversity of *MMQA* we analyze its key statistics, domains, and paraphrasing richness.

Key Statistics *MMQA* contains $26,878$ questions, and their main statistics are in Table 2. Since we focus on multimodality, we upsample the number of multimodal questions in the dev. and test sets compared to the training set. Also, about two thirds of the questions in *MMQA* are compositional. Questions are relatively long (18 words), but answers tend to be short (2.1 words). The answer for each question can be a single answer or a list of answers. While list answers comprise only 6.7% of the data, when considering compositional questions that contain an intermediate question within them, the proportion of list answers in intermediate questions is higher (17.3%).

Measurement	Value
# Distinct Questions	26,878
Train multimodal questions	38%
Dev.+test multimodal questions	48.4%
Train compositional questions	65.2%
Dev.+test compositional questions	68.2%
Average question length (words)	17.7
Average # of answers per question	1.14
List answers	6.7%
List answers per intermediate question	17.3%
Average answer length (words)	2.1
# of distinct words in questions	45,529
# of distinct words in answers	19,106

Table 2: Key statistics for *MMQA*.

Domain Diversity Figure 3 shows a sample of questions from *MMQA* categorized to different domains. While entertainment categories occupy a large portion of our dataset (Films 36%, TV 19%), we observe questions represent a wide variety of topics.

Figure 3: Domain diversity in *MMQA*. Area of each color corresponds to frequency of topic in the dataset.

Paraphrasing Richness Workers received a bonus when substantially modifying the PL questions. We observe that the average normalized edit distance between the NL questions and the PL questions is high (0.7), that NL questions are shorter (avg. length of 18.63 vs. 22.48 words for PL questions), and use a richer vocabulary (#unique words 36, 603 vs 33, 835).

4 MODELS

Here we present our baseline models. We first train models that interact with a single context modality given a question (§4.1), and use those as building blocks in our multimodal approaches (§4.2). We denote the question by Q, context paragraphs by $\mathcal{P}$, Table by T and context images by $\mathcal{I}$.

4.1 SINGLE-MODALITY QA MODULES

Text QA Module Following prior work (Min et al., 2019a; Asai et al., 2020), our text QA module takes as input a question Q and a paragraph $p \in \mathcal{P}$ and answers Q by selecting a span in each paragraph p independently, predicting the start and end positions (Devlin et al., 2019). Additionally, the model returns four scores for for every paragraph p corresponding to: if the answer is (*i*) a span in p; (*ii*) *"yes"*; (*iii*) *"no"*; or (*iv*) not in p. At inference time, the model selects the paragraph that has the lowest score for *iv* – the answer is not the paragraph. Our model is based on a pre-trained RoBERTa-large (Liu et al., 2019), fine-tuned on *MMQA*.

Table QA Module Following prior work (Herzig et al., 2020), our table QA module takes as input the question Q and the table T, and selects a subset of the table cells and an aggregation operation to compute the final answer. Specifically, we linearize the table T by rows, with column names prepended to the corresponding cells (Chen et al., 2019). For example, this converts the table in Figure 1 to the following text: *"Row 1: year is 1957; title is a dangerous age; role is David. Row 2..."*. Next, we concatenate the question to the linearized table, and encode them using RoBERTa-large. We then pass the contextualized representation of every token in the table cell to a linear classifier that computes the probability of the token being selected. The score for a cell is the average of its tokens. Cells with probability > 0.5 are selected. Finally, another linear multi-class classifier predicts an aggregation operation from SUM, MEAN, COUNT, YES, NO, and NONE. Aggregation operations are applied on the selected cells, YES and NO operations output *"yes"* or *"no"*, and the NONE operation outputs all selected cells.

Image QA Module Questions with visual information are handled by a multimodal transformer that processes the textual question and pre-computed image features. For a question Q and a set of images $\mathcal{I}$, we feed the model the question and the visual features $\Phi(i)$ extracted from each image $i \in \mathcal{I}$, along with the name of the *WikiEntity* associated with the image. For each image and question, the model predicts an answer from a fixed vocabulary determined by the answers in the training set and 3 special tokens: y_{dtr}, y_{p} and y_{n}. In questions where the expected answer is a phrase (e.g., ImageQ), we return the answer from the image where $p(y_{\text{dtr}})$ is lowest (similar to text QA). In questions where the expected answer is a subset of the images (e.g., Compose(TableQ,ImageQ)), we return all images where $p(y_{\text{p}}) > p(y_{\text{n}})$. Our model is based on the pre-trained model VILBERT-MT (Lu et al., 2020). Visual features are extracted by a vision network Φ, comprised of a Faster R-CNN (Ren et al., 2015) pre-trained on Visual Genome (Krishna et al., 2017).

4.2 MULTIMODALITY QA MODELS

We turn to models that interact with multiple modalities.

Multi-Hop Implicit Decomposition (*ImplicitDecomp*) Our dataset is designed to test reasoning across modalities. As a first attempt towards this goal, we introduce a 2-hop implicit decomposition baseline, capable of combining information scattered across modalities (illustrated in Figure 4).

We first train a question-type classifier, based on RoBERTa-large, that takes a question Q as input, and predicts one of the 16 possible question types (Table 1). The question type can be viewed as a program, specifying the relevant modalities, their order, and the logical operations. For example, if the question type is *Compose(TextQ,TableQ)*, the first hop should be conducted on the table T, and the second hop on the paragraphs $\mathcal{P}$. In each hop, we feed the model with the question Q, the question type, the hop number, and the context of the corresponding modality. The model automatically identifies which part of the question is relevant at the current hop and does not explicitly decompose the question into sub-questions

Figure 4: *ImplicitDecomp*: Modules with the same color share parameters. In this example, the text QA module is activated to produce the 1st-hop answer, and this intermediate answer is fed into the Image QA model to produce the final answer. Question type ([Q Type]) is determined by a separate classifier.

(hence the name *implicit decomposition*). In the second hop, answers from the first hop are also given as input so that the model can leverage this information and conduct cross-modal reasoning to output the final answer. For all single-modality question types (such as *TextQ* and *TableQ*), the model uses only the first hop to get the answer.

Single-Hop Routing (*AutoRouting*) A simple approach for answering questions without cross-modal reasoning is to first determine the modality where the answer is expected to occur, and then run the corresponding single-modality module. We use the aforementioned question type classifier to determine the modality where the answer will appear, route the question and the context for the predicted modality into the corresponding module, and use the output as the final answer.

Question-only and Context-only baselines We run the question-only and context-only baselines, suggested by (Kaushik & Lipton, 2018). Our question-only baseline is BART-large (Lewis et al., 2019): a sequence-to-sequence model that directly generates the answer given the question. For the context-only baseline, we first predict the question type using the classifier described above to pick a target module. We then feed the relevant context to the target module, replacing the question with an empty string.

4.3 TRAINING AND SUPERVISION

Our dataset provides rich supervision including not only the final answer but also question types and intermediate results. Therefore, we can train the pipeline modules in a supervised fashion. Specifically, we train the question type classifier using a cross entropy loss w.r.t the gold question type. For *AutoRouting*, each QA module is trained with the subset of samples whose final answer can be extracted from the corresponding modality. For *ImplicitDecomp*, only one model is trained per modality, which is used to answer both the first-hop and second-hop questions. The question-only and context-only baselines are trained in the corresponding format.

5 EXPERIMENTS

We evaluate models in three different setups: (1) questions that require a single modality to answer (*Single Modality*); (2) questions that require reasoning over multiple modalities (*Multi Modality*); (3) and all questions (*All*). Our evaluation metrics need to support lists of answers, and thus we use average F_1 and Exact Match (EM), as described in Dua et al. (2019), where answers on the gold and predicted lists are aligned. Human performance is estimated with 9 expert annotators, who answered 119 development set questions.

We show results in Table 3. *ImplicitDecomp* achieves significantly higher performance (57.1 F_1) compared to the other baselines, but lower than human performance (84.3 F_1 with provided context and 76.3 F_1 in the open-domain setting over all of Wikipedia), suggesting ample room for improvement. On the *Multi Modality* subset, *ImplicitDecomp*

	Single Modality		Mutli Modality		All	
	EM	F_1	EM	F_1	EM	F_1
Question-only	15.8	17.9	10.6	12.3	13.3	15.2
Context-only	8.0	9.7	8.3	11.1	8.2	10.4
AutoRouting	53.5	60.5	35.5	42.9	44.8	52.0
ImplicitDecomp	**56.6**	**62.8**	**44.9**	**51.1**	**50.9**	**57.1**
Human	80.0	83.0	79.7	85.2	79.8	84.3

Table 3: Test set results

substantially improves performance compared to *AutoRouting* ($42.9 \rightarrow 51.1$), emphasizing the superiority of our approach on multi-hop questions, while on single-hop questions this gap is smaller.

Since automatic evaluation of performance is non-trivial in our setup, we also manually evaluate human performance. In 91.6% of the cases, answers are either identical or semantically equivalent to the gold answer, 4.2% have an error in the question, and 4.2% are human errors. Human errors are owing to the length of the context, resulting in human fatigue (which models do not suffer from).

Analysis To demonstrate that *ImplicitDecomp* indeed performs multi-hop reasoning, successfully answering intermediate questions, we analyze *ImplicitDecomp* predictions for multimodal questions generated using the *Compose*, *Compare* and *Intersect* operations (Table 4). For these questions, we find that when the 1st-hop answer is correct, the model achieves an F_1 of 62.9, whereas when the 1st-hop prediction is incorrect, the F_1 drops to 38.2. This suggests that the model relies on the 1st-hop answer, effectively performing multi-hop reasoning. Last, our question type classifier obtains a high accuracy of 91.4% on the test set.

Type	Question	1st-hop prediction	Final prediction	1st-hop F_1	F_1
Compose	*Who finds the Easter Egg in the show where Mckenna Grace plays an Elementary School Kid?*	Ready Player One	Craig Queen	69.8	50.6
Compare	*Which player for the Miami Heat played the most minutes: Chris Bosh or the player with a corn-rows hairstyle?*	Udonis Haslem	Udonis Haslem	54.9	60.2
Intersect	*Chris Ashworth acted in what 2018 television show that has skyscrapers in cities on its cover?*	Elementary, Without a Trace	Elementary	27.8	51.4

Table 4: Examples where *ImplicitDecomp* correctly answers both the intermediate and the entire question, and a breakdown of the 1st-hop F_1 and final F_1 for the three logical operations: Compose, Compare, and Intersect.

To test weather the compositional questions created are indeed multi-hop, we conducted a qualitative analysis over 50 questions as suggested by Min et al. (2019b). We find that 12% are of the *Weak Distractors* category, that is, questions such as *"What year... "* when there is only one year appearing in the context, making the question easy. 2% have *Redundant evidence*, that is, questions such as *"Which Donald Trump TV show has ..."* where there is only one TV show starring Donald Trump, making the rest of the question redundant. The remaining 86% indeed require multi-hop reasoning.

6 CONCLUSION

We present *MMQA*, a new QA dataset that contains 26,878 examples, 40.0% of which require cross-modality reasoning. We describe a novel framework for generating complex multimodal questions at scale, and showcase the diversity and multimodal properties of the resulting dataset. We evaluate *MMQA* using a variety of models, and confirm that the best model exploits the multimodality of the dataset and takes into account multi-hop reasoning via implicit decomposition. However, human performance substantially exceeds the best model, establishing the need for further research involving multiple modalities in question answering systems, which we hope that our work will drive.

REFERENCES

S. Antol, A. Agrawal, J. Lu, M. Mitchell, D. Batra, C. L. Zitnick, and D. Parikh. Vqa: Visual question answering. In *International Conference on Computer Vision (ICCV)*, pp. 2425–2433, 2015.

Akari Asai, Kazuma Hashimoto, Hannaneh Hajishirzi, Richard Socher, and Caiming Xiong. Learning to retrieve reasoning paths over wikipedia graph for question answering. *ArXiv*, abs/1911.10470, 2020.

Wenhu Chen, Hongmin Wang, Jianshu Chen, Yunkai Zhang, Hong Wang, Shiyang Li, Xiyou Zhou, and William Yang Wang. Tabfact: A large-scale dataset for table-based fact verification. *arXiv preprint arXiv:1909.02164*, 2019.

Wenhu Chen, Hanwen Zha, Zhiyu Chen, Wenhan Xiong, Hong Wang, and William Wang. Hybridqa: A dataset of multi-hop question answering over tabular and textual data, 2020.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions. *arXiv preprint arXiv:1905.10044*, 2019.

J. Devlin, M. Chang, K. Lee, and K. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *North American Association for Computational Linguistics (NAACL)*, 2019.

D. Dua, Y. Wang, P. Dasigi, G. Stanovsky, S. Singh, and M. Gardner. Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs. In *North American Association for Computational Linguistics (NAACL)*, 2019.

Mor Geva, Yoav Goldberg, and Jonathan Berant. Are we modeling the task or the annotator? an investigation of annotator bias in natural language understanding datasets. *arXiv preprint arXiv:1908.07898*, 2019.

Darryl Hannan, Akshay Jain, and Mohit Bansal. Manymodalqa: Modality disambiguation and qa over diverse inputs, 2020.

Jonathan Herzig, P. Nowak, Thomas Müller, Francesco Piccinno, and Julian Martin Eisenschlos. Tapas: Weakly supervised table parsing via pre-training. In *ACL*, 2020.

Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. *arXiv preprint arXiv:2004.04906*, 2020.

Divyansh Kaushik and Zachary C Lipton. How much reading does reading comprehension require? a critical investigation of popular benchmarks. In *EMNLP*, 2018.

Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, et al. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International journal of computer vision*, 123(1):32–73, 2017.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, et al. Natural questions: a benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:453–466, 2019.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Ves Stoyanov, and Luke Zettlemoyer. Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension, 2019.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Jiasen Lu, Vedanuj Goswami, Marcus Rohrbach, Devi Parikh, and Stefan Lee. 12-in-1: Multi-task vision and language representation learning. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

Sewon Min, Eric Wallace, Sameer Singh, Matt Gardner, Hannaneh Hajishirzi, and Luke Zettlemoyer. Compositional questions do not necessitate multi-hop reasoning. In *ACL*, 2019a.

Sewon Min, Eric Wallace, Sameer Singh, Matt Gardner, Hannaneh Hajishirzi, and Luke Zettlemoyer. Compositional questions do not necessitate multi-hop reasoning. *arXiv preprint arXiv:1906.02900*, 2019b.

P. Pasupat and P. Liang. Compositional semantic parsing on semi-structured tables. In *Association for Computational Linguistics (ACL)*, 2015.

P. Rajpurkar. SQuAD. `https://rajpurkar.github.io/SQuAD-explorer/`, 2016.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pp. 91–99, 2015.

A. Talmor and J. Berant. The web as knowledge-base for answering complex questions. In *North American Association for Computational Linguistics (NAACL)*, 2018.

J. Welbl, P. Stenetorp, and S. Riedel. Constructing datasets for multi-hop reading comprehension across documents. *arXiv preprint arXiv:1710.06481*, 2017.

Z. Yang, P. Qi, S. Zhang, Y. Bengio, W. W. Cohen, R. Salakhutdinov, and C. D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

A APPENDIX

Please see separate file for supplementary material.