Symbolic Learning to Optimize: Towards Interpretability and Scalability

Abstract

Recent studies on *Learning to Optimize* (**L2O**) suggest a promising path to automating and accelerating the optimization procedure for complicated tasks. Existing L2O models parameterize optimization rules by neural networks, and learn those *numerical* rules via meta-training. However, they face two common pitfalls: (1) *scalability*: the numerical rules represented by neural networks create extra memory overhead for applying L2O models, and limits their applicability to optimizing larger tasks; (2) *interpretability*: it is unclear what each L2O model has learned in its black-box optimization rule, nor is it straightforward to compare different L2O models in an explainable way. To avoid both pitfalls, this paper proves the concept that we can "kill two birds by one stone", by introducing the powerful tool of *symbolic regression* to L2O. In this paper, we establish a holistic symbolic representation and analysis framework for L2O, which yields a series of insights for learnable optimizers. Leveraging our findings, we further propose a lightweight L2O model that can be meta-trained on large-scale problems and outperformed human-designed and tuned optimizers. Our work is set to supply a brand-new perspective to L2O research, and our codes will be fully released upon acceptance.

1 Introduction

Efficient and scalable optimization algorithms (a.k.a., *optimizers*) are the cornerstone of almost all computational fields. In many practical applications, we will repeatedly perform a certain type of *optimization tasks* over a specific distribution of data. Each time, the inputs that define the optimization problem are new but similar to previous related tasks. We say such an application has a narrow *task distribution*. Conventional optimizers are theory-driven, so they obtain performance guarantees over the classes of problems specified by the theory. Instead of manually designing and tuning task-specific optimizers, one may be naturally interested to pursue more general-purpose and data-driven optimization frameworks.

Learning to optimize (**L2O**) (Almeida et al., 2021; Andrychowicz et al., 2016; Chen et al., 2017; Li & Malik, 2017a; Chen et al., 2021) is an emerging paradigm that automatically develops an optimizer by learning from its performance on a set of optimization tasks. This data-driven procedure generates optimizers that efficiently solve problems similar to those in the training tasks. Although often lacking a solid theoretical basis, the training process shapes the *learned optimizer* according to problems of interest. When the task distribution is concentrated, the learned optimizer can specifically fit the tasks by discovering "shortcuts" that classic optimizers do not take (Li & Malik, 2017a;b). L2O has demonstrated many practical benefits including faster convergence and/or better solution quality (Chen et al., 2021), even saving clock time (Li et al., 2020b) and hardware energy (Li et al., 2020a).

With promising progress being made, the questions persist: *how far is L2O from becoming principled science? To what extent can we trust L2O as being mature for real applications?* As a fast-growing new field, fascinating open challenges remain concerning L2O, among which two particular barriers arise our attention in this work:

- **Interpretability.** The learned optimizers are often *hard to interpret*. Traditional algorithm design follows analytic principles and admits "white box" symbolic forms, which are clear to explain, analyze, troubleshoot, and prove. In contrast, existing L2O approaches fit update models using sophisticated data-driven predictors such as neural networks. As a result, it

is unclear what rules have been learned in those "black boxes", prohibiting their further explainable analysis and comparison.

- **Scalability.** The learned optimizers can be *hard to scale*. L2O methods use learnable predictors to fit update rules, which incur extra overhead in memory that grows proportionally with the amount of optimization task variables. Moreover, the training of a learned optimizer often involves backpropagating through a full unrolled sequence for the parameter updates in the optimization tasks, and the memory cost grows fast with the unroll length. The scale of that growth results in complexities that current L2O methods cannot handle.

Our proposed solution, centered at addressing the two research gaps, is a brand-new **symbolic representation and interpretation framework for L2O**. While benefiting from large modeling capacity, L2O update rules fit by numerical predictors are inexplainable and memory-heavy. In contrast, the symbolic representations of traditional optimizers enjoy low memory overhead and clear explainability. We aim to integrate the strengths of symbolic forms into L2O. We propose to convert a numerical L2O predictor into a symbolic form that preserves the same problem-specific performance and is still tunable. Those symbolic rules are light, scalable, and interpretable. They can even be made tunable and subject to further meta testing, by a lightweight trainable re-parameterization. Based on them, we will further develop a set of L2O interpretability metrics.

Our main **technical innovations** are summarized below:

- We build the first *symbolic learning to optimize* (**symbolic L2O**) framework that is generally applicable to existing L2O approaches. That include defining the optimizer symbolic space and the fitting approach to convert a numeric L2O to its symbolic counterpart.

- Under the symbolic L2O framework, we establish a unified scheme for L2O interpretability. Our synergistic analysis in the symbolic domain uncovers a number of new insights that are otherwise difficult to observe, including what "shortcuts" L2O methods essentially learn and how they differs across various methods.

- The lightweight symbolic representation also allows L2O to scale better, and we introduce a lightweight trainable re-parameterization to enable further fine-tuning of symbolic rules. For the first time, we obtain a symbolic L2O method that can be meta-trained on ResNet-50 level (23.5 million parameters) optimizee within 30 GB GPU memory, and achieved the state-of-the-art (SOTA) performance when applied to training larger (ResNet-152, 58.2 million parameters) or very different deep models (MobileNet v2 (Sandler et al., 2018)) on various datasets, outperforming existing manually designed and tuned optimizers.

2 RELATED WORKS

L2O lies at the intersection of ML and optimization research. It overlaps with meta-learning (Vilalta & Drissi, 2002; Hospedales et al., 2021), which contributes a significant portion of L2O development (Andrychowicz et al., 2016; Li & Malik, 2017a). L2O captures two main aspects of meta learning: rapid learning within each task, and transferable learning across many similar tasks. Using data-driven *predictors* to fit update rules, recent L2O approaches have shown success for a wide variety of problems, from convex optimization (Gregor & LeCun, 2010) and nonconvex optimization (Andrychowicz et al., 2016), to black-box optimization (Chen et al., 2017) and combinatorial optimization (Khalil et al., 2017). Application areas benefiting the most from L2O methods include signal processing and communication (Borgerding et al., 2017; Balatsoukas-Stimming & Studer, 2019), image processing (Zhang & Ghanem, 2018; Corbineau et al., 2019), medical imaging (Liang et al., 2020; Yin et al., 2021) and computational biology (Cao et al., 2019; Chen et al., 2019).

The pioneering L2O work (Andrychowicz et al., 2016) leverages a long short-term memory (LSTM) as the coordinate-wise predictor, which is fed with the optimizee gradients and outputs the optimizee parameter updates. Chen et al. (2017) takes the optimizee's objective value history as the input state of a reinforcement learning agent, which outputs the updates as actions. To enhance L2O generalization, (Lv et al., 2017) proposes random scaling and convex function regularizers tricks. (Wichrowska et al., 2017) introduces a hierarchical RNN to capture the relationship across the optimizee parameters and trains it via meta-learning on the ensemble of small representative problems.

Training LSTM-based L2O models is however notoriously difficult, that is rooted in the LSTM-style unrolling during L2O meta-training (Tallec & Ollivier, 2017; Metz et al., 2018; Pascanu et al., 2013; Parmas et al., 2019). A practical optimizer may need to take thousands or more of iterations. However,

since naively unrolling LSTM to this full length is impractical for both memory cost and trainability by gradient propagation. Most LSTM-based L2O methods (Andrychowicz et al., 2016; Chen et al., 2017; Lv et al., 2017; Wichrowska et al., 2017; Metz et al., 2018; Cao et al., 2019) take advantage of truncating the unrolled optimization, yet at the price of the so-called "truncation bias" (Lv et al., 2017) that hampers their learned optimizer's generalization to unseen tasks (Chen et al., 2020).

Most L2O approaches are "black boxes" with neither theoretical backup nor clear explanation on what they learn. A handful of efforts have been made on "demystifying" L2O, mainly about linking or reducing their behaviors to those of some analytic, better understood optimization algorithms. Maheswaranathan et al. (2020) offers to analyze and visualize the learned optimizers, and discover that they have learned interpretable mechanisms including momentum, gradient clipping, learning rate schedules, etc. Another well-known success was on interpreting the learned sparse coding algorithm (Gregor & LeCun, 2010), as related to a specific matrix factorization of the dictionary's Gram matrix (Moreau & Bruna, 2017), to the projected gradient descent trade-off between convergence speed and reconstruction accuracy (Giryes et al., 2018), or simply reduced to the original iterative algorithm with data-driven hyperparameter estimation (Liu et al., 2019). Other examples include analyzing the learned alternating minimization on graph recovery (Shrivastava et al., 2020), and an analogy between deep-unfolded gradient descent and Chebyshev step-sizes (Takabe & Wadayama, 2020). However, all existing interpretation works are highly restricted to some specific problem or algorithm involved.

3 TECHNICAL APPROACH

3.1 NOTATION AND PRELIMINARIES

Without loss of generality, let us consider an optimization problem $\min_{\mathbf{x}} f(\mathbf{x})$ where $\mathbf{x} \in \mathbb{R}^d$. A classic optimizer usually iteratively updates $\mathbf{x}$ based on a handcrafted rule. For example, the first-order gradient descent algorithm takes an update at iteration t based on the local gradient at the instantaneous point $\mathbf{x}_t : \mathbf{x}_{t+1} = \mathbf{x}_t - \alpha \nabla f(\mathbf{x}_t)$, where α is the step size.

L2O has much greater room to find flexible update rules. We define $\mathbf{z}_t$ as the optimization historical information available at time t, such as including the current/past iterates $\mathbf{x}_0, \ldots, \mathbf{x}_t$, and/or their gradients $\nabla f(x_0), \ldots, \nabla f(\mathbf{x}_t)$, etc. L2O models an update rule by a *predictor* function g of $\mathbf{z}_t$: $\mathbf{x}_{t+1} = \mathbf{x}_t - g(\mathbf{z}_t, \phi)$, where the mapping of g is parameterized by ϕ. Finding an optimal update rule can be formulated mathematically as searching for a good ϕ over the parameter space of g. Practically, g is often a neural network (NN). Since NNs are universal approximators (Hornik et al., 1989), L2O has the potential to discover completely new update rules without relying on existing rules. In order to find a desired ϕ associated with a fast optimizer, (Andrychowicz et al., 2016) proposed to minimize the weighted sum of the objective function $f(\mathbf{x}_t)$ over a time span T:

$$\min_{\phi} \mathbb{E}_{f \in \mathcal{T}} \left[\sum_{t=0}^{T-1} w_t f(\mathbf{x}_t) \right], \quad \text{with} \quad \mathbf{x}_{t+1} = \mathbf{x}_t - g(\mathbf{z}_t, \phi), \ t = 0, \ldots, T-1, \quad (1)$$

where $w_0, \ldots, w_{T-1}$ are the weights whose choices depend on empirical settings. T is also called the unrolling length. f represents a sample optimization task from an ensemble $\mathcal{T}$ that represent the target task distribution. Note that ϕ determines the objective value through determining the iterates $\mathbf{x}_t$. L2O solves the problem (1) for a desirable ϕ and correspondingly the update rule $g(\mathbf{z}_t, \phi)$.

A typical L2O workflow is divided into two stages (Chen et al., 2021): a *meta-training* stage that learns the optimizer with a set of similar optimization tasks from the task distribution; and a *meta-testing* stage that applies the learned optimizer to new unseen optimization tasks. The meta-training process often occurs offline and is time consuming. However, the online application of the method at meta-testing is (aimed to be) time saving.

3.2 MOTIVATION AND CHALLENGES

If we take a unified mathematical perspective, the execution of an optimizer can be represented either through a *symbolic* rule, or by *numeric* computation. Current L2O approaches parameterize their update rules g by *numerical predictors* that can be learned from data via meta-training. They often choose sophisticated predictive models such as LTSMs (Andrychowicz et al., 2016; Lv et al., 2017; Chen et al., 2020; Wichrowska et al., 2017), that predict the next update based on the current and historical optimization variables.

Despite the blessing of large learning capacity, the NN-based update rules are *uninterpretable* "black boxes". It is never well understood what rules existing L2O models have learned; nor is it easy to compare different L2O models and assess which has discovered more advanced rules. Moreover, numerical predictors, especially RNN-based ones, limit L2O scalability through severe *memory bottlenecks* (Metz et al., 2019; Wu et al., 2018). Their meta-training involves backpropagating through a full unrolled sequence of length T, for the parameter updates in their optimization task. At meta-testing time (though requiring less memory than meta-training), one has to store RNN's own parameters ϕ and hidden states, which are still far from negligible.

Those important gaps urge us to look back at symbolic update rules. Almost all traditional optimizers can be seen as formula-based symbolic methods within our framework, such as stochastic gradient descent (SGD), Adam, RMSprop, and so on. Their forms hinge on manual discovery and expert crafting. A symbolic optimizer has little memory overhead, and can be easily interpreted or transferred like an equation or a computer program (Bello et al., 2017; Runarsson & Jonsson, 2000; Orchard & Wang, 2016; Bengio et al., 1994). A handful of L2O methods tried to search for good symbolic rules from scratch, using evolutionary or reinforcement learning (Bello et al., 2017; Real et al., 2020; Runarsson & Jonsson, 2000; Orchard & Wang, 2016; Bengio et al., 1994). Unfortunately, those direct search methods quickly become inefficient when the search space of symbols becomes large. The open question remains as : *how to strike the balance between the tractability of finding an update rule, and the effectiveness, memory efficiency and interpretability of the found rule?*

In what follows, we will unify symbolic and numerical optimizers with a synergistic representation and analysis framework. In brief, we stick to numerical predictors at meta-training for its modeling flexibility and ease of optimization. We then convert numerical predictors to symbolic rules, which preserve almost the same effectiveness yet have negligible memory overhead and clear explainability. Facilitated by the new symbolic representations, we will develop a new suite of L2O interpretability metrics, and can meanwhile scale up L2O to much larger optimization tasks.

3.3 A SYMBOLIC DISTILLATION FRAMEWORK FOR L2O

We will first demonstrate how to convert the update predictor g: $\mathbf{x}_{t+1} = \mathbf{x}_t - g(\mathbf{z}_t, \phi)$ into *symbolic* forms that preserve the same effectiveness. Contrasting with numerical forms, symbolic rules bear two advantages: (i) being **white-box** functions and enabling **interpretability** (see Section 3.3); and (ii) being much **lighter**, e.g., unlike RNNs that have to carry their own weights and hidden states, which removes one memory bottleneck for **scaling up** to large optimization tasks (see Section 3.4).

To achieve this goal, we leverage a classical tool of symbolic regression (SR) (Cranmer, 2020), a type of regression analysis that searches the space of mathematical expressions to find an equation that best fits a dataset, both in terms of accuracy and simplicity. Different from conventional regression techniques that optimize the parameters for a pre-specified model structure, SR infers both model structures and parameters from data. Popular algorithms rely on genetic programming to evolve from scratch (Runarsson & Jonsson, 2000; Gustafson et al., 2005; Orchard & Wang, 2016). However, SR algorithms are slow on large problems and rely on many heuristics, if evolving from scratch (Runarsson & Jonsson, 2000; Gustafson et al., 2005; Orchard & Wang, 2016). They will become highly inefficient if further being entangled with the rule search, like existing methods (Bello et al., 2017; Runarsson & Jonsson, 2000; Orchard & Wang, 2016).

Inspired by the idea of "knowledge distillation" (Gou et al., 2021), we propose a *symbolic distillation* approach that **decouples** the rule search step (in the numeric domain) and the subsequent representation step (to the symbolic domain). We will first learn a numerical predictor g using existing L2O methods (e.g., RNN-based), and then apply SR to fit a symbolic form that approximates the input-output relationship captured by g. In this way, the former step can stay with the more efficient gradient-based search in a continuously parameterized space.

Specifically, we will generate an off-line database $\mathcal{D}$ of $(input, out)$ pairs, then to train SR to minimize a fitting loss on $\mathcal{D}$. Each pair is obtained from running the learned g on an optimization task: $input$ is a sequence of $\mathbf{z}_t$ generated during optimization within the fixed unrolling length T; and $output$ is the corresponding sequence of the RNN teacher $g(\mathbf{z}_t, \phi)$. The training procedure of SR is to iteratively mutate a population of equation candidates, and filter out the better performing ones to come up with better equations. The final output of SR is a population of best equations composed of variables from $input$ that best fit $output$ of its RNN teacher $g(\mathbf{z}_t, \phi)$ on the target task distribution, using operaters coming from the pre-defined search space.

3.4 CONCRETIZING THE SYMBOLIC DISTILLATION FRAMEWORK

To make symbolic distillation for L2O executable, two open questions have to be defined: **(i) "what to fit"**, i.e., what symbolic operators we use as building blocks to compose the final equation; and **(ii) "fit on what"**, i.e., what information we consider as SR input operands. These questions are open-ended and problem-dependent, and can be rather inconsistent among different L2O methods. To make our approach more generalizable, we choose relatively straightforward options for both.

For the first question, the selection of symbolic operators to use, we adopt the following set: $\{+, -, \times, /, (\cdot)^2, \sqrt{\cdot}, \exp(\cdot), x^y, \tanh, \text{arcsinh}, \sinh, \text{relu}, \text{erfc}\}$. The first eight operators are adopted since they are the basic building blocks of several traditional optimizers such as Adam/Momentum, and the rests are adopted since they are either the nonlinear activation functions used by typical L2O numerical predictors, or convey certain (upate) thresholding effects which often expected and empirically used in existing deep learning optimization (Sun, 2019). For a few operators whose input ranges are constrained to non-negative only, we extend them to be valid for any real-valued input (e.g., $\sqrt{x}$ is extended to $\text{sign}(x) * \sqrt{|x|}$, and x^y is extended to $\text{sign}(x) * |x|^y$, etc).

For the second question, we use the exact input variables of the numerical L2O (e.g., coordinate wise gradients) as a default option throughout this paper. To enable further flexibility for practitioners, we also enable to expand the input operand set, to provide additional optimization-related features and let the SR procedure decide which to use or not. On a high level, we model the obtained symbolic equation as a Finite Impulse Response (FIR) filter, and set a maximum horizon T of the input variables. In the following parts, if without further explanation, T is set to 20 (the latest 20 records of each input variables are visible to symbolic regression module). As another practical level consideration, in order to appropriately capture the non-linear dynamics of certain operators, the magnitude of input variables should better be re-scaled. In this paper, we re-scale all input variables so that they have the variances of 1.

We conduct a proof-of-concept experiment to distill a learned L2O rule using LSTM-based L2O (Andrychowicz et al., 2016). The input sequence is $\mathbf{z}_t = \{\nabla f(\mathbf{x}_t,)\nabla f(\mathbf{x}_{t-1}), ..., \nabla f(\mathbf{x}_{t-T+1})\}$, i.e., the current and past gradients within an unrolling length $T = 20$. The L2O meta-training was performed on multiple randomly-initialized LeNets on the MNIST dataset. To fit SR, we adopt a generic mathematical operator space defined in (Bello et al., 2017), and a classical genetic programming-based SR approach (Koza, 1994) that iteratively filters and randomly mutated equation candidates. The SR algorithm can score the equation complexity level as a function of the operator number, operator type diversity, and input variable number used (Cranmer et al., 2020). Hence, we can apply a range of complexity levels, and obtain a group of SR fitting rules from simple to complicated. One example of our distilled symbolic rules is displayed as (c_i, $i = 0,..., 19$, are scalars, omitted for simplicity):

$$\Delta x_t = \underbrace{0.013 e^{-0.835 \text{asinh}(t)}}_{\text{Time-decaying step size}} \left(\text{erfc}\left(\sinh\left(\nabla f(\mathbf{x}_t)\right) + \underbrace{\sum_{i=0}^{19} c_i \tanh\left(\nabla f(\mathbf{x}_{t-i})\right)}_{\text{``momentum''}} \right) - 1 \right) \quad (2)$$

3.5 INTERPRETABILITY FROM SYMBOLIC L2O REPRESENTATIONS

For general ML models, the interpretability is referred to as *the ability of the model to explain or to present in understandable terms to a human* (Doshi-Velez & Kim, 2017). When it specifically comes to an L2O model, its interpretability will be uniquely linked to the immense wealth of domain knowledge in optimization, from rigorous guarantees to empirical observations (Nocedal & Wright, 2006). We hence define **L2O interpretability** as *how well a learned optimizer's behavior can align with the optimization domain knowledge, or be understandable to the optimization practitioners*.

In fact, one may easily notice that the symbolic forms of L2O possess certain levels of "baked-in" interpretability. For example, the update rule (2) immediately supplies a few interesting observations: L2O discovers a momentum-like historic weight averaging mechanism, a time-decaying step size, as well as several normalization-like or (nonlinear) gradient clipping operations such as $\text{erfc}, \sinh$ and $\tanh$. All these are human-understandable as they represent well-accepted practices in deep learning optimization (Sun, 2019).

Our target is to establish a more principled and generally applicable L2O interpretability framework. The new framework will be dedicated to capturing L2O characteristics, quantifying their behaviors, and meaningfully comparing different learned optimizers. We propose two novel metrics that dissect L2O along two dimensions: (i) *Temporal Perception Field* (TPF), i.e., how long an input sequence $\mathbf{z}_t$ (past optimization trajectory) the learned optimizer "effectively" takes advantage of; and (ii) *Mapping Complexity* (MC), i.e., how complicated a predictor model g needs to "effectively" be.

The estimations of TPF and MC are both facilitated in the symbolic domain. For TPF, take Eqn. (2) for example again: the predicted update at time t involves a weighted (nonlinear) summation of past gradients $\nabla f(\mathbf{x}_{t-i}), i = 0, \cdots, T$ (set as 20). c_i can be seen as importance indicators for $\nabla f(\mathbf{x}_{t-i})$, and a preliminary idea to define TPF is simply the weighted mean of historical lengths:

$$\text{Temporal Perception Field} = \sum_{i=0}^{T-1} \frac{|c_i|}{\sum_{i=0}^{T-1} |c_i|} \cdot i \tag{3}$$

One challenge will be to estimate TPF when more complicated symbolic forms arise, e.g., the update rule has more heterogeneous compositions such as $a_i \left(\nabla f(\mathbf{x}_{t-i})\right)^{p_i} + b_i \left(\nabla f(\mathbf{x}_{t-i})\right)^{q_i} + c_i \tanh\left(\nabla f(\mathbf{x}_{t-i})\right)$. In such situations, more generic designs of TPF will have to be investigated and validated such as $\sum_{i=0}^{T-1} \frac{|a_i|+|b_i|+|c_i|}{\sum_{i=0}^{T-1} |a_i|+|b_i|+|c_i|} \cdot i$: we leave as future work.

For MC, the SR approach in (Cranmer et al., 2020) has defined a complexity score for any resultant equation, that is calculated based on the total number and types of operators as well as input variables used for fitting it. Based on that tool, we set a threshold on the maximally allowable difference between the original numerical predictor and its symbolically distilled form (over some $(input, out)$ validation set), and choose the minimum-complexity symbolic equation that falls under this threshold: its complexity score is used to indicate the intrinsic mapping complexity.

The above two definitions are in no way unique nor perfect: they are intended as our pilot study effort to quantify the understanding of L2O behaviors. We will extend the above ideas to comprehensively examining the existing L2O approaches. We aim at observing the relationship between the two metrics, and their empirical connections to L2O's convergence speed, stability, as well as transferrability under task distribution shifts. Extensive results will be reported in Section 4, from which we conclude a few hypotheses, including: (i) an L2O with larger TPF will converge faster and more stably on instances from the same task distribution, since it exploits more global optimization trajectory structure for this class of problems; and (ii) an L2O with smaller MC will be more transferable under distribution shifts, if meta-tuning (adaptation) is performed, owing to the predictor model's larger flexibility. We defer more details later in section 4.2 and the appendices A, B.

From the general taxonomy of interpretable deep learning (Li et al., 2021), our approach belongs to the category of using *surrogate models*, i.e., fitting a simple and interpretable model (symbolic equation) from the original complicated one (numerical predictor), and using this surrogate model's explanations to explain the original predictions. Our new interpretability metrics and analyses will be the first-of-its-kind for L2O. The findings will provide troubleshooting tools for existing L2O methods, and insights for designing new L2O methods.

3.6 SCALABLE L2O TUNING WITH SYMBOLIC REPRESENTATIONS

Symbolic L2O forms can not only be used as "frozen" update rules at testing, but also be tweaked to provide light-weight meta-tuning ability. Taking Eqn. (2) for example again, we can keep the equation form but set all c_i to be trainable coefficients, and continue to fit them on new data, using differentiable meta-training or other hyperparameter optimization (HPO) methods (Feurer & Hutter, 2019). This "tunability" is useful for *adapting* a learned optimizer to a shifted task distribution, such as to *larger optimization tasks* since the optimizer overhead now is much lighter compared to the original numerical predictor. The overall procedure of *training numerical L2O → distill symbolic rule → meta tuning on new task* are illustrated in Fig. 1.

4 INTERPRETABILITY AND SCALABILITY EVALUATIONS FOR SYMBOLIC L2O

In this section, we conduct a series of experiments for the proposed symbolic distillation approach for L2O. We first verify the ability of symbolic regression to recover underlying optimization rules

Figure 1: The proposed symbolic regression workflow for L2O models: The **meta training** step enjoys the ease of optimization in the neural network function representation space, and come up with a numerical L2O model; the **symbolic regression** step distill a light weight surrogate symbolic equation from the numerical L2O model; the **meta tuning** step make the distilled symbolic equation again amendable for re-parameterization.

through sanity checks in section 4.1, then leverage the interpretability of symbolic L2O to quantize several properties of the numerical L2O models in section 4.2, finally, we evaluate the scalability of the symbolic L2O in section 4.3.

4.1 SANITY CHECKS FOR SYMBOLIC REGRESSION ON OPTIMIZATION TASKS

With a handful of adaptation approaches discussed in section 3.3 (operator selection and modification, injection of inductive bias with processed features, variable magnitude re-scaling, etc.), the symbolic regression are adequately armd to be capable to recover the underlying rule of the optimizers. A sanity check for regressing known optimizers are presented in table 1. In the table, the gradient data are sampled from training a ResNet-50 on Cifar10 dataset, and the most recent 20 timesteps are provided for symbolic regression. The hyperparameters for symbolic regressions are tuned (more details for symbolic regression hyperparameters are put in Appendix C. As can be seen in the results, the symbolic regression almost faithfully reproduce the known equations.

Table 1: Sanity checks for SR's ability to retrieve known equations. "Seconds" corresponds to the computation time accomplished via a 2.6 GHz Intel Core i7 CPU with 16 GB 2400 MHz DDR4 Memory.

Target Equation	Recovered Equation	R^2-score	Seconds
$-0.01 * g_t$	$-0.01 * g_t$	1.0	49
$\sum_{i=0}^{10}(1 - 0.1i)g_{t-i}$	$g_t + g_{t-1} + 0.81g_{t-2} + 0.72g_{t-3} + 0.56 * g_{t-4} + 0.44g_{t-5} + 0.44 * g_{t-6} + 0.30 * g_{t-7} + 0.20g_{t-8}$	0.94	126
$g_t^2 + g_{t-1} + 2g_{t-2} + e^{g_{t-4}}$	$0.997g_t^2 + 2\tanh(0.47g_{t-1} + g_{t-2} - 0.101g_{t-9}) + 1.0007 + g_{t-4}$	0.98	256
Momentum(0.6)	$g_t + 0.6g_{t-1} + 0.35g_{t-2} + 0.22g_{t-3} + 0.12g_{t-4} + 0.05\mathrm{asinh}(g_{t-5} + g_{t-6})$	0.97	90
Adam(0.9)	$(\sum_{i=0}^{19} a_i g_{t-i} + b_i \mathrm{asinh}(g_{t-i}))/\sqrt{\sum_{i=0}^{19} c_i g_t^2}$ (Though some noisy asinh() appears, overall R^2-score remains high)	0.89	879

4.2 INTERPRETABILITY OF TRADITIONAL OPTIMIZERS AND LEARNED OPTIMIZERS

In this section, we align the learned optimizer's behavior with the optimization domain knowledge using the two quantization metrics defined in section 3.5, the Temporal Perception Field (TPF) and Mapping Complexity (MC). The results are presented in Table 2 and 3. To diversify the evaluations, in Table 2 and 3, we consider 3 different problems (optimization tasks) and 6 different numerical L2O backbones. The three problems are:

$$\mathcal{P}_1 : \min_{\boldsymbol{x}} : ||\boldsymbol{Ax} + \boldsymbol{b}||_2^2 + 0.5\boldsymbol{c}^{\mathrm{T}}\cos(\boldsymbol{x}) \qquad \mathcal{P}_2/\mathcal{P}_3 : \min_{\boldsymbol{x}} \mathrm{CrossEntropy}\,(\mathrm{labels}, f(\mathrm{datas}; \boldsymbol{x})) \quad (4)$$

The first problem $\mathcal{P}_1$ is a non-convex generalized Rastrigin function series used in Cao et al. (2019), where $\boldsymbol{A} \in \mathbb{R}^{10 \times 10}, \boldsymbol{x} \in \mathbb{R}^{10}$, elements in $\boldsymbol{A}, \boldsymbol{b}, \boldsymbol{c}$ are i.i.d. and sampled from $\mathcal{N}(0, 1)$. In $\mathcal{P}_2/\mathcal{P}_3$, the the datas and labels come from the MNIST dataset, and $\boldsymbol{x}$ is the parameters of an MLP with Relu activations and has hidden layers (50,20) for $\mathcal{P}_2$ and (50,20,20,12) for $\mathcal{P}_3$.

The six numerical L2O backbones are referred to as DM (Andrychowicz et al., 2016), RP (Lv et al., 2017), DM+CL+IL (imitation learning and curriculum learning (Chen et al., 2020) applied to DM (Andrychowicz et al., 2016)), RP+CL+IL (CL and IL (Chen et al., 2020) applied to RP (Lv et al., 2017)), RP_s (RP parameterized with fewer coefficients: its input projection reduced from 20 dimensional to 6 dimensional, and two layer LSTM reduced to one layer with half number of coefficients), and RP_si (enriched the input feature set of RP_s by adding a new set of Adam-type gradient feature).

Empirical observations. From table 3, We make the following observations. First, larger TPF helps L2O model to converge better, as DM+CL+IL is better than DM, and RP+CL+IL is better than RP. Second, with more diverse gradient features, the models are learned to have smaller mapping complexity, while still outperforms the model with use simple gradient features and high mapping complexity. This is verified by the performances comparison of RP_si > RP > DM, while the input features of RP_si is the most diverse one.

Table 2: The comparison of input feature set, mapping function, temporal perception field and mapping complexity across several optimizers.

Optimizers	SGD	$mom(\beta)$	$Adam(\beta_1, \beta_2)$	DM	RP
Input Features Set	g_t	g_t	$\hat{m}_t$	g_t	$\hat{m}_t, \hat{g}_t$
Mapping Function	$\psi(g_t) = -\alpha g_t$	$m_t = \beta m_{t-1} + (1-\beta)g_t$
$\psi(g_t) = -\alpha m_t$
$\psi(g_t) = -\alpha(1-\beta)\sum_{i=0}^{\infty}\beta^i g_{t-i}$	$\psi(\hat{m}_t) = -\alpha\hat{m}_t$
$\hat{m}_t$ defined in Eq. 5.	$LSTM(g_t)$	$LSTM(\hat{m}_t, \hat{g}_t)$
Temporal Perception Field	0	$\frac{\beta}{1-\beta}$	0	See Table. 3	See Table. 3
Mapping Complexity	1	$\approx \frac{1}{2}i_0^2$, where $\beta^{i_0} = 0.05$	1 (when viewing $\hat{m}_t$ as input)	See Table. 3	See Table. 3

Table 3: Above half: the Temporal Perception Field and Mapping Complexity of several learned L2O models. The values are averaged across three different problems $\mathcal{P}_1/\mathcal{P}_2/\mathcal{P}_3$. The tuples indicate the corresponding models have more than one type of inputs. Below half: the performance of numerical and their distilled symbolic equations, learned over $\mathcal{P}_2$ and evaluated over $\mathcal{P}_3$. The detailed interpretation of the results presented in this table is in the Appendix B, which also includes an optimization trajectory plot, Figure 4.

Numerical L2O Models	DM	DM+CL+IL	RP	RP+CL+IL	RP_s	RP_si
Temporal Perception Field	25.2	27.4	(5.3, 2.4)	(5.7, 3.1)	(5.5, 2.2)	**(4.6, 2.0, 4.1)**
Mapping Complexity	182.9	220.6	104.7	121.4	80.3	**67.0**
Eva Loss by numerical L2O	0.23 ± 0.13	0.19 ± 0.16	0.12 ± 0.07	0.11 ± 0.04	0.09 ± 0.05	**0.08 ± 0.05**
Eva Loss by distilled equation	0.33 ± 0.26	0.33 ± 0.19	0.14 ± 0.09	0.12 ± 0.09	0.10 ± 0.06	**0.09 ± 0.04**

4.3 SCALABILITY EVALUATIONS

In this section, we evaluate the scalability of symbolic L2O on large scale optimizees. Due to the memory burden of LSTM based L2O models, meta-training on large scale problems are considered as challenging tasks for LSTM based L2O model (Chen et al., 2020; Bello et al., 2017), as most L2O model work with small scale optimizee that is difficult to upscale to ResNet-50-level problems (Chen et al., 2020; Bello et al., 2017; Andrychowicz et al., 2016; Lv et al., 2017). However, the simple form and the hidden-states-free property of symbolic L2O enable it to be fast in inferencing and has little memory overhead for training, which brings better potential to scale up to these environments.

In the following, we show through experiments that meta-tuning a symbolic L2O on large scale neural network optimizees is not only feasible, but also leads to better performance than hand-designed and tuned optimizers. Since the RP_si shows the best empirical performance (shown in table 3 in the below half), we use the RP_si as the base numerical L2O model for symbolic distillation. We first picked train the RP_si model

The selection of the teacher L2O model. We select the best performing numerical L2O, the RP_si model (discussed in section 4.2) to perform symbolic distillation. We first meta-pre-train this RP_si teacher model on $\mathcal{P}_1$ to get an initialization. We then distill it into the symbolic equation, and meta-fine-tune the distilled symbolic equation on the large scale optimizees (problems).

The distilled symbolic equations used for meta-fine-tune. Recall that RP_si has three types of input features, the first two are the same as the RP model(Lv et al., 2017):

$$\hat{m}_t = m_t v_t^{-1/2}, \hat{g}_t = g_t v_t^{-1/2} \tag{5}$$

Table 4: Comparison of the meta-tuned symbolic rule and the traditional optimizers. Evaluation results are shown for optimizing a ResNet50 on Cifar10.

Optimizers	momentum=0.5			momentum=0.9		
	lr=0.001	lr=0.01	lr=0.1	lr=0.001	lr=0.01	lr=0.1
SGD (no cosine lr decay)	94.53	93.70	94.10	95.20	94.82	95.31
SGD (with cosine lr decay)	93.25	94.37	94.87	92.12	93.57	94.03
Symbolic L2O	**95.40**					

where g_t is the gradient, $m_t = [\beta_1 m_{t-1} + (1 - \beta_1)g_t]/(1 - \beta_1^t)$, and $v_t = [\beta_2 v_{t-1} + (1 - \beta_2)g_t^2]/(1 - \beta_2^t)$. The third input feature $\hat{n}_t$ contains trainable parameters $k_1, k_2, l_1, l_2, \alpha_1, \alpha_2$. The $\hat{n}_t$ is slightly modified from $\hat{m}_t$, where g_t in $\hat{m}_t$ becomes $k_1 g_t^{1+\alpha_1} + k_2 g_t^{1-\alpha_1}$, and g_t^2 in v_t becomes $l_1 g_t^{2+\alpha_2} + l_2 g_t^{2-\alpha_2}$. As previously shown in table 3, the RP_si model has the smallest mapping complexity and the temporal perception field. This is empirically verified by the output of symbolic distillation: the distilled rules for RP_si are all simple and take similar forms. We summarized this form as follows, and fix this form, to only tune the coefficient during the meta-fine-tune stage:

$$\psi(\mathcal{G}; W) = -\sum_{g \in \mathcal{G}} \sum_{\tau=0}^{L} [W]_{g,\tau} \cdot \gamma \tanh(g_{t-\tau}/\gamma) \tag{6}$$

where $\mathcal{G} = \{\hat{m}_t, \hat{g}_t, \hat{n}_t\}$ is the gradient features, $W \in \mathbb{R}^{3 \times L}$ and γ is the trainable coefficients. We verified that the equation 6 accurately fits the original RP_si, since the R^2 score is large (0.88), the evaluation performance is close (shown in table 3 at the below half), and the plotted input-output curve is close (shown in figure 3 in Appendix B.

We picked three large scale optimizees for our evaluations: ResNet-50, ResNet-152 and MobileNetV2, and studied two different datasets on these optimizees: the Cifar-100 and the Cifar-10. The scale of the optimizee is large enough so as to forbid a dozen of previous L2O models to train on normal size single GPU. Thanks to the light-weight property, the meta-training process for our symbolic L2O only takes less than 30GB GPU memory over ResNet-50. Also, thanks to the initialization from pre-trained RP_si, it only takes one pass for the 200-epochs' meta training then the symbolic L2O is ready for evaluations.

The evaluation results are plotted in Fig.2 and Table 4. In the evaluations, we include the following hand designed optimizers as baselines for comparison: SGD optimizer with learning rate selected from (0.1, 0.01, 0.001), momentum selected from (0.5, 0.9, 0.99), with and without the nestrov momentum, with and without cosine learning rate annealing, and the Adam optimizer with learning rate selected from (0.01, 0.001). In the legend of Fig. 2, default values are: learning rate = 0.1, momentum = 0.9, without using nestrov momentum, without using cosine learning rate annealing. The hyperparameters different from the default values are plotted in the figure. The LSTM based requires significantly more memory to apply to large scale problems, hence they are not included in this section.

As can be observed in the figure, our proposed symbolic L2O model outperformed most human-engineered optimizers not only in convergence rate, but also in final accuracies.

Figure 2: The performance comparison of the meta-fine-tuned symbolic L2O, and several traditional optimizers as baselines. The Symbolic L2O achieved the best performance even with the laboriously tuned traditional optimizers.

5 CONCLUSION

In this work, we proposed a principled learning and analysis framework for symbolic L2O. Our symbolic framework enabled better interpretability and scalability of L2O models, by first numerically learn a neural network based L2O model that enables a free room of optimization, then distill it into symbolic equation that links the immense wealth of optimization domain knowledge. This work revealed multiple insights that we believe are important for the L2O society, paving the way to make the L2O both more interpretable and boost the SOTA performance and scalability of L2O.

6 REPRODUCIBILITY CHECKLIST

To ensure reproducibility, we use the Machine Learning Reproducibility Checklist v2.0, Apr. 7 2020 (Pineau et al., 2021). An earlier version of this checklist (v1.2) was used for NeurIPS 2019 (Pineau et al., 2021).

- For all **models** and **algorithms** presented,
  - **A clear description of the mathematical settings, algorithm, and/or model.** We clearly describe all of the settings, formulations, and algorithms in Section 4.2.
  - **A clear explanation of any assumptions.** Our assumptions are justified in 4.2.
  - **An analysis of the complexity (time, space, sample size) of any algorithm.** We do not make the analysis.

- For any **theoretical claim**,
  - **A clear statement of the claim.** We do not make theoretical claims.
  - **A complete proof of the claim.** We do not make theoretical claims.

- For all **datasets** used, check if you include:
  - **The relevant statistics, such as number of examples.** We use widely adopted public datasets in Section 4.3.
  - **The details of train/validation/test splits.** We use the default splits as provided by the datasets.
  - **An explanation of any data that were excluded, and all pre-processing step.** We did not exclude any data or perform any pre-processing.
  - **A link to a downloadable version of the dataset or simulation environment.** We do not use specific environment that require additional labor to install.
  - **For new data collected,a complete description of the data collection process, such as instructions to annotators and methods for quality control.** We do not collect or release new datasets.

- For all shared **code** related to this work, check if you include:
  - **Specification of dependencies.** We give instructions in the supplemented codes.
  - **Training code.** The training code is available in the supplementary.
  - **Evaluation code.** The evaluation code is available in the supplementary.
  - **(Pre-)trained model(s).** We do not release any pre-trained models. The code to run all experiments in our work can be found in the supplementary.
  - **README file includes table of results accompanied by precise command to run to produce those results.** We include a README in the code.

- For all reported **experimental results**, check if you include:
  - **The range of hyper-parameters considered, method to select the best hyper-parameter configuration, and specification of all hyper-parameters used to generate results.** We provide all details of the hyper-parameter tuning in Section 4.2.
  - **The exact number of training and evaluation runs.** Ten independent repetitions are conducted for each experiments.
  - **A clear definition of the specific measure or statistics used to report results.** We use the classification accuracy on test-set, which is defined in Section 4.
  - **A description of results with central tendency (e.g. mean) & variation (e.g. error bars).** We report accuracy and loss values for all experiments.
  - **The average runtime for each result, or estimated energy cost.** We do not report the running time or energy cost.
  - **A description of the computing infrastructure used.** All detailed descriptions are presented in the supplementary materials.

REFERENCES

Diogo Almeida, Clemens Winter, Jie Tang, and Wojciech Zaremba. A generalizable approach to learning optimizers. *arXiv preprint arXiv:2106.00958*, 2021.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in neural information processing systems*, pp. 3981–3989, 2016.

Alexios Balatsoukas-Stimming and Christoph Studer. Deep unfolding for communications systems: A survey and some new directions. In *2019 IEEE International Workshop on Signal Processing Systems (SiPS)*, pp. 266–271. IEEE, 2019.

Irwan Bello, Barret Zoph, Vijay Vasudevan, and Quoc V Le. Neural optimizer search with reinforcement learning. *arXiv preprint arXiv:1709.07417*, 2017.

Samy Bengio, Yoshua Bengio, and Jocelyn Cloutier. Use of genetic programming for the search of a new learning rule for neural networks. In *Proceedings of the First IEEE Conference on Evolutionary Computation. IEEE World Congress on Computational Intelligence*, pp. 324–327. IEEE, 1994.

Mark Borgerding, Philip Schniter, and Sundeep Rangan. Amp-inspired deep networks for sparse linear inverse problems. *IEEE Transactions on Signal Processing*, 65(16):4293–4308, Aug 2017. ISSN 1941-0476. doi: 10.1109/TSP.2017.2708040.

Yue Cao, Tianlong Chen, Zhangyang Wang, and Yang Shen. Learning to optimize in swarms. In *Advances in Neural Information Processing Systems*, pp. 15018–15028, 2019.

Tianlong Chen, Weiyi Zhang, Zhou Jingyang, Shiyu Chang, Sijia Liu, Lisa Amini, and Zhangyang Wang. Training stronger baselines for learning to optimize. *Advances in Neural Information Processing Systems*, 33, 2020.

Tianlong Chen, Xiaohan Chen, Wuyang Chen, Howard Heaton, Jialin Liu, Zhangyang Wang, and Wotao Yin. Learning to optimize: A primer and a benchmark. *arXiv preprint arXiv:2103.12828*, 2021.

Xinshi Chen, Yu Li, Ramzan Umarov, Xin Gao, and Le Song. Rna secondary structure prediction by learning unrolled algorithms. In *International Conference on Learning Representations*, 2019.

Yutian Chen, Matthew W Hoffman, Sergio Gómez Colmenarejo, Misha Denil, Timothy P Lillicrap, Matt Botvinick, and Nando Freitas. Learning to learn without gradient descent by gradient descent. In *International Conference on Machine Learning*, pp. 748–756. PMLR, 2017.

M.-C. Corbineau, C. Bertocchi, E. Chouzenoux, M. Prato, and J.-C. Pesquet. Learned image deblurring by unfolding a proximal interior point algorithm. In *2019 IEEE International Conference on Image Processing (ICIP)*, pp. 4664–4668. IEEE, Sep 2019. ISBN 978-1-5386-6249-6. doi: 10.1109/ICIP.2019.8803438.

Miles Cranmer. Pysr: Fast & parallelized symbolic regression in python/julia, September 2020. URL https://doi.org/10.5281/zenodo.4052869.

Miles Cranmer, Alvaro Sanchez-Gonzalez, Peter Battaglia, Rui Xu, Kyle Cranmer, David Spergel, and Shirley Ho. Discovering symbolic models from deep learning with inductive biases. *NeurIPS 2020*, 2020.

Finale Doshi-Velez and Been Kim. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*, 2017.

Matthias Feurer and Frank Hutter. Hyperparameter optimization. In *Automated Machine Learning*, pp. 3–33. Springer, Cham, 2019.

Raja Giryes, Yonina C. Eldar, Alex M. Bronstein, and Guillermo Sapiro. Tradeoffs between convergence speed and reconstruction accuracy in inverse problems. *IEEE Transactions on Signal Processing*, 66(7):1676–1690, Apr 2018. ISSN 1941-0476. doi: 10.1109/TSP.2018.2791945.

Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. Knowledge distillation: A survey. *International Journal of Computer Vision*, 129(6):1789–1819, 2021.

Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *Proceedings of the 27th international conference on international conference on machine learning*, pp. 399–406, 2010.

Steven Gustafson, Edmund K Burke, and Natalio Krasnogor. On improving genetic programming for symbolic regression. In *2005 IEEE Congress on Evolutionary Computation*, volume 1, pp. 912–919. IEEE, 2005.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural networks*, 2(5):359–366, 1989.

Timothy M Hospedales, Antreas Antoniou, Paul Micaelli, and Amos J Storkey. Meta-learning in neural networks: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Elias Khalil, Hanjun Dai, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. *Advances in neural information processing systems*, 30: 6348–6358, 2017.

John R Koza. Genetic programming as a means for programming computers by natural selection. *Statistics and computing*, 4(2):87–112, 1994.

Chaojian Li, Tianlong Chen, Haoran You, Zhangyang Wang, and Yingyan Lin. Halo: Hardware-aware learning to optimize. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2020a.

Ke Li and Jitendra Malik. Learning to optimize. *International Conference on Learning Representations (ICLR)*, 2017a.

Ke Li and Jitendra Malik. Learning to optimize neural nets. *arXiv preprint arXiv:1703.00441*, 2017b.

Maojia Li, Jialin Liu, and Wotao Yin. Learning to combine quasi-newton methods. *NeruIPS workshop on on Optimization for Machine Learning*, 2020b.

Xuhong Li, Haoyi Xiong, Xingjian Li, Xuanyu Wu, Xiao Zhang, Ji Liu, Jiang Bian, and Dejing Dou. Interpretable deep learning: Interpretation, interpretability, trustworthiness, and beyond. *arXiv preprint arXiv:2103.10689*, 2021.

Dong Liang, Jing Cheng, Ziwen Ke, and Leslie Ying. Deep magnetic resonance image reconstruction: Inverse problems meet neural networks. *IEEE Signal Processing Magazine*, 37(1):141–151, 2020.

Jialin Liu, Xiaohan Chen, Zhangyang Wang, and Wotao Yin. ALISTA: Analytic weights are as good as learned weights in LISTA. In *International Conference on Learning Representations*, 2019.

Kaifeng Lv, Shunhua Jiang, and Jian Li. Learning gradient descent: Better generalization and longer horizons. *arXiv preprint arXiv:1703.03633*, 2017.

Niru Maheswaranathan, David Sussillo, Luke Metz, Ruoxi Sun, and Jascha Sohl-Dickstein. Reverse engineering learned optimizers reveals known and novel mechanisms. *arXiv preprint arXiv:2011.02159*, 2020.

Luke Metz, Niru Maheswaranathan, Jeremy Nixon, C Daniel Freeman, and Jascha Sohl-Dickstein. Understanding and correcting pathologies in the training of learned optimizers. *arXiv preprint arXiv:1810.10180*, 2018.

Luke Metz, Niru Maheswaranathan, Jeremy Nixon, Daniel Freeman, and Jascha Sohl-Dickstein. Understanding and correcting pathologies in the training of learned optimizers. In *International Conference on Machine Learning*, pp. 4556–4565. PMLR, 2019.

Thomas Moreau and Joan Bruna. Understanding the learned iterative soft thresholding algorithm with matrix factorization. In *International Conference on Learning Representations (ICLR)*, 2017. URL http://arxiv.org/abs/1706.01338.

Jorge Nocedal and Stephen Wright. *Numerical optimization*. Springer Science & Business Media, 2006.

Jeff Orchard and Lin Wang. The evolution of a generalized neural learning rule. In *2016 International Joint Conference on Neural Networks (IJCNN)*, pp. 4688–4694. IEEE, 2016.

Paavo Parmas, Carl Edward Rasmussen, Jan Peters, and Kenji Doya. Pipps: Flexible model-based policy search robust to the curse of chaos. *arXiv preprint arXiv:1902.01240*, 2019.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *International conference on machine learning*, pp. 1310–1318, 2013.

Joelle Pineau, Philippe Vincent-Lamarre, Koustuv Sinha, Vincent Lariviere, Alina Beygelzimer, Florence d'Alché Buc, Emily Fox, and Hugo Larochelle. Improving reproducibility in machine learning research. *Journal of Machine Learning Research*, 22:1–20, 2021.

Esteban Real, Chen Liang, David So, and Quoc Le. Automl-zero: Evolving machine learning algorithms from scratch. In *International Conference on Machine Learning*, pp. 8007–8019. PMLR, 2020.

Thomas Philip Runarsson and Magnus Thor Jonsson. Evolution and design of distributed learning rules. In *2000 IEEE Symposium on Combinations of Evolutionary Computation and Neural Networks. Proceedings of the First IEEE Symposium on Combinations of Evolutionary Computation and Neural Networks (Cat. No. 00*, pp. 59–63. IEEE, 2000.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

Harsh Shrivastava, Xinshi Chen, Binghong Chen, Guanghui Lan, Srinivas Aluru, Han Liu, and Le Song. Glad: Learning sparse graph recovery. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BkxpMTEtPB.

Ruoyu Sun. Optimization for deep learning: theory and algorithms. *arXiv preprint arXiv:1912.08957*, 2019.

Satoshi Takabe and Tadashi Wadayama. Theoretical interpretation of learned step size in deep-unfolded gradient descent. *arXiv:2001.05142 [cs, math, stat]*, Jan 2020. URL http://arxiv.org/abs/2001.05142. arXiv: 2001.05142.

Corentin Tallec and Yann Ollivier. Unbiasing truncated backpropagation through time. *arXiv preprint arXiv:1705.08209*, 2017.

Ricardo Vilalta and Youssef Drissi. A perspective view and survey of meta-learning. *Artificial intelligence review*, 18(2):77–95, 2002.

Olga Wichrowska, Niru Maheswaranathan, Matthew W Hoffman, Sergio Gomez Colmenarejo, Misha Denil, Nando Freitas, and Jascha Sohl-Dickstein. Learned optimizers that scale and generalize. In *International Conference on Machine Learning*, pp. 3751–3760. PMLR, 2017.

Yuhuai Wu, Mengye Ren, Renjie Liao, and Roger Grosse. Understanding short-horizon bias in stochastic meta-optimization. *arXiv preprint arXiv:1803.02021*, 2018.

Tianwei Yin, Zihui Wu, He Sun, Adrian V Dalca, Yisong Yue, and Katherine L Bouman. End-to-end sequential sampling and reconstruction for mr imaging. *arXiv preprint arXiv:2105.06460*, 2021.

Jian Zhang and Bernard Ghanem. Ista-net: Interpretable optimization-inspired deep network for image compressive sensing. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1828–1837, 2018.

A   More Details Regarding The Inpterpretability

A.1   Experimental Details

In our interpretability experiments, the 6 model we used are DM, RP, and modifications of RP. The RP model differ from the DM model in two ways: RP use two gradient features (discussed in equation 5, where DM used the pure gradient as its input. Additionally, RP has an input projection layer where DM does not.

A.2   More Detailed Discussions

The message conveyed by the RP_si distillation result. Among the comparison of table 3, the winner model is the RP_si, which has the smallest evaluation loss. On the same time, RP_si is also the simplest model. This does not mean that the optimal gradient descent rule is simplest rule, but rather, the optimal gradient descent rule is the simple combination of complex gradient features, as the input feature of RP_si is the most complex one compared with other model, such as RP or DM.

On the intuition behind TPF and MC: should they be large or small? In table 3, the TPF (temporal perception field) and MC (mapping complexity) are compared together with the performance (measured in the evaluation loss) of the model. The TPF/MC are measured for certain models w.r.t. its input, hence they are blind to the concrete components of the input. We link the different behaviors of different models and their TPF and MC, with the following summaries:

- Comparing among models with the same type of input (DM vs. DM + CL + IL, or RP vs. RP + CL + IL), the larger TPF/MC lead to better evaluation loss on the testing set (newly sampled, unseen problems).

- Comparing across model with different input features (i.e., DM vs. RP, or RM + CL + IL vs. RP + CL + IL, or RP vs RP + RP_si), the model with more complex input feature set (e.g., RP) not only outperform the model with simpler input set (e.g., DM), but they also have smaller temporal perception field and mapping complexity. Hence, improving the input feature diversity for the numerical L2O model will reduce both TPF and MC, while still leading to better performance.

The influence of pre-training problem selection on the final performance of symbolic L2O. Since obtaining the symbolic L2O model require a meta-pre-training step, one straightforward question may arise: what if the meta-pre-training step selected a different problem, how will the final results be affectd? To test the sensitiveness of the symbolic L2O to its meta-pre-train initialization step, we conducted ablation studies for the experiment in section 4.3 as follows.

We set up 3 different problem settings as the meta-pre-training problems, and pre-trained the RP_si (best performing) and the DM (worst performing) models. After that, we applied the symbolic distillation procedure, read out the distilled equation skeleton, set its coefficients as trainable, then meta-fine-tune the symbolic rule in the ResNet-50 on Cifar10. The three different problem we chose are: $\mathcal{P}_{1,2}$ introduced in section section 4.2, and $\mathcal{P}_4$, which is also minimizing the cross entropy of the MLP model, but the dataset is Cifar10 instead of MNIST.

We distill symbolic rule from the optimization trajectory data of the RP_si and DM models on three different problems. For RP_si, the distilled symbolic equations take the same skeleton, which is exactly equal to equation (6), just with different coefficients. However, with the DM model, the symbolic skeletons are significantly different, as shown as follows:

$$\mathcal{P}_1 : -\operatorname{asinh}^{0.89}\left(\log(1 + \sqrt{0.01g_t + 0.01\operatorname{asinh}(g_{t-1}) + 0.01\operatorname{asinh}(g_{t-2})})\right) \tag{7a}$$

$$\mathcal{P}_2 : -0.02g_t - 0.01\operatorname{sign}(g_t g_{t-1})\sinh\left(\sqrt{\operatorname{asinh}^{2.2}(g_t) + 0.7\operatorname{asinh}^{2.3}(g_{t-1}) + 0.5\operatorname{asinh}^{1.7}(g_{t-3}) + 0.2\operatorname{asinh}^{2.1}(g_{t-4})}\right) \tag{7b}$$

$$\mathcal{P}_4 : -0.02\frac{g_t + 0.4g_{t-1} + 0.2g_{t-2} - 0.01\tanh(g_{t-3}) - 0.01\tanh(g_{t-4})}{\sqrt{g_t^2 + g_{t-1}^2 + g_{t-2}^2}} \tag{7c}$$

Note that the most desired output from the symbolic regression step is the equation skeleton, and the coefficients are subject to be further fine-tuned in the meta-fine-tune stage. Hence, the message from the ablation study results is that:

- When the meta-pre-train problem are changed, the knowledge learned by the L2O model with more diverse input features (RP_si) could be more aligned under the same frame, compared with the L2O model with fewer input features (DM). In other words, more diverse input feature diversity of the optimizer will bring better tolerance/stability to the meta-pre-train problem selection.
- When the equation's skeleton is distilled correctly, the choice of the meta-pre-train problem does not have significant effect on the resulting symbolic L2O's performance.

The interpretations of the distilled equations 6 and 7. The equation 6 is the linear combination of multiple thresholded gradient features. First, these diverse features (gradient, Adam, learned exponential combination) enable higher chance to escape from flat local minima. Second, the nonlinear thresholding potentially smoothes noisy gradient signal and made the update more stable.

Equations 7 also have interpretable patterns. In $\mathcal{P}_1$, the $\sinh$ is a thresholding function which clip the gradient, and inside it is $\log(x + 1)$ with x being the big square root. The function $y = \log(x + 1)$ is close to the function $y = x$ when the magnitude of x is small, where the gradient magnitude is indeed usually small. In $\mathcal{P}_2$, the equation is close to SGD in the first term $-0.02g_t$. If the sign of g_t and g_{t-1} is the same, i.e., two most recent gradient holds the same sign, then $\mathrm{sign}(g_t g_{t-1}) = 1$, it descent more, otherwise it descent less. In $\mathcal{P}_4$, the equation is similar to Adam with additional $\tanh$ thresholding to certain components.

How much adaptation is needed during meta-fine-tune. This experiment follows the same setting of the above adaptation experiments for DM and RP_si: meta-pre-train on $\mathcal{P}_1/\mathcal{P}_2/\mathcal{P}_4$, and meta-fine-tune and evaluate on the ResNet-50 on Cifar10. To help understand how much improvement is needed in fine-tuning, the evaluation performances (measured in test set accuracies) before and after the fine-tuning step are provided in table 5.

From the table, it can be seen that the symbolic rule from RP_si, which have smaller MC, transfers better than DM. High complexity model DM, on the other hand, are less stable for different meta-pre-training problem.

Optimizers	DM model			RP_si model		
Meta-pre-trained from	$\mathcal{P}_1$	$\mathcal{P}_2$	$\mathcal{P}_4$	$\mathcal{P}_1$	$\mathcal{P}_2$	$\mathcal{P}_4$
Before meta-fine-tune	13.4	70.0	83.2	91.3	93.8	94.4
After meta-fine-tune	10.0	70.7	84.5	95.4	95.3	95.5

Table 5: Comparison for before and after meta-fine-tuning. The values are test accuracies of the symbolic equation distilled from DM and RP_si, when meta-pre-trained on $\mathcal{P}_1/\mathcal{P}_2/\mathcal{P}_4$.

Why could the symbolic distillation provide better interpretability. With regard to our claim in section 3.3: *white-box functions have better interpretability and lighter weight*, one question may arise: the interpretability and light weight properties do not seem unique to symbolic optimizers, but rather, they seem unique to simple optimizers.

Indeed, the simpler model will naturally hold better interpretability than the complex model. However, whether the rule learned by the numerical optimizer is simple or not is not revealed by the numerical optimizer itself: it is only after the proposed symbolic distillation is applied can people realize that the rule learned by RP is simple (has small MC). It is also only after the symbolic distillation uncovered this fact can people safely simplify the RP model into the RP_s model, to make it lighter weight and obtain better interpretability and better performance (see table 3).

In other words, the interpretability indeed belongs to simple optimizers, but a numerical optimizer can not tell the simplicity of the rules it has learned, prior to applying the proposed symbolic distillation. In this sense, the proposed symbolic distillation brings better interpretability to numerical L2O.

The running time of the proposed method. The proposed symbolic distillation procedure contains the following components: the meta-pre-training, SR step, meta-fine-tuning, and the final evaluation

to optimize the large scale problem. The execution time for each step is provided in table 6. The proposed TPF and MC metrics are all simple calculations based on the SR results, hence they are instantly available once the SR results are out. The execution times for SR and computing TPF/MC are measured on the 2.6 GHz Intel Core i7 CPU with 16 GB 2400 MHz DDR4 Memory, and other other computation times are measured on the Nvidia A6000 GPU.

Step	Meta-pre-train	SR	Meta-fine-tune	Final evaluation	Computing TPF/MC
Execution Time	3 min ($\mathcal{P}_1$) - 10 min ($\mathcal{P}_3$)	5 hours	< 20 hours	8 hours (MobileNetV2) - 20 hours (ResNet-152)	< 1 s

Table 6: The computation execution times of the experiments in section 4.3.

B   MORE DETAILS REGARDING THE SCALABILITY

B.1   EXPERIMENTAL DETAILS

During the symbolic regression step, the outputs are a list of distilled equation candidates. For each candidate, a unique complexity value could be measured using Cranmer (2020). During the sanity check in section 4.1, the complexity levels are chosen to be the largest output, which are relatively small (<5 for SGD, <50 for Momentum, 100 for Adam). During the experiments in section 4.3, we pick the equation with 100 complexity value, since this number gives the best fitting ability as well as the best performance (check figure 5 and table 8 for details) according to our extensive experiments.

We have also tested varying the random seed for both meta-pre-train and the symbolic regression step, and check the resulting symbolic equation skeleton. Due to the low MC of the learned rule of RP_si, the distilled equation stably shows the same form (equation 6), regardless of the random seeds.

We used 128 batch size, and in both meta-fine-tune phase and final evaluation phase, we trained the CNN optimizees for 200 epochs.

B.2   MORE DETAILED DISCUSSIONS

Verification of the symbolic rule fitting ability. We verified that the distilled equation and the original optimizer are well aligned. **First**, figure 3 shows the fitting curve of the symbolic equation against the numerical model. In this figure, we chose a fixed time during the optimization, and plot the output of both original numerical L2O and the distilled symbolic equation. The results show that the distilled equation fits the original model well. Second, in table 7, we have distilled different optimizers, and have shown SR's fitting ability for each, indicated by R^2-score. The high R^2-score further verified the fitting ability is reliable for our tasks.

Table 7: SR evaluations results: the fitting and optimization ability across different SR options.

Distilled from	$mom(0.5)$		$Adam(0.9, 0.9)$		DM		RP		RP_si	
	$\mathcal{P}_1$	$\mathcal{P}_2$	$\mathcal{P}_1$	$\mathcal{P}_2$	$\mathcal{P}_1$	$\mathcal{P}_2$	$\mathcal{P}_1$	$\mathcal{P}_2$	$\mathcal{P}_1$	$\mathcal{P}_2$
R^2-score	0.83	0.85	0.25	0.31	0.46	0.54	0.93	0.94	0.94	0.94

The interpretations of the symbolic L2O ultimately used in section 4.3. In section 4.3, we used the best numerical model (RP_si) as the benchmark to distill the symbolic equation, and the distilled equations for RP_si in most cases take the form of equation (6). We note that this simple nonlinear thresholding function yielded good fitting accuracy, with the R^2-score 0.88. We note that the simple form has already been verified in the small mapping complexity and temporal perception field of RL_si in table 3.

Performance comparison of the numerical rule and the distilled symbolic rule. In table 3, we offered the performance comparison between the numerical rules and their distilled symbolic surrogates. To further illustrate their convergence speed, we plot the optimization trajectories for the DM model (the worst performing one) and the RP_si model (the best performing one) in figure 4. Specifically, the lines in this figure correspond to the two rows: *Eva Loss by numerical L2O* and *Eva Loss by distilled equation*, and the two columns: *DM* and *RP_si*, in table 3.

Figure 3: The sampled mapping functions of different optimizers w.r.t. their input feature sets. The colorful marked lines are the numerical/hand-crafted models, while the black solid lines are the distilled symbolic equations. In the line markers, "A@B" means the mapping function is A, the input of this function is B, and at the current time step, B is the only variable. It can be observed that the symbolic distillation fits the underlying optimization algorithms accurately.

Figure 4: The optimization trajectories of the DM and the RP_si models.

The relationship between SR complexity and fitting ability/accuracy. The symbolic regression algorithm is able to generate a series of equations with different complexity. Intuitively, the over-simple equations under fits the L2O model, and the over-complex equations tends to overfit. The exact fitting curve is shown in Fig. 5. In this figure, the y coordinate is the R2-score of the fitting performance, the higher the better, and the x-coordinate is the complexity of the equation. With the increase of the complexity, the fitting performance tends to first increase then decrease.

The influence of complexity to the accuracy are displayed in table 8. The experimental setting in this table is the same setting as section 4.3, and the numerical optimizer used is also RP_si.

Interpreting the hyperbolic functions presented in the distilled equations. The hyperbolic functions appears in the distilled equations. There are two possible reasons for the occurances of the hyperbolic functions. First, the symbolic equations are learned through gradient-free random mutation, hence it is possible that such hyperbolic thresholding effect has a higher chance to reduce the uncertainty under noisy gradient data, which makes these operators to be more easily selected and kept among other mutated results. Note that for tanh()/asinh()/etc, these functions are approximately equal to $y = x$ function when the input magnitude is small (the case of tanh is plotted in figure 6). Therefore, only when the inputs have large magnitude will adding these functions result in significant difference in the output.

Complexity	10	100	200
Accuracy	93.5	95.4	12.0

Table 8: The evaluation accuracies of the distilled equations with different complexities from the RP_si model. The experimental setting is the same as section 4.3, and the values are over ResNet50 on Cifar10.

Figure 5: Left: the fitting performance of the equations with different level of complexity. The R^2-score indicates the fitting accuracy level of a single distilled equation compared with the original numerical optimizer. Right: the estimated TPF evaluated over distilled equations with different level of complexities. These figure revealed the relationship between the distilled equation complexity with the fitting ability and the estimated TPF. The values come from numerical L2Os meta-pre-trained over $\mathcal{P}_3$ (MNIST dataset with shallow MLP).

Figure 6: The $\tanh()$ function series. These functions are used in equation 6, where the learnable coefficient γ determine the region of the linearity (within which the $\tanh()$ function is close to $y = x$)

Second, the tanh() functions in the distilled equations of LSTM models are straightforward to understand: the symbolic rules are the surrogate of the LSTM model, and the LSTM uses the tanh() function as its non-linear activation function. Therefore, the tanh() function in the distilled equations could be correctly reflecting the nonlinearity of the LSTM teacher's updating dynamics.

We are more interested in the distillation of a real numerical L2O model, hence we have conducted a new series of experiments, by comparing not including and including the hyperbolic functions. The distilled equations without hyperbolic functions take similar forms than with the hyperbolic functions, and are slightly different in the coefficients. The R^2-score does not improve by dropping these functions. This could be explained by that even given the hyperbolic functions, the equations with and without these functions are all compared and screened during the SR step, hence the resulting equation is already the best among them, though with the hyperbolic.

$$\text{Given hyperbolic (R}^2 \text{ score} = 0.54): -0.02g_t - 0.01\text{sign}(g_t g_{t-1})\sinh\left(\sqrt{\text{asinh}^{2.2}(g_t) + 0.7\text{asinh}^{2.3}(g_{t-1}) + 0.5\text{asinh}^{1.7}(g_{t-3}) + 0.2\text{asinh}^{2.1}(g_{t-4})}\right) \quad (8a)$$

$$\text{Without hyperbolic (R}^2 \text{ score} = 0.53): -0.02g_t - 0.01\text{sign}(g_t g_{t-1})\left(\sqrt{g_t^2 + 0.9g_{t-1}^2 + 0.8g_{t-2}^2 + 0.7g_{t-3}^2 + 0.5g_{t-4}^{2.4} + 0.4g_{t-5}^2 + 0.3g_{t-6}^2 + 0.1g_{t-7}^{2.5}}\right) \quad (8b)$$

C SYMBOLIC REGRESSION PRELIMINARIES

The psudo-code for the SR algorithm. As described in section 1, the symbolic regression works by constantly mutating a list of equations to gradually obtain the better performing one. The core mutation algorithm of SR is provided in figure 7 as a pseudo-code.

The hyperparameters that we chose. There are several hyperparameters for the symbolic regression procedure that could potentially influence the performance. We list them as follows:

- The number of iterations: it means the number of executions, among which the best equations are picked. We set it to a large enough value, 300, since it shows in the experiment that any larger values leads to the similarly good results.

- The population number: it means the number of symbolic equation candidates used at each iteration. It is empirically observed that simpler models is enough to be accurately distilled with smaller population number. After tuning this parameter across all L2O models, we used the largest best population number, 200, for all models.

- Dataset size: it means the number of samples in the SR. We used 5000 samples across the experiments, which is verified to be sufficient for our purpose.

```
Algotithm: mutation operations in Symbolic Regression
function Random_Mutate (dataset):
    # cweights is the weights used to randomize mutation type.
    # If equation too big, don't add new operators
    if n >= maxsize || depth >= maxdepth
        cweights[3] = 0.0
        cweights[4] = 0.0
    end
    successful_mutation = false
    mutationChoice = rand() # randomly select one mutation type.
    # ------ Mutations ------
    while (!successful_mutation) && attempts < max_attempts
        tree = copyNode(prev)
        successful_mutation = true
        if mutationChoice < cweights[1]
            tree = mutateConstant(tree, temperature, options)
        elseif mutationChoice < cweights[2]
            # Can always mutate to the same operator
            tree = mutateOperator(tree, options)
        elseif mutationChoice < cweights[3]
            # Can potentially have a situation without success
            tree = appendRandomOp(tree, options, nfeatures)
        elseif mutationChoice < cweights[4]
            tree = insertRandomOp(tree, options, nfeatures)
        elseif mutationChoice < cweights[5]
            tree = deleteRandomOp(tree, options, nfeatures)
        elseif mutationChoice < cweights[6]
            tree = simplifyTree(tree, options) # Sometimes we simplify tree
            tree = combineOperators(tree, options)
            return PopMember(tree, beforeLoss, parent=parent_ref)
        elseif mutationChoice < cweights[7]
            tree = genRandomTree(5, options, nfeatures)
        else # no mutation applied
            return PopMember(tree, beforeLoss, parent=parent_ref)
        end
        attempts += 1
    end
    if !successful_mutation
        return PopMember(copyNode(prev), beforeLoss, parent=parent_ref)
    end
    if probChange < rand()
        return PopMember(copyNode(prev), beforeLoss, parent=parent_ref)
    else
        return PopMember(tree, afterLoss, parent=parent_ref)
    end
```

Figure 7: The pseudo-code for the core mutation operation used in the SR algorithm.