PolarNet: 3D Point Clouds for Language-Guided Robotic Manipulation

Abstract: The ability for robots to comprehend and execute manipulation tasks based on natural language instructions is a long-term goal in robotics. The dominant approaches for language-guided manipulation use 2D image representations, which face difficulties in combining multi-view cameras and inferring precise 3D positions and relationships. To address these limitations, we propose a 3D point cloud based policy called PolarNet for language-guided manipulation. It leverages carefully designed point cloud inputs, efficient point cloud encoders, and multimodal transformers to learn 3D point cloud representations and integrate them with language instructions for action prediction. PolarNet is shown to be effective and data efficient in a variety of experiments conducted on the RLBench benchmark. It outperforms state-of-the-art 2D and 3D approaches in both single-task and multi-task learning, even with 249 task variations.

Keywords: Robotic manipulation, 3D point clouds, language-guided policy

1 Introduction

Humans are highly capable of performing a wide range of manipulation tasks in 3D physical environments. One efficient and intuitive way to specify different tasks is through natural language instructions. Consequently, a long-term goal in robotics is to develop robots that can follow language instructions to perform various manipulation tasks.

Most existing work on language-guided robotic manipulation uses 2D image representations [1, 2, 3, 4]. BC-Z [1] applies ResNet [5] to encode a single-view image for action prediction. Hiveformer [3] employs transformers [6] to jointly encode multi-view images and all the history. Recent advances in vision and language learning [7, 8] have further paved the way in image-based manipulation [4]. CLIPort [4] and InstructRL [9] take advantage of pretrained vision-and-language models [8, 10] to improve generalization in multi-task manipulation. GATO [11] and PALM-E [12] jointly train robotic tasks with massive web image-text data for better representation and task reasoning.

Although 2D image-based policies have achieved promising results, they have inherent limitations for manipulation in the 3D world. First, they do not take full advantage of multi-view cameras for visual occlusion reasoning, as multi-view images are not explicitly aligned with each other, as shown in Figure 1. Second, accurately inferring the precise 3D positions and spatial relations [13] from 2D images is a significant challenge. Current 2D approaches mainly rely on extensive pretraining and sufficient in-domain data to achieve satisfactory performance.

To overcome the limitations of 2D-based manipulation policy learning, recent research has turned to 3D-based approaches. The use of 3D representations offers a natural way to fuse multi-view observations [14] and facilitates more accurate 3D localization [15], see Figure 1 (right). For example, PerAct [14] adopts an action-centric approach that takes a high-dimensional input of over 1 million voxels to classify the next active voxel, achieving state-of-the-art results for multi-task language-guided manipulation. However, such action-centric 3D voxels suffer from quantization errors and

Figure 1: (a): Variations of the "Reach and Drag" task in RLBench [19], with different target colors per variation. **(b)**: Although different views are complementary to represent the scene, they are not explicitly aligned with each other. **(c)** Merging multi-view cameras to construct a unified point cloud in 3D space. Design options of the point cloud input are carefully investigated in this work.

computation inefficiency. An alternative 3D representation is the point cloud, which has attracted research attention in 3D object detection [16], segmentation [17] and grounding [13]. However, the effective and efficient processing of 3D point clouds for robotic manipulation [18] is still under-explored. And the focus has primarily been on single-task manipulation, lacking the versatility to incorporate language instructions for completing multiple tasks simultaneously.

This paper proposes **PolarNet**, the first **po**int cloud-based **la**nguage-guided **r**obotic manipulation **net**work. We explore various design options for 3D point cloud representation, including the composition of point cloud features, the coverage space of the point cloud, the utilization of multiple camera views, and the choice of coordinate frame for point clouds. We utilize the PointNext architecture [17] to efficiently encode point cloud inputs. A multimodal transformer is employed to fuse the encoded point cloud with language instructions at an intermediate level. Finally, our PolarNet predicts 7-DoF (degrees of freedom) actions encompassing position, rotation and open state of a parallel gripper, which are executed by a motion planer to complete the task.

We conduct extensive experiments on RLBench [19] in three language-guided manipulation setups: single-task single-variation (one policy for each 10 tasks), multi-task single-variation (one policy for all 10 tasks), and multi-task multi-variation (one policy for 18 tasks with 249 variations). Figure 1 illustrates variations for the task "reach and drag". Our model significantly outperforms state-of-the-art 2D and 3D based models for all the three settings, demonstrating the effectiveness of PolarNet in integrating language guidance with a 3D point cloud based representation for robotic manipulation. We will release the code and trained models upon acceptance.

2 Related Work

Language-guided Robotic Manipulation. Language-guided policy learning has gained significant attention in robotics due to its potential for convenient human-robot interaction and skill generalization across diverse tasks [20, 21, 22, 23, 24, 25, 26, 27]. Several multi-task benchmarks have been established recently [28, 19, 29, 30, 31]. In our work, we use RLBench [19] since it provides hundreds of challenging manipulation tasks with demonstrations and instructions. Leveraging pretrained large language models [12, 32, 33, 3, 4, 9, 11] have been shown beneficial for language-guided manipulation. Most existing works are based on 2D images [2, 34, 1, 27, 3], while a few recent works explore the potential of 3D representations [14, 35]. Both C2F-ARM [35] and PerAct [14] utilize a 3D voxel representation. C2F-ARM proposes to represent the 3D scene in a coarse-to-fine manner to balance quantization error and computation cost. PerAct [14] uses an action-centric representation

that encodes the language and all 3D voxels in the workspace via a Perceiver transformer [36] and classifies which voxel is the next gripper position, making it less efficient. In contrast, we explore the point cloud representations and predict actions in a more efficient "point-centric" manner.

Manipulation Learning with Point Clouds. Due to the advantages of 3D representations, research has increasingly focused on vision-guided robotic manipulation from 3D point clouds [37, 18, 38, 39, 40, 41, 42, 43, 44]. The design choice of the point cloud representation plays an important role for the task performance. Strudel et al. [45] shows the benefits from normals for motion planning. Liu et al. [18] finds that normalizing point clouds in the end-effector and target object frames work significantly better than the vanilla world and robot base frames. Seita et al. [46] adds per-point flow vectors to improve manipulation of tools. Qin et al. [47] further shows direct sim-to-real transfer is possible with point clouds. However, existing work mainly utilizes point clouds to train a single-task policy and does not consider any language interactions. In this work, we jointly represent point clouds and language to perform various manipulation tasks, and systematically evaluate design choices for point cloud representations, such as the importance of colors.

Point Cloud Networks. Point cloud-based vision tasks have received more research attention such as 3D object detection [16], segmentation [48] and 3D object grounding [13, 15]. PointNet [48] and its extension PointNet++ [49] are the most popular networks for processing point clouds. Although more advanced networks based on transformers [6] have been proposed recently [50, 51], PointNext [17] demonstrates that small modifications on PointNet++ can even outperform the newer architectures. Our approach PolarNet is based on the state-of-the-art PointNext model [17] and evaluates different design choices in the context of language-guided manipulation.

3 Method

3.1 Problem Definition

We aim to learn a visual policy $\pi(a_t|O_t)$ to perform robotic manipulation tasks following natural language instructions, where $O_t \in O, a_t \in A$ are the observation and action at step t, O and A are the observation and action space respectively. In this work, the observation space O includes: 1) a language instruction $(x_1, \cdots, x_{N_x})$ where x_i is a tokenized word, 2) RGB images from K cameras $\{I_{rgb}^k\}_{k=1}^K, I_{rgb}^k \in \mathbb{R}^{H \times W \times 3}$, and 3) aligned depth images $\{I_{dep}^k\}_{k=1}^K, I_{dep}^k \in \mathbb{R}^{H \times W}$. We use $K = 3$ with cameras on the left shoulder, right shoulder and wrist of the robotic arm and $H = W = 128$ following previous work [2, 3]. The intrinsic and extrinsic camera parameters are known. The action space A consists of the pose and open state of the parallel gripper. The pose is composed of the Cartesian coordinates $a_t^{xyz} \in \mathbb{R}^3$ and rotation described with a quaternion $a_t^q \in \mathbb{R}^4$ in the world frame. The open state $a_t^o \in \{0, 1\}$ indicates whether the gripper is open or closed. We follow the standard setup in RLBench [34, 2, 3, 14] to predict action of key steps and use a motion planner to execute the action. More details about the key step are presented in Sec 2 of the supplementary material.

3.2 PolarNet: Point Cloud-based Language-guided Robotic Manipulation Policy

Figure 2 presents an overview of PolarNet for language-guided manipulation with 3D point clouds. We first describe the design choice of point cloud representations in Sec 3.2.1, and then introduce the details of the model architecture in Sec 3.2.2 followed by the training objectives in Sec 3.2.3.

3.2.1 Point Cloud Inputs

Preprocessing. Given I_{dep}^k and known camera instrincs and extrinsics at step t, we project each pixel in I_{dep}^k to the 3D world coordinates. Since I_{rgb}^k is aligned with I_{dep}^k, the RGB color of a pixel can be appended to the corresponding point. In this way, we obtain a point cloud $V_t^k \in \mathbb{R}^{H \times W \times 6}$ for each camera in the world frame, where each point consists of the XYZ coordinates and its RGB color. It is possible to merge point clouds from different cameras, as they are in the same coordinate system. To reduce redundancy, we use Open3D toolkit [52] to uniformly downsample the merged point cloud to one point per voxel. We use a voxel size of 1cm^3 following previous work [14]. We also estimate the normal of each point via Open3D. The geometric structure of the point cloud makes it straightforward to select relevant points, which is difficult for 2D images. For example, the background points like wall and floor are far away from the robot's workspace, and the manipulated

Figure 2: PolarNet for language-guided manipulation. The approach takes as input the merged point cloud obtained from multi-view RGB-D images and a language instruction, and uses Point-Next [17] for efficient point cloud encoding and CLIP text encoder [8] for language encoding. The point cloud and language are integrated via a multi-layer transformer at the intermediate level. PolarNet predicts the position (cyan node) using an integral over the heatmap of the point cloud with offset per point, and also rotation and open state of the gripper using global features.

objects are usually above the table surface[1]. Therefore, we simply define a 3D bounding box that covers the workspace above the table to crop the point cloud, only keeping points of the objects and the robotic arm. Our empirical results in Table 2 show that removing those irrelevant points are important. We randomly sample $N_v = 2048$ points in the processed point cloud as V_t.

Point cloud features. The type of point cloud representation [53] and normalization [18] can significantly impact the performance. Our paper is the first to study this impact systematically. In the experimental section 4.2, we first investigate different compositions of the point cloud inputs, including: 1) XYZ coordinates, 2) RGB color which is seldom used for robotic manipulation because most works focus on a single task requiring geometry structures only to be solved, 3) normal which has been shown effective to avoid obstacles [53], and 4) the height with respect to the manipulation table which helps infer the object location. We then compare two types of coordinate frame to normalize the point cloud into a unit ball: 1) using the gripper position as the coordinate origin which has the benefits to infer the object-robot relation [18], and 2) using the center of the point cloud as the origin which is a common practice in 3D scene understanding tasks [15]. Our empirical results in Table 1 and 2 indicate that all the four point cloud representations are beneficial with color of particular importance, while the two coordinate frames perform similarly.

3.2.2 Model Architecture

Language encoding. We employ the language encoder from the CLIP model [8] to tokenize and encode the language instructions. It is pre-trained on large-scale image-text pairs, enabling to effectively understand visually relevant instructions. We freeze the language encoder and add a linear layer to it to obtain the language embeddings $\hat{X} = (\hat{x}_1, \cdots, \hat{x}_{N_x}) = W_x \, \mathrm{CLIP}([x_1, \cdots, x_{N_x}])$.

Point cloud encoding. We encode the point cloud V_t with the state-of-the-art PointNext encoder [17]. It consists of L_e number of set abstraction (SA) blocks to hierarchically abstracts features of V_t. Each SA block contains a subsampling layer, a grouping layer, a multilayer perceptron (MLP), and a reduction layer. The subsampling layer at the l-th block uses farthest point sampling to select N_v^l points from V_t, and then the grouping layer finds neighbors for each selected point which are points within a radius r^l to the query. The MLP is shared for all the points to generate features. Finally, the reduction layer utilizes max pooling to aggregate features within the neighbors for the N_v^l query points. Assume v_i^l is the input feature of query point i at the l-th block and p_j^l is the XYZ coordinates of the point, the computation is formulated as:

$$v_i^{l+1} = \mathrm{MaxPool}_{j:(i,j)\in\mathcal{N}}\{\mathrm{MLP}([v_j^l; (p_j^l - p_i^l)/r^l])\}, \tag{1}$$

---

[1]There are few exceptions such as the "sliding block" task where the target is a green area on the table. We manually select those tasks and do not remove the table points for them.

where $\mathcal{N}$ denotes the set of neighbor points to the query point i, and $[\cdot]$ is the feature concatenation. Each SA block decreases the number of points by 2 times, while increases the dimensionality of the features by 2 times. We denote the encoded point cloud as $V_t^{L_e} = \{v_i^{L_e}\}_{i=1}^{N_v^e}$ where $N_v^e = N_v/2^{L_e}, v_i^{L_e} \in \mathbb{R}^{2^{L_e}d_e}$ and d_e is the hidden size in the first layer.

Vision-and-language fusion. We utilize a multi-layer transformer architecture [54] to integrate the point cloud features $V_t^{L_e}$ and the language embeddings $\hat{X}$. To be specific, we first add the XYZ position and step id embedding to the point cloud feature as follows:

$$\hat{v}_i^0 = W_v\, v_i^{L_e} + W_p\, p_i^{L_e} + E_s(t), \tag{2}$$

where $E_s(\cdot)$ is the sinusoidal positional encoding [6] to denote different steps. Then, in each transformer layer, we sequentially perform self-attention on the point cloud features, cross-attention from the point cloud to the language followed by a feedforward network, which is:

$$\text{Attn}(Q,K,V) = \text{Softmax}(\frac{W_Q Q(W_K K)^T}{\sqrt{d}})W_V V, \tag{3}$$

$$\hat{V}'^l = \text{Attn}(\hat{V}^l, \hat{V}^l, \hat{V}^l), \quad \hat{V}''^l = \text{Attn}(\hat{V}'^l, \hat{X}, \hat{X}), \quad \hat{V}^{l+1} = \text{LN}(W_2\, \text{GeLU}(W_1 \hat{V}''^l), \tag{4}$$

where d is the hidden size in the transformer layers and LN denotes layer normalization. We stack L layers to obtain the language-conditioned point cloud features $\hat{V}_t^L \in \mathbb{R}^{N_v/2^{L_e} \times d}$.

Action decoding. Since the gripper position a_{t+1}^{xyz} is in a continuous space, previous work [14] discretizing the action space can suffer from quantization error. However, a direct regression approach is often difficult in training leading to unsatisfactory performance [55]. Therefore, we take inspiration from the integral human pose regression [56] to get the best of the both worlds. For the position prediction, we use the PointNext decoder [17] with residual connection and upsampling to generate a heatmap over the input point cloud $H \in \mathbb{R}^{N_v \times 1}$ and an offset at each point $\Delta \in \mathbb{R}^{N_v \times 3}$. Albeit the point cloud only contains points of visible objects, the action position can cover the whole workspace. Thus we predict an offset to shift each point. The final predicted position is as follows:

$$\hat{a}_{t+1}^{xyz} = \sum_{i=1}^{N_v} H_i(p_i + \Delta_i). \tag{5}$$

It allows continuous output and the underlying heatmap representation makes it easy to train. The rotation and open state are more discrete in nature, thus we directly predict them as follows:

$$\hat{a}_{t+1}^q, \hat{a}_{t+1}^o = \text{MLP}([\text{MaxPool}(V_t^{L_e}); \text{MaxPool}(\hat{V}_t^L)]). \tag{6}$$

3.2.3 Training Objective

We use behavioral cloning for model training. Given the dataset $D = \{(X_i, \tau_i)\}_{i=1}^N$ with N pairs of successful demonstration τ_i and the corresponding instruction X_i, where τ_i is composed of a sequence of T key steps with visual observations $\{o_t\}_{t=1}^T$, and actions $\{a_t\}_{t=1}^T$. The training objective is to minimize the following loss, including a mean square error (MSE) on the gripper's position and rotation and a binary cross-entropy (BCE) loss on the open state classification:

$$\mathscr{L} = \frac{1}{|N|}\sum_{\tau \in D}\left[\sum_{t=1}^T \text{MSE}\left(\hat{a}_t^{xyz}, a_t^{xyz}\right) + \text{MSE}\left(\hat{a}_t^q, a_t^q\right) + \text{BCE}\left(\hat{a}_t^o, a_t^o\right)\right]. \tag{7}$$

4 Experiments

4.1 Experimental Setup

Evaluation setup. We consider three evaluation settings on RLBench [19] tasks. The *single-task single-variation [3]* consists of 10 tasks with one variation per task. We generate 100 demonstrations for each task variation. Separate models are trained for each task. The *multi-task single-variation* uses the same 10 tasks and training data as the single-task single-variation setup, but a unified model is trained to solve all the 10 tasks. The *multi-task multi-variation* includes 18 tasks where each task has multiple variations, resulting in 249 variations in total [14]. We generate 100 demonstrations

Table 1: Comparison of point cloud representations on the single-task single-variation evaluation.

RGB	Normal	Height	Pick & Lift	Pick-Up Cup	Put Knife	Put Money	Push Button	Reach Target	Slide Block	Stack Wine	Take Money	Take Umbrella	Avg.
×	×	×	26.2	44.0	81.1	95.9	99.6	27.8	89.3	91.0	70.3	95.3	72.1 $_{\pm4.4}$
✓	×	×	97.9	94.7	79.5	95.8	100.0	100.0	91.0	91.1	65.9	97.3	91.3 $_{\pm1.6}$
✓	✓	×	94.9	94.2	77.1	95.9	90.3	100.0	93.1	94.1	69.4	94.4	90.3 $_{\pm3.1}$
✓	×	✓	96.2	94.3	82.6	95.3	100.0	99.9	91.5	90.3	67.5	97.7	91.5 $_{\pm1.4}$
✓	✓	✓	96.7	91.9	82.5	96.1	99.9	99.9	93.5	94.1	68.6	97.5	**92.1** $_{\pm0.4}$

for each task, and thus a task variation may only have very limited demonstrations if there are many variations in the task. We train a single model for all the task variations, which is much more challenging due to the larger set of task variations and fewer training data per task variation. The details of the RLBench tasks in the three setups are presented in Sec 1 of the supplementary material.

Evaluation metrics. We use the task success rate (SR) to measure the performance which is 1 for complete success and 0 for failure per episode with no partial credits. For the first two setups, we evaluate on 500 unseen episodes per task ($500 \times 10 = 5000$ evaluation episodes in total) following [3]. We run experiments three times with three seeds and report the mean and standard deviation. For the last setup, we use the released dataset from [14] and evaluate on 25 episodes per task as [14] with a total number of $25 \times 18 = 450$ evaluation episodes.

Implementation details. For the model architecture, we use the PointNext-S model [17] with $L_e = 4$ SA blocks and compare $d_e = \{32, 64\}$. We initialize it with the weights trained on ShapeNet. The transformer layers have $d = 512$ and we compare $L = \{1, 2, 4\}$. We use the AdamW optimizer with a learning rate of 5×10^{-4} and a batch size of 8 demonstrations. We train for 20K, 200K and 600K for the single-task single-variation, multi-task single-variation and multi-task multi-variation setups respectively. We use a single NVIDIA V100 GPU for single-task setting and 4 GPUs to accelerate the training on multi-task settings. Our model is efficient to train, taking about 1 hour for single-task training and 30 hours to train for multi-task multi-variation.

4.2 Ablations

We study the impact of point cloud inputs and model architectures. Unless stated otherwise, we use a point cloud representation combining XYZ, RGB, normal and height, remove background and table points, and normalize them with the gripper position as the origin. The model uses $d_e = 32, L = 1$.

Point cloud representation. Table 1 compares point cloud input representations. The vanilla point cloud with only XYZ performs worst on average. The RGB color plays an important role for tasks requiring to distinguish colors such as "Pick-Up Cup" where the goal is to pick up the red cup amongst differently colored cups. It also benefits the scene understanding for tasks that do not explicitly require color such as "Put Knife". The improvement from normal of the point is marginal and unstable, which might result from noisy normal estimation. The height of point relative to the table is helpful, increasing the performance by 1.8% on average and 9.6% for the "Push Button" task.

Table 2: Comparison of point cloud processing on the single-task single-variation evaluation.

Coord origin	Remove Table	Remove Background	Avg.
Center	✓	✓	92.1 $_{\pm2.0}$
Gripper	×	×	81.6 $_{\pm3.2}$
Gripper	×	✓	89.9 $_{\pm2.8}$
Gripper	✓	✓	**92.1** $_{\pm0.4}$

Point cloud processing. We compare two different coordinate frames to normalize the point cloud, using the gripper position or the points center as the origin. As shown in Table 2, the two ways perform similarly while using the gripper position is more robust with lower standard deviation. More important in point cloud processing is to remove irrelevant points. The raw observed RGB-D images contain backgrounds such as wall and floor and the table. From Table 2 we can see that it is critical to remove those irrelevant points from the point cloud. Since we have a limited capacity to sample points, the irrelevant points make the interesting points sparser and harm the performance.

Table 5: Comparison with state-of-the-art methods on 10 tasks in single-task and multi-task setups. All the methods are trained on 100 demonstrations per task. We report the success rate (%) of our method on 500 episodes per task averaged over 3 seeds.

	Pick & Lift	Pick-Up Cup	Put Knife	Put Money	Push Button	Reach Target	Slide Block	Stack Wine	Take Money	Take Umbrella	Avg.
Single-task single-variation											
ARM [34]	70	80	-	-	-	100	-	70	-	70	-
Auto-λ [2]	82	72	36	31	95	100	36	23	38	37	55.0
Hiveformer [3]	92.2	77.1	69.7	96.2	99.6	100.0	95.4	81.9	82.1	90.1	88.4
Ours	96.7	91.9	82.5	96.1	99.9	99.9	93.5	94.1	68.6	97.5	**92.1**
Multi-task single-variation											
Auto-λ [2]	87	78	31	62	95	100	77	19	64	80	69.3
Hiveformer [3]	88.9	92.9	75.3	58.2	100.0	100.0	78.7	71.2	79.1	89.2	83.3
Ours	97.8	86.0	80.5	94.1	99.6	100.0	93.4	80.5	68.1	97.8	**89.8**

Table 3: Comparison of camera views on the single-task single-variation evaluation.

Left	Right	Wrist	Avg.
✓	✗	✗	37.6 $_{\pm4.8}$
✗	✓	✗	48.0 $_{\pm4.5}$
✗	✗	✓	35.0 $_{\pm5.5}$
✓	✓	✗	67.0 $_{\pm4.7}$
✓	✗	✓	80.2 $_{\pm3.0}$
✗	✓	✓	76.6 $_{\pm5.6}$
✓	✓	✓	**92.1** $_{\pm0.4}$

Multi-view cameras. Table 3 analyzes the contributions from multi-view cameras for point cloud construction. A single camera alone is insufficient to accomplish a task due to occlusions, decreasing the performance by more than 44%. The wrist camera performs worst among the three views. However, it is more complementary to the other two cameras, with more than 10% boost compared to the combination of left and right shoulder cameras. Using all the three cameras achieves the best performance with a significant margin (+11.9%, +15.5%, + 25.1% depending on the resp. two cameras).

Model capacity. We explore the influence of model capacities to the task performance in single-task single-variation and multi-task multi-variation setups in Table 4. In the single-task single-variation, a small network with $d_e = 32$ performs slightly better than a larger network with $d_e = 64$. We suspect that the larger model may require more demonstrations to train. However, the same model capacity does not perform well in the multi-task single-variation setup. It is essential to increase the model size to learn multiple manipulation tasks together. We also notice that the best model in multi-task single-variation still underperforms that in single-task single-variation by 2.3%. Particularly, the best epochs for each task vary a lot, indicating that a better multi-task learning strategy is in need.

In the following, we use $d_e = 32, L = 1$ for single-task setting and $d_e = 64, L = 2$ for the two multi-task settings.

4.3 Comparison with State of the Art

Single-task single-variation. We compare our model with ARM [34], Auto-λ [2] and Hiveformer [3] in the upper block of Table 5. All the three methods are based on multi-view 2D RGB-D images for action prediction. Our point cloud based model outperforms the state-of-the-art methods by a large margin, demonstrating the effectiveness of the 3D representations. The improvements are consistent across tasks except for "Take Money". We observe that the main problem on the "Take Money" task is due to the imperfect

Table 4: Comparison of model capacity on single-task and multi-task (MT) single-variation setups.

MT	d_e	L	Avg.
✗	32	1	**92.1** $_{\pm0.4}$
	64	1	91.0 $_{\pm0.9}$
✓	32	1	77.4 $_{\pm8.6}$
	64	1	89.3 $_{\pm2.0}$
	64	2	**89.8** $_{\pm1.5}$
	64	4	86.3 $_{\pm4.8}$

motion planner. As shown in Figure 3, when the check is placed inside of the safe, the robotic arm often collides with the safe door even if the predicted action is reasonable. Because of this, the groundtruth keystep action only achieves 89% success rate.

Multi-task single-variation. The lower block of Table 5 presents the performance under the multi-task single-variation setup. Our model also surpasses the state-of-the-art methods with 6.5% absolute gains compared to Hiveformer [3]. In Figure 4, we further compare state-of-the-art 2D-based

Table 6: Comparison with state-of-the-art methods on 18 tasks with 249 variations in total. All the methods are trained on 100 demonstrations per task. We report the success rate of our method on 25 episodes per task by default. († denotes our own implementation.)

	Open Drawer	Slide Block	Sweep to Dustpan	Meat off Grill	Turn Tap	Put in Drawer	Close Jar	Drag Stick	Stack Blocks	
C2FARM-BC [35]	20	16	0	20	68	4	24	24	0	
PerAct [14]	80	72	56	84	80	68	60	68	36	
Hiveformer† [3]	52	64	28	100	80	68	52	76	8	
Ours	84	56	52	100	80	32	36	92	4	

	Screw Bulb	Put in Safe	Place Wine	Put in Cupboard	Sort Shape	Push Buttons	Insert Peg	Stack Cups	Place Cups	Avg.
C2FARM-BC [35]	8	12	8	0	8	72	4	0	0	16
PerAct [14]	24	44	12	16	20	48	0	0	0	42.7
Hiveformer† [3]	8	76	80	32	8	84	0	0	0	45.3
Ours	44	84	40	12	12	96	4	8	0	**46.4**

model Hiveformer [3] with our PolarNet using 10 demonstrations per task in training. The results show that our 3D-based approach is also data efficient compared to the 2D-based method.

Figure 3: Failure case of "Take Money" task due to imperfect motion planner.

Multi-task multi-variation. In Table 6, we compare with state-of-the-art methods C2FARM-BC [35], PerAct [14] and Hiveformer [3]. For fair comparison, we add an additional front view camera following [14]. Both C2FARM-BC and PerAct utilize 3D voxels as inputs to train the manipulation policy. Our proposed point cloud based model is more efficient than the two 3D based models. It also improves PerAct by 3.7% on average over 18 tasks. In addition, PerAct [14] is less computationally efficient, requiring 16 days for training with 8 V100 GPUs, while we only use 4 V100 GPUs to train the same amount of iterations in 30 hours, which is roughly 13 times faster. Our 3D-based approach also achieves comparable performance as the state-of-the-art 2D-based approach Hiveformer on the setup which uses histories. It is interesting to further employ histories in our method and unify the 2D and 3D representations in the future work. We analyze the success and failure cases in the supplementary material and the video.

5 Conclusion

This work addresses language-guided robotic manipulation using 3D point clouds. The proposed PolarNet employs carefully designed point cloud inputs, an efficient point cloud encoder, and a multimodal transformer to predict 7-DoF actions for language-conditioned manipulation. We find that it is critical to use point color with colors, filter irrelevant points and merge multiple views. Extensive experiments on the RLBench benchmark demonstrate that PolarNet outperforms state-of-the-art models on a variety of tasks, from single-task single-variation to multi-task multi-variation with 249 task variations.

Limitations: Our multi-task model still does not perform as well as the best single-task model, requiring more advanced multi-task learning algorithms. Additionally, while our policy can perform multiple tasks with variations, we have not studied how it generalizes to new scenes, objects, and tasks. Finally, further evaluation on real-world robotic platforms is necessary to assess its performance in practical scenarios.

Figure 4: Comparison with different numbers of data per task for multi-task single-variation setting.

References

[1] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. BC-z: Zero-shot task generalization with robotic imitation learning. In *CoRL*, 2021.

[2] S. Liu, S. James, A. J. Davison, and E. Johns. Auto-Lambda: Disentangling dynamic task relationships. *TMLR*, 2022.

[3] P.-L. Guhur, S. Chen, R. Garcia-Pinel, M. Tapaswi, I. Laptev, and C. Schmid. Instruction-driven history-aware policies for robotic manipulations. In *CoRL*, 2022.

[4] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *CoRL*, 2021.

[5] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. 2016.

[6] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. u. Kaiser, and I. Polosukhin. Attention is all you need. In *NeurIPS*, 2017.

[7] J. Devlin, M. Chang, K. Lee, and K. Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In J. Burstein, C. Doran, and T. Solorio, editors, *NAACL-HLT*, 2019.

[8] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

[9] H. Liu, L. Lee, K. Lee, and P. Abbeel. Instruction-following agents with jointly pre-trained vision-language models. *arXiv preprint arXiv:2210.13431*, 2022.

[10] X. Geng, H. Liu, L. Lee, D. Schuurams, S. Levine, and P. Abbeel. Multimodal masked autoencoders learn transferable representations. *arXiv preprint arXiv:2205.14204*, 2022.

[11] S. Reed, K. Zolna, E. Parisotto, S. G. Colmenarejo, A. Novikov, G. Barth-maron, M. Giménez, Y. Sulsky, J. Kay, J. T. Springenberg, T. Eccles, J. Bruce, A. Razavi, A. Edwards, N. Heess, Y. Chen, R. Hadsell, O. Vinyals, M. Bordbar, and N. de Freitas. A generalist agent. *TMLR*, 2022.

[12] D. Driess, F. Xia, M. S. M. Sajjadi, C. Lynch, A. Chowdhery, B. Ichter, A. Wahid, J. Tompson, Q. Vuong, T. Yu, W. Huang, Y. Chebotar, P. Sermanet, D. Duckworth, S. Levine, V. Vanhoucke, K. Hausman, M. Toussaint, K. Greff, A. Zeng, I. Mordatch, and P. Florence. Palm-e: An embodied multimodal language model. In *arXiv preprint arXiv:2303.03378*, 2023.

[13] D. Z. Chen, A. X. Chang, and M. Nießner. Scanrefer: 3d object localization in rgb-d scans using natural language. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XX*, pages 202–221. Springer, 2020.

[14] M. Shridhar, L. Manuelli, and D. Fox. Perceiver-actor: A multi-task transformer for robotic manipulation. In *CoRL*, 2022.

[15] S. Chen, P.-L. Guhur, M. Tapaswi, C. Schmid, and I. Laptev. Language conditioned spatial relation reasoning for 3d object grounding. In *NeurIPS 2022-36th Conference on Neural Information Processing Systems*, 2022.

[16] Y. Zhou and O. Tuzel. Voxelnet: End-to-end learning for point cloud based 3d object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4490–4499, 2018.

[17] G. Qian, Y. Li, H. Peng, J. Mai, H. Hammoud, M. Elhoseiny, and B. Ghanem. Pointnext: Revisiting pointnet++ with improved training and scaling strategies. In *NeurIPS*, 2022.

[18] M. Liu, X. Li, Z. Ling, Y. Li, and H. Su. Frame mining: a free lunch for learning robotic manipulation from 3d point clouds. In *6th Annual Conference on Robot Learning*, 2022.

[19] S. James, Z. Ma, D. R. Arrojo, and A. J. Davison. RLBench: The robot learning benchmark & learning environment. *RA-L*, 2020.

[20] L. Shao, T. Migimatsu, Q. Zhang, K. Yang, and J. Bohg. Concept2robot: Learning manipulation concepts from instructions and human demonstrations. In *RSS*, 2020.

[21] M. Shridhar and D. Hsu. Interactive visual grounding of referring expressions for human-robot interaction. In *Proceedings of Robotics: Science and Systems*, 2018.

[22] brian ichter, A. Brohan, Y. Chebotar, C. Finn, K. Hausman, A. Herzog, D. Ho, J. Ibarz, A. Irpan, E. Jang, R. Julian, D. Kalashnikov, S. Levine, Y. Lu, C. Parada, K. Rao, P. Sermanet, A. T. Toshev, V. Vanhoucke, F. Xia, T. Xiao, P. Xu, M. Yan, N. Brown, M. Ahn, O. Cortes, N. Sievers, C. Tan, S. Xu, D. Reyes, J. Rettinghouse, J. Quiambao, P. Pastor, L. Luu, K.-H. Lee, Y. Kuang, S. Jesmonth, K. Jeffrey, R. J. Ruano, J. Hsu, K. Gopalakrishnan, B. David, A. Zeng, and C. K. Fu. Do as i can, not as i say: Grounding language in robotic affordances. In *CoLR*, 2022.

[23] C. Lynch, A. Wahid, J. Tompson, T. Ding, J. Betker, R. Baruch, T. Armstrong, and P. Florence. Interactive language: Talking to robots in real time. In *NeurIPs, 5th Robot Learning Workshop: Trustworthy Robotics*, 2022.

[24] S. Stepputtis, J. Campbell, M. Phielipp, S. Lee, C. Baral, and H. Ben Amor. Language-conditioned imitation learning for robot manipulation tasks. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *NeurIPs*, 2020.

[25] Y. Zhu, A. Joshi, P. Stone, and Y. Zhu. VIOLA: Object-centric imitation learning for vision-based robot manipulation. In *CoRL*, 2022.

[26] A. P. Shah, G. A. D. Lopes, and E. Najafi. Contact-based language for robotic manipulation planning. *2016 IROS*, 2016.

[27] C. Lynch and P. Sermanet. Language conditioned imitation learning over unstructured data. *RSS*, 2021.

[28] C. Li, R. Zhang, J. Wong, C. Gokmen, S. Srivastava, R. Martín-Martín, C. Wang, G. Levine, M. Lingelbach, J. Sun, M. Anvari, M. Hwang, M. Sharma, A. Aydin, D. Bansal, S. Hunter, K.-Y. Kim, A. Lou, C. R. Matthews, I. Villa-Renteria, J. H. Tang, C. Tang, F. Xia, S. Savarese, H. Gweon, K. Liu, J. Wu, and L. Fei-Fei. BEHAVIOR-1k: A benchmark for embodied AI with 1,000 everyday activities and realistic simulation. In *CoRL*, 2022.

[29] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *CoRL*, 2019.

[30] K. Zheng, X. Chen, O. Jenkins, and X. E. Wang. VLMbench: A compositional benchmark for vision-and-language manipulation. In *NeurIPs Datasets and Benchmarks Track*, 2022.

[31] Y. Jiang, A. Gupta, Z. Zhang, G. Wang, Y. Dou, Y. Chen, L. Fei-Fei, A. Anandkumar, Y. Zhu, and L. Fan. Vima: General robot manipulation with multimodal prompts. *ICML 2023*, 2022.

[32] S. Huang, Z. Jiang, H. Dong, Y. Qiao, P. Gao, and H. Li. Instruct2act: Mapping multi-modality instructions to robotic actions with large language model, 2023.

[33] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, J. Dabis, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, T. Jackson, S. Jesmonth, N. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, I. Leal, K.-H. Lee, S. Levine, Y. Lu, U. Malla, D. Manjunath, I. Mordatch, O. Nachum, C. Parada, J. Peralta, E. Perez, K. Pertsch, J. Quiambao, K. Rao,

M. Ryoo, G. Salazar, P. Sanketi, K. Sayed, J. Singh, S. Sontakke, A. Stone, C. Tan, H. Tran, V. Vanhoucke, S. Vega, Q. Vuong, F. Xia, T. Xiao, P. Xu, S. Xu, T. Yu, and B. Zitkovich. Rt-1: Robotics transformer for real-world control at scale. In *arXiv preprint arXiv:2212.06817*, 2022.

[34] S. James and A. J. Davison. Q-Attention: Enabling efficient learning for vision-based robotic manipulation. *RA-L*, 2022.

[35] S. James, K. Wada, T. Laidlow, and A. J. Davison. Coarse-to-fine q-attention: Efficient learning for visual robotic manipulation via discretisation. In *CVPR*, 2022.

[36] A. Jaegle, F. Gimeno, A. Brock, A. Zisserman, O. Vinyals, and J. Carreira. Perceiver: General perception with iterative attention, 2021.

[37] X. Lin, Y. Wang, Z. Huang, and D. Held. Learning visible connectivity dynamics for cloth smoothing. In *CoRL*, 2021.

[38] A. Alliegro, M. Rudorfer, F. Frattin, A. Leonardis, and T. Tommasi. End-to-end learning to grasp via sampling from object point clouds. *RA-L*, 2022.

[39] J. Lv, Q. Yu, L. Shao, W. Liu, W. Xu, and C. Lu. Sagci-system: Towards sample-efficient, generalizable, compositional, and incremental robot learning. In *ICRA*, 2022.

[40] S. James and A. J. Davison. Q-attention: Enabling efficient learning for vision-based robotic manipulation. *IEEE Robotics and Automation Letters*, 2022.

[41] M. Sundermeyer, A. Mousavian, R. Triebel, and D. Fox. Contact-graspnet: Efficient 6-dof grasp generation in cluttered scenes. 2021.

[42] B. Eisner, H. Zhang, and D. Held. FlowBot3D: Learning 3D Articulation Flow to Manipulate Articulated Objects. In *RSS*, 2022.

[43] Y. Qin, B. Huang, Z.-H. Yin, H. Su, and X. Wang. Dexpoint: Generalizable point cloud reinforcement learning for sim-to-real dexterous manipulation. *CoRL*, 2022.

[44] S. Song, A. Zeng, J. Lee, and T. Funkhouser. Grasping in the wild: Learning 6dof closed-loop grasping from low-cost demonstrations. *RA-L*, 2020.

[45] R. Strudel, R. G. Pinel, J. Carpentier, J.-P. Laumond, I. Laptev, and C. Schmid. Learning obstacle representations for neural motion planning. In *CoRL*, 2020.

[46] D. Seita, Y. Wang, S. J. Shetty, E. Y. Li, Z. Erickson, and D. Held. Toolflownet: Robotic manipulation with tools via predicting tool flow from point clouds. In *Conference on Robot Learning*, pages 1038–1049. PMLR, 2022.

[47] Y. Qin, B. Huang, Z.-H. Yin, H. Su, and X. Wang. Dexpoint: Generalizable point cloud reinforcement learning for sim-to-real dexterous manipulation. In *Conference on Robot Learning*, pages 594–605. PMLR, 2022.

[48] C. R. Qi, H. Su, K. Mo, and L. J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. 2017.

[49] C. R. Qi, L. Yi, H. Su, and L. J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *NeurIPS*, 2018.

[50] H. Zhao, L. Jiang, J. Jia, P. H. Torr, and V. Koltun. Point transformer. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 16259–16268, 2021.

[51] M.-H. Guo, J.-X. Cai, Z.-N. Liu, T.-J. Mu, R. R. Martin, and S.-M. Hu. Pct: Point cloud transformer. *Computational Visual Media*, 7:187–199, 2021.

[52] Q.-Y. Zhou, J. Park, and V. Koltun. Open3D: A modern library for 3D data processing. *arXiv:1801.09847*, 2018.

[53] R. Strudel, R. Garcia, J. Carpentier, J. Laumond, I. Laptev, and C. Schmid. Learning obstacle representations for neural motion planning. In *CoRL*, 2020.

[54] J. Lu, D. Batra, D. Parikh, and S. Lee. Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. *Advances in neural information processing systems*, 32, 2019.

[55] X. Sun, J. Shang, S. Liang, and Y. Wei. Compositional human pose regression. In *Proceedings of the IEEE international conference on computer vision*, pages 2602–2611, 2017.

[56] X. Sun, B. Xiao, F. Wei, S. Liang, and Y. Wei. Integral human pose regression. In *Proceedings of the European conference on computer vision (ECCV)*, pages 529–545, 2018.