Can multi-label classification networks know what they don't know?

Abstract

Estimating out-of-distribution (OOD) uncertainty is a central challenge for safely deploying machine learning models in the open-world environment. Improved methods for OOD detection in multi-class classification have emerged, while OOD detection methods for multi-label classification remain underexplored and use rudimentary techniques. We propose *JointEnergy*, a simple and effective method, which estimates the OOD indicator scores by aggregating energy scores from multiple labels. We show that JointEnergy can be mathematically interpreted from a joint likelihood perspective. Our results show consistent improvement over previous methods that are based on the maximum-valued scores, which fail to capture joint information from multiple labels. We demonstrate the effectiveness of our method on three common multi-label classification benchmarks, including MS-COCO, PASCAL-VOC, and NUS-WIDE. We show that JointEnergy can reduce the FPR95 by up to 10.05% compared to the previous best baseline, establishing *state-of-the-art* performance.

1 Introduction

Despite many breakthroughs in machine learning, formidable obstacles obstruct its deployment in the real world, where a model can encounter unknown out-of-distribution (OOD) samples. The problem of OOD detection—which attempts to identify and handle OOD inputs safely—has gained significant research attention lately [3, 19, 21, 27, 30, 31, 38, 23, 36]. Previous studies have primarily focused on detecting OOD examples in multi-class classification, where each sample is assigned to a single label. Unfortunately, this can be unrealistic in many real-world applications where images often have *multiple labels* of interest. For example, self-driving cars must differentiate between the road, traffic signs, and obstacles within a frame. In the medical domain, multiple abnormalities may be present in a medical image [55].

Currently, a critical research gap exists in developing and evaluating OOD detection algorithms for multi-label classification tasks that are more applicable to the real world. While one may be eager to conclude that solutions for multi-class setting should transfer to the multi-label setting, we argue that this is far from the truth. The main challenges posed in multi-label setting stem from the need to estimate uncertainty by *jointly leveraging the information across different labels,* as opposed to relying on one dominant label. Our analysis reveals that simply using single label output (*i.e.*, MaxLogit) [20] can be limiting. As a simple illustration, we contrast in Figure 1 of estimating OOD uncertainty using joint vs. single label information. MaxLogit can only capture the difference between the dominant outputs for `dog` (in-dist.) and `car` (OOD), while positive information from another dominant label `cat` (in-dist.) is dismissed.

In this paper, we address a pressing issue of OOD uncertainty estimation in the multi-label classi-fication setting, and propose a simple yet surprisingly effective method that jointly characterizes

Figure 1: Out-of-distribution detection for multi-label classification networks. During inference time, input $\mathbf{x}$ is passed through classifier f, and label-wise scores are computed for each label. OOD indicator scores are either the maximum-valued score (denoted by green outlines) or the sum of all scores. Taking the sum results in a larger difference in scores and more separation between in-distribution and OOD inputs (denoted by red lines), resulting in better OOD detection. Plots in the bottom right depict the probability densities of MaxLogit [20] versus *JointEnergy* (ours).

uncertainty from multiple labels. As a major advantage, our method circumvents the challenge to directly estimate the joint likelihood using generative models, which can be can computationally intractable to train and optimize, especially on multi-label datasets [22]. Formally, our proposed method, *JointEnergy*, derives a novel OOD score by combining label-wise energies over all labels. Despite its simplicity, we show that the JointEnergy can be theoretically interpreted from a joint likelihood perspective. The joint likelihood allows separability between in-distribution vs. OOD data, since OOD data is expected to have lower joint likelihood (*i.e.*, not associated with any of the labels). In contrast, having multiple dominant labels is indicative of an in-distribution input, which is the key aspect that JointEnergy captures. As shown in Figure 1, JointEnergy effectively amplifies the difference in scores between in-distribution and OOD inputs, compared to MaxLogit.

Extensive experiments show that JointEnergy outperforms existing methods on three common multi-label classification tasks, establishing **state-of-the-art** performance. For example, on a DenseNet trained with MS-COCO [32], our method reduces the false positive rate (at 95% TPR) by 10.05% when evaluated against OOD data from ImageNet [10], compared to the best performing baselines. Consistent performance improvement is observed on other multi-label tasks including PASCAL-VOC [13] and NUS-Wide [7], as well as alternative network architecture.

Importantly, our analysis demonstrates a strong compatibility between the label-wise energy function and aggregation function, supported by both mathematical interpretation and empirical results. As an ablation, we explore the effectiveness of applying summation to popular OOD scoring functions [20, 21, 31, 30]. We find that summing labels' scores using previous methods is inferior to summing labels' energies, emphasizing the need for JointEnergy. For example, simply summing over the logits across labels results in up to 51.93% degradation in FPR95 on MS-COCO. Our study therefore underlines the importance of properly choosing both the label-wise scoring function and the aggregation method. Below we summarize our key results and contributions:

- We propose a novel method JointEnergy—addressing an important yet underexplored problem—OOD detection for multi-label classification networks. Our method establishes state-of-the-art performance, reducing the average FPR95 by up to 10.05%. We show theoretical interpretaiton, underpinning our method from a joint likelihood perspective.

- We conduct extensive ablations which reveals important insights for multi-label OOD uncertainty estimation under (1) different aggregation functions, (2) different label-wise OOD scoring functions, and (3) the compatibility thereof.

- We curate three evaluation tasks in the multi-label setting from three real-world high-resolution image databases, which enables future research to evaluate OOD detection in a multi-label setting. Our code and dataset will be released for reproducible research.

2 Background

Multi-label Classification Multi-label classification is the supervised learning problem where an instance may be associated with multiple labels. Let $\mathcal{X}$ (resp. $\mathcal{Y}$) be the input (resp. output) space and let $\mathcal{P}$ be a distribution over $\mathcal{X} \times \mathcal{Y}$, and let $f : \mathcal{X} \rightarrow \mathcal{Y}$ be a neural network trained on samples drawn from $\mathcal{P}$ to predict the labels of an input sample $\mathbf{x}$. An input can be associated with a subset of labels in $\mathcal{Y} = \{1, 2, ..., K\}$. This set is represented by a vector $\mathbf{y} = [y_1, y_2, ..., y_K]$, where $y_i = 1$ if and only if label i is associated with instance $\mathbf{x}$, and 0 otherwise. We use a convolutional neural network with shared feature space and derive the multi-label output prediction. In contrast to learning completely disjoint classifiers [51], the end-to-end training with a shared representation space can better capture the dependencies among labels [43]. This has become a de facto training mechanism for multi-label classification, with various domain applications [34, 35, 55, 50].

Out-of-distribution Detection The problem of OOD detection for multi-label classification is defined as follows. Denote by $\mathcal{D}_{\text{in}}$ the marginal distribution of $\mathcal{P}$ over $\mathcal{X}$, which represents the distribution of in-distribution data. At test time, the environment can incur an out-of-distribution $\mathcal{D}_{\text{out}}$ over $\mathcal{X}$. The goal of OOD detection is to define a decision function G such that:

$$G(\mathbf{x}; f) = \begin{cases} 0 & \text{if } \mathbf{x} \sim \mathcal{D}_{\text{out}}, \\ 1 & \text{if } \mathbf{x} \sim \mathcal{D}_{\text{in}}. \end{cases}$$

An input is considered an OOD if it does not contain any label in the in-distribution data. In practice, $\mathcal{D}_{\text{out}}$ is often defined by a distribution that simulates anomalies encountered during deployment time, such as samples from an irrelevant distribution whose label set has no intersection with $\mathcal{Y}$.

3 Method

In this work, we propose a novel method for OOD detection in multi-label classification networks, where input can have several labels (see Figure 1). In what follows, we first introduce a label-wise energy function, and then propose *JointEnergy* that can leverage the joint information across labels in a theoretically meaningful way.

Label-wise Free Energy We consider a standard pre-trained multi-label neural classifier, with a shared parameter space θ up to the penultimate feature layer. During inference time, for a given input $\mathbf{x}$, the (logit) output for the i-th class is:

$$f_{y_i}(\mathbf{x}) = h(\mathbf{x}; \theta) \cdot \mathbf{w}_{\text{cls}}^i, \tag{1}$$

where $\mathbf{w}_{\text{cls}}^i$ is the weight vector corresponding to class i, and $h(\mathbf{x}; \theta)$ is the feature vector in the penultimate layer. The predictive probability for each binary label y_i is made by a binary logistic classifiers:

$$p(y_i = 1 \mid \mathbf{x}) = \frac{e^{f_{y_i}(\mathbf{x})}}{1 + e^{f_{y_i}(\mathbf{x})}},$$

where $i \in \{1, 2, ..., K\}$. The logistic classifier output can be viewed as the softmax with two logits—0 and $f_{y_i}(\mathbf{x})$, respectively. For each class y_i, we define *label-wise free energy* as follows:

$$E_{y_i}(\mathbf{x}) = -\log(1 + e^{f_{y_i}(\mathbf{x})}). \tag{2}$$

For illustration, we show the label-wise energy distribution for a subset of PASCAL-VOC classes in Figure 2 (green color). Label-wise energy capture the OOD uncertainty for a single label [36], but unfortunately does not capture uncertainty jointly across labels.

JointEnergy We propose a novel scoring function that takes into account the joint uncertainty across labels, and provide mathematical justification from a joint likelihood perspective. In particular, our method is the first to consider the joint estimation of OOD uncertainty across labels:

$$E_{\text{joint}}(\mathbf{x}) = \sum_{i=1}^{K} -E_{y_i}(\mathbf{x}) \tag{3}$$

Figure 2: Label-wise energy scores $-E_{y_i}(\mathbf{x})$ distribution. The in-distribution classes (each per row) are a subset from PASCAL-VOC (green). OOD test data is from ImageNet (gray), which is the same for all labels. x-axis is in log scale for visibility.

In particular, *JointEnergy* takes the summation of label-wise energy scores across all labels. Note that in the above equations, label-wise energy $E_{y_i}(\mathbf{x})$ by definition is a negative value, and the aggregation methods output a positive value by negation. This aligns with the convention that a larger score indicates in-distribution and vice versa.

Mathematical Interpretation We provide mathematical interpretation for *JointEnergy*. To interpret *JointEnergy*, we first resort to the energy-based model [28], where the conditional likelihood $p(\mathbf{x} \mid y_i = 1)$ is given by:

$$p(\mathbf{x} \mid y_i = 1) = \frac{e^{-E_{y_i}(\mathbf{x})}}{\int_{\mathbf{x}|y_i} e^{-E_{y_i}(\mathbf{x})}}, \tag{4}$$

and $Z_{y_i} = \int_{\mathbf{x}|y_i} e^{-E_{y_i}(\mathbf{x})}$ is the normalized density.

We now show that *JointEnergy* can be interpreted from the joint likelihood perspective:

$$E_{\text{joint}}(\mathbf{x}) = \sum_{i=1}^{K} \log \left(p(\mathbf{x} \mid y_i = 1) \cdot Z_{y_i} \right) \tag{5}$$

$$= \sum_{i=1}^{K} \log p(\mathbf{x} \mid y_i = 1) + \underbrace{\sum_{i=1}^{K} \log Z_{y_i}}_{Z:\text{constant for all } \mathbf{x}} \tag{6}$$

By applying Bayesian rule for each term $\log p(\mathbf{x} \mid y_i = 1)$ in Equation 6, we have

$$E_{\text{joint}}(\mathbf{x}) = \log \prod_{i=1}^{K} \frac{p(y_i = 1 \mid \mathbf{x}) \cdot p(\mathbf{x})}{p(y_i = 1)} + Z \tag{7}$$

$$= \log \prod_{i=1}^{K} p(y_i = 1 \mid \mathbf{x}) + K \cdot \log p(\mathbf{x})$$

$$+ \underbrace{(Z - \log \prod_{i=1}^{K} p(y_i = 1))}_{C:\text{ constant for all } \mathbf{x}} \tag{8}$$

Given all labels y_i are conditionally independent[1], we have $\prod_{i=1}^{K} p(y_i = 1 \mid \mathbf{x}) = p(y_1, y_2, ..., y_K \mid \mathbf{x})$. Therefore, Equation 8 is equivalent to:

$$
\begin{aligned}
E_{\text{joint}}(\mathbf{x}) &= \log p(y_1, y_2, \ldots, y_K \mid \mathbf{x}) \\
&\quad + K \cdot \log p(\mathbf{x}) + C \tag{9}
\end{aligned}
$$

$$
\begin{aligned}
&= \log \frac{p(\mathbf{x} \mid y_1, y_2, ..., y_K) \cdot \prod_{i=1}^{K} p(y_i)}{p(\mathbf{x})} \\
&\quad + K \cdot \log p(\mathbf{x}) + C \tag{10}
\end{aligned}
$$

$$
= \underbrace{\log p(\mathbf{x} \mid y_1, y_2, ..., y_K)}_{\text{joint conditional log likelihood, } \uparrow \text{ for in-distribution}}
$$

$$
+ \underbrace{(K-1) \cdot \log p(\mathbf{x})}_{\text{log data density, } \uparrow \text{ for in-distribution}} + \underbrace{Z}_{\text{constant for all } \mathbf{x}} \tag{11}
$$

Rationale of Equation 11   The equation above suggests that $E_{\text{joint}}(\mathbf{x})$ is aligned with the joint conditional log likelihood and log data density. The second term is desirable for OOD detection since it reflects the underlying data density, which is higher for in-distribution data $\mathbf{x}$. The first term takes into account joint estimation across labels, which is new to our multi-label setting and was not previously considered in multi-class setting [36]. The first term allows even further discriminativity between in- vs. OOD data, since OOD data is expected to have lower joint conditional likelihood (*i.e.*, not associated with any of the labels). In contrast, having multiple dominant labels is indicative of an in-distribution input, which is a characteristic that *JointEnergy* captures. As a major advantage, our method circumvents the challenge to directly estimate the joint likelihood using generative models, which can be can computationally intractable to train and optimize on multi-label datasets [22].

3.1   JointEnergy for Multi-Label OOD Detection

We propose using the JointEnergy function $E_{\text{joint}}(\mathbf{x})$ defined in Section 3 for OOD detection:

$$
G(\mathbf{x}; \tau) = \begin{cases} \text{out} & \text{if } E_{\text{joint}}(\mathbf{x}) \leq \tau, \\ \text{in} & \text{if } E_{\text{joint}}(\mathbf{x}) > \tau, \end{cases} \tag{12}
$$

where τ is the energy threshold, and can be chosen so that a high fraction of in-distribution data is correctly classified by $G(\mathbf{x}; \tau)$. The sensitivity analysis on τ is provided in Figure 3. A data point with higher JointEnergy $E_{\text{joint}}(\mathbf{x})$ is considered as in-distribution, and vice versa (see Figure 1).

4   Experiments

In this section, we describe our experimental setup (Section 4.1) and demonstrate the effectiveness of our method on several OOD evaluation tasks (Section 4.2). We also conduct extensive ablation studies and comparative analysis that leads to an improved understanding of different methods.

4.1   Setup

In-distribution Datasets We consider three multi-label datasets: MS-COCO [32], PASCAL-VOC [13], and NUS-WIDE [7]. MS-COCO consists of 82,783 training, 40,504 validation, and 40,775 testing images with 80 common object categories. PASCAL-VOC contains 22,531 images across 20 classes. NUS-WIDE includes 269,648 images across 81 concept labels. Since NUS-WIDE has invalid and untagged images, we follow the work [58] and use 119,986 training images and 80,283 test images.

Training Details We train three multi-label classifiers, one for each dataset above. The classifiers have a DenseNet-121 backbone architecture, with a final layer that is replaced by 2 fully connected layers. Each classifier is pre-trained on ImageNet-1K and then fine-tuned with the logistic sigmoid function to its corresponding multi-label dataset. We use the Adam optimizer [25] with standard parameters ($\beta_1 = 0.9$, $\beta_2 = 0.999$). The initial learning rate is 10^{-4} for the fully connected layers

---

[1]Note that this is sufficient but not necessary for our results to hold. Our theoretical assumption is made to ease and facilitate the interpretation from a joint likelihood perspective. Importantly, our experiments in Section 4 hold without imposing any condition and demonstrate superior performance.

Table 1: OOD detection performance comparison using energy-based approaches vs. competitive baselines. We use DenseNet [24] to train on the in-distribution datasets. We use a subset of ImageNet classes as OOD test data, as described in Section 4.1. All values are percentages. ↑ indicates larger values are better, and ↓ indicates smaller values are better. **Bold** numbers are superior results. Description of baseline methods, additional evaluation results on different OOD test data, and different architecture (*e.g.*, ResNet) can be found in the Appendix.

$\mathcal{D}_{in}$	MS-COCO	PASCAL-VOC	NUS-WIDE
		FPR95 / AUROC / AUPR	
OOD Score	↓	↑	↑
MaxLogit [20]	43.53 / 89.11 / 93.74	45.06 / 89.22 / 83.14	56.46 / 83.58 / 94.32
MSP [21]	79.90 / 73.70 / 85.37	74.05 / 79.32 / 72.54	88.50 / 60.81 / 87.00
ODIN [31]	43.53 / 89.11 / 93.74	45.06 / 89.22 / 83.16	56.46 / 83.58 / 94.32
Mahalanobis [30]	46.86 / 88.59 / 93.85	41.74 / 88.65 / 81.12	62.67 / 84.02 / 95.25
LOF [4]	80.44 / 73.95 / 86.01	86.34 / 69.21 / 58.93	85.21 / 67.75 / 89.61
Isolation Forest [33]	94.39 / 49.04 / 66.87	93.22 / 50.67 / 35.78	95.69 / 53.12 / 83.32
JointEnergy	**33.48 / 92.70 / 96.25**	**41.01 / 91.10 / 86.33**	**48.98 / 88.30 / 96.40**

and 10^{-5} for convolutional layers. We also augmented the data with random crops and random flips to obtain color images of size 256×256. After training, the mAP is 87.51% for PASCAL-VOC, 73.83% for MS-COCO, and 60.22% for NUS-WIDE. All experiments are conducted on NVIDIA GeForce RTX 2080Ti.

Out-of-distribution Datasets To evaluate the models trained on the in-distribution datasets above, we follow the same set up as in [20] and use ImageNet [10] for its generality. Besides, we evaluate against the Textures dataset [9] as OOD. For ImageNet, we use the same set of 20 classes chosen from ImageNet-22K as in [20]. These classes are chosen not to overlap with ImageNet-1k since the multi-label classifiers are pre-trained on ImageNet-1K. Specifically, we use the following classes for evaluating the MS-COCO and PASCAL-VOC pre-trained models: *dolphin, deer, bat, rhino, raccoon, octopus, giant clam, leech, venus flytrap, cherry tree, Japanese cherry blossoms, redwood, sunflower, croissant, stick cinnamon, cotton, rice, sugar cane, bamboo, and turmeric*. Since NUS-WIDE contains high-level concepts like animal, plants and flowers, we use a different set of classes that are distinct from NUS-WIDE: *asterism, battery, cave, cylinder, delta, fabric, filament, fire bell, hornet nest, kazoo, lichen, naval equipment, newspaper, paperclip, pythium, satellite, thumb, x-ray tube, yeast, zither*.

Evaluation Metrics We measure the following metrics that are commonly used for OOD detection: (1) the false positive rate (FPR95) of OOD examples when the true positive rate of in-distribution examples is at 95%; (2) the area under the receiver operating characteristic curve (AUROC); and (3) the area under the precision-recall curve (AUPR).

4.2 Results

How do JointEnergy compare to common OOD detection methods? In Table 1, we compare energy-based approaches against competitive OOD detection methods in literature, where *JointEnergy* demonstrates state-of-the-art performance. For fair comparisons, we consider approaches that rely on pre-trained models (without performing retraining or fine-tuning). Following the set up in [20], all the numbers reported are evaluated on ImageNet OOD test data, as described in Section 4.1. We provide additional evaluation results for the Texture OOD test dataset in the supplementary. Most baselines such as MaxLogit [20], Maximum Softmax Probability (MSP) [21], ODIN [31] and Mahalanobis [30] derive OOD indicator scores based on the maximum-valued statistics among all labels. Local Outlier Factor (LOF) [4] uses K-nearest neighbors (KNN) to estimate the local density, where OOD examples are detected from having lower density compared to their neighbors. Isolation forest [33] is a tree-based approach, which detects anomaly based on the path length from the root node to the terminating node.

Among different approaches, *JointEnergy* outperforms the best-performing baseline across all three multi-label classifiers considered. In particular, on a network trained with the MS-COCO dataset, *JointEnergy* reduces FPR95 by **10.05**%, compared to MaxLogit. We provide the AUROC curves for our method JointEnergy in Figure 3, for all three in-distribution datasets considered. The y-axis is the true positive rate (TPR), whereas the x-axis is the FPR. The curves indicate how the OOD

Table 2: Ablation study on the effect of summation for prior approaches. We use DenseNet [24] to train on the in-distribution datasets. We use ImageNet as OOD test data as described in Section 4.1. Note that *Sum* does not apply to tree-based or KNN-based approaches (e.g., LOF and Isolation Forest).

OOD Score	$\mathcal{D}_{in}$ Aggregation	MS-COCO	PASCAL FPR95 / AUROC / AUPR ↓ ↑ ↑	NUS-WIDE
Logit	Sum	95.46 / 61.81 / 80.39	87.18 / 72.68 / 61.24	96.53 / 51.75 / 82.55
Prob	Sum	45.04 / 89.32 / 94.40	**38.57** / 86.53 / 79.10	50.84 / 83.82 / 95.15
ODIN	Sum	56.56 / 84.62 / 92.24	50.35 / 79.45 / 70.19	56.26 / 81.04 / 94.34
Mahalanobis	Sum	53.43 / 87.52 / 93.35	44.43 / 87.76 / 79.86	69.05 / 80.46 / 94.09
LOF	Sum	N/A	N/A	N/A
Isolation Forest	Sum	N/A	N/A	N/A
Energy (ours)	Sum	**33.48 / 92.70 / 96.25**	41.01 / **91.10 / 86.33**	**48.98 / 88.30 / 96.40**

detection performance changes as we vary the threshold τ in Equation 12. *We additionally evaluate on a different architecture, ResNet [18], for which we observe consistent improvement and provide details in the supplementary.*

We also note here that existing approaches using a pre-trained model (such as Mahalanobis [30]) have hyperparameters that need to be tuned. In contrast, using an energy-based method on pre-trained models is parameter-free and easy to use and deploy. In particular, the Mahalanobis approach is based on the assumption that feature representation forms class-conditional Gaussian distributions, and hence may not be well suited for the multi-label setting (which requires joint distribution to be learned).

How do different aggregation methods affect OOD detection performance? In Table 3, we also perform a comparative analysis of the effect of different aggregation functions that combine label-wise energy scores. As an alternative, we consider

$$E_{\max}(\mathbf{x}) = \max_i -E_{y_i}(\mathbf{x}), \qquad (13)$$

Figure 3: AUROC curves for OOD detector obtained from three in-distribution multi-label classification datasets.

which finds the largest label-wise energy score among all labels. We observe that *MaxEnergy* does not outperform *JointEnergy*, which utilizes information jointly from across the labels. The performance of *MaxEnergy* is on par with MaxLogit since *MaxEnergy*, given by $\max_i \log(1+e^{f_{y_i}(\mathbf{x})})$, is approximately close to the MaxLogit when $f_{y_i}(\mathbf{x})$ is large. The results underline the importance of taking into account information from multiple labels, not just the maximum-valued label. This is because, in multi-label classification, the model may assign high probabilities to several classes. Theoretically, *JointEnergy* is also more meaningful, and can be interpreted from a joint likelihood perspective as shown in Section 3.

What is the effect of applying the aggregation method to prior methods? As an extension, we explore the effectiveness of applying the aggregation method to previous scoring functions such as logit [20], MSP [21] and ODIN [31]. The results are summarized in Table 2. We calculate scores based on the logit $f_{y_i}(\mathbf{x})$, sigmoid of the logit $\frac{1}{1+e^{-f_{y_i}(\mathbf{x})}}$, ODIN score, as well as Mahalanobis

Table 3: Ablation study on the effect of aggregation methods: max vs summation. Values are AUROC.

$\mathcal{D}_{in}$	MaxEnergy	JointEnergy
MS-COCO	89.11	**92.70**
PASCAL-VOC	89.22	**91.10**
NUS-WIDE	83.58	**88.30**

Figure 4: Label-wise energy scores $-E_{y_i}(\mathbf{x})$ for in-distribution example from PASCAL-VOC (left), and OOD input from ImageNet (right). The OOD input is misclassified using MaxLogit score since the dominant output has a high activation, making it indistinguishable from an in-distribution data's MaxLogit score. In contrast, *JointEnergy* correctly classifies both images since it results in larger differences in scores between in-distribution and OOD inputs.

distance score $M_{y_i}(\mathbf{x})$ by treating each label independently. We then perform summation across the label-wise scores as the overall OOD score. This ablation essentially replaces the *Max* aggregation with *Sum*, which helps understand the extent to which previous approaches are amenable in the multi-label setting. Note that the summation aggregation method does not apply to tree-based or KNN-based approaches such as LOF and Isolation Forest.

Interestingly, we found that applying summation over individual logit/MSP/ODIN/Mahalanobis scores from each label does not yield competitive results, and in many cases worsens the performance. For example, simply summing over the logits across the labels leads to severe degradation in performance since the outputs are mixed with positive and negative numbers. On MS-COCO, the FPR degrades from 43.53% using MaxLogit to 95.46% (using SumLogit). In contrast, *JointEnergy* does not suffer from this issue since the energy scores for each individual label have a uniform sign. More importantly, the label-wise scores derived from energy is theoretically more meaningful than logit/MSP/ODIN/Mahalanobis, since it is provably aligned with the probability density of the training data corresponding to the label. This underlines the importance of properly choosing the label-wise scoring function to be compatible with the aggregation method.

JointEnergy vs. SumProb We highlight the advantage of JointEnergy over SumProb both empirically and theoretically. As seen in Table 2, the performance difference between JointEnergy and SumProb is substantial. In particular, on MS-COCO, our method outperforms SumProb by 11.56% (FPR95). For threshold independent metric AUROC, JointEnergy consistently outperforms SumProb by 3.38% (MS-COCO), 4.57% (PASCAL), and 4.48% (NUS-WIDE).

Qualitative case study Lastly, to provide further insights on our method, we qualitatively examine examples from the multi-label classification dataset PASCAL-VOC (in-dist.) and OOD input from the ImageNet that are correctly classified by *JointEnergy* but not MaxLogit. In Figure 4 (left), we see an in-distribution example is labeled as `dog`, `car`, `chair` and `person`, with *MaxLogit* score 1.63 and *JointEnergy* score 3.23. We also show an OOD input (Figure 4, right) with a single dominant activation on the `bird` class, with MaxLogit score 2.14 and *JointEnergy* score 2.19. In this example, taking the sum appropriately resulted in a higher score for the in-distribution image than the OOD image. Contrarily, MaxLogit's score for the in-distribution image was lower than that of the OOD image, which results in ineffective detection.

5   Related Work

Multi-label classification The task of identifying multiple classes within an input example is of significant interest in many applications [51], with deep neural networks being commonly used as the classifier. Natural images usually contain several objects and may have many associated tags [54]. [15] use convolutional neural networks (CNN) to annotate images with 3 or 5 tags on the NUS-WIDE dataset. [5] use CNNs to tag images of road scenes from 52 possible labels. In the medical domain, [55] present a chest X-ray dataset in which one image may contain multiple abnormalities. Multi-label classification is also prominent in natural language processing [40]. Our proposed method is therefore relevant to a wide range of applications in the real world.

Out-of-distribution uncertainty for pre-trained models The softmax confidence score has become a common baseline for OOD detection [21]. A theoretical investigation [19] shows that neural networks with ReLU activation can produce arbitrarily high softmax confidence for OOD inputs. Several works attempt to improve the OOD uncertainty estimation by using deep ensembles [27], ODIN score [31], Mahalanobis distance-based confidence score [30], and generalized ODIN score [23]. [11] propose to learn the confidence score by using an auxiliary branch to derive the OOD score. Recent work using energy score demonstrated state-of-the-art performance on OOD detection tasks [36]. However, previous methods primarily focused on multi-class classification networks. In contrast, in our work, we propose a parameter-free measurement that allows effective OOD detection in the underexplored *multi-label* setting, where the information from across various labels are combined in a theoretically meaningful manner.

Out-of-distribution detection with model fine-tuning While our work primarily focused on OOD detection for pre-trained neural networks, a parallel line of research has also explored using auxiliary outlier OOD data to help the OOD detector generalize better. Auxiliary data allows the model to be explicitly regularized through fine-tuning, producing lower confidence on anomalous examples [3, 14, 37, 38, 48]. A loss function is used to force the predictive distribution of OOD samples toward a uniform distribution [29]. Recently, [38] explore training by adding a background class for an OOD score. However, existing works have primarily focused on the multi-class classification setting. We leave the fine-tuning aspect with auxiliary data for multi-label classification as future exploration.

Generative modeling for out-of-distribution detection Generative models [12, 26, 45, 53, 49] can be alternative approaches for detecting OOD examples, as they directly estimate the in-distribution density and can declare a test sample to be out-of-distribution if it lies in the low-density regions. However, as shown by [39], deep generative models can assign a high likelihood to out-of-distribution data. Deep generative models can be more effective for out-of-distribution detection using improved metrics [6], including likelihood ratio [44, 47]. Though our work is based on discriminative classification models, we show that label-wise energy scores can be theoretically interpreted from a data density perspective. More importantly, generative based models [22] can be prohibitively challenging to train and optimize, especially on large and complex multi-label datasets that we considered (*e.g.*, MS-COCO, NUS-WIDE etc). In contrast, our method relies on a discriminative multi-label classifier, which can be much easier to optimize using standard SGD.

Energy-based learning Energy-based machine learning models date back to Boltzmann machines [1, 46]. Energy-based learning [28, 41, 42] provides a unified framework for many probabilistic and non-probabilistic approaches to learning. Recent work [57] also demonstrated using energy functions to train GANs [16], where the discriminator uses energy values to differentiate between real and generated images. [56] first showed that a discriminative classifier can be interpreted from an energy-based perspective. Energy-based methods are also used in structure prediction [2, 52]. Grathwohl et al. [17] showed that a discriminative classifier can be interpreted from an energy-based perspective. The proposed JEM optimization objective estimates the joint distribution $p(\mathbf{x}, y)$ from a generative perspective, which requires estimating the normalized densities and can be intractable and unstable to compute. Liu et al. [36] propose to use energy score for OOD detection that is derived from a pure discriminatively trained classifier, which demonstrated superior performance for multi-class classification networks. In contrast, our work focuses on a multi-label setting, where we contribute both empirical and theoretical insights and demonstrate the effectiveness of utilizing information jointly from across all labels.

6 Conclusion and Outlook

In this work, we propose energy scores for OOD detection in the multi-label classification setting. We show that aggregating energies over all labels into *JointEnergy* results in better discrimination between in-distribution and OOD inputs compared to using information from only one label's information. Additionally, we justify the mathematical interpretation of *JointEnergy* from a joint likelihood perspective. *JointEnergy* obtains better OOD detection performance compared to competitive baseline methods, establishing new state-of-the-art on this task. Applications of multi-label classification can benefit from our methods, and we anticipate further research in OOD detection to extend this work. We hope our work will increase the attention toward a broader view of OOD uncertainty estimation for multi-label classification.

References

[1] David H Ackley, Geoffrey E Hinton, and Terrence J Sejnowski. A learning algorithm for boltzmann machines. *Cognitive science*, 9(1):147–169, 1985.

[2] David Belanger and Andrew McCallum. Structured prediction energy networks. In *International Conference on Machine Learning*, pages 983–992, 2016.

[3] Petra Bevandić, Ivan Krešo, Marin Oršić, and Siniša Šegvić. Discriminative out-of-distribution detection for semantic segmentation. *arXiv preprint arXiv:1808.07703*, 2018.

[4] Markus M Breunig, Hans-Peter Kriegel, Raymond T Ng, and Jörg Sander. Lof: identifying density-based local outliers. In *Proceedings of the 2000 ACM SIGMOD international conference on Management of data*, pages 93–104, 2000.

[5] Long Chen, Wujing Zhan, Wei Tian, Yuhang He, and Qin Zou. Deep integration: A multi-label architecture for road scene recognition. *IEEE Transactions on Image Processing*, 28(10):4883–4898, 2019.

[6] Hyunsun Choi and Eric Jang. Generative ensembles for robust anomaly detection. 2018.

[7] Tat-Seng Chua, Jinhui Tang, Richang Hong, Haojie Li, Zhiping Luo, and Yan-Tao Zheng. Nus-wide: A real-world web image database from national university of singapore. In *Proc. of ACM Conf. on Image and Video Retrieval (CIVR'09)*, Santorini, Greece., 2009.

[8] M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

[9] Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3606–3613, 2014.

[10] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[11] Terrance DeVries and Graham W Taylor. Learning confidence for out-of-distribution detection in neural networks. *arXiv preprint arXiv:1802.04865*, 2018.

[12] Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

[13] M. Everingham, S. M. A. Eslami, L. Van Gool, C. K. I. Williams, J. Winn, and A. Zisserman. The pascal visual object classes challenge: A retrospective. *International Journal of Computer Vision*, 111(1):98–136, January 2015.

[14] Yonatan Geifman and Ran El-Yaniv. Selectivenet: A deep neural network with an integrated reject option. *arXiv preprint arXiv:1901.09192*, 2019.

[15] Yunchao Gong, Yangqing Jia, Thomas Leung, Alexander Toshev, and Sergey Ioffe. Deep convolutional ranking for multilabel image annotation. *arXiv preprint arXiv:1312.4894*, 2013.

[16] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.

[17] Will Grathwohl, Kuan-Chieh Wang, Joern-Henrik Jacobsen, David Duvenaud, Mohammad Norouzi, and Kevin Swersky. Your classifier is secretly an energy based model and you should treat it like one. In *International Conference on Learning Representations*, 2019.

[18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pages 630–645. Springer, 2016.

[19] Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 41–50, 2019.

[20] Dan Hendrycks, Steven Basart, Mantas Mazeika, Mohammadreza Mostajabi, Jacob Steinhardt, and Dawn Song. A benchmark for anomaly segmentation. *arXiv preprint arXiv:1911.11132*, 2019.

[21] Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

[22] Tobias Hinz, Stefan Heinrich, and Stefan Wermter. Generating multiple objects at spatially distinct locations. *arXiv preprint arXiv:1901.00686*, 2019.

[23] Yen-Chang Hsu, Yilin Shen, Hongxia Jin, and Zsolt Kira. Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10951–10960, 2020.

[24] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4700–4708, 2017.

[25] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[26] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[27] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in neural information processing systems*, pages 6402–6413, 2017.

[28] Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and F Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

[29] Kimin Lee, Honglak Lee, Kibok Lee, and Jinwoo Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. *arXiv preprint arXiv:1711.09325*, 2017.

[30] Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems*, pages 7167–7177, 2018.

[31] Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *6th International Conference on Learning Representations, ICLR 2018*, 2018.

[32] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer, 2014.

[33] Fei Tony Liu, Kai Ming Ting, and Zhi-Hua Zhou. Isolation forest. In *2008 Eighth IEEE International Conference on Data Mining*, pages 413–422. IEEE, 2008.

[34] Jingzhou Liu, Wei-Cheng Chang, Yuexin Wu, and Yiming Yang. Deep learning for extreme multi-label text classification. In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 115–124, 2017.

[35] Shuhua Monica Liu and Jiun-Hung Chen. A multi-label classification based approach for sentiment classification. *Expert Systems with Applications*, 42(3):1083–1093, 2015.

[36] Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. *Advances in Neural Information Processing Systems*, 2020.

[37] Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. In *Advances in Neural Information Processing Systems*, pages 7047–7058, 2018.

[38] Sina Mohseni, Mandar Pitale, JBS Yadawa, and Zhangyang Wang. Self-supervised learning for generalizable out-of-distribution detection. 2020.

[39] Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? *arXiv preprint arXiv:1810.09136*, 2018.

[40] Jinseok Nam, Jungi Kim, Eneldo Loza Mencía, Iryna Gurevych, and Johannes Fürnkranz. Large-scale multi-label text classification—revisiting neural networks. In *Joint european conference on machine learning and knowledge discovery in databases*, pages 437–452. Springer, 2014.

[41] Marc'Aurelio Ranzato, Christopher Poultney, Sumit Chopra, and Yann L Cun. Efficient learning of sparse representations with an energy-based model. In *Advances in neural information processing systems*, pages 1137–1144, 2007.

[42] Marc'Aurelio Ranzato, Y-Lan Boureau, Sumit Chopra, and Yann LeCun. A unified energy-based framework for unsupervised learning. In *Artificial Intelligence and Statistics*, pages 371–379, 2007.

[43] Jesse Read and Fernando Perez-Cruz. Deep learning for multi-label classification. *arXiv preprint arXiv:1502.05988*, 2014.

[44] Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pages 14680–14691, 2019.

[45] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

[46] Ruslan Salakhutdinov and Hugo Larochelle. Efficient learning of deep boltzmann machines. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 693–700, 2010.

[47] Joan Serrà, David Álvarez, Vicenç Gómez, Olga Slizovskaia, José F Núñez, and Jordi Luque. Input complexity and out-of-distribution detection with likelihood-based generative models. *arXiv preprint arXiv:1909.11480*, 2019.

[48] Akshayvarun Subramanya, Suraj Srinivas, and R Venkatesh Babu. Confidence estimation in deep neural networks via density modelling. *arXiv preprint arXiv:1707.07013*, 2017.

[49] Esteban G Tabak and Cristina V Turner. A family of nonparametric density estimation algorithms. *Communications on Pure and Applied Mathematics*, 66(2):145–164, 2013.

[50] Konstantinos Trohidis, Grigorios Tsoumakas, George Kalliris, and Ioannis P Vlahavas. Multi-label classification of music into emotions. In *ISMIR*, volume 8, pages 325–330, 2008.

[51] Grigorios Tsoumakas and Ioannis Katakis. Multi-label classification: An overview. *International Journal of Data Warehousing and Mining (IJDWM)*, 3(3):1–13, 2007.

[52] Lifu Tu and Kevin Gimpel. Learning approximate inference networks for structured prediction. In *International Conference on Learning Representations*, 2018.

[53] Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. In *Advances in neural information processing systems*, pages 4790–4798, 2016.

[54] Jiang Wang, Yi Yang, Junhua Mao, Zhiheng Huang, Chang Huang, and Wei Xu. Cnn-rnn: A unified framework for multi-label image classification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2285–2294, 2016.

[55] Xiaosong Wang, Yifan Peng, Le Lu, Zhiyong Lu, Mohammadhadi Bagheri, and Ronald M Summers. Chestx-ray8: Hospital-scale chest x-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2097–2106, 2017.

[56] Jianwen Xie, Yang Lu, Song-Chun Zhu, and Yingnian Wu. A theory of generative convnet. In *International Conference on Machine Learning*, pages 2635–2644, 2016.

[57] Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial networks. In *5th International Conference on Learning Representations, ICLR 2017*, 2019.

[58] Feng Zhu, Hongsheng Li, Wanli Ouyang, Nenghai Yu, and Xiaogang Wang. Learning spatial regularization with image-level supervisions for multi-label image classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5513–5522, 2017.