BeDiscovER: The Benchmark of Discourse Understanding in the Era of Reasoning Language Models

Abstract

We introduce BeDiscovER (Benchmark of Discourse Understanding in the Era of Reasoning Language Models), an up-to-date, comprehensive suite for evaluating the discourse-level knowledge of modern LLMs. BeDiscovER compiles 5 publicly available discourse tasks across discourse lexicon, (multi-)sentential, and documental levels, with in total 52 individual datasets. It covers both extensively studied tasks such as discourse parsing and temporal relation extraction, as well as some novel challenges such as discourse particle disambiguation (e.g., "*just*"), and also aggregates a shared-task on Discourse Relation Parsing and Tree-banking[1] for multilingual and multi-framework discourse relation classification. We evaluate open-source LLMs: Qwen3 series, DeepSeek-R1, and frontier reasoning model GPT-5-mini on BeDiscovER, and find that state-of-the-art models exhibits strong performance in arithmetic aspect of temporal reasoning, but they struggle with long-dependency reasoning and some subtle semantic and discourse phenomena, such as rhetorical relation classification.

1 Introduction

Large Language Models (LLMs) have been tasked with solving increasingly difficult problems that require strong reasoning abilities across text understanding, common-sense, math, and coding (Shao et al., 2024; Jaech et al., 2024; Ke et al., 2025). Still, it is an open question how the discourse knowledge–that is, the ability to process and understand the interplay of multi-sentence and long-context information–of state-of-the-art reasoning models varies across various tasks and phenomena.

Discourse analysis is an active research area with demonstrated impact across downstream tasks, such as multi-span question answering (Prasad et al., 2023; Zhang et al., 2024), emotion detec-

tion (Juhng et al., 2023), and propaganda identification (Chernyavskiy et al., 2024). Its attention to both local and global levels of text understanding has also spurred advances in long-document language modeling (Feng et al., 2023; Ivgi et al., 2023; Buchmann et al., 2024). To achieve deeper understanding of natural language and induce stronger future reasoning models, it is essential for LLMs to capture and reason over discourse knowledge.

Recent studies have explored this question by evaluating LLMs such as ChatGPT's performance on a range of sentence-level tasks, such as temporal (Yuan et al., 2023; Wei et al., 2024), causal (Chan et al., 2024), and discourse relations (Yung et al., 2024; Fan et al., 2024; Miao et al., 2024). However, each of these studies uses a different set of models, metrics (probing, prompting, acceptability judgment), and on a small set of discourse tasks, limiting any possible bigger-picture conclusions.

We introduce the Benchmark of Discourse Understanding in the Era of Reasoning Language Models (BeDiscovER)–a comprehensive, practical benchmark that covers five broad areas of discourse knowledge, namely: (1) Discourse Marker Understanding, (2) Temporal Reasoning, (3) Discourse Relation Recognition, (4) Sentence Ordering, and (5) Dialogue Discourse Parsing. In total, BeDiscovER comprises around 30,000 test instances across 52 publicly available datasets (most were annotated by human experts), 16 languages, and 6 discourse annotation frameworks, providing a practical testbed for evaluating LLMs' reasoning skills across lexical and semantic, rhetorical, temporal (both logical and arithmetic), and commonsense knowledge.

We use BeDiscovER to study several reasoning LLMs: Qwen3-series models (Yang et al., 2025), DeepSeek-R1 (Guo et al., 2025), DeepSeek-R1-Distll-Qwen-32B (Guo et al., 2025), and GPT-5-mini (OpenAI, 2025). We evaluate whether the LLMs can be prompted to give accurate answers.

---

[1] https://sites.google.com/view/disrpt2025/

This gives us indirect evidence about each model's discourse knowledge and allows us to compare models in a consistent way. Through extensive experiments, we conclude that whereas models like GPT-5-mini appear to have significant reasoning ability across many tasks, this ability is concentrated in some specific tasks in discourse understanding where pre-training data is abundant.

To the best of our knowledge, this is the first comprehensive benchmark to evaluate modern LLM's discourse understanding. We use BeDiscovER to bring together research efforts on different levels of discourse knowledge, and to uncover several phenomena where even state-of-the-art language models clearly lack decent reasoning, and to bring into focus those areas that future studies evaluating and even pre-/post-training LLMs should investigate in greater depth.

2 Related Work

Large Language Models. Recent advances in computational infrastructure and the availability of large-scale corpora have driven the development of LLMs capable of remarkable generalization (OpenAI, 2025; Achiam et al., 2023; Team et al., 2023; Touvron et al., 2023). These capabilities have been further enhanced by instruction tuning (Wei et al., 2021) and reinforcement learning from human feedback (Ouyang et al., 2022), enabling models to perform complex reasoning and follow diverse natural language instructions (Ke et al., 2025).

This scaling paradigm has fueled a wave of increasingly capable LLMs and pushing the boundaries across a wide spectrum of benchmarks, from graduate-level exams (Rein et al., 2024) and mathematical problem solving (Phan et al., 2025) to competitive programming and multi-agent systems (Kapoor et al., 2024; Liang et al., 2024). Despite these breakthroughs, LLMs continue to exhibit persistent limitations, particularly in modeling long-range dependencies, maintaining discourse coherence, and avoiding factual inconsistencies (Ivgi et al., 2023; Liang et al., 2023; Wu et al., 2024a). Discourse analysis, which focuses on understanding document-level structure, coherence, and information flow, offers a principled lens through which these limitations can be exposed and addressed. We pursue this line of research in this paper.

Discourse Knowledge of LLMs. Earlier studies evaluate LM's discourse knowledge using probing tasks (Kim et al., 2019; Li et al., 2021; Tao et al., 2024) where a classifier is trained to predict discourse properties, or extracting sentence representation from PLM's attention networks (Chen et al., 2019; Huber and Carenini, 2022; Li et al., 2023). QA-based evaluation has emerged as a popular alternative, offering greater granularity and flexibility: QADiscourse (Pyatkin et al., 2020), QA for reference/ellipsis resolution (Aralikatte et al., 2021), QA for discourse faithfulness (Miao et al., 2024), and Question Under Discussion (QUD) (Wu et al., 2023, 2024b). We follow a similar approach that prompts the LLMs to answer questions that designed to test different levels of discourse knowledge, while focusing on their answer accuracy, among others.

The scope of discourse knowledge evaluation varies widely. Some studies focus on specific theoretical frameworks, such as PDTB-style (Webber et al., 2019) discourse relation recognition (Miao et al., 2024; Yung et al., 2024) or SDRT-style (Asher and Lascarides, 2003) dialogue parsing (Fan et al., 2024). Others target particular domains, such as stylistic discourse in literature (Wang et al., 2023), or specific relational phenomena, including event relations (Wei et al., 2024) and temporal relations (Yuan et al., 2023; Fatemi et al., 2024).

Another related line of research focuses on generation capabilities of LLMs, such as discourse coherence assessment with DiscoScore (Zhao et al., 2023) and high-quality, instruction-following longtext generation benchmarks like LongBench (Bai et al., 2024) and LongGenBench (Wu et al., 2025).

In this paper, we position our work on the understanding aspect of discourse knowledge. Unlike prior studies that concentrate on specific frameworks or narrowly defined discourse tasks, our goal is to develop a comprehensive evaluation suite that spans multiple levels, tasks, and phenomena of discourse understanding.

3 BeDiscovER: Motivation and Coverage

3.1 Motivation

Our motivation stems from the convergence of two research areas: discourse analysis and large language models. Traditionally, discourse analysis has centered on theoretical frameworks and phenomena such as anaphora resolution, discourse relations, and textual coherence. More recently, it has expanded toward computational goals, including modeling long-distance dependencies, generating coherent narratives, and supporting pragmatic rea-

Level	Task	Dataset	Test Examples[¶]	Discourse Knowledge[‡]
Lexical	(1) Disc. Marker Understanding	*Just*-Manual (Sheffield et al., 2025)	90	L&S, CS
		Just-Subtitle (Sheffield et al., 2025)	139	L&S, CS
		Otherwise[†]	294	L&S, CS
(multi-) Sentence	(2) Temporal Reasoning	TimeBank-Dense (Cassidy et al., 2014)	1515	T, Logi, CS
		TDDiscourse (Naik et al., 2019)	1,500	T, Logi, CS
		ToT-Arithmetic (Fatemi et al., 2024)	1,850	T, A, CS
	(3) Disc. Relation Recognition	DISRPT25 Shared Task* (Braud et al., 2024)	8,757 (43,716)	R, CS
Document	(4) Sentence Ordering	AAN abstract (Wang et al., 2018)	806 (2,687)	Logi, R, CS
		ArXiv abstract (Chen et al., 2016)	898 (179,691)	Logi, R, CS
		Neurips abstract (Logeswaran et al., 2018)	377 (377)	Logi, R, CS
		NSF abstract(Logeswaran et al., 2018)	814 (20,366)	Logi, R, CS
		ROC stories (Mostafazadeh et al., 2016)	883 (9,816)	Logi, R, CS
		SIND (Huang et al., 2016)	808 (5,055)	Logi, R, CS
		Wikipedia movie plots[‖]	836 (3,345)	Logi, R, CS
	(5) Dialogue Disc. Parsing	STAC (Asher et al., 2016)	1,045	R, T, L&S, CS
		Molweni (Li et al., 2020)	3,930	R, T, L&S, CS
		MSDC (Thompson et al., 2024b)	4,914	R, T, L&S, CS

Table 1: Overview of level, task, dataset, number of test examples, and discourse knowledge covered by BeDiscovER. Test examples[¶]: For tasks (3) and (4), we evaluate a subset of the original datasets, with the original sample sizes indicated in parentheses. Discourse Knowledge[‡] abbreviations: L&S, R, T, Logi, A, CS denote *Lexicon & Semantics*, *Rhetorical*, *Temporal*, *Logic*, *Arithmetic*, and *Commonsense*, respectively. The reference for the Otherwise dataset[†] will be added in a future revision. DISRPT25 Shared Task* consists of 38 datasets, see details in Braud et al. (2024). We use the preprocessed datasets from: https://github.com/disrpt/sharedtask2025. Wikipedia movie plots[‖] data comes from Basu Roy Chowdhury et al. (2021).

soning (Naik et al., 2019; Parmar et al., 2024; Wu et al., 2024a; Cao et al., 2025). Meanwhile, LLMs have evolved from sentence-level learners to systems capable of long-document understanding, coherent generation, and advanced reasoning (Besta et al., 2025). This evolution underscores the growing need for discourse-level evaluation to diagnose weaknesses and guide further model development. Despite this convergence, research on LLMs' discourse understanding remains fragmented across tasks and frameworks (see §2), offering only a partial view of their true capabilities.

To address this gap, we introduce a unified benchmark designed to comprehensively assess discourse knowledge across multiple dimensions and linguistic phenomena (Table 1). Through this evaluation, we aim to provide a high-level picture of the current state of discourse understanding in reasoning-oriented LLMs, uncover their limitations, and inspire future directions such as discourse-aware post-training to enhance reasoning and downstream task performance.

3.2 Task Coverage

BeDiscovER tasks represent well-established discourse evaluation settings in three levels: **I. Lexicon**: Task (1) Discourse Marker Understanding. **II. Multi-sentence**: Task (2) Temporal Reasoning and (3) Discourse Relation Recognition.

III. Document-level structure: Task (4) Sentence Ordering and (5) Dialogue Discourse Parsing. Although not exhaustive, our task selection is representative, covering diverse knowledge types.

Each task is supported by multiple datasets, summarized in Table 1. When different splits exist, we only include test subset. We carefully curate datasets to capture complementary aspects of discourse phenomena. For example, within Task (2), TimeBank-Dense (Cassidy et al., 2014) targets local events in adjacent sentences, while TDDiscourse (Naik et al., 2019) emphasizes long-distance relations. To further enrich this category, we include a subset of Test-of-Time (Fatemi et al., 2024) on arithmetic temporal reasoning.

To ensure diversity across languages, genres, and theoretical frameworks, we adopt the DISRPT Shared Task (Braud et al., 2024) rather than limiting to a single framework such as PDTB-style implicit relations (Webber et al., 2019) for (3) Relation Recognition. The latest DISRPT version introduces a unified relation taxonomy that consolidates over 300 relation types, facilitating cross-framework comparison. We further incorporate the most recent datasets: *Just* (Sheffield et al., 2025) and *Otherwise*[2] for Task (1). These datasets introduce an interesting perspective on polyfunctional

---
[2]The reference for *Otherwise* will be added in a future revision.

discourse particles and their subtle effects on textual meaning, enabling assessment of LLMs' sensitivity to fine-grained pragmatic distinctions.

3.3 Model Coverage

We test the following reasoning LLMs: **(a) Qwen3 series** (Yang et al., 2025): Qwen reasoning models from 0.6B to 32B. We report 1.7B, 14B, and 32B in main content, with additional model results in Appendices. We evaluate both the "thinking" mode (high reasoning effort) and "non-thinking" (low reasoning effort) mode. **(b) DeepSeek-R1** (Guo et al., 2025): DeepSeek reasoning model. **(c) DeepSeek-R1-distill-Qwen32B** (Guo et al., 2025): Qwen2.5-32B (Qwen, 2024) as the base model with direct distillation from DeepSeek-R1. **(d) GPT-5-mini** (OpenAI, 2025): the latest GPT models. We test "low" and "high" reasoning effort.

For open-source reasoning models such as Qwen3 and DeepSeek-R1, their reasoning process is observable, whereas in proprietary models like GPT-5, it remains implicit. Nevertheless, we can infer reasoning effort indirectly through the usage of thinking tokens. In Appendix C, we visualize model performance under low (i.e., "non-thinking") versus high (i.e., "thinking") reasoning effort and present interesting observations.

There exist multiple approaches for evaluating linguistic understanding in LLMs. Among them, QA-based prompting is particularly flexible and provides fine-grained interpretability. Accordingly, we formulate all tasks in an open-ended QA format. For classification tasks with a fixed label space, the label set is explicitly provided in the system prompt. Alternative methods such as sentence log-probabilities (Hu and Levy, 2023) and surprisal-based predictability scores (Giulianelli et al., 2023; Tsipidi et al., 2024) have been used to probe linguistic sensitivity. However, these approaches are less suited for capturing the fine-grained distinctions required in Task (1) and structure prediction (Tasks 4–5). To mitigate model variation, each experiment is run three times with different seeds, and we report the mean and standard deviation.

4 Understanding on Discourse Lexicons

This part presents **Task (1) Discourse Marker Understanding**. Owing to their polyfunctional nature, discourse markers such as the particle "just" and the adverbial "otherwise" have been extensively examined in formal semantics (Lee, 1987; Ro-

hde et al., 2016; Warstadt, 2020; Beltrama, 2022). These lexical items produce subtle yet diverse semantic and discourse effects. While human can reliably distinguish these discourse functions in context (Rohde et al., 2018), the extent to which LLMs exhibit similar sensitivity and proficiency remains unclear. To investigate this, we incorporate the newly curated *Just* (Sheffield et al., 2025) and *Otherwise* datasets into BeDiscovER.

4.1 Settings and Baselines

We design three QA-style prompting formats that vary in the amount of background information provided about the particle's functions: (i) BASIC: offers no explanation and directly asks the model to select a function label; (ii) DEF: adds a one-sentence definition for each label; and (iii) DEF+EXP: further includes a concrete example, resembling one-shot in-context learning. Prompt examples are provided in Appendix A.1.

We compare with direct prompting results for *Just* and continuation acceptability scores for *Otherwise* in their original papers. Sheffield et al. (2025) adopts a prompting setup similar to our DEF+EXP, whereas *Otherwise* employs a continuation acceptability approach: given a left-hand side (LHS) and right-hand side (RHS) clause, the language model evaluates the most plausible connective linking them. These connectives–explicit discourse markers such as *because if not*–capture the distinctive semantics associated with the adverbial *otherwise*. For evaluation, we report accuracy; other metrics are provided in Appendix B.1.

4.2 Results and Analysis

Table 2 presents main results of *Just*-Manual, *Just*-Subtitle, and *Otherwise* with BeDiscovER models (top) and baselines (middle and bottom parts).

In terms of prompting strategy, providing richer background information (DEF and DEF+EXP) generally improves performance, especially for large reasoning models (>32B). This trend holds across both datasets. However, for smaller and medium-sized models (small: <4B; medium: 4B–32B), additional context does not always help. On the more challenging *Just*–Subtitle and *Otherwise* datasets, excessive contextual information can even degrade performance. A relevant phenomenon is noted by Hu and Frank (2024), who show that increased task complexity can widen the demand gap for smaller models with limited parameters and training data, leading to reduced accuracy. We also observe a crit-

	Model	Size	*Just*-Manual (acc.)			*Just*-Subtitle (acc.)			*Otherwise* (acc.)		
			Basic	Def	Def+Exp	Basic	Def	Def+Exp	Basic	Def	Def+Exp
BeDiscovER	Qwen3-1.7B	1.7B	$38.9_{.7}$	$40.7_{4.2}$	$40.2_{2.2}$	$25.9_{0.9}$	$26.2_{1.5}$	$25.5_{1.3}$	$23.9_{0.6}$	$21.2_{1.3}$	$16.2_{1.3}$
	Qwen3-14B	14B	$60.2_{.6}$	$54.9_{2.0}$	$55.6_{1.4}$	$43.2_{2.1}$	$32.9_{1.7}$	$33.2_{1.3}$	$32.1_{.7}$	$\underline{45.2}_{2.5}$	$51.4_{1.6}$
	Qwen3-32B	32B	$59.8_{1.8}$	$65.6_{3.5}$	$64.4_{2.0}$	$48.5_{1.4}$	$48.9_{2.0}$	$47.1_{1.2}$	$34.3_{.4}$	$\mathbf{49.3}_{2.6}$	$\underline{66.1}_{.6}$
	DS-r1-distill-Qwen	32B	$56.7_{1.1}$	$63.7_{1.5}$	$59.6_{4.0}$	$31.8_{4.3}$	$40.5_{2.9}$	$35.8_{.2}$	$33.1_{1.5}$	$32.4_{1.8}$	$44.3_{3.5}$
	DeepSeek-r1-0528	37/671B	$53.7_{.4}$	$\underline{66.3}_{.7}$	$67.0_{1.4}$	$48.1_{3.1}$	$\underline{60.2}_{1.8}$	$59.5_{4.5}$	$31.2_{.9}$	$38.9_{1.8}$	$58.8_{1.7}$
	GPT-5-mini (low)	Unknown	$\mathbf{63.3}_{2.2}$	$65.9_{.3}$	$65.6_{.0}$	$\underline{56.4}_{1.4}$	$58.4_{1.4}$	$\underline{62.9}_{.5}$	$\underline{34.6}_{.6}$	$36.8_{1.1}$	$51.9_{3.3}$
	GPT-5-mini (high)	Unknown	$\underline{61.7}_{.6}$	$\mathbf{66.1}_{1.7}$	$65.6_{1.1}$	$\mathbf{57.4}_{1.7}$	$\mathbf{63.1}_{.0}$	$\mathbf{63.4}_{.3}$	$\mathbf{35.5}_{.5}$	$43.9_{1.0}$	$\mathbf{71.8}_{1.7}$
Contin.	GPT-Neo-1.3B	1.3B		-			-			$56.0^{\dagger}$ (surprisal score)	
	Mistral-7B-v0.1	7B		-			-			$59.0^{\dagger}$ (surprisal score)	
Prompting	Mistral-0.3-7B (2025)	7B			$\underline{69}^{*}$			27^{*}		-	
	OLMo2-13B (2025)	13B			46^{*}			18^{*}		-	
	Llama-3.3-70B (2025)	70B			$\mathbf{75}^{*}$			35^{*}		-	

Table 2: **Task (1) Discourse Marker Understanding** performance with BeDiscovER and baselines on *Just*-Manual, *Just*-Subtitle, and *Otherwise* datasets. Top: BeDiscovER scores. Middle: *Otherwise* dataset baseline scores, [†] denotes surprisal scores which calculates the continuation acceptability in language models. Bottom: prompting baselines in *Just* corpus (Sheffield et al., 2025). They use a similar "definition+example" prompting strategy. [*] scores are *approximated* from Figure 2 in Sheffield et al. (2025); the figure does not report exact values. Best score per column is in **bold** and second best underlined.

ical model size threshold (>2B parameters), beyond which performance improves sharply—consistent with findings by Sheffield et al. (2025). Compared to baselines, GPT-5-mini with high reasoning effort achieves the best performance, setting new state-of-the-art results on *Just*–Subtitle and *Otherwise*.

5 Understanding on (multi-)Sentences

5.1 Temporal Relation

Compared to individual discourse markers, **Task (2) Temporal Reasoning** requires EVENT-EVENT pair reasoning across sentences (adjacent like in TBD (Cassidy et al., 2014)) or distant in TDD (Naik et al., 2019)), making this task more difficult. To test LLM's arithmetic skills in time-related events, we include a subset from Test-of-Time (ToT) (Fatemi et al., 2024).

5.1.1 Settings and Baselines

Prior studies (Yuan et al., 2023; Chan et al., 2024) have shown that, despite prompt engineering, Chat-GPT (Schulman et al., 2022) performs poorly on temporal relation extraction, leaving a substantial gap compared to supervised methods. In TBD and TDD-Man, we use full news documents with target events annotated by <EVENT></EVENT> tags. Our prompt, adapted from the best-performing template in Yuan et al. (2023), presents a fixed set of relation labels as a multiple-choice QA task (see Appendix A.2).

For baselines, we consider both prompting-based baselines–ChatGPT (Yuan et al., 2023; Chan et al.,

2024), Gemini and GPT-4 (Fatemi et al., 2024)–and supervised methods employing graph-based neural networks like UCGraph, RSGT, and DTRE (Liu et al., 2021; Zhou et al., 2022; Wang et al., 2022), as well as prototypical network CPTRE (Yuan et al., 2024) to learn better label representations. All supervised baselines use much smaller PLMs such as BERT (Devlin et al., 2019) and RoBERTa (Liu et al., 2019) for node representation learning.

5.1.2 Results and Analysis

Table 3 summarizes the main results across all three datasets, with details provided in Appendix B.2. Overall, recent reasoning LLMs substantially outperform earlier models such as ChatGPT, achieving gains of 10–20% on TBD and TDD-Man, and a notable +30% improvement on ToT-Arithmetic. These results indicate enhanced temporal reasoning capability, particularly in arithmetic-related temporal inference. However, compared with supervised baselines, zero-shot LLMs still underperform on TBD and TDD-Man, both of which require precise logical reasoning over event ordering. While humans easily infer that an "investigation" typically follows a "crime" (example in TBD), such knowledge demands both temporal and commonsense understanding. When processing full documents containing multiple events, LLMs must reconstruct the logical storyline: a task that remains challenging even for advanced reasoning models.

In our ablation study, we simplify inputs by limiting context to sentences containing the target events. This pre-selection reduces reasoning load

	Model	Size	TBD (f1)	TDD-Man (f1)	ToT-Ari (acc.)
BeDiscovER	Qwen3-1.7B	1.7B	$26.2_{0.8}$	$21.9_{0.6}$	$46.5_{0.5}$
	Qwen3-14B	14B	$39.8_{0.1}$	$29.5_{0.6}$	$80.4_{1.2}$
	Qwen3-32B	32B	$40.8_{0.5}$	$31.6_{0.3}$	$81.6_{0.5}$
	DS-r1-distill-Qwen	32B	$23.8_{2.5}$	$18.6_{3.3}$	$68.0_{1.2}$
	DeepSeek-r1-0528	671B	$33.1_{0.0}$	$22.2_{0.0}$	$63.3_{0.5}$
	GPT-5-mini (low)	Unk.	$\underline{38.7}_{0.2}$	$\underline{34.4}_{0.2}$	$\underline{87.2}_{0.1}$
	GPT-5-mini (high)	Unk.	$\mathbf{43.4}_{0.3}$	$\mathbf{36.7}_{0.3}$	$\mathbf{88.2}_{0.0}$
Prompting	ChatGPT (2023)	Unk.	37.0	24.3	-
	ChatGPT (2024)	Unk.	27.0	16.8	-
	Gemini1.5-Pro (2024)	Unk.	-	-	53.4
	GPT-4 (2024)	Unk.	-	-	54.2
Supervised	UCGraph (2021)	125B	59.1	43.4	-
	RSGT (2022)	355M	68.7	-	-
	DTRE (2022)	125M	**70.2**	56.3	-
	CPTRE (2024)	125M	61.1	**56.5**	-

Table 3: **Task (2) Temporal Reasoning** performance: BeDiscovER (top), LLM-prompting baselines (middle), and supervised baselines (bottom) on TBD, TDD-Manual, and ToT-arithmetic datasets. Scores are micro-F1. Size in supervised baselines refer to PLM encoders like BERT/RoBERa-base (125M) and large (355M). Best un-/supervised score per column is in **bold** and second best underlined.

	Model	DEP	eRST	ISO	PDTB	RST	SDRT
BeDiscovER	Qwen3-1.7B	21.2	19.7	25.0	22.1	18.0	18.7
	Qwen3-14B	37.9	32.7	41.4	36.4	33.6	26.2
	Qwen3-32B	39.5	34.7	40.3	36.8	35.5	29.9
	DS-r1-distill-Qwen	32.6	29.9	38.7	29.8	32.9	24.6
	DeepSeek-r1-0528	44.3	**36.6**	51.4	43.7	43.6	26.6
	GPT-5-mini (low)	46.1	33.9	47.3	42.9	42.3	34.2
	GPT-5-mini (high)	**51.2**	36.0	**56.8**	**47.4**	**46.6**	**37.9**
Supervised	DeDisCo (2025)	**77.2**	**71.8**	**72.0**	**79.0**	**64.9**	**83.0**
	HITS	74.1	64.5	72.0	76.3	61.9	82.1
	DisCreT	72.3	58.1	60.0	75.3	56.4	77.5
	CLAC (2025)	74.9	57.5	54.8	74.7	56.2	77.4
	SeCoRel	69.7	53.8	52.8	70.6	52.5	76.4

Table 4: **Task (3): Discourse Relation Recognition [framework-split]** in the DISRPT Shared Task. BeDiscovER results (top) vs. supervised systems (bottom; all <4B parameters). Framework abbreviations: DEP - Dependency Structure (Yang and Li, 2018); eRST - Enhanced RST (Zeldes et al., 2025); ISO - ISO Framework (Bunt and Prasad, 2016); PDTB - Penn Discourse TreeBank (Prasad et al., 2005); RST – Rhetorical Structure Theory (Mann and Thompson, 1988); SDRT - Segmented Discourse Representation Theory (Asher and Lascarides, 2003). Scores are averaged across datasets in each framework, weighted by dataset size.

and yields modest gains on TBD (2–3%; tables 21 and 22). Conversely, for TDD-Man, where events are farther apart, removing intermediate context leads to a 2–9% drop in performance (tables 23 and 24). These findings suggest that LLM reasoning is sensitive to both context complexity and the availability of relevant information.

5.2 Discourse Relation

For **Task (3): Discourse Relation Recognition**, we adopt data from the DISRPT Shared Task. Discourse relations are conventionally defined between two text segments, Arg1 and Arg2 (Webber et al., 2019), and labeled with a rhetorical or semantic relation (e.g., *cause*, *contrast*). Instead of separating explicit and implicit relations, we adopt the unified label set from DISRPT25 (Braud et al., 2024), offering a harmonized framework for evaluating LLMs' discourse understanding.

5.2.1 Settings and Baselines

Prior studies have demonstrated that incorporating hand-crafted discourse features significantly improves relation classification performance (Gessler et al., 2021; Metheniti et al., 2024). Motivated by these findings, we integrate a selected set of features to enrich the input prompt, including language, framework, corpus name, argument direction (Arg1→Arg2 or inverse), and context in which the arguments appear. Our prompting setup closely follows DeDisCo (Ju et al., 2025) (see Appendix A.3), the top-performing system in the DISRPT25 relation classification track. Despite the multilingual data, we use English for all prompt instructions. Baseline results are drawn from the official DISRPT website[3], where all systems were fine-tuned on the training data with a model size cap of 4B parameters.

5.2.2 Results and Analysis

Table 4 presents weighted averages across datasets within each framework, proportional to the number of instances. We also present a language-view and per-dataset details in tables 26 to 30 in Appendix B.3.

Despite well-designed prompts providing rich contextual information, all reasoning LLMs perform substantially worse than supervised baselines, showing an average gap of around 20 points. Among the frameworks, eRST yields the lowest scores–likely due to its recent introduction and limited exposure during pretraining—with even the strongest model, GPT-5-mini, achieving only the low 30s. The ISO framework attains the highest LLM performance at 57%, which remains well below supervised results. In contrast, all fine-tuned systems perform markedly better, with DeDisCo reaching approximately 70% across frameworks.

---

[3] https://sites.google.com/view/disrpt2025/results

	AAN abstract		ArXiv abstract		Neurips abstract		NSF abstract		ROC stories		SIND		Wiki. mv. plts.	
Model	PMR	Acc	PMR	Acc	PMR	Acc	PMR	Acc	PMR	Acc	PMR	Acc	PMR	Acc
BeDiscovER														
Qwen3-1.7B	21.1_5	38.0_5	19.0_5	31.4_3	$11.0_{2.2}$	30.8_7	$6.6_{0.5}$	14.7_1	17.1_7	44.7_9	$14.6_{1.0}$	$35.6_{1.0}$	8.9_3	12.7_1
Qwen3-14B	55.5_9	70.6_3	43.4_3	59.1_6	43.0_8	66.1_1	14.3_0	29.2_6	67.3_4	82.5_4	31.2_9	55.1_4	18.2_1	27.1_2
Qwen3-32B	59.6_4	74.0_3	46.1_4	61.9_4	44.2_4	68.6_2	14.3_3	30.2_4	70.6_7	84.4_3	31.2_5	55.3_3	19.1_6	29.1_5
DS-r1-distill-Qwen	51.4_9	67.7_5	38.8_4	55.4_2	38.9_4	63.5_7	11.4_2	26.0_2	$63.2_{2.8}$	$79.8_{1.6}$	$29.0_{1.8}$	$53.3_{1.2}$	17.6_6	24.3_5
DeepSeek-r1-0528	$\underline{64.8}_4$	$\underline{75.5}_2$	46.6_5	61.9_3	$\underline{56.8}_5$	$\underline{74.9}_6$	15.7_2	28.5_2	$\mathbf{77.1}_{1.2}$	$\mathbf{88.2}_6$	$\mathbf{36.4}_{1.3}$	58.4_9	$\mathbf{23.8}_4$	28.0_4
GPT-5-mini (low)	61.1_6	75.4_0	$\underline{49.3}_1$	$\underline{65.6}_4$	50.5_4	73.1_1	$\underline{15.8}_1$	33.2_4	$68.3_{1.1}$	83.6_6	$31.5_{1.1}$	54.6_8	20.3_1	$\underline{32.0}_2$
GPT-5-mini (high)	$\mathbf{66.3}_7$	$\mathbf{78.7}_1$	$\mathbf{55.0}_1$	$\mathbf{69.8}_1$	$\mathbf{58.6}_3$	$\mathbf{78.6}_2$	$\mathbf{17.8}_2$	$\mathbf{35.5}_1$	$\underline{75.7}_{1.0}$	$\underline{87.3}_{04}$	$\underline{35.0}_{1.5}$	$\underline{58.2}_{1.0}$	$\underline{23.0}_5$	$\mathbf{40.1}_4$
Supervised														
BERSON (2020)	59.8	78.0	56.1	75.1	48.0	73.9	23.1	50.2	68.2	82.9	31.7	58.9	-	-
Re-BART (2021)	$\underline{73.5}$	$\underline{84.3}$	$\underline{62.4}$	$\underline{74.3}$	$\underline{57.0}$	$\underline{77.4}$	$\underline{29.7}$	50.2	$\underline{81.9}$	$\underline{90.8}$	$\underline{43.2}$	$\underline{64.5}$	25.8	42.0
COVER-BERSON (2023)	59.2	78.1	-	-	50.9	74.9	-	-	72.3	84.8	33.0	60.3	-	-
NAON-BART (2023)	$\mathbf{73.9}$	$\mathbf{87.2}$	$\mathbf{62.6}$	$\mathbf{79.2}$	$\mathbf{61.2}$	$\mathbf{84.2}$	$\mathbf{30.6}$	$\mathbf{54.8}$	$\mathbf{89.1}$	$\mathbf{95.1}$	$\mathbf{55.6}$	$\mathbf{79.6}$	-	-

Table 5: **Task (4) Sentence Ordering** results on seven publicly available datasets. We report perfect match rate (PMR) and accuracy; additional metrics in Appendix B.4. Best un-/supervised score per column is in **bold** and second best underlined.

From a language perspective (Table 26), BeDiscovER models exhibit nearly flat performance across languages, whereas supervised models show clear disparities between high-resource (e.g., English, Russian) and low-resource languages (e.g., Czech, Basque). This contrast suggests that LLMs still lack robust internal representations of discourse frameworks and theoretical knowledge, limiting their generalization across both frameworks and languages.

6 Understanding on Document Structure

6.1 Sentence Ordering

Task (4) Sentence Ordering reorders a set of shuffled sentences into a coherent text. It has been used to assess a model's understanding of causal and temporal relations (Barzilay and Lapata, 2008) and shown to aid discourse structure extraction (Li et al., 2023). We include, in this task, 7 publicly available datasets from two domains: scientific paper abstracts (AAN, ArXiv, Neurips, NSF (Wang et al., 2018; Chen et al., 2016; Logeswaran et al., 2018)) and narratives (ROC stories, SIND, and Movie plots (Mostafazadeh et al., 2016; Huang et al., 2016))[4].

6.1.1 Settings and Baselines

In our setup, we adopt a text-to-marker format that prompts the model to generate a sequence of re-ordered sentence labels (e.g., <s3>, <s1>) as output. This format, shown effective in ReBART (Basu Roy Chowdhury et al., 2021), produces clean and easily evaluable outputs. The prompt template is in Appendix A.4.

Supervised baselines use PLMs to encode sentences, followed by either a Pointer Network to predict sentence positions (e.g., BERSON and Cover-BERSON (Cui et al., 2020; Jia et al., 2023)) or a sequence-to-sequence model that generates the position sequence autoregressively, such as Re-BART (Basu Roy Chowdhury et al., 2021), or non-autoregressively: NAON-BART (Bin et al., 2023).

6.1.2 Results and Analysis

Table 5 presents the performance of BeDiscovER and supervised models across seven datasets. A clear scaling trend emerges where larger LLMs consistently outperform smaller ones. The strongest model, GPT-5-mini (high), even matches supervised performance on Movie plots, the most challenging dataset with the highest degree of sentence shuffling. On ROC stories, all models perform reasonably well, while in scientific abstract domain, GPT-5-mini again achieves competitive results, potentially benefiting from exposure to similar text during pretraining, though there remains room for improvement on longer inputs such as NSF. DeepSeek-R1 performs comparably to GPT-5-mini, slightly outperforming it on narrative datasets.

Overall, these results suggest that reasoning LLMs, especially larger ones, possess a good grasp of textual coherence, possibly stemming from their extensive pretraining on narrative-rich corpora.

6.2 Dialogue Discourse Parsing

While Task (4) focuses more on temporal and causal coherence, **Task (5): Dialogue Discourse Parsing** emphasizes rhetorical relations across the entire document. We additionally target dialogue rather than monologue to introduce greater genre diversity. This task includes three widely used dialogue discourse datasets: STAC (Asher et al., 2016), Molweni (Li et al., 2020), and the recently annotated MSDC based on Minecraft Dialogue Corpus (Thompson et al., 2024b), all in the SDRT

---

[4]Preprocessed data obtained from Basu Roy Chowdhury et al. (2021).

	Model	Size	STAC		Molweni		MSDC	
			Link	Full	Link	Full	Link	Full
BeDiscovER	Qwen3-1.7B	1.7B	$35.9_{1.8}$	$5.2_{0.0}$	$43.1_{0.3}$	$5.3_{0.3}$	$36.7_{2.8}$	$3.6_{0.2}$
	Qwen3-14B	14B	$61.3_{0.8}$	$29.8_{1.4}$	$\underline{60.1}_{0.6}$	$25.7_{0.7}$	$\mathbf{72.7}_{0.2}$	$22.6_{0.1}$
	Qwen3-32B	32B	$62.4_{1.1}$	$31.3_{0.3}$	$58.3_{0.6}$	$22.2_{0.9}$	$\underline{70.5}_{0.1}$	$23.0_{0.3}$
	DS-r1-distill-Qwen	32B	$61.5_{0.7}$	$22.3_{2.3}$	$58.6_{0.7}$	$16.1_{0.3}$	$69.6_{0.4}$	$25.7_{1.1}$
	DeepSeek-r1-0528	671B	$\mathbf{66.3}_{0.1}$	$\underline{38.7}_{0.5}$	$56.7_{0.7}$	$22.3_{1.3}$	$69.6_{0.7}$	$\underline{34.2}_{0.7}$
	GPT-5-mini (low)	Unk.	$61.1_{0.3}$	$32.1_{0.8}$	$55.6_{0.1}$	$\underline{27.7}_{0.3}$	$66.1_{0.1}$	$26.8_{0.4}$
	GPT-5-mini (high)	Unk.	$\underline{66.0}_{0.2}$	$\mathbf{38.8}_{0.7}$	$58.4_{0.6}$	$\mathbf{30.2}_{0.3}$	$66.4_{0.7}$	$\mathbf{31.9}_{0.5}$
Prompt	ChatGPT zero-shot (Chan et al., 2024)	Unk.	20.0	4.4	28.3	5.4	-	-
	ChatGPT (Fan et al., 2024)	Unk.	59.9	25.3	$\mathbf{63.7}$	23.8	-	-
Supervised	RoBERTa+pointer (Liu and Chen, 2021)	125M	72.9	57.0	$\underline{79.0}$	55.4	-	-
	RoBERTa+CLE (Chi and Rudnicky, 2022)	125M	$\underline{73.0}$	$\underline{58.1}$	81.0	$\underline{58.6}$	-	-
	T0+transition (Li et al., 2024)	3B	72.3	56.6	$\mathbf{83.4}$	$\mathbf{60.0}$	-	-
	Llama3 (Thompson et al., 2024a)	8B	$\mathbf{77.5}$	$\mathbf{60.7}$	-	-	88.3	79.5

Table 6: **Task (5) Dialogue Discourse Parsing** results on STAC, Molweni, and MDSC corpora, comparing BeDiscovER (top) with LLM-based prompting (middle) and supervised baselines (bottom).

framework (Asher and Lascarides, 2003).

6.2.1 Settings and Baselines

Directly prompting LLMs to generate SDRT-style discourse graphs from raw text remains challenging, as shown in prior studies with ChatGPT (Chan et al., 2024; Fan et al., 2024).

Following the parsing-as-generation paradigm (Li et al., 2024), we instead prompt the model to produce relation triples incrementally, where model predicts relations for each new utterance and appends the generated structure as context for subsequent predictions (prompt given in Appendix A.5). This incremental approach has achieved state-of-the-art performance with both sequence-to-sequence models (e.g., T0+Transition) and decoder-only architectures such as Llamipa (Thompson et al., 2024a). For comparison, we also include earlier baselines employing smaller PLMs with task-specific decoding strategies (Liu and Chen, 2021; Chi and Rudnicky, 2022).

For evaluation, we employ the micro-averaged F1 scores for link attachment and full structure.

6.2.2 Results and Analysis

Table 6 reports BeDiscovER performance using incremental prompting. This approach establishes a new state of the art for zero-shot prompting, achieving a 7–13% improvement in full structure prediction over prior ChatGPT results (Chan et al., 2024; Fan et al., 2024). Despite these gains, all reasoning LLMs still trail supervised baselines by a wide margin of 20–30%, particularly on full structure prediction, which requires accurate identification of both discourse links and their relations. The relation component appears to be the primary bottleneck, with relation recognition in SDRT framework scores below 40 (discussed in Section 5.2.2).

In an oracle setting, where gold triples are provided at each step ("single-turn" setup; Appendix B.5), we observe only modest improvements over auto-regressive parsing, suggesting limited impact from error propagation. Notably, models with higher reasoning effort outperform their lower-effort counterparts, especially on full-structure prediction, indicating that explicit reasoning enhances discourse parsing performance.

7 Conclusion and Discussion

To conclude, we introduce BeDiscovER, a comprehensive benchmark designed to evaluate the discourse knowledge of reasoning-oriented LLMs. Covering 3 levels, 5 tasks, and 52 datasets across multiple languages, frameworks, and genres, BeDiscovER offers a linguistically grounded and multifaceted assessment of how current LLMs understand discourse structure and coherence.

Beyond evaluation, BeDiscovER also serves as a baseline and reference point for future research on discourse-aware LLMs. Our findings highlight persistent challenges, particularly in temporal reasoning (logical not arithmetic) and rhetorical relation recognition where LLMs still lag behind humans and supervised systems. It is thus intriguing to investigate what LLMs learn and how transferable is discourse reasoning across contexts.

As an initial step toward deeper insight, we visualize the relationship between thinking effort and performance (Appendix C). Interestingly, across many tasks, longer reasoning traces do not necessarily yield better outcomes. Models often become more verbose without producing more meaningful reasoning. Improving the quality of reasoning thus remains a promising direction for advancing discourse-aware LLMs.

Limitations

BeDiscovER is designed to provide a broad, high-level overview of recent LLM performance across diverse discourse tasks. For this reason, our analysis focuses on aggregate results (overall accuracy, weighted F1) to capture general trends. However, future extensions could incorporate more fine-grained, class-level analyses to offer deeper insight.

For evaluation, we adopt a unified open-ended QA prompting strategy to ensure simplicity and consistency across tasks. While model outputs can be sensitive to prompt phrasing, we intentionally employ minimal and standardized wording, and make all prompt templates publicly available (Appendix A) to facilitate replication and future comparison.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Rahul Aralikatte, Matthew Lamm, Daniel Hardt, and Anders Søgaard. 2021. Ellipsis resolution as question answering: An evaluation. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 810–817, Online. Association for Computational Linguistics.

Nicholas Asher, Julie Hunter, Mathieu Morey, Benamara Farah, and Stergos Afantenos. 2016. Discourse structure and dialogue acts in multiparty dialogue: the STAC corpus. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC'16)*, pages 2721–2727, Portorož, Slovenia. European Language Resources Association (ELRA).

Nicholas Asher and Alex Lascarides. 2003. *Logics of conversation*. Cambridge University Press.

Yushi Bai, Jiajie Zhang, Xin Lv, Linzhi Zheng, Siqi Zhu, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. 2024. Longwriter: Unleashing 10,000+ word generation from long context llms. In *The Thirteenth International Conference on Learning Representations*.

Regina Barzilay and Mirella Lapata. 2008. Modeling local coherence: An entity-based approach. *Computational Linguistics*, 34(1):1–34.

Somnath Basu Roy Chowdhury, Faeze Brahman, and Snigdha Chaturvedi. 2021. Is everything in order? a simple way to order sentences. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 10769–10779, Online

and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Andrea Beltrama. 2022. Just perfect, simply the best: an analysis of emphatic exclusion. *Linguistics and Philosophy*, 45(2):321–364.

Maciej Besta, Julia Barth, Eric Schreiber, Ales Kubicek, Afonso Catarino, Robert Gerstenberger, Piotr Nyczyk, Patrick Iff, Yueling Li, Sam Houliston, and 1 others. 2025. Reasoning language models: A blueprint. *arXiv preprint arXiv:2501.11223*.

Yi Bin, Wenhao Shi, Bin Ji, Jipeng Zhang, Yujuan Ding, and Yang Yang. 2023. Non-autoregressive sentence ordering. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 4198–4214.

Chloé Braud, Amir Zeldes, Laura Rivière, Yang Janet Liu, Philippe Muller, Damien Sileo, and Tatsuya Aoyama. 2024. Disrpt: A multilingual, multi-domain, cross-framework benchmark for discourse processing. In *Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 4990–5005.

Jan Buchmann, Max Eichler, Jan-Micha Bodensohn, Ilia Kuznetsov, and Iryna Gurevych. 2024. Document structure in long document transformers. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1056–1073, St. Julian's, Malta. Association for Computational Linguistics.

Harry Bunt and Rashmi Prasad. 2016. Iso dr-core (iso 24617-8): Core concepts for the annotation of discourse relations. In *Proceedings 12th joint ACL-ISO workshop on interoperable semantic annotation (ISA-12)*, pages 45–54.

Zhuchen Cao, Sven Apel, Adish Singla, and Vera Demberg. 2025. Pragmatic reasoning improves llm code generation. *arXiv preprint arXiv:2502.15835*.

Taylor Cassidy, Bill McDowell, Nathanael Chambers, and Steven Bethard. 2014. An annotation framework for dense event ordering. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 501–506.

Chunkit Chan, Cheng Jiayang, Weiqi Wang, Yuxin Jiang, Tianqing Fang, Xin Liu, and Yangqiu Song. 2024. Exploring the potential of ChatGPT on sentence level relations: A focus on temporal, causal, and discourse relations. In *Findings of the Association for Computational Linguistics: EACL 2024*, pages 684–721, St. Julian's, Malta. Association for Computational Linguistics.

Mingda Chen, Zewei Chu, and Kevin Gimpel. 2019. Evaluation benchmarks and learning criteria for

discourse-aware sentence representations. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 649–662, Hong Kong, China. Association for Computational Linguistics.

Xinchi Chen, Xipeng Qiu, and Xuanjing Huang. 2016. Neural sentence ordering. *arXiv preprint arXiv:1607.06952*.

Alexander Chernyavskiy, Dmitry Ilvovsky, and Preslav Nakov. 2024. Unleashing the power of discourse-enhanced transformers for propaganda detection. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1452–1462, St. Julian's, Malta. Association for Computational Linguistics.

Ta-Chung Chi and Alexander Rudnicky. 2022. Structured dialogue discourse parsing. In *Proceedings of the 23rd Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 325–335.

Baiyun Cui, Yingming Li, and Zhongfei Zhang. 2020. BERT-enhanced relational sentence ordering network. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6310–6320, Online. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Yaxin Fan, Feng Jiang, Peifeng Li, and Haizhou Li. 2024. Uncovering the potential of chatgpt for discourse analysis in dialogue: An empirical study. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 16998–17010.

Bahare Fatemi, Mehran Kazemi, Anton Tsitsulin, Karishma Malkan, Jinyeong Yim, John Palowitch, Sungyong Seo, Jonathan Halcrow, and Bryan Perozzi. 2024. Test of time: A benchmark for evaluating llms on temporal reasoning. *ICLR 2025*.

Shangbin Feng, Zhaoxuan Tan, Wenqian Zhang, Zhenyu Lei, and Yulia Tsvetkov. 2023. KALM: Knowledge-aware integration of local, document, and global contexts for long document understanding. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2116–2138, Toronto, Canada. Association for Computational Linguistics.

Luke Gessler, Shabnam Behzad, Yang Janet Liu, Siyao Peng, Yilun Zhu, and Amir Zeldes. 2021. DisCoDisCo at the DISRPT2021 shared task: A system for discourse segmentation, classification, and connective detection. In *Proceedings of the 2nd Shared Task on Discourse Relation Parsing and Treebanking (DISRPT 2021)*, pages 51–62, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Mario Giulianelli, Sarenne Wallbridge, and Raquel Fernández. 2023. Information value: Measuring utterance predictability as distance from plausible alternatives. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5633–5653, Singapore. Association for Computational Linguistics.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Jennifer Hu and Michael Frank. 2024. Auxiliary task demands mask the capabilities of smaller language models. In *First Conference on Language Modeling*.

Jennifer Hu and Roger Levy. 2023. Prompting is not a substitute for probability measurements in large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5040–5060, Singapore. Association for Computational Linguistics.

Ting-Hao Kenneth Huang, Francis Ferraro, Nasrin Mostafazadeh, Ishan Misra, Aishwarya Agrawal, Jacob Devlin, Ross Girshick, Xiaodong He, Pushmeet Kohli, Dhruv Batra, C. Lawrence Zitnick, Devi Parikh, Lucy Vanderwende, Michel Galley, and Margaret Mitchell. 2016. Visual storytelling. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1233–1239, San Diego, California. Association for Computational Linguistics.

Patrick Huber and Giuseppe Carenini. 2022. Towards understanding large-scale discourse structures in pre-trained and fine-tuned language models. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2376–2394.

Maor Ivgi, Uri Shaham, and Jonathan Berant. 2023. Efficient long-text understanding with short-text models. *Transactions of the Association for Computational Linguistics*, 11:284–299.

Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, and 1 others. 2024. Openai o1 system card. *arXiv preprint arXiv:2412.16720*.

Sainan Jia, Wei Song, Jiefu Gong, Shijin Wang, and Ting Liu. 2023. Sentence ordering with a coherence verifier. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 9301–9314.

Zhuoxuan Ju, Jingni Wu, Abhishek Purushothama, and Amir Zeldes. 2025. Dedisco at the disrpt 2025 shared task: A system for discourse relation classification. *arXiv preprint arXiv:2509.11498*.

Swanie Juhng, Matthew Matero, Vasudha Varadarajan, Johannes Eichstaedt, Adithya V Ganesan, and H. Andrew Schwartz. 2023. Discourse-level representations can improve prediction of degree of anxiety. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1500–1511, Toronto, Canada. Association for Computational Linguistics.

Sayash Kapoor, Benedikt Stroebl, Zachary S Siegel, Nitya Nadgir, and Arvind Narayanan. 2024. Ai agents that matter. *arXiv preprint arXiv:2407.01502*.

Zixuan Ke, Fangkai Jiao, Yifei Ming, Xuan-Phi Nguyen, Austin Xu, Do Xuan Long, Minzhi Li, Chengwei Qin, Peifeng Wang, Silvio Savarese, and 1 others. 2025. A survey of frontiers in llm reasoning: Inference scaling, learning to reason, and agentic systems. *arXiv preprint arXiv:2504.09037*.

Najoung Kim, Roma Patel, Adam Poliak, Alex Wang, Patrick Xia, R. Thomas McCoy, Ian Tenney, Alexis Ross, Tal Linzen, Benjamin Van Durme, Samuel R. Bowman, and Ellie Pavlick. 2019. Probing what different NLP tasks teach machines about function word comprehension. In *Proceedings of the Eighth Joint Conference on Lexical and Computational Semantics (*SEM 2019)*, pages 235–249, Minneapolis, Minnesota. Association for Computational Linguistics.

David Lee. 1987. The semantics of just. *Journal of pragmatics*, 11(3):377–398.

Belinda Z. Li, Maxwell Nye, and Jacob Andreas. 2021. Implicit representations of meaning in neural language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1813–1827, Online. Association for Computational Linguistics.

Chuyuan Li, Patrick Huber, Wen Xiao, Maxime Amblard, Chloe Braud, and Giuseppe Carenini. 2023. Discourse structure extraction from pre-trained and fine-tuned language models in dialogues. In *Findings of the Association for Computational Linguistics: EACL 2023*, pages 2562–2579, Dubrovnik, Croatia. Association for Computational Linguistics.

Chuyuan Li, Yuwei Yin, and Giuseppe Carenini. 2024. Dialogue discourse parsing as generation: A sequence-to-sequence LLM-based approach. In *Proceedings of the 25th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 1–14, Kyoto, Japan. Association for Computational Linguistics.

Jiaqi Li, Ming Liu, Min-Yen Kan, Zihao Zheng, Zekun Wang, Wenqiang Lei, Ting Liu, and Bing Qin. 2020. Molweni: A challenge multiparty dialogues-based machine reading comprehension dataset with discourse structure. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 2642–2652, Barcelona, Spain (Online). International Committee on Computational Linguistics.

Xiaobo Liang, Zecheng Tang, Juntao Li, and Min Zhang. 2023. Open-ended long text generation via masked language modeling. In *Proc. ACL 2023*, pages 223–241, Toronto.

Yancheng Liang, Daphne Chen, Abhishek Gupta, Simon S Du, and Natasha Jaques. 2024. Learning to cooperate with humans using generative agents. *Advances in Neural Information Processing Systems*, 37:60061–60087.

Jian Liu, Jinan Xu, Yufeng Chen, and Yujie Zhang. 2021. Discourse-level event temporal ordering with uncertainty-guided graph completion. In *IJCAI*, pages 3871–3877.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Zhengyuan Liu and Nancy Chen. 2021. Improving multi-party dialogue discourse parsing via domain integration. In *Proceedings of the 2nd Workshop on Computational Approaches to Discourse*, pages 122–127, Punta Cana, Dominican Republic and Online. Association for Computational Linguistics.

Lajanugen Logeswaran, Honglak Lee, and Dragomir Radev. 2018. Sentence ordering and coherence modeling using recurrent neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

William C Mann and Sandra A Thompson. 1988. Rhetorical structure theory: Toward a functional theory of text organization. *Text-interdisciplinary Journal for the Study of Discourse*, 8(3):243–281.

Eleni Metheniti, Chloé Braud, and Philippe Muller. 2024. Feature-augmented model for multilingual discourse relation classification. In *Proceedings of the 5th Workshop on Computational Approaches to Discourse (CODI 2024)*, pages 91–104, St. Julians, Malta. Association for Computational Linguistics.

Yisong Miao, Hongfu Liu, Wenqiang Lei, Nancy Chen, and Min-Yen Kan. 2024. Discursive socratic questioning: Evaluating the faithfulness of language models' understanding of discourse relations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6277–6295.

Nasrin Mostafazadeh, Nathanael Chambers, Xiaodong He, Devi Parikh, Dhruv Batra, Lucy Vanderwende, Pushmeet Kohli, and James Allen. 2016. A corpus and cloze evaluation for deeper understanding of commonsense stories. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 839–849.

Aakanksha Naik, Luke Breitfeller, and Carolyn Rose. 2019. Tddiscourse: A dataset for discourse-level temporal ordering of events. In *Proceedings of the 20th Annual SIGdial Meeting on Discourse and Dialogue*, pages 239–249.

OpenAI. 2025. introducing-gpt-5.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Mihir Parmar, Hanieh Deilamsalehy, Franck Dernoncourt, Seunghyun Yoon, Ryan A. Rossi, and Trung Bui. 2024. Towards enhancing coherence in extractive summarization: Dataset and experiments with LLMs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 19810–19820, Miami, Florida, USA. Association for Computational Linguistics.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, and 1 others. 2025. Humanity's last exam. *arXiv preprint arXiv:2501.14249*.

Archiki Prasad, Trung Bui, Seunghyun Yoon, Hanieh Deilamsalehy, Franck Dernoncourt, and Mohit Bansal. 2023. MeetingQA: Extractive question-answering on meeting transcripts. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15000–15025, Toronto, Canada. Association for Computational Linguistics.

Rashmi Prasad, Aravind Joshi, Nikhil Dinesh, Alan Lee, Eleni Miltsakaki, and Bonnie Webber. 2005. The penn discourse treebank as a resource for natural language generation. In *Proceedings of the Corpus Linguistics Workshop on Using Corpora for Natural Language Generation*, pages 25–32.

Valentina Pyatkin, Ayal Klein, Reut Tsarfaty, and Ido Dagan. 2020. QADiscourse - Discourse Relations as QA Pairs: Representation, Crowdsourcing and Baselines. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2804–2819, Online. Association for Computational Linguistics.

Qwen. 2024. Qwen2.5: A party of foundation models.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2024. Gpqa: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

Hannah Rohde, Anna Dickinson, Nathan Schneider, Christopher N. L. Clark, Annie Louis, and Bonnie Webber. 2016. Filling in the blanks in understanding discourse adverbials: Consistency, conflict, and context-dependence in a crowdsourced elicitation task. In *Proceedings of the 10th Linguistic Annotation Workshop held in conjunction with ACL 2016 (LAW-X 2016)*, pages 49–58, Berlin, Germany. Association for Computational Linguistics.

Hannah Rohde, Alexander Johnson, Nathan Schneider, and Bonnie Webber. 2018. Discourse coherence: Concurrent explicit and implicit relations. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2257–2267, Melbourne, Australia. Association for Computational Linguistics.

John Schulman, Barret Zoph, Christina Kim, Jacob Hilton, Jacob Menick, Jiayi Weng, Juan Felipe Ceron Uribe, Liam Fedus, Luke Metz, Michael Pokorny, and 1 others. 2022. Chatgpt: Optimizing language models for dialogue. *OpenAI blog*, 2(4).

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

William Berkeley Sheffield, Kanishka Misra, Valentina Pyatkin, Ashwini Deo, Kyle Mahowald, and Junyi Jessy Li. 2025. Is it JUST semantics? a case study of discourse particle understanding in LLMs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 21704–21715, Vienna, Austria. Association for Computational Linguistics.

Mingxu Tao, Quzhe Huang, Kun Xu, Liwei Chen, Yansong Feng, and Dongyan Zhao. 2024. Probing multimodal large language models for global and local semantic representations. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 13050–13056.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, and 1 others. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Kate Thompson, Akshay Chaturvedi, Julie Hunter, and Nicholas Asher. 2024a. Llamipa: An incremental discourse parser. In *EMNLP 2024*, pages 6418–6430.

Kate Thompson, Julie Hunter, and Nicholas Asher. 2024b. Discourse structure for the minecraft corpus. In *Proceedings of the 2024 Joint International*

Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), pages 4957–4967.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Eleftheria Tsipidi, Franz Nowak, Ryan Cotterell, Ethan Wilcox, Mario Giulianelli, and Alex Warstadt. 2024. Surprise! Uniform Information Density isn't the whole story: Predicting surprisal contours in long-form discourse. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 18820–18836, Miami, Florida, USA. Association for Computational Linguistics.

Nawar Turk, Daniele Comitogianni, and Leila Kosseim. 2025. Clac at disrpt 2025: Hierarchical adapters for cross-framework multi-lingual discourse relation classification. *arXiv preprint arXiv:2509.16903*.

Liang Wang, Peifeng Li, and Sheng Xu. 2022. Dct-centered temporal relation extraction. In *Proceedings of the 29th international conference on computational linguistics*, pages 2087–2097.

Longyue Wang, Zefeng Du, Donghuai Liu, Deng Cai, Dian Yu, Haiyun Jiang, Yan Wang, Leyang Cui, Shuming Shi, and Zhaopeng Tu. 2023. Disco-bench: A discourse-aware evaluation benchmark for language modelling. *arXiv preprint arXiv:2307.08074*.

Qingyun Wang, Zhihao Zhou, Lifu Huang, Spencer Whitehead, Boliang Zhang, Heng Ji, and Kevin Knight. 2018. Paper abstract writing through editing mechanism. In *56th Annual Meeting of the Association for Computational Linguistics, ACL 2018*, pages 260–265. Association for Computational Linguistics (ACL).

Alex Warstadt. 2020. " just" don't ask: Exclusives and potential questions. In *Proceedings of Sinn und Bedeutung*, volume 24, pages 373–390.

Bonnie Webber, Rashmi Prasad, Alan Lee, and Aravind Joshi. 2019. The penn discourse treebank 3.0 annotation manual. *Philadelphia, University of Pennsylvania*, 35:108.

Jason Wei, Maarten Bosma, Vincent Y Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M Dai, and Quoc V Le. 2021. Finetuned language models are zero-shot learners. *arXiv preprint arXiv:2109.01652*.

Kangda Wei, Aayush Gautam, and Ruihong Huang. 2024. Are LLMs good annotators for discourse-level event relation extraction? In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1–19, Miami, Florida, USA. Association for Computational Linguistics.

Shengguang Wu, Shusheng Yang, Zhenglun Chen, and Qi Su. 2024a. Rethinking pragmatics in large language models: Towards open-ended evaluation and preference tuning. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 22583–22599.

Yating Wu, Ritika Mangla, Alex Dimakis, Greg Durrett, and Junyi Jessy Li. 2024b. Which questions should i answer? salience prediction of inquisitive questions. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 19969–19987.

Yating Wu, Ritika Mangla, Greg Durrett, and Junyi Jessy Li. 2023. QUDeval: The evaluation of questions under discussion discourse parsing. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5344–5363, Singapore. Association for Computational Linguistics.

Yuhao Wu, Ming Shan Hee, Zhiqiang Hu, and Roy Ka-Wei Lee. 2025. Longgenbench: Benchmarking long-form generation in long context llms. In *The Thirteenth International Conference on Learning Representations*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

An Yang and Sujian Li. 2018. SciDTB: Discourse dependency TreeBank for scientific abstracts. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 444–449, Melbourne, Australia. Association for Computational Linguistics.

Chenhan Yuan, Qianqian Xie, and Sophia Ananiadou. 2023. Zero-shot temporal relation extraction with ChatGPT. In *The 22nd Workshop on Biomedical Natural Language Processing and BioNLP Shared Tasks*, pages 92–102, Toronto, Canada. Association for Computational Linguistics.

Chenhan Yuan, Qianqian Xie, and Sophia Ananiadou. 2024. Temporal relation extraction with contrastive prototypical sampling. *Knowledge-Based Systems*, 286:111410.

Frances Yung, Mansoor Ahmad, Merel Scholman, and Vera Demberg. 2024. Prompting implicit discourse relation annotation. In *Proceedings of the 18th Linguistic Annotation Workshop (LAW-XVIII)*, pages 150–165, St. Julians, Malta. Association for Computational Linguistics.

Amir Zeldes, Tatsuya Aoyama, Yang Janet Liu, Siyao Peng, Debopam Das, and Luke Gessler. 2025. eRST: A signaled graph theory of discourse relations and organization. *Computational Linguistics*, 51(1):23–72.

Longyin Zhang, Bowei Zou, and Ai Ti Aw. 2024. Empowering tree-structured entailment reasoning: Rhetorical perception and LLM-driven interpretability. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 5783–5793, Torino, Italia. ELRA and ICCL.

Wei Zhao, Michael Strube, and Steffen Eger. 2023. Discoscore: Evaluating text generation with bert and discourse coherence. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 3865–3883.

Jie Zhou, Shenpo Dong, Hongkui Tu, Xiaodong Wang, and Yong Dou. 2022. Rsgt: Relational structure guided temporal relation extraction. In *Proceedings of the 29th international conference on computational linguistics*, pages 2001–2010.

A Appendix A. Prompt Templates

A.1 Task (1) Discourse Marker Understanding

Table table 7.

System prompt:
A conversation between User and Assistant. The User provides one sentence that contains a discourse marker 'just'. The assistant identifies the **discourse function** of the marker. Choose one of the following six labels: [Exclusionary, Unelaboratory, Unexplanatory, Emphatic, Temporal, Adjective]. Choose ONLY ONE label. Keep the answer short.

(for *Just* dataset)

System prompt:
A conversation between User and Assistant. The User provides two arguments linked with a discourse marker 'otherwise': [Arg1]. Otherwise, [Arg2]. The assistant identifies the **discourse function** of the marker. Choose one of the following four labels: [Argumentation, Consequence, Exception, Enumeration]. Choose ONLY ONE label. Keep the answer short.

(for *Otherwise* dataset)

User prompt:
<TEXT>

Question: What is the function of the discourse marker 'just' in the sentence above?

(for *Just* dataset)

User prompt:
Here are the main functions of 'just' along with their definition:

Exclusionary: 'Just' is used to exclude other possibilities or options.

Unelaboratory: 'Just' is used to deny further elaboration on an event or concept.

Unexplanatory: 'Just' is used to deny that there is an explanation or to offer a weak explanation with no stronger one available.

Emphatic: 'Just' is used to add emphasis to an already strong word or phrase.

Temporal: 'Just' is used to indicate that something happened very recently, or close to another event.

Adjective: 'Just' is used used as an adjective to describe a person or idea, especially a law or policy, as fair, appropriate, or lawful.

Given these, identify the function of 'just' in the following sentence. Respond with the function label.

<TEXT>

(for *Just* dataset)

User prompt:
Here are the main functions of 'just' along with their definition and examples:

Exclusionary: 'Just' is used to exclude other possibilities or options.
Example: "I'm just looking for a job, not a career."

Unelaboratory: 'Just' is used to deny further elaboration on an event or concept.
Example: "I just don't like it."

Unexplanatory: 'Just' is used to deny that there is an explanation or to offer a weak explanation with no stronger one available.
Example: "The lights just turn on and off."

Emphatic: 'Just' is used to add emphasis to an already strong word or phrase.
Example: "It's just amazing!"

Temporal: 'Just' is used to indicate that something happened very recently, or close to another event.
Example: "I just saw him a minute ago."

Adjective: 'Just' is used used as an adjective to describe a person or idea, especially a law or policy, as fair, appropriate, or lawful.
Example: "She is a just ruler."

Given these, identify the function of 'just' in the following sentence. Respond with the function label.

<TEXT>

(for ***Just*** dataset)

User prompt:
<TEXT>

Question: What is the function of the discourse marker 'Otherwise' between [Arg1] and [Arg2]?

(for ***Otherwise*** dataset)

Here are the main functions of 'Otherwise' along with their definition:

Consequence: If the situation in Arg1 doesn't occur, the situation in Arg2 would arise.

Argumentation: Arg2 is undesirable and can be possibly avoided by following Arg1.

Enumeration: It doesn't take the failure of Arg1 to consider Arg2 as another option.

Exception: Arg1 is an exception to Arg2.

Given these, identify the function of 'Otherwise' between [Arg1] and [Arg2] in the following sentence. Respond with the function label.

<TEXT>

(for ***Otherwise*** dataset)

User prompt:
Here are the main functions of 'Otherwise' along with their definition and examples. Arg1 and Arg2 are placed within square brackets:

Consequence: If the situation in Arg1 doesn't occur, the situation in Arg2 would arise.
Example: [I like you too.] Otherwise, [we wouldn't be friends.]

Argumentation: Arg2 is undesirable and can be possibly avoided by following Arg1.
Example: [We have to operate immediately.] Otherwise, [she will die.]

Enumeration: It doesn't take the failure of Arg1 to consider Arg2 as another option.
Example: [You can choose to go to the beach.] Otherwise, [you can stay at home and read a book.]

Exception: Arg1 is an exception to Arg2.
Example: [He is usually very punctual.] Otherwise, [he would have arrived on time.]

Given these, identify the function of 'Otherwise' between [Arg1] and [Arg2] in the following sentence. Respond with the function label.

<TEXT>

(for *Otherwise* dataset)

Table 7: Prompt Templates used for **Task (1) Discourse Marker Understanding**.

A.2 Task (2) Temporal Reasoning

Table 8.

System prompt:

A conversation between User and Assistant. The User provides a document with two target EVENT, each marked with <EVENT e>...</EVENT>. The assistant identifies the **temporal relation** between the two events.

Choose one of the following six labels: [IS_INCLUDED, INCLUDES, SIMULTANEOUS, BEFORE, AFTER, NONE]. Answer NONE if unsure. Keep the answer short and concise.

(for **TBD** and **TDD-Man** datasets)

System prompt:

A conversation between User and Assistant. The User asks a question that requires temporal arithmetic reasoning. The Assistant must reason using the logic and semantics of time to answer. Strictly follow the instructions when answering. Keep the answer short and concise.

(for **ToT-Arithmetic** dataset)

User prompt:
Given the document:

<DOCUMENT>

Quesiton: What is the temporal relation of <EVENT> <EVENT ID> with respect to <EVENT> <EVENT ID>? Choose one of the following labels: [IS_INCLUDED, INCLUDES, SIMULTANEOUS, BEFORE, AFTER, NONE].

(for **TBD** and **TDD-Man** datasets)

User prompt:
<QUESTION>

(for **ToT-Arithmetic** dataset)

Table 8: Prompt Templates used for **Task (2) Temporal Reasoning**.

A.3 Task (3) Discourse Relation Recognition

Table 9.

System prompt:
A conversation between User and Assistant. You are a helpful assistant.
Role and Goal:
You are an expert in discourse analysis, tasked with identifying the discourse relation between two sentence units based on the provided label. Your goal is to accurately determine the relationship between these two units.

Guidelines:
1. You will receive Unit1 and Unit2. Unit1 appears before Unit2 in the original text.
2. You will be informed about the language of these units.
3. You will be informed of the corpus from which the data is drawn, which may help guide your analysis.
4. The framework for analysis will be provided, outlining the structure used for discourse analysis.
5. You will be given the context in which these two units appear.
6. The direction of the relationship between these two units will be given.
7. You will be provided with a set of labels representing possible discourse relations. Do not modify any label. Choose one label that best fits the relationship between Unit1 and Unit2, and output only the chosen label.

Labels:
contrast, condition, mode, organization, frame, temporal, concession, reformulation, comment, query, attribution, alternation, purpose, explanation, elaboration, causal, conjunction.

User prompt:
Language:
<LANG>

Corpus:
<CORPUS>

Framework:
<FRAMEWORK>

Context:
<CONTEXT>

Direction:
<DIRECTION>

Unit1:
<UNIT1>

Unit2:
<UNIT2>

Question: What is the discourse relation between Unit1 and Unit2?"

Table 9: Prompt Templates used for **Task (3) Discourse Relation Recognition**.

A.4   Task (4) Sentence Ordering

Table 10.

System prompt:
A conversation between User and Assistant. The User provides a list of shuffled sentences. Each sentence is enclosed within sentence tags, e.g., <s 1> Sentence one. </s 1>. The Assistant reorders the sentences to form a coherent paragraph. Return only the sequence of sentence tags in the correct order, for example: <s 2> <s 1> <s 3>. Do not include any sentence content. Do not repeat or modify any sentence tags.

User prompt:
<s 1> <SENTENCE 1> </s 1>
<s 1> <SENTENCE 2> </s 1>
...
<s n> <SENTENCE n> </s n>

Table 10: Prompt Templates used for **Task (4) Sentence Ordering**.

A.5 Task (5) Dialogue Discourse Parsing

Table 11.

System prompt:

A conversation between User and Assistant. The User provides a boardgame dialogue history / Ubuntu chat log (context and structure), along with a new turn. The assistant identifies the **discourse structure** of the new turn in relation to the context. The structure should be represented in the format: RELATION(S_ID1, S_ID2), where RELATION is the discourse relation, S_ID2 is the ID of the new turn, and S_ID1 is the ID of the sentence in the context that it relates to. S_ID2 is bigger than S_ID1 since dialogue flow is unidirectional and there is no backward relation. Use the following discourse relations: [ACKNOWLEDGEMENT, ALTERNATION, BACKGROUND, CLARIF_Q, COMMENT, CONDITIONAL, CONTINUATION, CONTRAST, CORRECTION, ELABORATION, EXPLANATION, NARRATION, PARALLEL, QA_PAIR, Q_ELABORATION, RESULT]. If multiple relations exist, separate them with spaces. Provide only the structure without any additional text.

(for **STAC** and **Molweni** datasets)

System prompt:

A conversation between User and Assistant. The User provides a Minecraft game history (context and structure), along with a new turn. The assistant identifies the **discourse structure** of the new turn in relation to the context. The structure should be represented in the format: RELATION(S_ID1, S_ID2), where RELATION is the discourse relation, S_ID2 is the ID of the new turn, and S_ID1 is the ID of the sentence in the context that it relates to. S_ID2 is bigger than S_ID1 since dialogue flow is unidirectional and there is no backward relation. Use the following discourse relations: [AC-KNOWLEDGEMENT, ALTERNATION, CLARIF_Q, COMMENT, CONDITIONAL, CONFIRM_Q, CONTINUATION, CONTRAST, CORRECTION, ELABORATION, EXPLANATION, NARRATION, QA_PAIR, Q_ELABORATION, RESULT, SEQUENCE]. If multiple relations exist, separate them with spaces. Provide only the structure without any additional text.

(for **MSDC** dataset)

User prompt:
Context:
<CONTEXT>

Structure:
<STRUCTURE>

New turn:
<NEW TURN>

Question: What is the discourse structure of the new turn in relation to the context? Provide the answer in the format: RELATION(S_ID1, S_ID2).

Table 11: Prompt Templates used for **Task (5) Dialogue Discourse Parsing**.

B Appendix B. Detailed Results

B.1 Task (1) Discourse Marker Understanding

Tables tables 12 to 20.

		w/o reasoning					w/ reasoning				
Model	Size	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$17.3_{1.4}$	$4.0_{2.3}$	$17.3_{1.4}$	$5.7_{1.8}$	4	$32.0_{1.6}$	$18.4_{0.5}$	$32.0_{1.6}$	$22.9_{0.9}$	279
Qwen3-1.7B	1.7B	$14.0_{0.4}$	$2.2_{0.2}$	$10.5_{0.3}$	$3.7_{0.2}$	3	$38.9_{0.7}$	$41.9_{3.4}$	$38.9_{0.7}$	$31.9_{1.3}$	538
Qwen3-4B	4B	$34.7_{0.4}$	$30.3_{1.7}$	$34.7_{0.4}$	$27.0_{0.4}$	3	$55.1_{1.8}$	$62.5_{3.2}$	$55.1_{1.8}$	$50.7_{1.8}$	543
Qwen3-8B	8B	$44.7_{0.6}$	$44.0_{3.6}$	$44.7_{0.6}$	$34.5_{0.7}$	3	$59.1_{2.9}$	$67.5_{7.5}$	$59.1_{2.9}$	$54.0_{3.8}$	583
Qwen3-14B	14B	$57.8_{2.0}$	$55.6_{3.4}$	$57.8_{2.0}$	$53.1_{2.0}$	2	$60.2_{0.7}$	$62.3_{5.7}$	$60.2_{0.7}$	$52.6_{1.4}$	404
Qwen3-32B	32B	$55.1_{2.0}$	$60.6_{2.6}$	$55.1_{2.0}$	$51.4_{2.3}$	3	$59.8_{1.8}$	$60.0_{7.2}$	$59.8_{1.8}$	$53.5_{2.3}$	425
DS-r1-distill-Qwen	32B	-	-	-	-	-	$56.7_{0.9}$	$60.4_{9.9}$	$51.3_{4.6}$	$50.3_{5.5}$	304
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$53.7_{0.5}$	$20.9_{1.8}$	$19.5_{2.0}$	$18.5_{1.5}$	466
GPT-5-mini (low)	Unk.	-	-	-	-	-	$63.3_{2.4}$	$52.5_{5.0}$	$60.4_{6.0}$	$53.3_{5.5}$	94
GPT-5-mini (high)	Unk.	-	-	-	-	-	$61.7_{0.6}$	$56.6_{8.7}$	$61.7_{0.6}$	$53.5_{1.3}$	857

Table 12: Details on **Task (1) Discourse Marker Understanding** performance on *Just*-**Manual** dataset, using **basic** prompting strategy.

		w/o reasoning					w/ reasoning				
Model	Size	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$16.9_{1.1}$	$5.2_{2.1}$	$16.9_{1.1}$	$7.7_{2.3}$	3	$28.4_{1.6}$	$8.3_{4.2}$	$9.1_{2.2}$	$7.0_{1.8}$	1427
Qwen3-1.7B	1.7B	$34.4_{0.0}$	$20.6_{0.7}$	$34.4_{0.0}$	$22.8_{0.2}$	3	$40.7_{4.2}$	$15.9_{6.2}$	$14.1_{3.3}$	$12.9_{3.3}$	1624
Qwen3-4B	4B	$28.7_{0.2}$	$39.4_{3.3}$	$28.7_{0.2}$	$25.0_{0.4}$	2	$43.3_{2.0}$	$18.5_{5.8}$	$12.7_{4.1}$	$12.8_{3.9}$	1823
Qwen3-8B	8B	$49.6_{0.4}$	$28.7_{0.9}$	$49.6_{0.4}$	$35.3_{0.6}$	2	$50.9_{3.1}$	$37.6_{3.3}$	$26.1_{3.8}$	$27.1_{4.0}$	1443
Qwen3-14B	14B	$47.8_{0.0}$	$52.4_{0.1}$	$47.8_{0.0}$	$40.8_{0.1}$	3	$54.9_{2.0}$	$23.5_{1.3}$	$20.3_{0.3}$	$19.5_{0.3}$	1219
Qwen3-32B	32B	$68.2_{0.7}$	$71.5_{0.9}$	$68.2_{0.7}$	$66.3_{0.7}$	3	$65.6_{3.5}$	$46.6_{6.4}$	$47.5_{5.0}$	$44.9_{4.7}$	608
DS-r1-distill-Qwen	32B	-	-	-	-	-	$63.7_{1.4}$	$62.7_{6.6}$	$57.6_{4.2}$	$53.3_{2.8}$	326
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$66.3_{0.5}$	$61.7_{7.8}$	$60.0_{4.7}$	$53.1_{3.6}$	291
GPT-5-mini (low)	Unk.	-	-	-	-	-	$65.9_{0.5}$	$69.4_{3.5}$	$65.9_{0.5}$	$59.8_{1.4}$	70
GPT-5-mini (high)	Unk.	-	-	-	-	-	$66.1_{1.7}$	$72.7_{7.5}$	$66.1_{1.7}$	$60.2_{3.2}$	531

Table 13: Details on **Task (1) Discourse Marker Understanding** performance on *Just*-**Manual** dataset, using **"definition"** prompting strategy.

		w/o reasoning					w/ reasoning				
Model	Size	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$20.4_{1.2}$	$7.2_{0.4}$	$20.4_{1.2}$	$10.4_{0.7}$	3	$26.2_{1.8}$	$6.0_{1.9}$	$7.9_{1.5}$	$6.0_{1.4}$	1436
Qwen3-1.7B	1.7B	$40.4_{0.5}$	$25.4_{3.5}$	$40.4_{0.5}$	$28.1_{0.9}$	3	$40.2_{2.2}$	$16.9_{3.3}$	$16.3_{1.8}$	$14.5_{1.7}$	1587
Qwen3-4B	4B	$34.7_{0.4}$	$30.6_{0.2}$	$34.7_{0.4}$	$28.9_{0.4}$	3	$44.2_{2.7}$	$29.5_{10.8}$	$21.9_{8.8}$	$22.1_{8.9}$	1942
Qwen3-8B	8B	$42.2_{0.0}$	$61.6_{0.0}$	$42.2_{0.0}$	$33.5_{0.0}$	2	$46.4_{2.9}$	$34.1_{3.7}$	$22.8_{2.9}$	$24.3_{2.7}$	1505
Qwen3-14B	14B	$56.9_{0.4}$	$56.2_{1.5}$	$56.9_{0.4}$	$49.3_{0.7}$	3	$55.6_{1.3}$	$22.5_{5.7}$	$19.9_{5.4}$	$19.6_{5.2}$	1574
Qwen3-32B	32B	$69.8_{1.5}$	$69.1_{1.9}$	$69.8_{1.5}$	$67.8_{1.9}$	3	$64.4_{2.0}$	$42.1_{8.8}$	$41.0_{8.1}$	$39.2_{7.4}$	613
DS-r1-distill-Qwen	32B	-	-	-	-	-	$59.6_{2.9}$	$33.5_{3.1}$	$32.8_{3.7}$	$31.2_{3.3}$	313
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$67.0_{1.0}$	$52.0_{3.0}$	$52.7_{3.9}$	$48.0_{3.4}$	421
GPT-5-mini (low)	Unk.	-	-	-	-	-	$65.6_{0.0}$	$64.1_{0.4}$	$65.6_{0.0}$	$60.7_{0.1}$	74
GPT-5-mini (high)	Unk.	-	-	-	-	-	$65.6_{1.1}$	$64.0_{1.8}$	$65.6_{1.1}$	$60.3_{1.7}$	528

Table 14: Details on **Task (1) Discourse Marker Understanding** performance on *Just*-**Manual** dataset, using **"definition+example"** prompting strategy.

		w/o reasoning					w/ reasoning				
Model	Size	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$14.6_{0.8}$	$10.3_{5.0}$	$16.7_{0.4}$	$5.6_{1.3}$	4	$25.5_{1.3}$	$18.0_{2.6}$	$30.4_{7.3}$	$17.1_{1.0}$	260
Qwen3-1.7B	1.7B	$13.4_{0.0}$	$16.3_{5.3}$	$11.1_{0.4}$	$4.3_{0.2}$	3	$25.9_{0.8}$	$14.7_{1.6}$	$24.9_{1.0}$	$15.7_{1.1}$	491
Qwen3-4B	4B	$24.8_{1.0}$	$22.0_{1.1}$	$21.4_{0.9}$	$14.4_{0.7}$	3	$41.5_{0.9}$	$32.2_{2.9}$	$33.8_{0.8}$	$28.0_{0.5}$	537
Qwen3-8B	8B	$34.5_{0.5}$	$27.1_{1.3}$	$29.4_{0.4}$	$21.4_{0.4}$	2	$46.0_{1.1}$	$33.9_{5.7}$	$36.0_{0.5}$	$30.5_{0.5}$	610
Qwen3-14B	14B	$33.8_{1.1}$	$37.2_{1.6}$	$32.2_{0.8}$	$24.7_{0.9}$	2	$43.2_{1.9}$	$36.4_{2.2}$	$33.8_{2.5}$	$30.8_{2.3}$	463
Qwen3-32B	32B	$29.4_{0.8}$	$29.1_{1.7}$	$25.9_{0.3}$	$19.3_{0.7}$	3	$48.5_{1.7}$	$35.3_{4.0}$	$36.9_{1.3}$	$32.7_{1.5}$	415
DS-r1-distill-Qwen	32B	-	-	-	-	-	$31.8_{3.3}$	$33.4_{6.8}$	$25.7_{4.3}$	$21.7_{4.2}$	291
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$48.1_{4.0}$	$10.1_{3.9}$	$9.6_{4.1}$	$9.4_{3.9}$	419
GPT-5-mini (low)	Unk.	-	-	-	-	-	$56.4_{1.1}$	$36.8_{5.2}$	$38.2_{2.3}$	$34.6_{1.5}$	103
GPT-5-mini (high)	Unk.	-	-	-	-	-	$57.4_{1.7}$	$37.5_{3.6}$	$37.4_{0.4}$	$35.2_{0.1}$	818

Table 15: Details on **Task (1) Discourse Marker Understanding** performance on *Just*-**Subtitle** dataset, using **basic** prompting strategy.

Model	Size	w/o reasoning					w/ reasoning				
		Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$13.7_{0.4}$	$7.3_{0.6}$	$15.1_{1.0}$	$6.2_{0.9}$	4	$19.3_{1.2}$	$3.7_{1.2}$	$3.4_{1.2}$	$2.7_{0.2}$	1426
Qwen3-1.7B	1.7B	$19.7_{0.3}$	$9.5_{0.1}$	$19.8_{0.2}$	$10.8_{0.2}$	3	$26.2_{1.5}$	$9.5_{2.0}$	$7.6_{0.8}$	$6.4_{0.7}$	1705
Qwen3-4B	4B	$29.8_{0.3}$	$32.2_{0.2}$	$27.8_{0.5}$	$20.5_{0.3}$	3	$30.9_{2.4}$	$11.6_{4.2}$	$7.6_{2.6}$	$7.2_{2.4}$	1667
Qwen3-8B	8B	$31.3_{0.5}$	$30.8_{2.9}$	$46.1_{0.7}$	$27.4_{1.1}$	3	$32.3_{1.7}$	$19.5_{2.6}$	$13.6_{3.1}$	$12.5_{1.9}$	1667
Qwen3-14B	14B	$31.3_{0.5}$	$35.2_{1.6}$	$46.1_{1.0}$	$27.3_{0.5}$	3	$32.9_{1.7}$	$9.6_{4.4}$	$8.3_{3.5}$	$7.7_{3.3}$	1328
Qwen3-32B	32B	$32.8_{0.6}$	$30.3_{0.4}$	$30.5_{0.5}$	$25.0_{0.6}$	3	$48.9_{2.0}$	$18.3_{3.2}$	$18.3_{3.4}$	$17.7_{3.3}$	569
DS-r1-distill-Qwen	32B	-	-	-	-	-	$40.5_{2.5}$	$39.2_{5.8}$	$33.2_{3.6}$	$29.3_{3.6}$	308
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$60.2_{1.4}$	$35.8_{6.1}$	$34.1_{6.0}$	$32.5_{6.1}$	321
GPT-5-mini (low)	Unk.	-	-	-	-	-	$58.4_{1.1}$	$43.6_{2.4}$	$41.7_{1.2}$	$39.3_{1.3}$	65
GPT-5-mini (high)	Unk.	-	-	-	-	-	$63.1_{0.0}$	$43.7_{1.7}$	$44.2_{0.0}$	$41.9_{1.0}$	509

Table 16: Details on **Task (1) Discourse Marker Understanding** performance on *Just*-**Subtitle** dataset, using **"definition"** prompting strategy.

Model	Size	w/o reasoning					w/ reasoning				
		Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$19.1_{0.9}$	$7.8_{1.1}$	$18.4_{0.7}$	$9.6_{0.4}$	3	$16.9_{1.8}$	$3.2_{0.5}$	$3.8_{1.1}$	$2.4_{0.5}$	1439
Qwen3-1.7B	1.7B	$20.3_{0.4}$	$9.9_{0.4}$	$20.1_{0.5}$	$13.0_{0.3}$	3	$25.5_{1.9}$	$7.1_{1.5}$	$5.5_{0.9}$	$5.0_{0.4}$	1743
Qwen3-4B	4B	$29.9_{0.3}$	$24.8_{0.2}$	$27.7_{0.4}$	$21.7_{0.2}$	3	$30.3_{1.1}$	$21.4_{10.0}$	$13.3_{6.6}$	$12.8_{6.7}$	1944
Qwen3-8B	8B	$30.9_{0.6}$	$28.3_{2.2}$	$44.9_{0.6}$	$25.5_{0.7}$	2	$32.2_{1.4}$	$22.9_{5.1}$	$16.0_{4.7}$	$14.0_{2.8}$	1593
Qwen3-14B	14B	$36.2_{0.4}$	$38.2_{1.6}$	$48.6_{0.5}$	$32.3_{0.7}$	3	$33.2_{1.3}$	$14.6_{5.1}$	$11.5_{4.8}$	$10.8_{4.1}$	1427
Qwen3-32B	32B	$35.7_{1.1}$	$34.1_{1.6}$	$46.1_{0.5}$	$30.3_{0.8}$	2	$47.1_{1.2}$	$15.0_{1.1}$	$14.3_{1.1}$	$13.9_{1.1}$	718
DS-r1-distill-Qwen	32B	-	-	-	-	-	$35.8_{0.3}$	$17.9_{3.7}$	$13.4_{3.2}$	$12.5_{2.7}$	375
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$59.5_{3.6}$	$27.0_{1.3}$	$22.6_{2.7}$	$21.5_{2.6}$	380
GPT-5-mini (low)	Unk.	-	-	-	-	-	$62.9_{0.6}$	$48.0_{1.7}$	$44.0_{0.5}$	$42.1_{0.3}$	87
GPT-5-mini (high)	Unk.	-	-	-	-	-	$63.4_{0.3}$	$46.5_{1.3}$	$40.7_{0.0}$	$40.1_{0.2}$	534

Table 17: Details on **Task (1) Discourse Marker Understanding** performance on *Just*-**Subtitle** dataset, using **"definition+example"** prompting strategy.

Model	Size	w/o reasoning					w/ reasoning				
		Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$44.6_{0.0}$	$19.9_{0.0}$	$44.6_{0.0}$	$27.5_{0.0}$	3	$22.2_{1.3}$	$24.9_{2.8}$	$22.2_{1.3}$	$19.0_{1.5}$	277
Qwen3-1.7B	1.7B	$30.3_{0.7}$	$20.1_{0.2}$	$30.3_{0.7}$	$24.1_{0.4}$	2	$23.9_{0.6}$	$26.2_{4.1}$	$23.9_{0.6}$	$17.5_{0.9}$	492
Qwen3-4B	4B	$25.7_{0.2}$	$8.3_{0.2}$	$25.7_{0.2}$	$11.9_{0.2}$	1	$32.3_{1.2}$	$24.5_{17.9}$	$32.3_{1.2}$	$21.0_{0.7}$	569
Qwen3-8B	8B	$18.6_{0.1}$	$38.2_{2.5}$	$18.6_{0.1}$	$6.7_{0.2}$	2	$32.3_{0.7}$	$34.1_{0.5}$	$32.3_{0.7}$	$24.0_{0.7}$	512
Qwen3-14B	14B	$34.3_{0.1}$	$42.6_{0.6}$	$34.3_{0.1}$	$25.6_{0.1}$	2	$32.1_{1.0}$	$30.0_{3.4}$	$32.1_{1.0}$	$23.6_{0.9}$	509
Qwen3-32B	32B	$36.5_{1.3}$	$50.7_{5.3}$	$36.5_{1.3}$	$38.1_{1.3}$	2	$34.3_{0.4}$	$19.7_{0.4}$	$34.3_{0.4}$	$23.8_{0.4}$	373
DS-r1-distill-Qwen	32B	-	-	-	-	-	$33.1_{1.1}$	$25.9_{1.1}$	$33.1_{1.1}$	$24.9_{0.9}$	276
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$31.2_{0.8}$	$39.1_{1.2}$	$31.2_{0.8}$	$25.8_{0.4}$	373
GPT-5-mini (low)	Unk.	-	-	-	-	-	$34.6_{0.4}$	$25.4_{0.6}$	$34.6_{0.4}$	$25.5_{0.4}$	74
GPT-5-mini (high)	Unk.	-	-	-	-	-	$35.5_{0.5}$	$31.1_{5.6}$	$35.5_{0.5}$	$26.5_{0.2}$	375

Table 18: Details on **Task (1) Discourse Marker Understanding** performance on *Otherwise* dataset, using **basic** prompting strategy.

Model	Size	w/o reasoning					w/ reasoning				
		Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$44.6_{0.0}$	$19.9_{0.0}$	$44.6_{0.0}$	$27.5_{0.0}$	2	$22.7_{0.9}$	$25.0_{3.6}$	$22.7_{0.9}$	$18.1_{1.4}$	402
Qwen3-1.7B	1.7B	$24.2_{1.6}$	$28.3_{1.7}$	$24.2_{1.7}$	$20.5_{1.6}$	1	$21.2_{1.0}$	$35.9_{6.0}$	$21.2_{1.0}$	$11.9_{1.1}$	515
Qwen3-4B	4B	$30.3_{0.6}$	$56.1_{0.5}$	$30.3_{0.6}$	$32.3_{0.4}$	2	$21.8_{0.9}$	$61.8_{4.9}$	$21.8_{0.9}$	$15.1_{1.7}$	547
Qwen3-8B	8B	$33.6_{0.9}$	$65.2_{1.1}$	$33.6_{0.9}$	$33.5_{0.9}$	2	$39.0_{1.7}$	$70.1_{1.8}$	$39.0_{1.7}$	$38.6_{1.9}$	1033
Qwen3-14B	14B	$43.5_{0.4}$	$57.8_{0.4}$	$43.5_{0.4}$	$44.3_{0.5}$	2	$45.2_{2.6}$	$70.9_{1.8}$	$45.2_{2.6}$	$44.6_{2.1}$	766
Qwen3-32B	32B	$55.0_{0.2}$	$64.0_{1.2}$	$55.0_{0.2}$	$54.9_{0.4}$	2	$49.3_{2.3}$	$71.3_{1.5}$	$49.3_{2.3}$	$50.3_{1.8}$	737
DS-r1-distill-Qwen	32B	-	-	-	-	-	$32.4_{2.3}$	$60.0_{1.5}$	$32.4_{2.3}$	$31.4_{3.3}$	369
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$38.9_{1.9}$	$70.3_{1.6}$	$38.9_{1.9}$	$45.2_{1.7}$	682
GPT-5-mini (low)	Unk.	-	-	-	-	-	$36.8_{0.8}$	$64.0_{2.8}$	$36.8_{0.8}$	$34.0_{1.4}$	138
GPT-5-mini (high)	Unk.	-	-	-	-	-	$43.9_{1.0}$	$74.5_{4.1}$	$43.9_{1.0}$	$43.6_{1.3}$	751

Table 19: Details on **Task (1) Discourse Marker Understanding** performance on *Otherwise* dataset, using **"definition"** prompting strategy.

Model	Size	w/o reasoning					w/ reasoning				
		Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.	Acc	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$44.6_{0.0}$	$19.9_{0.1}$	$44.6_{0.0}$	$27.5_{0.1}$	2	$15.7_{1.4}$	$32.0_{14.3}$	$15.7_{1.4}$	$11.8_{2.1}$	1399
Qwen3-1.7B	1.7B	$21.0_{0.8}$	$32.2_{2.0}$	$21.0_{0.8}$	$11.7_{0.8}$	2	$16.2_{1.8}$	$48.6_{9.0}$	$16.2_{1.8}$	$13.1_{1.4}$	1442
Qwen3-4B	4B	$41.8_{0.8}$	$56.5_{0.5}$	$41.8_{0.8}$	$44.5_{0.7}$	2	$30.7_{1.9}$	$61.7_{1.5}$	$30.7_{1.9}$	$33.8_{1.9}$	1585
Qwen3-8B	8B	$46.7_{0.3}$	$60.2_{1.0}$	$46.7_{0.3}$	$49.2_{0.4}$	2	$45.6_{1.4}$	$71.8_{2.2}$	$45.6_{1.4}$	$46.8_{1.3}$	1574
Qwen3-14B	14B	$51.8_{0.7}$	$62.9_{0.5}$	$51.8_{0.7}$	$53.8_{0.6}$	2	$51.4_{1.6}$	$73.7_{0.6}$	$51.4_{1.6}$	$53.9_{1.1}$	1582
Qwen3-32B	32B	$63.8_{0.8}$	$67.5_{0.4}$	$63.8_{0.8}$	$62.9_{0.6}$	2	$66.1_{0.6}$	$74.5_{0.5}$	$66.1_{0.6}$	$65.3_{0.6}$	873
DS-r1-distill-Qwen	32B	-	-	-	-	-	$44.3_{2.7}$	$65.2_{2.7}$	$44.3_{2.7}$	$47.0_{2.8}$	453
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$58.8_{2.2}$	$74.3_{0.7}$	$58.8_{2.2}$	$63.9_{1.4}$	656
GPT-5-mini (low)	Unk.	-	-	-	-	-	$51.9_{2.4}$	$73.9_{1.5}$	$51.9_{2.4}$	$54.8_{2.5}$	152
GPT-5-mini (high)	Unk.	-	-	-	-	-	$71.8_{1.7}$	$79.5_{0.6}$	$71.8_{1.7}$	$71.7_{1.8}$	937

Table 20: Details on **Task (1) Discourse Marker Understanding** performance on *Otherwise* dataset, using **"definition+example"** prompting strategy.

B.2 Task (2) Temporal Reasoning

Tables tables 21 to 25.

		w/o reasoning					w/ reasoning				
Model	Size	micro-F1	weighted-Pre	weighted-Rec	weighted-F1	tok.	micro-F1	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$27.3_{9.3}$	$21.9_{2.0}$	$27.3_{9.3}$	$16.6_{9.4}$	3	$24.0_{0.8}$	$32.5_{1.7}$	$24.0_{0.8}$	$21.0_{1.0}$	285
Qwen3-1.7B	1.7B	$28.0_{0.5}$	$30.9_{12.1}$	$28.0_{0.5}$	$23.2_{0.5}$	2	$31.3_{0.3}$	$37.4_{0.9}$	$31.3_{0.3}$	$30.5_{0.5}$	568
Qwen3-4B	4B	$30.5_{0.3}$	$41.0_{1.0}$	$30.5_{0.3}$	$25.8_{0.5}$	2	$33.8_{0.5}$	$44.2_{1.0}$	$33.8_{0.5}$	$29.6_{0.3}$	718
Qwen3-8B	8B	$34.5_{0.4}$	$40.6_{2.0}$	$34.5_{0.4}$	$29.1_{0.7}$	2	$37.6_{1.0}$	$46.7_{1.1}$	$37.6_{1.0}$	$33.6_{0.8}$	754
Qwen3-14B	14B	$34.0_{0.2}$	$47.9_{0.4}$	$34.0_{0.2}$	$30.1_{0.4}$	2	$42.5_{0.1}$	$49.7_{0.7}$	$42.5_{0.1}$	$42.1_{0.5}$	472
Qwen3-32B	32B	$30.6_{0.5}$	$42.9_{0.5}$	$30.6_{0.5}$	$22.8_{0.2}$	2	$42.4_{0.4}$	$53.8_{0.9}$	$42.4_{0.4}$	$36.6_{0.3}$	464
DS-r1-distill-Qwen	32B	-	-	-	-	-	$27.7_{2.7}$	$49.2_{1.7}$	$27.7_{2.7}$	$26.5_{1.3}$	317
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$39.9_{0.0}$	$50.9_{0.0}$	$39.9_{0.0}$	$33.0_{0.0}$	476
GPT-5-mini (low)	Unk.	-	-	-	-	-	$41.9_{0.1}$	$55.1_{0.7}$	$41.9_{0.1}$	$38.8_{0.1}$	144
GPT-5-mini (high)	Unk.	-	-	-	-	-	$45.2_{0.3}$	$56.3_{0.0}$	$45.2_{0.3}$	$41.4_{0.6}$	731

Table 21: Details on **Task (2) Temporal Reasoning** performance on **TBD** dataset, using **"without context"** prompting strategy.

		w/o reasoning					w/ reasoning				
Model	Size	micro-F1	Weighted-Pre	Weighted-Rec	Weighted-F1	tok.	micro-F1	Weighted-Pre	Weighted-Rec	Weighted-F1	tok.
Qwen3-0.6B	0.6B	$32.0_{5.5}$	$23.2_{0.5}$	$32.0_{5.5}$	$24.0_{4.7}$	3	$21.0_{0.3}$	$30.2_{0.7}$	$21.0_{0.3}$	$17.9_{0.2}$	346
Qwen3-1.7B	1.7B	$23.4_{0.4}$	$34.7_{1.2}$	$23.4_{0.4}$	$15.6_{0.8}$	2	$26.2_{0.8}$	$37.6_{2.1}$	$26.2_{0.8}$	$22.3_{0.9}$	559
Qwen3-4B	4B	$28.3_{0.2}$	$42.7_{1.5}$	$28.3_{0.2}$	$18.8_{0.3}$	2	$31.7_{0.7}$	$45.6_{1.6}$	$31.7_{0.7}$	$26.1_{0.6}$	778
Qwen3-8B	8B	$25.4_{0.3}$	$46.8_{2.9}$	$25.4_{0.3}$	$16.8_{0.4}$	2	$35.3_{0.4}$	$50.6_{1.6}$	$35.3_{0.4}$	$29.6_{0.6}$	760
Qwen3-14B	14B	$31.1_{0.4}$	$51.0_{0.5}$	$31.1_{0.4}$	$27.7_{0.7}$	3	$39.8_{0.5}$	$53.7_{0.9}$	$39.8_{0.5}$	$39.6_{0.5}$	501
Qwen3-32B	32B	$27.8_{0.7}$	$54.4_{4.9}$	$27.8_{0.7}$	$21.1_{1.2}$	3	$40.8_{0.2}$	$56.6_{2.0}$	$40.8_{0.2}$	$34.5_{0.5}$	475
DS-r1-distill-Qwen	32B	-	-	-	-	-	$23.8_{2.5}$	$52.8_{3.0}$	$23.8_{2.5}$	$22.5_{0.7}$	283
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$33.1_{0.0}$	$57.3_{0.0}$	$33.1_{0.0}$	$28.6_{0.0}$	457
GPT-5-mini (low)	Unk.	-	-	-	-	-	$38.7_{0.2}$	$59.6_{0.2}$	$38.7_{0.2}$	$34.4_{0.6}$	166
GPT-5-mini (high)	Unk.	-	-	-	-	-	$43.4_{0.3}$	$61.9_{1.9}$	$43.4_{0.3}$	$38.0_{0.4}$	870

Table 22: Details on **Task (2) Temporal Reasoning** performance on **TBD** dataset, using **"with context"** prompting strategy.

		w/o reasoning					w/ reasoning				
Model	Size	micro-F1	weighted-Pre	weighted-Rec	weighted-F1	tok.	micro-F1	weighted-Pre	weighted-Rec	weighted-F1	tok.
Qwen3-0.6B	0.6B	$12.6_{0.1}$	$11.7_{7.8}$	$12.6_{0.1}$	$2.9_{0.2}$	3	$25.8_{1.1}$	$29.1_{1.1}$	$25.8_{1.1}$	$25.6_{1.0}$	392
Qwen3-1.7B	1.7B	$12.5_{0.0}$	$1.6_{0.0}$	$12.5_{0.0}$	$2.8_{0.0}$	2	$21.9_{0.6}$	$29.8_{2.5}$	$21.9_{0.6}$	$17.9_{0.6}$	594
Qwen3-4B	4B	$19.4_{0.5}$	$11.6_{0.3}$	$19.4_{0.5}$	$12.5_{0.3}$	2	$25.4_{0.4}$	$37.1_{0.9}$	$25.4_{0.4}$	$20.1_{0.5}$	879
Qwen3-8B	8B	$18.2_{0.2}$	$22.3_{0.4}$	$18.2_{0.2}$	$11.3_{0.1}$	2	$28.8_{0.3}$	$42.0_{1.6}$	$28.8_{0.3}$	$23.1_{0.4}$	846
Qwen3-14B	14B	$26.1_{0.2}$	$57.2_{2.6}$	$26.1_{0.2}$	$13.8_{0.1}$	2	$29.5_{0.5}$	$39.2_{1.5}$	$29.5_{0.5}$	$22.0_{0.5}$	582
Qwen3-32B	32B	$27.5_{0.1}$	$37.7_{1.5}$	$27.5_{0.1}$	$15.3_{0.7}$	2	$31.6_{0.4}$	$43.3_{2.5}$	$31.6_{0.4}$	$23.9_{0.5}$	509
DS-r1-distill-Qwen	32B	-	-	-	-	-	$18.6_{2.6}$	$42.4_{1.6}$	$18.6_{2.6}$	$15.8_{1.4}$	298
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$22.2_{0.0}$	$48.8_{0.0}$	$22.2_{0.0}$	$21.0_{0.0}$	478
GPT-5-mini (low)	Unk.	-	-	-	-	-	$34.4_{0.2}$	$49.6_{0.5}$	$34.4_{0.2}$	$30.5_{0.3}$	204
GPT-5-mini (high)	Unk.	-	-	-	-	-	$36.7_{0.3}$	$52.7_{0.5}$	$36.7_{0.3}$	$34.6_{0.2}$	1203

Table 23: Details on **Task (2) Temporal Reasoning** performance on **TDD-Man** dataset, using **"without context"** prompting strategy.

		w/o reasoning					w/ reasoning				
Model	Size	micro-F1	Weighted-Pre	Weighted-Rec	Weighted-F1	tok.	micro-F1	Weighted-Pre	Weighted-Rec	Weighted-F1	tok.
Qwen3-0.6B	0.6B	$17.4_{3.4}$	$10.0_{3.3}$	$17.4_{3.4}$	$8.0_{3.5}$	3	$23.1_{0.7}$	$31.2_{1.0}$	$23.1_{0.7}$	$19.2_{0.5}$	297
Qwen3-1.7B	1.7B	$13.0_{0.3}$	$29.5_{1.7}$	$13.0_{0.3}$	$5.8_{0.1}$	2	$21.4_{0.1}$	$36.7_{3.6}$	$21.4_{0.1}$	$18.4_{0.5}$	624
Qwen3-4B	4B	$19.4_{0.2}$	$11.0_{0.4}$	$19.4_{0.2}$	$12.6_{0.2}$	2	$23.8_{0.1}$	$40.6_{0.2}$	$23.8_{0.1}$	$19.9_{0.1}$	833
Qwen3-8B	8B	$23.4_{0.3}$	$20.8_{1.3}$	$23.4_{0.3}$	$14.3_{0.1}$	2	$27.6_{0.8}$	$44.8_{2.3}$	$27.6_{0.8}$	$24.8_{0.8}$	904
Qwen3-14B	14B	$22.8_{0.1}$	$46.7_{8.6}$	$22.8_{0.1}$	$13.7_{0.1}$	2	$24.0_{0.6}$	$39.6_{2.4}$	$24.0_{0.6}$	$20.4_{0.7}$	546
Qwen3-32B	32B	$24.9_{0.5}$	$29.6_{0.4}$	$24.9_{0.5}$	$15.0_{0.5}$	2	$28.9_{1.4}$	$44.1_{3.3}$	$28.9_{1.4}$	$24.4_{1.3}$	460
DS-r1-distill-Qwen	32B	-	-	-	-	-	$16.9_{2.8}$	$42.8_{2.9}$	$16.9_{2.8}$	$15.4_{1.6}$	298
DeepSeek-r1-0528	37/671B	-	-	-	-	-	$25.9_{0.0}$	$47.1_{0.0}$	$25.9_{0.0}$	$22.7_{0.0}$	433
GPT-5-mini (low)	Unk.	-	-	-	-	-	$27.2_{0.5}$	$53.3_{0.8}$	$27.2_{0.5}$	$28.6_{0.6}$	171
GPT-5-mini (high)	Unk.	-	-	-	-	-	$27.9_{0.2}$	$53.5_{0.0}$	$27.9_{0.2}$	$30.1_{0.1}$	935

Table 24: Details on **Task (2) Temporal Reasoning** performance on **TDD-Man** dataset, using **"with context"** prompting strategy.

Model	Size	Acc (all)	Acc (tz)	Acc (as)	Acc (scd)	Acc (mop)	Acc (dur)	Acc (cmp)	Acc (trk)	tok.
					baselines					
Claude-3-Sonnet	Unk.	-	74.00	58.57	29.60	26.57	15.00	39.14	40.40	-
GPT-4	Unk.	-	88.00	76.28	43.60	46.86	16.00	63.14	45.60	-
Gemini 1.5 Pro	Unk.	-	90.00	71.14	40.00	62.57	13.50	55.43	41.20	-
					w/o reasoning					
Qwen3-0.6B	0.6B	$7.0_{0.1}$	$17.0_{1.0}$	$8.9_{0.2}$	$9.7_{3.1}$	$0.0_{0.0}$	$0.0_{0.0}$	$8.4_{1.3}$	$10.8_{1.6}$	15
Qwen3-1.7B	1.7B	$8.9_{0.2}$	$22.7_{1.3}$	$14.4_{0.5}$	$7.6_{1.2}$	$0.3_{0.0}$	$2.0_{0.0}$	$11.7_{0.6}$	$10.8_{0.4}$	46
Qwen3-4B	4B	$15.3_{0.3}$	$32.0_{0.0}$	$22.4_{0.7}$	$7.2_{1.6}$	$0.2_{0.1}$	$11.2_{0.3}$	$24.8_{0.6}$	$17.7_{0.7}$	67
Qwen3-8B	8B	$18.2_{0.3}$	$45.3_{0.7}$	$21.7_{0.6}$	$8.4_{0.8}$	$0.6_{0.3}$	$12.2_{1.8}$	$26.7_{0.2}$	$29.7_{0.7}$	50
Qwen3-14B	14B	$24.4_{0.1}$	$53.3_{0.7}$	$35.6_{0.7}$	$11.7_{1.9}$	$0.1_{0.2}$	$18.2_{0.3}$	$32.8_{0.3}$	$37.3_{0.7}$	15
Qwen3-32B	32B	$22.3_{2.7}$	$46.3_{0.7}$	$35.8_{2.2}$	$6.1_{2.3}$	$0.0_{0.0}$	$13.0_{8.0}$	$33.8_{3.9}$	$32.8_{2.4}$	63
					w/ reasoning					
Qwen3-0.6B	0.6B	$21.7_{0.5}$	$20.7_{3.3}$	$40.5_{1.2}$	$6.4_{0.4}$	$18.1_{3.6}$	$3.3_{0.7}$	$32.1_{0.8}$	$16.1_{1.5}$	1361
Qwen3-1.7B	1.7B	$46.5_{0.7}$	$44.7_{2.3}$	$61.0_{1.0}$	$16.4_{2.8}$	$54.9_{0.8}$	$21.8_{1.7}$	$66.2_{1.8}$	$37.6_{1.6}$	1404
Qwen3-4B	4B	$64.5_{1.1}$	$84.7_{2.3}$	$69.6_{2.7}$	$49.1_{1.3}$	$82.6_{1.4}$	$35.0_{1.5}$	$77.9_{0.4}$	$44.0_{1.6}$	1258
Qwen3-8B	8B	$72.8_{0.9}$	$83.7_{2.3}$	$75.6_{1.5}$	$58.5_{1.9}$	$84.3_{1.7}$	$40.7_{2.3}$	$84.2_{0.7}$	$72.7_{1.3}$	1377
Qwen3-14B	14B	$80.4_{1.3}$	$95.7_{1.3}$	$86.0_{1.7}$	$78.3_{4.1}$	$90.0_{1.4}$	$35.8_{1.2}$	$84.9_{0.8}$	$84.3_{0.9}$	1084
Qwen3-32B	32B	$81.6_{0.4}$	$95.3_{0.7}$	$86.3_{1.1}$	$83.9_{2.9}$	$92.8_{0.3}$	$37.5_{0.5}$	$82.5_{0.6}$	$85.9_{1.3}$	1005
DS-r1-distill-Qwen	32B	$68.0_{1.2}$	$89.0_{1.0}$	$71.6_{0.4}$	$71.6_{2.0}$	$68.4_{12.7}$	$32.5_{2.5}$	$80.6_{1.7}$	$61.4_{1.8}$	883
DeepSeek-r1-0528	37/671B	$63.3_{0.0}$	$94.0_{0.0}$	$71.4_{0.0}$	$10.0_{0.0}$	$80.0_{0.0}$	$22.0_{0.0}$	$88.6_{0.0}$	$67.2_{0.0}$	2431
GPT-5-mini (low)	Unk.	$87.2_{0.0}$	$96.5_{0.5}$	$82.1_{0.7}$	$99.0_{0.6}$	$97.3_{0.1}$	$49.2_{0.2}$	$93.1_{0.3}$	$86.4_{0.0}$	286
GPT-5-mini (high)	Unk.	$88.2_{0.0}$	$97.0_{0.0}$	$84.3_{0.0}$	$99.8_{0.2}$	$98.4_{0.1}$	$49.8_{0.2}$	$92.4_{0.4}$	$89.4_{0.2}$	1028

Table 25: Details on **Task (2) Temporal Reasoning** performance on **ToT-Arithmetic** dataset.

B.3 Task (3) Discourse Relation Recognition

Tables tables 26 to 30.

	Model	Ces	Deu	Eng	Eus	Fas	Fra	Ita	Nld	Pcm	Pol	Por	Rus	Spa	Tha	Tur	Zho
BeDiscovER	Qwen3-1.7B	9.3	10.7	22.1	16.3	18.7	25.0	19.5	16.7	14.6	25	23.5	22.5	19.4	38.7	18.3	18.0
	Qwen3-14B	25.5	25.0	36.1	30.4	29.9	41.8	30.8	30.4	26.0	41.4	38.3	38.1	36.0	55.8	34.6	32.0
	Qwen3-32B	28.4	26.5	37.5	30.7	32.7	43.6	32.7	33.0	24.2	40.3	41.7	40.7	37.0	53.7	34.1	33.3
	DS-r1-distill-Qwen	26.0	24.8	32.9	28.1	26.9	37.7	25.3	31.8	22.4	38.7	36.6	27.2	36.1	38.4	27.6	27.8
	DeepSeek-r1-0528	39.8	38.1	42.1	38.4	31.7	43.5	40.4	36.9	28.0	51.3	47.6	38.4	48.1	61.1	42.2	42.1
	GPT-5-mini (low)	38.2	39.2	43.7	40.9	29.9	40.5	36.0	35.1	31.5	47.3	48.0	40.6	43.9	59.1	42.8	39.4
	GPT-5-mini (high)	43.2	44.3	47.1	42.5	33.0	44.3	40.8	38.4	36.9	56.7	51.4	45.1	50.0	64.9	45.6	45.8
Supervised	DeDisCo (Qwen3-4B)	56.1	65.5	78.4	50.1	59.3	60.1	72.0	67.4	59.9	72.0	75.9	73.9	72.3	97.1	64.0	78.6
	HITS	53.4	61.4	74.7	54.0	59.8	57.0	68.5	64.9	60.4	72.0	73.1	72.6	67.8	95.7	63.0	72.7
	DisCreT (RoBERTa)	48.0	57.3	70.6	54.4	57.6	58.0	66.7	59.7	57.7	60.0	74.8	66.7	63.2	97.0	63.5	67.8
	CLAC (BERT)	48.0	53.7	70.8	50.9	55.4	53.8	60.3	56.3	56.3	54.8	72.6	66.4	60.3	97.0	60.9	68.1
	SeCoRel	43.9	49.8	67.5	52.6	52.2	55.2	60.0	54.2	56.1	52.8	70.2	62.5	58.8	96.3	56.6	62.2

Table 26: Detals on **Task (3) Discourse Relation Recognition**, [language-split] scores on 16 languages in DISRPT shared task: BeDiscovER (top), supervised systems (bottom). Language abbreviations (left to right): Czech, German, English, Basque, Persian, French, Italian, Dutch, Nigerian Pidgin, Polish, Portuguese, Russian, Spanish, Thai, Turkish, and Chinese.

		ces.rst.crdt				deu.pdtb.pcc				deu.rst.pcc			
Model	Size	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$5.1_{2.3}$	3	$3.2_{1.1}$	2505	$8.4_{5.1}$	2	$9.1_{0.8}$	1979	$5.5_{2.2}$	2	$6.7_{1.2}$	1515
Qwen3-1.7B	1.7B	$13.1_{1.8}$	1107	$9.3_{1.8}$	2706	$13.4_{0.5}$	1504	$10.3_{2.1}$	2280	$13.9_{1.1}$	904	$11.1_{0.3}$	1833
Qwen3-4B	4B	$16.9_{0.7}$	3	$11.5_{2.0}$	2543	$21.5_{0.7}$	2	$12.5_{3.0}$	2120	$14.3_{0.7}$	3	$15.8_{0.7}$	1653
Qwen3-8B	8B	$22.7_{0.3}$	3	$11.3_{0.9}$	1544	$20.6_{0.5}$	5	$16.7_{2.4}$	1547	$12.9_{0.7}$	3	$17.7_{4.6}$	1245
Qwen3-14B	14B	$28.4_{0.7}$	3	$25.5_{1.5}$	1199	$28.0_{0.4}$	3	$23.0_{1.7}$	1121	$23.3_{0.5}$	3	$26.4_{1.4}$	950
Qwen3-32B	32B	$34.5_{0.6}$	2	$28.4_{1.3}$	689	$25.6_{1.2}$	2	$24.2_{3.6}$	660	$23.2_{1.7}$	2	$28.3_{1.0}$	602
DS-r1-distill-Qwen	32B	-	-	$26.0_{0.3}$	446	-	-	$24.2_{1.0}$	534	-	-	$25.3_{0.7}$	498
DeepSeek-r1-0528	37/671B	-	-	$39.9_{0.0}$	1108	-	-	$35.1_{0.0}$	694	-	-	$40.3_{0.0}$	711
GPT-5-mini (low)	Unk.	-	-	$38.2_{0.3}$	134	-	-	$37.1_{1.0}$	135	-	-	$40.7_{0.0}$	134
GPT-5-mini (high)	Unk.	-	-	$43.2_{0.0}$	954	-	-	$41.2_{0.0}$	1010	-	-	$46.5_{0.0}$	902
DeDisCO	-	56.08				67.53				64.10			
HITS	-	53.38				63.92				59.71			
DiscReT	-	47.97				63.92				52.75			

		eng.dep.covdtb				eng.dep.scidtb				eng.erst.gentle			
Model	Size	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$5.7_{1.2}$	4	$19.0_{0.3}$	516	$3.9_{1.1}$	3	$15.2_{0.8}$	553	$8.6_{3.3}$	3	$11.7_{0.4}$	551
Qwen3-1.7B	1.7B	$11.2_{4.1}$	160	$30.8_{0.6}$	1045	$6.1_{1.4}$	188	$28.6_{0.6}$	1023	$6.8_{0.1}$	155	$16.9_{0.2}$	1178
Qwen3-4B	4B	$34.2_{1.1}$	4	$34.9_{0.4}$	884	$27.3_{0.3}$	2	$33.2_{0.8}$	874	$14.0_{0.3}$	3	$19.5_{0.8}$	896
Qwen3-8B	8B	$29.9_{1.7}$	2	$36.6_{1.6}$	1298	$23.9_{1.4}$	3	$38.8_{2.1}$	1256	$13.8_{0.8}$	2	$20.9_{0.9}$	1219
Qwen3-14B	14B	$46.9_{1.1}$	2	$47.7_{0.4}$	804	$44.5_{0.8}$	2	$45.0_{0.3}$	829	$23.1_{0.3}$	3	$27.9_{0.9}$	756
Qwen3-32B	32B	$47.0_{1.4}$	2	$48.8_{0.7}$	480	$43.6_{0.8}$	2	$47.2_{0.2}$	454	$25.9_{0.4}$	2	$30.0_{0.6}$	484
DS-r1-distill-Qwen	32B	-	-	$40.9_{1.0}$	396	-	-	$38.0_{1.3}$	415	-	-	$24.1_{2.5}$	382
DeepSeek-r1-0528	37/671B	-	-	$50.4_{0.0}$	823	-	-	$48.2_{0.0}$	799	-	-	$25.5_{0.0}$	660
GPT-5-mini (low)	Unk.	-	-	$56.8_{2.1}$	107	-	-	$53.4_{1.0}$	99	-	-	$20.8_{0.4}$	103
GPT-5-mini (high)	Unk.	-	-	$58.5_{0.0}$	698	-	-	$55.5_{0.0}$	592	-	-	$25.1_{0.0}$	688
DeDisCO	-	71.46				84.29				68.30			
HITS	-	71.31				81.78				62.42			
DiscReT	-	69.22				78.22				53.53			

		eng.erst.gum				eng.pdtb.gentle				eng.pdtb.gum			
Model	Size	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$6.9_{1.4}$	3	$15.4_{0.4}$	484	$13.8_{3.0}$	2	$14.7_{0.4}$	785	$12.2_{3.5}$	3	$18.1_{0.7}$	564
Qwen3-1.7B	1.7B	$10.9_{1.1}$	119	$23.7_{0.3}$	1096	$12.4_{1.3}$	355	$23.2_{1.5}$	1347	$13.8_{2.6}$	199	$26.0_{0.3}$	1139
Qwen3-4B	4B	$20.9_{0.5}$	3	$28.8_{0.0}$	880	$16.5_{0.2}$	2	$29.6_{0.9}$	1176	$18.9_{0.2}$	3	$31.8_{0.4}$	1020
Qwen3-8B	8B	$19.0_{0.5}$	2	$29.9_{1.3}$	1331	$22.1_{0.0}$	3	$29.7_{1.0}$	1458	$23.3_{0.5}$	3	$34.8_{1.0}$	1454
Qwen3-14B	14B	$30.3_{0.3}$	2	$39.1_{0.8}$	743	$31.3_{0.3}$	2	$38.2_{0.7}$	919	$32.3_{0.4}$	3	$42.7_{0.4}$	826
Qwen3-32B	32B	$32.9_{0.5}$	2	$41.1_{0.1}$	483	$26.2_{0.8}$	2	$37.9_{0.1}$	569	$33.2_{1.5}$	2	$44.2_{0.3}$	548
DS-r1-distill-Qwen	32B	-	-	$37.8_{0.6}$	410	-	-	$29.1_{1.5}$	377	-	-	$28.9_{1.0}$	368
DeepSeek-r1-0528	37/671B	-	-	$51.6_{0.0}$	774	-	-	$45.1_{0.0}$	758	-	-	$46.6_{0.0}$	799
GPT-5-mini (low)	Unk.	-	-	$51.6_{2.0}$	92	-	-	$40.2_{0.6}$	108	-	-	$44.6_{2.0}$	103
GPT-5-mini (high)	Unk.	-	-	$50.8_{0.0}$	646	-	-	$47.7_{0.0}$	780	-	-	$47.4_{0.0}$	737
DeDisCO	-	76.50				67.30				73.48			
HITS	-	67.32				64.89				67.88			
DiscReT	-	64.21				64.25				69.31			

		eng.pdtb.pdtb				eng.pdtb.tedm				eng.rst.oll			
Model	Size	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$16.3_{3.2}$	3	$22.6_{0.6}$	459	$15.4_{3.0}$	2	$15.8_{1.3}$	1223	$6.3_{0.6}$	2	$12.4_{1.9}$	1530
Qwen3-1.7B	1.7B	$21.2_{2.7}$	107	$27.6_{0.2}$	1048	$17.9_{2.0}$	724	$20.1_{0.1}$	1600	$12.2_{1.1}$	952	$16.6_{0.4}$	1845
Qwen3-4B	4B	$23.3_{0.4}$	6	$35.8_{0.7}$	854	$24.5_{0.0}$	7	$23.7_{1.7}$	1487	$25.0_{0.5}$	3	$20.0_{0.3}$	1649
Qwen3-8B	8B	$29.6_{0.2}$	2	$38.7_{1.2}$	1212	$23.6_{0.6}$	3	$33.1_{3.1}$	1509	$24.4_{1.4}$	4	$23.1_{2.4}$	1296
Qwen3-14B	14B	$34.7_{0.6}$	2	$43.1_{0.4}$	715	$30.3_{1.0}$	2	$37.2_{0.7}$	932	$28.9_{0.3}$	3	$30.6_{1.5}$	961
Qwen3-32B	32B	$32.3_{0.6}$	2	$43.2_{0.1}$	520	$29.2_{0.7}$	2	$38.0_{2.7}$	601	$26.3_{1.0}$	2	$31.5_{0.6}$	609
DS-r1-distill-Qwen	32B	-	-	$39.0_{1.6}$	391	-	-	$34.7_{0.4}$	361	-	-	$32.3_{0.6}$	350
DeepSeek-r1-0528	37/671B	-	-	$56.1_{0.0}$	723	-	-	$40.8_{0.0}$	745	-	-	$38.7_{0.0}$	796
GPT-5-mini (low)	Unk.	-	-	$57.0_{0.5}$	98	-	-	$38.4_{0.0}$	108	-	-	$38.9_{1.3}$	110
GPT-5-mini (high)	Unk.	-	-	$63.6_{0.0}$	682	-	-	$40.0_{0.0}$	849	-	-	$41.7_{0.0}$	839
DeDisCO	-	83.54				68.95				62.73			
HITS	-	79.95				64.96				58.30			
DiscReT	-	75.06				61.54				47.23			

Table 27: Detals on **Task (3) Discourse Relation Recognition**, [language-framework-dataset-separate] scores on 38 separate datasets in DISRPT shared task (1/4).

Model	Size	eng.rst.rstdt				eng.rst.sts				eng.rst.umuc			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$3.9_{0.9}$	2	$15.8_{0.5}$	563	$7.9_{0.9}$	2	$13.2_{0.8}$	1290	$3.7_{1.6}$	2	$16.5_{1.1}$	988
Qwen3-1.7B	1.7B	$9.9_{1.4}$	186	$26.3_{0.7}$	1190	$13.7_{0.9}$	875	$16.6_{2.3}$	1692	$12.2_{2.1}$	450	$22.8_{1.4}$	1472
Qwen3-4B	4B	$31.0_{0.6}$	2	$33.7_{0.3}$	921	$26.3_{1.1}$	11	$21.7_{1.5}$	1475	$18.6_{0.2}$	5	$27.1_{0.8}$	1281
Qwen3-8B	8B	$25.6_{0.6}$	2	$36.1_{2.0}$	1312	$28.3_{1.0}$	3	$21.7_{1.2}$	1306	$18.5_{0.5}$	3	$34.0_{3.8}$	1291
Qwen3-14B	14B	$38.8_{0.6}$	3	$43.1_{0.6}$	814	$36.0_{0.9}$	3	$30.4_{1.6}$	924	$30.0_{0.8}$	3	$41.9_{1.5}$	878
Qwen3-32B	32B	$39.9_{1.1}$	2	$44.5_{1.1}$	556	$33.3_{1.2}$	2	$29.2_{1.0}$	614	$36.0_{0.4}$	2	$42.9_{0.3}$	593
DS-r1-distill-Qwen	32B	-	-	$48.8_{0.5}$	389	-	-	$32.8_{0.4}$	399	-	-	$37.6_{0.4}$	424
DeepSeek-r1-0528	37/671B	-	-	$63.7_{0.0}$	768	-	-	$36.3_{0.0}$	772	-	-	$49.6_{0.0}$	738
GPT-5-mini (low)	Unk.	-	-	$64.0_{2.1}$	102	-	-	$36.6_{0.0}$	114	-	-	$50.4_{0.4}$	115
GPT-5-mini (high)	Unk.	-	-	$69.3_{0.0}$	680	-	-	$37.0_{0.0}$	883	-	-	$56.6_{0.0}$	769
DeDisCO	-	73.09				54.27				65.91			
HITS	-	64.92				54.27				63.84			
DiscReT	-	60.93				42.68				59.09			

Model	Size	eng.sdrt.msdc				eng.sdrt.stac				eus.rst.ert			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$3.0_{0.4}$	2	$9.5_{0.2}$	514	$4.5_{0.5}$	2	$11.0_{0.6}$	651	$4.0_{0.8}$	3	$9.5_{0.5}$	1031
Qwen3-1.7B	1.7B	$3.8_{0.6}$	127	$17.1_{0.2}$	1149	$5.7_{0.2}$	19	$16.0_{0.8}$	1330	$5.8_{1.0}$	515	$16.3_{1.6}$	1451
Qwen3-4B	4B	$14.2_{0.3}$	3	$17.4_{0.2}$	808	$7.2_{0.2}$	2	$15.4_{0.4}$	1059	$23.4_{0.3}$	3	$17.4_{2.2}$	1234
Qwen3-8B	8B	$17.0_{0.6}$	3	$24.9_{0.3}$	880	$10.9_{0.8}$	2	$18.3_{0.4}$	1031	$19.9_{0.9}$	3	$20.1_{3.2}$	1307
Qwen3-14B	14B	$16.5_{0.3}$	2	$21.0_{0.6}$	670	$13.8_{0.7}$	2	$20.6_{0.6}$	873	$30.9_{0.2}$	3	$30.4_{1.4}$	813
Qwen3-32B	32B	$14.9_{0.4}$	2	$23.8_{0.4}$	488	$16.9_{1.4}$	2	$27.0_{1.1}$	548	$30.6_{0.5}$	2	$30.7_{0.4}$	534
DS-r1-distill-Qwen	32B	-	-	$19.2_{1.2}$	370	-	-	$21.3_{2.7}$	434	-	-	$28.1_{0.4}$	494
DeepSeek-r1-0528	37/671B	-	-	$17.1_{0.0}$	765	-	-	$25.8_{0.0}$	913	-	-	$38.4_{0.0}$	1006
GPT-5-mini (low)	Unk.	-	-	$25.4_{0.0}$	95	-	-	$41.3_{1.3}$	120	-	-	$40.9_{1.2}$	126
GPT-5-mini (high)	Unk.	-	-	$27.1_{0.0}$	673	-	-	$47.6_{0.0}$	826	-	-	$42.6_{0.0}$	838
DeDisCO	-	90.00				77.04				50.10			
HITS	-	89.60				75.89				54.02			
DiscReT	-	85.64				69.50				54.43			

Model	Size	fas.rst.prstc				fra.sdrt.annodis				ita.pdtb.luna			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$1.9_{1.0}$	2	$7.8_{0.6}$	932	$5.6_{2.8}$	2	$14.0_{0.3}$	852	$10.3_{0.6}$	2	$11.4_{0.7}$	1176
Qwen3-1.7B	1.7B	$5.9_{0.5}$	301	$18.7_{0.2}$	1283	$10.3_{2.1}$	356	$25.0_{0.9}$	1158	$12.4_{1.2}$	132	$19.5_{1.0}$	1530
Qwen3-4B	4B	$19.3_{0.0}$	3	$22.7_{1.1}$	1052	$21.9_{0.0}$	5	$31.5_{0.7}$	928	$16.7_{0.4}$	10	$26.2_{0.5}$	1356
Qwen3-8B	8B	$16.4_{1.2}$	2	$27.1_{3.3}$	1317	$26.3_{0.4}$	3	$38.8_{1.1}$	737	$22.8_{0.4}$	3	$30.0_{0.9}$	1329
Qwen3-14B	14B	$28.0_{1.2}$	2	$29.9_{2.7}$	865	$35.7_{1.0}$	3	$41.8_{0.4}$	617	$25.9_{0.5}$	3	$30.8_{1.7}$	856
Qwen3-32B	32B	$30.5_{0.6}$	2	$32.7_{0.4}$	548	$39.4_{0.5}$	2	$43.6_{0.7}$	440	$20.6_{2.1}$	2	$32.7_{2.0}$	494
DS-r1-distill-Qwen	32B	-	-	$26.9_{2.3}$	436	-	-	$37.7_{0.6}$	387	-	-	$25.3_{2.2}$	390
DeepSeek-r1-0528	37/671B	-	-	$31.8_{0.0}$	646	-	-	$43.5_{0.0}$	1032	-	-	$40.4_{0.0}$	1108
GPT-5-mini (low)	Unk.	-	-	$29.9_{1.5}$	145	-	-	$40.5_{1.0}$	97	-	-	$36.0_{0.4}$	131
GPT-5-mini (high)	Unk.	-	-	$33.1_{0.0}$	1106	-	-	$44.4_{0.0}$	644	-	-	$40.9_{0.0}$	912
DeDisCO	-	59.29				60.06				72.00			
HITS	-	59.80				57.00				68.53			
DiscReT	-	57.60				57.97				66.67			

Model	Size	nld.rst.nldt				pcm.pdtb.disconaija				pol.iso.pdc			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$4.6_{2.5}$	2	$11.1_{1.6}$	1297	$10.4_{1.2}$	2	$11.3_{0.3}$	702	$8.2_{2.8}$	2	$12.3_{0.8}$	836
Qwen3-1.7B	1.7B	$9.4_{0.8}$	635	$16.7_{0.8}$	1645	$12.1_{0.6}$	130	$14.6_{1.0}$	1447	$11.9_{2.9}$	410	$25.0_{1.5}$	1240
Qwen3-4B	4B	$20.9_{1.3}$	8	$18.8_{1.2}$	1477	$16.7_{0.9}$	4	$20.8_{1.6}$	1155	$26.8_{0.3}$	4	$30.8_{1.4}$	1060
Qwen3-8B	8B	$21.7_{1.7}$	4	$23.3_{0.7}$	1235	$17.6_{0.1}$	2	$18.8_{0.7}$	1484	$26.2_{0.2}$	3	$34.5_{2.4}$	1340
Qwen3-14B	14B	$33.8_{1.3}$	3	$30.4_{0.4}$	903	$22.0_{0.3}$	2	$26.0_{0.3}$	921	$32.3_{1.1}$	3	$41.4_{1.0}$	800
Qwen3-32B	32B	$34.2_{1.5}$	2	$33.0_{0.8}$	578	$17.6_{0.4}$	2	$24.2_{0.7}$	570	$31.9_{1.6}$	2	$40.3_{1.4}$	526
DS-r1-distill-Qwen	32B	-	-	$34.5_{2.4}$	491	-	-	$29.1_{0.8}$	415	-	-	$45.6_{3.3}$	468
DeepSeek-r1-0528	37/671B	-	-	$49.8_{0.0}$	1053	-	-	$39.8_{0.0}$	1117	-	-	$52.9_{0.0}$	1072
GPT-5-mini (low)	Unk.	-	-	$47.4_{2.0}$	121	-	-	$39.4_{0.4}$	124	-	-	$56.8_{0.2}$	107
GPT-5-mini (high)	Unk.	-	-	$50.6_{0.0}$	899	-	-	$44.1_{0.0}$	896	-	-	$59.2_{0.0}$	758
DeDisCO	-	67.38				59.88				72.01			
HITS	-	64.92				60.37				72.01			
DiscReT	-	59.69				57.72				60.03			

Table 28: Detals on **Task (3) Discourse Relation Recognition**, [language-framework-dataset-separate] scores on 38 separate datasets in DISRPT shared task (2/4).

Model	Size	por.pdtb.crpc				por.pdtb.tedm				por.rst.cstn			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$12.2_{5.3}$	3	$17.5_{0.6}$	652	$13.6_{4.2}$	2	$14.3_{1.9}$	1207	$6.0_{3.3}$	3	$10.3_{1.2}$	1476
Qwen3-1.7B	1.7B	$14.7_{2.9}$	247	$25.6_{0.6}$	1098	$17.3_{1.1}$	873	$23.5_{1.2}$	1530	$10.3_{0.4}$	618	$21.7_{1.8}$	1828
Qwen3-4B	4B	$23.7_{0.5}$	3	$26.4_{1.0}$	963	$25.7_{0.4}$	3	$24.5_{0.5}$	1377	$31.5_{0.9}$	18	$27.6_{2.2}$	1652
Qwen3-8B	8B	$28.5_{1.1}$	3	$31.6_{0.9}$	1353	$27.0_{2.4}$	3	$29.5_{1.3}$	1388	$30.4_{2.0}$	3	$34.9_{1.1}$	1322
Qwen3-14B	14B	$39.5_{0.9}$	3	$39.7_{0.3}$	794	$32.5_{0.2}$	3	$35.6_{2.0}$	873	$46.0_{0.3}$	3	$39.6_{3.0}$	971
Qwen3-32B	32B	$39.9_{1.6}$	2	$41.1_{0.6}$	545	$33.7_{1.5}$	2	$38.8_{1.9}$	569	$47.1_{0.3}$	2	$45.0_{1.0}$	624
DS-r1-distill-Qwen	32B	-	-	$34.5_{2.4}$	491	-	-	$29.1_{0.8}$	415	-	-	$45.6_{3.3}$	468
DeepSeek-r1-0528	37/671B	-	-	$49.8_{0.0}$	1053	-	-	$39.8_{0.0}$	1117	-	-	$52.9_{0.0}$	1072
GPT-5-mini (low)	Unk.	-	-	$47.4_{2.0}$	121	-	-	$39.4_{0.4}$	124	-	-	$56.8_{0.2}$	107
GPT-5-mini (high)	Unk.	-	-	$50.6_{0.0}$	899	-	-	$44.1_{0.0}$	896	-	-	$59.2_{0.0}$	758
DeDisCO	-			78.61				70.33				71.32	
HITS	-			76.12				65.11				70.22	
DiscReT	-			79.09				65.66				68.01	

Model	Size	rus.rst.rrt				spa.rst.rststb				spa.rst.sctb			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$5.9_{1.8}$	2	$13.3_{0.5}$	512	$7.6_{3.4}$	4	$12.2_{0.8}$	1063	$9.4_{4.1}$	2	$9.3_{1.0}$	2280
Qwen3-1.7B	1.7B	$9.4_{1.9}$	142	$22.5_{0.4}$	1070	$11.6_{0.8}$	681	$20.9_{1.2}$	1368	$3.4_{1.0}$	1081	$17.4_{2.1}$	2562
Qwen3-4B	4B	$22.8_{0.2}$	3	$29.8_{0.8}$	856	$23.0_{0.9}$	6	$23.2_{1.9}$	1262	$29.8_{1.6}$	3	$17.6_{1.9}$	2450
Qwen3-8B	8B	$19.7_{0.4}$	2	$31.6_{1.8}$	1283	$21.0_{1.1}$	5	$27.3_{0.6}$	1247	$35.6_{0.9}$	4	$19.5_{3.1}$	1547
Qwen3-14B	14B	$28.3_{0.3}$	3	$38.1_{0.7}$	783	$28.6_{0.5}$	3	$33.6_{0.9}$	886	$50.3_{0.6}$	5	$39.2_{1.1}$	1151
Qwen3-32B	32B	$35.4_{0.4}$	2	$40.7_{0.4}$	531	$29.8_{1.0}$	2	$32.5_{0.6}$	577	$46.5_{1.3}$	3	$43.2_{6.5}$	671
DS-r1-distill-Qwen	32B	-	-	$27.2_{0.5}$	364	-	-	$31.0_{1.4}$	478	-	-	$43.1_{2.8}$	468
DeepSeek-r1-0528	37/671B	-	-	$38.4_{0.0}$	1008	-	-	$39.0_{0.0}$	1195	-	-	$60.4_{0.0}$	1151
GPT-5-mini (low)	Unk.	-	-	$40.6_{1.4}$	135	-	-	$36.2_{0.5}$	112	-	-	$54.4_{0.9}$	107
GPT-5-mini (high)	Unk.	-	-	$45.2_{0.0}$	989	-	-	$43.2_{0.0}$	833	-	-	$59.1_{0.0}$	792
DeDisCO	-			73.93				69.25				80.50	
HITS	-			72.58				65.49				74.21	
DiscReT	-			66.68				61.50				67.92	

Model	Size	tha.pdtb.tdtb				tur.pdtb.tdb				tur.pdtb.tedm			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$9.1_{3.0}$	2	$21.2_{1.1}$	617	$6.4_{4.4}$	2	$12.4_{0.9}$	1118	$8.7_{4.1}$	3	$10.9_{0.8}$	1252
Qwen3-1.7B	1.7B	$21.4_{3.2}$	248	$38.7_{1.0}$	939	$12.0_{1.3}$	521	$17.7_{0.4}$	1501	$13.6_{3.2}$	692	$18.8_{0.8}$	1544
Qwen3-4B	4B	$28.8_{0.5}$	2	$43.2_{1.2}$	685	$19.0_{1.0}$	3	$25.2_{1.2}$	1361	$22.0_{0.6}$	3	$22.2_{1.2}$	1394
Qwen3-8B	8B	$38.7_{0.9}$	2	$53.2_{1.5}$	650	$18.0_{1.0}$	3	$26.3_{2.7}$	1385	$22.8_{0.6}$	4	$25.9_{0.3}$	1315
Qwen3-14B	14B	$43.3_{1.2}$	2	$55.8_{1.7}$	552	$27.8_{0.2}$	3	$36.9_{2.1}$	875	$27.5_{0.3}$	3	$32.7_{0.4}$	869
Qwen3-32B	32B	$42.8_{1.7}$	2	$53.7_{0.1}$	452	$29.3_{0.9}$	2	$35.2_{0.9}$	591	$26.9_{0.9}$	2	$33.3_{0.3}$	563
DS-r1-distill-Qwen	32B	-	-	$38.4_{0.7}$	342	-	-	$28.6_{1.0}$	405	-	-	$26.8_{1.2}$	394
DeepSeek-r1-0528	37/671B	-	-	$61.2_{0.0}$	641	-	-	$45.2_{0.0}$	1116	-	-	$39.8_{0.0}$	1031
GPT-5-mini (low)	Unk.	-	-	$59.1_{0.9}$	93	-	-	$50.2_{1.2}$	133	-	-	$36.8_{0.2}$	132
GPT-5-mini (high)	Unk.	-	-	$64.9_{0.0}$	659	-	-	$49.5_{0.0}$	875	-	-	$42.5_{0.0}$	1036
DeDisCO	-			97.10				68.65				58.68	
HITS	-			95.68				66.03				59.50	
DiscReT	-			97.02				65.80				60.88	

Model	Size	zho.dep.scidtb				zho.pdtb.cdtb				zho.pdtb.ted			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$3.9_{2.8}$	3	$6.9_{1.5}$	1738	$6.9_{5.0}$	4	$12.8_{1.0}$	807	$11.2_{1.6}$	2	$13.0_{0.4}$	583
Qwen3-1.7B	1.7B	$5.7_{1.3}$	416	$10.9_{0.3}$	1995	$8.2_{1.8}$	355	$23.9_{0.4}$	1223	$17.1_{0.5}$	250	$20.8_{0.1}$	1026
Qwen3-4B	4B	$26.8_{0.6}$	9	$16.7_{1.0}$	1954	$19.5_{0.4}$	2	$25.3_{0.4}$	1119	$23.3_{0.0}$	2	$25.9_{0.8}$	913
Qwen3-8B	8B	$24.7_{0.9}$	4	$17.2_{0.5}$	1383	$26.2_{0.4}$	3	$29.0_{1.2}$	1388	$25.2_{0.2}$	2	$27.0_{1.5}$	1297
Qwen3-14B	14B	$34.7_{1.1}$	3	$27.6_{1.2}$	1021	$27.3_{0.1}$	2	$35.1_{0.7}$	920	$27.4_{0.4}$	2	$32.8_{0.9}$	800
Qwen3-32B	32B	$31.2_{2.3}$	2	$29.0_{0.8}$	530	$31.3_{0.6}$	2	$34.9_{1.0}$	582	$27.7_{0.6}$	2	$33.6_{0.2}$	503
DS-r1-distill-Qwen	32B	-	-	$24.2_{0.9}$	288	-	-	$28.9_{0.7}$	314	-	-	$27.4_{0.8}$	291
DeepSeek-r1-0528	37/671B	-	-	$38.1_{0.0}$	1156	-	-	$37.9_{0.0}$	968	-	-	$45.9_{0.0}$	922
GPT-5-mini (low)	Unk.	-	-	$35.1_{0.7}$	127	-	-	$39.6_{0.9}$	113	-	-	$45.1_{0.4}$	108
GPT-5-mini (high)	Unk.	-	-	$44.2_{0.0}$	970	-	-	$42.7_{0.0}$	920	-	-	$52.6_{0.0}$	742
DeDisCO	-			75.35				89.97				75.64	
HITS	-			70.23				81.79				70.75	
DiscReT	-			69.77				77.57				67.74	

Table 29: Detals on **Task (3) Discourse Relation Recognition**, [language-framework-dataset-separate] scores on 38 separate datasets in DISRPT shared task (3/4).

Model	Size	zho.rst.gcdt				zho.rst.sctb			
		w/o r	tok.	w/ r	tok.	w/o r	tok.	w/ r	tok.
Qwen3-0.6B	0.6B	$6.3_{2.2}$	4	$14.9_{0.8}$	703	$4.3_{3.0}$	3	$6.2_{1.1}$	2321
Qwen3-1.7B	1.7B	$11.8_{0.9}$	188	$18.9_{0.2}$	1113	$4.6_{3.6}$	1310	$13.6_{1.5}$	2498
Qwen3-4B	4B	$19.3_{0.2}$	4	$24.2_{1.7}$	946	$33.5_{0.5}$	3	$15.7_{1.9}$	2348
Qwen3-8B	8B	$20.7_{0.3}$	3	$26.4_{1.9}$	1204	$32.7_{1.9}$	4	$17.4_{0.8}$	1521
Qwen3-14B	14B	$27.2_{0.4}$	3	$31.1_{0.3}$	785	$43.0_{0.4}$	4	$33.3_{2.5}$	1039
Qwen3-32B	32B	$31.4_{0.4}$	2	$33.2_{0.6}$	499	$43.4_{1.3}$	2	$37.1_{1.3}$	556
DS-r1-distill-Qwen	32B	-	-	$25.0_{0.8}$	278	-	-	$35.2_{0.6}$	293
DeepSeek-r1-0528	37/671B	-	-	$36.8_{0.0}$	1120	-	-	$54.1_{0.0}$	1036
GPT-5-mini (low)	Unk.	-	-	$31.8_{0.3}$	124	-	-	$44.7_{0.6}$	115
GPT-5-mini (high)	Unk.	-	-	$38.4_{0.0}$	944	-	-	$50.3_{0.0}$	882
DeDisCO	-	75.35				75.47			
HITS	-	71.46				57.86			
DiscReT	-	61.91				55.35			

Table 30: Detals on **Task (3) Discourse Relation Recognition**, [language-framework-dataset-separate] scores on 38 separate datasets in DISRPT shared task (4/4).

B.4   Task (4) Sentence Ordering

Tables tables 31 to 37

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$21.7_{0.3}$	$32.4_{4.7}$	$5.4_{0.9}$	$50.0_{1.9}$	$55.3_{0.5}$	24	$22.3_{0.3}$	$8.4_{0.0}$	$6.3_{0.8}$	$53.0_{0.4}$	$56.3_{0.1}$	559
Qwen3-1.7B	1.7B	$31.2_{0.2}$	$13.4_{0.6}$	$13.6_{0.2}$	$65.2_{0.3}$	$64.3_{0.1}$	25	$38.0_{0.2}$	$8.9_{0.7}$	$21.1_{0.4}$	$71.5_{0.6}$	$68.6_{0.5}$	720
Qwen3-4B	4B	$54.3_{0.1}$	$1.1_{0.0}$	$35.7_{0.2}$	$84.8_{0.0}$	$78.3_{0.1}$	25	$58.7_{0.3}$	$2.1_{0.5}$	$41.0_{0.4}$	$87.0_{0.0}$	$81.0_{0.1}$	449
Qwen3-8B	8B	$60.6_{0.1}$	$0.3_{0.1}$	$42.1_{0.1}$	$88.1_{0.1}$	$82.0_{0.1}$	25	$64.5_{0.2}$	$1.0_{0.1}$	$48.7_{0.4}$	$89.5_{0.1}$	$84.0_{0.2}$	413
Qwen3-14B	14B	$69.8_{0.0}$	$0.9_{0.1}$	$54.6_{0.1}$	$91.5_{0.0}$	$87.1_{0.0}$	25	$70.6_{0.4}$	$0.7_{0.0}$	$55.5_{0.7}$	$91.7_{0.1}$	$87.2_{0.2}$	451
Qwen3-32B	32B	$74.6_{0.1}$	$1.4_{0.1}$	$60.4_{0.1}$	$92.9_{0.1}$	$89.3_{0.1}$	25	$74.0_{0.3}$	$1.5_{0.1}$	$59.6_{0.4}$	$92.8_{0.1}$	$88.8_{0.2}$	445
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$67.7_{0.3}$	$2.6_{0.9}$	$51.4_{0.7}$	$90.3_{0.5}$	$85.8_{0.5}$	517
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$75.5_{0.0}$	$0.0_{0.0}$	$64.8_{0.0}$	$91.1_{0.0}$	$85.3_{0.0}$	1319
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$75.4_{0.0}$	$0.1_{0.1}$	$61.1_{0.6}$	$93.6_{0.1}$	$89.4_{0.1}$	144
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$78.7_{0.0}$	$0.1_{0.0}$	$66.3_{0.0}$	$94.5_{0.0}$	$91.4_{0.0}$	910

Table 31: Detals on **Task (4) Sentence Ordering** on **AAN abstract** dataset.

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$17.6_{0.6}$	$29.5_{4.8}$	$5.3_{0.8}$	$46.4_{1.4}$	$51.4_{0.6}$	27	$19.2_{0.3}$	$9.5_{1.5}$	$8.3_{0.7}$	$51.7_{0.4}$	$52.9_{0.0}$	629
Qwen3-1.7B	1.7B	$26.4_{0.2}$	$17.8_{0.1}$	$12.0_{0.2}$	$58.4_{0.2}$	$59.5_{0.2}$	30	$31.4_{0.6}$	$10.4_{0.5}$	$19.1_{0.5}$	$67.6_{0.1}$	$62.5_{0.5}$	829
Qwen3-4B	4B	$47.2_{0.1}$	$0.4_{0.2}$	$31.6_{0.1}$	$82.2_{0.0}$	$73.5_{0.1}$	27	$47.7_{0.1}$	$2.3_{0.3}$	$32.4_{1.5}$	$82.6_{0.2}$	$74.5_{0.3}$	477
Qwen3-8B	8B	$52.3_{0.2}$	$0.6_{0.0}$	$35.9_{0.3}$	$85.3_{0.0}$	$77.2_{0.1}$	27	$53.5_{0.3}$	$1.2_{0.1}$	$37.6_{0.5}$	$85.5_{0.3}$	$78.2_{0.1}$	458
Qwen3-14B	14B	$58.6_{0.2}$	$0.8_{0.1}$	$42.9_{0.2}$	$88.2_{0.0}$	$81.4_{0.1}$	27	$59.1_{0.4}$	$0.4_{0.4}$	$43.4_{0.4}$	$88.2_{0.1}$	$81.5_{0.1}$	475
Qwen3-32B	32B	$63.8_{0.2}$	$0.3_{0.0}$	$48.2_{0.2}$	$89.5_{0.0}$	$84.1_{0.1}$	27	$61.9_{0.2}$	$0.2_{0.0}$	$46.1_{0.3}$	$89.1_{0.3}$	$83.1_{0.2}$	450
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$55.4_{0.3}$	$2.5_{0.7}$	$38.8_{0.3}$	$85.8_{0.2}$	$79.2_{0.4}$	552
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$61.9_{0.0}$	$0.0_{0.0}$	$46.6_{0.0}$	$86.5_{0.0}$	$80.2_{0.0}$	1558
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$65.6_{0.4}$	$0.1_{0.1}$	$49.3_{0.1}$	$90.6_{0.1}$	$84.6_{0.0}$	162
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$69.8_{0.0}$	$0.0_{0.0}$	$55.0_{0.0}$	$91.9_{0.0}$	$86.9_{0.0}$	1568

Table 32: Detals on **Task (4) Sentence Ordering** on **ArXiv abstract** dataset.

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$15.5_{1.7}$	$32.7_{4.7}$	$1.7_{0.4}$	$48.1_{2.2}$	$51.0_{1.3}$	30	$17.1_{0.4}$	$10.4_{0.7}$	$1.7_{0.4}$	$52.5_{0.7}$	$52.2_{0.2}$	677
Qwen3-1.7B	1.7B	$23.8_{0.2}$	$21.0_{0.8}$	$3.7_{0.0}$	$61.6_{0.2}$	$58.5_{0.3}$	32	$30.8_{1.1}$	$14.2_{0.7}$	$11.0_{1.5}$	$69.2_{1.3}$	$64.6_{1.3}$	915
Qwen3-4B	4B	$48.5_{0.1}$	$1.5_{0.1}$	$21.4_{0.4}$	$84.6_{0.0}$	$76.2_{0.0}$	31	$54.1_{0.9}$	$2.8_{0.4}$	$26.2_{0.9}$	$86.5_{0.1}$	$78.1_{0.4}$	508
Qwen3-8B	8B	$54.3_{0.1}$	$0.8_{0.0}$	$25.6_{0.1}$	$87.1_{0.1}$	$78.9_{0.0}$	31	$60.0_{1.6}$	$1.7_{1.2}$	$33.5_{1.8}$	$89.4_{0.4}$	$81.8_{0.3}$	475
Qwen3-14B	14B	$66.3_{0.1}$	$0.8_{0.0}$	$42.2_{0.0}$	$91.5_{0.1}$	$85.6_{0.1}$	31	$66.1_{0.1}$	$0.3_{0.2}$	$43.0_{1.3}$	$91.8_{0.0}$	$85.7_{0.4}$	548
Qwen3-32B	32B	$71.2_{0.0}$	$0.7_{0.1}$	$47.7_{0.3}$	$92.5_{0.2}$	$87.8_{0.1}$	31	$68.6_{0.4}$	$0.6_{0.2}$	$44.2_{0.9}$	$92.3_{0.1}$	$86.9_{0.3}$	499
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$63.5_{1.0}$	$3.2_{0.8}$	$38.9_{0.4}$	$90.0_{0.5}$	$84.2_{0.2}$	599
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$74.9_{0.0}$	$0.0_{0.0}$	$56.8_{0.0}$	$91.6_{0.0}$	$86.2_{0.0}$	1494
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$73.1_{0.1}$	$0.0_{0.0}$	$50.5_{0.4}$	$94.1_{0.0}$	$88.8_{0.0}$	180
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$78.6_{0.0}$	$0.0_{0.0}$	$58.6_{0.0}$	$95.2_{0.0}$	$91.3_{0.0}$	1205

Table 33: Detals on **Task (4) Sentence Ordering** on **Neurips abstract** dataset.

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$9.6_{0.6}$	$41.6_{8.6}$	$1.1_{0.1}$	$43.5_{2.2}$	$38.8_{0.9}$	62	$10.7_{0.4}$	$28.2_{0.2}$	$4.3_{0.4}$	$49.7_{0.1}$	$41.0_{0.1}$	770
Qwen3-1.7B	1.7B	$12.7_{0.1}$	$42.3_{0.9}$	$1.9_{0.1}$	$52.1_{0.0}$	$44.7_{0.1}$	59	$14.7_{0.2}$	$33.2_{0.3}$	$6.6_{0.5}$	$57.3_{0.3}$	$46.2_{0.7}$	1242
Qwen3-4B	4B	$23.3_{0.1}$	$18.7_{0.1}$	$11.1_{0.0}$	$71.5_{0.1}$	$57.5_{0.1}$	54	$23.6_{0.0}$	$19.7_{2.0}$	$12.0_{0.4}$	$72.0_{0.2}$	$58.4_{0.3}$	610
Qwen3-8B	8B	$26.0_{0.1}$	$11.7_{0.3}$	$11.2_{0.1}$	$74.8_{0.1}$	$60.2_{0.2}$	65	$26.4_{0.3}$	$16.5_{2.4}$	$12.0_{0.3}$	$74.6_{0.2}$	$61.1_{0.3}$	591
Qwen3-14B	14B	$30.9_{0.0}$	$10.1_{0.6}$	$15.6_{0.0}$	$77.8_{0.1}$	$65.7_{0.2}$	52	$29.2_{0.5}$	$12.1_{1.7}$	$14.3_{0.1}$	$76.7_{0.3}$	$64.3_{0.1}$	616
Qwen3-32B	32B	$32.8_{0.3}$	$9.3_{0.5}$	$15.5_{0.1}$	$78.5_{0.1}$	$67.7_{0.1}$	52	$30.2_{0.3}$	$11.4_{0.1}$	$14.3_{0.2}$	$77.5_{0.2}$	$65.6_{0.2}$	546
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$26.0_{0.5}$	$23.7_{1.4}$	$11.4_{0.4}$	$72.9_{0.1}$	$61.4_{0.2}$	729
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$28.5_{0.0}$	$1.2_{0.0}$	$15.7_{0.0}$	$68.3_{0.0}$	$53.8_{0.0}$	2488
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$33.2_{0.4}$	$3.2_{0.2}$	$15.8_{0.1}$	$79.7_{0.0}$	$67.5_{0.0}$	310
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$35.5_{0.0}$	$0.1_{0.0}$	$17.8_{0.0}$	$81.2_{0.0}$	$70.1_{0.0}$	3625

Table 34: Detals on **Task (4) Sentence Ordering** on **NSF abstract** dataset.

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$22.8_{0.5}$	$21.4_{8.3}$	$1.2_{0.2}$	$52.5_{3.4}$	$57.9_{1.4}$	23	$25.6_{0.1}$	$7.7_{3.4}$	$2.3_{0.4}$	$56.6_{0.3}$	$60.5_{0.2}$	487
Qwen3-1.7B	1.7B	$37.5_{0.2}$	$0.0_{0.0}$	$8.0_{0.3}$	$68.8_{0.2}$	$68.1_{0.1}$	24	$44.7_{0.6}$	$1.9_{0.1}$	$17.1_{0.5}$	$73.8_{0.3}$	$74.0_{0.4}$	647
Qwen3-4B	4B	$63.6_{0.1}$	$0.0_{0.0}$	$35.1_{0.2}$	$86.5_{0.1}$	$83.5_{0.1}$	24	$72.3_{0.6}$	$0.1_{0.0}$	$50.2_{1.0}$	$90.0_{0.2}$	$88.0_{0.4}$	481
Qwen3-8B	8B	$69.1_{0.0}$	$0.0_{0.0}$	$43.6_{0.1}$	$89.3_{0.0}$	$86.3_{0.0}$	24	$78.4_{0.2}$	$0.0_{0.1}$	$59.9_{1.3}$	$92.5_{0.1}$	$90.6_{0.2}$	525
Qwen3-14B	14B	$79.5_{0.1}$	$0.0_{0.1}$	$61.5_{0.1}$	$92.8_{0.1}$	$91.1_{0.0}$	24	$82.5_{0.5}$	$0.0_{0.1}$	$67.3_{0.7}$	$94.0_{0.2}$	$92.5_{0.1}$	367
Qwen3-32B	32B	$82.7_{0.1}$	$0.1_{0.0}$	$67.0_{0.3}$	$94.2_{0.1}$	$92.6_{0.2}$	24	$84.4_{0.7}$	$0.0_{0.1}$	$70.6_{0.9}$	$94.7_{0.3}$	$93.3_{0.2}$	452
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$79.8_{1.0}$	$0.1_{0.0}$	$63.2_{1.5}$	$92.9_{0.6}$	$91.4_{0.5}$	529
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$88.2_{0.0}$	$0.0_{0.0}$	$77.1_{0.0}$	$96.1_{0.0}$	$94.9_{0.0}$	712
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$83.6_{0.6}$	$0.0_{0.0}$	$68.3_{1.1}$	$94.5_{0.1}$	$92.8_{0.2}$	137
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$87.3_{0.0}$	$0.0_{0.0}$	$75.7_{0.0}$	$95.9_{0.0}$	$94.7_{0.0}$	685

Table 35: Detals on **Task (4) Sentence Ordering** on **ROC stories** dataset.

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$21.9_{0.8}$	$24.6_{6.8}$	$2.0_{0.5}$	$47.9_{2.2}$	$55.8_{1.1}$	24	$24.6_{0.9}$	$10.9_{1.6}$	$5.1_{0.6}$	$54.3_{1.4}$	$57.8_{0.7}$	515
Qwen3-1.7B	1.7B	$28.3_{0.4}$	$6.0_{0.1}$	$3.9_{0.2}$	$57.3_{0.2}$	$61.5_{0.1}$	24	$35.6_{1.2}$	$2.8_{0.6}$	$14.6_{0.7}$	$66.4_{0.4}$	$65.7_{0.7}$	699
Qwen3-4B	4B	$46.9_{0.2}$	$0.8_{0.0}$	$22.2_{0.2}$	$76.4_{0.0}$	$73.3_{0.1}$	24	$49.6_{0.3}$	$0.9_{0.2}$	$24.8_{0.7}$	$78.5_{0.2}$	$75.2_{0.3}$	561
Qwen3-8B	8B	$50.0_{0.1}$	$0.2_{0.1}$	$25.9_{0.2}$	$78.9_{0.1}$	$75.4_{0.1}$	23	$52.0_{0.7}$	$0.3_{0.1}$	$27.4_{1.1}$	$80.2_{0.3}$	$76.7_{0.3}$	630
Qwen3-14B	14B	$53.9_{0.1}$	$0.0_{0.0}$	$29.3_{0.3}$	$81.2_{0.1}$	$77.5_{0.1}$	23	$55.1_{0.4}$	$0.1_{0.2}$	$31.2_{0.9}$	$81.4_{0.6}$	$78.1_{0.8}$	449
Qwen3-32B	32B	$54.0_{0.2}$	$0.2_{0.2}$	$29.7_{0.2}$	$80.8_{0.0}$	$77.6_{0.2}$	23	$55.3_{0.6}$	$0.5_{0.3}$	$31.2_{0.9}$	$81.8_{0.4}$	$78.2_{0.2}$	491
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$53.3_{1.2}$	$0.8_{0.8}$	$29.0_{1.2}$	$80.3_{0.4}$	$76.8_{0.4}$	536
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$58.4_{0.0}$	$0.1_{0.0}$	$36.4_{0.0}$	$82.4_{0.0}$	$79.1_{0.0}$	1471
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$54.6_{0.8}$	$0.0_{0.0}$	$31.5_{1.1}$	$81.1_{0.3}$	$77.9_{0.5}$	172
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$58.2_{0.0}$	$0.0_{0.0}$	$35.0_{0.0}$	$82.7_{0.0}$	$79.7_{0.0}$	1073

Table 36: Detals on **Task (4) Sentence Ordering** on **SIND** dataset.

Model	Size	w/o reasoning						w/ reasoning					
		Acc	Lumr	Pmr	Skip	Lcs	tok.	Acc	Lumr	Pmr	Skip	Lcs	tok.
Qwen3-0.6B	0.6B	$6.8_{0.3}$	$53.7_{10.2}$	$1.8_{0.6}$	$38.2_{1.7}$	$31.9_{1.5}$	114	$8.5_{0.1}$	$45.2_{1.2}$	$4.2_{0.8}$	$43.9_{0.8}$	$34.4_{0.5}$	941
Qwen3-1.7B	1.7B	$12.1_{0.1}$	$36.6_{1.0}$	$5.2_{0.1}$	$55.4_{0.1}$	$41.8_{0.1}$	73	$12.7_{0.2}$	$47.7_{1.8}$	$8.9_{0.3}$	$52.9_{0.3}$	$40.4_{0.3}$	1313
Qwen3-4B	4B	$20.2_{0.1}$	$26.3_{0.7}$	$12.8_{0.1}$	$72.7_{0.0}$	$53.3_{0.1}$	74	$21.2_{0.3}$	$33.7_{1.7}$	$14.1_{0.9}$	$71.9_{0.1}$	$54.5_{0.4}$	976
Qwen3-8B	8B	$20.8_{0.1}$	$21.1_{0.9}$	$14.8_{0.2}$	$72.8_{0.3}$	$53.7_{0.3}$	139	$23.2_{0.4}$	$31.5_{0.7}$	$15.9_{0.4}$	$75.1_{0.1}$	$58.2_{0.2}$	902
Qwen3-14B	14B	$27.2_{0.1}$	$23.5_{1.0}$	$17.4_{0.1}$	$80.5_{0.1}$	$63.1_{0.1}$	72	$27.1_{0.2}$	$29.5_{0.6}$	$18.2_{0.2}$	$79.1_{0.2}$	$63.7_{0.1}$	608
Qwen3-32B	32B	$30.4_{0.3}$	$15.2_{0.6}$	$19.3_{0.3}$	$82.7_{0.0}$	$65.9_{0.1}$	73	$29.1_{0.6}$	$21.5_{2.4}$	$19.1_{0.5}$	$80.9_{0.4}$	$65.2_{0.3}$	545
DS-r1-distill-Qwen	32B	-	-	-	-	-	-	$24.3_{0.6}$	$43.1_{5.5}$	$17.6_{0.8}$	$74.0_{1.1}$	$60.2_{0.7}$	886
DeepSeek-r1-0528	37/671B	-	-	-	-	-	-	$28.0_{0.0}$	$1.4_{0.0}$	$23.8_{0.0}$	$58.9_{0.0}$	$42.0_{0.0}$	2771
GPT-5-mini (low)	Unk.	-	-	-	-	-	-	$32.0_{0.2}$	$8.9_{0.3}$	$20.3_{0.1}$	$84.1_{0.0}$	$67.7_{0.0}$	701
GPT-5-mini (high)	Unk.	-	-	-	-	-	-	$40.1_{0.0}$	$0.7_{0.0}$	$23.0_{0.0}$	$87.9_{0.0}$	$74.4_{0.0}$	3762

Table 37: Detals on **Task (4) Sentence Ordering** on **Wikipedia movie plots** dataset.

B.5 Task (5) Dialogue Discourse Parsing

Tables tables 38 to 40.

		single turn						auto-regressive					
		w/o reasoning			w/ reasoning			w/o reasoning			w/ reasoning		
Model	Size	Link	Full	tok.	Link	Full	tok.	Link	Full	tok.	Link	Full	tok.
Qwen3-1.7B	1.7B	$17.5_{0.5}$	$2.5_{0.1}$	12	$39.7_{0.6}$	$8.4_{0.9}$	944	$16.0_{1.0}$	$0.4_{0.0}$	9	$35.9_{2.5}$	$5.2_{0.2}$	762
Qwen3-4B	4B	$42.8_{0.2}$	$8.0_{0.2}$	9	$56.9_{1.0}$	$22.0_{0.4}$	1020	$34.8_{0.7}$	$4.6_{0.3}$	9	$58.8_{0.7}$	$19.6_{0.8}$	849
Qwen3-8B	8B	$52.4_{0.2}$	$12.4_{0.3}$	9	$59.2_{0.3}$	$21.9_{0.5}$	942	$51.6_{0.9}$	$8.9_{1.1}$	9	$58.8_{0.1}$	$17.2_{0.9}$	754
Qwen3-14B	14B	$55.7_{0.2}$	$16.2_{0.2}$	9	$62.5_{1.3}$	$33.1_{0.3}$	750	$55.8_{0.3}$	$13.2_{0.9}$	9	$61.3_{0.5}$	$29.8_{1.3}$	703
Qwen3-32B	32B	$58.1_{0.4}$	$21.5_{1.4}$	9	$62.1_{0.2}$	$33.3_{0.4}$	611	$57.8_{0.6}$	$16.5_{1.3}$	9	$62.4_{0.5}$	$31.3_{0.3}$	583
DS-r1-distill-Qwen	32B	-	-	-	$62.9_{0.4}$	$25.5_{0.6}$	430	-	-	-	$61.5_{0.7}$	$22.3_{1.5}$	429
DeepSeek-r1-0528	37/671B	-	-	-	$68.0_{0.0}$	$42.3_{0.0}$	1494	-	-	-	$66.3_{0.5}$	$38.7_{0.0}$	1526
GPT-5-mini (low)	Unk.	-	-	-	$62.1_{0.4}$	$33.6_{0.8}$	146	-	-	-	$61.1_{0.3}$	$32.1_{0.8}$	142
GPT-5-mini (high)	Unk.	-	-	-	$67.0_{0.5}$	$39.9_{0.0}$	1235	-	-	-	$66.0_{0.0}$	$38.8_{0.0}$	1254

Table 38: Detals on **Task (5) Dialogue Discourse Parsing** on **STAC** dataset.

		single turn						auto-regressive					
		w/o reasoning			w/ reasoning			w/o reasoning			w/ reasoning		
Model	Size	Link	Full	tok.	Link	Full	tok.	Link	Full	tok.	Link	Full	tok.
Qwen3-1.7B	1.7B	$14.1_{0.2}$	$3.0_{0.1}$	17	$39.5_{0.3}$	$10.6_{0.5}$	907	$20.7_{0.5}$	$0.2_{0.0}$	8	$43.1_{0.5}$	$5.3_{0.4}$	728
Qwen3-4B	4B	$41.1_{0.5}$	$7.6_{0.2}$	9	$55.0_{0.3}$	$23.3_{0.7}$	994	$33.7_{0.7}$	$4.9_{0.4}$	9	$57.9_{0.3}$	$22.6_{0.2}$	943
Qwen3-8B	8B	$48.5_{0.2}$	$10.4_{0.4}$	8	$58.8_{0.6}$	$20.0_{0.2}$	1006	$46.4_{0.8}$	$7.4_{0.3}$	8	$60.6_{0.1}$	$16.8_{0.1}$	963
Qwen3-14B	14B	$58.0_{0.3}$	$19.9_{0.4}$	9	$59.6_{0.3}$	$27.2_{0.4}$	743	$61.4_{0.1}$	$18.0_{0.3}$	9	$60.1_{0.6}$	$25.7_{0.8}$	743
Qwen3-32B	32B	$59.0_{0.3}$	$18.4_{0.9}$	9	$59.0_{0.1}$	$24.7_{0.4}$	611	$58.1_{0.6}$	$13.7_{1.7}$	9	$58.3_{0.5}$	$22.2_{0.8}$	629
DS-r1-distill-Qwen	32B	-	-	-	$59.3_{0.4}$	$17.5_{0.4}$	445	-	-	-	$58.6_{0.6}$	$16.1_{0.3}$	446
DeepSeek-r1-0528	37/671B	-	-	-	$57.7_{0.0}$	$23.8_{0.0}$	1499	-	-	-	$56.7_{0.0}$	$22.3_{0.0}$	1511
GPT-5-mini (low)	Unk.	-	-	-	$57.3_{0.6}$	$29.0_{0.1}$	157	-	-	-	$55.6_{0.1}$	$27.7_{0.3}$	160
GPT-5-mini (high)	Unk.	-	-	-	$59.2_{0.0}$	$31.5_{0.0}$	1272	-	-	-	$58.4_{0.0}$	$30.2_{0.0}$	1344

Table 39: Detals on **Task (5) Dialogue Discourse Parsing** on **Molweni** dataset.

		single turn						auto-regressive					
		w/o reasoning			w/ reasoning			w/o reasoning			w/ reasoning		
Model	Size	Link	Full	tok.	Link	Full	tok.	Link	Full	tok.	Link	Full	tok.
Qwen3-1.7B	1.7B	$4.4_{0.0}$	$1.4_{0.0}$	16	$29.4_{0.1}$	$6.0_{0.3}$	926	$2.5_{0.2}$	$0.3_{0.0}$	149	$36.7_{2.2}$	$3.6_{0.1}$	747
Qwen3-4B	4B	$35.8_{0.2}$	$11.7_{0.2}$	10	$67.6_{0.5}$	$24.0_{0.4}$	893	$19.9_{0.9}$	$5.7_{0.1}$	10	$72.2_{0.1}$	$17.2_{0.5}$	764
Qwen3-8B	8B	$57.9_{0.4}$	$20.0_{0.2}$	11	$72.1_{0.1}$	$29.4_{0.5}$	832	$56.1_{0.8}$	$8.8_{0.2}$	11	$73.7_{0.2}$	$17.9_{0.3}$	657
Qwen3-14B	14B	$58.5_{0.2}$	$24.4_{0.2}$	12	$67.9_{0.2}$	$34.5_{0.2}$	658	$70.4_{0.2}$	$15.1_{0.4}$	10	$72.7_{0.2}$	$22.6_{0.1}$	536
Qwen3-32B	32B	$65.0_{0.3}$	$28.1_{0.3}$	12	$67.9_{0.2}$	$36.2_{0.4}$	551	$68.3_{0.8}$	$10.4_{0.7}$	10	$70.5_{0.1}$	$23.0_{0.3}$	491
DS-r1-distill-Qwen	32B	-	-	-	$68.9_{0.4}$	$36.1_{0.4}$	415	-	-	-	$69.6_{0.4}$	$25.7_{0.7}$	412
DeepSeek-r1-0528	37/671B	-	-	-	$69.4_{0.0}$	$48.6_{0.0}$	1702	-	-	-	$69.6_{0.0}$	$34.2_{0.0}$	1893
GPT-5-mini (low)	Unk.	-	-	-	$65.8_{0.0}$	$37.8_{0.0}$	141	-	-	-	$66.1_{0.1}$	$26.8_{0.4}$	146
GPT-5-mini (high)	Unk.	-	-	-	$69.1_{0.0}$	$46.3_{0.0}$	1321	-	-	-	$66.4_{0.0}$	$31.9_{0.0}$	1472

Table 40: Detals on **Task (5) Dialogue Discourse Parsing** on **MSDC** dataset.

C   Appendix C. Visualizations

C.1   Task (1) Discourse Marker Understanding

Figures figs. 1 to 3.

Figure 1: Performance comparison on **Task (1) Discourse Marker Understanding** on *Just*-**Manual** dataset with different **reasoning** mode or effort.

Figure 2: Performance comparison on **Task (1) Discourse Marker Understanding** on *Just*-**Subtitle** dataset with different **reasoning** mode or effort.

Figure 3: Performance comparison on **Task (1) Discourse Marker Understanding** on *Otherwise* dataset with different **reasoning** mode or effort.

C.2 Task (2) Temporal Reasoning

Figures figs. 4 to 6.

Figure 4: Performance comparison on **Task (2) Temporal Reasoning** on **TBD** dataset with different **reasoning** mode or effort.

Figure 5: Performance comparison on **Task (2) Temporal Reasoning** on **TDD-Man** dataset with different **reasoning** mode or effort.

Figure 6: Performance comparison on **Task (2) Temporal Reasoning** on **ToT-Arithmetic** dataset with different **reasoning** mode or effort.

C.3 Task (4) Sentence Ordering

Figures figs. 7 to 10.

Figure 7: Performance comparison on **Task (4) Sentence Ordering** on **AAN abstract** and **ArXiv abstract** datasets with different **reasoning** mode or effort.

Figure 8: Performance comparison on **Task (4) Sentence Ordering** on **Neurips abstract** and **NSF abstract** datasets with different **reasoning** mode or effort.

Figure 9: Performance comparison on **Task (4) Sentence Ordering** on **ROC stories** and **SIND** datasets with different **reasoning** mode or effort.

Figure 10: Performance comparison on **Task (4) Sentence Ordering** on **Wikipedia movie plots** dataset with different **reasoning** mode or effort.

C.4 Task (5) Dialogue Discourse Parsing

Figure fig. .

Figure 11: Performance comparison on **Task (4) Sentence Ordering** on **STAC**, **Molweni** and **MSDC** dataset with different **reasoning** mode or effort.