Understanding the Generalization Gap in Visual Reinforcement Learning

Abstract

Deep Reinforcement Learning (RL) agents have achieved superhuman performance on several video game suites. However, unlike humans, the trained policies fail to transfer between related games or even between different levels of the same game. Recent works have attempted to reduce this generalization gap using ideas such as data augmentation and learning domain invariant features. However, the transfer performance still remains unsatisfactory. In this work, we use procedurally generated video games to empirically investigate several hypotheses to explain the lack of transfer. We also show that simple auxiliary tasks can improve generalization of policies. Contrary to the belief that policy adaptation to new levels requires full policy finetuning, we find that visual features transfer across levels and only the parameters, that use these visual features to predict actions, requires finetuning. Finally, to inform fruitful avenues for future research, we construct simple oracle methods that close the generalization gap.

1 Introduction

Deep Reinforcement Learning (RL) has achieved tremendous success on several video game suites (Mnih et al., 2013; Vinyals et al., 2019; Berner et al., 2019). However, state-of-the-art (SOTA) RL agents are usually trained and tested on the same game. It turns out that the learned policy fails to transfer to different games or unseen levels (Cobbe et al., 2018; 2019). In contrast, humans are remarkable at transferring to new tasks and environments. Behavior studies (Dubey et al., 2018) show that humans make extensive use of visual priors such as object permanence, sub-goals, and intuitive physics when learning new games. Without these priors, data efficiency of humans can reduce by at least $10\times$ (Dubey et al., 2018). (Sax et al., 2018) learns visual priors with supervised learning on datasets with manual annotations of several semantically meaningful features. In practice however, acquiring such datasets is challenging.

In the absence of labelled datasets and human supervision, past works have explored three main ways to incorporate visual priors to improve generalization. The first paradigm is *data augmentation* (Michael et al., 2020; Kostrikov et al., 2020) where invariance in the learned representations is induced by training the agent on a large set of task-irrelevant variations of the observed data. Since the distinction between what is relevant vs irrelevant is task-dependent, the optimal choice of data augmentation is also task dependent. To avoid manual selection of data augmentations, UCB-DrAC (Raileanu et al., 2020) used upper confidence bound (UCB) algorithm (Auer, 2002) for choosing optimal augmentations. However, it remains unclear whether choosing one out of many task-agnostic data augmentations, such as cropping, helps in closing the generalization gap. In this paper, we show that set of transformations used in state-of-the-art methods are insufficient at closing the generalization gap. On the other hand, we also show that task-informed data augmentations close the generalization gap, but require task variation information ahead of time. How to construct task sensitive data augmentations is therefore an interesting avenue of future research for policy generalization. We discuss this finding in Section 3.

The second paradigm for transfer learning is to leverage *domain confusion* (Tzeng et al., 2014; 2015; Hoffman et al., 2013) for improving policy generalization. Domain confusion is commonly used in computer vision to make one data source distribution indistinguishable from the target distribution. It can be used to learn policy features that make different domains/levels indistinguishable, thereby discouraging the policy from learning spurious domain/level-specific features. iDAAC (Raileanu

(a) Jumper Levels	(b) Climber Levels

Figure 1: Visualization of different levels of (a) Jumper and (b) Climber. In both the games, the first and second level differ in theme whereas the first and third level differ in both theme and layout.

and Fergus, 2021) used this technique to improve policy generalization. However, our investigation reveals that even policies that generalize well contain domain/level specific information. Such information can not be completely removed from the policy network because the actions predicted by the policy depend on the game layout which in turn is predictive of the individual levels. Details of this investigation are provided in Section 4.

The third paradigm of improving generalization involves using *auxiliary prediction tasks* (such as depth prediction, image reconstruction, contrastive learning) to regularize the policy features to prevent learning spurious features (Jaderberg et al., 2016; Srinivas et al., 2020). In this work, we choose the auxiliary task of inverse model prediction (Agrawal et al., 2016) due to its simplicity. This improves policy generalization. We detail this finding in Section 5.

It is well-known that choice of hyper parameters has a substantial impact on the performance of RL agents. When it comes to policy generalization, discussions around hyperparameter selection have been limited. We show that state-of-the-art (SOTA) methods that improve policy generalization require careful hyperparameter selection for each task. When these methods are limited to choosing a single set of hyperparameters across different tasks, their performance becomes similar to PPO. We detail this finding in Section 6.

Finally, we question the commonly held belief in deep RL that policy adaptation to new visual tasks require full policy finetuning. Our experiments show that visual features learned by training on even a limited number of levels of one game transfer to new levels! Infact, only the layers of the policy network responsible for converting visual features into actions require finetuning. Details of this investigation are provided in Section 7.

To summarize our findings, we show that (i) better forms of data augmentation improve policy generalization; (ii) learning level-invariant (or domain-invariant) features may not be necessary for good generalization; (iii) regularizing the policy features using simple auxiliary tasks can improve generalization; (iv) SOTA methods that improve policy generalization heavily rely on careful hyperparameter selection for each task; (v) visual features, trained on a limited number of levels, transfer across levels, but the layers, that use these features to predict actions, require finetuning on new levels. We use Procgen (Cobbe et al., 2019), a suite of procedurally generated games, to demonstrate our findings.

2 PRELIMINARIES

We consider a distribution of tasks $p(\mathcal{T})$ where each task $t_i \sim p(\mathcal{T})$ is a Partially Observable Markov Decision Process (POMDPs) $\mathcal{M}_i = (S_i, O_i, A_i, T_i, \Omega_i, R_i, \gamma)$. S_i is the state space, O_i is the observation space, A_i is the action space, $T_i(s'|s, a)$ is the transition function, $\Omega_i(o'|s, a)$ is the observation function, $R_i(s, a)$ is the reward function and γ is the discount factor. The goal is to find a policy π_θ that maximizes the expected sum of discounted rewards over the distribution of tasks, $J(\pi_\theta) = \mathbb{E}_{\pi,\mathcal{T}} \left[\sum_{t=0}^{T-1} \gamma^t R_i(s_t, a_t) \right]$. During training, we only have access to a limited number of tasks $\hat{\mathcal{T}} = \{t_i\}_{i=1}^N$. Our goal is to find a policy π_θ that generalizes to new tasks sampled from the task distribution $p(\mathcal{T})$.

2.1 ENVIRONMENT SETUP

Since we want to understand the generalization gap in visual RL, we focus on domains which separate training and test tasks. Therefore, we choose the ProcGen suite (Cobbe et al., 2019), a collection of

Figure 2: UCB-DrAC with theme randomization (DrAC-TR) matches the performance of DrAC-FT on games with fixed themes indicating that it learned theme invariant features. Thus, it outperforms UCB-DrAC implying the need for better domain randomization and data augmentation. Black horizontal lines are the performance of a PPO baseline trained with fixed texture. Dashed line is training performance.

16 procedurally generated video games. For each game, there are multiple levels. We refer to each level as a separate task. A level is characterized by object positions, their textures, agent position, its texture and background. We collectively refer to a combination of object textures, the agent texture and background as *theme*. We collectively refer to positions of objects and the agent as layout. From Figure 1, we can see that the first and the second level differ in theme whereas the first and the third level differ in both the theme and the layout. We train the policy on the first two hundred levels and evaluate it on a subset of remaining levels (i.e. approximately two million unique levels).

2.2 METHODS

We are using a standard RL policy architecture $a \sim \pi_\theta(a|s)$ that consists of: a visual encoder $z = \pi_{\theta_1}^{enc}(s)$ and a policy head $a \sim \pi_{\theta_2}^h(a|z)$. Here, θ_1 refers to the parameters of the visual encoder and θ_2 refers to that of the policy head. Collectively, they are referred as $\theta = [\theta_1, \theta_2]$. We also have a value head $V_\psi^h(z)$ for predicting value function. We use the ResNet architecture used in IMPALA (Espeholt et al., 2018) as the visual encoder, which has 15 convolutional layers and gives out a flattened feature map. We refer to the flattened vector z as the *visual feature*. It is then passed into two 2-layer fully-connected neural networks with 256 hidden units for predicting the actions and the value function.

To study our hypothesis, we analyze PPO (Schulman et al., 2017) and the three state-of-the-art (SOTA) methods:

- **UCB-DrAC (Raileanu et al., 2020)** uses Upper Confidence Bound (UCB) to automatically select game specific data augmentations out of eight possible ones: *crop*, *grayscale*, *cutout*, *cutout-color*, *flip*, *rotate*, *random convolution* and *color jitter*. For brevity, we sometimes refer to UCB-DrAC as simply DrAC.
- **DAAC (Raileanu and Fergus, 2021)** separates the policy and the value network in PPO to ensure that overfitting in the value network doesn't cause overfitting in the policy network due to shared representation.
- **iDAAC (Raileanu and Fergus, 2021)** builds upon DAAC and introduces an auxillary loss which encourages the visual features of the policy to ignore the level specific features of the policy.

We use PPO's pytorch implementation (Kostrikov, 2018), the official implementation for UCB-DrAC (Raileanu et al., 2020), and the official implementation for DAAC/iDAAC (Raileanu and Fergus, 2021). See Appendix B for the hyperparameters used.

2.3 EVALUATION METRICS

Different procgen games have different score ranges which makes it difficult for us to average the scores across games. Recent works (Raileanu et al., 2020; Raileanu and Fergus, 2021) used percentage improvement over PPO for averaging across games. However, this metric doesn't properly take reward range of a game into account and is also biased by PPO's performance on that game, thereby being more susceptible to large variations. To remedy this, as suggested in (Cobbe et al., 2019), we use the *normalized score* $\frac{R-R_{min}}{R_{max}-R_{min}}$ to compute mean scores (MNS) across games. Here, R_{max} and R_{min} are game-dependent constants provided in (Cobbe et al., 2019). To calculate the final train and test performances of a policy, we evaluate the policy 100 times on train levels (1-200) and test levels for each game. We report the mean and standard deviation of final train and test performances computed using 5 different seeds.

3 INVESTIGATING POLICY GENERALIZATION WITH DATA AUGMENTATION

A policy can fail to generalize to a new level for primarily two reasons. In the first case, the policy can fail to generalize to a new configuration of objects. Second, the policy may not be theme invariant and can get affected by changes in agent texture, object textures, and background. To tackle the second issue, prior works (Raileanu et al., 2020; Michael et al., 2020) employed data augmentation techniques. However, it is unclear if UCB-DrAC completely achieves theme invariance.

If UCB-DrAC achieved theme invariance, its performance would be same as that when trained on ProcGen games with fixed themes. Therefore, we train UCB-DrAC on ProcGen games with fixed themes and refer to this oracle baseline as DrAC+FT for *fixed theme*. Our result, presented in Figure 2 shows a significant performance improvement from UCB-DrAC to DrAC+FT. This implies that UCB-DrAC does not produce theme invariance, and better data augmentation schemes is still needed. Moreover, as shown in Figure 3, it performs similar to PPO baseline when averaged across all the games, thereby reaffirming the need for better data augmentation schemes.

Furthermore, we implemented a variant of the ProcGen suite that uses a separate randomization process for the theme versus the game layouts. While each level of a game still has a fixed layout, it now randomly samples a different theme at every reset. We refer to this baseline as DrAC-TR for *theme randomization*. Our intent is to use this domain randomization scheme, that makes use of privileged access to the game engine, as a proxy of better data augmentation schemes. Figure 2 shows that DrAC+TR greatly improves over UCB-DrAC and gets closer to the performance of DrAC+FT. Our result demonstrates the viability of pushing for stronger data augmentation schemes for producing theme invariance and thus policy generalization. We hope to encourage the development towards this venue of research with our reported findings.

4 INVESTIGATING POLICY GENERALIZATION WITH DOMAIN CONFUSION

Another way to learn generalizable policies is by using *domain confusion* (Tzeng et al., 2014; 2015; Hoffman et al., 2013) which discourages policies from predicting task irrelevant properties of the

Table 1: Performance of level classifier trained on the encoder features of policies learned with PPO on 200 levels, with PPO on 100k levels, with DAAC on 200 levels, and with iDAAC on 200 levels, averaged across all procgen games.

	PPO (200)	PPO (100k)	DAAC	iDAAC
Train	0.95 ± 0.1	0.96 ± 0.1	0.95 ± 0.1	0.94 ± 0.11
Test	0.91 ± 0.16	0.87 ± 0.18	0.89 ± 0.12	0.87 ± 0.13

environment, thereby encouraging them to focus on task relevant properties. In addition to separating the policy and the value network, (Raileanu and Fergus, 2021) used this technique to prevent the policy from learning level-specific features and obtained SOTA results. Given these findings, we might think that we should make policies level invariant to obtain better generalization. However, a level (in a game) is not only defined by its theme but also by its layout which contains task relevant information. Therefore, learning level-invariant policies might remove layout features important for solving the task and thus hurt the performance of these policies. Hence, it's not clear if the policies, that generalize well, are independent of level-specific features.

To answer this, we first take the policies trained by PPO on 100k levels, by DAAC on 200 levels and by iDAAC on 200 levels on different games of procgen. All these policies have good generalization capabilities. We want to test if the visual features coming from these policies contain level-specific features. Therefore, we collect 1 trajectory with random exploration for each level from 1 to 200 (per game) and label each state in the trajectory with the corresponding level id. We then mix all the (state, level id) tuples in the collected trajectories and call the resulting dataset $\mathcal{D}$. The first 80% of $\mathcal{D}$ is labelled as train set and the remaining as the test set. For each of the policies described above, we use the train set to learn a linear level classifier on top of their visual features and evaluate the performance of the learned classifier on the test set. Table 1 shows that each of the classifier learned obtained a good train and test performance averaged across all games. We further provide the performance of these classifiers on individual games in the Appendix. This implies that all the above mentioned policies, with good generalization capabilities, contain level-specific features. To further bolster our claim, we use the train set to learn a linear classifier on top of visual features of policies trained by PPO on 200 levels and evaluate its performance on the test set. We see that its performance is similar to that of the previous classifiers. This shows that policies have level specific features regardless of whether it generalizes or not.

DAAC/iDAAC (Raileanu and Fergus, 2021) performs well due to less overfitting as a result of separation of policy and value networks and the regularization of policy features from its auxillary losses. However, the insight that these methods don't learn level-specific features and discouraging the policies to learn level-specific features leads to better generalization, isn't empirically grounded.

5 INVESTIGATING POLICY GENERALIZATION WITH AUXILIARY TASKS

Till now, we have explored domain randomization and domain confusion techniques to obtain generalizable policies. A third technique to improve policy generalization is use of auxiliary tasks to regularize visual features of the policy. (Jaderberg et al., 2016) showed that depth prediction helped in speeding up the policy learning as well as improving its generalization capabilities. However, depth information isn't always available during training. Therefore, we propose a simpler auxiliary task of encouraging the visual features coming from 2 consecutive states to predict the corresponding action. This inverse model regularization has been shown to be an effective regularization technique in prior works (Agrawal et al., 2016; Pathak et al., 2017; 2018). Let $z_t = \pi_{\theta_1}^{enc}(s_t)$. If f_ϕ is the inverse model and (s_t, a_t, s_{t+1}) is the state action state tuple, then this regularization minimizes $\mathcal{CE}(a_t, f_\phi(z_t, z_{t+1}))$ where $\mathcal{CE}$ is the cross-entropy loss. Figure 3 shows that this regularization is competitive with UCB-DrAC despite being simpler.

Figure 3: PPO with inverse model regularization (PPO inv m) is competitive against UCB-DrAC, DAAC and iDAAC in the ProcGen domain despite being a much simpler method.

Figure 4: We compare PPO, PPO with inverse model regularization (PPO inv m), UCB-DrAC, DAAC, and iDAAC on test levels (a) when using different hyperparameters for each game and (b) when using a single hyperparameter across all games.

6 Effects of hyperparameter selection on policy generalization

We have looked at different ways to learn policies that generalize across different levels. However, with exception of UCB-DrAC, all the other methods (PPO inv m, DAAC, iDAAC) depend on careful hyperparameter selection to improve over PPO. To see the impact of this careful hyperparameter selection, we choose a single set of hyperparameters for each method that gives the highest mean normalized score (MNS) on validation levels $201-400$. We then compare PPO with different methods, each using their single set of hyperparameters across all games, on test levels. Figure 4 shows that all methods perform similar to PPO on test levels when using a single set of hyperparameters across all games (see Appendix B for complete details). This suggests that improvements over PPO (by various methods) heavily depends on careful hyperparameter selection on each game. One can argue that different games require different hyperparameters due to their unique properties. However, careful hyperparameter tuning on each game is compute-intensive, and there's no available guidance on how to go about it other than do a grid search. Hence, automatically tuning hyperparameters in a compute-efficient manner is an important avenue for future works.

7 Investigating policy adaptation to new levels

Till now, we have focused on learning policies that generalize to new levels. Another related problem setting is policy adaptation to new levels. First, we train a policy on a limited number of levels (i.e., levels $1-200$). However, rather than directly evaluating the trained policy, we finetune the trained policy on new levels (i.e., levels $201-400$) to achieve the train-time performance quickly. In this setting, it is natural to wonder if finetuning of the entire policy is required to achieve the train-time performance on new levels. To answer this question, we fix the visual encoder $\pi_{\theta_1}^{enc}$ of a policy trained using PPO on levels $1-200$ of a game and finetune only the policy head $\pi_{\theta_2}^{h}$ (as well as the value head V_ψ) on levels $201-400$ of the game. If finetuning the entire policy on levels $201-400$ is required to achieve the train-time performance, then finetuning only the policy head on those levels should lead to a sub-optimal performance.

Figure 5 shows that the average returns of the policy on levels $201-400$ become similar to the average returns of the policy on levels $1-200$ after finetuning the policy head. Furthermore, finetuning the entire policy on levels $201-400$ levels gives a similar average return. These observations imply that finetuning only the policy head (on levels $201-400$) is sufficient to recover the average return of levels $1-200$. Additionally, we see that end-to-end training of policy on levels $201-400$ is less sample-efficient than finetuning the policy head as well as finetuning the entire policy. Moreover, training of policy head with randomly initialized visual encoder as well as imagenet (Krizhevsky et al., 2012) trained visual encoder on levels $201-400$ leads to poor average returns. These observations show that the visual encoder features learned from levels $1-200$ are meaningful and help finetune both the policy head and the entire policy. Overall, this implies that the visual features learned on training levels ($1-200$) are meaningful and transfer to new levels ($201-400$). Instead, it is the policy head feature that fails to transfer to new levels and requires further finetuning.

However, the strategy of training a policy on training levels ($1-200$) and then finetuning the policy head on new levels has limitations. As the number of new levels increases, it becomes harder to finetune the policy head on those levels and recover the average policy returns of the training levels. From Figure 6, we can see that finetuning the policy head on 200 and 1k new levels recovers the average policy returns of the training levels. But, it fails to do the same for 10k and 100k new levels.

8 Discussion

How to use visual features? Most of the work on visual transfer in RL has focused on learning generalizable visual features. However, another related problem setting is policy adaptation to new levels. Section 7 shows that visual features learned by PPO transfer to new levels but the policy head, tasked to combine visual features to predict actions, requires finetuning on new levels. This suggests a fruitful avenue for future work: instead of learning better visual features, focus on how to leverage the learned features to solve a new task.

Towards better data augmentation. UCB-DrAC performs similar to PPO baseline when averaged across all the games and doesn't fully address the problem of learning invariant features. Specifically,

Figure 5: **Transfer**: We compare fine-tuning the policy head (Head-only) versus the entire policy network (Full) on new levels $(201 - 400)$. The policy is trained on 200 levels. Fine tuning just the policy head allows us to recover this performance on the training levels ([1 - 200]), showing that the visual features only require a small number of training levels to generalize. We additionally include the learning curve of a policy trained from scratch (From Scratch), a policy head trained on a randomly initialized visual encoder (Head (Random)), and a policy head trained on a imagenet pretrained visual encoder (Head (ImageNet)) to show the importance of using learned visual features.

Figure 6: We compare fine-tuning the policy head (Head-only) versus the entire policy network (Full). The policy is trained on 200 training levels ([1 - 200]), and fine-tuned on (a) 200, (b) 1k, (c) 10k, and (d) 100k new test levels. We additionally include the learning curve of a policy trained from scratch (From Scratch), a policy head trained on a randomly initialized visual encoder (Head (Random)), and a policy head trained on a imagenet pretrained visual encoder (Head (ImageNet)) to show the ability for the visual features to transfer. The plots show the normalized reward averaged across all games (see results on individual games in Appendix C).

it is significantly worse as compared to training PPO with fixed texture. This indicates that better data augmentation techniques are required to make the policy invariant to irrelevant visual appearances. We show that one way to overcome this challenge is by combining UCB-DrAC with theme randomization. However, theme randomization requires task-specific knowledge of how the theme varies across different variants of the task. In general, such knowledge may not available to the agents. An exciting area of future investigation is to develop data augmentation method that can automatically discover task-relevant augmentations.

Further investigation of auxiliary losses. We show PPO, with inverse model regularization, significantly improves upon PPO despite being a simple change. Similarly, iDAAC made use of auxiliary losses to focus on task-relevant features of the environment. This indicates the need for further investigation into auxiliary losses for better policy generalization.

Towards compute-efficient hyperparameter tuning. We show that state-of-the-art (SOTA) methods that improve policy generalization heavily rely on careful hyperparameter selection for each game. However, hyperparameter tuning via grid search on each game is compute-intensive. Therefore, automatically tuning hyperparameters in a compute-efficient manner is a fruitful avenue for future works.

9 RELATED WORK

Overfitting in Reinforcement Learning. It is a common practice in reinforcement learning to train and test the policy in the same environment. However, it doesn't tell us if the policy is overfitting to that particular environment or learning some generalized behavior. Prior works (Cobbe et al., 2018; 2019; Justesen et al., 2018; **?**; Zhang et al., 2018a;b; Juliani et al., 2019; Rajeswaran et al., 2017; Raileanu and Rocktäschel, 2020; Grigsby and Qi, 2020; Kuttler et al., 2020) have studied this issue of overfitting in reinforcement learning by training and testing RL agents on different sets of environments and showing a performance gap. (Dubey et al., 2018) compared generalization in RL agents with generalization in humans and showed that the superior generalization ability in humans comes from visual priors (such as object segmentation and recognition, object permanence, intuitive physics, etc.) learned throughout their life. In our work, we try to understand the reasons behind the generalization gap in RL agents by performing empirical studies on Procgen (Cobbe et al., 2019) games, a suite of 16 visually diverse procedurally generated games. Furthermore, based on these empirical studies, we point to interesting avenues for future work that could help us further reduce this performance gap.

Learning Generalizable Policies in Reinforcement Learning. There have been many recent works which try to solve the issue of over-fitting in RL and learn a generalizable policy. (Cobbe et al., 2018; 2019) showed that classical techniques such as dropout (Srivastava et al., 2014), L2 regularization, and batch normalization (Ioffe and Szegedy, 2015) – originally developed for supervised learning – reduce the generalization gap in RL. Other works (Michael et al., 2020; Cobbe et al., 2018; Ye et al., 2019; Raileanu et al., 2020; Wang et al., 2020) have made use of data augmentation to learn policies that generalize well. Another popular approach is to use representation learning techniques such as variational information bottleneck (Igl et al., 2019) and bisimulation metrics (Agarwal et al., 2021; Zhang et al., 2020) to help with the problem of overfitting in RL. (Cobbe et al., 2020; Raileanu and Fergus, 2021) learned a separate network for policy and value function and showed that it helps reduce the generalization gap in RL. (Sax et al., 2018) showed that using mid-level visual features, such as segmentation, depth, keypoints, surface normals and others, as input to policy leads to better policy transfer. In our work, rather than proposing a novel approach to solve the issue of overfitting in RL, we try to understand the reasons behind the generalization issue through empirical studies, the gains made so far by state of the art methods (UCB-DrAC (Raileanu et al., 2020), DAAC/iDAAC (Raileanu and Fergus, 2021)), and the challenges that remain.

REFERENCES

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Karl Cobbe, Oleg Klimov, Chris Hesse, Taehoon Kim, and John Schulman. Quantifying generalization in reinforcement learning. *arXiv preprint arXiv:1812.02341*, 2018.

Karl Cobbe, Christopher Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. *arXiv preprint arXiv:1912.01588*, 2019.

Rachit Dubey, Pulkit Agrawal, Deepak Pathak, Thomas L Griffiths, and Alexei A Efros. Investigating human priors for playing video games. *arXiv preprint arXiv:1802.10217*, 2018.

Alexander Sax, Bradley Emi, Amir R Zamir, Leonidas Guibas, Silvio Savarese, and Jitendra Malik. Mid-level visual representations improve generalization and sample efficiency for learning visuomotor policies. *arXiv preprint arXiv:1812.11971*, 2018.

Laskin Michael, Lee Kimin, Stooke Adam, Pinto Lerrel, Abbeel Pieter, and Srinivas Aravind. Reinforcement learning with augmented data. *ArXiv*, abs/2004.14990, 2020.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

Roberta Raileanu, M. Goldstein, Denis Yarats, Ilya Kostrikov, and R. Fergus. Automatic data augmentation for generalization in deep reinforcement learning. *ArXiv*, abs/2006.12862, 2020.

Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

Eric Tzeng, Judy Hoffman, Ning Zhang, Kate Saenko, and Trevor Darrell. Deep domain confusion: Maximizing for domain invariance. *arXiv preprint arXiv:1412.3474*, 2014.

Eric Tzeng, Judy Hoffman, Trevor Darrell, and Kate Saenko. Simultaneous deep transfer across domains and tasks. In *Proceedings of the IEEE international conference on computer vision*, pages 4068–4076, 2015.

Judy Hoffman, Erik Rodner, Jeff Donahue, Trevor Darrell, and Kate Saenko. Efficient learning of domain-invariant image representations. *arXiv preprint arXiv:1301.3224*, 2013.

Roberta Raileanu and Rob Fergus. Decoupling value and policy for generalization in reinforcement learning. *arXiv preprint arXiv:2102.10330*, 2021.

Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

Aravind Srinivas, Michael Laskin, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. *ArXiv*, abs/2004.04136, 2020.

Pulkit Agrawal, Ashvin Nair, Pieter Abbeel, Jitendra Malik, and Sergey Levine. Learning to poke by poking: Experiential learning of intuitive physics. *arXiv preprint arXiv:1606.07419*, 2016.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Volodymir Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. *arXiv preprint arXiv:1802.01561*, 2018.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Ilya Kostrikov. Pytorch implementations of reinforcement learning algorithms. https://github.com/ikostrikov/pytorch-a2c-ppo-acktr-gail, 2018.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pages 2778–2787. PMLR, 2017.

Deepak Pathak, Parsa Mahmoudieh, Guanghao Luo, Pulkit Agrawal, Dian Chen, Yide Shentu, Evan Shelhamer, Jitendra Malik, Alexei A Efros, and Trevor Darrell. Zero-shot visual imitation. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, pages 2050–2053, 2018.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.

Niels Justesen, Ruben Rodriguez Torrado, Philip Bontrager, Ahmed Khalifa, Julian Togelius, and Sebastian Risi. Illuminating generalization in deep reinforcement learning through procedural level generation. *arXiv preprint arXiv:1806.10729*, 2018.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *ArXiv*, abs/1806.07937, 2018a.

Chiyuan Zhang, Oriol Vinyals, Rémi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *ArXiv*, abs/1804.06893, 2018b.

Arthur Juliani, Ahmed Khalifa, Vincent-Pierre Berges, J. Harper, Hunter Henry, Adam Crespi, J. Togelius, and D. Lange. Obstacle tower: A generalization challenge in vision, control, and planning. *ArXiv*, abs/1902.01378, 2019.

Aravind Rajeswaran, Kendall Lowrey, Emanuel Todorov, and Sham M. Kakade. Towards generalization and simplicity in continuous control. *ArXiv*, abs/1703.02660, 2017.

Roberta Raileanu and Tim Rocktäschel. Ride: Rewarding impact-driven exploration for procedurally-generated environments. *ArXiv*, abs/2002.12292, 2020.

Jake Grigsby and Yanjun Qi. Measuring visual generalization in continuous control from pixels. *ArXiv*, abs/2010.06740, 2020.

Heinrich Kuttler, Nantas Nardelli, Alexander H. Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The nethack learning environment. *ArXiv*, abs/2006.13760, 2020.

Nitish Srivastava, Geoffrey E. Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *J. Mach. Learn. Res.*, 15: 1929–1958, 2014.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *ArXiv*, abs/1502.03167, 2015.

Mang Ye, Xu Zhang, Pong C. Yuen, and Shih-Fu Chang. Unsupervised embedding learning via invariant and spreading instance feature. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6203–6212, 2019.

K. Wang, Bingyi Kang, Jie Shao, and Jiashi Feng. Improving generalization in reinforcement learning with mixture regularization. *ArXiv*, abs/2010.10814, 2020.

Maximilian Igl, Kamil Ciosek, Yingzhen Li, Sebastian Tschiatschek, Cheng Zhang, Sam Devlin, and Katja Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. In *Advances in Neural Information Processing Systems*, pages 13956–13968, 2019.

Rishabh Agarwal, Marlos C. Machado, P. S. Castro, and Marc G. Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. 2021.

Amy Zhang, Clare Lyle, Shagun Sodhani, Angelos Filos, Marta Kwiatkowska, Joelle Pineau, Yarin Gal, and Doina Precup. Invariant causal prediction for block mdps. *arXiv preprint arXiv:2003.06016*, 2020.

K. Cobbe, J. Hilton, O. Klimov, and John Schulman. Phasic policy gradient. *ArXiv*, abs/2009.04416, 2020.

A PPO WITH INVERSE MODEL REGULARIZATION

PPO (Schulman et al., 2017) is an actor-critic algorithm that alternates between sampling data with environment interaction and optimizing objective function with stochastic gradient descent. Let the policy being optimizes be π_θ and the associated value function be $V_{\theta,\psi}$. PPO maximizes

$$J_{\text{PPO}} = J_{\pi_\theta} - \alpha_1 J_V + \alpha_2 S_{\pi_\theta}$$

where S_{π_θ} is the entropy for aiding exploration,

$$S_{\pi_\theta} = \mathbb{E}_{s \in \pi_{\theta_{\text{old}}}} \left[- \sum_{a \in \mathcal{A}} \pi_\theta(a|s) \log \pi_\theta(a|s) \right]$$

J_V is the value function loss,

$$J_V = \mathbb{E}_{s \in \pi_{\theta_{\text{old}}}} [(V_{\theta,\psi}(s) - V_t^{\text{target}})^2]$$

and J_{π_θ} is the policy objective term

$$J_{\pi_\theta} = \mathbb{E}_{(s,a) \in \pi_{\theta_{\text{old}}}} \left[\min(r_\theta \hat{A}, \text{clip}(r_\theta, 1 - \epsilon, 1 + \epsilon) \hat{A}) \right]$$

Here, $r_\theta = \frac{\pi_\theta(a|s)}{\pi_{\theta_{\text{old}}}(a|s)}$ is the importance weight for estimating the advantage function and $\hat{A} = \hat{A}_{\theta_{\text{old}}}(s, a)$ is estimated advantage function for $\pi_{\theta_{\text{old}}}$ using returns and value function $V_{\theta,\psi}(s)$.

We make use of inverse models to regularize policy features for improved performance and better generalization. Let $z_t = \pi_{\theta_1}^{enc}(s_t)$. If f_ϕ is the inverse model and (s_t, a_t, s_{t+1}) is the state action state tuple coming from $\pi_{\theta_{\text{old}}}$, then this regularization minimizes $J_{\text{inv}} = \mathcal{CE}(a_t, f_\phi(z_t, z_{t+1}))$ where $\mathcal{CE}$ is the cross-entropy loss. Overall, PPO with inverse model regularization maximizes

$$J_{\text{PPO}} = J_{\pi_\theta} - \alpha_1 J_V + \alpha_2 S_{\pi_\theta} - \alpha_{\text{inv}} J_{\text{inv}}$$

where α_{inv} is the regularization constant associated with inverse model regurlarization loss.

B HYPERPARAMETERS

We use the default hyperparameters from PPO (Schulman et al., 2017), UCB-DrAC (Raileanu et al., 2020) and DAAC/iDAAC (Raileanu and Fergus, 2021). DrAC-FT and DrAC-TR uses same hyperparameters as UCB-DrAC (DrAC). PPO with inverse model regularization only introduces an extra hyperparameter α_{inv}. We write all the hyperparameters in table 2 and 2. While table 3 describes the best single set of hyperparameters for different methods selected using validation levels $201 - 400$, table 3 details game-specific changes to some of those hyperparameters for improved performance.

C PROCGEN RESULTS

Table 4 and 5 describe scores on train levels (1-200) and test levels across all procgen games for PPO, UCB-DrAC, DrAC-FT (UCB-DrAC with fixed theme games), DrAC-TR (UCB-DrAC with randomized theme games), DAAC, iDAAC, and PPO inv-m (PPO with inverse model regularization). Figure 7 places games next to the RL algorithm on which they perform the best. Some games are excluded as they perform the best on two or more RL algorithm. Figures 8, 9, and 10 show the learning curves for finetuning the policy head as well as the full policy on 1k, 10k and 100k new levels respectively. The policy was originally trained on levels 1-200 with PPO. End-to-end training of policy and training of policy head with randomly initialized visual encoder on new levels are also included as baselines. Finally, table 6 and 7 give train and test accuracy of level classifier trained on the encoder features of policies learned with PPO on 200 levels, with PPO on 100k levels, with DAAC on 200 levels, and with iDAAC on 200 levels on all procgen games.

Figure 7: Visualization of games placed next to the RL algorithm on which they perform the best. Some games are excluded as they perform the best on two or more RL algorithms.

Figure 8: **Transfer**: We compare fine-tuning the policy head (Head-only) versus the entire policy network (Full) on 1k new levels. The policy is trained on 200 levels. Fine tuning just the policy head allows us to recover this performance on the training levels ([1 - 200]). We additionally include the learning curve of a policy trained from scratch (From Scratch), a policy head trained on a randomly initialized visual encoder (Head (Random)), and a policy head trained on a imagenet pretrained visual encoder (Head (ImageNet)) to show the importance of using learned visual features.

Figure 9: **Transfer**: We compare fine-tuning the policy head (Head-only) versus the entire policy network (Full) on 10k new levels. The policy is trained on 200 levels. Fine tuning only the policy head fails to recover the performance on the training levels. We additionally include the learning curve of a policy trained from scratch (From Scratch), a policy head trained on a randomly initialized visual encoder (Head (Random)), and a policy head trained on a imagenet pretrained visual encoder (Head (ImageNet)) to show the importance of using learned visual features.

Figure 10: **Transfer**: We compare fine-tuning the policy head (Head-only) versus the entire policy network (Full) on 100k new levels. The policy is trained on 200 levels. Fine tuning only the policy head fails to recover the performance on the training levels. We additionally include the learning curve of a policy trained from scratch (From Scratch), a policy head trained on a randomly initialized visual encoder (Head (Random)), and a policy head trained on a imagenet pretrained visual encoder (Head (ImageNet)) to show the importance of using learned visual features.

Table 2: Best single set of hyperparameters for PPO, UCB-DrAC, DAAC and iDAAC selected using validation levels $201 - 400$.

Hyperparameter	Value
γ	0.999
λ	0.95
# timesteps per rollout	256
# epochs per rollout	3
# minibatches per epoch	8
entropy bonus (α_2)	0.01
value loss coefficient (α_1)	0.01
clip range	0.2
reward normalization	yes
learning rate	5e-4
# workers	1
# environments per worker	64
# total timesteps	25M
optimizer	Adam
LSTM	no
frame stack	no
α_{inv}	0.4
UCB augmentation coefficient (α_r)	0.1
UCB exploration coefficient (c)	0.1
UCB window length (K)	10
# DAAC/iDAAC actor epochs per rollout	1
# DAAC/iDAAC value epochs per rollout (v_e)	9
# DAAC/iDAAC value update frequency (v_f)	1
DAAC/iDAAC advantage loss coefficient (α_a)	0.25
iDAAC order loss coefficient (α_i)	0.001

Table 3: Game-specific changes to some hyperparameters for improved performance

Hyperparameter	v_e	v_f	α_a	α_i	α_{inv}
plunder	1	8	0.3	0.1	0.4
chaser	1	1	0.15	0.001	0.1
miner	9	32	0.25	0.1	1
climber	9	1	0.05	0.001	0.01
bigfish	9	32	0.05	0.01	0.1
dodgeball	9	32	0.25	0.001	0.1
maze	9	1	0.25	0.001	0.01
leaper	9	1	0.25	0.001	0.4
fruitbot	9	1	0.25	0.001	0.04
bossfight	9	1	0.25	0.001	0.1
jumper	9	1	0.25	0.001	0.1
ninja	9	1	0.25	0.001	0.4
starpilot	9	1	0.25	0.001	0.1
coinrun	9	1	0.25	0.001	0.004
heist	9	1	0.25	0.001	0.4
caveflyer	9	1	0.25	0.001	1

Table 4: Procgen scores on train levels (1-200) after training on 25M environment steps. MNS is shorthand for median normalized score across games. The mean and standard deviation are computed using 5 different seeds.

Game	PPO	UCB-DrAC	DrAC-FT	DrAC-TR	DAAC	iDAAC	PPO inv-m
bigfish	5.3 ± 1.2	19.3 ± 1.2	27.2 ± 1.5	24.2 ± 2.0	20.1 ± 1.6	21.8 ± 1.8	17.3 ± 6.9
bossfight	8.2 ± 0.4	8.1 ± 0.8	11.0 ± 0.7	8.8 ± 0.5	10.0 ± 0.4	10.4 ± 0.4	9.0 ± 0.6
caveflyer	7.8 ± 0.4	7.2 ± 0.4	9.2 ± 1.1	8.2 ± 1.3	5.8 ± 0.4	6.2 ± 0.6	9.4 ± 0.3
chaser	6.2 ± 1.0	7.1 ± 1.0	6.9 ± 0.7	7.6 ± 0.6	6.9 ± 1.2	7.5 ± 0.8	6.6 ± 0.7
climber	8.4 ± 0.4	8.6 ± 0.3	11.9 ± 0.2	9.5 ± 0.8	10.0 ± 0.3	10.2 ± 0.7	8.8 ± 0.3
coinrun	9.5 ± 0.2	8.4 ± 1.4	8.0 ± 1.2	9.3 ± 0.1	9.8 ± 0.0	9.8 ± 0.1	9.7 ± 0.1
dodgeball	4.3 ± 0.4	9.0 ± 1.0	12.1 ± 0.5	10.2 ± 1.3	5.2 ± 0.4	4.9 ± 0.3	8.3 ± 0.8
fruitbot	30.2 ± 0.5	29.2 ± 1.1	31.0 ± 0.5	30.3 ± 0.6	29.7 ± 0.4	29.1 ± 0.7	30.5 ± 0.4
heist	7.0 ± 1.1	6.9 ± 0.6	7.0 ± 0.4	7.1 ± 1.0	5.2 ± 0.7	4.5 ± 0.3	7.1 ± 0.5
jumper	8.9 ± 0.1	8.1 ± 0.2	9.2 ± 0.1	8.8 ± 0.3	8.6 ± 0.3	8.7 ± 0.2	9.1 ± 0.1
leaper	6.1 ± 1.1	4.1 ± 2.0	6.1 ± 1.2	5.0 ± 2.7	8.0 ± 1.1	8.3 ± 0.7	9.1 ± 1.3
maze	9.5 ± 0.2	8.8 ± 0.3	9.0 ± 0.3	9.4 ± 0.4	6.6 ± 0.4	6.4 ± 0.5	9.7 ± 0.2
miner	12.7 ± 0.1	12.2 ± 0.4	12.8 ± 0.0	12.6 ± 0.1	11.3 ± 0.9	11.5 ± 0.5	12.8 ± 0.1
ninja	7.7 ± 0.3	6.7 ± 0.6	9.7 ± 0.1	9.2 ± 0.1	8.8 ± 0.2	8.9 ± 0.3	9.2 ± 0.3
plunder	5.5 ± 0.8	7.1 ± 2.0	16.0 ± 3.3	9.5 ± 2.8	22.5 ± 2.8	24.6 ± 1.6	9.0 ± 3.8
starpilot	30.3 ± 1.5	32.5 ± 3.9	40.3 ± 3.0	34.3 ± 1.9	38.0 ± 2.6	38.6 ± 2.2	36.6 ± 2.1
MNS	0.57 ± 0.05	0.55 ± 0.09	0.72 ± 0.07	0.66 ± 0.08	0.62 ± 0.06	0.63 ± 0.05	0.69 ± 0.06

Table 5: Procgen scores on test levels after training on 25M environment steps. MNS is shorthand for median normalized score across games. The mean and standard deviation are computed using 3 different seeds.

Game	PPO	UCB-DrAC	DrAC-FT	DrAC-TR	DAAC	iDAAC	PPO inv-m
bigfish	1.7 ± 0.3	15.1 ± 3.8	26.2 ± 2.2	20.9 ± 2.7	17.8 ± 1.4	18.5 ± 1.2	12.3 ± 6.2
bossfight	7.8 ± 1.1	7.3 ± 0.2	11.2 ± 0.6	9.7 ± 0.8	9.6 ± 0.5	9.8 ± 0.5	8.6 ± 1.1
caveflyer	6.0 ± 0.7	5.0 ± 0.1	7.0 ± 1.5	6.9 ± 1.2	4.6 ± 0.2	5.0 ± 0.2	7.0 ± 0.2
chaser	5.7 ± 1.0	7.1 ± 0.3	6.4 ± 0.8	6.9 ± 1.2	6.6 ± 1.2	6.8 ± 1.2	2.7 ± 0.2
climber	5.7 ± 0.7	6.9 ± 0.4	11.2 ± 0.2	8.2 ± 1.1	7.8 ± 0.2	8.3 ± 0.2	5.9 ± 1.2
coinrun	8.9 ± 0.2	7.6 ± 0.4	7.3 ± 1.4	8.4 ± 0.3	9.2 ± 0.2	9.4 ± 0.2	9.1 ± 0.1
dodgeball	1.5 ± 0.4	6.0 ± 0.7	9.4 ± 0.2	7.7 ± 0.9	3.3 ± 0.5	3.2 ± 0.5	3.8 ± 0.8
fruitbot	25.1 ± 1.0	25.6 ± 0.2	27.8 ± 1.3	27.9 ± 1.7	28.6 ± 0.6	27.9 ± 0.6	27.0 ± 1.1
heist	2.7 ± 0.4	3.2 ± 1.1	3.6 ± 2.3	3.1 ± 1.4	3.3 ± 0.2	3.5 ± 0.2	3.6 ± 0.5
jumper	5.9 ± 0.4	5.5 ± 0.3	7.7 ± 0.5	7.1 ± 0.4	6.5 ± 0.4	6.3 ± 0.4	6.3 ± 0.3
leaper	6.4 ± 1.1	4.0 ± 1.6	6.0 ± 1.7	5.5 ± 2.4	7.3 ± 1.1	7.7 ± 1.1	8.7 ± 0.6
maze	6.2 ± 0.5	6.9 ± 0.5	8.1 ± 0.2	7.1 ± 1.3	5.5 ± 0.2	5.6 ± 0.2	6.0 ± 0.7
miner	9.0 ± 0.7	9.1 ± 0.3	11.2 ± 0.4	10.0 ± 0.9	8.6 ± 0.9	9.5 ± 0.9	10.1 ± 0.4
ninja	6.2 ± 0.5	5.0 ± 0.3	9.3 ± 0.3	8.6 ± 0.4	6.8 ± 0.4	6.8 ± 0.4	6.9 ± 0.4
plunder	4.7 ± 0.5	6.0 ± 0.9	13.6 ± 2.1	8.6 ± 2.0	20.7 ± 3.3	23.3 ± 3.3	8.3 ± 3.2
starpilot	28.8 ± 3.8	31.5 ± 4.3	42.1 ± 3.5	35.0 ± 1.6	36.4 ± 2.8	37.0 ± 2.3	36.7 ± 3.0
MNS	0.36 ± 0.06	0.37 ± 0.1	0.59 ± 0.10	0.51 ± 0.11	0.48 ± 0.06	0.50 ± 0.06	0.47 ± 0.07

Table 6: Train accuracy of level classifier trained on the encoder features of policies learned with PPO on 200 levels, with PPO on 100k levels, with DAAC on 200 levels, and with iDAAC on 200 levels on all procgen games.

	PPO (200)	PPO (100k)	DAAC	iDAAC
bigfish	1.00 ± 0.01	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
bossfight	1.00 ± 0.01	0.99 ± 0.01	1.00 ± 0.00	1.00 ± 0.00
caveflyer	1.00 ± 0.00	1.00 ± 0.00	0.98 ± 0.03	1.00 ± 0.00
chaser	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
climber	0.97 ± 0.02	0.95 ± 0.01	0.97 ± 0.00	0.97 ± 0.01
coinrun	0.67 ± 0.14	0.66 ± 0.27	1.00 ± 0.00	0.98 ± 0.02
dodgeball	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
fruitbot	0.97 ± 0.00	0.90 ± 0.01	0.70 ± 0.07	0.66 ± 0.03
heist	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
jumper	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	0.99 ± 0.01
leaper	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
maze	0.99 ± 0.01	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
miner	0.92 ± 0.03	1.00 ± 0.00	0.82 ± 0.02	0.78 ± 0.03
ninja	0.75 ± 0.02	0.83 ± 0.04	0.74 ± 0.07	0.73 ± 0.03
plunder	1.00 ± 0.00	1.00 ± 0.00	0.99 ± 0.01	0.99 ± 0.00
starpilot	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00

Table 7: Test accuracy of level classifier trained on the encoder features of policies learned with PPO on 200 levels, with PPO on 100k levels, with DAAC on 200 levels, and with iDAAC on 200 levels on all procgen games.

	PPO (200)	PPO (100k)	DAAC	iDAAC
bigfish	0.94 ± 0.04	0.74 ± 0.12	0.97 ± 0.01	0.97 ± 0.01
bossfight	0.78 ± 0.03	0.69 ± 0.02	0.78 ± 0.04	0.76 ± 0.02
caveflyer	1.00 ± 0.00	0.94 ± 0.02	0.82 ± 0.03	0.80 ± 0.03
chaser	1.00 ± 0.00	0.96 ± 0.01	0.89 ± 0.03	0.85 ± 0.02
climber	0.93 ± 0.02	0.72 ± 0.02	0.85 ± 0.05	0.79 ± 0.03
coinrun	0.38 ± 0.10	0.35 ± 0.22	0.95 ± 0.03	0.92 ± 0.03
dodgeball	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	0.99 ± 0.01
fruitbot	0.92 ± 0.01	0.79 ± 0.02	0.57 ± 0.06	0.54 ± 0.03
heist	1.00 ± 0.00	1.00 ± 0.00	0.99 ± 0.00	0.99 ± 0.00
jumper	1.00 ± 0.00	0.99 ± 0.00	0.88 ± 0.04	0.89 ± 0.04
leaper	1.00 ± 0.00	1.00 ± 0.00	0.99 ± 0.01	0.98 ± 0.00
maze	0.96 ± 0.02	0.99 ± 0.00	1.00 ± 0.00	1.00 ± 0.00
miner	0.92 ± 0.03	1.00 ± 0.00	0.81 ± 0.01	0.78 ± 0.03
ninja	0.70 ± 0.04	0.74 ± 0.03	0.71 ± 0.06	0.69 ± 0.03
plunder	1.00 ± 0.00	1.00 ± 0.00	0.99 ± 0.02	0.99 ± 0.00
starpilot	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00	1.00 ± 0.00