Fast Yet Effective Graph Unlearning through Influence Analysis

ABSTRACT

Recent evolving data privacy policies and regulations have led to increasing interest in the problem of removing information from a machine learning model. In this paper, we consider Graph Neural Networks (GNNs) as the target model, and study the problem of *edge unlearning in GNNs*, i.e., learning a new GNN model as if a specified set of edges never existed in the training graph. Despite its practical importance, the problem remains elusive due to the non-convexity nature of GNNs and the large scale of the input graph. Our main technical contribution is three-fold: 1) we cast the problem of fast edge unlearning as estimating the influence of the edges to be removed and eliminating the estimated influence from the original model in one-shot; 2) we design a computationally and memory efficient algorithm named EraEdge for edge influence estimation and unlearning; 3) under standard regularity conditions, we prove that EraEdge converges to the desired model. A comprehensive set of experiments on four prominent GNN models and three benchmark graph datasets demonstrate that EraEdge achieves significant speedup gains over retraining from scratch without sacrificing the model accuracy too much. The speedup is even more outstanding on large graphs. Furthermore, EraEdge witnesses significantly higher model accuracy than the existing GNN unlearning approaches.

1 INTRODUCTION

Recent legislation such as the General Data Protection Regulation (GDPR) (Regulation, 2018), the California Consumer Privacy Act (CCPA) (Pardau, 2018), and the Personal Information Protection and Electronic Documents Act (PIPEDA) (Parliament, 2000) requires companies to remove private user data upon request. This has prompted the discussion of "right to be forgotten" (Kwak et al., 2017), which entitles users to get more control over their data by deleting it from learned models. In case a company has already used the data collected from users to train their machine learning (ML) models, these models need to be manipulated accordingly to reflect data deletion requests.

In this paper, we consider Graph Neural Networks (GNNs) that receive frequent edge removal requests as our target ML model. For example, consider a social network graph collected from an online social network platform that witnesses frequent insertion/deletion of users (nodes) and/or change of social relations between users (edges). Some of these structural changes can be accompanied with users' withdrawal requests of their data. In this paper, we only consider the requests of removing social relations (edges). Then the owner of the platform is obligated by the laws to remove the effect of the requested edges, so that the GNN models trained on the graph do not "remember" their corresponding social interactions.

In general, a naive solution to deleting user data from a trained ML model is to retrain the model on the training data which excludes the samples to be removed. However, retraining a model from scratch can be prohibitively expensive, especially for complex ML models and large training data. To address this issue, numerous efforts (Mahadevan & Mathioudakis, 2021; Brophy & Lowd, 2021; Cauwenberghs & Poggio, 2000; Cao & Yang, 2015) have been spent on designing efficient unlearning methods that can remove the effect of some particular data samples without model retraining. One of the main challenges is how to estimate the effects of a given training sample on model parameters (Golatkar et al., 2021), which has led to research focusing on simpler convex learning problem such a linear/logistic regression (Mahadevan & Mathioudakis, 2021), random forests (Brophy & Lowd, 2021), support vector machines (Cauwenberghs & Poggio, 2000) and k-means clustering (Ginart et al., 2019), for which a theoretical analysis was established. Although there have

been some initial works on unlearning in deep neural networks (Golatkar et al., 2020a;b; 2021; Guo et al., 2020), efficient unlearning in GNNs still remains an open problem. To our best knowledge, there is only one existing graph unlearning solution which is named GraphEraser (Chen et al., 2022). GraphEraser follows the basic idea of Sharded, Isolated, Sliced, and Aggregated (SISA) method (Bourtoule et al., 2021) to split the training graph into several disjoint shards and train each shard model separately. Upon receiving an unlearning request, the model provider retrains only the affected shard model. Despite its efficiency, partitioning training data into disjoint shards severely damages the graph structure and thus incurs significant loss of target model accuracy (will be shown in our empirical evaluation).

In this paper, we design an efficient edge unlearning algorithm named EraEdge which directly modifies the parameters of the pre-trained model in one shot to remove the *influence* of the requested edges from the model. By adapting the idea of treating removal of data points as upweighting these data points (Koh & Liang, 2017), we compute the influence of the requested edges on the model as the change in model parameters due to upweighting these edges. However, due to the aggregation function of GNN models, it is non-trivial to estimate the change on GNN parameters as removing an edge $e(v_i, v_j)$ could affect not only the neighbors of v_i and v_j but also on multi-hops. Thus we design a new influence derivation method that takes the aggregation effect of GNN models into consideration when estimating the change in parameters. We address several theoretical and practical challenges of influence derivation due to the non-convexity nature of GNNs.

To demonstrate the efficiency and effectiveness of EraEdge, we systematically represent the empirical trade-off space between *unlearning efficiency* (i.e., the time performance of unlearning, *model accuracy* (i.e., the quality of the unlearned model), and *unlearning efficacy* (i.e., the extent to which the unlearned model has forgotten the removed edges). Our results show that, first, while achieving similar model accuracy and unlearning efficacy as the retrained model, EraEdge is significantly faster than retraining. For example, it speeds up the training time by $5.03\times$ for GCN model on Cora dataset. The speedup is even more outstanding on larger graphs; it can be two orders of magnitude on CS graph which contains around 160K edges. Second, EraEdge outperforms GraphEraser (Chen et al., 2022) considerably in model accuracy. For example, EraEdge witnesses an increase of 50% in model accuracy on Cora dataset compared to GraphEraser. Furthermore, EraEdge is much faster than GraphEraser especially on large graphs. For instance, EraEdge is $5.8\times$ faster than GraphEraser on CS dataset.

In summary, we made the following four main contributions: 1) We cast the problem of edge unlearning as estimating the *influence* of a set of edges on GNNs while taking the aggregation effects of GNN models into consideration; 2) We design EraEdge, a computationally and memory efficient algorithm that applies a one-shot update to the original model by removing the estimated influence of the removed edges from the model; 3) We address several theoretical and practical challenges of deriving edge influence, and prove that EraEdge converges to the desired model under standard regularity conditions; 4) We perform an extensive set of experiments on four prominent GNN models and three benchmark graph datasets, and demonstrate the efficiency and effectiveness of EraEdge.

2 GRAPH NEURAL NETWORK

Given a graph $G(V, E)$ that consists of a set of nodes V and their edges E, the goal of a Graph Neural Network (GNN) model is to learn a representation vector $\vec{h}$ (embedding) for each node v in G that can be used in downstream tasks (e.g., node classification, link prediction).

A GNN model updates the node embeddings through aggregating its neighbors' representations. The embedding corresponding to each node $v_i \in V$ at layer l is updated according to v_i's graph neighborhood (typically 1-hop neighborhood). This update operation can be expressed as follows:

$$H^{(l+1)} = \sigma(\mathsf{AGGREGATE}(A, H^{(l)}, \theta^{(l)})), \tag{1}$$

where σ is an activation function, A is the ajacency matrix of the given graph G, and $\theta^{(l)}$ denotes the trainable parameters as layer l. The initial embeddings at $\ell = 0$ are set to the input features for all the nodes, i.e., $H^{(0)} = X$.

Different GNN models use different AGGREGATE functions. In this paper, we consider four representative GNN models, namely Graph Convolutional Networks (GCN) (Kipf & Welling, 2017),

Symbol	Meaning
$G(V, E)$	Original graph.
E_{UL}	The set of edges to be removed.
$E \backslash E_{\mathrm{UL}}$	Edges remained after removal of E_{UL}.
$\mathcal{A}_{\mathrm{L}}$	A GNN learning algorithm.
$\mathcal{A}_{\mathrm{UL}}$	An unlearning algorithm.
θ_{OR}	Parameters of $\mathcal{A}_{\mathrm{L}}$ trained over $G(V, E)$.
θ_{RE}	Parameters of $\mathcal{A}_{\mathrm{L}}$ (re)trained over $G(V, E \backslash E_{\mathrm{UL}})$.
θ_{UL}	Parameters of $\mathcal{A}_{\mathrm{L}}$ obtained by $\mathcal{A}_{\mathrm{UL}}$.

Table 1: Notations

GraphSAGE (Hamilton et al., 2018), graph attention networks (GAT) (Veličković et al., 2018), and Graph Isomorphism Network (GIN) (Xu et al., 2019). These models differ on their AGGREGATE functions. We ignore the details of their AGGREGATE functions as our unlearning methods are model agnostic, and thus are independent from these functions.

After K iterations of message passing, a Readout function pools the node embeddings at the last layer and produce the final prediction results. The Readout function varies by the learning tasks. In this paper, we consider node classification as the learning task and the Readout function is a softmax function.

$$\hat{\mathbf{Y}} = \mathrm{softmax}(H^{(K)}\theta^{(K)}). \tag{2}$$

The final output of the target model for node v is a vector of probabilities, each corresponding to the predicted probability (or posterior) that v is assigned to a class. We consider cross entropy loss (Cox, 1958) which is the de-facto choice for classification tasks. In the following sections, we use $\mathcal{L}(\theta; v, E)$ to denote the loss on node v for simplicity because only edges are directly manipulated.

3 FORMULATION OF EDGE UNLEARNING PROBLEM

Despite that GNNs are widely applicable to many fields, there are very few studies (Chen et al., 2022) on graph unlearning so far. In this section, we will formulate the definition of the edge unlearning problem. Table 1 lists the notations we use in the paper.

Let $\mathcal{G}$ be the set of all graphs. In this paper, we only consider undirected graphs. Let Θ be the parameter space of the GNN models. A learning algorithm $\mathcal{A}_{\mathrm{L}}$ is a function that maps an instance $G(V, E) \in \mathcal{G}$ to a parameter $\theta \in \Theta$. Let θ_{OR} be the parameters of $\mathcal{A}_{\mathrm{L}}$ trained on G. Any user can submit an edge unlearning request to remove specific edges from G. In practice, unlearning requests are often submitted sequentially. For efficiency, we assume these requests are processed in a batch. As the response to these requests, $\mathcal{A}_{\mathrm{L}}$ has to erase the impacts of these edges and produce an unlearned model. A straightforward approach is to retrain the model on $G(V, E \backslash E_{\mathrm{UL}})$ from scratch and obtain the model parameters θ_{RE}. However, due to the high computational cost of retraining, an alternative solution is to apply a *unlearning* process $\mathcal{A}_{\mathrm{UL}}$ that takes E_{UL} and θ_{OR} as the input, and outputs the *unlearned model*.

The retrained and unlearned models should be sufficiently close and ideally identical. There are two types of notations in the literature that quantify the closeness of the retrained and unlearning models: (1) *both retraining and unlearning models are indistinguishable in the parameter space*, i.e., distributions of model parameters of both retraining and unlearning models are sufficiently close, where the distance in two distributions can be measured by ℓ_2 distance (Wu et al., 2020) and KL divergence (Golatkar et al., 2020b); (2) *both models are indistinguishable in the output space*, i.e., distributions of the learning outputs by both models are sufficiently close, where the distance between two output distributions can be measured by either test accuracy (Thudi et al., 2021) or the privacy leakage of membership inference attack launched on model outputs (Graves et al., 2021; Baumhauer et al., 2020). We argue that indistinguishably of the parameter space is not suitable for GNNs due to their non-convex loss functions (Tarun et al., 2021), as small changes of the training data can cause large changes in GNN parameters. Therefore, in this paper, we consider the indistinguishability of the output space between retrained and unlearned models as our unlearning notion. Formally, we define the edge unlearning problem as follows:

Definition 1 (**Edge Unlearning Problem**). *Given a graph $G(V, E)$, a set of edges $E_{\mathrm{UL}} \subset E$ that are requested to be removed from G, and a graph learning algorithm $\mathcal{A}_{\mathrm{L}}$, an edge unlearning algorithm $\mathcal{A}_{\mathrm{UL}}$ should satisfy the following:*

$$Readout(\theta_{\mathrm{RE}}) \approx Readout(\theta_{\mathrm{UL}}), \tag{3}$$

where $\mathsf{Readout}()$ is the readout function of GNNs that maps node embeddings to the output (e.g., the probability vector of node classification). The readout function varies for different learning tasks. In this paper, we consider the softmax function (Eqn. (2)) as the readout function. There are various choices to measure the similarity between the output softmax vectors of retrained and unlearned models. We consider Jensen–Shannon divergence (JSD) in our experiments.

4 MAIN ALGORITHM: EFFICIENT EDGE UNLEARNING

Given a graph $G(V, E)$ as input, one often finds a proper model represented by θ that fits the data by minimizing an empirical loss. In this paper, we consider cross-entropy loss (Cox, 1958) for node classification as our loss function. The **or**iginal model θ_{OR} is optimized by the following:

$$\theta_{\mathrm{OR}} = \arg\min_{\theta} \frac{1}{|V|} \sum_{v \in V} \mathcal{L}(\theta; v, E). \tag{4}$$

Assuming a set of edges E_{UL} is deleted from G and the new graph after this deletion is represented by $G_{\mathrm{UL}} = G(V, E \backslash E_{\mathrm{UL}})$, **re**training the model will give us a new model parameter θ_{RE} on G_{UL}:

$$\theta_{\mathrm{RE}} = \arg\min_{\theta} \frac{1}{|V|} \sum_{v \in V} \mathcal{L}(\theta; v, E \backslash E_{\mathrm{UL}}). \tag{5}$$

Figure 1 gives an overview of our unlearning solution named EraEdge. A major difficulty, as expected, is that obtaining θ_{RE} is prohibitively slow for complex networks and large datasets. To overcome this difficulty, the aim of EraEdge is to identify an update to θ_{OR} through an analogous *one-shot unlearning update*:

$$\theta_{\mathrm{UL}} = \theta_{\mathrm{OR}} - I_{E_{\mathrm{UL}}}, \tag{6}$$

where $I_{E_{\mathrm{UL}}}$ is the *influence* of E_{UL} on the target model, i.e., the change on the model parameters by E_{UL}. In general, $I_{E_{\mathrm{UL}}}$ is a $K \times d$ matrix, where K is the number of parameters in θ_{OR} (and both θ_{RE} and θ_{UL}), and d is the dimension of each parameter (i.e. embedding). This update can be interpreted from

Figure 1: Framework of EraEdge. Orange lines indicate the process of retraining and green lines indicate unlearning.

the optimization perspective that the model forgets E_{UL} by "reversing" the influence of E_{UL} from the model. The challenge is how to quantify $I_{E_{\mathrm{UL}}}$ to achieve the unlearning objective (Eqn. (3)). Next, we discuss the details of how to compute $I_{E_{\mathrm{UL}}}$.

Existing influence functions and their inapplicability. Influence functions (Koh & Liang, 2017) enable efficient approximation of the effect of some particular training points on a mode's prediction. The general idea of influence functions is the following: let θ and $\hat{\theta}$ be the model parameters before and after removing a data point z, the new parameters $\hat{\theta}_{\epsilon, z}$ after z is removed can be computed as following:

$$\hat{\theta}_{\epsilon, z} = \arg\min_{\theta} \frac{1}{m} \sum_{z_i \neq z} \mathcal{L}(\theta; z_i) + \epsilon \mathcal{L}(\theta; z), \tag{7}$$

where m is the number of data points in the original dataset, and ϵ is a small constant. Intuitively, the influence function computes the parameters after removal of z by upweighting z on the parameters with some small ϵ.

It seemly sounds that the influence function (Eqn. (7)) can be applied to the edge unlearning setting directly by upweighting those nodes that are included in any edge in E_{UL}. However, this is incorrect as removing one edge $e(v_i, v_j)$ from the graph can affect not only the prediction of v_i and v_j but also those of neighboring nodes of v_i and v_j, due to the aggregation function of GNN models.

4.1 Theoretical Characterization of Edge Influence on GNNs

In general, an ℓ-layer GNN aggregates the information of the ℓ-hop neighborhood of each node. Thus removing an edge $e(v_i, v_j)$ will affect not only v_i and v_j but also all nodes in the ℓ-hop neighborhood of v_i and v_j. To capture such aggregation effect in derivation of edge influence, first, we define the set of nodes (denoted as V_e) that will be affected by removing an edge $e(v_i, v_j)$ as:

$$V_e = \mathcal{N}(v_i) \cup \mathcal{N}(v_j) \cup \{v_i, v_j\},$$

where $\mathcal{N}(v)$ is the set of nodes connected to v in ℓ hops. Then given a set of edges $E_{\mathrm{UL}} \subset E$ to be removed, the set of nodes $V_{E_{\mathrm{UL}}}$ that will be affected by removing E_{UL} is defined as follows:

$$V_{E_{\mathrm{UL}}} = \bigcup_{e \in E_{\mathrm{UL}}} V_e. \tag{8}$$

Next, we follow the data perturbation idea of influence functions (Koh & Liang, 2017), and compute the new parameters $\theta_{\epsilon, E_{\mathrm{UL}}}$ after the removal of E_{UL} as follows:

$$\theta_{\epsilon, V_{E_{\mathrm{UL}}}} = \arg\min_{\theta} \frac{1}{|V|} \sum_{v \in V} \mathcal{L}(\theta; v, E) + \epsilon \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta; v, E \backslash E_{\mathrm{UL}}) - \epsilon \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta; v, E). \tag{9}$$

Intuitively, Eqn. (9) approximates the effects that moving ϵ mass of perturbation on $V_{E_{\mathrm{UL}}}$ with $E \backslash E_{\mathrm{UL}}$ in place of E. Then we obtain the following theorem.

Theorem 2. *Given the parameters θ_{OR} obtained by $\mathcal{A}_{\mathrm{UL}}$ on a graph G, and the loss function $\mathcal{L}$, assume that $\mathcal{L}$ is twice-differentiable and convex in θ, then the influence of a set of edges E_{UL} is:*

$$I_{E_{\mathrm{UL}}} = -H_{\theta_{\mathrm{OR}}}^{-1} \left(\nabla_{\theta} \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta_{\mathrm{OR}}; v, E \backslash E_{\mathrm{UL}}) - \nabla_{\theta} \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta_{\mathrm{OR}}; v, E) \right) \tag{10}$$

where $H_{OR} := \nabla^2 \frac{1}{|V|} \sum_{v \in V} L(\theta_{OR}, v, E)$ is the Hessian matrix of L with respect to θ_{OR}.

The proof of Theorem 2 can be found in Appendix A.1. According to Eqn (9), removing E_{UL} is equivalent to upweighting $\epsilon = \frac{1}{|V|}$ mass of perturbation. Therefore, $\theta_{\mathrm{UL}} = \theta_{\epsilon, V_{E_{\mathrm{UL}}}}$ when $\epsilon = \frac{1}{|V|}$. Finally, we have a linear approximation of θ_{UL}:

$$\theta_{\mathrm{UL}} \approx \theta_{\mathrm{OR}} + \frac{1}{|V|} I_{E_{\mathrm{UL}}}.$$

Dealing with non-convexity of GNNs. Theorem 2 assumes the loss function is convex. Given the non-convexity nature of GNN models, it is hard to reach the global minimum in practice. As a result, the Hessian matrix $H_{\theta_{\mathrm{OR}}}$ may have negative eigenvalues. To address this issue, we adapt the damping term based solution (Koh & Liang, 2017) to prevent $H_{\theta_{\mathrm{OR}}}$ from having negative eigenvalues by adding a damping term to the Hessian matrix, i.e., $(H_{\theta_{\mathrm{OR}}} + \lambda I)$.

4.2 Time and Memory Efficient Influence Estimator

Although by Theorem 2 estimating the edge influence amounts to solving a linear system, there are several practical and theoretical challenges. First, it can well be the case that the Hessian matrix $H_{\theta_{\mathrm{OR}}}$ is non-invertible. This is because our loss function is non-convex with respect to θ. As a consequence, the linear system may even not have a solution. Second, even storing a Hessian matrix in memory (either CPU or GPU) is expensive: in our experiments, we will show that Hessian matrices are huge, e.g. the Hessian matrix on the Physics dataset has size around $10^6 \times 10^6$ which would cost 60 GB memory. Lastly, even under the promise that the linear system is feasible, computing the inverse of such a huge size matrix is prohibitive.

Our *second technical contribution* thus is an algorithm that resolves all the challenges mentioned above.

Claim 3. *There is a computationally and memory efficient algorithm to solve the linear system of $I_{E_{\mathrm{UL}}}$ in Theorem 2.*

The starting point of our algorithm is a novel perspective that solving the linear system (Eqn. (10)) can be thought of as finding a *stationary point* of the following quadratic function:

$$f(x) = \arg \min_x \frac{1}{2} x^T A x - b^T x, \tag{11}$$

with $A = H_{\theta_{\mathrm{OR}}}$ and $b = \nabla_\theta \sum_{v \in V} \mathcal{L}(\theta_{\mathrm{OR}}; v, E \backslash E_{\mathrm{UL}})$. Note that even the function $f(x)$ is non-convex, there is rich literature establishing convergence guarantee to stationary points using gradient-descent-type algorithms; see e.g. (Bertsekas, 1999).

In this paper, we will employ the conjugate gradient (CG) method which exhibits promising computational efficiency for minimizing quadratic functions (Pytlak, 2008). In fact, it was well-known that as long as the step size satisfies the Wolfe conditions (Wolfe, 1969; 1971) and the objective function is Lipschitz and bounded from below, the sequence of iterates produced by CG asymptotically converges to a stationary point of $f(x)$, which corresponds to a solution $I_{E_{\mathrm{UL}}}$ that satisfies Eqn. (10). Note that these regularity conditions are satisfied as soon as the training data are bounded. Hence, we have the following convergence guarantee.

Lemma 4 (Theorem 2.1 of (Pytlak, 2008)). *The CG method generates a sequence of iterates $\{x_t\}_{t \geq 1}$ such that $\lim_{t \to +\infty} f(x_t) = 0$. In addition, the per-iteration time complexity is $O(|x|)$ where $|x|$ denotes the dimension of x.*

We note, however, that an appealing feature of Eqn. (10) is that we do not have to find a solution with exact zero gradient. This enables us to terminate CG early by monitoring the magnitude of the gradients. Our empirical study also shows that CG can get good approximation in a small number of iterations.

In addition, we propose a memory-efficient implementation of CG, which significantly reduces the memory cost.

Lemma 5. *The CG method can be implemented using $O(|\theta|)$ memory.*

Proof. To see why the above lemma holds, recall that a key step of CG update is calculating the gradient of $f(x)$ as

$$\nabla f(x) = H_{\theta_{\mathrm{OR}}} x - \left(\nabla_\theta \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta_{\mathrm{OR}}; v, E \backslash E_{\mathrm{UL}}) - \nabla_\theta \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta_{\mathrm{OR}}; v, E) \right).$$

As $H_{\theta_{\mathrm{OR}}} \in \mathbb{R}^{|\theta| \times |\theta|}$, we can not explicitly compute $H_{\theta_{\mathrm{OR}}}$. Instead, we utilize Hessian-vector product (Pearlmutter, 1994) to approximately calculate $H_{\theta_{\mathrm{OR}}} x$ by

$$H_{\theta_{\mathrm{OR}}} x \approx \frac{g(\theta_{\mathrm{OR}} + rx) - g(\theta_{\mathrm{OR}})}{r}, \tag{12}$$

for some very small step size $r > 0$, where $g(\theta) := \nabla_\theta \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta_{\mathrm{OR}}; v, E \backslash E_{\mathrm{UL}}) - \nabla_\theta \sum_{v \in V_{E_{\mathrm{UL}}}} \mathcal{L}(\theta_{\mathrm{OR}}; v, E)$. Note that the memory cost of evaluating the function value of $g(\cdot)$ is $O(|\theta|)$. Hence, Lemma 5 follows. $\square$

Remark 6. *Observe that a trivial implementation involves storing the Hessian matrix which consumes $O(|\theta|^2)$ memory. Returning to our previous example on the Physics dataset, a trivial implementation consumes 64 GB memory, while ours only needs 8 GB memory.*

Proof of Claim 3. Claim 3 follows from Lemma 4 and Lemma 5. $\square$

5 EXPERIMENTS

In this section, we empirically verify the efficiency and effectiveness of our unlearning method.

5.1 EXPERIMENTAL SETUP

All the experiments are executed on a GPU server with NVIDIA A100 (40G). All the algorithms are implemented in Python with PyTorch. We set the damping term $\lambda = 0.01$ for all experiments. The link to the code and datasets will be available in the camera-ready version.

Datasets. We use three well-known datasets, namely **Cora** (Sen et al., 2008), **Citeseer** (Yang et al., 2016), and **CS** (Shchur et al., 2018), that are popularly used for performance evaluation of GNNs (Shchur et al., 2018; Zhang et al., 2019). The statistical information of these datasets can be found in Appendix A.2.

GNN models. We consider four representative GNN models, namely GCN (Kipf & Welling, 2017), GAT (Veličković et al., 2018), GraphSAGE (Hamilton et al., 2017), and GIN (Xu et al., 2019). We configure the GNNs with one hidden layer and a softmax output layer. All GNN models are trained for 1,000 epochs with an early-stopping condition when the validation loss is not decreasing for 20 epochs. We randomly split each graph into a training set (60%), a validation set (20%), and a test set (20%). To eliminate the possible dominant impact of node features on model performance, we randomly initialize the values of node features such that they follow the Gaussian distribution.

Metrics. We evaluate the performance of EraEdge in terms of *efficiency*, *efficacy*, and *model accuracy*: (1) **Unlearning efficiency**: we measure the running time of EraEdge and retraining time for a given set of edges; (2) **Target model accuracy**: we measure *accuracy* of node classification, i.e., the percentage of nodes that are correctly classified by the model, as the accuracy of the target model. Higher accuracy indicates better accuracy retained by the unlearned model; (3) **Unlearning efficacy**: we measure the distance between the output space of both retrained and unlearned models as the Jensen–Shannon divergence (JSD) between the posterior distributions output by these two models. Smaller JSD indicates a higher similarity between the two models in terms of their outputs.

Baselines. We consider GraphEraser (Bourtoule et al., 2021) for comparison with EraEdge. GraphEraser has two partitioning strategies denoted as *balanced LPA* (**BLPA**) and *balanced embedding k-means* (**BEKM**), We consider both BLPA and BEKM as the baseline methods. We use the same setting of number of shards as in (Chen et al., 2022) for both BLPA and BEKM.

5.2 PERFORMANCE RESULTS

We evaluate the performance of EraEdge on four representative GNN models and three graph datasets, and compare the performance of the unlearned model with both the retrained model and two baselines in terms of model accuracy, unlearning efficiency, and unlearning efficacy.

Model accuracy. We report the results of GNN model accuracy in Table 2 (*Accuracy* column) for GCN+Cora and GraphSAGE+CS settings. The results for other settings can be found in Appendix A.3. We have the following observations. First, the model accuracy obtained by EraEdge stays very close to that of the retrained model, regardless of the number of the removed edges. The difference in model accuracy between retrained and unlearned models remains negligible (in range of [0.48%, 0.52%] and [0.01%, 0.2%] for the two settings respectively). Second, EraEdge witnesses significantly higher model accuracy compared to the two baseline approaches, especially for the GCN+Cora setting. For example, both BEKM and BLPA only can deliver the model accuracy as around 48% when removing 200 edges under the GCN+Cora setting. This shows that unlearning through graph partitioning can bring significant loss of target model accuracy. Meanwhile EraEdge demonstrates that the model accuracy can be as high as ∼79% (65% improvement).

Unlearning efficiency. We report the time performance results of EraEdge and retraining in Table 2 (*Running time.* column) for GCN+Cora and GraphSAGE+CS settings. The results of other settings can be found in Appendix A.3. We measure the running time of the two baselines as the average training time per shard, as all shards are trained in parallel. The most important observation is that EraEdge is significantly faster than retraining. For example, it speeds up the training time by $5\times$ under GCN+Cora setting when removing 1,000 edges, and $77\times$ under GraphSAGE+CS setting when removing 2,000 edges. Furthermore, EraEdge is much faster than the two baselines especially when training large graphs. For example, EraEdge is $5.8\times$ faster than BLPA and $3.5\times$ faster than BEKM under the GraphSAGE+CS setting when 2,000 edges were removed.

Unlearning efficacy. Figure 2 plots the results of unlearning efficacy which is measured as the JSD between the posterior probability output by both retraining and unlearning models. We observe

Table 2: **Performance of EraEdge, retrained models, and two baselines**. Different metrics are used to evaluate the performance, including the node classification accuracy of the retraining/unlearning model and running time. Each experiment is repeated 10 times. The results show that: (1) EraEdge is significantly faster than retraining while maintaining similar model accuracy; (2) EraEdge outperforms the baseline methods in model accuracy.

	# of Removed edges	Method	Accuracy (%)	Running time (s)
GCN + Cora	200	Retrain	79.06 ± 0.67	3.83 ± 0.44
		BLPA	48.06 ± 2.14	0.55 ± 0.11
		BEKM	47.86 ± 2.12	0.56 ± 0.11
		EraEdge	78.54 ± 0.78	0.90 ± 0.18
	1,000	Retrain	75.24 ± 1.22	4.48 ± 0.78
		BLPA	54.74 ± 3.64	0.81 ± 0.15
		BEKM	54.80 ± 3.60	0.54 ± 0.05
		EraEdge	74.76 ± 1.73	0.89 ± 0.11
GraphSAGE + CS	2,000	Retrain	87.19 ± 0.22	61.15 ± 4.40
		BLPA	80.03 ± 0.86	5.38 ± 1.30
		BEKM	80.80 ± 4.90	3.53 ± 0.54
		EraEdge	87.14 ± 0.21	0.79 ± 0.35
	10,000	Retrain	85.52 ± 0.26	57.13 ± 3.51
		BLPA	80.25 ± 0.76	6.20 ± 0.70
		BEKM	79.88 ± 4.59	4.01 ± 0.36
		EraEdge	85.57 ± 0.33	0.91 ± 0.43

Figure 2: **Unlearning efficacy**. We measure unlearning efficacy as the average JSD between the posterior distributions output by the retrained and unlearned models. Each experiment is repeated 10 times, where a different set of edges was sampled randomly for removal each time. The results show that the unlearned model is very close to the retrained model in the output space.

that JSD remains insignificant (at most 0.02) in all the settings. Furthermore, JSD stays relatively stable when the number of removed edges increase. This demonstrates the efficacy of EraEdge - it remains close to the retraining model even when a large number of edges is removed.

Main takeaway. While demonstrating similar accuracy as retraining, EraEdge is significantly faster than retraining, where the speedup gain becomes more outstanding when more edges are removed. Furthermore, EraEdge outperforms the baseline approaches considerably in both model accuracy and time performance.

6 RELATED WORK

Machine unlearning. Machine unlearning aims to remove some specific information from a pretrained ML model. Several attempts have been made to make unlearning more efficient than retrain-

ing from scratch. An earlier study converts ML algorithms to statistical query (SQ) learning, so that unlearning processes only need to retrain the summation of SQ learning (Cao & Yang, 2015). The concept of *SISA* (sharded, isolated, sliced, and aggregated) approach is proposed recently (Bourtoule et al., 2021) where a set of constituent models, trained on disjoint data *shards*, are aggregated to form an ensemble model. Given an unlearning request, only the affected constituent model is retrained. Alternative machine unlearning solutions directly modify the model's parameters to unlearn in a small number of updates (Guo et al., 2020; Neel et al., 2021; Sekhari et al., 2021). Recent studies have focused on various convex ML models including random forest (Brophy & Lowd, 2021; Schelter et al., 2021), k-means clustering (Ginart et al., 2019), and Bayesian inference models (Fu et al., 2021).

Machine unlearning in deep neural networks. Early work on deep machine unlearning focuses on removing the information from the network weights by imposing a condition of SGD based optimization during training (Golatkar et al., 2020a). The subsequent work (Golatkar et al., 2020b) estimates the network weights for the unlearned mode. However, all these methods suffer from high computational costs and constraints on the training process (Tarun et al., 2021). The *amnesiac unlearning* approach (Graves et al., 2021) focuses on Convolutional Neural Networks. It cancels parameter updates from only the batches containing the removed data. However, it assumes that the data to be removed is known before the training of the original model, which does not hold in our setting where edge removal requests are unknown and unpredictable. There also has been recent empirical and theoretical work in developing deep network unlearning in the application domain of computer vision (Du et al., 2019; Nguyen et al., 2020). To our best knowledge, *GraphEraser* (Chen et al., 2022) is the only work that considers unlearning in GNNs. It follows the SISA approach (Bourtoule et al., 2021) and splits graph into disjoint partitions (shards). Upon receiving an unlearning request, only the model on the affected shards is retrained. However, as splitting the training graph into disjoint partitions will damage the original graph structure, GraphEraser could downgrade the accuracy of the unlearned model significantly, especially when a large number of edges is to be removed. This has been demonstrated in our experiments.

Explanations of deep ML models by influence functions. One of the challenges of deep ML models is its non-transparency that hinders understanding of the prediction results. Recent works (Koh & Liang, 2017) adapt the concept of *influence function* - a classic technique from robust statistics — to formalize the impact of a training point on a prediction. Broadly speaking, the influence function attempts to estimate the change in the model's predictions if a particular training point is removed. Very recently, the concept of influence function has been extended to GNNs. For instance, influence functions are designed for GNNs to measure feature-label influence and label influence (Wang et al., 2019). Node-pair influence, i.e., the change in the prediction for node u if the features of the other node v are reweighted, is also studied (Wu et al., 2022). Unlike these works, we estimate the edge influence, i.e., the effect of removing particular edges on GNN models.

7 CONCLUSION

In this work, we study the problem of edge unlearning that aims to remove a set of target edges from GNNs. We design an approximate unlearning algorithm named EraEdge which enables fast yet effective edge unlearning in GNNs. An extensive set of experiments on four representative GNN models and three benchmark graph datasets demonstrates that EraEdge can achieve significant speedup gains over retraining without sacrificing the model accuracy too much.

There are several research directions for the future work. First, while EraEdge only considers edge unlearning, it can be easily extended to handle node unlearning, as removing a node v from a graph is equivalent to removing all the edges that connect with v in the graph. We will investigate the feasibility and performance of node unlearning through EraEdge. Second, an important metric of unlearning performance is *unlearning capacity*, i.e., the maximum number of edges that can be deleted while still ensuring good model accuracy. We will investigate how EraEdge can be tuned to meet the capacity requirement. Third, we will extend the study to a relevant topic, *continual learning* (CL), which studies how to learn from an infinite stream of data, so that the acquired knowledge can be used for future learning (Chen & Liu, 2018). An interesting question is how to support both continual learning (Chen & Liu, 2018) and private unlearning (CLPU) (Liu et al., 2022), i.e., the model learns and remembers permanently the data samples at large, and forgets specific samples completely and privately. We will explore how to extend EraEdge to support CLPU.

REFERENCES

Thomas Baumhauer, Pascal Schöttle, and Matthias Zeppelzauer. Machine unlearning: Linear filtration for logit-based classifiers. *arXiv preprint arXiv:2002.02730*, 2020.

Dimitri P. Bertsekas. *Nonlinear Programming*. Massachusetts: Athena Scientific, 1999.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *Symposium on Security and Privacy (SP)*, pp. 141–159, 2021.

Jonathan Brophy and Daniel Lowd. Machine unlearning for random forests. In *International Conference on Machine Learning*, pp. 1092–1104. Proceedings of Machine Learning Research, 2021.

Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In *Symposium on Security and Privacy*, pp. 463–480, 2015.

Gert Cauwenberghs and Tomaso Poggio. Incremental and decremental support vector machine learning. *Advances in neural information processing systems*, 13, 2000.

Min Chen, Zhikun Zhang, Tianhao Wang, Michael Backes, Mathias Humbert, and Yang Zhang. Graph unlearning. In *ACM Conference on Computer and Communications Security (CCS)*, 2022.

Zhiyuan Chen and Bing Liu. Lifelong machine learning. *Synthesis Lectures on Artificial Intelligence and Machine Learning*, 12(3):1–207, 2018.

David R Cox. The regression analysis of binary sequences. *Journal of the Royal Statistical Society: Series B (Methodological)*, 20(2):215–232, 1958.

Min Du, Zhi Chen, Chang Liu, Rajvardhan Oak, and Dawn Song. Lifelong anomaly detection through unlearning. In *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, pp. 1283–1297, 2019.

Shaopeng Fu, Fengxiang He, and Dacheng Tao. Knowledge removal in sampling-based bayesian inference. In *International Conference on Learning Representations*, 2021.

Antonio Ginart, Melody Guan, Gregory Valiant, and James Y Zou. Making ai forget you: Data deletion in machine learning. *Advances in Neural Information Processing Systems*, 32, 2019.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Eternal sunshine of the spotless net: Selective forgetting in deep networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9304–9312, 2020a.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Forgetting outside the box: Scrubbing deep networks of information accessible from input-output observations. In *European Conference on Computer Vision*, pp. 383–398, 2020b.

Aditya Golatkar, Alessandro Achille, Avinash Ravichandran, Marzia Polito, and Stefano Soatto. Mixed-privacy forgetting in deep networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 792–801, 2021.

Laura Graves, Vineel Nagisetty, and Vijay Ganesh. Amnesiac machine learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 11516–11524, 2021.

Chuan Guo, Tom Goldstein, Awni Hannun, and Laurens Van Der Maaten. Certified data removal from machine learning models. In *International Conference on Machine Learning*, pp. 3832–3842, 2020.

Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in neural information processing systems*, 30, 2017.

William L. Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Annual Conference on Neural Information Processing Systems*, 2018.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR*, 2017.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International Conference on Machine Learning*, pp. 1885–1894, 2017.

Chanhee Kwak, Junyeong Lee, Kyuhong Park, and Heeseok Lee. Let machines unlearn–machine unlearning and the right to be forgotten. In *America's Conference on Information Systems (AMCIS)*, 2017.

Bo Liu, Qiang Liu, and Peter Stone. Continual learning and private unlearning. *arXiv preprint arXiv:2203.12817*, 2022.

Ananth Mahadevan and Michael Mathioudakis. Certifiable machine unlearning for linear models. *arXiv preprint arXiv:2106.15093*, 2021.

Seth Neel, Aaron Roth, and Saeed Sharifi-Malvajerdi. Descent-to-delete: Gradient-based methods for machine unlearning. In *Algorithmic Learning Theory*, pp. 931–962, 2021.

Quoc Phong Nguyen, Bryan Kian Hsiang Low, and Patrick Jaillet. Variational bayesian unlearning. *Advances in Neural Information Processing Systems*, 33:16025–16036, 2020.

Stuart L Pardau. The california consumer privacy act: Towards a european-style privacy regime in the united states. *J. Tech. L. & Pol'y*, 23:68, 2018.

Canadian Parliament. Personal information protection and electronic documents act. *Consolidated Acts, SC 2000, c*, 5:13, 2000.

Barak A Pearlmutter. Fast exact multiplication by the hessian. *Neural computation*, 6(1):147–160, 1994.

Radoslaw Pytlak. *Conjugate gradient algorithms in nonconvex optimization*, volume 89. Springer Science & Business Media, 2008.

General Data Protection Regulation. General data protection regulation (gdpr). *Intersoft Consulting, Accessed in October*, 24(1), 2018.

Sebastian Schelter, Stefan Grafberger, and Ted Dunning. Hedgecut: Maintaining randomised trees for low-latency machine unlearning. In *Proceedings of the International Conference on Management of Data*, pp. 1545–1557, 2021.

Ayush Sekhari, Jayadev Acharya, Gautam Kamath, and Ananda Theertha Suresh. Remember what you want to forget: Algorithms for machine unlearning. *Advances in Neural Information Processing Systems*, 34, 2021.

Prithviraj Sen, Galileo Mark Namata, Mustafa Bilgic, Lise Getoor, Brian Gallagher, and Tina Eliassi-Rad. Collective classification in network data. *AI Magazine*, 29(3):93–106, 2008.

Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. *arXiv preprint arXiv:1811.05868*, 2018.

Ayush K Tarun, Vikram S Chundawat, Murari Mandal, and Mohan Kankanhalli. Fast yet effective machine unlearning. *arXiv preprint arXiv:2111.08947*, 2021.

Anvith Thudi, Gabriel Deza, Varun Chandrasekaran, and Nicolas Papernot. Unrolling sgd: Understanding factors influencing machine unlearning. *arXiv preprint arXiv:2109.13398*, 2021.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *International Conference on Learning Representations*, 2018.

Yaojing Wang, Yuan Yao, Hanghang Tong, Feng Xu, and Jian Lu. Discerning edge influence for network embedding. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, pp. 429–438, 2019.

Philip Wolfe. Convergence conditions for ascent methods. *SIAM review*, 11(2):226–235, 1969.

Philip Wolfe. Convergence conditions for ascent methods. ii: Some corrections. *SIAM review*, 13 (2):185–188, 1971.

Fan Wu, Yunhui Long, Ce Zhang, and Bo Li. Linkteller: Recovering private edges from graph neural networks via influence analysis. In *Symposium on Security and Privacy (SP)*, 2022.

Yinjun Wu, Edgar Dobriban, and Susan Davidson. Deltagrad: Rapid retraining of machine learning models. In *International Conference on Machine Learning*, pp. 10355–10366, 2020.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations*, 2019.

Zhilin Yang, William Cohen, and Ruslan Salakhudinov. Revisiting semi-supervised learning with graph embeddings. In *International conference on machine learning*, pp. 40–48, 2016.

Chuxu Zhang, Dongjin Song, Chao Huang, Ananthram Swami, and Nitesh V Chawla. Heterogeneous graph neural network. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 793–803, 2019.

Dataset	#. Features	#. Nodes	#. Edges	#. Classes	Min Degree	Max Degree	Avg. Degree
Cora	1,433	2,708	5,429	7	2	198	21.82
CiteSeer	3,703	3,327	4,552	6	2	126	13.83
CS	6,805	18,333	163,788	15	3	262	36.43

Table 3: Description of datasets

A APPENDIX

A.1 PROOF OF THEOREM 2

Proof. For simplicity, we first define

$$R(\theta, V, E) = \sum_{v \in V} L(\theta, v, E). \tag{13}$$

Then, we formulate a GNN learning process as

$$\theta_{\mathrm{OR}} = \arg\min_{\theta} \frac{1}{|V|} R(\theta, V, E). \tag{14}$$

Since removing edges can be considered as perturbing the input, we introduce Eqn 9,

$$\theta_{\epsilon} = \arg\min_{\theta} \frac{1}{|V|} \sum_{v \in V} L(\theta; v, E) + \epsilon \sum_{v \in V_{E_{\mathrm{UL}}}} L(\theta; v, E \backslash E_{\mathrm{UL}}) - \epsilon \sum_{v \in V_{E_{\mathrm{UL}}}} L(\theta; v, E)$$

$$= \arg\min_{\theta} \frac{1}{|V|} R(\theta, V, E) + \epsilon R(\theta, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \epsilon R(\theta, V_{E_{\mathrm{UL}}}, E). \tag{15}$$

We note a necessary condition is that the gradient of Eqn 15 at θ_{ϵ} is zero. Then, we have

$$0 = \frac{1}{|V|} \nabla_{\theta} R(\theta_{\epsilon}, V, E) + \epsilon \nabla_{\theta} R(\theta_{\epsilon}, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \epsilon \nabla_{\theta} R(\theta_{\epsilon}, V_{E_{\mathrm{UL}}}, E). \tag{16}$$

Next, we apply Taylor series at θ_{OR} and we get

$$0 \approx \frac{1}{|V|} \nabla_{\theta} R(\theta_{\mathrm{OR}}, V, E) + \epsilon \nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \epsilon \nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E)$$

$$+ \Big[\frac{1}{|V|} \nabla_{\theta}^2 R(\theta_{\mathrm{OR}}, V, E) + \epsilon \nabla_{\theta}^2 R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \epsilon \nabla_{\theta}^2 R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E) \Big] (\theta_{\epsilon} - \theta_{\mathrm{OR}}),$$

$$\tag{17}$$

where we have dropped $o(\theta_{\mathrm{OR}} - \theta_{\epsilon})$ for approximation. Then Eqn (17) is a linear system of E_{UL}, the influence of E_{UL}. Since θ_{OR} is the minimum of Eqn (14), we have $\frac{1}{|V|} \nabla R(\theta_{\mathrm{OR}}, V, E) = 0$. As ϵ is a small value, we drop the two $o(\epsilon)$ terms and have the following:

$$\frac{1}{|V|} \nabla_{\theta}^2 R(\theta_{\mathrm{OR}}, V, E)(\theta_{\epsilon} - \theta_{\mathrm{OR}}) + \epsilon \Big(\nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E) \Big) \approx 0. \tag{18}$$

Suppose Eqn (14) is convex, then

$$\theta_{\epsilon} - \theta_{\mathrm{OR}} \approx -\frac{1}{|V|} \nabla_{\theta}^2 R(\theta_{\mathrm{OR}}, V, E)^{-1} \Big(\nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E) \Big) \epsilon \tag{19}$$

Denote

$$I_{E_{\mathrm{UL}}} := \frac{d(\theta_{\epsilon} - \theta_{\mathrm{OR}})}{d\epsilon} \Big|_{\epsilon=0} = -H_{\theta_{\mathrm{OR}}}^{-1} \Big(\nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E \backslash E_{\mathrm{UL}}) - \nabla_{\theta} R(\theta_{\mathrm{OR}}, V_{E_{\mathrm{UL}}}, E) \Big) \tag{20}$$

where $H_{OR} := \nabla^2 \frac{1}{|V|} \sum_{v \in V} L(\theta_{OR}, v, E)$. $\qquad\square$

Figure 3: **Unlearning efficiency**. The results show that EraEdge speeds up the training time significantly compared with retraining.

A.2   DESCRIPTION OF DATASETS

Table 3 summarizes the statistical information of the three graph datasets (Cora, Citeseer, and CS) we used in the experiments. Cora and Citeseer datasets are citation graphs, while CS dataset is a co-author graph.

A.3   ADDITIONAL PERFORMANCE RESULTS

Model efficiency. Figure 3 presents the model efficiency results on the three datasets. We observe that EraEdge is significantly faster than retraining. For example, EraEdge outperforms by 9.95$\times$, 5.41$\times$, 69.36$\times$, and 3.12$\times$ on CS dataset respectively over retraining (Figure 3 (c), (f), (i), and (l)).

Figure 4: **Accuracy of the target GNN model after retraining/unlearning**. The results show that EraEdge still maintains a competitive model accuracy which is close to that of the retraining model.

Model accuracy. Figure 4 presents the results of model accuracy for all settings. First, the accuracy of the target model by EraEdge is very close to that by the retrained model. In particular, the average difference in model accuracy between retrained and unlearned models are in the range of [0.11%, 0.68%], [0.02%, 0.74%], [0.06%, 0.65%] and [0.07%, 1.00%] for GCN, GAT, GraphSAGE, and GIN on Cora, [0.01%, 0.71%], [0.05%, 0.44%], [0.05%, 0.65%], and [0.02%, 1.25%] on CiteSeer, and [0.02%, 0.22%], [0.01%, 0.20%, [0.05%, 0.23%], and [0.01%, 0.22%] on CS, respectively. Furthermore, the model accuracy of the unlearned model stays close to that of the retrained model, regardless of the number of removed edges. This demonstrates that EraEdge can handle the removal of a large number of edges.