Biologically-Plausible Determinant Maximization Neural Networks for Blind Separation of Correlated Sources

Abstract

Extraction of latent sources of complex stimuli is critical for making sense of the world. While the brain solves this blind source separation (BSS) problem continuously, its algorithms remain unknown. Previous work on biologically-plausible BSS algorithms assumed that observed signals are linear mixtures of statistically independent or uncorrelated sources, limiting the domain of applicability of these algorithms. To overcome this limitation, we propose novel biologically-plausible neural networks for the blind separation of potentially dependent/correlated sources. Differing from previous work, we assume some general geometric, not statistical, conditions on the source vectors allowing separation of potentially dependent/correlated sources. Concretely, we assume that the source vectors are sufficiently scattered in their domains which can be described by certain polytopes. Then, we consider recovery of these sources by the Det-Max criterion, which maximizes the determinant of the output correlation matrix to enforce a similar spread for the source estimates. Starting from this normative principle, and using a weighted similarity matching approach that enables arbitrary linear transformations adaptable by local learning rules, we derive two-layer biologically-plausible neural network algorithms that can separate mixtures into sources coming from a variety of source domains. We demonstrate that our algorithms outperform other biologically-plausible BSS algorithms on correlated source separation problems.

1 Introduction

Our brains constantly and effortlessly extract latent causes, or sources, of complex visual, auditory or olfactory stimuli sensed by sensory organs [1–11]. This extraction is mostly done without any instruction, in an unsupervised manner, making the process an instance of the blind source separation (BSS) problem [12, 13]. Indeed, visual and auditory cortical receptive fields were argued to be the result of performing BSS on natural images [1, 2] and sounds [4]. The wide-spread use of BSS in the brain suggests the existence of generic circuit motifs that perform this task [14]. Consequently, the literature on biologically-plausible neural network algorithms for BSS is growing [15–19].

Because BSS is an underdetermined inverse problem, BSS algorithms make generative assumptions on observations. In most instances of the biologically-plausible BSS algorithms, complex stimuli are assumed to be linear mixtures of latent sources. This assumption is particularly fruitful and is used to model, for example, natural images [1, 20], and responses of olfactory neurons to complex odorants [21–23]. However, linear mixing by itself is not sufficient for source identifiability; further assumptions are needed. Previous work on biologically-plausible algorithms for BSS of linear mixtures assumed sources to be statistically independent [17, 19] or uncorrelated [16, 18]. However, these assumptions are very limiting when considering real data where sources can themselves be correlated.

(a) $\mathcal{B}_{\ell_1}$ (sparse) (b) $\mathcal{B}_{\ell_\infty}$ (anti-sparse) (c) Δ (normalized nonnegative) (d) $\mathcal{B}_{\ell_\infty,+}$ (nonnegative anti-sparse) (e) $\mathcal{B}_{\ell_1,+}$ (nonnegative sparse)

Figure 1: Examples of source domains leading to identifiable generative models.

In this paper, we address the limitation imposed by independence assumptions and provide biologically-plausible BSS neural networks that can separate potentially correlated sources. We achieve this by considering various general geometric identifiability conditions on sources instead of statistical assumptions like independence or uncorrelatedness. In particular, 1) we make natural assumptions on the domains of source vectors–like nonnegativity, sparsity, anti-sparsity or bounded-ness (Figure 1)–and 2) we assume that latent source vectors are sufficiently spread in their domain [24, 25]. Because these identifiability conditions are not stochastic in nature, our neural networks are able to separate both independent and dependent sources.

We derive our biologically-plausible algorithms from a normative principle. A common method for exploiting our geometric identifiability conditions is to disperse latent vector estimates across their presumed domain by maximizing the determinant of their sample correlation matrix, i.e., the Det-Max approach [24, 26–29]. Starting from a Det-Max objective function with constraints that specify the domain of source vectors, and using mathematical tools introduced for mapping optimization algorithms to adaptive Hebbian neural networks [18, 30, 31], we derive two-layered neural networks that can separate potentially correlated sources from their linear mixtures (Figure 2). These networks contain feedforward, recurrent and feedback synaptic connections updated via Hebbian or anti-Hebbian update rules. The domain of latent sources determines the structure of the output layer of the neural network (Figure 2, Table 1 and Appendix D).

In summary, our main contributions in this article are the following:

- We propose a normative framework for generating biologically plausible neural networks that are capable of separating correlated sources from their mixtures by deriving them from a Det-Max objective function subject to source domain constraints.
- Our framework can handle infinitely many source types by exploiting their source domain topology.
- We demonstrate the performance of our networks in simulations with synthetic and realistic data.

(a) General source domain with sparse components (b) Antisparse sources

Figure 2: Det-Max WSM neural network for blind source separation. The network takes a mixed input $\mathbf{x}$ and produces latent components $\mathbf{y}$ at the output. The output layer depends on the choice of source domain. Mutually sparse components are connected by inhibitory neurons at the output layer.

1.1 Other related work

Several algorithms for separation of linearly mixed and correlated sources have been proposed outside the domain of biologically-plausible BSS. These algorithms make other forms of assumptions on the latent sources. Nonnegative matrix factorization (NMF) assumes that the latent vectors are nonnegative [13, 32–34]. Simplex structured matrix factorization (SSMF) assumes that the latent vectors are members of the unit-simplex [24, 35, 36]. Sparse component analysis (SCA) often assumes that the latent vectors lie in the unity ℓ_1-norm-ball [29, 37–41]. Antisparse bounded component analysis (BCA) assumes latent vectors are in the ℓ_∞-norm-ball [27, 28, 42]. Recently introduced polytopic matrix factorization (PMF) extends the identifiability-enabling domains to infinitely many polytopes obeying a particular symmetry restriction [25, 43, 44].

The mapping of optimization algorithms to biologically-plausible neural networks have been formalized in the similarity matching framework [30, 31, 45, 46]. Several BSS algorithms were proposed within this framework: 1) Nonnegative Similarity Matching (NSM) [16, 47] separates linear mixtures of uncorrelated nonnegative sources, 2) [19] separates independent sources, and 3) Bounded Similarity Matching (BSM) separates uncorrelated anti-sparse bounded sources from ℓ_∞-norm-ball [18]. BSM introduced a weighted inner product-based similarity criterion, referred to as the weighted similarity matching (WSM). Compared to these algorithm, the neural network algorithms we propose in this article 1) cover more general source domains, 2) handle potentially correlated sources, 3) use a two-layer WSM architecture (relative to single layer WSM architecture of BSM, which is not capable of generating arbitrary linear transformations) and 4) offer a general framework for neural-network-based optimization of the Det-Max criterion.

2 Problem statement

2.1 Sources

We assume that there are n real-valued sources, represented by the vector $\mathbf{s} \in \mathcal{P}$, where $\mathcal{P}$ is a particular subset of $\mathbb{R}^n$. Our algorithms will address a wide range of source domains. We list some examples before giving a more general criterion:

- *Bounded sparse sources*: A natural convex domain choice for sparse sources is the unit ℓ_1 norm ball $\mathcal{B}_{\ell_1} = \{\mathbf{s} \mid \|\mathbf{s}\|_1 \leq 1\}$ (Figure 1.(a)). The use of ℓ_1-norm as a convex (non)sparsity measure has been quite successful with various applications including sparse dictionary learning/component analysis [29, 38, 40, 48, 49] and modeling of V1 receptive fields [2].

- *Bounded anti-sparse sources*: A common domain choice for anti-sparse sources is the unit ℓ_∞-norm-ball: $\mathcal{B}_{\ell_\infty} = \{\mathbf{s} \mid \|\mathbf{s}\|_\infty \leq 1\}$ (Figure 1.(b)). If vectors drawn from $\mathcal{B}_{\ell_\infty}$ are well-spread inside this set, some samples would contain near-peak magnitude values simultaneously at all their components. The potential equal spreading of values among the components justifies the term "anti-sparse" [50] or "democratic" [51] component representations. This choice is well-suited for both applications in natural images and digital communication constellations [27, 42].

- *Normalized nonnegative sources*: Simplex structured matrix factorization [24, 35, 36] uses the unit simplex [34, 52] $\Delta = \{\mathbf{s} \mid \mathbf{s} \geq 0, \mathbf{1}^T\mathbf{s} = 1\}$ (Figure 1.(c)) as the source domain. Nonnegativity of sources naturally arises in biological context, for example in demixing olfactory mixtures [53].

- *Nonnegative bounded anti-sparse sources*: A non-degenerate polytopic choice of the nonnegative sources can be obtained through the combination of anti-sparseness and nonnegativity constraints. This corresponds to the intersection of $\mathcal{B}_{\ell_\infty}$ with the nonnegative orthant $\mathbb{R}_+^n$, represented as $\mathcal{B}_{\ell_\infty,+} = \mathcal{B}_{\ell_\infty} \cap \mathbb{R}_+^n$ [25] (Figure 1.(d)).

- *Nonnegative bounded sparse sources*: Another polytopic choice for nonnegative sources can be obtained through combination of the sparsity and nonnegativity constraints which yields the intersection of $\mathcal{B}_{\ell_1}$ with the nonnegative orthant $\mathbb{R}_+$, [25]: $\mathcal{B}_{\ell_1,+} = \mathcal{B}_{\ell_1} \cap \mathbb{R}_+^n$ (Figure 1.(e)).

Except the unit simplex Δ, all the examples above are examples of an infinite set of identifiable polytopes whose symmetry groups are restricted to the combinations of component permutations and sign alterations as formalized in PMF framework for BSS [43]. Further, instead of a homogeneous choice of features, such as sparsity and nonnegativity, globally imposed on all elements of the component vector, we can assign these attributes at the subvector level and still obtain identifiable polytopes. For example, the reference [25] provides the set

112 $\mathcal{P}_{ex} = \left\{ \mathbf{s} \in \mathbb{R}^3 \,\middle|\, s_1, s_2 \in [-1, 1], \, s_3 \in [0, 1], \, \left\| \begin{bmatrix} s_1 \\ s_2 \end{bmatrix} \right\|_1 \leq 1, \, \left\| \begin{bmatrix} s_2 \\ s_3 \end{bmatrix} \right\|_1 \leq 1 \right\}$, as a simple il-

113 lustration of such polytopes with heterogeneous structure where s_3 is nonnegative, s_1, s_2 are signed,

114 and $\begin{bmatrix} s_1 & s_2 \end{bmatrix}^T, \begin{bmatrix} s_2 & s_3 \end{bmatrix}^T$ are sparse subvectors, while sparsity is not globally imposed. In this

115 article, we concentrate on particular source domains including the unit simplex, and the subset of

116 identifiable polytopes for which the attributes such as sparsity and nonnegativity are defined at the

117 subvector level in the general form

$$\mathcal{P} = \left\{ \mathbf{s} \in \mathbb{R}^n \,\middle|\, s_i \in [-1, 1] \, \forall i \in \mathcal{I}_s, \, s_i \in [0, 1] \, \forall i \in \mathcal{I}_+, \, \|\mathbf{s}_{\mathcal{J}_k}\|_1 \leq 1, \, \mathcal{J}_k \subseteq \mathbb{Z}_n, \, k \in \mathbb{Z}_L \right\}, \quad (1)$$

118 where $\mathcal{I}_+ \subseteq \mathbb{Z}_n$ is the index set for nonnegative sources, and I_s is its complement, $\mathbf{s}_{\mathcal{J}_k}$ is the subvector

119 constructed from the elements with indices in $\mathcal{J}_k$, and L is the number of sparsity constraints imposed

120 in the subvector level.

121 The Det-Max criterion for BSS is based on the assumption that the source samples are well-spread in

122 their presumed domain. The references [54] and [25] provide precise conditions on the scattering of

123 source samples which guarantee their identifiability for the unit simplex and polytopes, respectively.

124 Appendix A provides a brief summary of these conditions.

125 We emphasize that our assumptions about the sources are deterministic. Therefore, our proposed

126 algorithms do not exploit any stochastic assumptions such as independence or uncorrelatedness, and

127 can separate both independent and dependent (potentially correlated) sources.

2.2 Mixing

129 The sources $\mathbf{s}_t$ are mixed through a mixing matrix $\mathbf{A} \in \mathbb{R}^{m \times n}$.

$$\mathbf{x}_t = \mathbf{A}\mathbf{s}_t, \qquad t \in \mathbb{Z}. \tag{2}$$

130 We only consider the (over)determined case with $m \geq n$ and assume that the mixing matrix is full-

131 rank. While we consider noiseless mixtures to achieve perfect separability, the optimization setting

132 proposed for the online algorithm features a particular objective function that safeguards against

133 potential noise presence. We use $\mathbf{S}(t) = \begin{bmatrix} \mathbf{s}_1 & \ldots & \mathbf{s}_t \end{bmatrix} \in \mathbb{R}^{n \times t}$ and $\mathbf{X}(t) = \begin{bmatrix} \mathbf{x}_1 & \ldots & \mathbf{x}_t \end{bmatrix} \in$

134 $\mathbb{R}^{m \times t}$ to represent data snapshot matrices, at time t, for sources and mixtures, respectively.

2.3 Separation

136 The goal of the source separation is to obtain an estimate of $\mathbf{S}(t)$ from the mixture measurements

137 $\mathbf{X}(t)$ when the mixing matrix $\mathbf{A}$ is unknown. We use the notation $\mathbf{y}_t$ to refer to source estimates,

138 which are linear transformations of observations, i.e., $\mathbf{y}_i = \mathbf{W}\mathbf{x}_i$, where $\mathbf{W} \in \mathbb{R}^{n \times m}$. We define

139 $\mathbf{Y}(t) = \begin{bmatrix} \mathbf{y}_1 & \mathbf{y}_2 & \ldots & \mathbf{y}_t \end{bmatrix} \in \mathbb{R}^{n \times t}$ as the output snapshot matrix. "Ideal separation" is defined

140 as the condition where the outputs are scaled and permuted versions of original sources, i.e., they

141 satisfy $\mathbf{y}_t = \mathbf{P}\mathbf{\Lambda}\mathbf{s}_t$, where $\mathbf{P}$ is a permutation matrix, and $\mathbf{\Lambda}$ is a full rank diagonal matrix.

3 Determinant maximization based blind source separation

143 Among several alternative solution methods for the BSS problem, the determinant-maximization (Det-

144 Max) criterion has been proposed within the NMF, BCA, and PMF frameworks, [25–27, 29, 34, 43].

145 Here, the separator is trained to maximize the (log)-determinant of the sample correlation matrix

146 for the separator outputs, $J(\mathbf{W}) = \log(\det(\hat{\mathbf{R}}_y(t)))$, where $\hat{\mathbf{R}}_y(t)$ is the sample correlation matrix

147 $\hat{\mathbf{R}}_y(t) = \frac{1}{t} \sum_{i=1}^{t} \mathbf{y}_i \mathbf{y}_i^T = \frac{1}{t} \mathbf{Y}(t)\mathbf{Y}(t)^T$. Further, during the training process, the separator outputs

148 are constrained to lie inside the presumed source domain, i.e. $\mathcal{P}$. As a result, we can pose the

149 corresponding optimization problem as [25, 34]

$$\underset{\mathbf{Y}(t)}{\text{maximize}} \quad \log(\det(\mathbf{Y}(t)\mathbf{Y}(t)^T)) \tag{3a}$$

$$\text{subject to} \quad \mathbf{y}_i \in \mathcal{P}, i = 1, \ldots, t, \tag{3b}$$

150 where we ignored the constant $\frac{1}{t}$ term. Here, the determinant of the correlation matrix acts as a spread

151 measure for the output samples. If the original source samples $\{\mathbf{s}_1, \ldots, \mathbf{s}_t\}$ are sufficiently scattered

152 inside the source domain $\mathcal{P}$, as described in Section 2.1 and Appendix A, then the global solution of

153 this optimization can be shown to achieve perfect separation [25, 34, 54].

4 An alternative optimization formulation of determinant-maximization based on weighted similarity matching

Here, we reformulate the Det-Max problem 3 described above in a way that allows derivation of a biologically-plausible neural network for the linear BSS setup in Section 2. Our formulation applies to all source types discusses in 2.1.

We propose the following optimization problem:

$$
\underset{\substack{\mathbf{Y}(t),\mathbf{H}(t),D_{1,11}(t),\ldots D_{1,nn}(t),\mathbf{D}_1(t) \\ D_{2,11}(t),\ldots D_{2,nn}(t),\mathbf{D}_2(t)}}{\text{minimize}} \quad \sum_{i=1}^{n} \log(D_{1,ii}(t)) + \sum_{i=1}^{n} \log(D_{2,ii}(t)) \tag{4a}
$$

$$
\text{subject to} \quad \mathbf{X}(t)^T \mathbf{X}(t) - \mathbf{H}(t)^T \mathbf{D}_1(t)\mathbf{H}(t) = 0, \tag{4b}
$$

$$
\mathbf{H}(t)^T \mathbf{H}(t) - \mathbf{Y}(t)^T \mathbf{D}_2(t)\mathbf{Y}(t) = 0, \tag{4c}
$$

$$
\mathbf{y}_i \in \mathcal{P}, i = 1, \ldots, n, \tag{4d}
$$

$$
\mathbf{D}_l(t) = \text{diag}(D_{l,11}(t), \ldots, D_{l,nn}(t)), \quad l = 1, 2, \tag{4e}
$$

$$
D_{l,11}(t), D_{l,22}(t), \ldots, D_{l,nn}(t) > 0, \quad l = 1, 2 \tag{4f}
$$

Here, $\mathbf{X}(t) \in \mathbb{R}^{m \times t}$ is the matrix containing input (mixture) vectors, $\mathbf{Y}(t) \in \mathbb{R}^{n \times t}$ is the matrix containing output vectors, $\mathbf{H}(t) \in \mathbb{R}^{n \times t}$ is a slack variable containing an intermediate signal $\{\mathbf{h}_i \in \mathbb{R}^n, i = 1, \ldots, t\}$, corresponding to the hidden layer of the neural network implementation in Section 5, in its columns $\mathbf{H}(t) = [\begin{array}{cccc} \mathbf{h}_1 & \mathbf{h}_2 & \ldots & \mathbf{h}_t \end{array}]$. $D_{1,11}(t), D_{1,22}(t), \ldots, D_{1,nn}(t)$ for $l = 1, 2$ are nonnegative slack variables to be described below, and $\mathbf{D}_l$ is the diagonal matrix containing weights $D_{l,ii}$ for $i = 1, \ldots, n$ and $l = 1, 2$. The constraint (4d) ensures that the outputs lie in the presumed domain of sources.

This problem is related to the weighted similarity matching (WSM) objective introduced in [18]. Constraints (4b) and (4c) define two separate WSM conditions. In particular, the equality constraint in (4b) is a WSM constraint between inputs and the intermediate signal $\mathbf{H}(t)$. This constraint imposes that the pairwise weighted correlations of the signal $\{\mathbf{h}_i, i = 1, \ldots, t\}$ are the same as correlations among the elements of the input signal $\{\mathbf{x}_i, i = 1, \ldots, t\}$, i.e., $\mathbf{x}_i^T \mathbf{x}_j = \mathbf{h}_i^T \mathbf{D}_1(t)\mathbf{h}_j$, $\forall i, j \in \{1, \ldots, t\}$. $D_{1,11}(t), D_{1,22}(t), \ldots, D_{1,nn}(t)$ correspond to inner product weights used in these equalities. Similarly, the equality constraint in (4c) defines a WSM constraint between the intermediate signal and outputs. This equality can be written as $\mathbf{h}_i^T \mathbf{h}_j = \mathbf{y}_i^T \mathbf{D}_2(t)\mathbf{y}_j$, $i, j \in \{1, \ldots, t\}$, and $D_{2,11}(t), D_{2,22}(t), \ldots, D_{2,nn}(t)$ correspond to the inner product weights used in these equalities. The optimization involves minimizing the logarithm of the determinant of the weighting matrices.

Now we state the relation between our WSM-based objective and the original Det-Max criterion (3).

Theorem 1. *If $\mathbf{X}(t)$ is full column-rank, then global optimal $\mathbf{Y}(t)$ solutions of* (3) *and* (4) *coincide.*

Proof of Theorem 1. See Appendix B for the proof. The proof relies on a lemma that states that the optimization constraints enforce inputs and outputs to be related by an arbitrary linear transformation. □

5 Biologically-plausible neural networks for WSM-based BSS

The optimization problems we considered so far were in an offline setting, where all inputs are observed together and all outputs are produced together. However, biology operates in an online fashion, observing an input and producing the corresponding output, before seeing the next input. Therefore, in this section, we first introduce an online version of the batch WSM-problem (4). Then we show that the corresponding gradient descent algorithm leads to a two-layer neural network with biologically-plausible local update rules.

5.1 Online optimization setting for WSM-based BSS

We first propose an online extension of WSM-based BSS (4). In the online setting, past outputs cannot be altered, but past inputs and outputs still carry valuable information about solving the BSS

192 problem. We will write down an optimization problem whose goal is to produce the sources $\mathbf{y}_t$ given
193 a mixture $\mathbf{x}_t$, while exploiting information from all the fixed previous inputs and outputs.

194 We first introduce our notation. We consider exponential weighting of the signals as a recipe for
195 dynamical adjustment to potential nonstationarity in the data. We define the weighted input data
196 snapshot matrix by time t as, $\boldsymbol{\mathcal{X}}(t) = \left[\begin{array}{cccc} \gamma^{t-1}\mathbf{x}_1 & \dots & \gamma\mathbf{x}_{t-1} & \mathbf{x}_t \end{array}\right] = \mathbf{X}(t)\boldsymbol{\Gamma}(t)$, where γ is the
197 forgetting factor and $\boldsymbol{\Gamma}(t) = \text{diag}(\gamma^{t-1}, \dots, \gamma, 1)$. The exponential weighting emphasizes recent
198 mixtures by reducing the impact of past samples. Similarly, we define the corresponding weighted
199 output snapshot matrix for output as $\boldsymbol{\mathcal{Y}}(t) = \left[\begin{array}{cccc} \gamma^{t-1}\mathbf{y}_1 & \dots & \gamma\mathbf{y}_{t-1} & \mathbf{y}_t \end{array}\right] = \mathbf{Y}(t)\boldsymbol{\Gamma}(t)$, and the
200 hidden layer vectors as $\boldsymbol{\mathcal{H}}(t) = \left[\begin{array}{cccc} \gamma^{t-1}\mathbf{h}_1 & \dots & \gamma\mathbf{h}_{t-1} & \mathbf{h}_t \end{array}\right] = \mathbf{H}(t)\boldsymbol{\Gamma}(t)$. We further define
201 $\tau = \lim_{t\to\infty} = \sum_{k=0}^{t-1} \gamma^{2k} = \frac{1}{1-\gamma^2}$ as a measure of the effective time window length for sample
202 correlation calculations based on the exponential weights.

203 In order to derive an online cost function, we first converted equality constraints in (4b) and (4c)
204 to similarity matching cost functions $J_1(\mathbf{H}(t), \mathbf{D}_1(t)) = \frac{1}{2\tau^2}\|\boldsymbol{\mathcal{X}}(t)^T\boldsymbol{\mathcal{X}}(t) - \boldsymbol{\mathcal{H}}(t)^T\mathbf{D}_1(t)\boldsymbol{\mathcal{H}}(t)\|_F^2$,
205 $J_2(\mathbf{H}(t), \mathbf{D}_2(t), \mathbf{Y}(t)) = \frac{1}{2\tau^2}\|\boldsymbol{\mathcal{H}}(t)^T\boldsymbol{\mathcal{H}}(t) - \boldsymbol{\mathcal{Y}}(t)^T\mathbf{D}_2(t)\boldsymbol{\mathcal{Y}}(t)\|_F^2$. Then, a weighted combination
206 of similarity matching costs and the objective function in (4a) yields the final cost function

$$
\begin{aligned}
\mathcal{J}(\mathbf{H}(t), \mathbf{D}_1(t), \mathbf{D}_2(t), \mathbf{Y}(t)) = {} & \lambda_{SM}[\beta J_1(\mathbf{H}(t), \mathbf{D}_1(t)) + (1-\beta)J_2(\mathbf{H}(t), \mathbf{D}_2(t), \mathbf{Y}(t))] \\
& + (1-\lambda_{SM})[\sum_{k=1}^{n} \log(D_{1,kk}(t)) + \sum_{k=1}^{n} \log(D_{2,kk}(t))]. \quad (5)
\end{aligned}
$$

207 Here, $\beta \in [0,1]$ and $\lambda_{SM} \in [0,1]$ are parameters that convexly combine similarity matching costs
208 and the objective function. Finally, we can state the online optimization problem for determining the
209 current output $\mathbf{y}_t$, the corresponding hidden state $\mathbf{h}_t$ and for updating the gain parameters $\mathbf{D}_l(t)$ for
210 $l = 1, 2$, as

$$
\underset{\substack{\mathbf{y}_t, \mathbf{h}_t, D_{1,11}(t), \dots D_{1,nn}(t), \mathbf{D}_1(t) \\ D_{2,11}(t), \dots D_{2,nn}(t), \mathbf{D}_2(t)}}{\text{minimize}} \quad \sum_{i=1}^{n} \mathcal{J}(\mathbf{H}(t), \mathbf{D}_1(t), \mathbf{D}_2(t), \mathbf{Y}(t)) \tag{6a}
$$

$$
\text{subject to} \qquad\qquad\qquad\qquad\qquad \mathbf{y}_t \in \mathcal{P}, \tag{6b}
$$

$$
\mathbf{D}_l(t) = \text{diag}(D_{l,11}(t), \dots, D_{l,nn}(t)), \quad l = 1, 2, \tag{6c}
$$

$$
D_{l,11}(t), D_{l,22}(t), \dots, D_{l,nn}(t) > 0, \quad l = 1, 2 \tag{6d}
$$

211 As shown in Appendix C.1, part of $\mathcal{J}$ that depends on $\mathbf{h}_t$ and $\mathbf{y}_t$ can be written as

$$
\begin{aligned}
C(\mathbf{h}_t, \mathbf{y}_t) = {} & 2\mathbf{h}_t^T\mathbf{D}_1\mathbf{M}_H(t)\mathbf{D}_1(t)\mathbf{h}_t - 4\mathbf{h}_t^T\mathbf{D}_1(t)\mathbf{W}_{HX}(t)\mathbf{x}_t \\
& + 2\mathbf{y}_t^T\mathbf{D}_2(t)\mathbf{M}_Y(t)\mathbf{D}_2(t)\mathbf{y}_t - 4\mathbf{y}_t^T\mathbf{D}_2(t)\mathbf{W}_{YH}(t)\mathbf{h}_t + 2\mathbf{h}_t^T\mathbf{M}_H(t)\mathbf{h}_t, \quad (7)
\end{aligned}
$$

212 where the dependence on past inputs and outputs appear in the weighted correlation matrices:

$$
\begin{aligned}
\mathbf{M}_H(t) &= \frac{1}{\tau}\sum_{k=1}^{t-1}(\gamma^2)^{t-1-k}\mathbf{h}_k\mathbf{h}_k^T, \quad \mathbf{W}_{HX}(t) = \frac{1}{\tau}\sum_{k=1}^{t-1}(\gamma^2)^{t-1-k}\mathbf{h}_k\mathbf{x}_k^T, \\
\mathbf{W}_{YH}(t) &= \frac{1}{\tau}\sum_{k=1}^{t-1}(\gamma^2)^{t-1-k}\mathbf{y}_k\mathbf{h}_k^T, \quad \mathbf{M}_Y(t) = \frac{1}{\tau}\sum_{k=1}^{t-1}(\gamma^2)^{t-1-k}\mathbf{y}_k\mathbf{y}_k^T.
\end{aligned} \tag{8}
$$

5.2 Description of network dynamics for bounded anti-sparse sources

214 We now show that the gradient-descent minimization of the online WSM cost function in (6) can
215 be interpreted as the dynamics of a neural network with local learning rules. The exact network
216 architecture is determined by the presumed identifiable source domain $\mathcal{P}$, which can be chosen in
217 infinitely many ways. In this section, we concentrate on the domain choice $\mathcal{P} = \mathcal{B}_\infty$ as an illustrative
218 example. In Section 5.3, we discuss how to generalize the results of this section by modifying the
219 output layer for different identifiable source domains. We start by writing the update expressions for
220 the optimization variables based on the gradients of $\mathcal{J}(\mathbf{h}_t, \mathbf{y}_t, \mathbf{D}_1(t), \mathbf{D}_2(t))$:

221 Update dynamics for $\mathbf{h}_t$: Following previous work [47, 55], and using the gradient of (7) in (A.8)
222 with respect to $\mathbf{h}_t$, we can write down an update dynamics for $\mathbf{h}_t$ in the form

$$
\begin{aligned}
\frac{d\mathbf{v}(\tau)}{d\tau} = {} & -\mathbf{v}(\tau) - \lambda_{SM}[((1-\beta)\bar{\mathbf{M}}_H(t) + \beta\mathbf{D}_1(t)\bar{\mathbf{M}}_H(t)\mathbf{D}_1(t))\mathbf{h}(\tau) \\
& + \beta\mathbf{D}_1(t)\mathbf{W}_{HX}(t)\mathbf{x}(\tau) + (1-\beta)\mathbf{W}_{YH}(t)^T\mathbf{D}_2(t)\mathbf{y}(\tau)] \quad (9)
\end{aligned}
$$

$$
\mathbf{h}_{t,i}(\tau) = \sigma_A\left(\frac{\mathbf{v}_i(\tau)}{\lambda_{SM}\Gamma_{Hii}(t)((1-\beta) + \beta D_{1,ii}(t)^2)}\right), \quad \text{for } i = 1, \dots n, \tag{10}
$$

where $\mathbf{\Gamma}_H(t)$ is a diagonal matrix containing diagonal elements of $\mathbf{M}_H(t)$ and $\bar{\mathbf{M}}_H(t) = \mathbf{M}_H(t) - \mathbf{\Gamma}_H(t)$, $\sigma(\cdot)$ is the clipping function, defined as $\sigma_A(x) = \begin{cases} x & -A \le x \le A, \\ A\,\mathrm{sign}(x) & \text{otherwise.} \end{cases}$. This dynamics can be shown to minimize (7) [55]. Here $\mathbf{v}(\tau)$ is an internal variable that could be interpreted as the voltage dynamics of a biological neuron, and is defined based on a linear transformation of $\mathbf{h}_t$ in (A.9). Equation (9) defines $\mathbf{v}(\tau)$ dynamics from the gradient of (7) with respect to $\mathbf{h}_t$ in (A.8). Due to the positive definite linear map in (A.9), the expression in (A.8) also serves as a descent direction for $\mathbf{v}(\tau)$. Furthermore, $\sigma(\cdot)$ function is the projection onto $A\mathcal{B}_\infty$, where $[-A, A]$ is the presumed dynamic range for the components of $\mathbf{h}_t$. We note that there is no explicit constraint set for $\mathbf{h}_t$ in the online optimization setting of Section 5.1, and therefore, A can be chosen as large as desired in the actual implementation. We included the nonlinearity in (10) to model the limited dynamic range of an actual (biological) neuron.

Update dynamics for output $\mathbf{y}_t$: We write the update dynamics for the output $\mathbf{y}_t$, based on (A.11) as

$$\frac{d\mathbf{u}(\tau)}{d\tau} = -\mathbf{u}(\tau) + \mathbf{W}_{YH}(t)\mathbf{h}(\tau) - \bar{\mathbf{M}}_Y(t)\mathbf{D}_2(t)\mathbf{y}(\tau), \tag{11}$$

$$\mathbf{y}_{t,i}(\tau) = \sigma_1\left(\frac{\mathbf{u}_i(\tau)}{\Gamma_{Yii}(t)D_{2,ii}(t)}\right), \quad \text{for } i = 1, \ldots n, \tag{12}$$

which is derived using the same approach for $\mathbf{h}_t$, where we used the descent direction expression in (A.11), and the substitution in (A.12). Here, $\mathbf{\Gamma}_Y(t)$ is a diagonal matrix containing diagonal elements of $\mathbf{M}_Y(t)$ and $\bar{\mathbf{M}}_Y(t) = \mathbf{M}_Y(t) - \mathbf{\Gamma}_Y(t)$. Note that the nonlinear mapping $\sigma_1(\cdot)$ is the projection onto the presumed domain of sources, i.e., $\mathcal{P} = \mathcal{B}_\infty$, which is elementwise clipping operation.

The state space representations in (9)-(10) and (11)-(12) correspond to a two-layer recurrent neural network with input $\mathbf{x}_t$, hidden layer activation $\mathbf{h}_t$, output layer activation $\mathbf{y}_t$, $\mathbf{W}_{HX}$ ($\mathbf{W}_{HX}^T$) and $\mathbf{W}_{YH}$ ($\mathbf{W}_{YH}^T$) are the feedforward (feedback) synaptic weight matrices for the first and the second layers, respectively, and $\bar{\mathbf{M}}_H$ and $\bar{\mathbf{M}}_Y$ are recurrent synaptic weight matrices for the first and the second layers, respectively. The corresponding neural network schematic is provided in Figure 2.(b). The gain and synaptic weight dynamics below describe the learning mechanism for this network:

Update dynamics for gains $D_{l,ii}$: Using the derivative of the cost function with respect to $D_{1,ii}$ in (A.13), we can write the dynamics corresponding to the gain variable $D_{1,ii}$ as

$$\mu_{D_1}\frac{dD_{1,ii}(t)}{dt} = -(\lambda_{SM}\beta)(\|\mathbf{M}_{Hi,:}\|_{\mathbf{D}_1(t)}^2 - \|\mathbf{W}_{HXi,:}\|_2^2) - (1 - \lambda_{SM})\frac{1}{D_{1,ii}(t)}, \tag{13}$$

where μ_{D_1} corresponds to the learning time-constant. Similarly, for the gain variable $D_{2,ii}$, the corresponding coefficient dynamics expression based on (A.14) is given by

$$\mu_{D_2}\frac{dD_{2,ii}(t)}{dt} = -(\lambda_{SM}\beta)(\|\mathbf{M}_{Yi,:}\|_{\mathbf{D}_2(t)}^2 - \|\mathbf{W}_{YHi,:}\|_2^2) - (1 - \lambda_{SM})\frac{1}{D_{2,ii}(t)}, \tag{14}$$

where μ_{D_2} corresponds to the learning time-constant.

The inverses of the inner product weights $D_{l,ii}$ correspond to homeostatic gain parameters. The inspection of the gain updates in (13) and (14) leads to an interesting observation: whether the corresponding gain is going to increase or decrease depends on the balance between the norms of the recurrent and the feedforward synaptic strengths, which are the statistical indicators of the recent output and input activations, respectively. Hence, the homeostatic gain of the neuron will increase (decrease) if the level of recent output activations falls behind (surpasses) the level of recent input activations to balance input/output energy levels. The resulting dynamics align with the experimental homeostatic balance observed in biological neurons [56].

Based on the definitions of the synaptic weight matrices in (8), we can write their updates as

$$\mathbf{M}_H(t+1) = \gamma^2\mathbf{M}_H(t) + (1-\gamma^2)\mathbf{h}_t\mathbf{h}_t^T, \quad \mathbf{M}_Y(t+1) = \gamma^2\mathbf{M}_Y(t) + (1-\gamma^2)\mathbf{y}_t\mathbf{y}_t^T, \tag{15}$$

$$\mathbf{W}_{HX}(t+1) = \gamma^2\mathbf{W}_{HX}(t) + (1-\gamma^2)\mathbf{h}_t\mathbf{x}_t^T, \quad \mathbf{W}_{YH}(t+1) = \gamma^2\mathbf{W}_{YH}(t) + (1-\gamma^2)\mathbf{y}_t\mathbf{h}_t^T.$$

These updates are local in the sense that they only depend on variables available to the synapse, and hence are biologically plausible.

5.3 Det-max WSM neural network examples for more general source domains

Det-Max Neural Network obtained for the source domain $\mathcal{P} = \mathcal{B}_\infty$ in Section 5.2 can be extended to more general identifiable source domains by only changing the output dynamics. In Appendix D, we provide illustrative examples for different identifiable domain choices. Table 1 summarizes the output dynamics obtained for the identifiable source domain examples in Figure 1.

Table 1: Example source domains from Figure 1 and the corresponding output dynamics.

Source Domain	Output Dynamics	Output Activation
$\mathcal{P} = \mathcal{B}_{\infty,+}$ Nonnegative Anti-sparse	$\mathbf{y}_{t,i}(\tau) = \sigma_+ \left(\frac{\mathbf{u}_i(\tau)}{\Gamma_{Y\,ii}(t)D_{2,ii}(t)} \right)$	$\sigma_+(x)$
$\mathcal{P} = \mathcal{B}_1$ Sparse	$\mathbf{y}_{t,i}(\tau) = \mathrm{ST}_{\lambda_1(\tau)} \left(\frac{u_i(\tau)}{\lambda_{SM}(1-\beta)\Gamma_{Y\,ii}(t)D_{2,ii}(t)} \right)$ $\frac{da(\tau)}{d\tau} = -a(\tau) + \sum_{k=0}^{n} |\mathbf{y}_k(\tau)| - 1 + \lambda_1(\tau),$ $\lambda_1(\tau) = \mathrm{ReLU}(a(\tau))$	$\mathrm{ST}_\lambda(x)$
$\mathcal{P} = \mathcal{B}_{1,+}$ Nonnegative Sparse	$\mathbf{y}_{t,i}(\tau) = \mathrm{ReLU} \left(\frac{u_i(\tau)}{\lambda_{SM}(1-\beta)\Gamma_{Y\,ii}(t)D_{2,ii}(t)} - \lambda_1(\tau) \right)$ $\frac{da(\tau)}{d\tau} = -a(\tau) + \sum_{k=0}^{n} \mathbf{y}_k(\tau) - 1 + \lambda_1(\tau),$ $\lambda_1(\tau) = \mathrm{ReLU}(a(\tau))$	$\mathrm{ReLU}(x)$
$\mathcal{P} = \Delta$ Unit Simplex	$\mathbf{y}_{t,i}(\tau) = \mathrm{ReLU} \left(\frac{u_i(\tau)}{\lambda_{SM}(1-\beta)\Gamma_{Y\,ii}(t)D_{2,ii}(t)} - \lambda_1(\tau) \right)$ $\frac{d\lambda_1(\tau)}{d\tau} = -\lambda_1(\tau) + \sum_{k=0}^{n} \mathbf{y}_k(\tau) - 1 + \lambda_1(\tau)$	$\mathrm{ReLU}(x)$

We can make the following observations on Table 1: (1) For sparse and unit simplex settings, there is an additional inhibitory neuron which takes input from all outputs and whose activation is the inhibitory signal $\lambda_1(\tau)$, (2) The source attributes, which are globally defined over all sources, determine the activation functions at the output layer. The proposed framework can be applied to any polytope described by (1) for which the corresponding Det-Max neural network will contain combinations of activation functions in Table 1 as illustrated in Figure 2.(a).

6 Numerical experiments

In this section, we illustrate the applications of the proposed WSM-based source separation framework for both synthetic and natural sources. More details on these experiments and additional examples are provided in Appendix E, including applications to sparse dictionary learning (Appendix E.6).

6.1 Synthetically correlated source separation

Figure 3: The SINRs of WSM, NSM, ICA, PMF, and LD-InfoMax algorithms as a function of the correlation parameter ρ.

In order to illustrate the correlated source separation capability of the proposed WSM neural networks, we consider a numerical experiment with five copula-T distributed (uniform and correlated) sources. For the correlation calibration matrix for these sources, we use Toeplitz matrix whose first row is $[1 \quad \rho \quad \rho \quad \rho \quad \rho]$. The ρ parameter determines the correlation level, and we considered the range $[0, 0.6]$ for this parameter. These sources are mixed with a 10×5 random matrix with independent and identically distributed (i.i.d.) standard normal random variables. The mixtures are corrupted by i.i.d. normal noise corresponding to 30dB signal-to-noise ratio (SNR) level. In this experiment, we employ the nonnegative-antisparse-WSM neural network (Figure 8 in Appendix D.2) whose activation

functions at the output layer are nonnegative-clipping functions, as the sources are nonnegative uniform random variables.

We compared the signal-to-interference-plus-noise-power-ratio (SINR) performance of our algorithm with the NSM algorithm [16], Infomax ICA algorithm [1], as implemented in Python MNE Toolbox [57], LD-InfoMax algorithm [58], and PMF algorithm [25]. Figure 3 shows the SINR performances of these algorithms (averaged over 300 realizations) as a function of the correlation parameter ρ. We observe that our WSM-based network performs well despite correlations. In contrast, performance of NSM and ICA algorithms, which assume uncorrelated sources, degrade noticeably with increasing correlation levels. In addition, we note that the performance of batch Det-Max algorithms, i.e., LD-InfoMax and PMF, are also robust against source correlations. Furthermore, due to their batch nature, these algorithms typically achieved better performance results than our neural network with online-restriction, as expected.

6.2 Image separation

To further illustrate the correlated source separation advantage of our approach, we consider a natural image separation scenario. For this example, we have three RGB images with sizes $324 \times 432 \times 3$ as sources (Figure 4.(a)). The sample Pearson correlation coefficients between the images are $\rho_{12} = 0.263$, $\rho_{13} = 0.066$, $\rho_{23} = 0.333$. We use a random 5×3 mixing matrix whose entries are drawn from i.i.d standard normal distribution. The corresponding mixtures are shown in Figure 4.(b).

Figure 4: **(a)** Original RGB images, **(b)** Mixture RGB images, **(c)** ICA outputs, **(d)** NSM outputs (using pre-whitened mixtures), **(e)** WSM outputs.

We applied ICA, NSM and WSM algorithms to the mixtures. Figure 4.(c),(d),(e) shows the corresponding outputs. High-resolution versions of all images in this example are available in Appendix E.4 in addition to the comparisons with LD-Infomax and PMF algorithms. The Infomax ICA algorithm's outputs have SINR level of 13.92dB, and this performance is perceivable as residual interference effects in the corresponding output images. The NSM algorithm achieves significantly higher SINR level of 17.45dB and the output images visually reflect this better performance. Our algorithm achieves the best SINR level of 27.49dB, and the corresponding outputs closely resemble the original source images.

7 Discussion and Conclusion

We proposed a general framework for generating biologically plausible neural networks that are capable of separating correlated sources from their linear mixtures, and demonstrated their successful correlated source separation capability through synthetic and natural sources.

Our networks suffer from the same limitations of other recurrent biologically-plausible BSS networks. First, certain hyperparameters can significantly influence algorithm performance (see Appendix E.9). Especially, the inner product gains (D_{ii}) are sensitive to the combined choices of algorithm parameters, which require careful tuning. Second, the numerical experiments with our neural networks are relatively slow due to the recursive computations in (9)-(10) and (11)-(12) for hidden layer and output vectors, which is common to all biologically plausible recurrent source separation networks (see Appendix F). This could perhaps be addressed by early-stopping the recursive computation [59].

References

[1] Anthony J Bell and Terrence J Sejnowski. An information-maximization approach to blind separation and blind deconvolution. *Neural computation*, 7(6):1129–1159, 1995.

[2] Bruno A Olshausen and David J Field. Emergence of simple-cell receptive field properties by learning a sparse code for natural images. *Nature*, 381(6583):607–609, 1996.

[3] Adelbert W Bronkhorst. The cocktail party phenomenon: A review of research on speech intelligibility in multiple-talker conditions. *Acta Acustica united with Acustica*, 86(1):117–128, 2000.

[4] Michael S Lewicki. Efficient coding of natural sounds. *Nature neuroscience*, 5(4):356–363, 2002.

[5] Hiroki Asari, Barak A Pearlmutter, and Anthony M Zador. Sparse representations for the cocktail party problem. *Journal of Neuroscience*, 26(28):7477–7490, 2006.

[6] Rajiv Narayan, Virginia Best, Erol Ozmeral, Elizabeth McClaine, Micheal Dent, Barbara Shinn-Cunningham, and Kamal Sen. Cortical interference effects in the cocktail party problem. *Nature neuroscience*, 10(12):1601–1607, 2007.

[7] Mark A Bee and Christophe Micheyl. The cocktail party problem: what is it? how can it be solved? and why should animal behaviorists study it? *Journal of comparative psychology*, 122 (3):235, 2008.

[8] Josh H McDermott. The cocktail party problem. *Current Biology*, 19(22):R1024–R1027, 2009.

[9] Nima Mesgarani and Edward F Chang. Selective cortical representation of attended speaker in multi-talker speech perception. *Nature*, 485(7397):233–236, 2012.

[10] Elana M Zion Golumbic, Nai Ding, Stephan Bickel, Peter Lakatos, Catherine A Schevon, Guy M McKhann, Robert R Goodman, Ronald Emerson, Ashesh D Mehta, Jonathan Z Simon, et al. Mechanisms underlying selective neuronal tracking of attended speech at a "cocktail party". *Neuron*, 77(5):980–991, 2013.

[11] Takuya Isomura, Kiyoshi Kotani, and Yasuhiko Jimbo. Cultured cortical neurons can perform blind source separation according to the free-energy principle. *PLoS Comput Biol*, 11(12): e1004643, 2015.

[12] Pierre Comon and Christian Jutten. *Handbook of Blind Source Separation: Independent component analysis and applications*. Academic press, 2010.

[13] Andrzej Cichocki, Rafal Zdunek, Anh Huy Phan, and Shun-ichi Amari. *Nonnegative matrix and tensor factorizations: applications to exploratory multi-way data analysis and blind source separation*. John Wiley & Sons, 2009.

[14] Jitendra Sharma, Alessandra Angelucci, and Mriganka Sur. Induction of visual orientation modules in auditory cortex. *Nature*, 404(6780):841–847, 2000.

[15] David M. Eagleman, Olivier J-M. D. Coenen, Vladimir Mitsner, Thomas M. Bartol, Anthony J. Bell, and Terrence J. Sejnowski. Cerebellar glomeruli: Does limited extracellular calcium implement a sparse encoding strategy? In *Proceedings of the 8th Annual Joint Symposium on Neural Computation*, 2001.

[16] Cengiz Pehlevan, Sreyas Mohan, and Dmitri B Chklovskii. Blind nonnegative source separation using biological neural networks. *Neural computation*, 29(11):2925–2954, 2017.

[17] Takuya Isomura and Taro Toyoizumi. Error-gated hebbian rule: A local learning rule for principal and independent component analysis. *Scientific reports*, 8(1):1–11, 2018.

[18] Alper T Erdogan and Cengiz Pehlevan. Blind bounded source separation using neural networks with local learning rules. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3812–3816. IEEE, 2020.

[19] Yanis Bahroun, Dmitri Chklovskii, and Anirvan Sengupta. A normative and biologically plausible algorithm for independent component analysis. *Advances in Neural Information Processing Systems*, 34, 2021.

[20] Bruno A Olshausen and David J Field. Sparse coding with an overcomplete basis set: A strategy employed by v1? *Vision research*, 37(23):3311–3325, 1997.

[21] Yilun Zhang and Tatyana O Sharpee. A robust feedforward model of the olfactory system. *PLoS computational biology*, 12(4):e1004850, 2016.

[22] Kamesh Krishnamurthy, Ann M Hermundstad, Thierry Mora, Aleksandra M Walczak, and Vijay Balasubramanian. Disorder and the neural representation of complex odors: smelling in the real world. *arXiv preprint arXiv:1707.01962*, 2017.

[23] Vijay Singh, Martin Tchernookov, and Vijay Balasubramanian. What the odor is not: Estimation by elimination. *Physical Review E*, 104(2):024415, 2021.

[24] Chia-Hsiang Lin, Wing-Kin Ma, Wei-Chiang Li, Chong-Yung Chi, and ArulMurugan Ambikapathi. Identifiability of the simplex volume minimization criterion for blind hyperspectral unmixing: The no-pure-pixel case. *IEEE Transactions on Geoscience and Remote Sensing*, 53 (10):5530–5546, 2015.

[25] Gokcan Tatli and Alper T. Erdogan. Polytopic matrix factorization: Determinant maximization based criterion and identifiability. *IEEE Transactions on Signal Processing*, 69:5431–5447, 2021. doi: 10.1109/TSP.2021.3112918.

[26] Reinhard Schachtner, Gerhard Pöppel, and Elmar Wolfgang Lang. Towards unique solutions of non-negative matrix factorization problems by a determinant criterion. *Digital Signal Processing*, 21(4):528–534, 2011.

[27] Alper T Erdogan. A class of bounded component analysis algorithms for the separation of both independent and dependent sources. *IEEE Transactions on Signal Processing*, 61(22): 5730–5743, 2013.

[28] Huseyin A Inan and Alper T Erdogan. A convolutive bounded component analysis framework for potentially nonstationary independent and/or dependent sources. *IEEE Transactions on Signal Processing*, 63(1):18–30, 2014.

[29] Eren Babatas and Alper T Erdogan. An algorithmic framework for sparse bounded component analysis. *IEEE Transactions on Signal Processing*, 66(19):5194–5205, 2018.

[30] Cengiz Pehlevan and Dmitri B Chklovskii. A normative theory of adaptive dimensionality reduction in neural networks supplementary information. *Proceedings of Advances in Neural Information Processing Systems 28 (NIPS 2015)*, 2015.

[31] Cengiz Pehlevan and Dmitri B Chklovskii. Neuroscience-inspired online unsupervised learning algorithms: Artificial neural networks. *IEEE Signal Processing Magazine*, 36(6):88–96, 2019.

[32] Ji-Cheng Chen. The nonnegative rank factorizations of nonnegative matrices. *Linear Algebra and Its Applications*, 62:207–217, November 1984.

[33] Pentti Paatero and Unto Tapper. Positive matrix factorization: A non-negative factor model with optimal utilization of error estimates of data values. *Environmetrics*, 5(2):111–126, 1994.

[34] Xiao Fu, Kejun Huang, Nicholas D Sidiropoulos, and Wing-Kin Ma. Nonnegative matrix factorization for signal and data analytics: Identifiability, algorithms, and applications. *IEEE Signal Process. Mag.*, 36(2):59–80, 2019.

[35] Tsung-Han Chan, Wing-Kin Ma, ArulMurugan Ambikapathi, and Chong-Yung Chi. A simplex volume maximization framework for hyperspectral endmember extraction. *IEEE Transactions on Geoscience and Remote Sensing*, 49(11):4177–4193, 2011.

[36] Chia-Hsiang Lin, Ruiyuan Wu, Wing-Kin Ma, Chong-Yung Chi, and Yue Wang. Maximum volume inscribed ellipsoid: A new simplex-structured matrix factorization framework via facet enumeration and convex optimization. *SIAM Journal on Imaging Sciences*, 11(2):1651–1679, 2018.

[37] Pando Georgiev, Fabian Theis, and Andrzej Cichocki. Sparse component analysis and blind source separation of underdetermined mixtures. *IEEE transactions on neural networks*, 16(4): 992–996, 2005.

[38] David L Donoho. For most large underdetermined systems of equations, the minimal l1-norm near-solution approximates the sparsest near-solution. *Communications on Pure and Applied Mathematics*, 59(7):907–934, 2006.

[39] Christopher Rozell, Don Johnson, Richard Baraniuk, and Bruno Olshausen. Locally competitive algorithms for sparse approximation. In *2007 IEEE International Conference on Image Processing*, volume 4, pages IV–169. IEEE, 2007.

[40] Michael Elad. *Sparse and redundant representations: from theory to applications in signal and image processing*. Springer Science & Business Media, 2010.

[41] Eren Babatas and Alper T Erdogan. Time and frequency based sparse bounded component analysis algorithms for convolutive mixtures. *Signal Processing*, page 107590, 2020.

[42] Sergio Cruces. Bounded component analysis of linear mixtures: A criterion of minimum convex perimeter. *IEEE Transactions on Signal Processing*, 58(4):2141–2154, 2010.

[43] Gokcan Tatli and Alper T. Erdogan. Generalized polytopic matrix factorization. *2021 IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP)*, June 2021.

[44] Bariscan Bozkurt and Alper T. Erdogan. On identifiable polytope characterization for polytopic matrix factorization. *2022 IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP)*, May 2022.

[45] Cengiz Pehlevan and Dmitri B Chklovskii. A hebbian/anti-hebbian network derived from online non-negative matrix factorization can cluster and discover sparse features. In *2014 48th Asilomar Conference on Signals, Systems and Computers*, pages 769–775. IEEE, 2014.

[46] Anirvan Sengupta, Cengiz Pehlevan, Mariano Tepper, Alexander Genkin, and Dmitri Chklovskii. Manifold-tiling localized receptive fields are optimal in similarity-preserving neural networks. In *Advances in Neural Information Processing Systems*, pages 7080–7090, 2018.

[47] Cengiz Pehlevan. A spiking neural network with local learning rules derived from nonnegative similarity matching. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 7958–7962. IEEE, 2019.

[48] Kenneth Kreutz-Delgado, Joseph F Murray, Bhaskar D Rao, Kjersti Engan, Te-Won Lee, and Terrence J Sejnowski. Dictionary learning algorithms for sparse representation. *Neural computation*, 15(2):349–396, 2003.

[49] Yuanqing Li, Andrzej Cichocki, and Shun-ichi Amari. Analysis of sparse representation and blind source separation. *Neural computation*, 16(6):1193–1234, 2004.

[50] Clément Elvira, Pierre Chainais, and Nicolas Dobigeon. Bayesian antisparse coding. *IEEE Transactions on Signal Processing*, 65(7):1660–1672, 2016.

[51] Christoph Studer, Tom Goldstein, Wotao Yin, and Richard G Baraniuk. Democratic representations. *arXiv preprint arXiv:1401.3420*, 2014.

[52] David Donoho and Victoria Stodden. When does non-negative matrix factorization give a correct decomposition into parts? *Advances in neural information processing systems*, 16: 1141–1148, 2003.

[53] Agnieszka Grabska-Barwińska, Simon Barthelmé, Jeff Beck, Zachary F Mainen, Alexandre Pouget, and Peter E Latham. A probabilistic approach to demixing odors. *Nature neuroscience*, 20(1):98–106, 2017.

[54] Xiao Fu, Kejun Huang, and Nicholas D Sidiropoulos. On identifiability of nonnegative matrix factorization. *IEEE Signal Processing Letters*, 25(3):328–332, 2018.

[55] Christopher J Rozell, Don H Johnson, Richard G Baraniuk, and Bruno A Olshausen. Sparse coding via thresholding and local competition in neural circuits. *Neural computation*, 20(10): 2526–2563, 2008.

[56] Gina G Turrigiano. Homeostatic plasticity in neuronal networks: the more things change, the more they stay the same. *Trends in neurosciences*, 22(5):221–227, 1999.

[57] Alexandre Gramfort, Martin Luessi, Eric Larson, Denis A. Engemann, Daniel Strohmeier, Christian Brodbeck, Roman Goj, Mainak Jas, Teon Brooks, Lauri Parkkonen, and Matti S. Hämäläinen. MEG and EEG data analysis with MNE-Python. *Frontiers in Neuroscience*, 7 (267):1–13, 2013. doi: 10.3389/fnins.2013.00267.

[58] Alper T Erdogan. An information maximization based blind source separation approach for dependent and independent sources. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 4378–4382. IEEE, 2022.

[59] Victor Minden, Cengiz Pehlevan, and Dmitri B Chklovskii. Biologically plausible online principal component analysis without recurrent neural dynamics. In *2018 52nd Asilomar Conference on Signals, Systems, and Computers*, pages 104–111. IEEE, 2018.

[60] Cengiz Pehlevan, Alexander Genkin, and Dmitri B Chklovskii. A clustering neural network model of insect olfaction. In *2017 51st Asilomar Conference on Signals, Systems, and Computers*, pages 593–600. IEEE, 2017.