The Gyro-Structure of Some Matrix Manifolds

Abstract

In this paper, we study the gyrovector space structure (*gyro-structure*) of matrix manifolds. Our work is motivated by the success of hyperbolic neural networks (HNNs) that have demonstrated impressive performance in a variety of applications. At the heart of HNNs is the theory of gyrovector spaces that provides a powerful tool for studying hyperbolic geometry. Here we focus on two matrix manifolds, i.e., Symmetric Positive Definite (SPD) and Grassmann manifolds, and consider connecting the Riemannian geometry of these manifolds with the basic operations, i.e., the binary operation and scalar multiplication on gyrovector spaces. Our work reveals some interesting facts about SPD and Grassmann manifolds. First, SPD matrices with the Affine-Invariant (AI) and Log-Euclidean (LE) geometries have rich structure with strong connection to hyperbolic geometry. Second, linear subspaces, when equipped with our proposed basic operations, form what we call *gyrocommutative and gyrononreductive gyrogroups*. Furthermore, they share remarkable analogies with gyrovector spaces. We demonstrate the applicability of our approach for human activity understanding and question answering.

1   Introduction

Data lying on matrix manifolds are commonly encountered in various applied areas such as medical imaging [3, 30], shape analysis [35], drone classification [5], image recognition [10], and human behavior analysis [9, 14, 15, 19, 20, 21, 28, 34]. These data arise from constraint sets of the problem, for which there is a natural representation of elements in the form of matrix arrays [2]. Due to the non-Euclidean nature of these data, traditional optimization algorithms usually fail to obtain good results in the matrix manifold setting. While a large body of works [5, 6, 7, 9, 19, 20, 21, 28, 29, 42] has been developed to generalize traditional optimization algorithms to this setting, there is still a lack of works that translate the language of differential geometry to basic operations on matrix manifolds so that they can be used in computational building blocks of neural network models on these manifolds just as basic operations on Euclidean spaces, e.g., matrix-matrix addition and scalar-matrix multiplication are used in deep neural networks (DNNs).

To address the above issue, we propose a novel framework based on the theory of gyrovector spaces [38, 39, 40] that has been successfully applied in the context of HNNs [11, 33]. Our aim is to uncover hidden analogies between the target manifolds and Euclidean spaces in the same way that we uncover hidden analogies between hyperbolic and Euclidean spaces [11, 33, 38, 39, 40]. Although there are some works [1, 16, 22, 23, 24, 25, 27] showing the gyro-structure of SPD manifolds with the AI geometry, none of them provides a rigorous mathematical formulation for the connection between the basic operations of [1, 16, 17, 22, 23, 24, 25] and the AI geometry of SPD manifolds. In this paper, we show how the basic operations can be constructed from the Riemannian geometry of matrix manifolds, and derive their closed-form expressions for SPD and Grassmann manifolds. In the case of SPD manifolds with the LE geometry, one recovers precisely the operations of [3] that give these manifolds a vector space structure. In the case of Grassmann manifolds, we obtain

gyrocommutative and gyrononreductive gyrogroups that share remarkable analogies with gyrovector spaces. Our main contributions are (1) We propose a method for constructing some basic operations, i.e., matrix-matrix addition and scalar-matrix multiplication on SPD and Grassmann manifolds; (2) We derive closed-form expressions of these operations for SPD manifolds with the LE geometry and Grassmann manifolds; (3) We verify the gyro-structure of SPD manifolds with the LE geometry, and some axioms of gyrovector spaces for Grassmann manifolds; (4) We showcase our approach on the tasks of human activity understanding and question answering.

2 Background

2.1 Gyrovector Spaces

Gyrovector spaces form the setting for hyperbolic geometry in the same way that vector spaces form the setting for Euclidean geometry [38, 39, 40]. We first recap the definitions of gyrogroups and gyrocommutative gyrogroups proposed in [38, 39, 40]. For greater mathematical detail and in-depth discussion, we refer the interested reader to these papers.

Definition 2.1 (**Gyrogroups [40]**). *A pair* $(G, \oplus)$ *is a groupoid in the sense that it is a nonempty set, G, with a binary operation, $\oplus$. A groupoid $(G, \oplus)$ is a gyrogroup if its binary operation satisfies the following axioms for $a, b, c \in G$:*

(G1) There is at least one element $e \in G$ called a left identity such that $e \oplus a = a$.

(G2) There is an element $\ominus a \in G$ called a left inverse of a such that $\ominus a \oplus a = e$.

(G3) There is an automorphism $\mathrm{gyr}[a, b] : G \to G$ *for each $a, b \in G$ such that*

$$a \oplus (b \oplus c) = (a \oplus b) \oplus \mathrm{gyr}[a, b]c \quad \textit{(Left Gyroassociative Law).}$$

The automorphism $\mathrm{gyr}[a, b]$ *is called the gyroautomorphism, or the gyration of G generated by a, b.*

(G4) $\mathrm{gyr}[a, b] = \mathrm{gyr}[a \oplus b, b]$ *(Left Reduction Property).*

Definition 2.2 (**Gyrocommutative Gyrogroups [40]**). *A gyrogroup $(G, \oplus)$ is gyrocommutative if it satisfies*

$$a \oplus b = \mathrm{gyr}[a, b](b \oplus a) \quad \textit{(Gyrocommutative Law).}$$

The following definition of gyrovector spaces is slightly different from Definition 3.2 in [40].

Definition 2.3 (**Gyrovector Spaces**). *A gyrocommutative gyrogroup $(G, \oplus)$ equipped with a scalar multiplication*

$$(t, x) \to t \odot x : \mathbb{R} \times G \to G$$

is called a gyrovector space if it satisfies the following axioms for $s, t \in \mathbb{R}$ and $a, b, c \in G$:

(V1) $1 \odot a = a, 0 \odot a = t \odot e = e$*, and* $(-1) \odot a = \ominus a$*.*

(V2) $(s + t) \odot a = s \odot a \oplus t \odot a$*.*

(V3) $(st) \odot a = s \odot (t \odot a)$*.*

(V4) $\mathrm{gyr}[a, b](t \odot c) = t \odot \mathrm{gyr}[a, b]c$*.*

(V5) $\mathrm{gyr}[s \odot a, t \odot a] = \mathrm{Id}$*, where* Id *is the identity map.*

Note that the axioms of gyrovector spaces considered in our work are more strict than those proposed in [22, 23, 24, 25]. Thus many results proved in [22, 23, 24, 25] can be applied to our case, which gives rise to interesting applications.

3 Proposed Approach

For simplicity of exposition, we will concentrate on real matrices. Denote by $\mathrm{M}_{n,m}$ the space of $n \times m$ matrices, Sym_n^+ the space of $n \times n$ SPD matrices, Sym_n the space of $n \times n$ symmetric matrices, O_n the space of $n \times n$ orthogonal matrices, $\mathrm{Gr}_{n,p}$ the p-dimensional subspaces of $\mathbb{R}^n$. Let $\mathcal{M}$ be a matrix manifold, $T_{\mathbf{P}}\mathcal{M}$ be the tangent space of $\mathcal{M}$ at $\mathbf{P} \in \mathcal{M}$. Denote by $\exp(\mathbf{P})$ and $\log(\mathbf{P})$ the usual matrix exponential and logarithm of $\mathbf{P}$, $\mathrm{Exp}_{\mathbf{P}}(\mathbf{W})$ the exponential map at $\mathbf{P}$ that

associates to a tangent vector $\mathbf{W} \in T_{\mathbf{P}}\mathcal{M}$ a point of $\mathcal{M}$, $\mathrm{Log}_{\mathbf{P}}(\mathbf{Q})$ the logarithmic map of $\mathbf{Q} \in \mathcal{M}$ at $\mathbf{P}$. Let $\mathcal{T}_{\mathbf{P}\to\mathbf{Q}}(\mathbf{W})$ be the parallel transport of $\mathbf{W}$ from $\mathbf{P}$ to $\mathbf{Q}$ along geodesics connecting $\mathbf{P}$ and $\mathbf{Q}$. We will use superscripts for the exponential and logarithmic maps, and the parallel transport to indicate their associated Riemannian metric (in the case of SPD manifolds) or the target manifolds (in the case of Grassmann manifolds).

Definition 3.1. *Let r be a positive real number. The binary operation $\mathbf{P} \oplus^r \mathbf{Q}$ where $\mathbf{P}, \mathbf{Q} \in \mathcal{M}$ is obtained by projecting $\mathbf{Q}^r$ in the tangent space at the identity element $\mathbf{I} \in \mathcal{M}$ with the logarithmic map, computing the parallel transport of this projection from $\mathbf{I}$ to $\mathbf{P}^r$ along geodesics connecting $\mathbf{I}$ and $\mathbf{P}^r$, and then projecting it back on the manifold with the exponential map, i.e.,*

$$\mathbf{P} \oplus^r \mathbf{Q} = \big(\mathrm{Exp}_{\mathbf{P}^r}(\mathcal{T}_{\mathbf{I}\to\mathbf{P}^r}(\mathrm{Log}_{\mathbf{I}}(\mathbf{Q}^r))) \big)^{\frac{1}{r}}. \tag{1}$$

Definition 3.2. *The scalar multiplication $t \otimes \mathbf{P}$ where $t \in \mathbb{R}$ and $\mathbf{P} \in \mathcal{M}$ is obtained by projecting $\mathbf{P}$ in the tangent space at the identity element $\mathbf{I} \in \mathcal{M}$ with the logarithmic map, multiplying this projection by the scalar t in $T_{\mathbf{I}}\mathcal{M}$, and then projecting it back on the manifold with the exponential map, i.e.,*

$$t \otimes \mathbf{P} = \mathrm{Exp}_{\mathbf{I}}(t \, \mathrm{Log}_{\mathbf{I}}(\mathbf{P})). \tag{2}$$

3.1 Gyrovector Spaces of SPD Matrices

We investigate the gyro-structure of SPD manifolds with the AI and LE geometries in Sections 3.1.1 and 3.1.2, respectively. The AI and LE frameworks are reviewed in the supplemental material. We refer the interested reader to this document for our theoretical results that reveal hidden analogies between SPD manifolds with the AI and LE geometries and Euclidean spaces.

3.1.1 AI Gyrovector Spaces

We first examine SPD manifolds with the AI geometry. Lemma 3.3 gives a compact expression of the binary operation (matrix-matrix addition).

Lemma 3.3. *For $\mathbf{P}, \mathbf{Q} \in \mathrm{Sym}_n^+$, the binary operation $\mathbf{P} \oplus_{ai}^r \mathbf{Q}$ is given as*

$$\mathbf{P} \oplus_{ai}^r \mathbf{Q} = (\mathbf{P}^{\frac{r}{2}} \mathbf{Q}^r \mathbf{P}^{\frac{r}{2}})^{\frac{1}{r}}. \tag{3}$$

Proof See the supplemental material.

An implicit assumption in Eq. (3) is that positive definite matrices are taken from the computations related to matrix powers. This assumption is used in all computations in Sections 3.1.1 and 3.1.2.

The identity element of Sym_n^+ is the $n \times n$ identity matrix $\mathbf{I}_n$. Then, from Eq. (3), the inverse of $\mathbf{P}$ is given by

$$\ominus_{ai}^r \mathbf{P} = \mathbf{P}^{-1}.$$

Lemma 3.4. *For $\mathbf{P} \in \mathrm{Sym}_n^+$ and $t \in \mathbb{R}$, the scalar multiplication $t \otimes_{ai} \mathbf{P}$ is given as*

$$t \otimes_{ai} \mathbf{P} = \mathbf{P}^t. \tag{4}$$

Proof See the supplemental material.

Definition 3.5 (**AI Gyrovector Spaces**). *Define a binary operation $\oplus_{ai}^r$ and a scalar multiplication $\otimes_{ai}$ by Eqs. (3) and (4), respectively. Define a gyroautomorphism generated by $\mathbf{P}$ and $\mathbf{Q}$ as*

$$\mathrm{gyr}_{ai}^r[\mathbf{P}, \mathbf{Q}]\mathbf{R} = \big(F_{ai}^r(\mathbf{P}, \mathbf{Q})\mathbf{R}^r(F_{ai}^r(\mathbf{P}, \mathbf{Q}))^{-1} \big)^{\frac{1}{r}}, \tag{5}$$

where $F_{ai}^r(\mathbf{P}, \mathbf{Q}) = (\mathbf{P}^{\frac{r}{2}} \mathbf{Q}^r \mathbf{P}^{\frac{r}{2}})^{-\frac{1}{2}} \mathbf{P}^{\frac{r}{2}} \mathbf{Q}^{\frac{r}{2}}$.

Theorem 3.6. *Gyrogroups $(\mathrm{Sym}_n^+, \oplus_{ai}^r)$ with the scalar multiplication $\otimes_{ai}$ form gyrovector spaces $(\mathrm{Sym}_n^+, \oplus_{ai}^r, \otimes_{ai})$.*

Proof See the supplemental material.

We note that the expressions of the binary operation, scalar multiplication, and gyroautomorphism given in Eqs. (3), (4), and (5) have already been found in [1, 16, 17, 22, 23, 24, 25]. However, none of them pointed out the relations in Eqs. (1) and (2).

 3.1.2   LE Gyrovector Spaces

119   We now study the gyro-structure of SPD manifolds with the LE geometry.

120   **Lemma 3.7.** *For* $\mathbf{P}, \mathbf{Q} \in \mathrm{Sym}_n^+$, *the binary operation* $\mathbf{P} \oplus_{le}^r \mathbf{Q}$ *is given as*

$$\mathbf{P} \oplus_{le}^r \mathbf{Q} = \left(\exp(\log(\mathbf{P}^r) + \log(\mathbf{Q}^r)) \right)^{\frac{1}{r}}. \tag{6}$$

121   **Proof**   See the supplemental material.

122   From Lemma 3.7, the inverse of $\mathbf{P}$ is given by

$$\ominus_{le}^r \mathbf{P} = \mathbf{P}^{-1}.$$

123   Similarly to the scalar multiplication $\otimes_{ai}$, the scalar multiplication $\otimes_{le}$ is constructed from Eq. (2).
124   Lemma 3.8 gives an expression of this operation that is straightforward.

125   **Lemma 3.8.** *For* $\mathbf{P} \in \mathrm{Sym}_n^+$ *and* $t \in \mathbb{R}$, *the scalar multiplication* $t \otimes_{le} \mathbf{P}$ *is given by*

$$t \otimes_{le} \mathbf{P} = \mathbf{P}^t. \tag{7}$$

126   **Definition 3.9** (**LE Gyrovector Spaces**). *Define a binary operation* $\oplus_{le}^r$ *and a scalar multiplication*
127   $\otimes_{le}$ *by Eqs.* (6) *and* (7), *respectively. Define a gyroautomorphism generated by* $\mathbf{P}$ *and* $\mathbf{Q}$ *as*

$$\mathrm{gyr}_{le}^r[\mathbf{P}, \mathbf{Q}] = \mathrm{Id}.$$

128   **Theorem 3.10.** *Gyrogroups* $(\mathrm{Sym}_n^+, \oplus_{le}^r)$ *with the scalar multiplication* $\otimes_{le}$ *form gyrovector spaces*
129   $(\mathrm{Sym}_n^+, \oplus_{le}^r, \otimes_{le})$.

130   **Proof**   See the supplemental material.

131   The conclusion of Theorem 3.10 agrees with [3] which shows that the space of SPD matrices
132   with the LE geometry has a vector space structure. This vector space structure is given by the
133   operations defined in [3] that turn out to be the binary operation and scalar multiplication on LE
134   gyrovector spaces in the specific case where $r = 1$. Indeed, it can be shown that the mapping
135   $\exp : (\mathrm{Sym}_n, +, .) \to (\mathrm{Sym}_n^+, \oplus_{le}^r, \otimes_{le})$ is a vector space isomorphism. Thus, for any r, the
136   operations defined above also turn the space of SPD matrices with the LE geometry into a vector
137   space. This generalizes the result of [3].

138   **3.2   Grassmann Gyrocommutative and Gyrononreductive Gyrogroups**

139   We adopt the following definition for Grassmann manifolds:

$$\mathrm{Gr}_{n,p} = \{ \mathbf{P} \in \mathrm{M}_{n \times n} \,|\, \mathbf{P}^T = \mathbf{P}, \mathbf{P}^2 = \mathbf{P}, \mathrm{rank}(\mathbf{P}) = p \}.$$

140   The Riemannian geometry of Grassmann manifolds is reviewed in the supplemental material.

141   Let $\mathbf{I}_{n,p} = \begin{bmatrix} \mathbf{I}_p & 0 \\ 0 & 0 \end{bmatrix}$ be the identity element of $\mathrm{Gr}_{n,p}$. For the sake of convenience, we denote
142   $\overline{\mathbf{P}} = \mathrm{Log}_{\mathbf{I}_{n,p}}^{gr}(\mathbf{P})$. For $\mathbf{P}, \mathbf{Q} \in \mathrm{Gr}_{n,p}$, assuming that $\mathbf{I}_{n,p}$ and $\mathbf{P}$ are not in each other's cut locus (see
143   the supplemental material for a definition of cut locus of Grassmann manifolds), and $\mathbf{I}_{n,p}$ and $\mathbf{Q}$ are
144   not in each other's cut locus, the binary operation is defined as

$$\mathbf{P} \oplus_{gr} \mathbf{Q} = \mathrm{Exp}_{\mathbf{P}}^{gr}(\mathcal{T}_{\mathbf{I}_{n,p} \to \mathbf{P}}(\mathrm{Log}_{\mathbf{I}_{n,p}}^{gr}(\mathbf{Q}))).$$

145   **Lemma 3.11.** *For* $\mathbf{P}, \mathbf{Q} \in \mathrm{Gr}_{n,p}$, *the binary operation* $\mathbf{P} \oplus_{gr} \mathbf{Q}$ *is given as*

$$\mathbf{P} \oplus_{gr} \mathbf{Q} = \exp([\overline{\mathbf{P}}, \mathbf{I}_{n,p}]) \mathbf{Q} \exp(-[\overline{\mathbf{P}}, \mathbf{I}_{n,p}]), \tag{8}$$

146   *where* $[.,.]$ *denotes the matrix commutator.*

147   **Proof**   See the supplemental material.

148   Lemma 3.12 gives a closed-form expression of the binary operation in terms of $\mathbf{P}$ and $\mathbf{Q}$.

149   **Lemma 3.12.** *For* $\mathbf{P}, \mathbf{Q} \in \mathrm{Gr}_{n,p}$, *the binary operation* $\mathbf{P} \oplus_{gr} \mathbf{Q}$ *is given as*

$$\mathbf{P} \oplus_{gr} \mathbf{Q} = \exp\left(\frac{1}{2} \log \left((\mathbf{I}_n - 2\mathbf{P})(\mathbf{I}_n - 2\mathbf{I}_{n,p}) \right) \right) \mathbf{Q}$$

$$\exp\left(-\frac{1}{2} \log \left((\mathbf{I}_n - 2\mathbf{P})(\mathbf{I}_n - 2\mathbf{I}_{n,p}) \right) \right).$$

150 **Proof** See the supplemental material.

151 For $\mathbf{P} \in \mathrm{Gr}_{n,p}$ such that $\mathbf{I}_{n,p}$ and $\mathbf{P}$ are not in each other's cut locus, the inverse $\ominus_{gr}\mathbf{P}$ of $\mathbf{P}$ is
152 defined as

$$\ominus_{gr}\mathbf{P} = \mathrm{Exp}_{\mathbf{I}_{n,p}}^{gr}(-\mathrm{Log}_{\mathbf{I}_{n,p}}^{gr}(\mathbf{P})).$$

153 The scalar multiplication is defined as in Eq. (2) (subject to the assumption stated above).

154 **Lemma 3.13.** *For $\mathbf{P} \in \mathrm{Gr}_{n,p}$ and $t \in \mathbb{R}$, the scalar multiplication $t \otimes_{gr} \mathbf{P}$ is given by*

$$t \otimes_{gr} \mathbf{P} = \exp([t\overline{\mathbf{P}}, \mathbf{I}_{n,p}])\mathbf{I}_{n,p}\exp(-[t\overline{\mathbf{P}}, \mathbf{I}_{n,p}]). \tag{9}$$

155 **Proof** See the supplemental material.

156 Lemma 3.14 gives a closed-form expression of the scalar multiplication in terms of t and $\mathbf{P}$.

157 **Lemma 3.14.** *For $\mathbf{P} \in \mathrm{Gr}_{n,p}$ and $t \in \mathbb{R}$, the scalar multiplication $t \otimes_{gr} \mathbf{P}$ is given by*

$$t \otimes_{gr} \mathbf{P} = \exp\left(\frac{t}{2}\log\left((\mathbf{I}_n - 2\mathbf{P})(\mathbf{I}_n - 2\mathbf{I}_{n,p}))\right)\right)\mathbf{I}_{n,p}$$
$$\exp\left(-\frac{t}{2}\log\left((\mathbf{I}_n - 2\mathbf{P})(\mathbf{I}_n - 2\mathbf{I}_{n,p}))\right)\right).$$

158 **Proof** See the supplemental material.

159 Grassmann manifolds, when equipped with the above operations, do not form gyrovector spaces.
160 However, as we will show later, they still form spaces that verify most of the axioms of gyrovector
161 spaces. Note that since these operations can only be defined under the assumptions stated at the
162 beginning of this section, all the axioms in Section 2.1 must be considered under these assumptions.
163 We thus make them implicitly in the following. Now let us introduce some definitions and identities
164 required for the main result of this section.

165 **Definition 3.15** (**Nonreductive Gyrogroups**). *A groupoid $(G, \oplus)$ is a nonreductive gyrogroup if its*
166 *binary operation satisfies axioms (G1), (G2), and (G3).*

167 **Definition 3.16** (**Gyrocommutative and Gyrononreductive Gyrogroups**). *A nonreductive gy-*
168 *rogroup $(G, \oplus)$ is gyrocommutative and gyrononreductive if it satisfies the Gyrocommutative Law.*

169 **Definition 3.17** (**Nonreductive Gyrovector Spaces**). *A gyrocommutative and gyrononreductive*
170 *gyrogroup $(G, \oplus)$ equipped with a scalar multiplication $\odot$ is called a nonreductive gyrovector space*
171 *if it satisfies axioms (V1), (V2), (V3), (V4), and (V5).*

172 **Definition 3.18** (**Grassmann Gyrocommutative and Gyrononreductive Gyrogroups**). *Define*
173 *a binary operation $\oplus_{gr}$ and a scalar multiplication $\otimes_{gr}$ by Eqs. (8) and (9), respectively. For*
174 *$\mathbf{P}, \mathbf{Q} \in \mathrm{Gr}_{n,p}$, assuming that $\mathbf{I}_{n,p}$ and $\mathbf{P}$ are not in each other's cut locus, $\mathbf{I}_{n,p}$ and $\mathbf{Q}$ are not in*
175 *each other's cut locus, $\mathbf{I}_{n,p}$ and $\mathbf{P} \oplus_{gr} \mathbf{Q}$ are not in each other's cut locus, then a gyroautomorphism*
176 *generated by $\mathbf{P}$ and $\mathbf{Q}$ can be defined as*

$$\mathrm{gyr}_{gr}[\mathbf{P}, \mathbf{Q}]\mathbf{R} = F_{gr}(\mathbf{P}, \mathbf{Q})\mathbf{R}(F_{gr}(\mathbf{P}, \mathbf{Q}))^{-1}, \tag{10}$$

177 *where $F_{gr}(\mathbf{P}, \mathbf{Q})$ is given by*

$$F_{gr}(\mathbf{P}, \mathbf{Q}) = \exp(-[\overline{\mathbf{P} \oplus_{gr} \mathbf{Q}}, \mathbf{I}_{n,p}])\exp([\overline{\mathbf{P}}, \mathbf{I}_{n,p}])$$
$$\exp([\overline{\mathbf{Q}}, \mathbf{I}_{n,p}]). \tag{11}$$

178 **Lemma 3.19.** *For $\mathbf{P}, \mathbf{F} \in \mathrm{Gr}_{n,p}$, $\mathbf{O} \in \mathrm{O}_n$, $\Delta \in T_{\mathbf{P}}\mathrm{Gr}_{n,p}$, $m \in \mathbb{N}$, and $s \in \mathbb{R}$, the following*
179 *identities hold:*

180 *1. $\mathrm{Log}_{\mathbf{O}\mathbf{F}\mathbf{O}^T}^{gr}(\mathbf{O}\mathbf{P}\mathbf{O}^T) = \mathbf{O}\,\mathrm{Log}_{\mathbf{F}}^{gr}(\mathbf{P})\mathbf{O}^T$;*

181 *2. $\mathrm{Exp}_{\mathbf{O}\mathbf{P}\mathbf{O}^T}^{gr}(\mathbf{O}\Delta\mathbf{O}^T) = \mathbf{O}\,\mathrm{Exp}_{\mathbf{P}}^{gr}(\Delta)\mathbf{O}^T$;*

182 *3. $[\Delta, \mathbf{P}]^m = (\mathbf{I}_n - 2\mathbf{P})(-[\Delta, \mathbf{P}])^m(\mathbf{I}_n - 2\mathbf{P})$;*

183 *4. $\exp(s[\Delta, \mathbf{P}]) = (\mathbf{I}_n - 2\mathbf{P})\exp(-s[\Delta, \mathbf{P}])(\mathbf{I}_n - 2\mathbf{P})$.*

Proof See the supplemental material.

Theorem 3.20. *Groupoids* $(\mathrm{Gr}_{n,p}, \oplus_{gr})$ *form gyrocommutative and gyrononreductive gyrogroups. Furthermore, gyrocommutative and gyrononreductive gyrogroups* $(\mathrm{Gr}_{n,p}, \oplus_{gr})$ *with the scalar multiplication* $\otimes_{gr}$ *satisfy axioms (V1) and (V4), and axioms (V2), (V3), and (V5) under the following conditions:*

(V2) $(s+t) \otimes_{gr} \mathbf{P} = s \otimes_{gr} \mathbf{P} \oplus_{gr} t \otimes_{gr} \mathbf{P}$ *for* $\mathbf{P} \in \mathrm{Gr}_{n,p}$, $t \in \mathbb{R}$, *and* $s \in \mathbb{R}$ *such that:*

$$|s| < \min_{\lambda_i} \left\{ \frac{\pi}{2|\mathrm{Im}(\lambda_i)|} \right\},$$

where λ_i *is an eigenvalue of* $[\overline{\mathbf{P}}, \mathbf{I}_{n,p}]$, *and* $\mathrm{Im}(\lambda_i)$ *is the imaginary part of* λ_i.

(V3) $(st) \otimes_{gr} \mathbf{P} = s \otimes_{gr} (t \otimes_{gr} \mathbf{P})$ *for* $\mathbf{P} \in \mathrm{Gr}_{n,p}$, $s \in \mathbb{R}$, *and* $t \in \mathbb{R}$ *such that:*

$$|t| < \min_{\lambda_i} \left\{ \frac{\pi}{2|\mathrm{Im}(\lambda_i)|} \right\}.$$

(V5) $\mathrm{gyr}_{gr}[s \otimes_{gr} \mathbf{P}, t \otimes_{gr} \mathbf{P}] = \mathrm{Id}$ *for* $\mathbf{P} \in \mathrm{Gr}_{n,p}$, *and* $s, t \in \mathbb{R}$ *such that:*

$$\max\{|s|, |t|, |s+t|\} < \min_{\lambda_i} \left\{ \frac{\pi}{2|\mathrm{Im}(\lambda_i)|} \right\}.$$

Proof See the supplemental material.

The following corollaries might be useful in practice for the verification of axioms (V2), (V3), and (V5).

Corollary 3.21. *Gyrocommutative and gyrononreductive gyrogroups* $(\mathrm{Gr}_{n,p}, \oplus_{gr})$ *with the scalar multiplication* $\otimes_{gr}$ *satisfy axioms (V2), (V3), and (V5) if the right-hand sides of the inequalities stated in Theorem 3.20 are replaced with*

$$\frac{\pi}{2\|[\overline{\mathbf{P}}, \mathbf{I}_{n,p}]\|},$$

where $\|.\|$ *denotes the Hilbert-Schmidt norm.*

Proof See the supplemental material.

Corollary 3.22. *Gyrocommutative and gyrononreductive gyrogroups* $(\mathrm{Gr}_{n,p}, \oplus_{gr})$ *with the scalar multiplication* $\otimes_{gr}$ *satisfy axioms (V2), (V3), and (V5) under the following conditions: (V2)* $|s| \leq 1$; *(V3)* $|t| \leq 1$; *(V5)* $\max\{|s|, |t|, |s+t|\} \leq 1$.

Proof See the supplemental material.

It follows from Corollary 3.22 that if $\max\{|s|, |t|, |s+t|\} \leq 1$, then Grassmann manifolds, when equipped with the basic operations defined in Eqs. (8) and (9), verify all the axioms of nonreductive gyrovector spaces. Although they do not verify the Left Reduction Law, it is easy to show that they verify the Left Cancellation Law.

4   Applications

In this section, we propose new methods for human activity understanding and question answering. We refer the interested reader to the supplemental material for more applications.

4.1   Human Activity Understanding

Motivated by the work of [11] that develops recurrent neural networks (RNNs) on hyperbolic spaces, in this section, we propose a class of RNNs on SPD manifolds for human activity understanding. It is worth mentioning that the operations defined in Section 3.1 as well as those constructed in Section 4.1.1 can be used to build any type of neural networks on SPD manifolds, e.g., convolutional neural networks. However, since RNNs are based on update equations that involve the basic operations on matrices, they are well suited for validating our approach.

4.1.1 Proposed Method

We will make use of the basic operations on AI and LE gyrovector spaces and the concept of gyroderivative in these spaces (see the supplemental material) that is similar to hyperbolic derivative [4] in Möbius gyrovector spaces. We also need to generalize some operations of Euclidean RNNs to the SPD manifold setting. Here we focus on 2 operations, i.e., matrix scaling and pointwise nonlinearity.

Matrix Scaling   If $\mathbf{P} \in \mathrm{Sym}_n^+$ and $\mathbf{W} \in \mathbb{R}^n, \mathbf{W} > 0$, then the matrix scaling $\mathbf{W} \otimes_{spd}^v \mathbf{P}$ is given by

$$\mathbf{W} \otimes_{spd}^v \mathbf{P} = \mathbf{U} \operatorname{diag}(\mathbf{W} * \mathbf{V}) \mathbf{U}^T,$$

where $\mathbf{U} \operatorname{diag}(\mathbf{V}) \mathbf{U}^T$ is the eigenvalue decomposition of $\mathbf{P}$, and $\mathbf{W} * \mathbf{V}$ is the element-wise multiplication.

Pointwise nonlinearity   If φ is a pointwise nonlinear activation function, then the pointwise nonlinearity $\varphi^{\otimes_a}(\mathbf{P})$ is given by

$$\varphi^{\otimes_a}(\mathbf{P}) = \mathbf{U} \operatorname{diag}(\max(\epsilon \mathbf{I}, \varphi(\mathbf{V}))) \mathbf{U}^T,$$

where $\epsilon > 0$ is a rectification threshold, and $\mathbf{U} \operatorname{diag}(\mathbf{V}) \mathbf{U}^T$ is the eigenvalue decomposition of $\mathbf{P}$.

By adapting a class of models that are invariant to time rescaling [36] to the SPD manifold setting using the gyro-chain-rule in AI and LE gyrovector spaces (see the supplemental material), we obtain the following update equations for our models:

$$\mathbf{P}_t = \varphi^{\otimes_a}(\mathbf{W}_h \otimes_{spd}^v \mathbf{H}_{t-1} + \mathbf{W}_x \otimes_{spd}^v \mathbf{X}_t), \tag{12}$$

$$\mathbf{H}_t = \mathbf{H}_{t-1} \oplus \alpha \odot ((\ominus \mathbf{H}_{t-1}) \oplus \mathbf{P}_t), \tag{13}$$

where $\mathbf{X}_t \in \mathrm{Sym}_n^+$ is the input at frame t, $\mathbf{H}_{t-1}, \mathbf{H}_t \in \mathrm{Sym}_n^+$ are the hidden states at frames $t-1$ and t, respectively, $\mathbf{W}_h, \mathbf{W}_x \in \mathbb{R}^n$, and $\alpha \in \mathbb{R}$ is a learnable parameter.

4.1.2 Results

We use three datasets, i.e., HDM05 [15], FPHA [12], and NTU RGB+D 60 (NTU60) [32]. These datasets include three different types of activities: body actions (HDM05), hand actions (FPHA), and interaction actions (NTU60). We compare our networks against state-of-the-art methods from four categories, i.e., SPD neural networks, Euclidean RNNs, transformers, and HNNs. In the same spirit of previous works [5, 19, 34], we are interested in comparing manifold networks with a focus on SPD manifolds, and do not necessarily seek state-of-the-art performance for the target task. We use a temporal pyramid representation for each sequence. At temporal pyramid M, a given sequence is partitioned into M subsequences of equal size. Each subsequence is then fed to a model with its own parameter set. The outputs from all the models are concatenated to create a final representation of the sequence. We run each model three times and report the best accuracy from these three runs [11]. The implementation details, network architecture, and experimental settings can be found in the supplemental material. This document also provides the mean accuracies and standard deviations of some representative methods, an ablation study, and a comparison of our networks against graph neural networks (GNNs).

Comparison against SPD Neural Networks   Our networks, referred to as GyroAI-HAUNet and GyroLE-HAUNet, are compared against SPDNet [19], SPDNetBN [5], and SPD-SRU [7]. Results of these networks are obtained using their official code[1,2,3] with default parameter settings. Results for $M = 1$ and $M = 3$[4] are given in Tab. 1. On HDM05 dataset, GyroAI-HAUNet outperforms SPDNet and SPD-SRU, and performs worse than SPDNetBN when $M = 1$. However, when $M = 3$, GyroAI-HAUNet gives the best result among the competing networks. On FPHA and NTU60 datasets, GyroAI-HAUNet gives the best results for both $M = 1$ and $M = 3$. In terms of model size,

---

[1] https://github.com/zhiwu-huang/SPDNet

[2] https://papers.nips.cc/paper/2019/hash/6e69ebbfad976d4637bb4b39de261bf7-Abstract.html

[3] https://github.com/zhenxingjian/SPD-SRU/tree/master

[4] For all the networks, setting $M > 3$ did not yield better results on the three datasets.

Table 1: Accuracy comparison (%) of our networks against state-of-the-art SPD neural networks.

Dataset	SPDNet		SPDNetBN		SPD-SRU		GyroAI-HAUNet		GyroLE-HAUNet	
	$M=1$	$M=3$	$M=1$	$M=3$	$M=1$	$M=3$	$M=1$	$M=3$	$M=1$	$M=3$
HDM05	58.44	72.75	62.54	76.25	42.26	54.79	61.50	78.14	57.01	74.53
#HDM05	0.12 MB	0.77 MB	0.13 MB	0.82 MB	0.05 MB	0.32 MB	0.05 MB	0.31 MB	0.05 MB	0.31 MB
FPHA	87.65	88.17	88.52	91.83	78.57	85.16	89.73	96.00	83.03	89.94
#FPHA	0.04 MB	0.28 MB	0.05 MB	0.31 MB	0.019 MB	0.114 MB	0.018 MB	0.110 MB	0.018 MB	0.110 MB
NTU60	73.26	77.38	75.84	79.52	66.25	75.34	83.12	94.72	77.25	89.44
#NTU60	0.03 MB	0.20 MB	0.04 MB	0.28 MB	0.004 MB	0.027 MB	0.004 MB	0.026 MB	0.004 MB	0.026 MB

Table 2: Accuracy comparison (%) of our networks against LSTM, ST-TR, and HypGRU.

Dataset	LSTM		ST-TR		HypGRU		GyroAI-HAUNet		GyroLE-HAUNet	
	$M=1$	$M=3$	$M=1$	$M=3$	$M=1$	$M=3$	$M=1$	$M=3$	$M=1$	$M=3$
HDM05	49.42	72.82	69.75	76.12	51.35	58.50	61.50	78.14	57.01	74.53
#HDM05	0.09 MB	0.54 MB	4.62 MB	27.73 MB	0.10 MB	0.61 MB	0.05 MB	0.31 MB	0.05 MB	0.31 MB
FPHA	66.43	81.22	86.32	91.34	56.70	61.42	89.73	96.00	83.03	89.94
#FPHA	0.07 MB	0.41 MB	4.59 MB	27.55 MB	0.08 MB	0.47 MB	0.02 MB	0.11 MB	0.02 MB	0.11 MB
NTU60	85.39	87.27	92.18	93.78	86.51	88.03	83.12	94.72	77.25	89.44
#NTU60	0.006 MB	0.035 MB	4.58 MB	27.50 MB	0.006 MB	0.039 MB	0.004 MB	0.026 MB	0.004 MB	0.026 MB

GyroAI-HAUNet and GyroLE-HAUNet require far fewer parameters than SPDNet and SPDNetBN in all cases. For example, on FPHA dataset, when $M=3$, GyroAI-HAUNet outperforms SPDNetBN by 4.17% with 2.8 times fewer parameters. Also, on NTU60 dataset, when $M=3$, GyroAI-HAUNet outperforms SPDNetBN by 15.20% with 10.7 times fewer parameters.

Comparison against Euclidean RNNs, transformers, and HNNs Our networks are compared against LSTM, ST-TR [31], and HypGRU [11]. Results of LSTM are obtained using its implementation provided by the Tensorflow framework. Those of ST-TR and HypGRU are obtained using their official code.[5,6] Results for $M=1$ and $M=3$ are shown in Tab. 2. We can observe that our models outperform the competing models by large margins in most cases. Furthermore, our models are more advantageous than these models in terms of model size.

4.2 Question Answering

In this section, we consider learning word embeddings in $\mathrm{Gr}_{n,p}$. We also investigate the use of product manifold $\mathrm{Gr}_{n_1,p} \times \mathrm{Sym}_{n_2}^+$ for training word embeddings. This idea is mainly motivated by the works of [8, 13] that show the efficacy of mixed-curvature representations for graph embeddings.

4.2.1 Proposed Method

The core idea is to learn a scoring function [27, 37] given as

$$\phi_{qa}(q, a) = -w_f d(\mathbf{Q}, \mathbf{A}) + w_b,$$

where $\mathbf{Q}$ and $\mathbf{A}$ are embeddings of question q and answer a, respectively, $w_f, w_b \in \mathbb{R}$ are parameters of the model, and $d(.)$ is a distance function in the target manifolds. We define a matrix scaling operation as follows.

Matrix Scaling We parameterize a point $\mathbf{P} \in \mathrm{Gr}_{n,p}$ by a matrix $\mathbf{B} \in \mathrm{M}_{p,n-p}$ such that

$$\begin{bmatrix} 0 & \mathbf{B} \\ -\mathbf{B}^T & 0 \end{bmatrix} = [\bar{\mathbf{P}}, \mathbf{I}_{n,p}].$$

Then point $\mathbf{P}$ can be computed (see Eq. (8) and the supplemental material) by

$$\mathbf{P} = \exp([\bar{\mathbf{P}}, \mathbf{I}_{n,p}])\mathbf{I}_{n,p}\exp(-[\bar{\mathbf{P}}, \mathbf{I}_{n,p}]) = \exp\left(\begin{bmatrix} 0 & \mathbf{B} \\ -\mathbf{B}^T & 0 \end{bmatrix} \right)\mathbf{I}_{n,p}\exp\left(-\begin{bmatrix} 0 & \mathbf{B} \\ -\mathbf{B}^T & 0 \end{bmatrix} \right).$$

---

[5] https://github.com/Chiaraplizz/ST-TR
[6] https://github.com/dalab/hyperbolic_nn

Table 3: Comparison of our models against the SPD models of [27]. The SPD models learn embeddings in Sym_{14}^+. Our Grassmann model learns embeddings in $\mathrm{Gr}_{14,7}$. Our models based on the product manifold learn embeddings in $\mathrm{Gr}_{14,7} \times \mathrm{Sym}_8^+$. Results (mean $\pm$ standard deviation) are computed over three runs.

DOF	Model	TrecQA		WikiQA		Time (TrecQA,seconds)	
		MAP	MRR	MAP	MRR	Train/epoch	Test
105	$\mathrm{SPD}_{\mathrm{Sca}}^R$	47.77 ± 0.18	57.54 ± 0.32	59.42 ± 0.04	60.57 ± 0.05	15.35	1.41
105	$\mathrm{SPD}_{\mathrm{Sca}}^{F_1}$	48.35 ± 1.24	57.64 ± 2.23	60.68 ± 0.42	62.01 ± 0.34	15.56	1.43
105	$\mathrm{SPD}_{\mathrm{Rot}}^R$	48.07 ± 0.89	54.49 ± 0.87	59.37 ± 1.25	60.74 ± 1.50	15.98	1.41
105	$\mathrm{SPD}_{\mathrm{Rot}}^{F_1}$	49.02 ± 1.62	58.72 ± 1.85	60.60 ± 0.67	62.28 ± 0.74	16.09	1.43
105	$\mathrm{SPD}_{\mathrm{Ref}}^R$	48.79 ± 0.91	57.12 ± 1.23	59.07 ± 0.53	60.58 ± 0.52	15.98	1.41
105	$\mathrm{SPD}_{\mathrm{Ref}}^{F_1}$	48.33 ± 0.48	56.18 ± 0.97	59.93 ± 0.18	61.80 ± 0.39	16.09	1.43
49	GyroGR-QANet	50.18 ± 1.29	58.19 ± 2.59	56.69 ± 1.45	58.26 ± 1.45	3.69	0.25
85	GyroGR-SPD$_{\mathrm{Sca}}^{F_1}$-QANet	50.10 ± 0.30	57.70 ± 0.93	60.62 ± 0.25	62.42 ± 0.16	11.62	0.90
85	GyroGR-SPD$_{\mathrm{Rot}}^{F_1}$-QANet	50.27 ± 0.56	58.62 ± 1.35	59.78 ± 0.15	61.66 ± 0.23	11.72	0.90
85	GyroGR-SPD$_{\mathrm{Ref}}^{F_1}$-QANet	48.83 ± 1.89	58.11 ± 0.87	60.41 ± 0.39	61.86 ± 0.35	11.72	0.90

The matrix scaling $\otimes_{gr}^m$ is defined as

$$\mathbf{A} \otimes_{gr}^m \mathbf{P} = \exp\left(\begin{bmatrix} 0 & \mathbf{A}*\mathbf{B} \\ -(\mathbf{A}*\mathbf{B})^T & 0 \end{bmatrix}\right)\mathbf{I}_{n,p}\exp\left(-\begin{bmatrix} 0 & \mathbf{A}*\mathbf{B} \\ -(\mathbf{A}*\mathbf{B})^T & 0 \end{bmatrix}\right),$$

where $\mathbf{A} \in \mathrm{M}_{p,n-p}$. The embedding of question q is computed from those of its tokens as

$$\mathbf{Q} = \mathbf{B} \oplus_{gr} \left((\mathbf{S} \otimes_{gr}^m \mathbf{T}_1) \oplus_{gr} (\mathbf{S} \otimes_{gr}^m \mathbf{T}_2)\ldots \oplus_{gr} (\mathbf{S} \otimes_{gr}^m \mathbf{T}_l)\right),$$

where $\mathbf{T}_i \in \mathrm{Gr}_{n,p}, i = 1,\ldots,l$ are embeddings of the tokens in question q, $\mathbf{S} \in \mathrm{M}_{p,n-p}$ and $\mathbf{B} \in \mathrm{Gr}_{n,p}$ are parameters of the model. The embedding of answer a is the summation of those of its tokens using operation $\oplus_{gr}$. For $\mathbf{P}, \mathbf{Q} \in \mathrm{Gr}_{n,p}$, the distance function $d(.,.)$ is defined as

$$d(\mathbf{P},\mathbf{Q}) = d_{gr}(\mathbf{P},\mathbf{Q}) = \|\mathbf{P}-\mathbf{Q}\|_F.$$

We also train word embeddings in product manifold $\mathrm{Gr}_{n_1,p} \times \mathrm{Sym}_{n_2}^+$ using the distance function

$$d((\mathbf{P}_{gr},\mathbf{P}_{spd}),(\mathbf{Q}_{gr},\mathbf{Q}_{spd})) = d_{gr}(\mathbf{P}_{gr},\mathbf{Q}_{gr}) + \tau d_{spd}^{F_1}(\mathbf{P}_{spd},\mathbf{Q}_{spd}),$$

where $\mathbf{P}_{gr}, \mathbf{Q}_{gr} \in \mathrm{Gr}_{n_1,p}$, $\mathbf{P}_{spd}, \mathbf{Q}_{spd} \in \mathrm{Sym}_{n_2}^+$, $d_{spd}^{F_1}(.,.)$ is the Finsler distance function proposed in [27], and τ is a constant. This results in three models based on the scaling, rotation, and reflection transformations of [27].

4.2.2 Results

We use two datasets, i.e., TrecQA [41] (clean version) and WikiQA [43]. The mean average precision (MAP) and mean reciprocal rank (MRR) are used as evaluation metrics [37]. We compare our models[7] against the SPD models of [27]. Since the codes of these models are not publicly available, we implemented them by following closely the instructions in [27]. The implementation details and experimental settings can be found in the supplemental material.

Tab. 3 reports the means and standard deviations of MAP and MRR from three runs (DOF stands for degrees of freedom). Our Grassmann model GyroGR-QANet performs favorably against most of the SPD models on TrecQA dataset. Also, results of our models based on the product manifold show the efficacy of mixed-curvature representations [8, 13] in question answering. Note that the numbers of DOF of our models are smaller than those of the SPD models. We also note that techniques in [18, 26] could potentially improve the performance of our models.

5 Conclusion

We have shown that the AI and LE geometries of SPD manifolds have strong connection to hyperbolic geometry, and Grassmann manifolds share very similar properties with gyrovector spaces. We have presented new methods for human activity understanding and question answering.

---

[7]Code available at https://github.com/spratmnt/qa.

References

[1] T. Abe and O. Hatori. Generalized Gyrovector Spaces and a Mazur–Ulam Theorem. *Publicationes Mathematicae Debrecen*, 87:393–413, 2015. 1, 3

[2] P.-A. Absil, R. Mahony, and R. Sepulchre. *Optimization Algorithms on Matrix Manifolds*. Princeton University Press, 2007. 1

[3] V. Arsigny, P. Fillard, X. Pennec, and N. Ayache. Fast and Simple Computations on Tensors with Log-Euclidean Metrics. Technical Report RR-5584, INRIA, 2005. 1, 4

[4] G. S. Birman and A. A. Ungar. The Hyperbolic Derivative in the Poincaré Ball Model of Hyperbolic Geometry. *Journal of Mathematical Analysis and Applications*, 254(1):321–333, 2001. 7

[5] D. A. Brooks, O. Schwander, F. Barbaresco, J.-Y. Schneider, and M. Cord. Riemannian Batch Normalization for SPD Neural Networks. In *NeurIPS*, pages 15463–15474, 2019. 1, 7

[6] R. Chakraborty, J. Bouza, J. Manton, and B. C. Vemuri. ManifoldNet: A Deep Neural Network for Manifold-valued Data with Applications. *TPAMI*, 44(2):799–810, 2020. 1

[7] R. Chakraborty, C.-H. Yang, X. Zhen, M. Banerjee, D. Archer, D. E. Vaillancourt, V. Singh, and B. C. Vemuri. A Statistical Recurrent Model on the Manifold of Symmetric Positive Definite Matrices. In *NeurIPS*, pages 8897–8908, 2018. 1, 7

[8] C. Cruceru, G. Bécigneul, and O.-E. Ganea. Computationally Tractable Riemannian Manifolds for Graph Embeddings. In *AAAI*, pages 7133–7141, 2021. 8, 9

[9] Z. Dong, S. Jia, C. Zhang, M. Pei, and Y. Wu. Deep Manifold Learning of Symmetric Positive Definite Matrices with Application to Face Recognition. In *AAAI*, pages 4009–4015, 2017. 1

[10] M. Engin, L. Wang, L. Zhou, and X. Liu. DeepKSPD: Learning Kernel-matrix-based SPD Representation for Fine-grained Image Recognition. In *ECCV*, pages 629–645, 2018. 1

[11] O. Ganea, G. Becigneul, and T. Hofmann. Hyperbolic neural networks. In *NeurIPS*, page 5350–5360, 2018. 1, 6, 7, 8

[12] G. Garcia-Hernando, S. Yuan, S. Baek, and T.-K. Kim. First-Person Hand Action Benchmark with RGB-D Videos and 3D Hand Pose Annotations. In *CVPR*, pages 409–419, 2018. 7

[13] A. Gu, F. Sala, B. Gunel, and C. Ré. Learning Mixed-Curvature Representations in Products of Model Spaces. In *ICLR*, 2019. 8, 9

[14] M. Harandi, M. Salzmann, and R. Hartley. Dimensionality Reduction on SPD Manifolds: The Emergence of Geometry-Aware Methods. *TPAMI*, 40:48–62, 2018. 1

[15] M. T. Harandi, M. Salzmann, and R. Hartley. From Manifold to Manifold: Geometry-Aware Dimensionality Reduction for SPD Matrices. In *ECCV*, pages 17–32, 2014. 1, 7

[16] O. Hatori. Examples and Applications of Generalized Gyrovector Spaces. *Results in Mathematics*, 71:295–317, 2017. 1, 3

[17] O. Hatori. Extension of Isometries in Generalized Gyrovector Spaces of the Positive Cones. *Contemporary Mathematics - American Mathematical Society*, 687:145–156, 2017. 1, 3

[18] K. Helfrich, D. Willmott, and Q. Ye. Orthogonal Recurrent Neural Networks with Scaled Cayley Transform. In *ICML*, pages 1974–1983, 2018. 9

[19] Z. Huang and L. V. Gool. A Riemannian Network for SPD Matrix Learning. In *AAAI*, pages 2036–2042, 2017. 1, 7

[20] Z. Huang, C. Wan, T. Probst, and L. V. Gool. Deep Learning on Lie Groups for Skeleton-Based Action Recognition. In *CVPR*, pages 6099–6108, 2017. 1

[21] Z. Huang, J. Wu, and L. V. Gool. Building Deep Networks on Grassmann Manifolds. In *AAAI*, pages 3279–3286, 2018. 1

[22] S. Kim. Distributivity on the Gyrovector Spaces. *Kyungpook Mathematical Journal*, 55:13–20, 2015. 1, 2, 3

[23] S. Kim. Gyrovector Spaces on the Open Convex Cone of Positive Definite Matrices. *Mathematics Interdisciplinary Research*, 1(1):173–185, 2016. 1, 2, 3

[24] S. Kim. Operator Inequalities and Gyrolines of the Weighted Geometric Means. *CoRR*, abs/2009.10274, 2020. 1, 2, 3

[25] S. Kim. Ordered Gyrovector Spaces. *Symmetry*, 12(6), 2020. 1, 2, 3

[26] M. Lezcano-Casado. Trivializations for Gradient-Based Optimization on Manifolds. In *NeurIPS*, pages 9154–9164, 2019. 9

[27] F. López, B. Pozzetti, S. Trettel, M. Strube, and A. Wienhard. Vector-valued Distance and Gyrocalculus on the Space of Symmetric Positive Definite Matrices. In *NeurIPS*, pages 18350–18366, 2021. 1, 8, 9

[28] X. S. Nguyen. GeomNet: A Neural Network Based on Riemannian Geometries of SPD Matrix Space and Cholesky Space for 3D Skeleton-Based Interaction Recognition. In *ICCV*, pages 13379–13389, 2021. 1

[29] X. S. Nguyen, L. Brun, O. Lézoray, and S. Bougleux. Learning Recurrent High-order Statistics for Skeleton-based Hand Gesture Recognition. In *ICPR*, pages 975–982, 2020. 1

[30] X. Pennec. *Statistical Computing on Manifolds for Computational Anatomy*. Habilitation à diriger des recherches, Université Nice Sophia-Antipolis, 2006. 1

[31] C. Plizzari, M. Cannici, and M. Matteucci. Skeleton-based Action Recognition via Spatial and Temporal Transformer Networks. *Computer Vision and Image Understanding*, 208:103219, 2021. 8

[32] A. Shahroudy, J. Liu, T.-T. Ng, and G. Wang. NTU RGB+D: A Large Scale Dataset for 3D Human Activity Analysis. In *CVPR*, pages 1010–1019, 2016. 7

[33] R. Shimizu, Y. Mukuta, and T. Harada. Hyperbolic Neural Networks++. In *ICLR*, 2021. 1

[34] R. S. Sukthanker, Z. Huang, S. Kumar, E. G. Endsjo, Y. Wu, and L. V. Gool. Neural Architecture Search of SPD Manifold Networks. In *IJCAI*, pages 3002–3009, 2021. 1, 7

[35] H. Tabia, H. Laga, D. Picard, and P.-H. Gosselin. Covariance Descriptors for 3D Shape Matching and Retrieval. In *CVPR*, pages 4185–4192, 2014. 1

[36] C. Tallec and Y. Ollivier. Can Recurrent Neural Networks Warp Time? In *ICLR*, 2018. 7

[37] Y. Tay, A. T. Luu, and S. C. Hui. Hyperbolic Representation Learning for Fast and Efficient Neural Question Answering. *ACM International Conference on Web Search and Data Mining*, pages 583–591, 2018. 8, 9

[38] A. A. Ungar. *Beyond the Einstein Addition Law and Its Gyroscopic Thomas Precession: The Theory of Gyrogroups and Gyrovector Spaces*. Fundamental Theories of Physics, vol. 117, Springer, Netherlands, 2002. 1, 2

[39] A. A. Ungar. *Analytic Hyperbolic Geometry: Mathematical Foundations and Applications*. World Scientific Publishing Co. Pte. Ltd., Hackensack, NJ, 2005. 1, 2

[40] A. A. Ungar. *Analytic Hyperbolic Geometry in N Dimensions: An Introduction*. CRC Press, 2014. 1, 2

[41] M. Wang, N. A. Smith, and T. Mitamura. What is the Jeopardy Model? A Quasi-Synchronous Grammar for QA. In *Joint Conference on Empirical Methods in Natural Language Processing and Computational Natural Language Learning*, pages 22–32, 2007. 9

[42] R. Wang, X.-J. Wu, and J. Kittler. SymNet: A Simple Symmetric Positive Definite Manifold Deep Learning Method for Image Set Classification. *IEEE Transactions on Neural Networks and Learning Systems*, pages 1–15, 2021. 1

[43] Y. Yang, W.-t. Yih, and C. Meek. WikiQA: A Challenge Dataset for Open-Domain Question Answering. In *Conference on Empirical Methods in Natural Language Processing*, pages 2013–2018, 2015. 9