GT-GAN: General Purpose Time Series Synthesis with Generative Adversarial Networks

Abstract

Time series synthesis is an important research topic in the field of deep learning, which can be used for data augmentation. Time series data types can be broadly classified into regular or irregular. However, there are no existing generative models that show good performance for both types without any model changes. Therefore, we present a general purpose model capable of synthesizing regular and irregular time series data. To our knowledge, we are the first designing a general purpose time series synthesis model, which is one of the most challenging settings for time series synthesis. To this end, we design a generative adversarial network-based method, where many related techniques are carefully integrated into a single framework, ranging from neural ordinary/controlled differential equations to continuous time-flow processes. Our method outperforms all existing methods.

1 Introduction

Time series data occurs frequently in real-world applications [Reinsel, 2003, Fu, 2011, Li et al., 2018, Yu et al., 2018, Wu et al., 2019, Guo et al., 2019, Bai et al., 2019, Song et al., 2020, Huang et al., 2020a, Ren et al., 2021, Tekin et al., 2021]. Among many tasks related to time series, synthesizing time series data is one of the most important tasks because real-world time series data is frequently imbalanced and/or insufficient. Since regular and irregular time series data have different characteristics, however, different model designs had been adopted for them. Therefore, existing time series synthesis work focuses on either regular or irregular time series synthesis [Yoon et al., 2019, Alaa et al., 2021]. To our knowledge, there are no existing methods that work well for both types.

Regular time series means regularly sampled observations without any missing ones, and irregular times series means that some observations are missing from time to time. Irregular time series is much harder to process than regular time series. For instance, it is known that neural networks perform better after transforming time series data into its frequency domain, i.e., the Fourier transform, and some time series generative models use this approach [Alaa et al., 2021]. However, it prevents the Fourier transform of time series from being used as a pre-processing method in the case of irregular time series since it is not easy to observe pre-determined frequencies from highly irregular time series [Kidger et al., 2019]. Therefore, we propose a general purpose model that can synthesize both time series types without any model changes.

To achieve the goal, we design a sophisticated model which utilizes a diverse set of technologies, ranging from generative adversarial networks (GANs [Goodfellow et al., 2014]), and autoencoders (AEs) to neural ordinary differential equations (NODEs [Chen et al., 2018]), neural controlled differential equations (NCDEs [Kidger et al., 2020]), and continuous time-flow processes (CTFPs [Deng et al., 2020]), which reflects the difficulty of the problem.

Fig. 1 shows the overall design of our proposed method. One of the key points in our model design is that we combine the *adversarial* training of GANs and the *exact maximum likelihood* training of

Figure 1: The overall design of our method, GT-GAN. Each color means a separate workflow. The autoencoder and the GAN share the workload to synthesize regular and irregular time series.

CTFPs into a single framework. However, the exact maximum likelihood training is applicable only to invertible mapping functions whose input and output sizes are the same. Therefore, we design an *invertible* generator, and adopt an autoencoder, on whose hidden space our GAN performs the adversarial training.

Figure 2: An example of sampling two irregular series from a fake continuous path represented by an ordinary differential equation (ODE). In other words, we solve ODE problems to sample regular/irregular time series.

In other words, i) the hidden vector size of the encoder is the same as the noisy vector of the generator, ii) the generator produces a set of fake hidden vectors, iii) the decoder converts the set into a fake continuous path (cf. Fig. 2), and iv) the discriminator provides feedback after reading the sampled fake sample. We note that in the third step, a fake continuous path is created by the decoder. Therefore, we can sample any arbitrary regular/irregular time series sample from the fake path, which shows the flexibility in our method.

We conduct experiments with 4 datasets and 7 baselines. Since our method is able to support both the regular and irregular time series synthesis, we test for both of them. Our method outperforms other baselines in both environments. Our contributions can be summarized as follows:

1. We design a model based on various state-of-the-art deep learning technologies. Our method is able to process any types of time series data, ranging from regular to irregular, without any model changes.

2. Our experimental results and visualization prove the efficacy of the proposed model.

3. Since our task is one of the most challenging tasks for time series synthesis, the proposed model architecture is carefully designed. Our ablation studies show that our proposed model does not work well if any part is missing.

2 Related work and preliminaries

GANs are one of the most representative generative technology. Ever since the first introduction in its seminal research paper, GANs have been adopted to main different domains. Recently, researchers focused on their synthesis for time series data. Therefore, there have been proposed several GANs for time series synthesis. C-RNN-GAN [Mogren, 2016] has a regular GAN framework that can be applied to sequential data by using LSTM in its generator and discriminator. Recurrent Conditional GAN (RCGAN [Esteban et al., 2017]) took a similar approach except that its generator and discriminator take conditional input for better synthesis. WaveNet [van den Oord et al., 2016] also generates time series data from the conditional probability of previous data by using the dilated casual convolution. WaveGAN [Donahue et al., 2019] has a similar approach with DCGAN [Radford et al., 2016], where its generator is based on WaveNet. We can modify the teacher-forcing (T-Forcing [Graves, 2014]) and professor-forcing (P-Forcing [Lamb et al., 2016]) models to generate time series data from noise vectors, although they are not GAN models, by using the forecasting characteristic of those models.

Figure 3: The detailed architecture of our proposed method. Neural CDEs (or NCDEs) are a recent breakthrough for processing time series. GRU-ODEs are a continuous interpretation of gated recurrent units (GRUs) based on NODEs. CTFPs are a flow-based concept to convert an input time series process into a target process. CTFPs are not a GAN-based concept but we integrate them into our framework, considering the challenging nature of the general purpose time series synthesis.

TimeGAN [Yoon et al., 2019] is yet another model for time series synthesis. This model aims mainly at synthesizing fake *regular* time series samples. They proposed a framework where the adversarial training of GANs and the supervised training of predicting $\mathbf{x}_{i+1}$ from $\mathbf{x}_i$, where $\mathbf{x}_i$ and $\mathbf{x}_{i+1}$ mean two multivariate time series values at time t_i and t_{i+1}, respectively.

3 Proposed method

In this section, we describe our design. Since our general purpose time series synthesis is a challenging task, the proposed design is much more complicated than other baselines.

3.1 Overall workflow

We first describe the overall workflow in our model design, which consists of several different data paths (and several different training methods based on the data paths) as follows:

1. **Autoencoder path:** Given an time series sample $\{(t_i, \mathbf{x}_i^{real})\}_{i=0}^N$, the encoder produces a set of hidden vectors $\{\mathbf{h}_i^{real}\}_{i=0}^N$. The decoder recovers a continuous path $\hat{X}^{real}$, which enhances the flexibility of our proposed method. From the path $\hat{X}^{real}$, we sample $\{(t_i, \hat{\mathbf{x}}_i^{real})\}_{i=0}^N$. We train the encoder and the decoder using the standard autoencoder (AE) loss to match $\mathbf{x}_i^{real}$ and $\hat{\mathbf{x}}_i^{real}$ for all i.

2. **Adversarial path:** Given a set of noisy vectors $\{\mathbf{z}_i\}_{i=0}^N$, our generator produces a set of fake hidden vectors $\{\mathbf{h}_i^{fake}\}_{i=0}^N$. The decoder recovers a fake continuous path $\hat{X}^{fake}$ from $\{\mathbf{h}_i^{fake}\}_{i=0}^N$. We sample $\{(t_j, \mathbf{x}_j^{fake})\}_{j=0}^M$ from $\hat{X}^{fake}$ and feed it into the discriminator. For irregular time series synthesis, we sample t_j in $[0, T]$. We train the generator, the decoder, and the discriminator using the standard adversarial loss.

3. **Log-density path:** Given a set of hidden vectors $\{\mathbf{h}_i^{real}\}_{i=0}^N$ for an time series sample $\{(t_i, \mathbf{x}_i^{real})\}_{i=0}^N$, the inverse path of the generator reproduces a set of noisy vectors $\{\hat{\mathbf{z}}_i\}_{i=0}^N$. We feed $\{\hat{\mathbf{z}}_i\}_{i=0}^N$ into its forward path again to reproduce $\{\hat{\mathbf{h}}_i^{real}\}_{i=0}^N$, where $\hat{\mathbf{h}}_i^{real} = \mathbf{h}_i^{real}$ for all i. During the forward pass, we calculate the negative log probability of $-\log p(\hat{\mathbf{h}}_i^{real})$ for all i with the change of variable theorem and minimize it for training, being inspired by Grover et al. [2018] and Deng et al. [2020].

In particular, we note that the dimensionality of the hidden space in the autoencoder is the same as that of the latent input space of the generator, i.e., $\dim(\mathbf{h}) = \dim(\mathbf{z})$. This is needed for the exact likelihood training in the generator — the change of variable theorem requires that the input and output sizes are the same to estimate the exact likelihood. In addition to it, we let the autoencoder and the generator share the workload to synthesize fake time series by combining them into a single framework, i.e., the generator synthesizes fake hidden vectors and the decoder reproduces human-readable fake time series from them.

3.2 Autoencoder

Encoder General NCDEs, which are considered as a continuous analogue to recurrent neural networks (RNNs), are defined as follows:

$$
\begin{aligned}
\mathbf{h}(t_{i+1}) &= \mathbf{h}(t_i) + \int_{t_i}^{t_{i+1}} f(\mathbf{h}(t); \theta_f) dX(t) \\
&= \mathbf{h}(t_i) + \int_{t_i}^{t_{i+1}} f(\mathbf{h}(t); \theta_f) \frac{dX(t)}{dt} dt,
\end{aligned}
\tag{1}
$$

where $X(t)$ is a continuous path created from a raw discrete time series sample $\{(t_i, \mathbf{x}_i^{real})\}_{i=0}^N$ by an interpolation algorithm — we note that $X(t_i) = (t_i, \mathbf{x}_i^{real})$ for all i, and for other non-observed time-points the interpolation algorithm fills out values. Note that NCDEs keep reading the time-derivative of $X(t)$, denoted $\dot{X}(t) \overset{\text{def}}{=} \frac{dX(t)}{dt}$. In our case, we collect $\{\mathbf{h}_i^{real}\}_{i=0}^N$ as follows:

$$
\mathbf{h}_{i+1}^{real} = \mathbf{h}_i^{real} + \int_{t_i}^{t_{i+1}} f(\mathbf{h}(t); \theta_f) \frac{dX(t)}{dt} dt,
\tag{2}
$$

where $\mathbf{h}_0^{real} = \texttt{FC}_{\dim(\mathbf{x}) \to \dim(\mathbf{h})}(\mathbf{x}_0^{real})$ and $\texttt{FC}_{input\_size \to output\_size}$ is a fully-connected layer with specific input and output sizes. We refer to Appendix B for the ODE function f definition.

Therefore, the input time series $\{(t_i, \mathbf{x}_i^{real})\}_{i=0}^N$ is represented by a set of hidden vectors $\{(t_i, \mathbf{h}_i^{real})\}_{i=0}^N$. Because NCDEs are a continuous analogue to RNNs, it shows the best fit to processing irregular time series [Kidger et al., 2020].

Decoder Our decoder, which reproduces a time series from its hidden representations, is based on GRU-ODEs [Brouwer et al., 2019] and is defined as follows:

$$
\bar{\mathbf{d}}(t_{i+1}) = \mathbf{d}(t_i) + \int_{t_i}^{t_{i+1}} g(\mathbf{d}(t), t; \theta_g) dt,
\tag{3}
$$

$$
\mathbf{d}(t_{i+1}) = \texttt{GRU}(\mathbf{h}_{i+1}, \bar{\mathbf{d}}(t_{i+1})),
\tag{4}
$$

$$
(t_{i+1}, \hat{\mathbf{x}}_{i+1}) = (t_{i+1}, \texttt{FC}_{\dim(\mathbf{d}) \to \dim(\mathbf{x})}(\mathbf{d}(t_{i+1}))),
\tag{5}
$$

where $\mathbf{d}(t_0) = \texttt{FC}_{\dim(\mathbf{h}) \to \dim(\mathbf{d})}(\mathbf{h}_0)$ and $\mathbf{h}_i$ means either the i-th real or fake hidden vector, i.e., $\mathbf{h}_i^{real}$ or $\mathbf{h}_i^{fake}$ — recall that in Fig. 3, the decoder is involved in both the autoencoder and the synthesis processes. $\hat{\mathbf{x}}$ means a reproduced copy of $\mathbf{x}$. GRU-ODEs uses the technology called neural ordinary differential equations (NODEs) to *continuously* interpret GRUs and we refer to Appendix B for the ODE function g definition.

In particular, the gated recurrent unit (GRU) at Eq. (4) is called as *jump* which is known to be effective in processing time series with NODEs [Brouwer et al., 2019, Jia and Benson, 2019]. We train the encoder-decoder using the standard reconstruction loss between $\mathbf{x}_i^{real}$ and $\hat{\mathbf{x}}_i^{real}$ for all i in all training time series samples.

3.3 Generative adversarial network

Figure 4: An example of our generation

Generator Whereas generators typically read a noisy vector to generate a fake sample in standard GANs, our generator reads a continuous path (or time series) sampled from a Wiener process to generate a fake time series sample — this generation concept is known as continuous time flow processes (CTFPs [Deng et al., 2020]). Fig. 4 shows an example of our generation process. The input to our generation process is a random path sampled from a Wiener process, which is represented by a time series of latent vectors $\{(t_i, \mathbf{z}_i)\}_{i=0}^N$ in the path, and the output is a path of hidden vectors which is also represented by a time series of hidden vectors $\{(t_i, \mathbf{h}_i^{fake})\}_{i=0}^N$. Therefore, our generator can be written as follows:

$$
\mathbf{h}_i^{fake} = \mathbf{w}_i(1) = \mathbf{w}_i(0) + \int_0^1 r(\mathbf{w}_i(\tau), a_i(t), t; \theta_r) d\tau,
\tag{6}
$$

where $\mathbf{w}_i(0) = \mathbf{z}_i$, $a_i(0) = t_i$. Here, τ means a virtual time variable of the integral problem, and t_i is a real physical time contained in a time series sample $\{(t_i, \mathbf{x}_i^{real})\}_{i=0}^{M}$. We note that this design corresponds to a NODE model augmented with $a_i(t)$. We refer to Appendix B for the ODE function r definition.

Owing to the invertible nature of NODEs, we can calculate the exact log-density of $\mathbf{h}_i^{real}$, i.e., the probability that $\mathbf{h}_i^{real}$ is generated by the generator, using the change of variable theorem and the Hutchinson's stochastic trace estimator as follows [Grathwohl et al., 2019, Deng et al., 2020]:

$$\hat{\mathbf{w}}(0) = \mathbf{h}_i^{real} + \int_1^0 r(\mathbf{w}(\tau), a_i(\tau), t; \theta_r)d\tau, \tag{7}$$

$$\log \Pr(\hat{\mathbf{h}}_i^{real}) = \log \Pr(\hat{\mathbf{w}}(0))$$
$$+ \int_0^1 tr\Big(\frac{\partial r(\mathbf{w}(\tau), a_i(\tau), t; \theta_r)}{\partial \mathbf{w}(\tau)}\Big)d\tau, \tag{8}$$

where $\hat{\mathbf{w}}(0)$ means $\hat{\mathbf{z}}_i^{real}$ in Fig. 3. $\hat{\mathbf{h}}_i^{real}$ means a reproduced copy of $\mathbf{h}_i^{real}$ by our generator. Eq. (7) corresponds to "CTFP^{-1}", and Eqs. (6) and (8) to "CTFP" in Fig. 3. We note that in Eq. (7), the integral time is reversed to solve the reverse-mode integral problem.

Therefore, we minimize the negative log-density, denoted $-\log \Pr(\hat{\mathbf{h}}_i^{real})$, for each t_i, and our generator is trained by the two different training paradigms: i) the adversarial training against the discriminator, and ii) the maximum likelihood estimator (MLE) training with the log-density.

Discriminator We design our discriminator based on the GRU-ODE technology as follows:

$$\bar{\mathbf{c}}(t_{i+1}) = \mathbf{c}(t_i) + \int_{t_i}^{t_{i+1}} q(\mathbf{c}(t), t; \theta_q)dt, \tag{9}$$

$$\mathbf{c}(t_{i+1}) = \texttt{GRU}(\mathbf{x}_{i+1}, \bar{\mathbf{c}}(t_{i+1})), \tag{10}$$

where $\mathbf{c}(t_0) = \texttt{FC}_{\dim(\mathbf{x}) \to \dim(\mathbf{c})}(\mathbf{x}_0)$, and $\mathbf{x}_i$ means the i-th time series value, i.e., $\mathbf{x}_i^{real}$ or $\mathbf{x}_i^{fake}$. The ODE function q has the same architecture as g but with its own parameters θ_q. After that, we calculate the real or fake classification $\mathbf{y} = \sigma(\texttt{FC}_{\dim(\mathbf{c}) \to 2}(\mathbf{c}(t_N)))$, where σ is a softmax activation.

3.4 Training method

We use the mean squared reconstruction loss, i.e., the mean of $\|\mathbf{x}_i^{real} - \hat{\mathbf{x}}_i^{real}\|_2^2$ for all i, to train the encoder-decoder architecture. Then, we use the standard GAN loss to train the generator and the discriminator. In our preliminary experiments, we found that the original GAN loss is suitable for our task. Instead of other variations, such as WGAN-GP [Gulrajani et al., 2017], therefore, we use the standard GAN loss. We train our model in the following sequence:

1. We pre-train the encoder-decoder networks the reconstruction loss for K_{AE} iterations.

2. After the above pre-training step, we start to jointly train all networks in the following sequence for K_{JOINT} iterations: i) training the encoder-decoder networks with the reconstruction loss, ii) training the discriminator-generator networks with the GAN loss, iii) training the decoder to improve the discriminator's classification output with the discriminator loss and iv) the generator with the MLE loss every P_{MLE} iteration. We found that too frequent MLE training incurs mode-collapse so we use it every P_{MLE} iteration.

In particular, the 2-ii step to train the decoder to help the discriminator out is one additional point where the autoencoder and the GAN are integrated into a single framework. In other words, the generator should deceive both the decoder and the discriminator.

The well-posedness[1] of NCDEs and GRU-ODEs was already proved in Lyons et al. [2007, Theorem 1.3] and Brouwer et al. [2019] under the mild condition of the Lipschitz continuity. We show that our NCDE layers are also well-posed problems. Almost all activations, such as ReLU, Leaky ReLU,

---

[1] A well-posed problem means i) its solution uniquely exists, and ii) its solution continuously changes as input data changes.

SoftPlus, Tanh, Sigmoid, ArcTan, and Softsign, have a Lipschitz constant of 1. Other common neural network layers, such as dropout, batch normalization and other pooling methods, have explicit Lipschitz constant values. Therefore, the Lipschitz continuity of ODE/CDE functions can be fulfilled in our case. In other words, it is a well-posed training problem. As a result, our training algorithm solves a well-posed problem so its training process is stable in practice.

4   Experimental evaluations

Our software and hardware environments are as follows: UBUNTU 18.04 LTS, PYTHON 3.8.10, PYTORCH 1.8.1, TENSORFLOW 2.5.0, CUDA 11.2, and NVIDIA Driver 417.22, i9 CPU, and NVIDIA RTX 3090. The mean and variance of 10 runs are reported for model evaluation.

4.1   Experimental environments

Datasets   We conduct experiments with 2 simulated and 2 real-world datasets. Sines has 5 features where each feature is created with different frequencies and phases independently. For each feature, $i \in \{1, ..., 5\}$, $x_i(t) = sin(2\pi f_i t + \theta_i)$, where $f_i \sim \mathcal{U}[0, 1]$ and $\theta_i \sim \mathcal{U}[-\pi, \pi]$. MuJoCo is multivariate physics simulation time series data with 14 features. Stocks is the Google stock price data from 2004 to 2019. Each observation represents one day and has 6 features. Energy is a UCI appliance energy prediction dataset with 28 values. To create the challenging irregular environments, 30, 50, 70% of observations from each time series sample $\{(t_i, \mathbf{x}_i^{real})\}_{i=0}^N$ is randomly dropped — in other words, N decreases to $0.7N, 0.5N, 0.3N$. Dropping random values has been mainly used to create irregular time series environments in the literature [Kidger et al., 2019, Xu and Xie, 2020, Huang et al., 2020b, Tang et al., 2020, Zhang et al., 2021, Jhin et al., 2021, Deng et al., 2021]. Therefore, we conduct experiments with both the regular and the irregular environments.

Baselines   We consider the following baselines for the regular time series experiments: TimeGAN, RCGAN, C-RNN-GAN, WaveGAN, WaveNet, T-Forcing, and P-Forcing. For the irregular experiments, we exclude WaveGAN and WaveNet, which cannot handle irregular time series, and redesign other baselines by replacing their GRU with GRU-$\triangle t$ and GRU-Decay (GRU-D) [Che et al., 2018]. GRU-$\triangle t$ and GRU-D are effective models for processing irregular time series data. GRU-$\triangle t$ additionally uses the time difference between observations as input. GRU-D is a modification of GRU-$\triangle t$ to learnt exponential decays between observations. TimeGAN-$\triangle t$, RCGAN-$\triangle t$, C-RNN-GAN-$\triangle t$, T-Forcing-$\triangle t$, and P-Forcing-$\triangle t$ (resp. TimeGAN-D, RCGAN-D, C-RNN-GAN-D, T-Forcing-D, and P-Forcing-Decay) are modified with GRU-$\triangle t$ (resp. GRU-D) and can handle irregular data.

Our ablation studies also involve many advanced methods, based on NODEs, VAEs, flow models, and so forth. We intentionally leave these advanced methods for our ablation studies since our proposed method internally has them as sub-parts.

Evaluation metrics   For quantitative evaluation of synthesized data, it is evaluated with the discriminative score and the predictive score used in TimeGAN [Yoon et al., 2019]. The discriminative score measures the similarity between the original data and the synthesized data. After learning a model that classifies the original data and the synthesized data using a neural network, it is tested whether the original data and the synthesized data are classified well. The discriminative score is |Accuracy-0.5|, and if the score is low, classification is difficult, so the original data and the synthesized data are decided to be similar. The predictive score measures the effectiveness of the synthesized data using the train-synthesis-and-test-real (TSTR) method. After training a model that predicts the next step using the synthesized data, the mean absolute error (MAE) is calculated between the predicted values and the ground-truth values in test data. If the MAE is small, the model trained using the synthesized data is decoded to be similar to the original data. For qualitative evaluation, the synthetic data is visualized with the original data. There are two methods for visualization. One is to project original and synthetic data in a two dimensional space using t-SNE [Van der Maaten and Hinton, 2008]. The other one is the kernel density estimation to draw data distributions.

4.2   Experimental results

Regular time series synthesis   In Table 1, we list the results of the regular time series synthesis. GT-GAN shows better performance on most cases than TimeGAN, the previous state-of-the-art

Table 1: Regular time series

	Method	Sines	Stocks	Energy	MuJoCo
Discriminative Score	GT-GAN	.012±.014	**.077±.031**	**.221±.068**	**.245±.029**
	TimeGAN	**.011±.008**	.102±.021	.236±.012	.409±.028
	RCGAN	.022±.008	.196±.027	.336±.017	.436±.012
	C-RNN-GAN	.229±.040	.399±.028	.499±.001	.412±.095
	T-Forcing	.495±.001	.226±.035	.483±.004	.499±.000
	P-Forcing	.430±.227	.257±.026	.412±.006	.500±.000
	WaveNet	.158±.011	.232±.028	.397±.010	.385±.025
	WaveGAN	.277±.013	.217±.022	.363±.012	.357±.017
Predictive Score	GT-GAN	.097±.000	.040±.000	.312±.002	**.055±.000**
	TimeGAN	**.093±.019**	.038±.001	**.273±.004**	.082±.006
	RCGAN	.097±.001	.040±.001	.292±.005	.081±.003
	C-RNN-GAN	.127±.004	**.038±.000**	.483±.005	.055±.004
	T-Forcing	.150±.022	.038±.001	.315±.005	.142±.014
	P-Forcing	.116±.004	.043±.001	.303±.006	.102±.013
	WaveNet	.117±.008	.042±.001	.311±.005	.333±.004
	WaveGAN	.134±.013	.041±.001	.307±.007	.324±.006
	Original	.094±.001	.036±.001	.250±.003	.031±.003

	Method	Sines	Stocks	Energy	MuJoCo
Discriminative Score	GT-GAN	**.363±.063**	**.251±.097**	**.333±.063**	**.249±.035**
	TimeGAN-△t	.494±.012	.463±.020	.448±.027	.471±.016
	RCGAN-△t	.499±.000	.436±.064	.500±.000	.500±.000
	C-RNN-GAN -△t	.500±.000	.500±.001	.500±.000	.500±.000
	T-Forcing-△t	.395±.063	.305±.002	.477±.011	.348±.041
	P-Forcing-△t	.344±.127	.341±.035	.500±.000	.493±.010
	TimeGAN-D	.496±.008	.411±.040	.479±.010	.463±.025
	RCGAN-D	.500±.000	.500±.000	.500±.000	.500±.000
	C-RNN-GAN-D	.500±.000	.500±.000	.500±.000	.500±.000
	T-Forcing-D	.408±.087	.409±.051	.347±.046	.494±.004
	P-Forcing-D	.500±.000	.480±.060	.491±.020	.500±.000
Predictive Score	GT-GAN	**.099±.004**	**.021±.003**	**.066±.001**	**.048±.001**
	TimeGAN-△t	.145±.025	.087±.001	.375±.011	.118±.032
	RCGAN-△t	.144±.028	.181±.014	.351±.056	.433±.021
	C-RNN-GAN-△t	.754±.000	.091±.007	.500±.000	.447±.000
	T-Forcing-△t	.116±.002	.070±.013	.251±.000	.056±.001
	P-Forcing-△t	.102±.002	.083±.018	.255±.001	.089±.011
	TimeGAN-D	.192±.082	.105±.053	.248±.024	.098±.006
	RCGAN-D	.388±.113	.523±.020	.409±.020	.361±.073
	C-RNN-GAN-D	.664±.001	.345±.002	.440±.000	.457±.001
	T-Forcing-D	.100±.002	.027±.002	.090±.001	.100±.001
	P-Forcing-D	.154±.004	.079±.008	.147±.001	.173±.002
	Original	.071±.004	.011±.002	.045±.001	.041±.002

(a) Stocks   (b) Energy

Figure 5: Visualizations and distributions of the regular time series synthesized by GT-GAN and TimeGAN

model. As shown in the 1ˢᵗ row in Fig. 5, GT-GAN covers original data areas better than TimeGAN. In addition, the 2ⁿᵈ row in Fig. 5 is the distributions of the fake data generated by GT-GAN and TimeGAN. The synthesized data's distributions from GT-GAN are more similar to those of the original data than TimeGAN, which shows the efficacy of the *explicit* likelihood training of GT-GAN against the *implicit* likelihood training of TimeGAN.

Irregular time series synthesis In Tables 2, 3, and 4, we list the results of the irregular time series synthesis. GT-GAN shows better discriminative and predictive scores than other baselines in all cases. In Table 2, where we drop random 30% of observations from each time series sample, GT-GAN shows the best outcomes, outperforming TimeGAN by large margins. Baselines modified with GRU-△t and those with GRU-Decay show comparable results and it is hard to say one is better than the other in this table.

In Table 3 (50% dropped), many baselines do not show reasonable synthesis quality, e.g., TimeGAN-D, TimeGAN-△t, RCGAN-D, C-RNN-GAN-D, and C-RNN-GAN-△t have a discriminative score of 0.5. Surprisingly, T-Forcing-D, T-Forcing-△t, P-Forcing-D, and P-Forcing-△t work well in this case. However, our model clearly shows the best performance in all datasets. Baselines modified with GRU-△t show slightly better than them modified with GRU-Decay in this case.

Table 3: Irregular time series (50% dropped)

	Method	Sines	Stocks	Energy	MuJoCo
Discriminative Score	GT-GAN	**.372±.128**	**.265±.073**	**.317±.010**	**.270±.016**
	TimeGAN-$\triangle t$	.496±.008	.487±.019	.479±.020	.483±.023
	RCGAN-$\triangle t$	.406±.165	.478±.049	.500±.000	.500±.000
	C-RNN-GAN-$\triangle t$	.500±.000	.500±.000	.500±.000	.500±.000
	T-Forcing -$\triangle t$	.408±.137	.308±.010	.478±.011	.486±.005
	P-Forcing-$\triangle t$	.428±.044	.388±.026	.498±.005	.491±.012
	TimeGAN-D	.500±.000	.477±.021	.473±.015	.500±.000
	RCGAN-D	.500±.000	.500±.000	.500±.000	.500±.000
	C-RNN-GAN-D	.500±.000	.500±.000	.500±.000	.500±.000
	T-Forcing-D	.430±.101	.407±.034	.376±.046	.498±.001
	P-Forcing-D	.499±.000	.500±.000	.500±.000	.500±.000
Predictive Score	GT-GAN	**.101±.010**	**.018±.002**	**.064±.001**	**.056±.003**
	TimeGAN-$\triangle t$	.123±.040	.058±.003	.501±.008	.402±.021
	RCGAN-$\triangle t$	.142±.005	.094±.013	.391±.014	.277±.061
	C-RNN-GAN-$\triangle t$	.741±.026	.089±.001	.500±.000	.448±.001
	T-Forcing-$\triangle t$	.379±.029	.075±.032	.251±.000	.069±.002
	P-Forcing-$\triangle t$	.120±.005	.067±.014	.263±.003	.189±.026
	TimeGAN-D	.169±.074	.254±.047	.339±.029	.375±.011
	RCGAN-D	.519±.046	.333±.044	.250±.010	.314±.023
	C-RNN-GAN-D	.754±.000	.273±.000	.438±.000	.479±.000
	T-Forcing-D	.104±.001	.038±.003	.090±.000	.113±.001
	P-Forcing-D	.190±.002	.089±.010	.198±.005	.207±.008
	Original	.071±.004	.011±.002	.045±.001	.041±.002

Table 4: Irregular time series (70% dropped)

	Method	Sines	Stocks	Energy	MuJoCo
Discriminative Score	GT-GAN	**.278±.022**	**.230±.053**	**.325±.047**	**.275±.023**
	TimeGAN-$\triangle t$	.500±.000	.488±.009	.496±.008	.494±.009
	RCGAN-$\triangle t$	.433±.142	.381±.086	.500±.000	.500±.000
	C-RNN-GAN-$\triangle t$	.500±.000	.500±.000	.500±.000	.500±.000
	T-Forcing-$\triangle t$	.374±.087	.365±.027	.468±.008	.428±.022
	P-Forcing-$\triangle t$	.288±.047	.317±.019	.500±.000	.498±.003
	TimeGAN-D	.498±.006	.485±.022	.500±.000	.492±.009
	RCGAN-D	.500±.000	.500±.000	.500±.000	.500±.000
	C-RNN-GAN-D	.500±.000	.500±.000	.500±.000	.500±.000
	T-Forcing-D	.436±.067	.404±.068	.336±.032	.493±.005
	P-Forcing-D	.500±.000	.449±.150	.494±.011	.499±.000
Predictive Score	GT-GAN	**.088±.005**	**.020±.005**	**.076±.001**	**.051±.001**
	TimeGAN-$\triangle t$	.734±.000	.072±.000	.496±.000	.442±.000
	RCGAN-$\triangle t$	.218±.072	.155±.009	.498±.000	.222±.041
	C-RNN-GAN-$\triangle t$	.751±.014	.084±.002	.500±.000	.448±.001
	T-Forcing-$\triangle t$	.113±.001	.070±.022	.251±.000	.053±.002
	P-Forcing-$\triangle t$	.123±.004	.050±.002	.285±.006	.117±.034
	TimeGAN-D	.752±.001	.228±.000	.443±.000	.372±.089
	RCGAN-D	.404±.034	.441±.045	.349±.027	.420±.056
	C-RNN-GAN-D	.632±.001	.281±.019	.436±.000	.479±.001
	T-Forcing-D	.102±.001	.031±.002	.091±.000	.114±.003
	P-Forcing-D	.278±.045	.107±.009	.193±.006	.191±.005
	Original	.071±.004	.011±.002	.045±.001	.041±.002

(a) Stocks

(b) Energy

Figure 6: Visualizations and distributions of the irregular time series (70% dropped) by GT-GAN, T-Forcing-$\triangle$t and T-Forcing-D

Finally, Table 4 (70% dropped) shows the results of the most challenging experiments in our paper. All baselines do not work well because of the high dropping rate. T-Forcing-D, T-Forcing-$\triangle t$, P-Forcing-D, and P-Forcing-$\triangle t$, which showed reasonable performance with a dropping rate no larger than 50%, do not work well in this case. This shows that they are vulnerable to highly irregular time series data. Other GAN-based baselines are vulnerable as well. Our method greatly outperforms all existing methods, e.g., a discriminative score of 0.278 by GT-GAN vs. 0.436 by T-Forcing-D vs. 0.288 by P-Forcing-$\triangle t$ for Sines, and a predictive score of 0.051 by GT-GAN vs. 0.114 by T-Forcing-D vs. 0.053 by T-Forcing-$\triangle t$ for MuJoCo. Fig 6 visually compare our method and the best performing baseline for the dropping rate of 70% — figures for other dropping rates and data are in Appendix I and similar patterns are observed in them.

Ablation & sensitivity analyses GT-GAN is characterized by the MLE training with the negative log-density in Eq. (8), and the pre-training step of the encoder and decoder. Table 5 shows the results of various GT-GAN modifications with some training mechanism removed. The model using the negative log-

Table 5: Ablation study for training options. Refer to Appendix E for other ablation studies with irregular time series.

	Method (Regular)	Sines	Stocks	Energy	MuJoCo
Disc.	GT-GAN	**.012**	**.077**	**.221**	**.245**
	w/o Eq. (8)	.023	.159	.356	.278
	w/o pre-training	.046	.175	.312	.290
Pred.	GT-GAN	.097	.040	.312	.055
	w/o Eq. (8)	.097	.043	.315	.057
	w/o pre-training	**.096**	**.038**	**.299**	**.052**

Table 6: Ablation study for model architecture in MuJoCo.

Energy	GT-GAN (w.o. AE)		GT-GAN (Flow only)		GT-GAN (AE only)		GT-GAN (Full model)	
Metric	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.
30% dropped	.500	.054	.467	.156	.495	.162	**.249**	**.048**
50% dropped	.500	.064	.457	.111	.495	.162	**.270**	**.056**
70% dropped	.500	.066	.455	.107	.496	.146	**.275**	**.051**

density training shows better performance than the model not using it. That is, the MLE training makes the synthetic data more like the real data. When the pre-trained autoencoder is not used, the predictive score is better than GT-GAN. However, the discriminative score is the worst.

In Table 6, we alter the architecture for our model. We modify our proposed GT-GAN model by removing its sub-parts to create simpler ablation models: i) In the first ablation model, we remove the autoencoder and perform the adversarial training only with our generator and discriminator, denoted "GT-GAN (w.o. AE)". In other words, our generation directly outputs raw observations (instead of hidden vectors), which will be fed into

Figure 7: Visualization and distribution of MuJoCo (70% dropped) by GT-GAN and Flow only

our GRU-ODE-based discriminator. ii) The second ablation model, denoted "GT-GAN (Flow only)", has only our CTFP-based generator and we train it with the maximum likelihood training — we note that this construction is the same as training flow-based models. This model is equivalent to the original CTFP model [Deng et al., 2020]. iii) The third ablation model has only the autoencoder, denoted "GT-GAN (AE only)". However, we convert it to a variational autoencoder (VAE) model. In the full GT-GAN model, the encoder produces a set of hidden vectors $\{(t_i, \mathbf{h}_i^{real})\}_{i=0}^N$. In this ablation model, however, this is changed to $\{(t_i, \mathcal{N}(\mathbf{h}_i^{real}, \mathbf{1}))\}_{i=0}^N$, where $\mathcal{N}(\mathbf{h}_i^{real}, \mathbf{1})$ means the unit Gaussian centered at $\mathbf{h}_i^{real}$. The decoder is the same as its full model. We use the variational training for this model. Among the ablation models, GT-GAN (Flow only) outperforms the discriminator score in most cases. However, our full model is clearly the best in all cases. Our study shows that the ablation models of GT-GAN do not perform as well as its full model if any parts are missing, as shown in Fig 7. Refer to Appendix E for the ablation studies with other datasets.

The hyperparameters that significantly affect model performance are the absolute tolerance (atol), the relative tolerance (rtol), and the period of the MLE training (P_{MLE}) for the generator. The atol and rtol determine the error control performed by the ODE solvers in CTFPs. We test with various options of the hyperparameters in Appendix F. We found that there is an appropriate error tolerance (atol, rtol) depending on the data input size. For example, the datasets with small input sizes (i.e., Sines, Stocks) have good discriminator scores with (1e-2, 1e-3), and the datasets with large input sizes (i.e., Energy, MuJoCo) show good results with (1e-3, 1e-2).

5 Conclusions and discussions

Time series synthesis is an important research topic in deep learning and had been separately studied for regular or irregular time series synthesis. However, there are still no existing generative models that can handle both regular and irregular time series without model changes. Our proposed method, GT-GAN, is based on various advanced deep learning technologies, ranging from GANs to NODEs, NCDEs, and so forth, and is able to process all possible types of time series without any changes in its model architecture and parameters. Our experiments, which incorporate various synthetic and real-world datasets, prove the efficacy of the proposed method. In our ablation studies, only our full method without any missing parts shows reasonable synthesis capabilities.

Limitations Our model shows the best performance in both regular and irregular time series synthesis. However, since our model has a complicated architecture, many hyperparameters exist. Sometimes it is hard to train such large models, which involves a large scale hyperparameter search.

Societal impacts Time series data is one of the most widely used data in the field of machine learning. In many cases, time series data carries sensitive personal information, in which case one can use our method to synthesize fake time series and protect privacy. Likewise, we believe that our method has much more positive impacts on our society than negative ones.

References

Ahmed Alaa, Alex James Chan, and Mihaela van der Schaar. Generative time-series modeling with fourier flows. In *ICLR*, 2021.

Lei Bai, Lina Yao, Salil S. Kanhere, Xianzhi Wang, and Quan Z. Sheng. Stg2seq: Spatial-temporal graph to sequence model for multi-step passenger demand forecasting. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 1981–1987, 7 2019. doi: 10.24963/ijcai.2019/274.

Edward De Brouwer, Jaak Simm, Adam Arany, and Yves Moreau. Gru-ode-bayes: Continuous modeling of sporadically-observed time series. In *NeurIPS*, 2019.

Zhengping Che, Sanjay Purushotham, Kyunghyun Cho, David Sontag, and Yan Liu. Recurrent neural networks for multivariate time series with missing values. *Scientific reports*, 8(1):1–12, 2018.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

Ruizhi Deng, Bo Chang, Marcus A. Brubaker, Greg Mori, and Andreas M. Lehrmann. Modeling continuous stochastic processes with dynamic normalizing flows. In *NeurIPS*, 2020.

Ruizhi Deng, Marcus A. Brubaker, Greg Mori, and Andreas M. Lehrmann. Continuous latent process flows. In *NeurIPS*, 2021.

Chris Donahue, Julian McAuley, and Miller Puckette. Adversarial audio synthesis, 2019.

Cristóbal Esteban, L. Stephanie Hyland, and Gunnar Rätsch. Real-valued (medical) time series generation with recurrent conditional gans, 2017.

Tak-chung Fu. A review on time series data mining. *Engineering Applications of Artificial Intelligence*, 24(1):164–181, 2011.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NeurIPS*, 2014.

Will Grathwohl, Ricky T. Q. Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. In *ICLR*, 2019.

Alex Graves. Generating sequences with recurrent neural networks, 2014.

Aditya Grover, Manik Dhar, and Stefano Ermon. Flow-gan: Combining maximum likelihood and adversarial learning in generative models. In *AAAI*, 2018.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron Courville. Improved training of wasserstein gans. *arXiv preprint arXiv:1704.00028*, 2017.

Shengnan Guo, Youfang Lin, Ning Feng, Chao Song, and Huaiyu Wan. Attention based spatial-temporal graph convolutional networks for traffic flow forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):922–929, Jul. 2019. doi: 10.1609/aaai.v33i01.3301922.

Rongzhou Huang, Chuyin Huang, Yubao Liu, Genan Dai, and Weiyang Kong. Lsgcn: Long short-term traffic prediction with graph convolutional networks. In *IJCAI*, pages 2355–2361, 2020a.

Zijie Huang, Yizhou Sun, and Wei Wang. Learning continuous system dynamics from irregularly-sampled partial observations. In *NeurIPS*, 2020b.

Sheo Yon Jhin, Heejoo Shin, Seoyoung Hong, Minju Jo, Solhee Park, Noseong Park, Seungbeom Lee, Hwiyoung Maeng, and Seungmin Jeon. Attentive neural controlled differential equations for time-series classification and forecasting. In *ICDM*, 2021.

Junteng Jia and Austin R Benson. Neural jump stochastic differential equations. In *NeurIPS*, 2019.

Patrick Kidger, Patric Bonnier, Imanol Perez Arribas, Cristopher Salvi, and Terry J. Lyons. Deep signature transforms. In *NeurIPS*, 2019.

Patrick Kidger, James Morrill, James Foster, and Terry J. Lyons. Neural controlled differential equations for irregular time series. In *NeurIPS*, 2020.

Alex Lamb, Anirudh Goyal, Ying Zhang, Saizheng Zhang, Aaron Courville, and Yoshua Bengio. Professor forcing: A new algorithm for training recurrent networks, 2016.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. In *International Conference on Learning Representations (ICLR '18)*, 2018.

Terry J Lyons, Michael Caruana, and Thierry Lévy. *Differential equations driven by rough paths*. Springer, 2007.

Olof Mogren. C-rnn-gan: Continuous recurrent neural networks with adversarial training, 2016.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks, 2016.

Gregory C Reinsel. *Elements of multivariate time series analysis*. Springer Science & Business Media, 2003.

Xiaoli Ren, Xiaoyong Li, Kaijun Ren, Junqiang Song, Zichen Xu, Kefeng Deng, and Xiang Wang. Deep learning-based weather prediction: A survey. *Big Data Research*, 23, 2021.

Chao Song, Youfang Lin, Shengnan Guo, and Huaiyu Wan. Spatial-temporal synchronous graph convolutional networks: A new framework for spatial-temporal network data forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(01):914–921, Apr. 2020. doi: 10.1609/aaai.v34i01.5438.

Xianfeng Tang, Huaxiu Yao, Yiwei Sun, Charu Aggarwal, Prasenjit Mitra, and Suhang Wang. Joint modeling of local and global temporal dynamics for multivariate time series forecasting with missing values. In *AAAI*, 2020.

Selim Furkan Tekin, Oguzhan Karaahmetoglu, Fatih Ilhan, Ismail Balaban, and Suleyman Serdar Kozat. Spatio-temporal weather forecasting and attention mechanism on convolutional lstms. *arXiv preprint*, 2021.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio, 2016.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, and Chengqi Zhang. Graph wavenet for deep spatial-temporal graph modeling. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 1907–1913, 7 2019.

Chen Xu and Yao Xie. Conformal prediction for dynamic time-series. In *ICML*, 2020.

Jinsung Yoon, Daniel Jarrett, and Mihaela van der Schaar. Time-series generative adversarial networks. In *NeurIPS*, 2019.

Bing Yu, Haoteng Yin, and Zhanxing Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI-18*, pages 3634–3640, 7 2018. doi: 10.24963/ijcai.2018/505.

Xiang Zhang, Marko Zeman, Theodoros Tsiligkaridis, and Marinka Zitnik. Graph-guided network for irregularly sampled multivariate time series. In *ICLR*, 2021.

A Datasets

We use 2 simulated (Sines, MuJoCo) and 2 real-world (Stocks, Energy) datasets. Table. 7 shows the statistics of the datasets. All datasets are available online via the link. We note that in some of our datasets, the time series length N can be varied from one time series sample to another. However, our framework has no problems in dealing with those varying lengths.

Table 7: Dataset Statistics

Dataset	# of Samples	$\dim(\mathbf{x})$	Average of N	Link	License
Sines	10,000	5	24 time-points	-	-
Stocks	3,773	6	24 days	Link	-
Energy	19,711	28	24 hours	Link	CC BY 4.0
MuJoCo	4,620	14	24 time-points	Link	Apache License 2.0

B ODE/CDE functions in GT-GAN

B.1 Encoder

Our encoder based on NCDEs has the following CDE function f.[2]

Table 8: The architecture of the network f in the encoder

Layer	Design	Input Size	Output Size
1	ReLU(Linear)	$N \times \dim(\mathbf{x})$	$N \times 4\dim(\mathbf{x})$
2	ReLU(Linear)	$N \times 4\dim(\mathbf{x})$	$N \times 4\dim(\mathbf{x})$
3	ReLU(Linear)	$N \times 4\dim(\mathbf{x})$	$N \times 4\dim(\mathbf{x})$
4	Tanh(Linear)	$N \times 4\dim(\mathbf{x})$	$N \times \dim(\mathbf{x})$

B.2 Decoder, Discriminator

Our decoder and discriminator based on GRU-ODEs have the following ODE functions.[3] They have the same architecture but their parameters are separated.

Table 9: The architecture of the network g in the decoder

Layer	Design	Input Size	Output Size
	$r_t =$Sigmoid(Linear)	$N \times \dim(\mathbf{h})$	$N \times \dim(\mathbf{h})$
1	$z_t =$Sigmoid(Linear)	$N \times \dim(\mathbf{h})$	$N \times \dim(\mathbf{h})$
	$u_t =$Tanh(Linear)	$N \times \dim(\mathbf{h})$	$N \times \dim(\mathbf{h})$
	$dh = (1 - z_t) * (u_t - h_t)$	$N \times \dim(\mathbf{h})$	$N \times \dim(\mathbf{h})$

Table 10: The architecture of the network q in the discriminator

Layer	Design	Input Size	Output Size
	$r_t =$Sigmoid(Linear)	$N \times \dim(\mathbf{x})$	$N \times \dim(\mathbf{x})$
1	$z_t =$Sigmoid(Linear)	$N \times \dim(\mathbf{x})$	$N \times \dim(\mathbf{x})$
	$u_t =$Tanh(Linear)	$N \times \dim(\mathbf{x})$	$N \times \dim(\mathbf{x})$
	$dh = (1 - z_t) * (u_t - h_t)$	$N \times \dim(\mathbf{x})$	$N \times \dim(\mathbf{x})$

---

[2]CDE: https://github.com/patrick-kidger/NeuralCDE (Apache-2.0 license)

[3]ODE: https://github.com/rtqichen/torchdiffeq (MIT license)

B.3 Generator

Our generator has the following ODE function f in Table 11.

Table 11: The architecture of the network r in the generator

Layer	Design	Input Size	Output Size
1	Softplus(Linear)	$N \times \dim(\mathbf{h}+1)$	$N \times \dim(\mathbf{h})$
2	Softplus(Linear)	$N \times \dim(\mathbf{h}+1)$	$N \times \dim(\mathbf{h})$
3	Softplus(Linear)	$N \times \dim(\mathbf{h}+1)$	$N \times \dim(\mathbf{h})$

C Baselines

For the regular time series baseline models, i.e., TimeGAN, RCGAN, C-RNN-GAN, T-forcing, and P-forcing, we use the 3-layer GRU-based neural network architecture with a hidden size that is 4 times larger than the input size. We use or modify the following accessible source codes to run.

- TimeGAN : https://github.com/jsyoon0823/TimeGAN
- RCGAN : https://github.com/3778/Ward2ICU
- C-RNN-GAN : https://github.com/olofmogren/c-rnn-gan
- T-forcing, P-forcing : https://github.com/mojesty/professor_forcing
- GRU-D : https://github.com/zhiyongc/GRU-D

Because ordinary GRUs can not be applied to irregular time series, we replace the first layer GRU to GRU-$\triangle t$ and GRU-D in all those baselines so that the redesigned baseline models, i.e., TimeGAN-$\triangle t$, RCGAN-$\triangle t$, C-RNN-GAN-$\triangle t$, T-forcing-$\triangle t$, P-forcing-$\triangle t$, TimeGAN-D, RCGAN-D, C-RNN-GAN-D, T-forcing-D and P-forcing-D, can process irregular time series data.

D Evaluation metrics

$t_0 \quad t_1 \quad t_2 \quad t_{N-1} \quad t_N$

(a) How to calculate the predictive score for the regular time series synthesis in TimeGAN

$t_0 \quad t_1 \quad t_2 \quad t_{N-1} \quad t_N$

(b) How to calculate the predictive score for the irregular time series in this paper

Figure 8: Predictive task according to the data type

For fair comparison, we reuse the experimental environments of TimeGAN for the discriminative score. However, we found that TimeGAN's predictive task is rather straightforward as shown in Fig. 8 (a). It predicts only one element in yellow from other four past elements in blue. Since only one element is used for evaluation, we found that the original predictive score of TimeGAN can be biased. Instead, our predictive task predicts the entire vector, as shown in Fig. 8 (b), and therefore, our predictive score is measured under much more challenging environments. We use this more challenging predictive score definition for our irregular time series synthesis. We stick to the TimeGAN's definition for the regular time series experiment for fair comparison but use our challenging predictive score metric for all other experiments.

E Additional ablation studies

In Tables 12 to 17, we report the missing ablation study tables in the main paper.

Table 12: Ablation study for training options with the irregular time series (30% dropped)

Metric	Method	Sines	Stocks	Energy	MuJoCo
Discriminative	GT-GAN	**.363**	**.251**	**.333**	.249
Score	w/o Eq. (8)	.498	.266	.392	.303
(Lower the Better)	w/o pre-training	.499	.305	.345	**.241**
Predictive	GT-GAN	**.099**	.021	.066	**.048**
Score	w/o Eq. (8)	.241	**.015**	.064	.061
(Lower the Better)	w/o pre-training	.273	.022	**.061**	.049

Table 13: Ablation study for training options with the irregular time series (50% dropped)

Metric	Method	Sines	Stocks	Energy	MuJoCo
Discriminative	GT-GAN	**.372**	.265	**.317**	**.270**
Score	w/o Eq. (8)	.500	.323	.381	.274
(Lower the Better)	w/o pre-training	.500	**.209**	.325	**.270**
Predictive	GT-GAN	**.101**	.018	.064	.056
Score	w/o Eq. (8)	.277	.018	**.063**	.051
(Lower the Better)	w/o pre-training	.103	**.017**	.071	**.051**

Table 14: Ablation study for training options with the irregular time series (70% dropped)

Metric	Method	Sines	Stocks	Energy	MuJoCo
Discriminative	GT-GAN	**.278**	**.230**	**.325**	.275
Score	w/o Eq. (8)	.319	.274	.382	.290
(Lower the Better)	w/o pre-training	.408	.311	.345	**.249**
Predictive	GT-GAN	.088	**.020**	.076	.052
Score	w/o Eq. (8)	**.082**	.025	**.066**	.051
(Lower the Better)	w/o pre-training	.104	**.020**	.085	**.049**

Table 15: Ablation study for model architecture in Sines

Sines	GT-GAN (w.o. AE)		GT-GAN (Flow only)		GT-GAN (AE only)		GT-GAN (Full model)	
Metric	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.
30% dropped	.472	.262	.500	.513	.477	.270	**.363**	**.099**
50% dropped	.480	.254	.500	.610	.475	.253	**.372**	**.101**
70% dropped	.481	.248	.499	.614	.477	.266	**.278**	**.088**

Table 16: Ablation study for model architecture in Stocks

Stocks	GT-GAN (w.o. AE)		GT-GAN (Flow only)		GT-GAN (AE only)		GT-GAN (Full model)	
Metric	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.
30% dropped	.500	.088	.492	.140	.486	.088	**.251**	**.021**
50% dropped	.500	.088	.491	.128	.492	.125	**.265**	**.018**
70% dropped	.500	.088	.490	.128	.492	.122	**.230**	**.020**

Table 17: Ablation study for model architecture in Energy

Energy	GT-GAN (w.o. AE)		GT-GAN (Flow only)		GT-GAN (AE only)		GT-GAN (Full model)	
Metric	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.	Disc.	Pred.
30% dropped	.500	.305	.498	.252	.495	.162	**.333**	**.066**
50% dropped	.500	.365	.499	.160	.499	.135	**.317**	**.064**
70% dropped	.499	.376	.499	.184	.499	.131	**.325**	**.076**

F Sensitivity analyses

We provide performance (discriminative score and predictive score) depending on hyperparameters (i.e. atol (absolute tolerance)= $\{1e-1, 1e-2, 1e-3\}$, rtol (relative tolerance)= $\{1e-1, 1e-2, 1e-3\}$ and $P_{MLE} = \{1, 2, 3\}$) for each different datasets.

(a) Sines   (b) Stocks   (c) Energy   (d) MuJoCo

Figure 9: The sensitivity of the discriminative score (the 1^{st} row) and predictive score (the 2^{nd} row) w.r.t. some key hyperparameters for regular data

(a) Sines   (b) Stocks   (c) Energy   (d) MuJoCo

Figure 10: The sensitivity of the discriminative score (the 1^{st} row) and predictive score (the 2^{nd} row) w.r.t. some key hyperparameters for irregular data (dropped 30%)

Figure 11: The sensitivity of the discriminative score (the 1st row) and predictive score (the 2nd row) w.r.t. some key hyperparameters for irregular data (dropped 50%)

Figure 12: The sensitivity of the discriminative score (the 1st row) and predictive score (the 2nd row) w.r.t. some key hyperparameters for irregular data (dropped 70%)

G The best hyperparamter set for GT-GAN

- 'atol' means absolute tolerance for the generator.
- 'rtol' means relative tolerance for the generator.
- 'P_{MLE}'means the period of the negative log-density training for the generator.
- 'K_{AE}' means the autoencoder's pre-training iteration numbers.
- 'd-layer' means the number of discriminator's GRU layers.
- 'r-acti' means the last activation function of the decoder.
- 'reg-recon' means the reconstruction regularization for the generator.
- 'reg-kinetic' means the kinetic-energy regularization for the generator.
- 'reg-jacobian' means the Jacobian-norm2 regularization for the generator.
- 'reg-direct' means the directional-penalty regularization for the generator.

Table 18: The best hyperparameters

method	Data	atol	rtol	P_{MLE}	K_{AE}	d-layer	r-acti	reg-recon	reg-kinetic	reg-jacobian	reg-direct
GT-GAN (Regular)	Sines	1e-2	1e-3	1	5000	1	softplus	0.01	0.05	0.1	0.1
	Stocks	1e-2	1e-3	2	10000	1	softplue	0.01	0.01	0.05	0.01
	Energy	1e-3	1e-2	2	5000	2	sigmoid	0.01	0.5	0.1	0.01
	MuJoCo	1e-3	1e-2	2	5000	2	sigmoid	0.01	0.05	0.01	0.01
GT-GAN (Dropped 30%)	Sines	1e-2	1e-3	2	5000	1	softplus	0.01	0.05	0.01	0.01
	Stocks	1e-2	1e-3	2	10000	1	softplue	0.01	None	None	0.05
	Energy	1e-3	1e-2	2	5000	2	sigmoid	0.01	0.5	0.1	0.01
	MuJoCo	1e-3	1e-2	2	2500	2	sigmoid	0.01	0.5	0.1	0.01
GT-GAN (Dropped 50%)	Sines	1e-2	1e-3	2	5000	2	softplus	0.01	0.05	0.01	0.01
	Stocks	1e-3	1e-3	2	10000	1	softplue	None	0.05	0.01	0.05
	Energy	1e-3	1e-2	2	5000	2	sigmoid	0.01	0.5	0.1	0.01
	MuJoCo	1e-3	1e-2	2	1500	2	sigmoid	0.1	0.1	0.01	0.01
GT-GAN (Dropped 70%)	Sines	1e-2	1e-3	2	5000	1	softplus	0.01	0.05	0.01	0.01
	Stocks	1e-2	1e-3	1	10000	1	softplue	None	0.05	0.01	0.05
	Energy	1e-3	1e-2	2	2500	2	sigmoid	0.01	0.5	0.1	0.01
	MuJoCo	1e-3	1e-2	2	2500	2	sigmoid	0.01	0.5	0.1	0.01

H Model size & training time comparison

In Table 19, we report the model size and training time of our method and TimeGAN, one of the best performing baseline. As shown, our model has much smaller numbers of parameters than TimeGAN. However, it take much longer time to train our model than TimeGAN. This is mainly because we need to solve various differential equations, which is not needed for TimeGAN. The memory requirements are more or less the same in both models. Therefore, these exist pros and cons for our method in comparison with the state-of-the-art baseline.

Table 19: Comparison of model size and training time

	Sines		Stocks		Energy		MuJoCo	
Model	GT-GAN	TimeGAN	GT-GAN	TimeGAN	GT-GAN	TimeGAN	GT-GAN	TimeGAN
Parameter	41,913	34,026	41,776	48,775	57,104	1,043,179	47,346	264,447
Memory (MB)	1,675	1,419	1,653	1,423	1,839	1,611	1,655	1,546
Training Time (HH:MM)	10:12	2:56	12:20	2:59	10:39	3:37	13:12	3:10

I Visualizations with t-SNE and data distribution

We introduce additional visualization outcomes in Figs. 13 to 21.

(a) 30%   (b) 50%   (c) 70%

Figure 13: t-SNE visualization of recovered irregular Sines data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

(a) 30%   (b) 50%   (c) 70%

Figure 14: t-SNE visualization of recovered irregular Stocks data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

(a) 30%   (b) 50%   (c) 70%

Figure 15: t-SNE visualization of recovered irregular Energy data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

(a) 30%   (b) 50%   (c) 70%

Figure 16: t-SNE visualization of recovered irregular MuJoCo data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

Figure 17: Distributions of the Sines data (the 1ˢᵗ column is for a dropping rate of 30%, the 2ⁿᵈ column for a rate of 50%, and the 3ʳᵈ column for a rate of 70%)

Figure 18: Distributions of the Stocks data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

(a) 30%   (b) 50%   (c) 70%

Figure 19: Distributions of the Energy data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

(a) 30%   (b) 50%   (c) 70%

Figure 20: Distributions of the MuJoCo data (the 1st column is for a dropping rate of 30%, the 2nd column for a rate of 50%, and the 3rd column for a rate of 70%)

 ## J   Algorithm

Algorithm 1: How to train `GT-GAN`

Input: Pre-train iteration number K_{AE}, Joint-train iteration number K_{JOINT}, MLE train period P_{MLE}, Encoder $\boldsymbol{\theta}_f$, Decoder $\boldsymbol{\theta}_g$, Generator $\boldsymbol{\theta}_r$, and Discriminator $\boldsymbol{\theta}_q$

1 Initialize $\boldsymbol{\theta}_f$, $\boldsymbol{\theta}_g$, $\boldsymbol{\theta}_r$ and $\boldsymbol{\theta}_q$;
2 $k \leftarrow 0$;
3 **while** $k < K_{AE}$ **do**
4     $\mathbf{h}_{real} \leftarrow \text{Encoder}(\mathbf{x}_{real}; \boldsymbol{\theta}_f)$;
5     $\hat{\mathbf{x}}_{real} \leftarrow \text{Decoder}(\mathbf{h}_{real}; \boldsymbol{\theta}_g)$;
6   Update $\boldsymbol{\theta}_f$ and $\boldsymbol{\theta}_g$ with $\|\mathbf{x}_{real} - \hat{\mathbf{x}}_{real}\|^2$;
7     $k \leftarrow k + 1$;
8 **end**
9 $k \leftarrow 0$;
10 **while** $k < K_{JOINT}$ **do**
11     $\mathbf{h}_{real} \leftarrow \text{Encoder}(\mathbf{x}_{real}; \boldsymbol{\theta}_f)$;
12     $\hat{\mathbf{x}}_{real} \leftarrow \text{Decoder}(\mathbf{h}_{real}; \boldsymbol{\theta}_g)$;
13   Update $\boldsymbol{\theta}_f$ and $\boldsymbol{\theta}_g$ with $\|\mathbf{x}_{real} - \hat{\mathbf{x}}_{real}\|^2$;
14   **if** $k \mod P_{MLE} \equiv 0$ **then**
15        $\hat{\mathbf{z}} \leftarrow \text{Generator}^{-1}(\mathbf{h}_{real}, \boldsymbol{\theta}_r)$;
16        $\hat{\mathbf{h}}_{real} \leftarrow \text{Generator}(\hat{\mathbf{z}}, \boldsymbol{\theta}_r)$;
17   Update $\boldsymbol{\theta}_r$ with $-\log \Pr(\hat{\mathbf{h}}_{real})$;
18   **end**
19     $\mathbf{h}_{fake} \leftarrow \text{Generator}(\mathbf{z}, \boldsymbol{\theta}_r)$;
20     $\mathbf{x}_{fake} \leftarrow \text{Decoder}(\mathbf{h}_{fake}, \boldsymbol{\theta}_g)$;
21   Update $\boldsymbol{\theta}_r$ and $\boldsymbol{\theta}_q$ with the adversarial loss with $\text{Discriminator}(\mathbf{x}_{fake}, \mathbf{x}_{real}, \boldsymbol{\theta}_q)$;
22     $k \leftarrow k + 1$;
23 **end**

We describe the training method in Alg. (1). We first pre-train the autoencoder in the first while loop, followed by the second while loop for the main training step. The main training step consists of i) fine-tuning the autoencoder, ii) training the generation with the log-density loss, iii) training the GAN part with the adversarial loss.

K   Visualization of ablation study

Figure 21: t-SNE visualization of GT-GAN and GT-GAN (w/o pre-training)